

## 5440. XOR Operation in an Array

[My Submissions \(/contest/weekly-contest-194/problems/xor-operation-in-an-array/submissions/\)](/contest/weekly-contest-194/problems/xor-operation-in-an-array/submissions/)

[Back to Contest \(/contest/weekly-contest-194/\)](/contest/weekly-contest-194/)

Given an integer `n` and an integer `start`.

Define an array `nums` where `nums[i] = start + 2*i` (0-indexed) and `n == nums.length`.

Return the bitwise XOR of all elements of `nums`.

User Accepted: 5271

User Tried: 5342

Total Accepted: 5324

Total Submissions: 5663

Difficulty: Easy

### Example 1:

**Input:** `n = 5, start = 0`

**Output:** 8

**Explanation:** Array `nums` is equal to `[0, 2, 4, 6, 8]` where `(0 ^ 2 ^ 4 ^ 6 ^ 8) = 8`. Where "`^`" corresponds to bitwise XOR operator.

### Example 2:

**Input:** `n = 4, start = 3`

**Output:** 8

**Explanation:** Array `nums` is equal to `[3, 5, 7, 9]` where `(3 ^ 5 ^ 7 ^ 9) = 8`.

### Example 3:

**Input:** `n = 1, start = 7`

**Output:** 7

### Example 4:

**Input:** `n = 10, start = 5`

**Output:** 2

### Constraints:

- `1 <= n <= 1000`
- `0 <= start <= 1000`
- `n == nums.length`

JavaScript



```
1 ▾ /**
2   * @param {number} n
3   * @param {number} start
4   * @return {number}
5   */
6 ▾ var xorOperation = function(n, start) {
7
8   };
```

☐ Custom Testcase☒ Use Example Testcases Run Submit

Copyright © 2020 LeetCode

[Help Center \(/support/\)](/support/) | [Terms \(/terms/\)](/terms/) | [Privacy Policy \(/privacy/\)](/privacy/)

 [United States \(/region/\)](/region/)