

7023. Apply Operations to Maximize Score

My Submissions (/contest/weekly-contest-358/problems/apply-operations-to-maximize-score/submissions/)

Back to Contest (/contest/weekly-contest-358/)

You are given an array `nums` of `n` positive integers and an integer `k`.

Initially, you start with a score of `1`. You have to maximize your score by applying the following operation at most `k` times:

- Choose any **non-empty** subarray `nums[l, ..., r]` that you haven't chosen previously.
- Choose an element `x` of `nums[l, ..., r]` with the highest **prime score**. If multiple such elements exist, choose the one with the smallest index.
- Multiply your score by `x`.

Here, `nums[l, ..., r]` denotes the subarray of `nums` starting at index `l` and ending at the index `r`, both ends being inclusive.

The **prime score** of an integer `x` is equal to the number of distinct prime factors of `x`. For example, the prime score of `300` is `3` since `300 = 2 * 2 * 3 * 5 * 5`.

Return the **maximum possible score** after applying at most `k` operations.

Since the answer may be large, return it modulo $10^9 + 7$.

User Accepted:	0
User Tried:	0
Total Accepted:	0
Total Submissions:	0
Difficulty:	Hard

Example 1:

Input: `nums = [8,3,9,3,8]`, `k = 2`

Output: `81`

Explanation: To get a score of `81`, we can apply the following operations:

- Choose subarray `nums[2, ..., 2]`. `nums[2]` is the only element in this subarray. Hence, we multiply the score by `nums[2]`.
- Choose subarray `nums[2, ..., 3]`. Both `nums[2]` and `nums[3]` have a prime score of `1`, but `nums[2]` has the smaller index. Hence, It can be proven that `81` is the highest score one can obtain.

Example 2:

Input: `nums = [19,12,14,6,10,18]`, `k = 3`

Output: `4788`

Explanation: To get a score of `4788`, we can apply the following operations:

- Choose subarray `nums[0, ..., 0]`. `nums[0]` is the only element in this subarray. Hence, we multiply the score by `nums[0]`.
- Choose subarray `nums[5, ..., 5]`. `nums[5]` is the only element in this subarray. Hence, we multiply the score by `nums[5]`.
- Choose subarray `nums[2, ..., 3]`. Both `nums[2]` and `nums[3]` have a prime score of `2`, but `nums[2]` has the smaller index. Hence, It can be proven that `4788` is the highest score one can obtain.

Constraints:

- $1 \leq \text{nums.length} = n \leq 10^5$
- $1 \leq \text{nums}[i] \leq 10^5$
- $1 \leq k \leq \min(n * (n + 1) / 2, 10^9)$

JavaScript

📄

↺

⚙️

```
1 const multi_mod = (x, y, mod) => Number(ll(x) * ll(y) % ll(mod));
2
3 const ll = BigInt;
4 const powmod = (a, b, mod) => { let r = 1; while (b > 0) { if (b & 1) r = multi_mod(r, a, mod); b >>= 1; a =
  multi_mod(a, a, mod); } return r; };
5
6 const mod = 1e9 + 7;
7 const maximumScore = (a, k) => {
8   let max = Math.max(...a), cnt = [], d = [], lpf = LeastPrimeFactors(max + 1);
9   a.map(x => {
10     let f = factorizationLPF(x, lpf);
11     cnt.push(f.length);
12   });
13 }
```

```

13 // 左右扩展区间 单调栈
14 let [L, R] = MonotonicStack_PrevNextWall(cnt), res = 1;
15 a.map((x, i) => d.push([cnt[i], i, (i - L[i]) * (R[i] - i), x])); // 左右端点的扩展长度(i - L[i]) * (R[i] - i), 该元素的
子数组数目
16 d.sort((x, y) => y[3] - x[3]);
17 for (const [, , t, x] of d) {
18   let use = Math.min(t, k);
19   k -= use;
20   let pow = powmod(x, use, mod);
21   res = multi_mod(res, pow, mod);
22 }
23 return res;
24 };
25
26 const LeastPrimeFactors = (n) => {
27   let lpf = Array(n + 1).fill(0);
28   for (let i = 2; i <= n; i++) {
29     if (lpf[i] == 0) {
30       lpf[i] = i;
31       for (let j = i * i; j <= n; j += i) {
32         if (lpf[j] == 0) lpf[j] = i;
33       }
34     }
35   }
36   return lpf;
37 };
38
39 const factorizationLPF = (n, lpf) => {
40   let f = Array(9), i = 0;
41   while (lpf[n] > 0) {
42     let p = lpf[n];
43     if (i == 0 || p != f[i - 1][0]) {
44       f[i++] = [p, 1];
45     } else {
46       f[i - 1][1]++;
47     }
48     n /= p;
49   }
50   return f.slice(0, i);
51 };
52
53 const MonotonicStack_PrevNextWall = (a) => { // left/right farthest index to reach
54   let n = a.length, L = Array(n).fill(-1), R = Array(n).fill(n), st = [];
55   for (let i = 0; i < n; i++) {
56     while (st.length && a[st[st.length - 1]] < a[i]) R[st.pop()] = i;
57     if (st.length) L[i] = st[st.length - 1];
58     st.push(i);
59   }
60   return [L, R];
61 };

```

☐ Custom Testcase[Use Example Testcases](#)[Run](#)[Submit](#)Submission Result: **Accepted** (/submissions/detail/1021301534/) ?[More Details](#) (/submissions/detail/1021301534/)

Share your acceptance!

Copyright © 2023 LeetCode

[Help Center](#) (/support) | [Jobs](#) (/jobs) | [Bug Bounty](#) (/bugbounty) | [Online Interview](#) (/interview/) | [Students](#) (/student) | [Terms](#) (/terms) | [Privacy Policy](#) (/privacy)[United States](#) (/region)