Difficulty:



(Medium)

2785. Sort Vowels in a String

My Submissions (/contest/biweekly-contest-109/problems/sort-vowels-in-a-string/submissions/)

Back to Contest (/contest/biweekly-contest-109/)

Given a 0-indexed string $\,\textbf{s}\,$, $\,\textbf{permute}\,$ s $\,$ to get a new string $\,\textbf{t}\,$ such that:

- All consonants remain in their original places. More formally, if there is an index i with 0 <= i < s.length such
 that s[i] is a consonant, then t[i] = s[i].
- The vowels must be sorted in the nondecreasing order of their ASCII values. More formally, for pairs of indices i, j with 0 <= i < j < s.length such that s[i] and s[j] are vowels, then t[i] must not have a higher ASCII value than t[j].

User Accepted: 14135
User Tried: 14805
Total Accepted: 14478
Total Submissions: 19476

Return the resulting string.

The vowels are 'a', 'e', 'i', 'o', and 'u', and they can appear in lowercase or uppercase. Consonants comprise all letters that are not vowels.

Example 1:

```
Input: s = "lEetcOde"
Output: "lEOtcede"
Explanation: 'E', '0', and 'e' are the vowels in s; 'l', 't', 'c', and 'd' are all consonants. The vowels are sorted according
```

Example 2:

```
Input: s = "lYmpH"
Output: "lYmpH"
Explanation: There are no vowels in s (all characters in s are consonants), so we return "lYmpH".
```

Constraints:

- 1 <= s.length <= 10⁵
- s consists only of letters of the English alphabet in uppercase and lowercase.

Discuss (https://leetcode.com/problems/sort-vowels-in-a-string/discuss)

```
JavaScript
                                                                                                                         ₁ S
    const isVowel = (c) => 'aeiouAEIOU'.indexOf(c) != -1;
2
    const ord = (c) => c.charCodeAt();
3
4
    const sortVowels = (s) => {
        s = s.split("");
5
        let ia = [], ib = [], res = Array(s.length);
6
7
        s.map((c, i) \Rightarrow {
8
             isVowel(c) ? ia.push(c) : ib.push(c);
9
        });
10
        ia.sort((x, y) \Rightarrow ord(x) - ord(y));
11
        let p = 0, q = 0;
12
        s.map((c, i) \Rightarrow res[i] = isVowel(c) ? ia[p++] : ib[q++]);
13
        return res.join("");
14
    };
```

United States (/region)

Custom Testcase

Use Example Testcases

Run

Submission Result: Accepted (/submissions/detail/1001257804/)

More Details ➤ (/submissions/detail/1001257804/)

Share your acceptance!

Copyright © 2023 LeetCode

Help Center (/support) | Jobs (/jobs) | Bug Bounty (/bugbounty) | Online Interview (/interview/) | Students (/student) | Terms (/terms) | Privacy Policy (/privacy)