o oundergrou⊩ system/)

# 6042. Count Lattice Points Inside a Circle

My Submissions (/contest/weekly-contest-290/problems/count-lattice-points-inside-a-circle/submissions/) Back to Contest (/contest/weekly-contest-290/)


Given a 2D integer array circles where circles[i] =  $[x_i, y_i, r_i]$  represents the center  $(x_i, y_i)$  and radius  $r_i$  of the i<sup>th</sup> circle drawn on a grid, return the **number of lattice points** that are present inside **at least one** circle.

### Note:

- A lattice point is a point with integer coordinates.
- Points that lie on the circumference of a circle are also considered to be inside it.

# User Accepted: 0 User Tried: 0 Total Accepted: 0 Total Submissions: 0 Difficulty: Medium

## Example 1:



Input: circles = [[2,2,1]]

Output: 5 Explanation:


The figure above shows the given circle.

The lattice points present inside the circle are (1, 2), (2, 1), (2, 2), (2, 3), and (3, 2) and are shown in green.

Other points such as (1, 1) and (1, 3), which are shown in red, are not considered inside the circle.

Hence, the number of lattice points present inside at least one circle is 5.

## Example 2:



Input: circles = [[2,2,2],[3,4,1]]

Output: 16 Explanation:

The figure above shows the given circles.

There are exactly 16 lattice points which are present inside at least one circle.

Some of them are (0, 2), (2, 0), (2, 4), (3, 2), and (4, 4).

## **Constraints:**

- 1 <= circles.length <= 200
- circles[i].length == 3
- 1 <=  $x_i$ ,  $y_i$  <= 100

• 1 <=  $r_i$  <=  $min(x_i, y_i)$ 

```
JavaScript
                                                                                                                                         C
  1 ▼ const countLatticePoints = (circles) => {
          let res = new Set();
  З ч
          for (const [x, y, r] of circles) {
  4
               // let topRight = [x + r, y + r], bottomRight = [x + r, y - r];
  5
               // let topLeft = [x - r, y + r], bottomLeft = [x - r, y - r];
  6
               // pr(topLeft, bottomLeft, topRight, bottomRight)
  7 ▼
               for (let i = x - r; i \le x + r; i ++) {
                    for (let j = y - r; j <= y + r; j++) {
    if (inCircle(i, j, x, y, r)) res.add(i + ' ' + j);</pre>
  8٠
  9
 10
                    }
 11
 12
 13
          return res.size;
 14
      };
 15
 16 ▼
      const inCircle = (x, y, cx, cy, r) \Rightarrow \{
          let disPow = Math.abs(x - cx) ** 2 + Math.abs(y - cy) ** 2;
 17
 18
          return disPow <= r * r;
 19
      };
☐ Custom Testcase
                      Use Example Testcases
                                                                                                                                Run
                                                                                                                                           △ Submit
Submission Result: Accepted (/submissions/detail/686335655/) ?
                                                                               More Details > (/submissions/detail/686335655/)
Share your acceptance!
              ₫2
Copyright © 2022 LeetCode
Help Center (/support) | Jobs (/jobs) | Bug Bounty (/bugbounty) | Online Interview (/interview/) | Students (/student) | Terms (/terms) | Privacy Policy (/privacy)
United States (/region)
```