5753. Largest Color Value in a Directed Graph

My Submissions (/contest/weekly-contest-240/problems/largest-color-value-in-a-directed-graph/submissions/)

Back to Contest (/contest/weekly-contest-240/)

There is a **directed graph** of `n` colored nodes and `m` edges. The nodes are numbered from `0` to `n - 1`.

You are given a string `colors` where `colors[i]` is a lowercase English letter representing the **color** of the i^{th} node in this graph (**0-indexed**). You are also given a 2D array `edges` where `edges[j] = [a_j, b_j]` indicates that there is a **directed edge** from node a_j to node b_j.

A valid **path** in the graph is a sequence of nodes $x_1 \rightarrow x_2 \rightarrow x_3 \rightarrow \ldots \rightarrow x_k$ such that there is a directed edge from x_i to x_{i+1} for every $1 \le i < k$. The **color value** of the path is the number of nodes that are colored the **most frequently** occurring color along that path.

Return *the **largest color value** of any valid path in the given graph, or* `-1` *if the graph contains a cycle*.

User Accepted:	0
User Tried:	0
Total Accepted:	0
Total Submissions:	0
Difficulty:	Hard

Example 1:




```
Input: colors = "abaca", edges = [[0,1],[0,2],[2,3],[3,4]]
Output: 3
Explanation: The path 0 -> 2 -> 3 -> 4 contains 3 nodes that are colored "a" (red in the above image).
```

Example 2:




```
Input: colors = "a", edges = [[0,0]]
Output: -1
Explanation: There is a cycle from 0 to 0.
```

Constraints:

- `n == colors.length`
- `m == edges.length`
- `1 <= n <= 10^5`
- `0 <= m <= 10^5`
- `colors` consists of lowercase English letters.
- `0 <= a_j, b_j < n`

Java

```
class Solution {
    public int largestPathValue(String colors, int[][] edges) {

    }
}
```