5495. Most Visited Sector in a Circular Track

My Submissions (/contest/weekly-contest-203/problems/most-visited-sector-in-a-circular-track/submissions/)

Back to Contest (/contest/weekly-contest-203/)

Given an integer `n` and an integer array `rounds`. We have a circular track which consists of `n` sectors labeled from `1` to `n`. A marathon will be held on this track, the marathon consists of `m` rounds. The `i^th` round starts at sector `rounds[i - 1]` and ends at sector `rounds[i]`. For example, round 1 starts at sector `rounds[0]` and ends at sector `rounds[1]`

Return *an array of the most visited sectors* sorted in **ascending** order.

Notice that you circulate the track in ascending order of sector numbers in the counter-clockwise direction (See the first example).

User Accepted:	0
User Tried:	0
Total Accepted:	0
Total Submissions:	0
Difficulty:	Easy

Example 1:




```
Input: n = 4, rounds = [1,3,1,2]
Output: [1,2]
Explanation: The marathon starts at sector 1. The order of the visited sectors is as follo
1 --> 2 --> 3 (end of round 1) --> 4 --> 1 (end of round 2) --> 2 (end of round 3 and the
We can see that both sectors 1 and 2 are visited twice and they are the most visited secto
```

Example 2:

```
Input: n = 2, rounds = [2,1,2,1,2,1,2,1,2]
Output: [2]
```

Example 3:

```
Input: n = 7, rounds = [1,3,5,7]
Output: [1,2,3,4,5,6,7]
```

Constraints:

- `2 <= n <= 100`
- `1 <= m <= 100`
- `rounds.length == m + 1`
- `1 <= rounds[i] <= n`
- `rounds[i] != rounds[i + 1]` for `0 <= i < m`

JavaScript

```
/**
 * @param {number} n
 * @param {number[]} rounds
 * @return {number[]}
 */
var mostVisited = function(n, rounds) {

};
```

Custom Testcase Use Example Testcases

Run Submit