

☆ Premium

ref=nb_npl)





0

0

5894. Two Out of Three

My Submissions (/contest/weekly-contest-262/problems/two-out-of-three/submissions/) Back to Contest (/contest/weekly-contest-262/) Given three integer arrays nums1, nums2, and nums3, return a distinct array containing all the values that are User Accepted: present in at least two out of the three arrays. You may return the values in any order. **User Tried:**

Example 1:

```
Total Accepted:
                                                                                                                             0
Input: nums1 = [1,1,3,2], nums2 = [2,3], nums3 = [3]
                                                                                                Total Submissions:
                                                                                                                             0
Output: [3,2]
Explanation: The values that are present in at least two arrays are:
                                                                                                                        (Easy)
                                                                                                Difficulty:
- 3, in all three arrays.
- 2, in nums1 and nums2.
```

Example 2:

```
Input: nums1 = [3,1], nums2 = [2,3], nums3 = [1,2]
Output: [2,3,1]
Explanation: The values that are present in at least two arrays are:
- 2, in nums2 and nums3.
- 3, in nums1 and nums2.
- 1, in nums1 and nums3.
```

Example 3:

```
Input: nums1 = [1,2,2], nums2 = [4,3,3], nums3 = [5]
Explanation: No value is present in at least two arrays.
```

Constraints:

- 1 <= nums1.length, nums2.length, nums3.length <= 100
- 1 <= nums1[i], nums2[j], nums3[k] <= 100

```
JavaScript
                                                                                                                   δ
                                                                                                                         \mathfrak{C}
 1 \cdot | const twoOutOfThree = (a1, a2, a3) => {
 2
         let a = \text{new Set}([...a1, ...a2, ...a3]);
         let s1 = new Set(a1), s2 = new Set(a2), s3 = new Set(a3);
 3
 4
         let res = new Set();
 5 •
         for (const x of a) {
 6
             if (s1.has(x) && s2.has(x)) res.add(x);
 7
             if (s1.has(x) && s3.has(x)) res.add(x);
 8
             if (s2.has(x) && s3.has(x)) res.add(x);
 9
10
         return [...res];
11
    };
```

☐ Custom Testcase (Use Example Testcases

Submission Result: Accepted (/submissions/detail/568604457/) ?

More Details > (/submissions/detail/568604457/)

• Run

△ Submit

Share your acceptance!

Copyright © 2021 LeetCode

Help Center (/support) | Jobs (/jobs) | Bug Bounty (/bugbounty) | Online Interview (/interview/) | Students (/student) | Terms (/terms) | Privacy Policy (/privacy)

United States (/region)