

5783. Design Movie Rental System

[My Submissions \(/contest/biweekly-contest-55/problems/design-movie-rental-system/submissions/\)](#)

[Back to Contest \(/contest/biweekly-contest-55/\)](#)

You have a movie renting company consisting of n shops. You want to implement a renting system that supports searching for, booking, and returning movies. The system should also support generating a report of the currently rented movies.

Each movie is given as a 2D integer array `entries` where `entries[i] = [shopi, moviei, pricei]` indicates that there is a copy of movie `moviei` at shop `shopi` with a rental price of `pricei`. Each shop carries **at most one** copy of a movie `moviei`.

The system should support the following functions:

- Search:** Finds the **cheapest 5 shops** that have an **unrented copy** of a given movie. The shops should be sorted by **price** in ascending order, and in case of a tie, the one with the **smaller** `shopi` should appear first. If there are less than 5 matching shops, then all of them should be returned. If no shop has an unrented copy, then an empty list should be returned.
- Rent:** Rents an **unrented copy** of a given movie from a given shop.
- Drop:** Drops off a **previously rented copy** of a given movie at a given shop.
- Report:** Returns the **cheapest 5 rented movies** (possibly of the same movie ID) as a 2D list `res` where `res[j] = [shopj, moviej]` describes that the j^{th} cheapest rented movie `moviej` was rented from the shop `shopj`. The movies in `res` should be sorted by **price** in ascending order, and in case of a tie, the one with the **smaller** `shopj` should appear first, and if there is still tie, the one with the **smaller** `moviej` should appear first. If there are fewer than 5 rented movies, then all of them should be returned. If no movies are currently being rented, then an empty list should be returned.

Implement the `MovieRentingSystem` class:

- `MovieRentingSystem(int n, int[][] entries)` Initializes the `MovieRentingSystem` object with n shops and the movies in `entries`.
- `List<Integer> search(int movie)` Returns a list of shops that have an **unrented copy** of the given `movie` as described above.
- `void rent(int shop, int movie)` Rents the given `movie` from the given `shop`.
- `void drop(int shop, int movie)` Drops off a previously rented `movie` at the given `shop`.
- `List<List<Integer>> report()` Returns a list of cheapest **rented** movies as described above.

Note: The test cases will be generated such that `rent` will only be called if the shop has an **unrented** copy of the movie, and `drop` will only be called if the shop had **previously rented** out the movie.

Example 1:

Input

```
["MovieRentingSystem", "search", "rent", "rent", "report", "drop", "search"]
[[3, [[0, 1, 5], [0, 2, 6], [0, 3, 7], [1, 1, 4], [1, 2, 7], [2, 1, 5]]], [1], [0, 1], [1, 2], [], [1, 2], [2]]
```

Output

```
[null, [1, 0, 2], null, null, [[0, 1], [1, 2]], null, [0, 1]]
```

Explanation

```
MovieRentingSystem movieRentingSystem = new MovieRentingSystem(3, [[0, 1, 5], [0, 2, 6], [0, 3, 7], [1, 1, 4],
movieRentingSystem.search(1); // return [1, 0, 2], Movies of ID 1 are unrented at shops 1, 0, and 2. Shop 1 is
movieRentingSystem.rent(0, 1); // Rent movie 1 from shop 0. Unrented movies at shop 0 are now [2,3].
movieRentingSystem.rent(1, 2); // Rent movie 2 from shop 1. Unrented movies at shop 1 are now [1].
movieRentingSystem.report();   // return [[0, 1], [1, 2]]. Movie 1 from shop 0 is cheapest, followed by movie 2
movieRentingSystem.drop(1, 2); // Drop off movie 2 at shop 1. Unrented movies at shop 1 are now [1,2].
movieRentingSystem.search(2);  // return [0, 1]. Movies of ID 2 are unrented at shops 0 and 1. Shop 0 is cheape
```

Constraints:

- $1 \leq n \leq 3 \times 10^5$
- $1 \leq \text{entries.length} \leq 10^5$
- $0 \leq \text{shop}_i < n$
- $1 \leq \text{movie}_i, \text{price}_i \leq 10^4$
- Each shop carries **at most one** copy of a movie movie_i .
- At most 10^5 calls **in total** will be made to `search`, `rent`, `drop` and `report`.

JavaScript



```

1  /**
2   * @param {number} n
3   * @param {number[][]} entries
4   */
5  var MovieRentingSystem = function(n, entries) {
6
7  };
8
9  /**
10   * @param {number} movie
11   * @return {number[]}
12   */
13  MovieRentingSystem.prototype.search = function(movie) {
14
15  };
16
17  /**
18   * @param {number} shop
19   * @param {number} movie
20   * @return {void}
21   */
22  MovieRentingSystem.prototype.rent = function(shop, movie) {
23
24  };
25
26  /**
27   * @param {number} shop
28   * @param {number} movie
29   * @return {void}
30   */
31  MovieRentingSystem.prototype.drop = function(shop, movie) {
32
33  };
34
35  /**
36   * @return {number[][]}
37   */
38  MovieRentingSystem.prototype.report = function() {
39
40  };
41
42  /**
43   * Your MovieRentingSystem object will be instantiated and called as such:
44   * var obj = new MovieRentingSystem(n, entries)
45   * var param_1 = obj.search(movie)
46   * obj.rent(shop,movie)
47   * obj.drop(shop,movie)
48   * var param_4 = obj.report()
49   */

```

☐ Custom Testcase☒ Use Example Testcases

Run

Submit

Copyright © 2021 LeetCode

[Help Center \(/support\)](/support/) | [Jobs \(/jobs\)](/jobs/) | [Bug Bounty \(/bugbounty\)](/bugbounty/) | [Online Interview \(/interview/\)](/interview/) | [Students \(/student\)](/student/) | [Terms \(/terms\)](/terms/) |

[Privacy Policy \(/privacy\)](/privacy/)

 [United States \(/region\)](/region/)