



## 2498. Frog Jump II

[My Submissions \(/contest/biweekly-contest-93/problems/frog-jump-ii/submissions/\)](#)
[Back to Contest \(/contest/biweekly-contest-93/\)](#)

You are given a **0-indexed** integer array `stones` sorted in **strictly increasing order** representing the positions of stones in a river.

A frog, initially on the first stone, wants to travel to the last stone and then return to the first stone. However, it can jump to any stone **at most once**.

The **length** of a jump is the absolute difference between the position of the stone the frog is currently on and the position of the stone to which the frog jumps.


- More formally, if the frog is at `stones[i]` and is jumping to `stones[j]`, the length of the jump is  $|\text{stones}[i] - \text{stones}[j]|$ .

The **cost** of a path is the **maximum length of a jump** among all jumps in the path.

Return the **minimum** cost of a path for the frog.

User Accepted:	3210
User Tried:	3877
Total Accepted:	3383
Total Submissions:	6405
Difficulty:	Medium

## Example 1:




**Input:** `stones = [0,2,5,6,7]`

**Output:** 5

**Explanation:** The above figure represents one of the optimal paths the frog can take. The cost of this path is 5, which is the maximum length of a jump. Since it is not possible to achieve a cost of less than 5, we return it.

## Example 2:



**Input:** `stones = [0,3,9]`

**Output:** 9

**Explanation:**

The frog can jump directly to the last stone and come back to the first stone. In this case, the length of each jump will be 9. The cost for the path will be  $\max(9, 9) = 9$ . It can be shown that this is the minimum achievable cost.

## Constraints:

- $2 \leq \text{stones.length} \leq 10^5$
- $0 \leq \text{stones}[i] \leq 10^9$
- `stones[0] == 0`
- `stones` is sorted in a strictly increasing order.

Discuss (<https://leetcode.com/problems/frog-jump-ii/discuss/>)

JavaScript



```
1 const maxJump = (a) => {  
2   let n = a.length, res = a[1];  
3   for (let i = 0; i + 2 < n; i++) res = Math.max(res, a[i+2] - a[i]);  
4   return res;  
5 };
```

☐ Custom Testcase[Use Example Testcases](#)[Run](#)[Submit](#)Submission Result: **Accepted** (</submissions/detail/857786253/>) ?[More Details >](/submissions/detail/857786253/)

Share your acceptance!

[◀1](#)

Copyright © 2022 LeetCode

[Help Center \(/support/\)](/support/) | [Jobs \(/jobs/\)](/jobs/) | [Bug Bounty \(/bugbounty/\)](/bugbounty/) | [Online Interview \(/interview/\)](/interview/) | [Students \(/student/\)](/student/) | [Terms \(/terms/\)](/terms/) | [Privacy Policy \(/privacy/\)](/privacy/) [United States \(/region/\)](/region/)