

6322. Check Knight Tour Configuration

My Submissions (/contest/weekly-contest-337/problems/check-knight-tour-configuration/submissions/)


Back to Contest (/contest/weekly-contest-337/)

There is a knight on an $n \times n$ chessboard. In a valid configuration, the knight starts **at the top-left cell** of the board and visits every cell on the board **exactly once**.

You are given an $n \times n$ integer matrix `grid` consisting of distinct integers from the range $[0, n * n - 1]$ where `grid[row][col]` indicates that the cell (row, col) is the `grid[row][col]`th cell that the knight visited. The moves are **0-indexed**.

Return `true` if `grid` represents a valid configuration of the knight's movements or `false` otherwise.

Note that a valid knight move consists of moving two squares vertically and one square horizontally, or two squares horizontally and one square vertically. The figure below illustrates all the possible eight moves of a knight from some cell.



Example 1:

0	11	16	5	20
17	4	19	10	15
12	1	8	21	6
3	18	23	14	9
24	13	2	7	22

Input: `grid = [[0,11,16,5,20],[17,4,19,10,15],[12,1,8,21,6],[3,18,23,14,9],[24,13,2,7,22]]`
Output: `true`
Explanation: The above diagram represents the grid. It can be shown that it is a valid configuration.

Example 2:

0	3	6
5	8	1
2	7	4

Input: `grid = [[0,3,6],[5,8,1],[2,7,4]]`
Output: `false`
Explanation: The above diagram represents the grid. The 8th move of the knight is not valid considering its position after the

Constraints:

- $n == \text{grid.length} == \text{grid[0].length}$

- $3 \leq n \leq 7$
- $0 \leq \text{grid}[\text{row}][\text{col}] < n * n$
- All integers in `grid` are **unique**.

JavaScript



```
1 const checkValidGrid = (g) => {
2   if (g[0][0] !== 0) return false;
3   let n = g.length, a = Array(n * n);
4   for (let i = 0; i < n; i++) {
5     for (let j = 0; j < n; j++) a[g[i][j]] = [i, j];
6   }
7   for (let i = 1; i < n * n; i++) {
8     let [x1, y1] = a[i - 1], [x2, y2] = a[i];
9     if (!ok(x1, y1, x2, y2)) return false;
10  }
11  return true;
12 };
13
14 const ok = (x1, y1, x2, y2) => {
15   let dx = Math.abs(x1 - x2), dy = Math.abs(y1 - y2);
16   return (dx == 1 && dy == 2) || (dx == 2 && dy == 1)
17 };
```

☐ Custom Testcase

Use Example Testcases

Run

Submit

Submission Result: **Accepted** (/submissions/detail/917821240/) ⓘ

More Details > (/submissions/detail/917821240/)

Share your acceptance!

Copyright © 2023 LeetCode

[Help Center \(/support\)](#) | [Jobs \(/jobs\)](#) | [Bug Bounty \(/bugbounty\)](#) | [Online Interview \(/interview/\)](#) | [Students \(/student\)](#) | [Terms \(/terms\)](#) | [Privacy Policy \(/privacy\)](#)[United States \(/region\)](#)