6063. Maximum Score of a Node Sequence

| My Submissions (/contest/biweekly-contest-76/problems/maximum-score-of-a-node-sequence/submissions/) | Back to Contest (/contest/biweekly-contest-76/) |

There is an **undirected** graph with `n` nodes, numbered from `0` to `n − 1`.

You are given a **0-indexed** integer array `scores` of length `n` where `scores[i]` denotes the score of node `i`. You are also given a 2D integer array `edges` where `edges[i] = [a_i, b_i]` denotes that there exists an **undirected** edge connecting nodes `a_i` and `b_i`.

A node sequence is **valid** if it meets the following conditions:

- There is an edge connecting every pair of **adjacent** nodes in the sequence.
- No node appears more than once in the sequence.

The score of a node sequence is defined as the **sum** of the scores of the nodes in the sequence.

Return *the **maximum score** of a valid node sequence with a length of* `4`. If no such sequence exists, return `−1`.

User Accepted:	0
User Tried:	0
Total Accepted:	0
Total Submissions:	0
Difficulty:	Hard

Example 1:


```
Input: scores = [5,2,9,8,4], edges = [[0,1],[1,2],[2,3],[0,2],[1,3],[2,4]]
Output: 24
Explanation: The figure above shows the graph and the chosen node sequence [0,1,2,3].
The score of the node sequence is 5 + 2 + 9 + 8 = 24.
It can be shown that no other node sequence has a score of more than 24.
Note that the sequences [3,1,2,0] and [1,0,2,3] are also valid and have a score of 24.
The sequence [0,3,2,4] is not valid since no edge connects nodes 0 and 3.
```

Example 2:


```
Input: scores = [9,20,6,4,11,12], edges = [[0,3],[5,3],[2,4],[1,3]]
Output: -1
Explanation: The figure above shows the graph.
There are no valid node sequences of length 4, so we return -1.
```

Constraints:

- `n == scores.length`
- $4 <= n <= 5 * 10^4$
- $1 <= scores[i] <= 10^8$
- $0 <= edges.length <= 5 * 10^4$
- `edges[i].length == 2`
- $0 <= a_i, b_i <= n - 1$
- $a_i != b_i$
- There are no duplicate edges.

C++

```cpp
1 ▾ class Solution {
2   public:
3 ▾     int maximumScore(vector<int>& scores, vector<vector<int>>& edges) {
4   
5       }
6   };
```

☐ **Custom Testcase**   (Use Example Testcases)

▶ Run   ☁ Submit

Help Center (/support) | Jobs (/jobs) | Bug Bounty (/bugbounty) | Online Interview (/interview/) | Students (/student) | Terms (/terms) | Privacy Policy (/privacy)

🇺🇸 United States (/region)