

5627. Stone Game VII

My Submissions (/contest/weekly-contest-219/problems/stone-game-vii/submissions/)

Back to Contest (/contest/weekly-contest-219/)

Alice and Bob take turns playing a game, with **Alice starting first**.

There are n stones arranged in a row. On each player's turn, they can **remove** either the leftmost stone or the rightmost stone from the row and receive points equal to the **sum** of the remaining stones' values in the row. The winner is the one with the higher score when there are no stones left to remove.

Bob found that he will always lose this game (poor Bob, he always loses), so he decided to **minimize the score's difference**. Alice's goal is to **maximize the difference** in the score.

Given an array of integers `stones` where `stones[i]` represents the value of the i^{th} stone **from the left**, return the **difference** in Alice and Bob's score if they both play **optimally**.

| | |
|--------------------|--------|
| User Accepted: | 0 |
| User Tried: | 0 |
| Total Accepted: | 0 |
| Total Submissions: | 0 |
| Difficulty: | Medium |

Example 1:

Input: stones = [5,3,1,4,2]
Output: 6
Explanation:

- Alice removes 2 and gets 5 + 3 + 1 + 4 = 13 points. Alice = 13, Bob = 0, stones = [5,3,1,4].
- Bob removes 5 and gets 3 + 1 + 4 = 8 points. Alice = 13, Bob = 8, stones = [3,1,4].
- Alice removes 3 and gets 1 + 4 = 5 points. Alice = 18, Bob = 8, stones = [1,4].
- Bob removes 1 and gets 4 points. Alice = 18, Bob = 12, stones = [4].
- Alice removes 4 and gets 0 points. Alice = 18, Bob = 12, stones = [].

The score difference is 18 - 12 = 6.

Example 2:

Input: stones = [7,90,5,1,100,10,10,2]
Output: 122

Constraints:

- $n == \text{stones.length}$
- $2 \leq n \leq 1000$
- $1 \leq \text{stones}[i] \leq 1000$

Java

```
1 class Solution {
2     public int stoneGameVII(int[] stones) {
3
4     }
5 }
```