

Daily Coding Problem #120

Problem

This problem was asked by Microsoft.

Implement the singleton pattern with a twist. First, instead of storing one instance, store two instances. And in every even call of `getInstance()`, return the first instance and in every odd call of `getInstance()`, return the second instance.

Solution

This question is more about programming and design patterns than computer science.

The singleton pattern allows you to limit the number of objects of a class to one instance. This is helpful in a large application either to conserve resources such as memory or to make correctness easier to reason about. For example, to represent configuration of a system, it would be helpful to have one centralized object.

In this particular question, we ask for a twist on the classic singleton by allowing two instances of a class. We do this by adding another static field as well as `calls` variable to keep track of the number of calls made to `getInstance`.

```
public class Service {  
    private static Service instanceOne = null;  
    private static Service instanceTwo = null;
```

```
    private static int calls = 0;
```

```
private Service() {  
    // Disallow creation through the constructor  
}  
  
public static Service getInstance() {  
    if(instanceOne == null) {  
        instanceOne = new Service();  
        instanceTwo = new Service();  
    }  
  
    if (calls++ % 2 == 0) {  
        return instanceOne;  
    }  
    return instanceTwo;  
}  
}
```

© Daily Coding Problem 2019

[Privacy Policy](#)

[Terms of Service](#)

[Press](#)