

1. Suppose that an input image is given by the following array and the 3×3 kernel used by a convolutional layer is shown below.

$$\begin{bmatrix} 0 & 1 & 0 & 1 \\ 0 & 1 & 0 & 1 \\ 1 & 1 & 1 & 1 \\ 0 & -2 & 0 & -2 \end{bmatrix}$$

Image

$$\begin{bmatrix} -\frac{1}{2} & 1 & -\frac{1}{2} \\ -\frac{1}{2} & 1 & -\frac{1}{2} \\ -\frac{1}{2} & 1 & -\frac{1}{2} \end{bmatrix}$$

3×3 kernel

- (a) Find the output from the convolutional layer w/ zero-padding
- (b) suppose that the convolutional layer is followed by a max pooling layer w/ 2×2 filter. What would be the output if stride of 2 is used for max pooling?

2. Suppose a dataset consists of the following six points (where each row corresponds to a data point).

$$\begin{bmatrix} 0 & 1 \\ 0 & -1 \\ 1 & 0 \\ -1 & 1 \\ -2 & 0 \\ -1 & -1 \end{bmatrix} = X$$

Find the two clusters w/ associated centroids after two iterations, starting w/ two initial centroids $C_1 = [0 \ 1]$ & $C_2 = [-1 \ 1]$, using k-means clustering.

3. Consider the following dataset.

$$X = \begin{bmatrix} 0.66 & 0.68 & 0.66 \\ 0.04 & 0.76 & 0.17 \\ 0.85 & 0.74 & 0.71 \\ 0.93 & 0.39 & 0.03 \end{bmatrix}$$

Find the 1-dimensional embedding representation using classical multidimensional scaling.


Solution

1a.
$$\begin{bmatrix} -1 & 2 & -2 & 2 \\ -0.5 & 2 & -2 & 2.5 \\ 1 & -1 & 1 & -0.5 \\ 1.5 & -2 & 2 & -1.5 \end{bmatrix}$$

1b.
$$\begin{bmatrix} 2 & 2.5 \\ 1.5 & 2 \end{bmatrix}$$

2. Iteration 1.

step 1. Assign each point to the closest centroid



Initially $C_1 = \{1, 2, 3\}$

$C_2 = \{4, 5, 6\}$

step 2: new centroids

$$\begin{aligned} \bar{C}_1 &= \frac{1}{3} ([0 \ 1] + [1 \ 0] + [0 \ -1]) \\ &= \left[\frac{1}{3} \ 0 \right] \end{aligned}$$

$$\begin{aligned} \bar{C}_2 &= \frac{1}{3} ([-1 \ 1] + [-2 \ 0] + [-1 \ -1]) \\ &= \left[-\frac{4}{3} \ 0 \right] \end{aligned}$$

Iteration 2.

step 1. Assign each point to the closest centroid
clearly, the assignments would not change
because the first three data points are
closer to \bar{C}_1 , while the last three data
points are closer to \bar{C}_2 .

step 2. Since memberships have not changed
the centroids are the same and the
algorithm will terminate

3. To find the 1-dimensional embedding, we need to first compute the centered Gram matrix

$$B = HXX^TH$$

where $H = I_{4 \times 4} - \frac{1}{n} \mathbf{1} \mathbf{1}^T$

$$B = \begin{bmatrix} 0.0746 & -0.0783 & 0.0978 & -0.0940 \\ -0.0783 & 0.3997 & -0.1926 & -0.1288 \\ 0.0978 & -0.1926 & 0.1632 & -0.0684 \\ -0.0940 & -0.1288 & -0.0684 & 0.2913 \end{bmatrix}$$

Then, compute the eigenvalues & eigenvectors of B . Since we are interested in one-dimensional embedding, it is given by the eigenvector corresponding to the largest eigenvalue

$$\underline{v}^1 = [0.1793 \quad -0.8518 \quad 0.4261 \quad 0.2464]$$