

Moving from for to foreach

Henry Scharf

November 20, 2014

Contents

THOUGHTS:	1
Why?	1
Options in R	2
Why foreach?	2
Goal: transform a traditional for loop into a foreach loop	2
The data and research question	2
some nice figures	3
K fold CV with a for loop	3
Bootstrapping with an apply function	4
Bootstrapping with a foreach loop	4
Components of a foreach loop	5
iterators	5

THOUGHTS:

- need something more compelling for `iterators`
- more complicated example for `.combine?` mean?
- do their own code? fix some code?
- images for heavy analysis?
- model search? random forest? svm? other ML topics?
- references
- dornig in my bootstrap?

Why?

Embarassingly parallel tasks

- computational tasks which involve many, separate, independently executable calculations

- common statistical examples of embarrassingly parallel processes:
- bootstrapping
 - cross-validation
 - simulating independent random variables (`dorng`)
- non-parallel processes:
 - MCMC algorithms
 - stepwise model selection (e.g.: `step()`)
- For loops that do not explicitly involve dependent calculations are wasteful, especially if we have multiple processors available
- Perhaps even worse, the time cost of using a wasteful approach can put some useful statistical tools beyond our reach!

Options in R

- changing from a for loop to one of the `apply()` functions can help, but still doesn't use multiple processors
- `parallel` package (thanks, Miranda!)
- don't use R

Why foreach?

We would like to find a way to make use of our whole computer, and make useful tasks like bootstrapping available to use, but without having to invest large amounts of time in learning new programming languages. Enter **foreach**, which keeps the structure of a for loop, but allows us to drop two key assumptions:

- sequentiality
- single processor architecture

Goal: transform a traditional for loop into a foreach loop

We will begin with a simple chunk of R code involving a for loop, and transform it. Along the way, we'll take a look at the equivalent computation done with an `apply()` function, and see that using `foreach` and multiple processors outperforms this too.


The data and research question

We are going to look at data from the New York City bikeshare program (Citibike).

- 7 busiest (on average) locations from May 2014
- response is # of arrivals each hour of every day in the month
- covariates are hour of the day, and whether the day is a weekend

Goal: find a model which can offer good prediction. Start with a few plausible models and use K fold cross validation to decide which one to use.

some nice figures



K fold CV with a for loop

We now suppose that we are conducting an analysis wherein we'd like to fit a linear regression, then obtain estimates of standard errors for each slope parameter through bootstrapping.

Here's some familiar code:

```
data(airquality)
dim(airquality)
```

```
## [1] 153 6
```

```

names(airquality)

## [1] "Ozone" "Solar.R" "Wind" "Temp" "Month" "Day"

N <- 10^2
## make a function to be used in all three instances
boot.func <- function(i) {
  train.set <- sample(1:153, size = 153, replace = T)
  fit <- lm(Ozone ~ .^2, data = airquality[train.set, ])
  coef.mse <- summary(fit)$coef[, 2]
  return(coef.mse)
}
## 'for' version
coef.mse.for <- NULL
system.time(
  for (i in 1:N) {
    coef.mse.for <- cbind(coef.mse.for, boot.func(i))
  }
)[3]

## elapsed
## 0.287

```

Bootstrapping with an apply function

If you're good with `apply()` functions you might upgrade to

```

## apply version
system.time(
  coef.mse.sapply <- sapply(X = 1:N, FUN = boot.func)
)[3]

## elapsed
## 0.28

```

Neither of the first two methods take advantage of multiple processors. While `apply()` functions avoid the inherently sluggish nature of for loops in R, they are still ignorant of the processor structure. We want to chop the job into halves, fourths, etc. and use the *whole* computer!

Bootstrapping with a foreach loop

Here is the same computation written with a `foreach()` loop

```

## foreach version
library(foreach)
library(doRNG)

## Loading required package: rngtools
## Loading required package: pkgmaker
## Loading required package: registry

```

```
library(doParallel)

## Loading required package: iterators
## Loading required package: parallel

registerDoParallel(cores = 4) ## multi-threading issues with cores = 2
system.time(
  coef.mse.foreach <- foreach(i = 1:N,
                              .inorder = FALSE,
                              .combine = 'cbind',
                              .options.RNG = 1985) %dorng% boot.func(i)
) [3]

## elapsed
## 0.362
```

Components of a foreach loop

- %do% and %dopar%
- arguments to consider
 - .combine can take on the intuitive values c, cbind,
 - .inorder

iterators

Sometimes the list or vector that we are iterating over (in the above case, the vector 1:N) can be a very large object. In our case, the vector is quite reasonable in size, but perhaps the object we were iterating over was a multi-dimensional object, with many values, and a high level of precision. In this case, we'd be storing a massive object, which could potentially fill up our useable memory and slow things down. We could save memory by only keeping the piece of our list we need for a given calculation, and dumping the rest. This is the idea behind the `iterators` package in R.

Our same example with an iterator instead of a list