



Date: 13/02/25

Lab Practical #10 :

Perform password cracking concept using brute force tools- L0phtCrack and John the ripper.

1. set the path of your file.

```
(student@student)-[~]
$ john --wordlist=/usr/share/wordlists/rockyou.txt newp.txt
Using default input encoding: UTF-8
Loaded 1 password hash (sha512crypt, crypt(3) $6$ [SHA512 256/256 AVX2 4x])
No password hashes left to crack (see FAQ)
```

2. incremental option converts your txt file to ASCII code
3. After convert into ASCII code --show option show cracked password.

```
(student@student)-[~]
$ john --incremental newp.txt
Using default input encoding: UTF-8
Loaded 1 password hash (sha512crypt, crypt(3) $6$ [SHA512 256/256 AVX2 4x])
Cost 1 (iteration count) is 5000 for all loaded hashes
Will run 12 OpenMP threads
Press 'q' or Ctrl-C to abort, almost any other key for status
stdin (?)
1g 0:00:06:52 DONE (2025-02-13 09:25) 0.002423g/s 11405p/s 11405c/s 11405C/s ap1
lt..sedoh
Use the "--show" option to display all of the cracked passwords reliably
Session completed.

(student@student)-[~]
$ john --show newp.txt
?:stdin
1 password hash cracked, 0 left
```

Date: 13/02/25

```
(student@student)-[~]
$ john --wordlist=/usr/share/wordlists/rockyou.txt newp.txt
Using default input encoding: UTF-8
Loaded 1 password hash (sha512crypt, crypt(3) $6$ [SHA512 256/256 AVX2 4x])
Cost 1 (iteration count) is 5000 for all loaded hashes
Will run 12 OpenMP threads
fopen: /usr/share/wordlists/rockyou.txt: No such file or directory
```

```
(student@student)-[~]
$
```

```
(root@student)-[~]
# nano pass.txt
(root@student)-[~]
# nano pass.txt
(root@student)-[~]
# cat pass.txt
:
test01:$y$j9T$zIxDOMiNqclVurKInYP3G/$ZxJiQ3ggKu4z8AGPOnpmz/QDLsmRHv3nseUuaEjypSB:20131:0:99999:7:::
test02:$y$j9T$77xRPovh6CsEoz5pWqzIv1$3IhgsCwzO8sNi0CNWQRn49QfGwesv/AOGcxB3aM/db0:20131:0:99999:7:::

(root@student)-[~]
# john -foamat==crypt pass.txt
Unknown option: "-foamat==crypt"

(root@student)-[~]
# john -format==crypt pass.txt
Unknown ciphertext format name requested

(root@student)-[~]
# john -format=crypt pass.txt
Using default input encoding: UTF-8
Loaded 2 password hashes with 2 different salts (crypt, generic crypt(3) [?/64])
Cost 1 (algorithm [1:descrypt 2:md5crypt 3:sunmd5 4:bcrypt 5:sha256crypt 6:sha512crypt]) is 0 for all loaded hashes
Cost 2 (algorithm specific iterations) is 1 for all loaded hashes
Will run 12 OpenMP threads
Proceeding with single, rules:Single
Press 'q' or Ctrl-C to abort, almost any other key for status
0g 0:00:00:27 74.41% 1/3 (ETA: 08:59:30) 0g/s 144.1p/s 144.1c/s 144.1c/s [t99999]..test019999942
```



Date: 13/02/25

```
root@student: ~
dnsmasq:!:20061:!:
ssllh:!:20061:!:
postgres:!:20061:!:
avahi:!:20061:!:
_gvm:!:20061:!:
speech-dispatcher:!:20061:!:
fwupd-refresh:!:20061:!:
inetsim:!:20061:!:
geoclue:!:20061:!:
lightdm:!:20061:!:
sddm:!:20061:!:
gnome-remote-desktop:!:20061:!:
statd:!:20061:!:
sane:!:20061:!:
polkitd:!:20061:!:
rtkit:!:20061:!:
colord:!:20061:!:
Debian-gdm:!:20061:!:
nm-openvpn:!:20061:!:
nm-openconnect:!:20061:!:
student:$y$j9T$zIxDOMiNqclVUrKInYP3G/$ZxJiQ3ggKu4z8AGPonpmz/QDL5mRHv3nseUuaEjyp5B:20131:0:99999:7:::
test01:$y$j9T$zIxDOMiNqclVUrKInYP3G/$ZxJiQ3ggKu4z8AGPonpmz/QDL5mRHv3nseUuaEjyp5B:20131:0:99999:7:::
test02:$y$j9T$77xRPovhC6sEoz5pWqzIv1$3IhgsCwz08sNi0CNWQRn49QfGwesv/ADGcxB3aM/db0:20131:0:99999:7:::

(root@student)~# nano pass.txt
(root@student)~# nano pass.txt
(root@student)~# cat pass.txt
:
test01:$y$j9T$zIxDOMiNqclVUrKInYP3G/$ZxJiQ3ggKu4z8AGPonpmz/QDL5mRHv3nseUuaEjyp5B:20131:0:99999:7:::
test02:$y$j9T$77xRPovhC6sEoz5pWqzIv1$3IhgsCwz08sNi0CNWQRn49QfGwesv/ADGcxB3aM/db0:20131:0:99999:7:::

(root@student)~# john -format=crypt pass.txt
```

```
zsh: permission denied: /etc/shadow

(root@student)~# adduser test01
info: Adding user `test01' ...
info: Selecting UID/GID from range 1000 to 59999 ...
info: Adding new group `test01' (1001) ...
info: Adding new user `test01' (1001) with group `test01 (1001)' ...
info: Creating home directory `/home/test01' ...
info: Copying files from `/etc/skel' ...
New password:
Retype new password:
passwd: password updated successfully
Changing the user information for test01
Enter the new value, or press ENTER for the default
Full Name []: Test 01
Room Number []: 0
Work Phone []: 0
Home Phone []: 0
Other []: 0
Is the information correct? [Y/n] y
info: Adding new user `test01' to supplemental / extra groups `users' ...
info: Adding user `test01' to group `users' ...

(root@student)~# adduser test02
info: Adding user `test02' ...
info: Selecting UID/GID from range 1000 to 59999 ...
info: Adding new group `test02' (1002) ...
info: Adding new user `test02' (1002) with group `test02 (1002)' ...
info: Creating home directory `/home/test02' ...
info: Copying files from `/etc/skel' ...
New password:
Retype new password:
passwd: password updated successfully
Changing the user information for test02
Enter the new value, or press ENTER for the default
Full Name []:
```



Date: 13/02/25

```
test02:$y$j9T$77xRPovh6CsEoz5pWqzIv1$3IhgsCwzO8sNi0CNWQRn49QfGwesv/AOGcxB3aM/db0:20131:0:99999:7:::

(root@student)-[~]
# cat /etc/shadow
root:!:20061:0:99999:7:::
daemon:!:20061:0:99999:7:::
bin:!:20061:0:99999:7:::
sys:!:20061:0:99999:7:::
sync:!:20061:0:99999:7:::
games:!:20061:0:99999:7:::
man:!:20061:0:99999:7:::
lp:!:20061:0:99999:7:::
mail:!:20061:0:99999:7:::
news:!:20061:0:99999:7:::
uucp:!:20061:0:99999:7:::
proxy:!:20061:0:99999:7:::
www-data:!:20061:0:99999:7:::
backup:!:20061:0:99999:7:::
list:!:20061:0:99999:7:::
irc:!:20061:0:99999:7:::
_apt:!:20061:0:99999:7:::
nobody:!:20061:0:99999:7:::
systemd-network:!:20061:!:
_galera:!:20061:!:
mysql:!:20061:!:
tss:!:20061:!:
systemd-coredump:!:20061:!:
strongswan:!:20061:!:
systemd-timesync:!:20061:!:
rwhod:!:20061:!:
_gophish:!:20061:!:
iodine:!:20061:!:
messagebus:!:20061:!:
tcpdump:!:20061:!:
miredo:!:20061:!:
_rpc:!:20061:!:
Debian-snmpp:!:20061:!:
redis:!:20061:!:
nats:!:20061:!:
```

```
test01:$y$j9T$zIxDOMiNqclVUrKInYP3G/$zXjiQ3ggKu4z8AGPONpmz/QDLsmRHv3nseUuaEjypSB:20131:0:99999:7:::
test02:$y$j9T$77xRPovh6CsEoz5pWqzIv1$3IhgsCwzO8sNi0CNWQRn49QfGwesv/AOGcxB3aM/db0:20131:0:99999:7:::

(root@student)-[~]
# cat /etc/passwd
root:x:0:0:root:/root:/usr/bin/zsh
daemon:x:1:1:daemon:/usr/sbin:/usr/sbin/nologin
bin:x:2:2:bin:/bin:/usr/sbin/nologin
sys:x:3:3:sys:/dev:/usr/sbin/nologin
sync:x:4:65534:sync:/bin:/bin/sync
games:x:5:60:games:/usr/games:/usr/sbin/nologin
man:x:6:12:man:/var/cache/man:/usr/sbin/nologin
lp:x:7:7:lp:/var/spool/lpd:/usr/sbin/nologin
mail:x:8:8:mail:/var/mail:/usr/sbin/nologin
news:x:9:9:news:/var/spool/news:/usr/sbin/nologin
uucp:x:10:10:uucp:/var/spool/uucp:/usr/sbin/nologin
proxy:x:13:13:proxy:/bin:/usr/sbin/nologin
www-data:x:33:33:www-data:/var/www:/usr/sbin/nologin
backup:x:34:34:backup:/var/backups:/usr/sbin/nologin
list:x:38:38:Mailing List Manager:/var/list:/usr/sbin/nologin
irc:x:39:39:ircd:/run/ircd:/usr/sbin/nologin
_apt:x:42:65534:./nonexistent:/usr/sbin/nologin
nobody:x:65534:65534:nobody:/nonexistent:/usr/sbin/nologin
systemd-network:x:998:998:systemd Network Management:./usr/sbin/nologin
_galera:x:100:65534:./nonexistent:/usr/sbin/nologin
mysql:x:101:102:MariaDB Server,./nonexistent:/bin/false
tss:x:102:103:TPM software stack,./var/lib/tpm:/bin/false
systemd-coredump:x:992:992:systemd Core Dumper:./usr/sbin/nologin
strongswan:x:103:65534:./var/lib/strongswan:/usr/sbin/nologin
systemd-timesync:x:991:991:systemd Time Synchronization:./usr/sbin/nologin
rwhod:x:104:65534:./var/spool/rwho:/usr/sbin/nologin
_gophish:x:105:105:./var/lib/gophish:/usr/sbin/nologin
iodine:x:106:65534:./run/iodine:/usr/sbin/nologin
messagebus:x:107:106:./nonexistent:/usr/sbin/nologin
tcpdump:x:108:107:./nonexistent:/usr/sbin/nologin
miredo:x:109:65534:./var/run/miredo:/usr/sbin/nologin
_rpc:x:110:65534:./run/rpcbind:/usr/sbin/nologin
Debian-snmpp:x:111:109:./var/lib/snmpp:/bin/false
```