

The logo of the University of Bonn, featuring a blue square in the top left corner and a grey square in the top right corner, separated by a white curved line.

UNIVERSITÄT **BONN**

Juergen Gall

Optical Flow
MA-INF 2201 - Computer Vision
WS24/25

Visual motion





Uses of motion

- Estimating 3D structure
- Segmenting objects based on motion cues
- Learning and tracking dynamical models
- Recognizing events and activities


Motion field

- The motion field is the projection of the 3D scene motion into the image



Motion field and optical flow


- $\mathbf{X}(t)$ is a moving 3D point
- Velocity of scene point:
 $\mathbf{V} = d\mathbf{X}/dt$
- $\mathbf{x}(t) = (x(t), y(t))$ is the projection of \mathbf{X} in the image
- Apparent velocity \mathbf{v} in the image: given by components $v_x = dx/dt$ and $v_y = dy/dt$
- These components are known as the *motion field* of the image





Optical flow

- Definition: optical flow is the *apparent* motion of brightness patterns in the image
- Ideally, optical flow would be the same as the motion field
- Have to be careful: apparent motion can be caused by lighting changes without any actual motion

- Have to be careful: apparent motion can be caused by lighting changes without any actual motion




Estimating optical flow


 $I(x,y,t-1)$

 $I(x,y,t)$

- Given two subsequent frames, estimate the apparent motion field $u(x,y)$ and $v(x,y)$ between them

The brightness constancy constraint



- Brightness Constancy Equation:

$$I(x, y, t - 1) = I(x + u(x, y), y + v(x, y), t)$$

Linearizing the right side using Taylor expansion:

$$I(x, y, t - 1) \approx I(x, y, t) + I_x \cdot u(x, y) + I_y \cdot v(x, y)$$

Hence, $I_x \cdot u + I_y \cdot v + I_t \approx 0$ or $\nabla I \cdot (u, v) + I_t \approx 0$

The brightness constancy constraint

$$I_x \cdot u + I_y \cdot v + I_t = 0$$

- How many equations and unknowns per pixel?
 - One equation, two unknowns

The brightness constancy constraint


- Intuitively, what does this constraint mean?

$$\nabla I \cdot (u, v) + I_t = 0$$


- The component of the flow perpendicular to the gradient (i.e., parallel to the edge) is unknown

- If (u, v) satisfies the equation, so does $(u+u', v+v')$ if

$$\nabla I \cdot (u', v') = 0$$




The aperture problem




Perceived motion


The aperture problem



The barber pole illusion



The barber pole illusion



The barber pole illusion



http://en.wikipedia.org/wiki/Barberpole_illusion

Solving the aperture problem

- How to get more equations for a pixel?
- **Spatial coherence constraint:** pretend the pixel's neighbors have the same (u,v)
 - If we use a 5x5 window, that gives us 25 equations per pixel

$$0 = I_t(\mathbf{p}_i) + \nabla I(\mathbf{p}_i) \cdot [u \ v]$$

$$\begin{bmatrix} I_x(\mathbf{p}_1) & I_y(\mathbf{p}_1) \\ I_x(\mathbf{p}_2) & I_y(\mathbf{p}_2) \\ \vdots & \vdots \\ I_x(\mathbf{p}_{25}) & I_y(\mathbf{p}_{25}) \end{bmatrix} \begin{bmatrix} u \\ v \end{bmatrix} = - \begin{bmatrix} I_t(\mathbf{p}_1) \\ I_t(\mathbf{p}_2) \\ \vdots \\ I_t(\mathbf{p}_{25}) \end{bmatrix}$$

B. Lucas and T. Kanade. [An iterative image registration technique with an application to stereo vision](#). In *Proceedings of the International Joint Conference on Artificial Intelligence*, pp. 674–679, 1981.

Solving the aperture problem

- Least squares problem:

$$\begin{bmatrix} I_x(p_1) & I_y(p_1) \\ I_x(p_2) & I_y(p_2) \\ \vdots & \vdots \\ I_x(p_{25}) & I_y(p_{25}) \end{bmatrix} \begin{bmatrix} u \\ v \end{bmatrix} = - \begin{bmatrix} I_t(p_1) \\ I_t(p_2) \\ \vdots \\ I_t(p_{25}) \end{bmatrix} \quad \begin{matrix} A & d = b \\ 25 \times 2 & 2 \times 1 & 25 \times 1 \end{matrix}$$

- Is this system always solvable?
- Only if rank of A is 2
- Not the case for edges

B. Lucas and T. Kanade. [An iterative image registration technique with an application to stereo vision](#). In *Proceedings of the International Joint Conference on Artificial Intelligence*, pp. 674–679, 1981.

Conditions for solvability



Bad case



Good case

Lucas-Kanade flow

- Linear least squares problem

$$\begin{bmatrix} I_x(\mathbf{p}_1) & I_y(\mathbf{p}_1) \\ I_x(\mathbf{p}_2) & I_y(\mathbf{p}_2) \\ \vdots & \vdots \\ I_x(\mathbf{p}_{25}) & I_y(\mathbf{p}_{25}) \end{bmatrix} \begin{bmatrix} u \\ v \end{bmatrix} = - \begin{bmatrix} I_t(\mathbf{p}_1) \\ I_t(\mathbf{p}_2) \\ \vdots \\ I_t(\mathbf{p}_{25}) \end{bmatrix} \quad \begin{matrix} A & d = b \\ 25 \times 2 & 2 \times 1 & 25 \times 1 \end{matrix}$$

Solution given by $(A^T A) d = A^T b$

$$\begin{bmatrix} \sum I_x I_x & \sum I_x I_y \\ \sum I_x I_y & \sum I_y I_y \end{bmatrix} \begin{bmatrix} u \\ v \end{bmatrix} = - \begin{bmatrix} \sum I_x I_t \\ \sum I_y I_t \end{bmatrix}$$

$$\begin{matrix} A^T A & A^T b \end{matrix}$$

The summations are over all pixels in the window

B. Lucas and T. Kanade. [An iterative image registration technique with an application to stereo vision](#). In *Proceedings of the International Joint Conference on Artificial Intelligence*, pp. 674–679, 1981.


Lucas-Kanade flow

$$\begin{matrix} \begin{bmatrix} \sum I_x I_x & \sum I_x I_y \\ \sum I_x I_y & \sum I_y I_y \end{bmatrix} & \begin{bmatrix} u \\ v \end{bmatrix} & = & - & \begin{bmatrix} \sum I_x I_t \\ \sum I_y I_t \end{bmatrix} \\ A^T A & & & & A^T b \end{matrix}$$

- Recall the Harris corner detector: $M = A^T A$ is the *second moment matrix*

Interpreting the eigenvalues

Classification of image points using eigenvalues of the second moment matrix:





- gradients have small magnitude
- small λ_1 , small λ_2
- system is ill-conditioned



- gradients have one dominant direction
- large λ_1 , small λ_2
- system is ill-conditioned

High-texture or corner region



- gradients have different directions, large magnitudes
- large λ_1 , large λ_2
- system is well-conditioned

Errors in Lucas-Kanade

- The motion is large (larger than a pixel)
 - Iterative refinement
 - Coarse-to-fine estimation
 - Exhaustive neighborhood search (feature matching)
- A point does not move like its neighbors
 - Motion segmentation
- Brightness constancy does not hold
 - Exhaustive neighborhood search with normalized correlation

Feature tracking

- So far, we have only considered optical flow estimation in a pair of images
- If we have more than two images, we can compute the optical flow from each frame to the next
- Given a point in the first image, we can in principle reconstruct its path by simply “following the arrows”

Shi-Tomasi feature tracker

- Find good features using eigenvalues of second-moment matrix
 - Key idea: “good” features to track are the ones whose motion can be estimated reliably
- From frame to frame, track with Lucas-Kanade
 - This amounts to assuming a translation model for frame-to-frame feature movement
- Check consistency of tracks by *affine* registration to the first observed instance of the feature
 - Affine model is more accurate for larger displacements
 - Comparing to the first frame helps to minimize drift

Tracking example



Figure 1: Three frame details from Woody Allen's *Manhattan*. The details are from the 1st, 11th, and 21st frames of a subsequence from the movie.





Figure 2: The traffic sign windows from frames 1,6,11,16,21 as tracked (top), and warped by the computed deformation matrices (bottom).

Dense motion estimation

- For each pixel in an image, optical flow determines the corresponding pixel in the next image
- Can be cast as a variational problem



Image sequence $I(x, y, t)$



Optical flow field $(u, v)(x, y, t)$.

Horn-Schunck model

- Most basic model → good to start with
- Assumption I:
Gray value constancy (optic flow constraint)

$$I_x u + I_y v + I_t = 0 \quad \text{reminder: subscripts denote partial derivatives}$$

Linearized version of

$$I(x + u, y + v, t + 1) - I(x, y, t) = 0$$

- Assumption II:
Smoothness of optic flow field

$$|\nabla u|^2 + |\nabla v|^2 \rightarrow \min$$

- Combined in an energy functional:

$$E(u, v) = \int_{\Omega} (I_x u + I_y v + I_t)^2 + \alpha (|\nabla u|^2 + |\nabla v|^2) dx dy$$

Analysis of Horn-Schunck model

$$E(u, v) = \int_{\Omega} (I_x u + I_y v + I_t)^2 + \alpha (|\nabla u|^2 + |\nabla v|^2) dx dy$$

- First term penalizes deviations from optic flow constraints
- Second term penalizes deviations from smoothness
- Parameter α steers relative importance of assumptions

Theoretical analysis

- Both terms of the energy are convex in (u, v)

$$E(u, v) = \int_{\Omega} (I_x u + I_y v + I_t)^2 + \alpha(|\nabla u|^2 + |\nabla v|^2) dx dy$$

- Linear combination of two convex functionals is again convex
- There exists one unique minimum (Schnörr 1994)
- Further properties (Schnörr 1994):
 - Solution depends continuously on the input data
 - Smoothness: $u, v \in H^2(\Omega)$ (twice differentiable)

Euler-Lagrange equations

$$E(u, v) = \int_{\Omega} (I_x u + I_y v + I_t)^2 + \alpha(|\nabla u|^2 + |\nabla v|^2) dx dy$$

- Necessary conditions for a minimum: Euler-Lagrange equations

$$\left. \frac{d}{d\epsilon} E(u(x) + \epsilon h(x), v(x)) \right|_{\epsilon=0} = 0 \quad \forall h(x)$$

$$\left. \frac{d}{d\epsilon} E(u(x), v(x) + \epsilon h(x)) \right|_{\epsilon=0} = 0 \quad \forall h(x)$$

- This leads to:

$$(I_x u + I_y v + I_t) I_x - \alpha \Delta u = 0$$

$$(I_x u + I_y v + I_t) I_y - \alpha \Delta v = 0$$

- Discretization needed to solve for (u, v)

Spatial discretization

- Euler-Lagrange equation (for u):

$$(I_x u + I_y v + I_t) I_x - \alpha \Delta u = 0$$

- Approximate Laplacian by

$$\Delta u = u_{xx} + u_{yy}$$

$$\approx \frac{u_{i+1,j} + u_{i-1,j} + u_{i,j+1} + u_{i,j-1} - 4u_{i,j}}{h^2}$$

Pixel indices

0	1	0
1	-4	1
0	1	0

- Grid size usually set to $h = 1$
- Relevant in multi-grid schemes

Gradient descent

- Gradient descent
$$-\frac{dE}{du} = \Delta u - \frac{1}{\alpha}(I_x u + I_y v + I_t)I_x$$

- Most simple iterative scheme (explicit scheme)

$$u_{i,j}^0 = 0$$

$$u_{i,j}^{k+1} = \boxed{k} + \tau \left(\Delta u_{i,j}^k - \frac{1}{\alpha}(I_x u_{i,j}^k + I_y v_{i,j}^k + I_t)I_x \right)$$

Iteration index

- Right hand side contains only known values
→ easy to evaluate
- Stable for step sizes $\tau \leq \frac{1}{4}$
- Drawbacks:
 - Terribly slow
 - Updates eventually become too small (number precision)

Linear system of equations

- Euler-Lagrange equations

$$(I_x u + I_y v + I_t) I_x - \alpha \Delta u = 0$$

$$(I_x u + I_y v + I_t) I_y - \alpha \Delta v = 0$$

- Discretized version

$$\frac{u_{i+1,j} + u_{i-1,j} + u_{i,j+1} + u_{i,j-1} - 4u_{i,j}}{h^2} - \frac{1}{\alpha} (I_x u_{i,j} + I_y v_{i,j} + I_t) I_x = 0$$

$$\frac{v_{i+1,j} + v_{i-1,j} + v_{i,j+1} + v_{i,j-1} - 4v_{i,j}}{h^2} - \frac{1}{\alpha} (I_x u_{i,j} + I_y v_{i,j} + I_t) I_y = 0$$

- Linear in (u, v)

Concatenation of u and v



- Can be written in matrix-vector notation $A^h w = b$

Linear system of equations

- Sparse linear system

$$A^h = \begin{pmatrix} d & & & & & & \\ & d & & & & & \\ & & d & & & & \\ & & & d & & & \\ & & & & d & & \\ d & & & & & d & \\ & d & & & & & d \\ & & d & & & & \\ & & & d & & & \\ & & & & d & & \\ & & & & & d & \\ & & & & & & d \end{pmatrix} + \begin{pmatrix} s & s & & s & & & \\ s & s & s & & s & & \\ & s & s & s & & s & \\ s & & s & s & s & s & \\ & s & & s & s & s & \\ & & s & & s & s & \\ & & & s & s & s & \\ s & s & & s & & & \\ s & s & s & & s & & s \\ & s & & s & s & s & \\ & & s & & s & s & \\ & & & s & s & s & \end{pmatrix}$$

- Blocks due to coupling of u and v
- **Data term** contributes only to block main diagonals
- **Smoothness term** has four additional block off-diagonals (coupling of neighboring pixels)

Solving the linear system

- Gauß-elimination
Not recommendable for sparse matrices (very slow)
- Iterative methods: Jacobi method (quite slow)
- Faster: Gauß-Seidel method
- Even faster: Successive over-relaxation (SOR)
- Other approaches:
 - Multi-grid methods
 - Conjugate gradient (CG) with a preconditioner (good for GPU implementation)
 - Primal-dual methods (require another numerical approach)

SOR for Horn-Schunck method

- Split the matrix into the diagonal part D , the lower triangle L and the upper triangle U

$$Aw = b \quad \Leftrightarrow \quad Dw = b - Lw - Uw$$

- Update scheme:

$$u_i^{k+1} = (1-\omega) u_i^k + \omega \frac{\sum_{j \in \mathcal{N}^-(i)} u_j^{k+1} + \sum_{j \in \mathcal{N}^+(i)} u_j^k - \frac{1}{\alpha} ((I_x I_y)_i v_i^k + (I_x I_t)_i)}{\sum_{j \in \mathcal{N}^-(i) \cup \mathcal{N}^+(i)} 1 + \frac{1}{\alpha} (I_x^2)_i}$$

- Relaxation parameter $\omega \in (0, 2)$
- Gauß-Seidel method for $\omega = 1$
- Optimal ω (fastest convergence) depends on the problem
Horn-Schunck method: $\omega = 1.98$

[Thomas Brox. From Pixels to Regions: Partial Differential Equations in Image Analysis. 2005]

Computation speed with various solvers

- Results from Bruhn et al. 2005, CPU

	Iterations	Frames/sec	Speedup
Gauß-Seidel	21931	0.026	1
SOR	286	1.381	54
Cascadic GS	237	1.667	65
Cascadic SOR	25	8.125	316
Full multi-grid	1	18.229	708

- Speedup of multi-grid techniques much smaller for extended models

Average angular error

- Established measure of how accurate an optic flow method is
- Computes the angle between the correct $(u_c, v_c)^\top$ and estimated $(u, v)^\top$ flow vector

$$\text{AAE} := \frac{1}{n} \sum_{i=1}^n \arccos \left(\frac{(u_c)_i u_i + (v_c)_i v_i + 1}{\sqrt{((u_c)_i^2 + (v_c)_i^2 + 1)(u_i^2 + v_i^2 + 1)}} \right)$$

- Alternative: average endpoint error:

$$\text{AEE} := \frac{1}{n} \sum_{i=1}^n \left(((u_c)_i - u_i)^2 + ((v_c)_i - v_i)^2 \right)$$

Middlebury flow benchmark

Popular optical flow benchmark

<http://vision.middlebury.edu/flow/>

Poor correlation with real-world problems





8 test sequences with ground truth




8 training sequences with ground truth

MPI-Sintel Optical Flow Dataset

Ground-truth from
open-source
movie Sintel
(Butler et al. ECCV
2012)



Yosemite Flow Sequences




Barron, J. L., Fleet, D. J. and Beauchemin, S. S., Performance of optical flow techniques, International Journal of Computer Vision, 12(1):43-77, 1994.


Results with Horn-Schunck method




Input sequence



Horn-Schunck (7.17°)



Ground truth



Lucas-Kanade (8.78°)


Yosemite test sequence

Illumination changes




Occlusion

Motion discontinuities





“Large” displacements



Limitations of Horn-Schunck method


Cloud region not well estimated due to illumination changes

Motion discontinuities blurred



Outliers due to occlusion

Underestimation of large displacements





Motion discontinuities



Occlusions



Illumination changes



Large displacements




Really large displacements

Motion discontinuities



- Different, independently moving objects cause discontinuities in the correct flow field
- Usually we do not know the object boundaries



Motion discontinuities and the smoothness assumption

- Fact: smoothness assumption not satisfied everywhere
- Quadratic penalizer \rightarrow Gaussian error distribution

$$E(u, v) = \int_{\Omega} (I_x u + I_y v + I_t)^2 + \alpha (|\nabla u|^2 + |\nabla v|^2) dx dy$$

- Too much influence given to outliers \rightarrow blurring

Non-quadratic smoothness term

Applying a robust function:


$$E_S(u, v) = \int_{\Omega} \Psi(|\nabla u|^2 + |\nabla v|^2) dx dy$$

For example:

Total variation (TV)

$$\Psi(s^2) = \sqrt{s^2 + \epsilon^2}, \quad \epsilon = 0.001$$

Advantage: still convex
→ global optimum!



Fixed-point iteration

Lagrange equations for regularizer

$$-\operatorname{div} \left(\psi'(|\nabla u|^2 + |\nabla v|^2) \nabla u \right) = 0$$

$$-\operatorname{div} \left(\psi'(|\nabla u|^2 + |\nabla v|^2) \nabla v \right) = 0$$

TV penalizer depends on the unknown flow

$$\psi'(s^2) = \frac{1}{\sqrt{s^2 + \epsilon^2}}$$

Solution:


- Keep ψ' fixed for an (initial) solution (u, v) (fixed point)
- Solve resulting linear system to obtain a new fixed point
- Update ψ' , iterate

[Brox et al. **High Accuracy Optical Flow Estimation Based on a Theory for Warping**. ECCV 2004]


Result: improvements at motion discontinuities




Non-quadratic smoothness term (6.36°)



Horn-Schunck (7.17°)



Ground truth



Occlusions



Some pixels of frame 1 no longer visible in frame 2

Pixels matched to most similar pixels in frame 2
→ erroneous motion vectors

Dealing with occlusions and non-Gaussian noise

Robust function applied to the data term:
(Black-Anandan 1996, Mémin-Pérez 1998)

$$E(u, v) = \int_{\Omega} \Psi \left((I_x u + I_y v + I_t)^2 \right) + \alpha \Psi \left(|\nabla u|^2 + |\nabla v|^2 \right) dx dy$$

Interpretation: less importance given to pixels with high matching cost \rightarrow mainly occlusions

Nonlinear system can again be solved with fixed point iterations


Result: Better treatment of occlusions




Both terms non-quadratic (5.97°)




Non-quadratic smoothness term (6.36°)



Ground truth



Horn-Schunck (7.17°)



Illumination changes

Typically caused by:

- shadows
- light source flickering
- self-adaptive cameras
- different viewing angles and non-Lambertian surfaces



“Schefflera” from Middlebury benchmark



Two frames from a Miss Marple movie Thomas Brox

Matching the gradient

- Brightness constancy assumption:

$$I(x + u, y + v, t + 1) - I(x, y, t) = 0$$

- Gradient constancy assumption
(Uras et al. 1988, Schnörr 1994, Brox et al. 2004)

$$\nabla I(x + u, y + v, t + 1) - \nabla I(x, y, t) = 0$$

- Two important positive effects:
 1. More information: two more equations
 2. Invariant to additive brightness changes
- Negative effects:
 1. Not rotation invariant
 2. More sensitive to noise

Combination of features

- Linearization:

$$I_{xx}u + I_{xy}v + I_{xt} = 0$$


$$I_{xy}u + I_{yy}v + I_{yt} = 0$$

- Combine with gray value constancy assumption:

$$\begin{aligned} E(u, v) = & \int_{\Omega} \psi \left((I_x u + I_y v + I_t)^2 \right) dx dy \\ & + \gamma \int_{\Omega} \psi \left((I_{xx}u + I_{xy}v + I_{xt})^2 + (I_{xy}u + I_{yy}v + I_{yt})^2 \right) dx dy \\ & + \alpha E_{\text{Smooth}} \end{aligned}$$

- Separate robust penalizer ψ for each feature (Bruhn-Weickert 2005)


Result: Illumination changes no longer a problem




Gradient constancy (3.5°)



Both terms non-quadratic (5.97°)





Ground truth




Horn-Schunck (7.17°)



Large displacements



Horn&Schunck



Brox et al. 2004

Linearization and large displacements

- Constancy assumptions have been linearized

$$I(x+u, y+v, t+1) - I(x, y, t) = 0 \quad \rightarrow \quad I_x u + I_y v + I_t = 0$$

- Assumes that the image is a linear gradient
- Locally (between two pixels), this is true
→ Linearization only valid for very small displacements (subpixel displacements)
- If images are quite smooth, approximation is good enough for larger displacements
- But typical images are not smooth at all



Non-linearized constancy assumption




- Energy functional:

$$E(u, v) = \int_{\Omega} \Psi \left((I(\mathbf{x} + \mathbf{w}) - I(\mathbf{x}))^2 \right) + \alpha \Psi \left(|\nabla u|^2 + |\nabla v|^2 \right) d\mathbf{x}$$


$$\mathbf{x} := (x, y, t) \quad \mathbf{w} := (u, v, 1)$$

- Correct description of the matching criterion (no approximation)
- Problem:
 - Not convex in \mathbf{w} \rightarrow multiple local minima
- One can work with the non-linearized assumptions and iteratively estimate an increment using the Gauss-Newton method
- Computing the increment requires computation of warped images


Result: higher accuracy, large displacements possible

Non-linearized constancy (2.44°)Gradient constancy (3.5°)

Ground truth

Horn-Schunck (7.17°)

Other results: zoom into a scene



Car in a movie



from "Miss Marple: A Pocket Full of Rye"




SIFT flow (Liu et al. 2008)

- Label transfer from training to test data



Training
image



Training
annotation




Test image




Warped
annotation

- Requires flow from test image to training image
- Only feasible if the two images are sufficiently similar
- Search most similar training image in a database using global image descriptors




SIFT flow

- Compute SIFT descriptors densely in both images
- Apply combinatorial method (Shekhovtsov et al. Efficient MRF Deformation Model for Non-Rigid Image Matching. CVIU 2008) to estimate the flow between both images



- Warping the annotation of the training image yields the transferred annotation of the test image



More results



Image 1



Image 2



SIFT flow



Warping



Image 1



Image 2



SIFT flow



Warping



Image 1



Image 2



SIFT flow



Warping

Incorporating correspondences from descriptor matching

$$\begin{aligned}
 E(\mathbf{w}(\mathbf{x})) = & \int \Psi \left(|I_2(\mathbf{x} + \mathbf{w}(\mathbf{x})) - I_1(\mathbf{x})|^2 \right) d\mathbf{x} \\
 & + \gamma \int \Psi \left(|\nabla I_2(\mathbf{x} + \mathbf{w}(\mathbf{x})) - \nabla I_1(\mathbf{x})|^2 \right) d\mathbf{x} \\
 & + \alpha \int \Psi \left(|\nabla u(\mathbf{x})|^2 + |\nabla v(\mathbf{x})|^2 \right) d\mathbf{x}
 \end{aligned}$$

point correspondences from HOG descriptors

$$+ \beta \int \rho(\mathbf{x}) \Psi \left((u(\mathbf{x}) - u'(\mathbf{x}))^2 + (v(\mathbf{x}) - v'(\mathbf{x}))^2 \right) d\mathbf{x}$$






Matching
score

Robust
function

Flow = correspondence vector

[T. Brox and J. Malik. **Large displacement optical flow: descriptor matching in variational motion estimation**. PAMI 2011]

Comparison to SIFT flow



Input images
(overlaid)

Classical coarse-to-
fine method


LDOF

SIFT flow

How do we find object regions?

Video analysis/motion segmentation

- Motion cues can be very clear when objects move
- Several indications in biological vision (studies with infants and healed blind people)



Motion segmentation

- Goal: separate regions by their motion
- Typical chicken-egg problem:
 - A motion field is necessary for estimating the partitioning
 - A partitioning helps estimate the motion field
- Standard approach (layered motion: Wang-Adelson 1994):
 1. First compute optical flow
 2. Then compute segmentation based on the optical flow


Example



Input sequence



Estimated flow field



Flow segmentation

Simultaneous flow estimation and segmentation

- So far: two-step approach
 - Decide on the optic flow
 - Use result for segmentation
- Problem: wrong decisions in the first step cannot be corrected → optical flow estimation cannot benefit from segmentation
- Solution: state joint problem in one energy functional
- Optimize in both variables simultaneously


Motion competition

- Joint energy functional (Cremers-Soatto 2005):


$$E(u_i, v_i, C) = \sum_{i=1}^N \int_{\Omega_i} (I_x u_i + I_y v_i + I_z)^2 \mathrm{d}\mathbf{x} + \nu |C|$$

- Remarks:
 - Partitioning of the image domain into N disjoint regions
 - Simple parametric (constant) motion field in each region Ω_i
 - Length constraint prefers smooth contours
- Alternating optimization:
 - Estimate motion field in the initial regions
(Lucas-Kanade method restricted to the region's domain)
 - Evolve the contour according to the motion field (e.g. with level sets)
 - Iterate
- Segmentation and motion estimation are coupled and benefit from each other

Two easy examples



Segmentation



Optical flow




Segmentation




Optical flow


Accurate motion fields



With segmentation (1.22°)




Without segmentation (1.78°)



Correct flow field



Motion segmentation based on point trajectories

- Two-frame optical flow can only separate objects with different motion in these two particular frames
- Idea: make use of the temporal context
→ point trajectories over multiple frames
- Trajectories obtained via point tracking
- Clustering based on this information can separate objects even at times where they do not move



Trajectories obtained with tracker from Sundaram et al. 2010

Clustering of point trajectories



[P. Ochs. **Segmentation of moving objects by long term video analysis**. PAMI 2014]


Thomas Brox

Recall: Spectral clustering

1. Compute Laplacian eigenmap

$$V^T \Lambda V = D^{-1/2} (D - W) D^{-1/2}$$


2. Consider all eigenvectors with eigenvalue $\lambda < 0.04$



...

3. Run multi-region segmentation on eigenvectors

Results on movie shots



The logo of the University of Bonn, featuring a blue square with a white curved line and a grey square.

UNIVERSITÄT **BONN**