

Package ‘gmethods’

January 29, 2021

Type Package

Title An implementation of g-methods

Version 0.1.0

Date 2020-11-26

Depends R (>= 4.0.2)

Description This package facilitates causal inference by implementing g-methods: g-formula, inverse probability weighting (IPW), and g-estimation. These methods are comprehensively described in Causal Inference: What If book by Hernán and Robins using 1 of 4 NHEFS datasets described in this book (<https://www.hsph.harvard.edu/miguel-hernan/causal-inference-book/>). This package only provides nhefs table, a cleaned version of NHEFS data, for example data. The remaining datasets from that book could be retrieved from cidata R package (<https://github.com/malcolmbaret/cidata>) for more information.

License GPL-3

Encoding UTF-8

LazyData true

Roxygen list(markdown = TRUE)

RoxygenNote 7.1.1

Imports tidyverse,
pbapply,
geepack

Suggests BiocStyle,
knitr,
rmarkdown,
kableExtra,
testthat

URL <https://github.com/herdiantrisufriyana/gmethods>

BugReports <https://github.com/herdiantrisufriyana/gmethods/issues>

VignetteBuilder knitr

R topics documented:

gestimation	2
gformula	3
input_example	3
ipw	4
Index	5

gestimation	<i>Causal inference by g-estimation</i>
-------------	---

Description

This function conduct causal inference by implementing g-estimation. Please read (<https://www.hsph.harvard.edu/miguel-hernan/causal-inference-book/>) before applying this test.

Usage

```
gestimation(formula, data, bootstrap = 30, state = 33, verbose = F)
```

Arguments

formula	An object of class "formula": a symbolic description of the model to be fitted.
data	A data frame containing the variables in the model.
bootstrap	An integer determining how many times this procedure being repeated by re-sampling with replacement.
state	An integer to set random seed for reproducible results.
verbose	A logical determining whether a progress bar is shown.

Value

output A list containing the formula, exposure of interest, marginal effect, 95% confidence interval (CI), significance by p-value obtained from the CI (<https://doi.org/10.1136/bmj.d2304>), data, bootstrapping times, random seed, and index for each bootstrap set.

Examples

```
# Load example data for formula and data
input=input_example()
formula=input$formula
data=input$data

# Conduct g-formula
gestimation(formula,data)
```

gformula	<i>Causal inference by g-formula</i>
----------	--------------------------------------

Description

This function conduct causal inference by implementing g-formula. Please read (<https://www.hsph.harvard.edu/miguel-hernan/causal-inference-book/>) before applying this test.

Usage

```
gformula(formula, data, bootstrap = 30, state = 33, verbose = F)
```

Arguments

formula	An object of class "formula": a symbolic description of the model to be fitted.
data	A data frame containing the variables in the model.
bootstrap	An integer determining how many times this procedure being repeated by re-sampling with replacement.
state	An integer to set random seed for reproducible results.
verbose	A logical determining whether a progress bar is shown.

Value

output A list containing the formula, exposure of interest, marginal effect, 95% confidence interval (CI), significance by p-value obtained from the CI (<https://doi.org/10.1136/bmj.d2304>), data, bootstrapping times, random seed, and index for each bootstrap set.

Examples

```
# Load example data for formula and data
input=input_example()
formula=input$formula
data=input$data

# Conduct g-formula
gformula(formula,data)
```

input_example	<i>Make an input example for gmethods package</i>
---------------	---

Description

This function load a causal model as formula object and a data frame of nhefs table, a cleaned version of NHEFS data. In Causal Inference: What If book by Hernán and Robins, four NHEFS datasets are described in this book (<https://www.hsph.harvard.edu/miguel-hernan/causal-inference-book/>). The remaining datasets from that book could be retrieve from cidata R package (<https://github.com/malcolmbarrett/cidata>) for more information.

Usage

```
input_example()
```

Value

output A list of a formula and a data frame with dimension of 1629 rows and 10 columns.

Examples

```
# Load example data for formula and data
input=input_example()
formula=input$formula
data=input$data
```

ipw

*Causal inference by Inverse Probability Weighting (IPW)***Description**

This function conduct causal inference by implementing inverse probability weighting (IPW). Please read (<https://www.hsph.harvard.edu/miguel-hernan/causal-inference-book/>) before applying this test.

Usage

```
ipw(formula, data, bootstrap = 30, state = 33, verbose = F)
```

Arguments

formula	An object of class "formula": a symbolic description of the model to be fitted.
data	A data frame containing the variables in the model.
bootstrap	An integer determining how many times this procedure being repeated by re-sampling with replacement.
state	An integer to set random seed for reproducible results.
verbose	A logical determining whether a progress bar is shown.

Value

output A list containing the formula, exposure of interest, marginal effect, 95% confidence interval (CI), significance by p-value obtained from the CI (<https://doi.org/10.1136/bmj.d2304>), data, bootstrapping times, random seed, and index for each bootstrap set.

Examples

```
# Load example data for formula and data
input=input_example()
formula=input$formula
data=input$data

# Conduct g-formula
ipw(formula,data)
```

Index

- * **IPW**
 - ipw, [4](#)
- * **data**
 - input_example, [3](#)
- * **example**
 - input_example, [3](#)
- * **g-estimation**
 - gestimation, [2](#)
- * **g-formula**
 - gformula, [3](#)
- * **inverse**
 - ipw, [4](#)
- * **probability**
 - ipw, [4](#)
- * **weighting,**
 - ipw, [4](#)

gestimation, [2](#)
gformula, [3](#)

input_example, [3](#)
ipw, [4](#)