



Getting started with napari

DEEP NAPARI

Herearri METUAREA, Engineer, Université d'Angers, France
David ROUSSEAU, Full professor, Université d'Angers, France

15th November 2023
Room PC4 - Belambra clubs & hôtels, BAS-MADRAGUE





Expert



PRO S2 (Weighted Loss) Unet_segmentation_notebook.ipynb ☆

Fichier Modifier Affichage Insérer Exécution Outils Aide Dernière modification effectuée le 27 juillet

+ Code + Texte

▼ Split train data into train and validation

```
[ ] from sklearn.model_selection import train_test_split
x_train, x_val, y_train, y_val = train_test_split(X_train, Y_train, test_size=0.2, random_state=42) #text_
[ ] print('Train data shape is:',x_train.shape)

print('validation data shape is:',x_val.shape)

Train data shape is: (32, 256, 256, 3)
validation data shape is: (8, 256, 256, 3)

[ ] # Fiting the model
results = model.fit(x_train, y_train,
                     validation_data=(x_val,y_val),
                     batch_size=2, epochs=50,
                     callbacks=[early_stop,Model_check])

Epoch 11/50
16/16 [=====] - ETA: 0s - loss: 5.5026e-04 - dice_coefficient: 0.2432
Epoch 11: val_loss improved from 0.00069 to 0.00065, saving model to /content/gdrive/My Drive/data/best_mo
16/16 [=====] - 1s 44ms/step - loss: 5.5026e-04 - dice_coefficient: 0.2432 - val_
Epoch 12/50
```



Biologist



deepImageJ



NIS-element





Expert



CO PRO S2 (Weighted Loss) Unet_segmentation_notebook.ipynb ☆

Fichier Modifier Affichage Insérer Exécution Outils Aide Dernière modification effectuée le 27 juillet

+ Code + Texte

Split train data into train and validation


```
[ ] from sklearn.model_selection import train_test_split
x_train, x_val, y_train, y_val = train_test_split(X_train, Y_train, test_size=0.2, random_state=42) #text_
[ ] print('Train data shape is:',x_train.shape)

print('validation data shape is:',x_val.shape)

Train data shape is: (32, 256, 256, 3)
validation data shape is: (8, 256, 256, 3)

[ ] # Fiting the model
results = model.fit(x_train, y_train,
                     validation_data=(x_val,y_val),
                     batch_size=2, epochs=50,
                     callbacks=[early_stop,Model_check])

Epoch 11/50
16/16 [=====] - ETA: 0s - loss: 5.5026e-04 - dice_coefficient: 0.2432
Epoch 11: val_loss improved from 0.00069 to 0.00065, saving model to /content/gdrive/My Drive/data/best_mo
16/16 [=====] - 1s 44ms/step - loss: 5.5026e-04 - dice_coefficient: 0.2432 - val_
```



interface that
satisfies
everyone



Biologist





Expert



PRO Fichier Modifier Affichage Insérer Exécution Outils Aide Dernière modification effectuée le 27 juillet

+ Code + Texte

▼ Split train data into train and validation

```
[ ] from sklearn.model_selection import train_test_split
x_train, x_val, y_train, y_val = train_test_split(X_train, Y_train, test_size=0.2, random_state=42) #text_
[ ] print('Train data shape is:',x_train.shape)

print('validation data shape is:',x_val.shape)

Train data shape is: (32, 256, 256, 3)
validation data shape is: (8, 256, 256, 3)

[ ] # Fiting the model
results = model.fit(x_train, y_train,
                     validation_data=(x_val,y_val),
                     batch_size=2, epochs=50,
                     callbacks=[early_stop,Model_check])

Epoch 11/50
16/16 [=====] - ETA: 0s - loss: 5.5026e-04 - dice_coefficient: 0.2432
Epoch 11: val_loss improved from 0.00069 to 0.00065, saving model to /content/gdrive/My Drive/data/best_mo
16/16 [=====] - 1s 44ms/step - loss: 5.5026e-04 - dice_coefficient: 0.2432 - val_
Epoch 12/50
```



napari



Biologist




NIS-element





napari





Help scientist to access Python's scientific ecosystem, with no prior coding experience

Multi-dimensional data viewer in Python
open-source, community-developed

Napari

Process large data and run Deep Learning (DL) model




Deep learning in Napari


Apple flower detection




Plugin: napari-blossom



Apple detection in orchard




Plugin: napari-apple




Deep learning in Napari

Apple flower detection



Plugin: napari-blossom

Apple detection in orchard



And many more !

Topic of this workshop

Objective

Create a napari plugin from image processing code including DL model

What we will do

Review a DL code

Create a napari plugin in local

Integrate DL model (tensorflow) in plugin


What we will not do

Teach Python programming and the base of deep learning (requirements)

Deploy the plugin in napari-hub platform (napari library plugin)

Practical session

Let's suppose we have



```
In [69]: # INPUT
# Write model ESRF_Seg_Hands_on_best_model.h5 path
model_path_ = "/home/g-laris89/DEEP-NAPARI/Exercise-4_My first widget/model/ESRF_Seg_Hands_on_best_model.h5"
input_ = "/home/g-laris89/DEEP-NAPARI/Exercise-2_Notebook_Code/images/03f583ec5018739f4abb9b3b4a580ac43bd933c4337ad8877aa18l

model_New = tf.keras.models.load_model(model_path_,custom_objects={'dice_coefficient': dice_coefficient})

_, IMG_HEIGHT, IMG_WIDTH, IMG_CHANNELS = list(model_New.input.shape)

img_ = imread(input_)

nbr_image = len(img_.shape)
if nbr_image==3:
    img_ = img_[:, :, :IMG_CHANNELS]
    X = np.zeros((1, IMG_HEIGHT, IMG_WIDTH, IMG_CHANNELS), dtype=np.uint8)
    h_or, w_or, _ = img_.shape
    ORIGIN = np.zeros((1, h_or, w_or, IMG_CHANNELS), dtype=np.uint8)
    ORIGIN[0] = img_
    img = resize(img_, (IMG_HEIGHT, IMG_WIDTH), mode='constant', preserve_range=True)
    X[0] = img
elif nbr_image==4:
    img_ = img_[:, :, :, :IMG_CHANNELS]
    X = np.zeros((img_.shape[0], IMG_HEIGHT, IMG_WIDTH, IMG_CHANNELS), dtype=np.uint8)
    shape_h, shape_w = [], []
    for i in range(img_.shape[0]):
        print(img_[i,...].shape)
        shape_h.append(img_[i,...].shape[0])
        shape_w.append(img_[i,...].shape[1])
        img = resize(img_[i,...], (IMG_HEIGHT, IMG_WIDTH), mode='constant', preserve_range=True)
        X[i] = img

    ORIGIN = np.zeros((img_.shape[0],np.max(shape_h),np.max(shape_w),IMG_CHANNELS), dtype=np.uint8)
    for i in range(img_.shape[0]):
        ORIGIN[i,...][:shape_h[i], :shape_w[i],:] = img_[i,...]

preds_test = model_New.predict(X, verbose=1)
# we apply a threshold on predicted mask (probability mask) to convert it to a binary mask.
preds_test_opt = (preds_test > 0.5).astype(np.uint8)




if nbr_image==3:
    result_ = np.squeeze(preds_test_opt[0, :, :, 0])
    output_ = np.zeros((1,h_or,w_or), dtype=np.uint8)
    res_ = resize(result_, (h_or, w_or), mode='constant', preserve_range=True)
    output_[0] = res_
elif nbr_image==4:
    img_ = img_[:, :, :, :IMG_CHANNELS]
    result_ = np.squeeze(preds_test_opt[:, :, :, 0])
    output_ = np.zeros((img_.shape[0],np.max(shape_h),np.max(shape_w)), dtype=np.uint8)
    for i in range(img_.shape[0]):
        res_ = resize(result_[i], (shape_h[i], shape_w[i]), mode='constant', preserve_range=True)
        output_[i,...][:shape_h[i], :shape_w[i]] = res_
```

1/1 [=====] - 0s 290ms/step




Practical session

Deploy DL model in Napari plugin



Practical session

Go to this page: <https://github.com/hereariim/DEEP-NAPARI>



The screenshot shows the GitHub repository page for "DEEP-NAPARI". The repository is public and has 1 branch and 0 tags. The main branch contains 4 commits from "hereariim" with the commit message "readme update". The commits are dated 9 minutes ago, 20 minutes ago, 10 minutes ago, 20 minutes ago, and 9 minutes ago. The repository has 1 watch, 0 forks, and 0 stars. The README.md file is open, showing the text "DEEP NAPARI : Napari as a tool for phenotyping" and logos for CNRS, Inserm, Institut Fresnel, GDR ONDES, and Imabio.

hereariim / DEEP-NAPARI

Type ⌘ to search

Code Issues Pull requests Actions Projects Wiki Security Insights Settings

DEEP-NAPARI Public

main 1 branch 0 tags Go to file Add file Code

hereariim readme update 4b81128 9 minutes ago 4 commits

- Exercise-1_Getting started import all data 20 minutes ago
- Exercise-2_Getting started plugin import all data 20 minutes ago
- Exercise-3_My first plugin import all data 20 minutes ago
- Exercise-4_My first widget import all data 20 minutes ago
- Exercise-5_Do it yourself import all data 20 minutes ago
- Extra-Deploy_in_builtin import all data 20 minutes ago
- images-credit logo update 10 minutes ago
- Introduction.pdf import all data 20 minutes ago
- README.md readme update 9 minutes ago

About

This is a training tutorial to learn how to integrate deep learning model into napari plugin from scratch

Readme Activity 0 stars 1 watching 0 forks

Releases

No releases published Create a new release

Packages

No packages published Publish your first package

Languages

Jupyter Notebook 90.4% Python 9.6%


Suggested Workflows

Based on your tech stack


Practical Session is done

Please, remove the plugin in your PC

```
pip uninstall napari-mifobio
```




and



To go further in this exercise

Tutorial on the presentation, design of a plugin... and even more



ImHorPhen Bio imaging research group

@imhorphenbioimagingresearch · 365 subscribers · 175 videos

ImHorPhen is a bioimaging, research group, headed by Prof. David Rousseau, located in An... >

www6.angers-nantes.inrae.fr/irhs/Recherche/Imagerie-pour-l-Horticulture-et-le... and 1 more link

[Subscribe](#)

Home Videos Playlists Community

Latest Popular Oldest

Deepaas & Napari hand in hand 23:57
116 views · 1 year ago

Creating and modifying a Napari widget 19:48
32 views · 2 months ago

Getting started with Napari in Phenotyping 12:52
17 views · 2 months ago

NAPARI Plugin for deep segmentation and manual correction 35:42
196 views · 1 year ago

Installer NAPARI et faire son premier plugin 13:14
140 views · 1 year ago

Easy shallow learning with Ilastik 16:06
464 views · 2 years ago

Panorama des solutions "user-friendly" de deep learning en bioimagerie 14:30
38 views · 1 year ago

Installation de Cellpose 42:53
753 views · 1 year ago



Conclusion



What we learnt ?

What we learnt ?

What we learnt ?

What we learnt ?

We learnt a method to use easily your DL model with GUI aka Napari



We learnt a method to use easily your DL model with GUI aka Napari



I hope this method we let you deploy your DL model to help experimental scientist





Thanks ! I will deploy my model for Cell detection

me ! for nucleus detection

me ! for bird detection

me ! for disease detection







Wow, that's a lot of plugins created

me ! for nucleus detection

me ! for bird detection

me ! for disease detection




Imagine, we have a single plugin to read all your DL model.



No need to create a set of plugins and your DL model remains confidential





Does it exist ?



Does it exist ?

Sure !!!!!



napari hub Plugins



Manini MAChiNe INference & correction

manini



MANINI

An user-friendly plugin that enables to annotate images from a pre-trained model (segmentation, classification, detection) given by an user.

[Herearii Metuarea](#)

[View project data](#)

Description Activity NEW!


license BSD-3-Clause pypi v0.0.6 python 3.8 | 3.9 | 3.10 tests passing codecov 9% napari hub manini


Manini (MAChiNe INference & Correction) is thought as a tool to boost the collaborative contribution of end-users to the assessment of deep learning model during their testing phase. It is a user-Friendly plugin that enables to manually correct the result of an inference of deep learning model by an end-user. The plugin covers the following informational tasks: segmentation, classification and object detection.

White paper

Herearii Metuarea, David Rousseau. Toward more collaborative deep learning project management in nplant


</> ⚙️ ⚙️
White paper
Installation
Description
License
Issues





1. Choose the type of Deep learning task

2. Import your data (Image, Model, Class (optional))




3. Run


4. Correct your data



Segmentation




Classification



Detection

To know more about it

Manini presentation



[MANINI Napari Plugin Part 2](#)

Aucune vue • il y a 3 heures

[MANINI Napari Plugin Part 1](#)

3 vues • il y a 1 jour





INRAe

IRHS
Institut de Recherche en
Horticulture et Semences

IMHORPHEN

**université
angers**



Thanks you for your attention