

From Functor Composition to Monad Transformers

© 2018 Hermann Hueck

<https://github.com/hermannhueck/monad-transformers>

Agenda

1. Nested Monads in for comprehensions
2. Functors compose.
3. Aside: Creating `List[Int => Int]` and `List[Option[Int => Int]]`
4. Applicatives compose.
5. Do Monads compose?
6. Monad Transformers - Example `OptionT`
7. Generic Monad Processing
8. Best Practices
9. `OptionT` - implementation
10. Resources

1. Nested Monads in for comprehensions

Imports for Cats

```
import cats._, cats.data._, cats.implicits._  
// import mycats._, transform._, Functor.syntax._, Monad.syntax._
```

Imports for my own implementation of Functor, Applicative, Monad and OptionT

```
// import cats._, cats.data._, cats.implicits._  
import mycats._, transform._, Functor.syntax._, Monad.syntax._
```

The same client code works with Cats and with my implementation.
Only the imports need to be changed.

For comprehension for List[Option[Int]]

```
val loi1: List[Option[Int]] = List(Some(1), None, Some(2), Some(3))
val loi2: List[Option[Int]] = List(Some(1), None, Some(2), Some(3))

val result1: List[Option[Int]] =
  for {
    oi1: Option[Int] <- loi1
    if oi1.isDefined
    oi2: Option[Int] <- loi2
    if oi2.isDefined
  } yield Option(oi1.get * oi2.get)

// result1: List[Option[Int]] = List(Some(1), Some(2),
//   Some(3), Some(2), Some(4), Some(6), Some(3), Some(6), Some(9))
```

Compiler translates for comprehension to flatMap, map and withFilter

```
val result2 =  
  loi1  
    .filter(_.isDefined)  
    .flatMap { oi1 =>  
      loi2  
        .filter(_.isDefined)  
        .map { oi2 =>  
          Option(oi1.get * oi2.get)  
        }  
    }  
  
// result2: List[Option[Int]] = List(Some(1), Some(2),  
//   Some(3), Some(2), Some(4), Some(6), Some(3), Some(6), Some(9))
```

A nested for comprehension

```
val result3: List[Option[Int]] =  
for {  
  oi1: Option[Int] <- loi1  
  oi2: Option[Int] <- loi2  
} yield for {  
  i1: Int <- oi1  
  i2: Int <- oi2  
} yield i1 * i2  
  
// result3: List[Option[Int]] = List(Some(1), None,  
//   Some(2), Some(3), None, None, None, None, Some(2),  
//   None, Some(4), Some(6), Some(3), None, Some(6), Some(9))
```


Wanted:

a for comprehension to process Ints nested in 2 contexts
... something like this one:

```
// This code does not compile!  
val result4: List[Option[Int]] =  
for {  
  i1: Int <- loi1  
  i2: Int <- loi2  
} yield i1 * i2
```

2. Functors compose.

Mapping a List[Int] with a Functor[List]

```
val li = List(1, 2, 3)

val lSquared1 = li.map(x => x * x) // invokes List.map
// lSquared1: List[Int] = List(1, 4, 9)

val lSquared2 = li.fmap(x => x * x) // invokes Functor[List].fmap
// lSquared2: List[Int] = List(1, 4, 9)

val lSquared3 = Functor[List].map(li)(x => x * x) // invokes Functor[List].map
// lSquared3: List[Int] = List(1, 4, 9)
```

Mapping a List[Option[Int]] with Functor[List] and Functor[Option]

```
val loi = List(Some(1), None, Some(2), Some(3))

val loSquared1 = loi.map(oi => oi.map(x => x * x))
// loSquared1: List[Option[Int]] = List(Some(1), None, Some(4), Some(9))

val loSquared2 = Functor[List].map(loi)(oi => Functor[Option].map(oi)(x => x * x))
// loSquared2: List[Option[Int]] = List(Some(1), None, Some(4), Some(9))

val loSquared3 = (Functor[List] compose Functor[Option]).map(loi)(x => x * x)
// loSquared3: List[Option[Int]] = List(Some(1), None, Some(4), Some(9))

val cf = Functor[List] compose Functor[Option]
val loSquared4 = cf.map(loi)(x => x * x)
// loSquared4: List[Option[Int]] = List(Some(1), None, Some(4), Some(9))
```

Pimping List[Option[A]]

```
implicit class PimpedListOptionA[A](list: List[Option[A]]) {  
  // functor type: Functor[Lambda[X => List[Option[X]]]]  
  val functor = Functor[List] compose Functor[Option]  
  def map[B](f: A => B): List[Option[B]] = functor.map(list)(f)  
  def fmap[B](f: A => B): List[Option[B]] = functor.map(list)(f)  
}  
  
val loSquared5 = loi.fmap(x => x * x)  
// loSquared5: List[Option[Int]] = List(Some(1), None, Some(4), Some(9))
```

3. Aside:

Creating `List[Int => Int]`

and `List[Option[Int => Int]]`

Creating a List[Int => Int]

```
val lf1_1 = List((x:Int) => x * 1, (x:Int) => x * 2, (x:Int) => x * 3)
// lf1_1: List[Int => Int] = List($$Lambda$..., $$Lambda$..., $$Lambda$...)

val lf1_2 = List((_:Int) * 1, (_:Int) * 2, (_:Int) * 3)
// lf1_2: List[Int => Int] = List($$Lambda$..., $$Lambda$..., $$Lambda$...)
```

Creating a List[Int => Int] from List[Int]

```
val lf1_3 = List(1, 2, 3).map(x => (y:Int) => y * x)
// lf1_3: List[Int => Int] = List($$Lambda$..., $$Lambda$..., $$Lambda$...)

val lf1_4 = List(1, 2, 3).map(x => (_:Int) * x)
// lf1_4: List[Int => Int] = List($$Lambda$..., $$Lambda$..., $$Lambda$...)
```


Creating a List[Option[Int => Int]]

```
val lf1 = lf1_4
// lf1: List[Int => Int] = List($$Lambda$..., $$Lambda$..., $$Lambda$...)

val lof1 = lf1 map Option.apply
// lof1: List[Option[Int => Int]] = List(Some($$Lambda$...), Some($$Lambda$...), S
```

4. Applicatives compose.

Applying a List[Int => Int] to a List[Int] with Applicative

```
val liResult = Applicative[List].ap(lf1)(li)  
// liResult: List[Int] = List(1, 2, 3, 2, 4, 6, 3, 6, 9)
```

Applying a `List[Option[Int => Int]]` to a `List[Option[Int]]` with `Applicative`

```
val loiResult = (Applicative[List] compose Applicative[Option]).ap(loi1)(loi)  
// loiResult: List[Option[Int]] = List(Some(1), None, Some(2), Some(3),  
//   Some(2), None, Some(4), Some(6), Some(3), None, Some(6), Some(9))
```

5. Do Monads compose?

Do Monads compose?

```
val ca = Applicative[List] compose Applicative[Option]
// ca: cats.Applicative[[a]List[Option[a]]] = cats.Alternative$$anon$1@69102316
val cm = Monad[List] compose Monad[Option]
// cm: cats.Applicative[[a]List[Option[a]]] = cats.Alternative$$anon$1@48b5e9dd
```

Do Monads compose?

- Functors compose.
- Applicatives compose.
- Monads do NOT compose!

The solution: Monad Transformers

6. Monad Transformers - Example OptionT

What is OptionT?

- OptionT is a generic case class which encapsulates an F[Option[A]].
- F is the generic type constructor of another monad like List, Future, Either, Id.
- A Monad instance for OptionT (implementing pure and flatMap) must be provided in implicit scope in order to allow flatMapping over OptionT.

```
final case class OptionT[F[_], A](value: F[Option[A]]) {  
  // ...  
}  
  
object OptionT {  
  implicit def monad[F[_]](implicit F: Monad[F]): Monad[OptionT[F, ?]] =  
    new Monad[OptionT[F, ?]] {  
      override def pure[A](a: A): OptionT[F, A] = ???  
      override def flatMap[A, B](fa: OptionT[F, A])  
        (f: A => OptionT[F, B]): OptionT[F, B] = ???  
    }  
}
```

Creating an `OptionT[List, Int]` to encapsulate a `List[Option[Int]]`

```
val loi = List(Some(1), None, Some(2), Some(3))  
// loi: List[Option[Int]] = List(Some(1), None, Some(2), Some(3))  
  
val otli = OptionT[List, Int](loi)  
// otli: cats.data.OptionT[List,Int] = OptionT(List(Some(1), None, Some(2), Some(3)))  
  
otli.value // same as: loi  
// res6: List[Option[Int]] = List(Some(1), None, Some(2), Some(3))
```

FlatMapping an OptionT[List, Int]

flatMap takes a function of type: $A \Rightarrow \text{OptionT}[F, B]$
In our case the type is: $\text{Int} \Rightarrow \text{OptionT}[\text{List}, \text{String}]$

```
def fillListWith(x: Int): List[Option[String]] = List.fill(x)(Option(x.toString))

val otliFlatMapped = otli.flatMap(x => OptionT[List, String](fillListWith(x)))
// otliFlatMapped: cats.data.OptionT[List,String] =
//   OptionT(List(Some(1), None, Some(2), Some(2), Some(3), Some(3), Some(3)))

otliFlatMapped.value
// res7: List[Option[String]] =
//   List(Some(1), None, Some(2), Some(2), Some(3), Some(3), Some(3))
```

Convenience function flatMapF

flatMapF takes a function of type: $A \Rightarrow F[Option[B]]$
In our case the type is: $Int \Rightarrow List[Option[String]]$

```
val otliFlatMappedF = otli.flatMapF(x => fillListWith(x))
// otliFlatMappedF: cats.data.OptionT[List,String] =
//   OptionT(List(Some(1), None, Some(2), Some(2), Some(3), Some(3), Some(3)))

otliFlatMappedF.value
// res8: List[Option[String]] =
//   List(Some(1), None, Some(2), Some(2), Some(3), Some(3), Some(3))
```

Mapping an OptionT[List, Int]

```
val otliMapped = Monad[OptionT[List, ?]].map(otli) { _.toString + "!" }  
// otliMapped: cats.data.OptionT[+[A]List[A],String] =  
//   OptionT(List(Some(1!), None, Some(2!), Some(3!)))  
  
otliMapped.value  
// res9: List[Option[String]] = List(Some(1!), None, Some(2!), Some(3!))
```

OptionT.{isDefined isEmpty getOrElse}

```
otli.isDefined  
// res10: List[Boolean] = List(true, false, true, true)  
  
otli.isEmpty  
// res11: List[Boolean] = List(false, true, false, false)  
  
otli.getOrElse(42)  
// res12: List[Int] = List(1, 42, 2, 3)
```

For comprehension with `OptionT[List, Int]` encapsulating `List[Option[Int]]`

```
val result4: OptionT[List, Int] = for {  
  x <- otli  
  y <- otli  
} yield x * y  
// result4: cats.data.OptionT[List,Int] =  
//   OptionT(List(Some(1), None, Some(2), Some(3), None, Some(2),  
//               None, Some(4), Some(6), Some(3), None, Some(6), Some(9)))  
  
result4.value  
// res13: List[Option[Int]] =  
//   List(Some(1), None, Some(2), Some(3), None, Some(2),  
//        None, Some(4), Some(6), Some(3), None, Some(6), Some(9))
```

7. Generic Monad Processing

Using processIntMonads with OptionT

OptionT encapsulates 2 monads, but it is itself also a monad.

Hence it can be passed to a function accepting any Monad F[Int].

```
def processIntMonads[F[_]: Monad](monad1: F[Int], monad2: F[Int]): F[Int] =  
  for {  
    x <- monad1  
    y <- monad2  
  } yield x * y  
  
val result5 = processIntMonads(otli, otli)  
// result5: cats.data.OptionT[List,Int] = OptionT(List(Some(1), None, Some(2),  
//      Some(3), None, Some(2), None, Some(4), Some(6), Some(3), None, Some(6), Some(  
  
result5.value  
// res14: List[Option[Int]] = List(Some(1), None, Some(2),  
//      Some(3), None, Some(2), None, Some(4), Some(6), Some(3), None, Some(6), Some(
```

Using processIntMonads with other Monads

- List
- Vector
- Option
- Future

```
processIntMonads(List(1, 2, 3), List(10, 20, 30))  
// res16: List[Int] = List(10, 20, 30, 20, 40, 60, 30, 60, 90)  
  
processIntMonads(Vector(1, 2, 3), Vector(10, 20, 30))  
// res17: scala.collection.immutable.Vector[Int] = Vector(10, 20, 30, 20, 40, 60,  
  
processIntMonads(Option(5), Option(5))  
// res18: Option[Int] = Some(25)  
  
val fi = processIntMonads(Future(5), Future(5))  
// fi: scala.concurrent.Future[Int] = Future(<not completed>)  
Await.ready(fi, 1.second)  
fi  
// res20: scala.concurrent.Future[Int] = Future(Success(25))
```

Using processIntMonads with other OptionT-Monads

- OptionT[Vector, Int]
- OptionT[Option, Int]
- OptionT[Future, Int]

```
val otvi = OptionT[Vector, Int](Vector(Option(3), Option(5)))
processIntMonads(otvi, otvi).value
// res21: Vector[Option[Int]] = Vector(Some(9), Some(15), Some(15), Some(25))

val otoi = OptionT[Option, Int](Option(Option(5)))
processIntMonads(otoi, otoi).value
// res22: Option[Option[Int]] = Some(Some(25))

val otfi = processIntMonads(OptionT(Future(Option(5))), OptionT(Future(Option(5))))
Await.ready(otfi.value, 1.second)
otfi.value
// res23: scala.concurrent.Future[Option[Int]] = Future(Success(Some(25)))
```

8. Best Practices

Don't stack too many transformers!

- A monad transformer is just another monad (wrapping 2 monads).
- You can wrap the transformer into another transformer (2 Transformers = 3 monads)
- This procedure creates a transformer stack.
- Too many stacked transformers do not make your code more understandable.
- Too many stacked transformers can degrade performance.

Don't expose monad transformers to your API!

- This would make your API harder to understand.
- The user of your API may not know what a monad transformer is.
- Just call `transformer.value` before you expose it.
- Thus you expose `List[Option[A]]` instead of `OptionT[List, A]`.

9. OptionT - implementation

```

import mycats.{Functor, Monad}

final case class OptionT[F[_], A](value: F[Option[A]]) {

  def map[B](f: A => B)(implicit F: Functor[F]): OptionT[F, B] =
    OptionT(F.map(value)(_ map f))

  def flatMap[B](f: A => OptionT[F, B])(implicit F: Monad[F]): OptionT[F, B] =
    OptionT(
      F.flatMap(value)(optA =>
        optA.map(a => f(a).value)
        .getOrElse(F.pure(Option.empty[B]))
      )
    )

  def flatMapF[B](f: A => F[Option[B]])(implicit F: Monad[F]): OptionT[F, B] =
    flatMap(f andThen OptionT.apply)

  def isDefined(implicit F: Functor[F]): F[Boolean] = F.map(value)(_.isDefined)
  def isEmpty(implicit F: Functor[F]): F[Boolean] = F.map(value)(_.isEmpty)
  def getOrElse(default: => A)(implicit F: Functor[F]): F[A] = F.map(value)(_.getOrElse(default))
}

object OptionT {

  implicit def functor[F[_] : Functor]: Functor[OptionT[F, ?]] = new Functor[OptionT[F, ?]] {
    override def map[A, B](fa: OptionT[F, A])(f: A => B): OptionT[F, B] = fa map f
  }

  implicit def monad[F[_]](implicit F: Monad[F]): Monad[OptionT[F, ?]] = new Monad[OptionT[F, ?]] {
    override def pure[A](a: A): OptionT[F, A] = OptionT(F.pure(Option(a)))
    override def flatMap[A, B](fa: OptionT[F, A])(f: A => OptionT[F, B]): OptionT[F, B] =
      fa flatMap f
  }
}

```


10. Resources

- Code and Slides of this Talk: <https://github.com/hermannhueck/monad-transformers>
- "Monad transformers down to earth" - Talk by Gabriele Petronella at Scala Days Copenhagen 2017 <https://www.youtube.com/watch?v=jd5e71nFEZM>
- "FSiS Part 7 - OptionT transformer" - Live coding video tutorial by Michael Pilquist, 2015 <https://www.youtube.com/watch?v=ZNUTMabdgzo>

Thanks for Listening

Q & A

