

# Pro Builders Express, Inc

1840 W Whittier Blvd, La Habra, CA 90631

Phone: 866-360-1526 Fax 310-456-8302

Phone: 562-921-5001

**Date:** 2-August-2017

**Page:** 1 of 2



**Customer:** Maria Salas  
1629 Second  
Street  
Duarte, CA

**Quote:** 72  
**Date:** 2-August-2017  
**By:** Gary Banks  
**Desc:** Room Addition

## Scope of Work

Project Specification Project Specification Project Specification Project  
SpecificationProject SpecificationProject SpecificationProject SpecificationProject  
SpecificationProject SpecificationProject SpecificationProject Specification

#	Specifications	Qty
---	----------------	-----

### Demolition

Demolition of Non-Reinforced Concrete Slab Up to 4" Thick and Dumping of Debris	0 sqft
---	--------

Demolition of Drywall From Wood or Metal Framed Walls and Dumping of Debris	0 sqft
---	--------

Supply Labor For Demolition of Stucco And Lath From Exterior Walls and Dumping of Debris	0 sqft
--	--------

Demolition of Existing Wood Gramed Wall Assembly, Removal of Existing Electrical Romex Wire, Stud Walls, Sill Plate Cut All Foundation Bolts As Necessay Demolition of existing kitchen ceiling	0 sqft
---	--------

Customers Initials

Date

# Pro Builders Express, Inc

1840 W Whittier Blvd, La Habra, CA 90631

Phone: 866-360-1526 Fax 310-456-8302

Phone: 562-921-5001

Date: 2-August-2017

Page: 2 of 2

---

## Foundation/Footings

Excavate and Finish a 24" x 12" Reinforced Concrete Footing With Reinforcing Steel Tied and Finished at Grade "Contractor Not Responsible For Removal of Excavated Dirt from Job Site." Includes upgrade 12" footing to 24" footing. Footing With Reinforcing Steel Tied and Finished at Grade. "Contractor Not Responsible For Removal of Excavated Dirt from Job Site."	0 ft
---	------

---

Supply Labor and Equipment For A Concrete Pump To Remote Location for Pumping Of Concrete as Required	0 pump
---	--------

---

Pour A 3" 2500 PSI Reinforced Concrete Slab on Grade With Typical Excavation, Slab Base, and Forms. "Contractor Cannot Be Responsible for Minor Cracks in Concrete During the Curing Process" "Contractor Not Responsible For Removal of Excavated Dirt from Job Site."	0 sqft
---	--------

---

Pour A 5 1/2" 2500 PSI Reinforced Concrete Slab on Grade With Typical Excavation, Slab Base, Wire Mesh, Forms, and Vapor Barrier. "Contractor Cannot Be Responsible for Minor Cracks in Concrete During the Curing Process" "Contractor Not Responsible For Removal of Excavated Dirt from Job Site."	0 sqft
---	--------

---

This is a quotation based on Customer Specifications and by itself is not a contract to do work. Pro-Builders Express cannot be responsible for changes in Work or Price due to County, State, or Federal Building Requirements that were not Specified nor Based on Approved Plans.

---

Grand Total With Tax: \$0

\_\_\_\_\_  
Customer Signature

\_\_\_\_\_  
Date

\_\_\_\_\_  
Pro-Builders Express Signature

\_\_\_\_\_  
Date

MUST BE SIGNED AND DATED ALONG WITH CONTRACT TO BECOME VALID.

\_\_\_\_\_  
Customers Initials

\_\_\_\_\_  
Date