

Key Value Offset

File path: Assets/UIAnimationToolkit/Editor/Animation/Anim_KeyValueOffset.cs

Menu: Tools > UI Animation Toolkit > Animation > Key Value Offset

Overview

Shift selected numeric keyframe values so a chosen anchor key matches the scene’s current property value. All selected keys on the same property receive the same value delta; their times remain unchanged. Useful when adapting an existing motion to a new resting position, scale or other starting/ending value.

How to use

1. Open the target clip on the appropriate animated scene root. Set the intended scene property value outside animation preview.
2. Select the actual keys to change in the Animation window. Selecting a property row alone is not sufficient.
3. Open Key Value Offset and choose First Key or Last Key as the anchor for each selected property.
4. Check Clip, Root and selected-key count. Click Apply Key Value Offset.
5. Review the result and use Undo if needed. The tool temporarily stops animation preview to read scene values, then attempts to restore preview if it was active.

Interface and parameters

Key Value Offset

ANCHOR

First Key | Last Key

Clip

Panel_Open.anim

Root

PanelRoot

Selection

3 selected keyframes ready

Apply Key Value Offset

Interface schematic based on current source; example object and clip names.

Control / parameter	Description
First Key	Use the earliest selected key on each property as its value anchor.
Last Key	Use the latest selected key on each property as its value anchor.

Control / parameter	Description
Clip / Root	Automatically detected animation context.
Selected-key count	The action requires a clip, scene root and selected keys.
Apply Key Value Offset	Compute $\text{delta} = \text{scene value} - \text{anchor value}$, then add that delta to selected values on each binding.

Example

Selected values are 10, 30 and 50. The scene value is 100. With First Key, delta is 90 and the values become 100, 120 and 140. With Last Key, delta is 50 and they become 60, 80 and 100. Key times do not move.

Notes

- Unselected keys retain their stored values; interpolation near the edges of the selected region can still change visually.
- Object-reference curves are skipped, as are missing paths and unsupported/unreadable properties. Read the final status for processed and skipped counts.
- Euler channels use the closest equivalent angle to reduce unintended full-turn offsets.
- The clip is marked dirty and Undo is recorded. Save the modified asset when satisfied. This tool is different from Frame Offset, which changes key times.