

Problem 1 Warm-up [15 Points]

Please answer the following questions using the knowledge you learned from CS 35L.

- (1) Suppose you want to create a directory and necessary parent directories. You don't know the exact command and that command may take a number of options. Try to explain how will you search for the command and the proper options. [5 Points]

- (2) Write a regular expression to match all the valid function definitions that take a single argument in a python script. [5 Points]
The python function is defined as:
`def <identifier>(<identifier>):`
A valid identifier in python is starting from alphabetical characters or underscore and follows alphabetical characters or digits or underscore. To make things simple, we assume that there are no white spaces before and after each token except the one after "def" and there are no comments in the code.

- (3) You and Bob are colleagues and you need to send some secret documents. You want to send Bob a file with signature but also encrypted using public key encryptions. In this process, which key would you use to encrypt a message, which key would Bob use to decrypt a message, which key would you use to create the signature and which key would Bob use to verify it? [5 Points]

- (3) Suppose you have found out that the bug is in "foo.c" and fixed it. You want to have a "code review" by sending your team an email enclosed your change in the code. What command will you use to generate the content of email?
Suppose your teammates have acknowledged your change and you want to get your fix into your repository. Explain what Git commands will you use to check in your code and how other members sync up with your change. (Suppose you already have a remote repository set up.) [6 Points]

Problem 3 Data Analysis using Shell Scripts [20 Points]

You work for a sports consulting company who provides statistic analysis for NBA players. Despite that you have many advanced data mining tools, many tasks can be done simply using shell commands. Try to design and implement your script to satisfy the following customers' demands.

Your data is a tab-separated file formatted as following:
Position College Height Weight Points-per-game Minutes-per-game Draft-Year Player-Name
For example, the record of Vince Carter and Alan Iverson looks like the following:
<Guard>/<Forward> UNC 6-6 215 22.2 36.4 1998 Vince Carter
<Guard> GeorgeTown 6-0 165 26.7 41.1 1996 Alan Iverson
The file is **nba.txt**. (Hint: Using the text processing tools we introduced in class such as `grep`, `sed`, `tr` etc. You can either write a command or a script containing multiple commands)

- (1) One high school basketball star get offer from many different schools. He wants to know which school is better in terms of number of their graduations playing in NBA. Explain how would you use simple Linux command to compare two schools. Your script takes two arguments that are school names, and exists with status 0 if the first school has more NBA players and 1 otherwise.
e.g. `./compare.sh UCLA USC` should exit with code 0 since UCLA is better than USC. © [6 points] (There is more space to write on next page)

Problem 2 Programming in Collaborative Environment (20 Points)

You and your friends teamed up to do a course project. You want to utilize the open source tools you have learnt in CS 35L to manage the collaboration. Consider the following scenarios and briefly mention which tool will you choose, commands to complete the specific task and the reasoning of your choice (e.g. What will the tool do? What's the effect of your command?)

- (1) As the team leader, you have written up three documentations for the project. "**Contact.txt**" records the contact information of your team members, which should be filled in by your teammates and be readable for everyone in the class. "**README**" defines some instructions to your teammates, and you don't expect any one except you to change it. "**MeetingNotes.txt**" consists notes of internal group meetings, which should be accessible to the team members only.

Assume all of your files are updated to a Linux server, where each student has a Linux user account and belongs to a user group representing the team. Explain how to use Linux commands to manage the access permissions of above files. (Your project folder is at `/projects/team-1/` and you are the owner of the folder. You can change the permission settings of the folder and any files under it). [7 Points]

- (2) Your team use Git to manage the code. After the latest sync, you find out that your program has some bugs and failed in a test case. You remember that the program works well last week, so there is something wrong with latest updates. Explain how to find the bug in the code using Git commands and other necessary tools. [7 Points]

- (2) One NBA team manager is looking for a player who can play two or more positions (e.g. <Guard>/<Forward>, <Center>/<Forward>). We assume that all the positions are valid in the record. We won't have incorrect positions or duplicate positions in one record) Explain how to find them out? [7 points]

- (3) A news reporter wants to write a story about best scorers drafted in year 2003. Explain how to generate a sorted list of those players (the output should contain the points-per-game, minutes-per-game, draft year and the name of the player. Output is sorted by points-per-game in descending order). [7 points] (There is more space to write on next page)

Problem 4 One Day of System Administrators [45 Points]

Suppose you are working for the student union to manage their web server. The manager assigned you some jobs to be done. Use tools learned from CS 35L to complete the following tasks:

- (1) In the Christmas party held by the students union, there is a lottery session. Instead of using lottery tickets, you want to implement a program to randomly pick up a winner from the registered email address. Implement a **python script** lottery.py to do so. The script should take an argument which is a text file containing email addresses of all the registered guests, if no argument is given, it will try to read from "guest-emails.txt". Each line is an email address following a tab and the guest name. (e.g. johnsmith@ucla.edu John Smith).

The program will output a congratulation message:

```
$ ./lottery.py guest-emails
```

```
"Congratulation, John Smith! You won the lottery! Our secret gift has been sent to your email: johnsmith@ucla.edu"
```

Part of the code is given. Please fill in the #TODO part of the code (See next page). If you want to change the given code, please comment out the original code by prefixing a "#" and writing your code right below it.

If you cannot figure out writing the program, try to briefly explain your idea. [15 Points]

Quick python refs:

Suppose s is a string, s = "abc\n"

s.find(a) returns the index of the first occurrence of substring a in s
e.g. s.find("b") # returns 1

s.strip() remove the preceding and trailing space characters
e.g. s.strip() # returns "abc"

- (2) Some students reported that their personal info in the student union website was stolen. It is suggested that there may be some security hole in your code. You are asked to examine the existing code on your server. Try to analyze the following code snippets and point out if there is a security hole. If yes, please point out the security hole and explain briefly how to exploit it and how to prevent it. If you cannot find the hole in this piece of code, please briefly explain what are other possible reasons why students lost their privacy information. [10 points]

```
# the following code is for the "retrieve SSN number" function
# the function will return a string contains the SSN
# the code is written in python
username = response.POST["username"]
# get the username from the http POST request
# e.g. http://service.com/?username=xxxxxx, and username will be "xxxxxx"
string query = "SELECT SSN from SSN-table WHERE username = " + username
dbm = DatabaseManager() # initialize a data base manager
dbm.makeQuery(query) # issue the query to the database
```

- (3) One senior system administrator argues that the security hole may be resulted from your C code using function memcpy. However, you are confident that your work won't be attacked because of the way you write the Makefile. Briefly explain what you did to prevent the attack. [5 Points]

```
#
# lottery.py
# Find the lucky winner by random picking from registration records

import random, sys

def random_pick(tuples):

    # Random pick an item from the list tuples
    return random.choice(tuples)

def read_tuples(filename):

    # return a list of tuples by parsing the file
    # Each element of the list is a tuple of two strings: (email, name)
    # e.g. ("johnsmith@ucla.edu", "John Smith")
    tuples = []
    f = open(filename, 'r')
    for line in f.readlines():
        #TODO parse each line into tuples

    f.close()
    return tuples

def print_message(tup):

    # tup is the tuple containing winner's email and name
    # e.g. ("johnsmith@ucla.edu", "John Smith")
    #TODO print the congratulation message

def main():
    if(len(sys.argv) > 1):
        print "Too few arguments"
    #TODO complete the main function
```

- (4) One of your daily tasks is to generate a visiting count histogram by analyzing the http access log. You need to count the occurrence of a list of urls to know which part of your site is particularly popular, e.g.:

```
http://studentunion.com/class/
http://studentunion.com/recreation/
```

...

Assume we already have the urls extracted from the log, and the following function performs the counting job.

```
/* Count the occurrences of urls in url_from_log
 * url_list is the list of candidate urls you need to count
 * counters[i] indicates the occurrence of url_list[i]
 * m and n is the size of url_list and url_from_log
 * correspondingly
 */
void count_urls(char** url_list, int m
                char** url_from_log, int n
                int* counters, ) {
    int i, j;
    for(i = 0; i < m; i++)
        for (j = 0; j < n; j++)
            if (strcmp(url_list[i], url_from_log[j]) == 0)
                counters[j]++;
}
```

Your server has 8 cores, and you want to exploit the multicores to speed up your job. Please implement the multithread version of count_urls. If you cannot provide the complete code, please provide a design of the program to illustrate your ideas. [15 Points]