

# CS131 - Week 1

---

UCLA Spring 2019

TA: Kimmo Karkkainen

# Where to find these slides

- Piazza -> Resources -> Discussion 1C
  - Slides are usually uploaded after the discussion section

# Today

- Administration
- Introduction to OCaml
- Homework 1

# Me

- TA: Kimmo Karkkainen
- My email: [kimmo@cs.ucla.edu](mailto:kimmo@cs.ucla.edu)
  - (please use Piazza for questions on homework)
- Office hours Wednesday 10:30-12:30 @ Boelter Hall 3256S

# Homework

- Working on homework yourself is important to success in CS131!
  - Midterm/final usually have some questions related to homework problems
  - Discussing general ideas is ok, sharing code or details is not
    - **We will check submissions against old solutions**
- Homework will be mostly graded using automated scripts
  - Not compiling -> No credit :(
  - Code must behave exactly as the specs say
  - Function signature must match your function signature, otherwise you will get no credit
- Correctness is more important than performance, but you might lose some points if the solution is really inefficient
  - E.g. a given test case takes an hour to finish
  - Mainly a problem in homeworks 2 (OCaml) and 4 (Prolog)

# Homework

- All homework related questions - ask on Piazza
  - Can use private note/question if not sure
  - Questions can be sent anonymously, so that only TAs will see your name
- Homework will be submitted to CCLE

# Homework

- First homework due next Tuesday (April 9th) 11:55pm
- **Warning:** Second homework will take significantly more time than the first homework
  - Start working early, even though there is a bit more time reserved for it
- Tentative homework schedule available on [course website](#)
- Larger project at the end of the course

# Grading

- Homework 32%
  - Each homework has equal weight, project will be worth twice as much
  - Late homeworks will be penalized, penalty doubles every day
    - 1 day = 1%, 2 days = 2%, 3 days = 4%, 4 days = 8%...
- Midterm 24%
- Final exam 44%



# Discussion sections

- Main focus is on skills that are needed to solve the homeworks
  - E.g. The basics of programming languages that we use
- Tentative schedule:
  - Week 1: OCaml + HW1
  - Week 2: OCaml + HW2
  - Week 3: OCaml + HW2
  - Week 4: Midterm review
  - Week 5: Java + HW3
  - Week 6: Prolog + HW4
  - Week 7: Scheme + HW5
  - Week 8: Python + Project
  - Week 9: ? + HW6
  - Week 10: Final exam review

# Questions about the course?

---

# OCaml programming language



**OCaml**

OCaml is an industrial strength programming language supporting functional, imperative and object-oriented styles



# What is Functional Programming?

# What is Functional Programming?

- **There are no side effects - variable's value never changes**
  - No global variables that can be changed from multiple places
  - If you call a function twice with the same arguments, the output should be the same

# Why are we learning this?

- Similar ideas can be found in most modern programming languages, even if they would not be considered functional languages
  - We will see this later when we cover other languages
- Functional programming makes debugging and testing easy
  - Functions will always behave in the same way with the same input, not depending on a global state
- Easy to build scalable systems
  - Distributing code on multiple machines is easier when there is no state that needs to be shared between them
- Many problems can be solved with very little code
  - Less code -> Less bugs

# OCaml introduction

- Functional programming language
- Statically typed
  - Every variable has a type, functions define what the types of input parameters should be
  - Compiler/interpreter can warn you about many programming mistakes early on
  - Makes it faster to execute, as there is less need for safety checks when running the code
- Garbage collection
- Compiled
  - But includes an interactive interpreter

# OCaml introduction

Companies using OCaml:



+ many more use other functional programming languages




# Installing OCaml

- Installation instructions: <https://ocaml.org/docs/install.html>
  - Make sure you are using version 4.07.1
- You can use SEASnet servers too
  - Inxsrv06.seas.ucla.edu, Inxsrv07.seas.ucla.edu, Inxsrv09.seas.ucla.edu, and Inxsrv10.seas.ucla.edu
  - If you don't have a SEASnet account, apply for one ASAP:  
<https://www.seas.ucla.edu/acctapp/>
  - Make sure that the OCaml version is correct (ocaml --version should show 4.07.1)
    - If not, check that /usr/local/cs/bin is in your path
    - Instructions for this are on the course website under homework #1

# Alternative Toplevel - utop

- <https://github.com/ocaml-community/utop>
- Not necessary, but makes coding a bit nicer



The screenshot shows the utop OCaml toplevel interface. At the top, a title bar reads "utop". Below it, a prompt "⇒ utop" is visible. A yellow box contains the text "Welcome to utop version 2.2.0 (using OCaml version 4.06.1)!". The main area displays a list of directives: #require, #list, #camlp4o, #camlp4r, #predicates, Topfind.reset, and #thread, each with a brief description. Below this, a message says "Type #utop\_help for help about using utop." The user has entered the expression "→ 2 + Random.int;;", which has resulted in an error: "Error: This expression has type int → int but an expression was expected of type int". The user then enters "→ 2 + Random.int 100;;", which results in the output "- : int = 46". At the bottom, there is a row of buttons for various OCaml modules: Arg, Arith\_status, Array, ArrayLabels, Assert\_failure, Big\_int, Bigarray, Buffer, Bytes, BytesLabels, and Callba.

```
⇒ utop

Welcome to utop version 2.2.0 (using OCaml version 4.06.1)!

Findlib has been successfully loaded. Additional directives:
#require "package" ;;      to load a package
#list ;;                  to list the available packages
#camlp4o ;;               to load camlp4 (standard syntax)
#camlp4r ;;               to load camlp4 (revised syntax)
#predicates "p,q, ... " ;; to set these predicates
Topfind.reset() ;;        to force that packages will be reloaded
#thread ;;                to enable threads

Type #utop_help for help about using utop.

→ 2 + Random.int;;
Error: This expression has type int → int
      but an expression was expected of type int
→ 2 + Random.int 100;;
- : int = 46
→ █
```

Arg	Arith_status	Array	ArrayLabels	Assert_failure	Big_int	Bigarray	Buffer	Bytes	BytesLabels	Callba
-----	--------------	-------	-------------	----------------	---------	----------	--------	-------	-------------	--------

# Hello, World!

```
# print_string "Hello, World!\n";;  
Hello, World!  
- : unit = ()
```

- First part (print\_string) is the function that is called, next is argument (“Hello, World\n”)
- Statement ends with **two** semi-colons (;;)
  - Necessary when using the interactive session, not needed in code files
- Next line is printed by the function
- Last line is the return value (unit), which conveys no information in this case

# Comments

- (\* This is a comment \*)
- (\* This is  
\* a very  
\* long  
\* comment \*)
- (\* Nested (\* comments \*) are allowed too \*)

# “Variables”


- Not really variables, the value cannot be changed

```
# let my_value = 5;;  
val my_value : int = 5
```

- Note: OCaml supports mutable variables too, but they should not be used in the homework
  - The purpose of the homework is to learn how to program using functional paradigm


# Lists

- Defining a list: *let numbers = [ 1; 2; 3; 4; 5 ]*
- All elements have the same type
- Under the hood, lists are immutable singly-linked lists
  - i.e. iterating them is fast, but random access is slow



# List operations

- List consists of a head and a tail
  - Accessing these elements can be done with *List.hd* and *List.tl*
- Adding a new element into the beginning of a list is easy:
  - $0 :: [1; 2; 3]$  gives us a new list  $[0; 1; 2; 3]$
  - $0 :: 1 :: 2 :: [3]$  gives us  $[0; 1; 2; 3]$  as well!
  - $::$  is right associative, meaning that the previous statement becomes  $0 :: (1 :: (2 :: [3]))$
  - $1 :: 2$  or  $[1] :: [2]$  are not valid! Why?
- **Note:** Lists are immutable!
  - Need to create a new list to change any of the values



# Functions

```
# let average a b =  
    (a + b) / 2;;  
val average : int -> int -> int = <fun>
```

- *let* binds a function with parameters *a* and *b* to name *average*
- Note that inputs and outputs are inferred to be **integers**
- Assigning a value and defining a function use the same syntax
  - Variables can be thought of as functions that take no input values and return a constant output value

```
# let average a b =  
    (a +. b) /. 2.0;;  
val average : float -> float -> float = <fun>
```



# Functions

- Calling a function:

```
# let my_average = average 3 5;;  
Error: This expression has type int but an expression was expected of type  
      float  
# let my_average = average 3.0 5.0;;  
val my_average : float = 4.
```

- **Note:** The input values are listed without parentheses or commas

# Recursive functions

- Recursive functions must be specified explicitly (*let rec*), otherwise the compiler will give an error about an undefined function

```
# let rec factorial a =  
    if a = 1 then 1 else a * factorial (a-1);;  
val factorial : int -> int = <fun>
```

```
# factorial 5;;  
- : int = 120
```

- **Note:** Parentheses necessary around (a-1), otherwise OCaml will try to call factorial a

# Defining local variables in functions

- Add keyword *in* after the let statement to make the value available in the following statement

```
# let average a b =  
  let sum = a +. b in  
  sum /. 2.0;;  
val average : float -> float -> float = <fun>
```

# Lambda functions

- Lambda functions (aka Anonymous functions) are not bound to any name
- Useful when using a function as a function argument
  - Very common in functional programming
  - *“Higher-order function”*

```
# (fun x -> x*x) 5;;  
- : int = 25
```

# Useful list operations - map

- *Map* transforms a list by applying a function on each element

```
# List.map (fun x -> x*x) [1; 2; 3; 4; 5];;  
- : int list = [1; 4; 9; 16; 25]
```

# Useful list operations - filter

- *Filter* returns a list containing elements that match a given condition

```
# List.filter (fun x -> x < 3) [1; 2; 3; 4; 5];;  
- : int list = [1; 2]
```

# Useful list operations - rev

- *Rev* returns a reversed list

```
# List.rev [1; 2; 3; 4; 5];;  
- : int list = [5; 4; 3; 2; 1]
```

# Useful list operations - for\_all

- *For\_all* returns true if a condition applies to every element in the list

```
# List.for_all (fun x -> x < 3) [1; 2; 3; 4; 5];;  
- : bool = false  
# List.for_all (fun x -> x < 6) [1; 2; 3; 4; 5];;  
- : bool = true
```



# Useful list operations - exists

- *Exists* checks if any element in the list matches a condition

```
# List.exists (fun x -> x = 3) [1; 2; 3; 4; 5];;  
- : bool = true  
# List.exists (fun x -> x = 6) [1; 2; 3; 4; 5];;  
- : bool = false
```

# List module problems

Solve the following using only List-module functions (e.g. map, filter, for\_all, exists, ...)

[1; 2; 3; 4; 5]



[2; 3; 4; 5; 6]

# List module problems

Solve the following using only List-module functions (e.g. map, filter, for\_all, exists, ...)


[1;2;3;4;5;6;7;8]



[2;4;6;8]

# List module problems

Solve the following using only List-module functions (e.g. map, filter, for\_all, exists, ...)



# Pattern matching

- Some problems can be solved using either conditional statements or pattern matching:

```
# let is_zero x =  
  if x = 0 then true else false;;
```

```
# let is_zero x = match x with  
  0 -> true  
  | _ -> false;;
```

- More powerful version of the *switch* statement used in some other languages
- Pattern matching allows you to list all the different cases in a clean way
  - Underscore ( `_` ) matches any value that does not match the earlier rules
  - Cleaner than conditionals when there is a large number of possible cases
- Compiler lets you know which cases do not match to any of the rules

# Pattern matching - Conditions

- Patterns can also include conditions using *when* statement:

```
# let rec factorial a = match a with  
  x when x < 2 -> 1  
  | x -> x * factorial (x-1);;
```

# Pattern matching - Tuples

```
let tuple_matcher x = match x with  
| (1, a) -> a  
| _ -> 0;
```

```
tuple_matcher (1, 5);;  
- : int = 5
```

```
tuple_matcher (0, 5);;  
- : int = 0
```

# Data types - Native types

- Native data types in OCaml:
  - int (1, 2, -100)
  - float (1.53, -1053.6)
  - char ('a', '\n')
  - string ("foo", "bar", "this is a longer text")
  - bool (true, false)
  - unit ( () )
    - Means "no value"
    - Usually the return value of functions that have side effects, e.g. print\_string



# Data types - Native types

- More native data types:
  - list ( [1; 2; 3; 4; 5], ["foo"; "bar"] )
    - Elements have the same type
    - As mentioned earlier, lists immutable -> list manipulation functions return a new list
  - tuple ( (1, 5, "foo", "bar") )
    - Can combine different data types
    - Accessing elements: `fst my_tuple`, `snd my_tuple`
      - No easy access to other elements
    - Less easy to manipulate than lists
    - Very useful with pattern matching
  - functions ( `let my_fun x = x + 1` )

# Data types - Own data types

- The most simple use case is to wrap an existing type:

```
type age = int;;  
type name = string;;  
type person = age * name;;  
  
let print_name (p : person) = match p with  
| (p_age, p_name) -> print_string p_name;;  
  
let my_person = (111,"Bilbo" : person);;  
print_name my_person;;  
Bilbo
```

# Data types - Variants

- Used when there are multiple subtypes of one main type

```
type ccle_user =  
  Student of string  
  | TA of string  
  | Professor of string ;;
```

```
let user = Professor "Eggert";;
```

```
val user : ccle_user = Professor "Eggert"
```

# Pattern matching - Types

```
type my_type =  
  | A of string  
  | B of int;;  
  
let my_print x = match x with  
  | A a -> print_string a  
  | B b -> print_int b;;  
  
my_print (A "some string");;  
some string  
  
my_print (B 5);;  
5
```

# Context-Free Grammars

---

# Context-Free Grammars

- Grammar defines a language
  - What strings are valid in a language
- E.g. We could define a grammar for our own programming language to define what kind of syntax is allowed
  - Grammar does not say what the instructions in that language mean, it just defines what syntax is allowed
  - E.g. We could check that ***print("Hello World!")*** is valid, without defining what it does
- There are multiple types of grammars, but for the first homework you only need to know about *Context-Free Grammars*
  - Some other grammars will be covered in the lectures

# Context-Free Grammars

- Grammar consists of rules (E.g. *NOUN -> Mary*), non-terminal symbols (E.g. *NOUN*), and terminal symbols (e.g. *mary*)
- Grammar has a starting point, in this case *PHRASE*
- Rules tell us how non-terminal symbols can be replaced
- Possible strings: *mary eats*; *mary drinks*; *mark eats*; *mark drinks*

## ***Example grammar:***

*PHRASE -> NOUN VERB*

*NOUN -> mary*

*NOUN -> mark*

*VERB -> eats*

*VERB -> drinks*

# Context-Free Grammars

- Let's consider a slightly modified grammar
- The non-terminal symbol ADJECTIVE is not used on the right-hand side of any rule, so it will never be used -> unreachable rule
  - In your homework, you have to remove all the rules that can't be reached from the starting point using one or more rules

## ***Example grammar:***

*PHRASE -> NOUN VERB*

*NOUN -> mary*

*NOUN -> mark*

*VERB -> eats*

*VERB -> drinks*

***ADJECTIVE -> red***



# Homework #1

---

# Homework #1

- Deadline next Tuesday (April 9th) at 11:55pm
- See <http://web.cs.ucla.edu/classes/spring19/cs131/hw/hw1.html> for details

# Allowed modules

- In the first homework, you are allowed to use two modules: *List* and *Pervasives*
  - **Pervasives** module provides the core functionality of OCaml
    - No need to explicitly import this module
  - **List** module contains functions that are useful when operating with lists
    - This module is not imported by default!
- Before you can call a function that is in a module, you need to import it:  
*open List*
- Alternatively, you can add the module name into the function call,  
e.g. `List.filter`

# Homework #1


1. Write a function to determine if one list is a subset of another list
  - i.e. is every element of list  $a$  also in list  $b$
2. Write a function to determine if two sets are equal
  - Both should contain the same elements
3. Write a function that returns the union of two sets
  - A set that has every element that exists in either set or in both of them
4. Write a function that returns the intersection of two sets
  - A set that contains every element that is in both of the given sets
5. Write a function that returns the difference of two sets
  - All elements that belong to the first set but do not belong to the second set

# Homework #1

6. Write a function that returns the computed fixed point of a given function
- Value  $x$  where  $f(x) = x$

Computed fixed point can be found by testing iteratively  $f(x)$ ,  $f(f(x))$ ,  $f(f(f(x)))$ , and so on

- Some functions do not have a fixed point
- This technique does not always find fixed points



# Homework #1

7. Write a function that takes a grammar as its input and returns a grammar where all the unreachable rules have been removed
  - Recommended reading: [https://en.wikipedia.org/wiki/Context-free\\_grammar](https://en.wikipedia.org/wiki/Context-free_grammar)
8. Write at least one test case for each of the previous functions

# Homework #1 - Submission

- You are expected to submit 3 files:
  - hw1.ml - The functions that you implemented
  - hw1test.ml - Test cases for your functions
  - hw1.txt - Written assessment of how you ended up solving the problems the way you did
    - See course website for details

# HW1 - Note

- Copy the type definition into your code file

```
type ('nonterminal, 'terminal) symbol =  
  | N of 'nonterminal  
  | T of 'terminal
```



# Homework #1 - How to get started

- Read and understand the given test cases
  - If the problem definition seems unclear, the test cases might help you understand how your code should behave
- Read through the documentation for *List* and *Pervasives* modules
  - Most problems can be solved with very little code if you don't reinvent the wheel
- Think whether the functions that you wrote for earlier problems can be used to solve the later problems
  - The power of functional programming comes from reusing very simple functions to implement more powerful functions
- **Make sure your solution works on SEASnet servers!**

# Helpful resources

- OCaml tutorial <https://ocaml.org/learn/tutorials/>
- Try OCaml <https://try.ocamlpro.com>
  - Interactive tutorial in your browser
  - Covers some topics that are not used in this course

# Questions?

- Piazza
  - Fastest way to get answers
  - TAs and your classmates can answer your question, so this is the best channel to get help when you're stuck
- Come to office hours
  - My office hour is Wednesday 10:30-12:30, others will be posted on CCLE
- Come ask after the discussion sections