

	0.5000.00.710.71
TYPE	DESCRIPTION
	RECESSED MOUNTED DOWNLIGHT, 100W LOW VOLTAGE TUNGESTEN HALOGEN WITH DICHROIC REFLECTOR, GOLD FINISHED, FIXED TYPE WITH 240V/12V TRAFO
⊢ <u>*</u>	150 WATTS QT-DE HALOGEN LAMP WALL MOUNTED. FITTING WITH DIE CAST ALUMINUM SUPPORT AND DIE CAST ALUMINIUM OF BASS COMPLETE WITH SAFETY GLASS ON TOP OF THE DIFFUSER (IP44)
 ₩•	100 WATTS QT-DE HALOGEN LAMP CILLING MOUNTED FITTING WITH DIE CAST ALUMINUM SUPPORT AND DIE CAST ALUMINIUM OF BASS COMPLETE WITH SAFETY GLASS ON TOP OF THE DIFFUSER (1P44)
4-	FLOOD LIGHT WITH 400W HPMV, LAMP 240V,50HZ 5M HEIGHT WATER PROOF 1Y
(M)	FLOOD LIGHT WITH 200W HPMV. LAMP 240V,50HZ 5M HEIGHT WATER PROOF 1
A1	4x18 WATTS RECESSED MODULAR 600x600mm SEALED LUMINAIRE IP54. WITH PRISMATIC TP(a) DIFFUSER AND HF ELECTRONIC CONTROL GEAR. DIFFUSER FRAME SECURED B1/4 TURN FASTENERS.
A1+E	SAME AS ABOVE BUT WITH INTEGRAL EMERGENCY CONVERSION KIT FOR 3 HRS.
A and the second	4x18 WATTS RECESSED MODULAR 600x600mm LUMINAIRE BODY IN WHITE STOVE ENAMELLED STEELHIGH FREQUENCY ELECTRONIC BALLAST WITH SPECULAR ALUMINIUM LOUVRE TO LG3 CAT 2 MIRROR FINISH .
A+E	SAME AS ABOVE BUT WITH INTEGRAL EMERGENCY CONVERSION KIT FOR 3 HRS. DURATION .
	1x36W RECESSED MOUNTING TYPE (FOR STEEL STRIPS) LIGHT FITTING 1X36 FLUORESCENT LAMP , IP-54.
L+E	SAME AS ABOVE BUT WITH INTEGRAL EMERGENCY CONVERSION KIT FOR 3 HRS. DURATION .
н	2x36W SURFACE MOUNTED WITH ACRYLIC DIFFUSER, IP65, FLOURESCENT LIGHT FITTING POLYCARBONATE CONTROLLER HIGH FREQUENCY BALLAST. FOR BEASMENT
H+E∏	SAME AS ABOVE BUT WITH INTEGRAL EMERGENCY CONVERSION KIT FOR 3HRS. DURATION . FOR BEASMENT
5	LIGHT SWITCH 1-GANG, 1-WAY, 240V, 10A
VSA	LIGHT SWITCH 1-GANG, 2-WAY, 240V, 10A (Aler-e-tour)
D	CONVENTIONAL DIMMER SWITCH, 240V, 1500W
W	INDICATION FOR WEATHERPROOF TYPE FITTING
ф	WALL MOUNTED FAN
	HIGH BAY INDUSTRIAL TYPE FIXTURE WITH 300W HPMV LAMP 240V, 50HZ

