

```

import { useState } from "react";

const SEED_CLIENTS = [
  { id: 1, name: "Carlos M.", phone: "831-555-0192", address: "Salinas, CA", note
  { id: 2, name: "Rosa T.", phone: "831-555-0347", address: "Monterey, CA", notes
];
const SEED_JOBS = [
  { id: 1, clientId: 1, date: "2026-04-28", description: "Oil change + tire rotat
  { id: 2, clientId: 2, date: "2026-05-01", description: "Brake pad replacement (
  { id: 3, clientId: 1, date: "2026-05-03", description: "AC diagnostic", status:
];
const SEED_INVOICES = [
  { id: 1, clientId: 1, jobId: 1, date: "2026-04-28", items: [{ desc: "Oil change
  { id: 2, clientId: 2, jobId: 2, date: "2026-05-01", items: [{ desc: "Front brak
];

const S = {
  app: { minHeight: "100vh", backgroundColor: "#0d0d0d", color: "#f0ebe0", fontFa
  header: { borderBottom: "2px solid #b91c1c", padding: "16px 24px", display: "fl
  logo: { fontSize: "26px", fontWeight: 900, letterSpacing: "8px", color: "#f0ebe
  logoAccent: { color: "#b91c1c" },
  tagline: { fontSize: "10px", letterSpacing: "3px", color: "#4b5563", textTransf
  nav: { display: "flex", gap: 0, padding: "0 24px", backgroundColor: "#111111",
  navBtn: (a) => ({ padding: "14px 18px", background: "none", border: "none", col
  main: { padding: "24px", maxWidth: "960px", margin: "0 auto" },
  statGrid: { display: "grid", gridTemplateColumns: "repeat(4, 1fr)", gap: "12px"
  statCard: { backgroundColor: "#111", border: "1px solid #1f1f1f", padding: "20p
  statNum: { fontSize: "32px", fontWeight: 900, color: "#b91c1c", lineHeight: 1 }
  statLabel: { fontSize: "9px", letterSpacing: "2px", color: "#4b5563", textTrans
  card: { backgroundColor: "#111", border: "1px solid #1f1f1f", borderRadius: "2p
  sectionTitle: { fontSize: "10px", letterSpacing: "3px", color: "#4b5563", textT
  table: { width: "100%", borderCollapse: "collapse" },
  th: { textAlign: "left", fontSize: "9px", letterSpacing: "2px", color: "#4b5563
  td: { padding: "12px", borderBottom: "1px solid #0d0d0d", fontSize: "13px", col
  tdMuted: { padding: "12px", borderBottom: "1px solid #0d0d0d", fontSize: "12px"
  badge: (s) => ({ display: "inline-block", padding: "2px 8px", fontSize: "9px",
  label: { fontSize: "9px", letterSpacing: "2px", color: "#4b5563", textTransform
  input: { width: "100%", backgroundColor: "#0d0d0d", border: "1px solid #1f1f1f"
  select: { width: "100%", backgroundColor: "#0d0d0d", border: "1px solid #1f1f1f
  textarea: { width: "100%", backgroundColor: "#0d0d0d", border: "1px solid #1f1f
  btn: { backgroundColor: "#b91c1c", color: "#f0ebe0", border: "none", padding: "
  btnSm: { backgroundColor: "#b91c1c", color: "#f0ebe0", border: "none", padding:
  btnGhost: { backgroundColor: "transparent", color: "#4b5563", border: "1px soli
  row: { display: "flex", gap: "12px", marginBottom: "12px", flexWrap: "wrap" },

```

```

col: { flex: 1, minWidth: "140px" },
fg: { marginBottom: "14px" },
quoteBox: { backgroundColor: "#0d0d0d", border: "1px solid #1f1f1f", borderRadi
dot: (on) => ({ width: "6px", height: "6px", borderRadius: "50%", backgroundCol
divider: { border: "none", borderTop: "1px solid #1f1f1f", margin: "20px 0" },
};

```

```

export default function Sueldo() {
  const [tab, setTab] = useState("dashboard");
  const [clients, setClients] = useState(SEED_CLIENTS);
  const [jobs, setJobs] = useState(SEED_JOBS);
  const [invoices, setInvoices] = useState(SEED_INVOICES);
  const [apiKey, setApiKey] = useState(import.meta.env.VITE_ANTHROPIC_KEY || "");
  const [showKeyInput, setShowKeyInput] = useState(false);

  const [nc, setNc] = useState({ name: "", phone: "", address: "", notes: "" });
  const [nj, setNj] = useState({ clientId: "", date: "", description: "", status:
  const [ni, setNi] = useState({ clientId: "", date: new Date().toISOString().spl
  const [qf, setQf] = useState({ jobType: "", vehicle: "", parts: "", hours: "",
  const [qResult, setQResult] = useState("");
  const [qLoading, setQLoading] = useState(false);
  const [qError, setQError] = useState("");
  const [viewInvoice, setViewInvoice] = useState(null);
  const [copied, setCopied] = useState(false);

  const clientName = (id) => clients.find(c => c.id === Number(id))?.name || "-";

  const addClient = () => {
    if (!nc.name.trim()) return;
    setClients([...clients, { ...nc, id: Date.now() }]);
    setNc({ name: "", phone: "", address: "", notes: "" });
  };

  const addJob = () => {
    if (!nj.description.trim() || !nj.clientId) return;
    setJobs([...jobs, { ...nj, id: Date.now(), clientId: Number(nj.clientId), amo
    setNj({ clientId: "", date: "", description: "", status: "pending", amount: "
  };

  const updateJobStatus = (id, status) => setJobs(jobs.map(j => j.id === id ? { .

  const invoiceTotal = () => ni.items.reduce((s, i) => s + (parseFloat(i.price) |

  const addInvoice = () => {
    if (!ni.clientId) return;
    const total = invoiceTotal();
    setInvoices([...invoices, { ...ni, id: Date.now(), clientId: Number(ni.client

```

```

    setNi({ clientId: "", date: new Date().toISOString().split("T")[0], items: [{
};

const addInvoiceItem = () => setNi({ ...ni, items: [...ni.items, { desc: "", qt
const updateItem = (idx, field, val) => {
  const items = [...ni.items];
  items[idx] = { ...items[idx], [field]: val };
  setNi({ ...ni, items });
};

const removeItem = (idx) => setNi({ ...ni, items: ni.items.filter((_, i) => i !

const generateQuote = async () => {
  if (!qf.jobType) return;
  if (!apiKey) { setQError("Add your Anthropic API key in Settings (top right)
  setQLoading(true);
  setQResult("");
  setQError("");
  try {
    const prompt = `You are a pricing assistant for an independent mobile mecha

Job Type: ${qf.jobType}
Vehicle/Equipment: ${qf.vehicle || "Not specified"}
Parts Needed: ${qf.parts || "TBD"}
Estimated Hours: ${qf.hours || "TBD"}
Labor Rate: $$${qf.rate}/hr
Notes: ${qf.notes || "None"}

Write a clean, professional quote with itemized parts, labor cost, and TOTAL. Kee

    const res = await fetch("https://api.anthropic.com/v1/messages", {
      method: "POST",
      headers: { "Content-Type": "application/json", "x-api-key": apiKey, "anth
      body: JSON.stringify({ model: "claude-sonnet-4-20250514", max_tokens: 100
    });
    const data = await res.json();
    const text = data.content?.map(b => b.text || "").join("") || "";
    if (!text) throw new Error("No response");
    setQResult(text);
  } catch {
    setQError("Error generating quote. Check your API key and try again.");
  }
  setQLoading(false);
};

const copyQuote = () => {
  navigator.clipboard.writeText(qResult);
  setCopied(true);

```

```

    setTimeout(() => setCopied(false), 2000);
  };

const totalEarned = jobs.filter(j => j.status === "completed").reduce((s, j) =>
const pendingCount = jobs.filter(j => j.status === "pending").length;
const unpaidCount = invoices.filter(i => i.status !== "paid").length;

const TABS = [
  { id: "dashboard", label: "Dashboard" },
  { id: "clients", label: "Clients" },
  { id: "jobs", label: "Jobs" },
  { id: "invoices", label: "Invoices" },
  { id: "quote", label: "AI Quote" },
];

return (
  <div style={S.app}>
    { /* Header */ }
    <div style={S.header}>
      <div>
        <div style={S.logo}>SUEL<span style={S.logoAccent}>DO</span></div>
        <div style={S.tagline}>Mobile Trades Platform</div>
      </div>
      <div style={{ display: "flex", alignItems: "center", gap: "16px" }}>
        {showKeyInput ? (
          <div style={{ display: "flex", gap: "8px", alignItems: "center" }}>
            <input
              style={{ ...S.input, width: "260px", fontSize: "11px" }}
              type="password"
              value={apiKey}
              onChange={e => setApiKey(e.target.value)}
              placeholder="sk-ant-... (Anthropic API key)"
            />
            <button style={S.btnSm} onClick={() => setShowKeyInput(false)}>Save
          </div>
        ) : (
          <button style={S.btnGhost} onClick={() => setShowKeyInput(true)}>
            {apiKey ? "✓ API Key Set" : "⚙ API Key"}
          </button>
        )}
      </div>
      <span style={S.dot(true)} />
      <span style={{ fontSize: "10px", letterSpacing: "2px", color: "#4b556" }}>
    </div>
  </div>

```

```

    { /* Nav */ }
    <div style={S.nav}>
      { TABS.map(t => (
        <button key={t.id} style={S.navBtn(tab === t.id)} onClick={() => setTab(t.id)} />
      )) }
    </div>

    <div style={S.main}>

      { /* DASHBOARD */ }
      { tab === "dashboard" && (
        <div>
          <div style={S.statGrid}>
            <div style={S.statCard}>
              <div style={S.statNum}>${totalEarned.toLocaleString()}</div>
              <div style={S.statLabel}>Total Earned</div>
            </div>
            <div style={S.statCard}>
              <div style={S.statNum}>{jobs.length}</div>
              <div style={S.statLabel}>Total Jobs</div>
            </div>
            <div style={S.statCard}>
              <div style={{ ...S.statNum, color: pendingCount > 0 ? "#fb923c" : }}>
                <div style={S.statLabel}>Pending Jobs</div>
              </div>
            <div style={S.statCard}>
              <div style={S.statNum}>{clients.length}</div>
              <div style={S.statLabel}>Clients</div>
            </div>
          </div>
          { unpaidCount > 0 && (
            <div style={{ backgroundColor: "#7c2d1222", border: "1px solid #7c2d1222" }}>
              <span style={{ color: "#fb923c", fontSize: "11px", fontWeight: 700 }}>{unpaidCount}</span>
              <button style={S.btnSm} onClick={() => setTab("invoices")}>View</button>
            </div>
          ) }
        </div>

        <div style={S.sectionTitle}>Recent Jobs</div>
        <div style={S.card}>
          <table style={S.table}>
            <thead>
              <tr>
                <th style={S.th}>Client</th>
                <th style={S.th}>Description</th>
                <th style={S.th}>Date</th>
                <th style={S.th}>${}</th>
              </tr>
            </thead>
            <tbody>
              { jobs.map(job => (
                <tr>
                  <td style={S.th}>{job.client}</td>
                  <td style={S.th}>{job.description}</td>
                  <td style={S.th}>{job.date}</td>
                  <td style={S.th}>{job.status}</td>
                </tr>
              )) }
            </tbody>
          </table>
        </div>
      ) }
    </div>
  ) }

```

```

        <th style={S.th}>Status</th>
      </tr>
    </thead>
    <tbody>
      {[...jobs].reverse().slice(0, 6).map(j => (
        <tr key={j.id}>
          <td style={S.td}>{clientName(j.clientId)}</td>
          <td style={S.td}>{j.description}</td>
          <td style={S.tdMuted}>{j.date}</td>
          <td style={S.td}>${j.amount}</td>
          <td style={S.td}><span style={S.badge(j.status)}>{j.status}</span>
        </tr>
      )]}
    </tbody>
  </table>
</div>
</div>
)}

```

```

{/* CLIENTS */}

```

```

{tab === "clients" && (

```

```

  <div>

```

```

    <div style={S.sectionTitle}>Add Client</div>

```

```

    <div style={S.card}>

```

```

      <div style={S.row}>

```

```

        <div style={S.col}>

```

```

          <label style={S.label}>Name *</label>

```

```

          <input style={S.input} value={nc.name} onChange={e => setNc({

```

```

        </div>

```

```

        <div style={S.col}>

```

```

          <label style={S.label}>Phone</label>

```

```

          <input style={S.input} value={nc.phone} onChange={e => setNc({

```

```

        </div>

```

```

      </div>

```

```

      <div style={S.row}>

```

```

        <div style={S.col}>

```

```

          <label style={S.label}>Address</label>

```

```

          <input style={S.input} value={nc.address} onChange={e => setNc({

```

```

        </div>

```

```

        <div style={S.col}>

```

```

          <label style={S.label}>Notes</label>

```

```

          <input style={S.input} value={nc.notes} onChange={e => setNc({

```

```

        </div>

```

```

      </div>

```

```

      <button style={S.btn} onClick={addClient}>+ Add Client</button>

```

```

    </div>

```

```

<div style={S.sectionTitle}>All Clients ({clients.length})</div>
{clients.map(c => (
  <div key={c.id} style={{ ...S.card, padding: "16px 20px" }}>
    <div style={{ display: "flex", justifyContent: "space-between", a
      <div>
        <div style={{ fontWeight: 700, fontSize: "15px", marginBottom
          <div style={{ fontSize: "12px", color: "#4b5563" }}>{c.phone}
            {c.notes && <div style={{ fontSize: "12px", color: "#6b7280",
              </div>
            <div style={{ textAlign: "right" }}>
              <div style={{ fontSize: "10px", color: "#4b5563", letterSpacing
                {jobs.filter(j => j.clientId === c.id).length} job{jobs.fil
              </div>
              <div style={{ fontSize: "14px", fontWeight: 700, color: "#b91
                ${jobs.filter(j => j.clientId === c.id && j.status === "com
              </div>
            </div>
          </div>
        </div>
      </div>
    </div>
  )})
)}
</div>
)}

{/* JOBS */}
{tab === "jobs" && (
  <div>
    <div style={S.sectionTitle}>Log a Job</div>
    <div style={S.card}>
      <div style={S.row}>
        <div style={S.col}>
          <label style={S.label}>Client *</label>
          <select style={S.select} value={nj.clientId} onChange={e => set
            <option value="">Select client</option>
            {clients.map(c => <option key={c.id} value={c.id}>{c.name}</o
          </select>
        </div>
        <div style={S.col}>
          <label style={S.label}>Date</label>
          <input style={S.input} type="date" value={nj.date} onChange={e
        </div>
      </div>
      <div style={S.row}>
        <div style={{ flex: 2, minWidth: "200px" }}>
          <label style={S.label}>Description *</label>
          <input style={S.input} value={nj.description} onChange={e => se
        </div>
        <div style={S.col}>

```

```

        <label style={S.label}>Amount ($)</label>
        <input style={S.input} type="number" value={nj.amount} onChange
    </div>
    <div style={S.col}>
        <label style={S.label}>Status</label>
        <select style={S.select} value={nj.status} onChange={e => setNj
            <option value="pending">Pending</option>
            <option value="completed">Completed</option>
        </select>
    </div>
</div>
<button style={S.btn} onClick={addJob}>+ Log Job</button>
</div>

<div style={S.sectionTitle}>Job History ({jobs.length})</div>
<div style={S.card}>
    <table style={S.table}>
        <thead>
            <tr>
                <th style={S.th}>Client</th>
                <th style={S.th}>Description</th>
                <th style={S.th}>Date</th>
                <th style={S.th}>Amount</th>
                <th style={S.th}>Status</th>
                <th style={S.th}>Action</th>
            </tr>
        </thead>
        <tbody>
            {[...jobs].reverse().map(j => (
                <tr key={j.id}>
                    <td style={S.td}>{clientName(j.clientId)}</td>
                    <td style={S.td}>{j.description}</td>
                    <td style={S.tdMuted}>{j.date}</td>
                    <td style={{ ...S.td, fontWeight: 700 }}>${j.amount}</td>
                    <td style={S.td}><span style={S.badge(j.status)}>{j.status}</td>
                    <td style={S.td}>
                        {j.status === "pending" && (
                            <button style={S.btnSm} onClick={() => updateJobStatus(
                                )}
                        </td>
                    </tr>
                )]}
            </tbody>
        </table>
    </div>
</div>
)}

```



```

{/* INVOICES */}
{tab === "invoices" && (
  <div>
    {viewInvoice ? (
      <div>
        <button style={S.btnGhost} onClick={() => setViewInvoice(null)}>-
        <div style={{ marginTop: "20px" }}>
          <div style={{ ...S.card, borderColor: "#b91c1c22" }}>
            <div style={{ display: "flex", justifyContent: "space-between" }}>
              <div>
                <div style={{ fontSize: "22px", fontWeight: 900, letterSpacing: 1.5 }}>
                  <div style={{ fontSize: "10px", color: "#4b5563", marginT: 10px }}>
                    <div style={{ fontSize: "10px", color: "#4b5563" }}>Salin
                  </div>
                <div style={{ textAlign: "right" }}>
                  <div style={{ fontSize: "10px", letterSpacing: "2px", color: "#4b5563" }}>
                    <div style={{ fontSize: "12px", color: "#d1cf99", marginT: 10px }}>
                      <div style={{ marginTop: "8px" }}><span style={S.badge} (viewInvoice ? (
                        </div>
                      </div>
                    </div>
                  </div>
                <div style={{ fontSize: "10px", color: "#4b5563", letterSpacing: 1.5 }}>
                  <div style={{ fontWeight: 700, marginBottom: "20px" }}><div>
                    <hr style={S.divider} />
                    <table style={{ ...S.table, marginBottom: "16px" }}>
                      <thead>
                        <tr>
                          <th style={S.th}>Description</th>
                          <th style={{ ...S.th, textAlign: "center" }}>Qty</th>
                          <th style={{ ...S.th, textAlign: "right" }}>Price</th>
                          <th style={{ ...S.th, textAlign: "right" }}>Total</th>
                        </tr>
                      </thead>
                      <tbody>
                        {viewInvoice.items.map((item, i) => (
                          <tr key={i}>
                            <td style={S.td}>{item.desc}</td>
                            <td style={{ ...S.td, textAlign: "center" }}>{item.qt}</td>
                            <td style={{ ...S.td, textAlign: "right" }}>${item.pr}</td>
                            <td style={{ ...S.td, textAlign: "right", fontWeight: 700 }}>
                              </td>
                            </tr>
                        ))}
                      </tbody>
                    </table>
                    <hr style={S.divider} />
                    <div style={{ textAlign: "right" }}>
                      <div style={{ fontSize: "10px", color: "#4b5563", letterSpacing: 1.5 }}>

```

```

    <div style={{ fontSize: "28px", fontWeight: 900, color: "#b
  </div>
  <hr style={S.divider} />
  <div style={{ fontSize: "11px", color: "#4b5563" }}>Thank you
</div>
{viewInvoice.status !== "paid" && (
  <button style={S.btn} onClick={() => { setInvoices(invoices.m
    )}
  </div>
</div>
) : (
  <div>
    <div style={S.sectionTitle}>Create Invoice</div>
    <div style={S.card}>
      <div style={S.row}>
        <div style={S.col}>
          <label style={S.label}>Client *</label>
          <select style={S.select} value={ni.clientId} onChange={e =>
            <option value="">Select client</option>
            {clients.map(c => <option key={c.id} value={c.id}>{c.name
          </select>
        </div>
        <div style={S.col}>
          <label style={S.label}>Date</label>
          <input style={S.input} type="date" value={ni.date} onChange
        </div>
      </div>
      <div style={S.sectionTitle}>Line Items</div>
      {ni.items.map((item, i) => (
        <div key={i} style={{ ...S.row, alignItems: "flex-end" }}>
          <div style={{ flex: 3, minWidth: "160px" }}>
            {i === 0 && <label style={S.label}>Description</label>
            <input style={S.input} value={item.desc} onChange={e => u
          </div>
          <div style={{ width: "70px" }}>
            {i === 0 && <label style={S.label}>Qty</label>
            <input style={S.input} type="number" value={item.qty} onC
          </div>
          <div style={{ width: "100px" }}>
            {i === 0 && <label style={S.label}>Price ($)</label>
            <input style={S.input} type="number" value={item.price} o
          </div>
          {ni.items.length > 1 && (
            <button style={{ ...S.btnGhost, padding: "9px 10px", colo
          )}
        </div>
      )}}
    </div>
  )}
)

```

```

    <div style={{ display: "flex", gap: "12px", alignItems: "center"
      <button style={S.btnGhost} onClick={addInvoiceItem}>+ Add Lin
      <div style={{ marginLeft: "auto", fontSize: "13px", color: "#
        Total: <span style={{ color: "#b91c1c", fontWeight: 900, fo
      </div>
    </div>
    <hr style={S.divider} />
    <button style={S.btn} onClick={addInvoice}>Generate Invoice</bu
  </div>

  <div style={S.sectionTitle}>All Invoices ({invoices.length})</div>
  <div style={S.card}>
    <table style={S.table}>
      <thead>
        <tr>
          <th style={S.th}>#</th>
          <th style={S.th}>Client</th>
          <th style={S.th}>Date</th>
          <th style={S.th}>Total</th>
          <th style={S.th}>Status</th>
          <th style={S.th}>View</th>
        </tr>
      </thead>
      <tbody>
        {[...invoices].reverse().map(inv => (
          <tr key={inv.id}>
            <td style={S.tdMuted}>#{inv.id}</td>
            <td style={S.td}>{clientName(inv.clientId)}</td>
            <td style={S.tdMuted}>{inv.date}</td>
            <td style={{ ...S.td, fontWeight: 700 }}>${inv.total.to
            <td style={S.td}><span style={S.badge(inv.status)}>{inv
            <td style={S.td}><button style={S.btnSm} onClick={() =>
          </tr>
        )})
      </tbody>
    </table>
  </div>
</div>
))
</div>
)}

{ /* AI QUOTE */}
{tab === "quote" && (
  <div>
    <div style={S.sectionTitle}>AI Quote Generator</div>
    <div style={{ fontSize: "11px", color: "#4b5563", marginBottom: "20px

```

```

    Describe the job – AI builds a professional quote you can send in s
  </div>
  {!apiKey && (
    <div style={{ backgroundColor: "#1e3a5f22", border: "1px solid #1e3
       Add your Anthropic API key (top right) to unlock AI Quote gene
    </div>
  )}
  <div style={S.card}>
    <div style={S.row}>
      <div style={{ flex: 2, minWidth: "180px" }}>
        <label style={S.label}>Job Type *</label>
        <input style={S.input} value={qf.jobType} onChange={e => setQf(
      </div>
      <div style={S.col}>
        <label style={S.label}>Vehicle</label>
        <input style={S.input} value={qf.vehicle} onChange={e => setQf(
      </div>
    </div>
    <div style={S.row}>
      <div style={{ flex: 2, minWidth: "180px" }}>
        <label style={S.label}>Parts Needed</label>
        <input style={S.input} value={qf.parts} onChange={e => setQf({
      </div>
      <div style={S.col}>
        <label style={S.label}>Est. Hours</label>
        <input style={S.input} type="number" value={qf.hours} onChange=
      </div>
      <div style={S.col}>
        <label style={S.label}>Labor $/hr</label>
        <input style={S.input} type="number" value={qf.rate} onChange={
      </div>
    </div>
    <div style={S.fg}>
      <label style={S.label}>Additional Notes</label>
      <textarea style={S.textarea} value={qf.notes} onChange={e => setQ
    </div>
    <button style={{ ...S.btn, opacity: qLoading ? 0.6 : 1 }} onClick={
      {qLoading ? "Generating..." : "⚡ Generate Quote"}
    </button>
  </div>

  {(qResult || qLoading || qError) && (
    <div>
      <div style={S.sectionTitle}>Your Quote</div>
      <div style={S.quoteBox}>
        {qLoading && <span style={{ color: "#4b5563", letterSpacing: "2
        {qError && <span style={{ color: "#fb923c" }}>{qError}</span>}

```

```

        {qResult}
      </div>
      {qResult && (
        <div style={{ marginTop: "12px", display: "flex", gap: "12px" }}
          <button style={S.btn} onClick={copyQuote}>{copied ? "✓ Copied"
            <button style={S.btnGhost} onClick={() => { setQResult(""); s
          </div>
        }}
      </div>
    )}
  </div>
  )}
</div>

<div style={{ borderTop: "1px solid #1f1f1f", padding: "16px 24px", display
  <div style={{ fontSize: "9px", letterSpacing: "2px", color: "#2a2a2a" }}>
    <div style={{ fontSize: "9px", letterSpacing: "1px", color: "#2a2a2a" }}>
  </div>
</div>
);
}

```