

Hertie School/SCRIPTS Data Science Workshop Series

Session 1: A gentle introduction to base R and RStudio

*Therese Anders**

Allison Koh†

January 10, 2020

Plan for this workshop series

This workshop series is geared toward learning basic data management in R. This includes tasks like manipulating variables, creating new variables, subsetting data, reshaping data, and merging. We will also cover some introductory regular expression applications. In this workshop series we will cover only basic visualization methods in R. Aspects like data analysis, web-scraping, or higher-level statistical programming are not covered.

Scheduled sessions:

1. **Introduction to R** (working directories, arithmetic, logical operators, basic indexing, data types, basic functions such as `sum`, `mean`, `names`, `seq`, `rep`, installing packages, reading and writing data, dealing with missing data, data frames, indexing on data frames, getting an overview of the data with numerical and graphical summaries).
2. **Modern data management in R using the tidyverse** (`dplyr`, `tidyr`, `readr`, and `lubridate` packages)

Getting started in R

R is a programming language for statistical computing and data visualization, that is a open source alternative to commercial statistical packages such as Stata or SPSS. R is maintained and developed by a vibrant community of programmers and statisticians and offers many user-written packages to extend basic functionality.

In this workshop, we will be using R together with the integrated development environment (IDE) **RStudio**. In addition to offering a ‘cleaner’ programming development than the basic R editor, RStudio offers a large number of added functionalities for integrating code into documents, built-in tools and web-development. To get started, please download the latest version of RStudio and R from this website:

<https://www.rstudio.com/products/rstudio/download/>

Getting Help

The key to learning R is: **Google!** This workshop will give you an overview over basic R functions, but to really learn R you will have to actively use it yourself, trouble shoot, ask questions, and google! The R mailing list and other help pages such as <http://stackoverflow.com> offer a rich archive of questions and answers by the R community. For example, if you google “recode data in r” you will find a variety of useful websites explaining how to do this on the first page of the search results. Also, don’t be surprised if you find a variety of different ways to execute the same task.

RStudio also has a useful help menu. In addition, you can get information on any function or integrated data set in R through the console, for example:

*Instructor, Hertie School/SCRIPTS, anders@hertie-school.org.

†Teaching assistant, Hertie School, kohallison3@gmail.com.

```
?plot
```

In addition, there are a lot of free R comprehensive guides, such as Quick-R at <http://www.statmethods.net> or the R cookbook at <http://www.cookbook-r.com>.

Working Directories

R needs to know where to look for files if you want to read data and where to store files if you write data. This includes the code you will be typing in this session. The `getwd()` command returns the current working directory. We can change the working directory with `setwd()` (see below).

Think of your computer as a filing cabinet. During the course of this workshop, you will be writing a number of R scripts, that are essentially text files with commands for R. In order to execute these files, we need to tell R where to look for the list of commands we want to execute. Setting a working directory is analogous to telling R in which file in the filing cabinet we stored our document (code) and into which file in the filing cabinet to put new documents (such as graphs, new data frames, new code).

```
getwd() # Prints the current working directory
```

```
## [1] "/Users/thereseanders/Dropbox/Dissertation/TerritorialControl/Analysis/tc_hmm_decay_191011/ds-wor
```

```
#setwd("/cloud/project")
```

Important for Windows users: In R, the backslash is an escape character (we will be talking more about this in the session about `stringr`). Therefore, entering file paths is a little different in Windows than on a Mac. On a windows machine you would enter:

```
setwd("C:/Documents and Settings/Data")
```

OR

```
setwd("C:\\Documents and Settings\\Data")
```

Arithmetic in R

You can use R as a calculator!

	Operator	Example
Addition	+	2+4
Subtraction	-	2-4
Multiplication	*	2*4
Division	/	4/2
Exponentiation	^	2^4
Square Root	<code>sqrt()</code>	<code>sqrt(144)</code>
Absolute Value	<code>abs()</code>	<code>abs(-4)</code>

```
4*9
```

```
## [1] 36
```

```
sqrt(144)
```

```
## [1] 12
```

Just like any regular calculator, you have to pay attention to the order of operations! Example:

```
6 * 8 - sqrt(7) + abs(-10) * (4/5)
```

```
## [1] 53.35425
```

```
6 * (8 - sqrt(7)) + abs(-10) * (4/5)
```

```
## [1] 40.12549
```

Logical operators

	Operator
Less than	<
Less than or equal to	<=
Greater than	>
Greater than or equal to	>=
Exactly equal to	==
Not equal to	!=
Not x	!x
x or y	x y
x and y	x & y

Logical operators are incredibly helpful for any type of exploratory analysis, data cleaning and/or visualization task.

```
4 > 2
```

```
## [1] TRUE
```

```
4 <= 2
```

```
## [1] FALSE
```

Objects in R

Assigning values to objects

R stores information as an *object*. You can name objects whatever you like. Just remember to not use names that are reserved for build-in functions or functions in the packages you use, such as `sum`, `mean`, or `abs`. Most of the time, R will let you use these as names, but it leads to confusion in your code.

A few things to remember

- Do not use special characters such as `$` or `%`. Common symbols that are used in variable names include `.` or `_`.
- Remember that R is case sensitive.
- To assign values to objects, we use the assignment operator `<-`. Sometimes you will also see `=` as the assignment operator. This is a matter of preference and subject to debate among R programmers. Personally, I use `<-` to assign values to objects and `=` within functions.
- The `#` symbol is used for commenting and demarcation. Any code following `#` will not be executed.

Below, R stores the result of the calculation in an object named `result`. We can access the value by referring to the object name.

```
result <- 5/3  
result
```

```
## [1] 1.666667
```

If we assign a different value to the object, the value of the object will be changed.

```
result <- 5-3
result
```

```
## [1] 2
```

Vectors

R can deal with a variety of data types, including vectors, scalars, matrices, data frames, factors, and lists. Today, we will focus on vectors.

A **vector** is one of the simplest type of data you can work with in R. “A vector or a one-dimensional array simply represents a collection of information stored in a specific order” (Imai 2017: 14). It is essentially a list of data of a single type (either numerical, character, or logical). To create a vector, we use the function `c()` (‘concatenate’) to combine separate data points. The general format for creating a vector in R is as follows: `name_of_vector <- c(“what you want to put into the vector”)`. Suppose, we have data on the population in millions for the five most populous countries in 2016. The data come from the World Bank.

```
pop1 <- c(1379, 1324, 323, 261, 208)
pop1
```

```
## [1] 1379 1324 323 261 208
```

We can use the function `c()` to combine two vectors. Suppose we had data on 5 additional countries.

```
pop2 <- c(194, 187, 161, 142, 127)
pop <- c(pop1, pop2)
pop
```

```
## [1] 1379 1324 323 261 208 194 187 161 142 127
```

Variable types

There are four main variable types you should be familiar with:

- **Numerical:** Any number. **Integer** is a numerical variable without any decimals.
- **Character:** This is what Stata (and other programming languages such as Python) calls a string. We typically store any alphanumeric data that is not ordered as a character vector.
- **Logical:** A collection of TRUE and FALSE values.
- **Factor:** Think about it as an ordinal variable, i.e. an ordered categorical variable.

First, let's check which variable type our population data were stored in. The output below tells us that the object `pop` is of class numeric, and has the dimensions `[1:10]`, that is 10 elements in one dimension.

```
str(pop)
```

```
## num [1:10] 1379 1324 323 261 208 ...
```

Suppose, we wanted to add information on the country names. We can enter these data in character format. To save time, we will only do this for the five most populous countries.

```
cname <- c("CHN", "IND", "USA", "IDN", "BRA")
str(cname)
```

```
## chr [1:5] "CHN" "IND" "USA" "IDN" "BRA"
```

Now, let's code a logical variable that shows whether the country is in Asia or not. Note that R recognizes both TRUE and T (and FALSE and F) as logical values.

```
asia <- c(TRUE, TRUE, F, T, F)
str(asia)
```

```
## logi [1:5] TRUE TRUE FALSE TRUE FALSE
```

Lastly, we define a factor variable for the regime type of a country in 2016. This variable can take on one of four values (based on data from the Economist Intelligence Unit): Full Democracy, Flawed Democracy, Hybrid Regimes, and Autocracy. Note that empirically, we don't have a "hybrid category" here. We could define an empty factor level, but we will skip this step here.

```
regime <- c("Autocracy", "FlawedDem", "FullDem", "FlawedDem", "FlawedDem")
regime <- as.factor(regime)
str(regime)
```

```
## Factor w/ 3 levels "Autocracy","FlawedDem",...: 1 2 3 2 2
```

Data types are important! R will not perform certain operations if you don't get the variable type right. The good news is that we can switch between data types. This can sometimes be tricky, especially when you are switching from a factor to a numerical type¹. We won't go into this too much here; just remember: Google is your friend!

Let's convert the factor variable `regime` into a character. Also, for practice, let's convert the `asia` variable to character and back to logical.

```
regime <- as.character(regime)
str(regime)
```

```
## chr [1:5] "Autocracy" "FlawedDem" "FullDem" "FlawedDem" "FlawedDem"
```

```
asia <- as.character(asia)
str(asia)
```

```
## chr [1:5] "TRUE" "TRUE" "FALSE" "TRUE" "FALSE"
```

```
asia <- as.logical(asia)
str(asia)
```

```
## logi [1:5] TRUE TRUE FALSE TRUE FALSE
```

Exercise 1: Why won't R let us do the following?

```
no_good <- (a,b,c)
```

```
no_good_either <- c(one, two, three)
```

Exercise 2: What's the difference? (Bonus: What do you think is the class of the output vector?)

```
diff <-c(TRUE, "TRUE")
```

Exercise 3: What is the class of the following vector?

```
vec <- c("1", "2", "3")
```

Vector operations

You can do a variety of things like have R print out particular values or ranges of values in a vector, replace values, add additional values, etc. We will not get into all of these operations today, but be aware that (for all practical purposes) if you can think of a vector manipulation operation, R can probably do it.

¹Sometimes you have to do a work around, like switching to a character first, and then converting the character to numeric. You can concatenate commands: `myvar <- as.numeric(as.character(myvar))`.

We can do arithmetic operations on vectors! Let's use the vector of population counts we created earlier and double it.

```
pop1

## [1] 1379 1324 323 261 208
pop1_double <- pop1 * 2
pop1_double

## [1] 2758 2648 646 522 416
```

Exercise 4: What do you think this will do?

```
pop1 + pop2
```

Exercise 5: And this?

```
pop_c <- c(pop1, pop2)
```

Functions

There are a number of special functions that operate on vectors and allow us to compute measures of location and dispersion.

	Function
<code>min()</code>	Returns the minimum of the values or object.
<code>max()</code>	Returns the maximum of the values or object.
<code>sum()</code>	Returns the sum of the values or object.
<code>length()</code>	Returns the length of the values or object.
<code>mean()</code>	Returns the average of the values or object.
<code>median()</code>	Returns the median of the values or object.
<code>var()</code>	Returns the variance of the values or object.
<code>sd()</code>	Returns the standard deviation of the values or object.

```
min(pop)

## [1] 127
max(pop)

## [1] 1379
mean(pop)

## [1] 430.6
```

Exercise 6: Using functions in R, how else could we compute the mean population value?

```
## [1] 430.6
```

Accessing elements of vectors

There are many ways to access elements that are stored in an object. Here, we will focus on a method called *indexing*, using square brackets as an operator.

Below, we use square brackets and the index 1 to access the first element of the top 5 population vector and the corresponding country name vector.

```
pop1[1]
```

```
## [1] 1379
```

```
cname[1]
```

```
## [1] "CHN"
```

We can use indexing to access multiple elements of a vector. For example, below we use indexing to implicitly print the second and fifth elements of the population and the country name vectors, respectively.

```
pop[c(2,5)]
```

```
## [1] 1324 208
```

```
cname[c(2,5)]
```

```
## [1] "IND" "BRA"
```

We can assign the first element of the population vector to a new object called `first`.

```
first <- pop[1]
```

Below, we make a copy of the country name vector and delete the *last* element. Note, that we can use the `length()` function to achieve the highest level of *generalizability* in our code. Using `length()`, we do not need to know the index of the last element of our vector to drop the last element.

```
cname_copy <- cname
```

```
## Option 1: Dropping the 5th element
```

```
cname_copy[-5]
```

```
## [1] "CHN" "IND" "USA" "IDN"
```

```
## Option 2 (for generalizability): Getting the last element and dropping it.
```

```
length(cname_copy)
```

```
## [1] 5
```

```
cname_copy[-length(cname_copy)]
```

```
## [1] "CHN" "IND" "USA" "IDN"
```

Indexing can be used to alter values in a vector. Suppose, we notice that we wrongly entered the fifth element of the regime type vector (or the regime type changed).

```
regime
```

```
## [1] "Autocracy" "FlawedDem" "FullDem" "FlawedDem" "FlawedDem"
```

```
regime[5] <- "FullDem"
```

```
regime
```

```
## [1] "Autocracy" "FlawedDem" "FullDem" "FlawedDem" "FullDem"
```

Exercise 7: We made even more mistakes when entering the data! We want to subtract 10 from the third and fifth element of the top 5 population vector. *How would you do it?*

More functions

The myriad of functions that are either built-in to base R or parts of user-written packages are the greatest strength of R. For most applications we encounter in our daily programming practice, R already has a function, or someone smart wrote one. Below, we introduce a few additional helpful functions from base R.

	Function
<code>seq()</code>	Returns sequence from input1 to input2 by input3.
<code>rep()</code>	Repeats input1 input2 number of times.
<code>names()</code>	Returns the names (labels) of objects.
<code>which()</code>	Returns the index of objects.

Let's create a vector of indices for our top 5 population data.

```
cindex <- seq(from = 1, to = length(pop1), by = 1)
cindex
```

```
## [1] 1 2 3 4 5
```

We can use the `rep()` function to repeat data.

```
rep(30, 5)
```

```
## [1] 30 30 30 30 30
```

Exercise 8 Use `rep()` and `seq` to print the following data.

```
## [1] 1.0 1.5 2.0 2.5 3.0 1.0 1.5 2.0 2.5 3.0
```

Suppose, we wanted to record whether we had completed the data collection process for the top 10 most populous countries. First, suppose we completed the process on every second country.

```
completed <- rep(c("yes","no"), 5)
completed
```

```
## [1] "yes" "no" "yes" "no" "yes" "no" "yes" "no" "yes" "no"
```

Now suppose that we have completed the data collection process for the first 5 countries, but not the latter 5 countries (we don't have their names, location, or regime type yet).

```
completed2 <- rep(c("yes","no"), each = 5)
completed2
```

```
## [1] "yes" "yes" "yes" "yes" "yes" "no" "no" "no" "no" "no"
```

We can give our data informative labels. Let's use the country names vector as labels for our top 5 population vector.

```
names(pop1)
```

```
## NULL
```

```
cname
```

```
## [1] "CHN" "IND" "USA" "IDN" "BRA"
```

```
names(pop1) <- cname
names(pop1)
```

```
## [1] "CHN" "IND" "USA" "IDN" "BRA"
```

```
pop1
```

```
## CHN IND USA IDN BRA
## 1379 1324 323 261 208
```

We can use labels to access data using indexing and logical operators. Suppose, we wanted to access the population count for Brazil in our top 5 population data.


```
pop1[names(pop1) == "BRA"]
```

```
## BRA  
## 208
```

Exercise 9 Access all top 5 population ratings that are greater or equal than the mean value of population ratings.

```
## [1] 699  
## CHN IND  
## 1379 1324
```

Exercise 10 Access all top 5 population ratings that are less than the population of the most populous country, but not the US.

```
## IND IDN BRA  
## 1324 261 208
```

Operating on multiple vectors simultaneously

We did not work with data frames yet, but remember that our data input is ordered. The first element of the `pop1` vector corresponds with the first element of the `cname`, `regime`, and `asia` vectors. We can use this to run more sophisticated queries on our data.

Suppose, we wanted to know the regime type of Indonesia. Given that our vectors are ordered, we can use indexing to extract the data. First, let's see what happens if we run a simple logical query.

```
cname == "IDN"
```

```
## [1] FALSE FALSE FALSE TRUE FALSE
```

```
regime[cname == "IDN"]
```

```
## [1] "FlawedDem"
```

We can also use the `which()` function that returns the index of the vector element.

```
which(cname == "IDN")
```

```
## [1] 4
```

```
regime[which(cname == "IDN")]
```

```
## [1] "FlawedDem"
```

Exercise 11 Print out the population count for all Asian countries within the top 5 most populous countries that are not autocracies.

```
## IND IDN  
## 1324 261
```

Working with data frames in R

Importing data

Most data formats we commonly use are not native to R and need to be imported. Luckily, there is a variety of packages available to import just about any non-native format. One of the essential libraries is called `foreign` and includes functions to import `.csv`, `.dta` (Stata), `.dat`, `.sav` (SPSS), etc. The `foreign` package is pre-installed. However, we need to tell R that we want to use functions from this package by calling it into the working environment using the `library()` command.

```
library(foreign)
```

In this example, we will use data from the Armed Conflict Location & Event Data Project (ACLED), which offers real-time data and analysis on political violence and protests around the world. This dataset includes riots and protests from January 2010 to December 2019.

When reading the data, remember that you need to either specify the complete file name or change your working directory using `setwd()` to the folder in which you saved the data.

```
mydata <- read.csv("ACLED_countries.csv")
class(mydata)
```

```
## [1] "data.frame"
```

Dimensions of a data frame

Let's find out what this data looks like. First, use the `str()` function to explore the variable names and which data class they are stored in. Note: `int` stands for `integer` and is a special case of the class `numeric`.

```
str(mydata)
```

```
## 'data.frame':   103 obs. of  5 variables:
## $ country      : Factor w/ 102 levels "Afghanistan",...: 1 2 3 4 5 6 7 8 9 10 ...
## $ region       : Factor w/ 10 levels "Caucasus and Central Asia",...: 9 3 6 4 1 1 5 9 3 10
## $ nconflicts   : int  40765 582 7362 1108 3118 12627 1861 16802 293 215 ...
## $ nconflict_no_fatalities: int  23946 581 5321 728 3110 12578 1846 13114 293 165 ...
## $ fatalities   : int  119973 1 8451 13788 8 59 22 4640 0 114 ...
```

If we are only interested in what the variables are called, we can use the `names()` function.

```
names(mydata)
```

```
## [1] "country"      "region"
## [3] "nconflicts"   "nconflict_no_fatalities"
## [5] "fatalities"
```

As we saw in the last session, we can alter the names of vectors by using the `names()` function and indexing. Because data frames are essentially just combinations of vectors, we can do the same for variable names inside data frames. Suppose we want to change the variable `nconflicts`.

```
names(mydata)[3] <- "nconflict"
names(mydata)
```

```
## [1] "country"      "region"
## [3] "nconflict"    "nconflict_no_fatalities"
## [5] "fatalities"
```

We can use the `summary()` function to get a first look at the data.

```
summary(mydata)
```

```
##           country           region      nconflict
## Tunisia      : 2      Europe           :15      Min.       :  1.0
## Afghanistan: 1  Middle East           :15      1st Qu.: 315.5
## Albania      : 1  Western Africa        :15      Median :1250.0
## Algeria      : 1  Eastern Africa         :13      Mean    :6216.3
## Angola       : 1  Caucasus and Central Asia: 8      3rd Qu.:5993.5
## Armenia      : 1  Middle Africa          : 8      Max.    :70734.0
## (Other)      :96      (Other)           :29
```

```
## nconflict_no_fatalities fatalities
## Min. : 1 Min. : 0.0
## 1st Qu.: 289 1st Qu.: 17.5
## Median : 1037 Median : 236.0
## Mean : 4667 Mean : 9543.3
## 3rd Qu.: 4536 3rd Qu.: 7020.0
## Max. : 63665 Max. : 119973.0
##
```

A data frame has two dimensions: rows and columns.

```
nrow(mydata) # Number of rows
```

```
## [1] 103
```

```
ncol(mydata) # Number of columns
```

```
## [1] 5
```

```
dim(mydata) # Rows first then columns.
```

```
## [1] 103 5
```

Accessing elements of a data frame

As a rule, whenever we use two-dimensional indexing in R, the order is: `[row,column]`. To access the first row of the data frame, we specify the row we want to see and leave the column slot following the comma empty.

```
mydata[1,]
```

```
##      country      region nconflict nconflict_no_fatalities fatalities
## 1 Afghanistan Southern Asia    40765             23946      119973
```

We can use the concatenate function `c()` to access multiple rows (or columns) at once. Below we print out the first and second row of the dataframe.

```
mydata[c(1,2),]
```

```
##      country      region nconflict nconflict_no_fatalities fatalities
## 1 Afghanistan Southern Asia    40765             23946      119973
## 2    Albania      Europe      582              581           1
```

We can also access a range of rows by separating the minimum and maximum value with a `:`. Below we print out the first five rows of the dataframe.

```
mydata[1:5,]
```

```
##      country      region nconflict nconflict_no_fatalities fatalities
## 1 Afghanistan Southern Asia    40765             23946      119973
## 2    Albania      Europe      582              581           1
## 3    Algeria Northern Africa    7362             5321
## 4    Angola Middle Africa    1108              728
## 5  Armenia Caucasus and Central Asia    3118             3110
## fatalities
## 1      119973
## 2           1
## 3       8451
## 4      13788
## 5           8
```

If we try to access a data point that is out of bounds, R returns the value `NULL`.

```
mydata[3,3]
```

```
## [1] 7362
```

Exercise 1 Access the element of the data frame `mydata` that is stored in row 1, column 1.

```
## [1] Afghanistan
```

```
## 102 Levels: Afghanistan Albania Algeria Angola Armenia ... Zimbabwe
```

Exercise 2 Access the element of the data frame `mydata` that is stored in column 2, row 3.

```
## [1] Northern Africa
```

```
## 10 Levels: Caucasus and Central Asia Eastern Africa ... Western Africa
```

The \$ operator

The `$` operator in R is used to specify a variable within a data frame. This is an alternative to indexing.

```
mydata$nconflict
```

```
## [1] 40765 582 7362 1108 3118 12627 1861 16802 293 215 459
## [12] 52 765 2105 7760 1919 2621 4625 912 411 312 14519
## [23] 112 10260 50 191 190 5122 215 197 1446 858 1312
## [34] 1121 151 67561 3371 5708 22354 1580 1838 491 374 6427
## [45] 289 39 319 41 2956 83 1294 8857 1365 512 384
## [56] 3193 598 444 213 2177 1250 9070 682 5143 971 15011
## [67] 275 9 54496 6568 9690 5 243 1134 3734 370 6096
## [78] 963 1275 1079 29667 11667 6227 2 3855 12528 70734 68
## [89] 782 7420 321 5756 1 10334 21 4866 30131 4 102
## [100] 503 45298 1148 5891
```

Exercise 3: How would you access all elements of the variable `country` using indexing rather than the `$` operator?

```
## [1] Afghanistan Albania
## [3] Algeria Angola
## [5] Armenia Azerbaijan
## [7] Bahrain Bangladesh
## [9] Belarus Benin
## [11] Bosnia and Herzegovina Botswana
## [13] Bulgaria Burkina Faso
## [15] Burundi Cambodia
## [17] Cameroon Central African Republic
## [19] Chad Croatia
## [21] Cyprus Democratic Republic of Congo
## [23] Djibouti Egypt
## [25] Equatorial Guinea Eritrea
## [27] eSwatini Ethiopia
## [29] Gabon Gambia
## [31] Georgia Ghana
## [33] Greece Guinea
## [35] Guinea-Bissau India
## [37] Indonesia Iran
## [39] Iraq Israel
## [41] Ivory Coast Jordan
## [43] Kazakhstan Kenya
## [45] Kosovo Kuwait
```

##	[47]	Kyrgyzstan	Laos
##	[49]	Lebanon	Lesotho
##	[51]	Liberia	Libya
##	[53]	Madagascar	Malawi
##	[55]	Malaysia	Mali
##	[57]	Mauritania	Moldova
##	[59]	Montenegro	Morocco
##	[61]	Mozambique	Myanmar
##	[63]	Namibia	Nepal
##	[65]	Niger	Nigeria
##	[67]	North Macedonia	Oman
##	[69]	Pakistan	Palestine
##	[71]	Philippines	Qatar
##	[73]	Republic of Congo	Romania
##	[75]	Russia	Rwanda
##	[77]	Saudi Arabia	Senegal
##	[79]	Serbia	Sierra Leone
##	[81]	Somalia	South Africa
##	[83]	South Sudan	Spain
##	[85]	Sri Lanka	Sudan
##	[87]	Syria	Tajikistan
##	[89]	Tanzania	Thailand
##	[91]	Togo	Tunisia
##	[93]	Tunisia	Turkey
##	[95]	Turkmenistan	Uganda
##	[97]	Ukraine	United Arab Emirates
##	[99]	Uzbekistan	Vietnam
##	[101]	Yemen	Zambia
##	[103]	Zimbabwe	
##	102 Levels: Afghanistan Albania Algeria Angola Armenia ... Zimbabwe		
##	[1]	Afghanistan	Albania
##	[3]	Algeria	Angola
##	[5]	Armenia	Azerbaijan
##	[7]	Bahrain	Bangladesh
##	[9]	Belarus	Benin
##	[11]	Bosnia and Herzegovina	Botswana
##	[13]	Bulgaria	Burkina Faso
##	[15]	Burundi	Cambodia
##	[17]	Cameroon	Central African Republic
##	[19]	Chad	Croatia
##	[21]	Cyprus	Democratic Republic of Congo
##	[23]	Djibouti	Egypt
##	[25]	Equatorial Guinea	Eritrea
##	[27]	eSwatini	Ethiopia
##	[29]	Gabon	Gambia
##	[31]	Georgia	Ghana
##	[33]	Greece	Guinea
##	[35]	Guinea-Bissau	India
##	[37]	Indonesia	Iran
##	[39]	Iraq	Israel
##	[41]	Ivory Coast	Jordan
##	[43]	Kazakhstan	Kenya
##	[45]	Kosovo	Kuwait

```
## [47] Kyrgyzstan      Laos
## [49] Lebanon          Lesotho
## [51] Liberia          Libya
## [53] Madagascar       Malawi
## [55] Malaysia         Mali
## [57] Mauritania       Moldova
## [59] Montenegro       Morocco
## [61] Mozambique       Myanmar
## [63] Namibia          Nepal
## [65] Niger            Nigeria
## [67] North Macedonia Oman
## [69] Pakistan         Palestine
## [71] Philippines      Qatar
## [73] Republic of Congo Romania
## [75] Russia           Rwanda
## [77] Saudi Arabia     Senegal
## [79] Serbia           Sierra Leone
## [81] Somalia          South Africa
## [83] South Sudan      Spain
## [85] Sri Lanka        Sudan
## [87] Syria            Tajikistan
## [89] Tanzania         Thailand
## [91] Togo             Tunisia
## [93] Tunisia          Turkey
## [95] Turkmenistan     Uganda
## [97] Ukraine          United Arab Emirates
## [99] Uzbekistan       Vietnam
## [101] Yemen            Zambia
## [103] Zimbabwe
## 102 Levels: Afghanistan Albania Algeria Angola Armenia ... Zimbabwe
```

Exercise 4: Print out every second element from the variable `nconflict` using indexing methods and the sequence function `seq()`.

```
## [1] 40765 7362 3118 1861 293 459 765 7760 2621 912 312
## [12] 112 50 190 215 1446 1312 151 3371 22354 1838 374
## [23] 289 319 2956 1294 1365 384 598 213 1250 682 971
## [34] 275 54496 9690 243 3734 6096 1275 29667 6227 3855 70734
## [45] 782 321 1 21 30131 102 45298 5891
```

Exercise 5: What are two ways to find the mean value of the variable `nconflict` using indexing (i.e. not using the `$` operator)?

```
## Warning in mean.default(mydata[, 2]): argument is not numeric or logical:
## returning NA
## [1] NA
## [1] 6216.272
```

Exercise 6: How would you find the maximum value for number of conflicts using the `$` operator?

```
## [1] 70734
```

Exercise 7: Print the country that corresponds to the maximum world population value using the `$` operator and indexing!

```
## [1] Syria
## 102 Levels: Afghanistan Albania Algeria Angola Armenia ... Zimbabwe
```

NAs in R

NA is how R denotes missing values. For certain functions, NAs cause problems.

```
vec <- c(4, 1, 2, NA, 3)
mean(vec) #Result is NA!
```

```
## [1] NA
```

```
sum(vec) #Result is NA!
```

```
## [1] NA
```

We can tell R to remove the NA and execute the function on the remainder of the data.

```
mean(vec, na.rm = T)
```

```
## [1] 2.5
```

```
sum(vec, na.rm = T)
```

```
## [1] 10
```

Adding observations

First, let's add another observation to the data. Suppose we wanted to add an observation for Germany, which will be a missing value. We can use the same operations we used for vectors to add data. Here, we will use the `rbind()` function to do so. `rbind()` stands for “row bind.” Save the output in a new data frame!

```
obs <- c("Germany", NA, NA)
mydata_new <- rbind(mydata, obs)
```

```
## Warning in `[<-.factor`(`*tmp*`, ri, value = "Germany"): invalid factor
## level, NA generated
```

```
dim(mydata_new)
```

```
## [1] 104 5
```

We can also create new variables that use information from the existing data. If we know the number of conflicts without fatalities by country, we can calculate the number of conflicts *with* fatalities to generate the variable `nconflict_fatalities`. By using the `$` operator, we can directly assign the new variable to the data frame `mydata_new`.

```
mydata$nconflict_fatalities <- mydata$nconflict - mydata$nconflict_no_fatalities
head(mydata, 3) #prints out the first 3 rows of the data frame
```

```
##      country      region nconflict nconflict_no_fatalities fatalities
## 1 Afghanistan Southern Asia    40765             23946      119973
## 2   Albania      Europe         582              581           1
## 3   Algeria Northern Africa     7362             5321       8451
##  nconflict_fatalities
## 1             16819
## 2              1
## 3             2041
```

Saving data

Suppose we wanted to save this newly created data frame. We have multiple options to do so. If we wanted to save it as a native `.RData` format, we would run the following command.

```
# Make sure you specified the right working directory!
# save(mydata, file = "mydata_new.RData")
```

Most of the time, however, we would want to save our data in formats that can be read by other programs as well. .csv is an obvious choice. After saving the new file, check the folder that is your working directory to see whether the newly saved file shows up there!

```
# write.csv(mydata_new, file = "mydata_new.csv")
```

(Very basic) data visualization

Today, we will be covering some basics of data visualization in R using the native plotting functions. For more advanced data visualization functions, see the **ggplot2** package and the related material for a two-session introductory workshop on data visualization <https://github.com/thereseanders/Workshop-Intro-to-ggplot2>.


Basic graphical summaries of data

Type	Operator
Histogram	<code>hist()</code>
Stem and leaf plot	<code>stem()</code>
Boxplot	<code>boxplot()</code>
Kernel density plot	<code>plot(density())</code>
Basic scatterplot	<code>plot()</code>

Boxplot of population density

We can get an overview of the number of conflicts per country using the `boxplot()` function.

```
boxplot(mydata$nconflict)
```



Suppose we wanted to know whether there are more conflicts with fatalities on average for countries with a higher overall number of conflicts. Let's first look at the distribution of number of conflicts.

```
summary(mydata$nconflict)
```

```
##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
##       1.0   315.5  1250.0  6216.3  5993.5 70734.0
```

Create a new dummy variable that codes whether a state has a relatively high number of conflicts (greater than the median).

```
median(mydata$fatalities)
```

```
## [1] 236
```



```
mydata$fatalities_high <- ifelse(mydata$fatalities > median(mydata$fatalities), 1, 0)
head(mydata$fatalities_high)
```


```
## [1] 1 0 1 1 0 0
```

```
table(mydata$fatalities_high) # We split the observations exactly in half.
```

```
##
##  0  1
## 52 51
```

We can display two indicators in the same boxplot. We can use this feature to answer the question whether larger states are on average more or less dense than smaller states.


```
boxplot(mydata$nconflict ~ mydata$fatalities_high)
```



Histogram of number of conflicts


```
hist(mydata$nconflict, breaks=100)
```

Histogram of mydata\$nconflict



Density plot of fatalities


```
plot(density(mydata$fatalities))
```



Basic scatter plots

How does population size vary with area? Are they correlated at all?

```
plot(mydata$fatalities, mydata$nconflict)
```




Basic graphic options

Aside from arguably not being very informative, the plot above is not very pretty. Let's give it titles, use color and shapes!

```
plot(mydata$fatalities, mydata$nconflict,
     main = "ACLED (2010-2019)", #Adding a main title.
     xlab = "Fatalities", #Adding a x-axis title.
     ylab = "Number of Conflicts", #Adding a y-axis title.
     col = "tomato", #Changing the color of the data points.
     pch = 18) #Changing the shape
```

ACLED (2010–2019)



Yeah, ok. Its not much prettier (especially the labeling on the axes), but you get the point...

A few additional notes on graphical options:

- R can display any color in the RBG or HEX system. However it also has a ton of colors that you can just refer to by name, see <http://www.stat.columbia.edu/~tzheng/files/Rcolor.pdf>.
- Same with the shapes and line types, see http://www.cookbook-r.com/Graphs/Shapes_and_line_types/.
- R colors in all their glory: <http://www.stat.columbia.edu/~tzheng/files/Rcolor.pdf>.

Sources

Economist Intelligence Unit (2017): *Democracy Index*. <https://infographics.economist.com/2017/DemocracyIndex/>.

Imai, Kosuke (2017): *Quantitative Social Science. An Introduction*. Princeton and Oxford: Princeton University Press.

Raleigh, Clionadh, Andrew Linke, Håvard Hegre and Joakim Karlsen. 2010. Introducing ACLED – Armed Conflict Location and Event Data. *Journal of Peace Research* 47(5), 651-660.

World Bank (2017): *Population, total*. <https://data.worldbank.org/indicator/sp.pop.totl?end=2016&start=2015>.