

A row of white medium-duty trucks, likely Kenworth models, are parked in front of a large, modern warehouse. The scene is set at dusk or dawn, with a dramatic sky featuring large, dark clouds and a soft glow from the low sun. The warehouse has a long, low profile with a series of lights along its side. The wet pavement in the foreground reflects the lights from the trucks and the warehouse, creating a shimmering effect.

MEDIUM TRUCK RADIAL PRODUCT GUIDE

ROADONE

Main Features

☑ All-Position Steer Tire:
Versatile design suitable for various applications.

☑ Waved Channel Design:
Reduces groove bottom strain for improved performance and durability.

☑ Wide, Solid Shoulder Ribs:
Provide enhanced resistance to maneuvering scrub and extend tread life.

☑ Optimized Rib Distribution:
Ensures added stiffness for greater stability and even wear.



RL616

Item	Size	OD (Inch)	SW (Inch)	T/D X/32	Load Index	Max Load (Lbs)	PSI
RL1309	11R22.5/14	41.3	10.8	21	144/142	6175/5840	105/105
RL1311	11R22.5/16	41.3	10.8	21	146/143	6610/6005	120/120
RL1314	11R24.5/14	43.3	10.8	21	146/143	6610/6005	105/105
RL1316	11R24.5/16	43.3	10.8	21	149/146	7160/6610	120/120
RL1321	295/75R22.5/14	39.8	11.6	21	144/141	6175/5675	110/110
RL1319	285/75R24.5/14	41.4	11.0	21	144/141	6175/5675	110/110

ROADONE

Main Features

☑ Long-Haul Drive Tire: Premium close-shoulder design for reliable performance.

☑ Wider Footprint: Enhances traction and promotes even wear for extended tire life.

☑ Block Tread Pattern: Reduces tread squirm for improved stability.

☑ Stone Ejectors: Minimize stone retention to protect the tire from damage.



RL716

Item	Size	OD (Inch)	SW (Inch)	T/D X/32	Load Index	Max Load (Lbs)	PSI
RL1310	11R22.5/14	41.9	10.8	30	144/142	6175/5840	105/105
RL1312	11R22.5/16	41.9	10.8	30	146/143	6610/6005	120/120
RL1315	11R24.5/14	43.9	10.8	30	146/143	6610/6005	105/105
RL1317	11R24.5/16	43.9	10.8	30	149/146	7160/6610	120/120
RL1322	295/75R22.5/14	40.4	11.6	28	144/141	6175/5675	110/110
RL1320	285/75R24.5/14	41.9	11.0	28	144/141	6175/5675	110/110

ROADONE

Main Features

- ☑ On/Off-Highway Tire: Built for durability in mixed-service conditions.
- ☑ Advanced Cut and Chip Design: New-generation pattern enhances resistance to damage.
- ☑ Cut/Chip-Resistant Tread Compound: Increases toughness for extended performance.
- ☑ High-Scrub Application: Engineered to withstand demanding, abrasive environments.



RL916

Item	Size	OD (Inch)	SW (Inch)	T/D X/32	Load Index	Max Load (Lbs)	PSI
RL1313	11R22.5/16	41.5	11.0	21.4	146/143	6610/6005	120/120
RL1318	11R24.5/16	43.5	11.0	21.4	149/146	7160/6610	120/120

ROADONE

Main Features

- ☑ Long-Haul Trailer Tire: Designed for efficiency and reliability in extended journeys.
- ☑ Optimized Rib Pattern: Ensures even wear and maximizes tread life for increased mileage.
- ☑ Enhanced Groove Structure: Promotes efficient water evacuation for improved wet traction.
- ☑ Tough Sidewall Protection: Resists damage from turning forces for enhanced durability.



T810

Item	Size	OD (Inch)	SW (Inch)	T/D X/32	Load Index	Max Load (Lbs)	PSI
RL1002	11R22.5/14	41.5	11.0	13.5	144/142	6175/5840	105/105
RL1012	11R24.5/14	43.5	11.0	13.5	146/143	6610/6005	105/105
RL1022	295/75R22.5/14	39.9	11.7	13.5	144/141	6175/5675	110/110
RL1047	285/75R24.5/14	41.3	11.1	13.5	144/141	6175/5675	110/110
RL1031	255/70R22.5/16	36.6	10.0	13.5	140/137	5510/5070	120/120

ROADONE

Main Features

- ☑ Aggressive Tread Pattern: Designed for excellent traction on mixed and off-road surfaces.
- ☑ Reinforced Sidewalls: Built to resist damage in rugged conditions for added durability.
- ☑ Wide Grooves: Facilitate efficient debris ejection to maintain performance.
- ☑ Tough Tread Compound: Resists cuts, chips and tears.



LLA08

Item	Size	OD (Inch)	SW (Inch)	T/D X/32	Load Index	Max Load (Lbs)	PSI
RL1009	11R22.5/16	41.5	11.0	18.9	146/143	6610/6005	120/120
RL1019	11R24.5/16	43.5	11.0	20.8	149/146	7160/6610	120/120

ROADONE

Main Features

- ☑ Long-Haul Highway Tire: Engineered for optimal performance in over-the-road applications.
- ☑ Decoupling Groove Design: Enhances stability and tread durability.
- ☑ Even Tread Wear: Promotes consistent performance throughout the tire's lifespan.
- ☑ Reliable Long-Distance Service: Ideal for extended highway use with minimal downtime.



LLF16

Item	Size	OD (Inch)	SW (Inch)	T/D X/32	Load Index	Max Load (Lbs)	PSI
RL1001	11R22.5/14	41.5	11.0	18.3	144/142	6175/5840	105/105
RL1006	11R22.5/16	41.5	11.0	18.3	146/143	6610/6005	120/120
RL1011	11R24.5/14	43.5	11.0	18.3	146/143	6610/6005	105/105
RL1016	11R24.5/16	43.5	11.0	18.3	149/146	7160/6610	120/120
RL1021	295/75R22.5/14	39.9	11.7	18.3	144/141	6175/5675	110/110
RL1026	285/75R24.5/14	41.3	11.1	18.3	144/141	6175/5675	110/110

ROADONE

Main Features

- ☑ Versatile Tread Design: Provides dependable performance in both on-highway and mixed-service applications.
- ☑ Wide Grooves: Promote excellent water evacuation and grip in various conditions.
- ☑ Durable Block Pattern: Ensures resistance to wear and damage for extended service life.
- ☑ Reinforced Sidewalls: Built for stability and protection against external impacts.



LLA28

Item	Size	OD (Inch)	SW (Inch)	T/D X/32	Load Index	Max Load (Lbs)	PSI
RL1039	425/65R22.5/20	44.3	16.6	22	165	11350	120

ROADONE

Main Features

- ☑ Fuel-Saving Performance: Continuous rib design lowers rolling resistance for better mileage.
- ☑ Wet Grip Technology: Fine siping ensures safety in wet and slippery conditions.
- ☑ Quiet Ride: Reduced road noise thanks to optimized tread alignment.
- ☑ Enhanced Durability: Durable tread compound extends the tire's lifespan.



LLF02

Item	Size	OD (Inch)	SW (Inch)	T/D X/32	Load Index	Max Load (Lbs)	PSI
RL1041	315/80R22.5/20	42.4	12.3	18.3	156/150	8820/7385	123/123

ROADONE

Main Features

☑ All-Weather Performance:
Multi-groove design offers exceptional traction in both wet and dry conditions.

☑ Improved Water Dispersion:
Deep channels reduce the risk of hydroplaning, ensuring safety.

☑ Long-Lasting Tread Life:
High-density tread composition provides extended durability.

☑ Comfortable Ride Quality:
Enhanced contact patch reduces vibrations for a smooth driving experience.



F820

Item	Size	OD (Inch)	SW (Inch)	T/D X/32	Load Index	Max Load (Lbs)	PSI
RL1058	215/75R17.5/16	30.2	8.3	15.7	135/133J	4805/4540	123
RL1034	225/70R19.5/12	31.9	8.9	15.7	125/123M	3640/3415	95
RL1056	225/70R19.5/14	31.9	8.9	15.7	128/126M	3970/3750	110
RL1059	235/75R17.5/16	31.4	9.2	16.4	141/140L	5675/5510	123
RL1035	245/70R19.5/14	33.0	9.8	16.4	133/131M	4540/4300	110
RL1416	255/70R22.5/16	36.6	10.0	17.6	140/137M	5510/5070	120
RL1036	265/70R19.5/16	34.1	10.3	17.0	140/138L	5510/5200	112
RL1304	275/70R22.5/16	37.7	10.9	18.3	148/145M	6945/6393	130
RL1510	275/70R22.5/18	37.7	10.9	18.3	150/148M	7385/6945	130

ROADONE

Main Features

- ☑ High Mileage Capability: Zigzag tread design ensures even wear for extended tire life.
- ☑ Improved Traction: Deep grooves provide better grip on wet and slippery surfaces.
- ☑ Optimized Rolling Resistance: Low resistance for enhanced fuel efficiency.
- ☑ Quiet Performance: Uniform tread blocks reduce road noise for smoother rides.



LLA18

Item	Size	OD (Inch)	SW (Inch)	T/D X/32	Load Index	Max Load (Lbs)	PSI
RL1037	385/65R22.5/20	42.2	15.3	20.8	160	9920	130

ROADONE

Main Features

☑ **Enhanced Drainage Performance:** Straight-line grooves ensure superior water dispersion, reducing hydroplaning.

☑ **Durable Tread Design:** Reinforced structure withstands high loads for long-haul operations.

☑ **Reduced Rolling Resistance:** Advanced pattern minimizes energy loss for better fuel efficiency.

☑ **Improved Road Contact:** Optimized tread contact patch enhances stability and control.



D928

Item	Size	OD (Inch)	SW (Inch)	T/D X/32	Load Index	Max Load (Lbs)	PSI
RL1003	11R22.5/14	41.7	11.0	25.8	144/142	6175/5840	105/105
RL1007	11R22.5/16	41.7	11.0	25.8	146/143	6610/6005	120/120
RL1013	11R24.5/14	43.7	11.0	25.8	146/143	6610/6005	105/105
RL1017	11R24.5/16	43.7	11.0	25.8	149/146	7160/6610	120/120
RL1023	295/75R22.5/14	40.2	11.7	25.8	144/141	6175/5675	110/110
RL1028	285/75R24.5/14	41.6	11.1	25.8	144/141	6175/5675	110/110

ROADONE

Main Features

- ☑ Superior Durability: Reinforced structure handles heavy loads with ease.
- ☑ Outstanding Grip: Hexagonal tread blocks deliver exceptional traction on rugged terrains.
- ☑ Self-Cleaning Properties: High void ratio efficiently removes mud and debris.
- ☑ Enhanced Stability: Wide shoulders improve cornering and overall vehicle balance.



LLA38

Item	Size	OD (Inch)	SW (Inch)	T/D X/32	Load Index	Max Load (Lbs)	PSI
RL1038	385/65R22.5/20	42.2	15.3	20.8	160	9920	130
RL1040	425/65R22.5/20	44.3	16.6	22.0	165	11355	120
RL1043	445/65R22.5/20	45.3	17.5	22.7	168	12345	120

ROADONE

Main Features

- ☑ All-Terrain Versatility: Zigzag grooves enhance performance across various road conditions.
- ☑ Consistent Wear: Balanced tread pattern minimizes irregular wear for longer lifespan.
- ☑ Improved Water Dispersion: Deep channels effectively reduce hydroplaning.
- ☑ Enhanced Driving Comfort: Optimized tread design reduces vibrations and noise.



LLA78

Item	Size	OD (Inch)	SW (Inch)	T/D X/32	Load Index	Max Load (Lbs)	PSI
RL1170	235/75R17.5/18	31.4	9.2	16.4	143/141J	6005/5675	127/127
RL1033	235/75R17.5/16	31.4	9.2	16.4	141/140	5675/5510	123/123



Main Features

- ☑ Fuel-Efficient Design: Continuous ribs reduce rolling resistance for improved mileage.
- ☑ Quiet Operation: Fine siping pattern minimizes road noise for a comfortable ride.
- ☑ Consistent Performance: Balanced tread wear ensures reliable operation over long distances.
- ☑ Optimized Load Capacity: Designed for heavy loads with evenly distributed weight support.



F816

Item	Size	OD (Inch)	SW (Inch)	T/D X/32	Load Index	Max Load (Lbs)	PSI
RL2001	11R22.5/14	41.2	11.0	18.3	144/142M	6175/5840	105
RL2002	11R22.5/16	41.2	11.0	18.3	146/143M	6610/6005	120
RL2007	11R24.5/14	43.2	11.0	18.3	146/143M	6610/6005	105
RL2008	11R24.5/16	43.2	11.0	18.3	149/146M	7160/6610	120
RL2009	295/75R22.5/14	39.6	11.5	18.3	144/141M	6175/5675	110
RL2012	285/75R24.5/14	41.0	11.0	18.3	144/141M	6175/5675	110
RL2014	295/75R22.5/16	39.6	11.5	18.3	146/143M	6610/6005	120

ROADONE

Main Features

- ☑ **Balanced Wear Resistance:** Hexagonal blocks and optimized contact patch prevent irregular wear.
- ☑ **Fuel-Efficient Tread:** Low rolling resistance enhances vehicle fuel economy.
- ☑ **All-Season Performance:** Versatile design ensures traction in various weather conditions.
- ☑ **Durable Construction:** Reinforced tread withstands heavy loads and long-haul demands.



LLF86

Item	Size	OD (Inch)	SW (Inch)	T/D X/32	Load Index	Max Load (Lbs)	PSI
RL1032	215/75R17.5/16	30.2	8.3	15.7	135/133	4805/4540	123/123

ROADONE

Main Features

☑ **Heavy-Duty Design:** Reinforced sidewalls for resistance against cuts and punctures.

☑ **Superior Traction:** Interlocking blocks provide reliable grip on soft and uneven surfaces.

☑ **Efficient Mud Ejection:** Wide grooves prevent accumulation of debris, maintaining traction.

☑ **Optimized Load Support:** Designed for stability under high-weight applications.



LLD37

Item	Size	OD (Inch)	SW (Inch)	T/D X/32	Load Index	Max Load (Lbs)	PSI
RL2003	11R22.5/14	41.7	11.0	25.2	144/142	6175/5840	105/105
RL2004	11R22.5/16	41.7	11.0	25.2	146/143	6610/6005	120/120
RL2005	11R24.5/14	43.7	11.0	25.2	146/143	6610/6005	105/105
RL2006	11R24.5/16	43.7	11.0	25.2	149/146	7160/6610	120/120
RL2010	295/75R22.5/14	40.0	11.5	25.2	144/141	6175/5675	110/110
RL2011	285/75R24.5/14	41.3	11.0	25.2	144/141	6175/5675	110/110

ROADONE

Main Features

- ☑ Design: Aggressive block pattern for improved traction on muddy and uneven surfaces.
- ☑ Application: Perfect for construction and mining vehicles requiring off-road capabilities.
- ☑ Performance: Self-cleaning tread design to maintain grip in challenging conditions.
- ☑ Durability: Heavy-duty construction to resist cuts and abrasions in rough environments.



RDP200

Item	Size	OD (Inch)	SW (Inch)	T/D X/32	Load Index	Max Load (Lbs)	PSI
RL2015	11R22.5/14	41.7	11.0	28.3	144/142L	6175/5840	105
RL2016	11R22.5/16	41.7	11.0	28.3	146/143L	6610/6005	120
RL2017	11R24.5/14	43.9	11.0	28.3	146/143L	6610/6005	105
RL2018	11R24.5/16	43.9	11.0	28.3	149/146L	7160/6610	120
RL2019	295/75R22.5/14	40.2	11.7	27.7	144/141L	6175/5675	110
RL2020	285/75R24.5/14	41.6	11.1	27.7	144/141L	6175/5675	110

ROADONE

Main Features

☑ Design: Advanced lug-type pattern for consistent performance on both wet and dry roads.

☑ Application: Optimized for medium to heavy-duty trucks operating in regional or highway settings.

☑ Performance: Enhanced cornering and braking under heavy loads.

☑ Durability: Long-lasting rubber compound for extended mileage.



RDP202

Item	Size	OD (Inch)	SW (Inch)	T/D X/32	Load Index	Max Load (Lbs)	PSI
RL2021	215/75R17.5/16	30.2	8.4	18.9	135/133L	4850/4540	123
RL2022	225/70R19.5/12	31.9	8.9	18.9	125/123M	3640/3415	95
RL2023	225/70R19.5/14	31.9	8.9	18.9	128/126N	3970/3750	110
RL2024	245/70R19.5/14	31.9	8.9	20.2	133/131M	4540/4300	110
RL2025	245/70R19.5/16	31.9	8.9	20.2	135/133M	4805/4540	120

ROADONE

Main Features

☑ Long-Haul Steer Tire: Optimized for highway applications with a premium straight-rib design for reliable performance and precise handling.

☑ Wide Rib Pattern: Promotes even wear and enhances road contact for improved mileage.

☑ Five-Rib Tread Design: Ensures excellent stability and steering response, even at high speeds.

☑ Stone Ejectors: Reduce stone retention to prevent casing damage and extend tire life.



AP717

Item	Size	OD (Inch)	SW (Inch)	T/D X/32	Load Index	Max Load (Lbs)	PSI
RL2030	11R22.5/16	41.2	11.1	21	146/143L	6610/6005	120
RL2031	11R24.5/16	43.2	11.1	21	149/146L	7610/6610	120
RL2032	215/75R17.5/16	30.2	8.4	16	135/133J	4805/4540	123
RL2033	225/70R19.5/14	31.8	8.9	16	128/126L	3970/3750	110
RL2034	235/75R17.5/18	31.3	9.3	17	143/141J	6005/5675	127
RL2035	245/70R19.5/16	33.0	9.6	17	135/133L	4805/4540	120
RL2036	255/70R22.5/16	36.6	10.2	17	140/137M	5510/5070	120
RL2037	295/75R22.5/16	39.9	11.5	21	146/143L	6610/6005	120

ROADONE

Main Features

- ☑ Large Tread Blocks: Provide strong traction and stability on various road conditions.
- ☑ Wide Circumferential Grooves: Improve water evacuation for enhanced wet performance and safety.
- ☑ Staggered Shoulder Design: Promotes even wear while boosting cornering grip and stability.
- ☑ Reinforced Block Rigidity: Ensures long mileage, durability, and heavy load resistance.



DP919

Item	Size	OD (Inch)	SW (Inch)	T/D X/32	Load Index	Max Load (Lbs)	PSI
RL2044	11R22.5/16	41.5	11.1	26.6	146/143	6610/6005	120
RL2046	11R24.5/16	43.5	11.1	26.6	149/146	7160/6610	120
RL2048	295/75R22.5/16	40.2	11.5	26.6	146/143	6610/6005	120
RL2050	285/75R24.5/16	41.9	11.1	26.6	147/144	6780/6175	120

ROADONE

Main Features

- ☑ Closed Shoulder Rib Design: Enhances stability and resists irregular wear, ideal for long-haul and regional steer applications.
- ☑ Five-Rib Tread Pattern: Provides precise handling and even pressure distribution for extended mileage and smoother ride quality.
- ☑ Straight Circumferential Grooves: Efficiently channel water away to improve wet traction and reduce hydroplaning risk.
- ☑ Solid Center Rib: Increases directional stability and steering response for highway driving confidence



LFL866

Item	Size	OD (Inch)	SW (Inch)	T/D X/32	Load Index	Max Load (Lbs)	PSI
RL2038	245/70R17.5/18	31.1	9.8	18.3	143/141J	6005/5675	127

ROADONE

Main Features

☑ Highway Rib Tread Design: Optimized straight-rib pattern delivers excellent stability, smooth ride, and precise handling.

☑ Long Mileage Compound: Wear-resistant rubber promotes even tread wear and extends overall service life.

☑ Low Rolling Resistance: Reduces heat build-up and fuel consumption for improved operating efficiency.

☑ Durable Heavy-Duty Construction: Reinforced casing enhances load capacity and toughness for demanding regional and long-haul applications.



RL917

Item	Size	OD (Inch)	SW (Inch)	T/D X/32	Load Index	Max Load (Lbs)	PSI
RL2038	245/70R17.5/18	31.1	9.8	18.3	143/141J	6005/5675	127
RL2052	11R22.5/16	41.1	11.1	19	146/143K	6610/6005	120
RL2053	11R24.5/16	43.1	11.1	19	149/146K	7160/6610	120
RL2054	255/70R22.5/16	36.5	10.2	17	140/137M	5510/1070	120

ROADONE

OUR CORE VALUES



PROFESSIONAL

Sutong has over 40 years of experience in the tire industry, serving as a global resource integrator and supply chain expert, with a dedicated team providing 24-hour service worldwide.



PRECISE

Sutong ensures 90-day delivery for overseas shipments, 5-day delivery from distribution centers, and 24-hour outbound for online orders, maintaining a 98% fill rate for precise and efficient service.



PERSONAL

Sutong customizes programs for each customer, treating them like family. We personalize all our services, deeply caring about our customers' success, because their success is our success.



33402 Highway 290, Hockley TX 77447
Tel: (713) 690-5500 Fax: (713) 690-5501