



MEDIUM TRUCK RADIAL
SUPERCARGO

Unique Tread Design

- Strategic tread pattern promotes grip and traction.
- Provides stability at higher speeds.
- Resulting in longer tread life that prevents irregular wear.
- Wide grooves prevent hydroplaning and boosting wet grip traction.

Reinforced Construction

- Specially formulated for heavy loads.
- Withstands high heat demands.
- Increased retreadability.
- Suitable for multiple applications.

Fuel Efficiency

- Smartway approved design.
- Promotes even wear and enhances fuel efficiency.

S202

(All Position)



Item	Size	OD (Inch)	SW (Inch)	T/D X/32	Loading Index	Max Load (Lbs)	PSI	Speed Rating
SLMS029	11R22.5 14PR	41.5	11	20.0	144/142	6175/5840	105	M
SLMS002	11R22.5 16PR	41.5	11	20.0	146/143	6610/6005	120	M
SLMS033	11R24.5 14PR	43.5	11	20.0	146/143	6610/6005	105	M
SLMS006	11R24.5 16PR	43.5	11	20.0	149/146	7160/6610	120	M
SLMS012	285/75R24.5 14PR	41.3	11	19.0	144/141	6175/5675	110	M
SLMS018	295/75R22.5 14PR	39.9	11.7	19.0	144/141	6175/5675	110	M
SLMS017	295/75R22.5 16PR	39.9	11.7	18.9	146/143	6610/6005	120	M
SLMS010	255/70R22.5 16PR	36.6	10	19.0	140/137	5510/5070	120	M
SLMS026	12R22.5 16 16PR	42.7	12	20.0	150/147	7390/6780	120	L
SLMS051	215/75R17.5 16PR	30.08	8.1	16.4	135/133	4805/4540	125	J
SLMS052	235/75R17.5 18PR	31.34	9.01	16.4	143/141	6005/5675	125	J
SLMS053	245/70R17.5 18PR	31.3	9.57	17.0	143/141	6005/5675	127	K
SLMS048	225/70R19.5 14PR	31.89	8.93	16.4	128/126	3970/3750	110	M
SLMS049	245/70R19.5 16PR	33.03	9.59	16.4	135/133	4805/4540	120	M
SLMS061	315/80R22.5 18PR	42.4	12.3	20.2	154/151	8270/7610	120	M
SLMS062	315/80R22.5 20PR	42.4	12.3	20.2	156/150	8820/7390	120	M
SLMS063	315/80R22.5 22PR	42.4	12.3	20.2	158/156	9370/8820	120	M
SLMS071	275/80R22.5 16PR	40.0	11.0	18.9	147/144	6780/6175	120	M
SLMS072	275/70R22.5 16PR	37.72	10.87	25	148/145	6940/6395	130/130	L
SLMS073	275/70R22.5 16PR	37.72	10.87	25	152/148	7830/6940	135/135	L

Specialized Tread Formulation

- Prevents debris buildup.
- Enhance water dispersion.
- Deeper tread design ensures longer wear.
- Flat tread design helps to avoid uneven wear patterns.
- Enhances stability and handling.

Specially Engineered Casing Designed

- Enhanced retreadability by reducing casing fatigue.
- Ensures stability by distributing ground pressure evenly.
- Enhances high-speed performance and durability.
- Provides better load heating resistance traction.
- Prevents irregular wear.

Fuel Efficiency

- Smartway approved design.
- Promotes even wear and enhances fuel efficiency.



D271
(Close Shoulder Drive)

Item	Size	OD (Inch)	SW (Inch)	T/D X/32	Loading Index	Max Load (Lbs)	PSI	Speed Rating
SLMS031	11R22.5 14PR	41.5	11	30.2	144/141	6175/5840	105	L
SLMS004	11R22.5 16PR	41.5	11	30.2	146/143	6610/6005	120	L
SLMS034	11R24.5 14PR	43.5	11	30.2	146/143	6610/6005	105	M
SLMS007	11R24.5 16PR	43.5	11	30.2	149/146	7160/6610	120	M
SLMS014	285/75R24.5 14PR	41.3	11	26.0	144/141	6175/5675	110	M
SLMS020	295/75R22.5 14PR	39.9	11.7	26.0	144/141	6175/5675	110	L
SLMS019	295/75R22.5 16PR	39.9	11.7	26.0	146/143	6610/6005	120	L

Enhanced Shoulder Pattern

- Improved stability and even wear.
- Promotes even wear across the tire surface.
- Ensuring longer-lasting performance.

Longitudinal Grooves

- Multiple sipes for enhanced traction and grip.
- Resist hydroplaning.
- Quickly evacuates water from the tread.
- Reduces the risk of aquaplaning on wet roads.

Smartway Verified

- Meets environmental and fuel efficiency standards.
- Improved fuel economy.



S205
(Steer)

Item	Size	OD (Inch)	SW (Inch)	T/D X/32	Loading Index	Max Load (Lbs)	PSI	Speed Rating
SLMS028	11R22.5 14PR	41.5	11	18.0	144/141	6175/5840	105	M
SLMS001	11R22.5 16PR	41.5	11	18.0	146/143	6610/6005	120	M
SLMS016	295/75R22.5 14PR	39.9	11.7	18.0	144/141	6175/5675	110	M

Specially Designed Angled Tread Blocks

- Promote self-cleaning.
- Enhance both traction and handling performance.

Reinforced Construction

- Handle heavier loads
- Ensures stability by distributing ground pressure evenly.
- Improved retreadability.
- Provides better load heating resistance and traction.
- Prevents irregular wear.

Deep tread depth

- Resists uneven wear.
- Increased tread life.



D272
(Open Shoulder Drive)

Item	Size	OD (Inch)	SW (Inch)	T/D X/32	Loading Index	Max Load (Lbs)	PSI	Speed Rating
SLMS032	11R22.5 14PR	41.5	11	24.0	144/141	6175/5840	105	L
SLMS005	11R22.5 16PR	41.5	11	24.0	146/143	6610/6005	120	L
SLMS035	11R24.5 14PR	43.5	11	24.0	146/143	6610/6005	105	M
SLMS008	11R24.5 16PR	43.5	11	24.0	149/146	7160/6610	120	M
SLMS044	285/75R24.5 14PR	41.3	11	26.0	144/141	6175/5675	110	M
SLMS022	295/75R22.5 14PR	39.9	11.7	26.0	144/141	6175/5675	110	L
SLMS021	295/75R22.5 16PR	39.9	11.7	26.0	146/143	6610/6005	120	L

Specialized zig-zag Tread Pattern

- Provides better hydroplaning resistance.
- Improved braking performance.
- Improved mileage.
- Shorter braking distances.

Durability and Extended Life

- Cut and chip-resistant rubber compound ensuring durability.

Rubber Tread Protrusions

- Provide self-cleaning capabilities for consistent traction.
- Protects the tire casing from damage.

Four-Belt Internal Structure

- Ensures stability by distributing ground pressure evenly.
- Enhances high-speed performance and durability.
- Prevents irregular wear.
- Enhanced Retreadability.



A576
(Chip & Cut)

Item	Size	OD (Inch)	SW (Inch)	T/D X/32	Loading Index	Max Load (Lbs)	PSI	Speed Rating
SLMS009	255/70R22.5 16PR	36.6	10	18.0	140/137	5510/5070	120	M
SLMS037	11R22.5 16PR	41.5	11	20.0	146/143	6610/6005	120	M
SLMS039	11R24.5 16PR	43.5	11	20.0	149/146	7160/6610	120	M

Extra Reinforced Shoulder

- Enhances stability and durability.
- Ensures consistent performance even under heavy loads.

Reinforced Belt Construction

- Ensures stability by distributing ground pressure evenly.
- Enhances high-speed performance and durability.
- Provides better load heating resistance and traction.
- Prevents irregular wear.

Rubber Formulation for Durability

- Engineered to resist cuts, chips, and punctures.
- Durability extends the tire’s tread life.

Fuel Efficiency

- Smartway approved design.
- Promotes even wear and enhances fuel efficiency.



T210
(Trailer)

Item	Size	OD (Inch)	SW (Inch)	T/D X/32	Loading Index	Max Load (Lbs)	PSI	Speed Rating
SLMS040	11R22.5 14PR	41.5	11	13.2	144/142	6175/5840	105/105	M
SLMS042	11R24.5 14PR	43.5	11	13.2	146/143	6610/6005	105/105	M
SLMS046	295/75R22.5 14PR	39.9	11.7	13.2	144/141	6175/5675	110/110	L
SLMS059	285/75R24.5 14PR	41.3	11.1	13.2	144/141	6175/5675	110/110	M
SLMS060	285/75R24.5 16PR	41.3	11.1	13.2	147/144	6780/6175	120/120	M
SLMS050	255/70R22.5 16PR	36.46	9.67	13.2	140/137	5510/5070	120	M

Special Rubber Formula

- That enhances durability, traction, and wear resistance.
- Suitable for both on-road and off-road applications.

Optimized Tread Pattern

- Provides excellent grip on different surfaces, including highways, construction sites, and rough terrain.
- Ensures stability during cornering and braking maneuvers.

All-Steel Radial Construction

- Enhances load-carrying capacity, durability, and overall performance.

Versatility

- Design allows it to handle both highway driving and off-road conditions.
- Ideal for trucks, trailers, side tippers, water tankers, and flatbeds.



D251

(Mixed Service Heavy loads)

Item	Size	OD (Inch)	SW (Inch)	T/D X/32	Loading Index	Max Load (Lbs)	PSI	Speed Rating
SLMS003	11R22.5 16PR	41.5	11	25.2	146/143	6610/6005	120	M

Special Rubber Formula

- Designed for durability, traction, and longevity.

Optimized Tread Pattern

- Enhances grip on various road surfaces, improving safety and performance.

All-Steel Radial Construction

- Ensures stability, even wear, and resistance to heat buildup.

Suitable for Various Applications

- Ideal for trucks, trailers, side tippers, water tankers, and flat decks.



D252

(Mixed Service Heavy loads)

Item	Size	OD (Inch)	SW (Inch)	T/D X/32	Loading Index	Max Load (Lbs)	PSI	Speed Rating
SLMS027	12R22.5 16PR	42.7	12	22.5	150/147	7390/6780	120	K

Robust Construction

- Designed for enhanced durability and load-bearing capacity.
- Traditional design provides improved stability and traction.
- Enhanced resistance to wear and tear.

Deep Trench Excavation Pattern

- Deep trench excavation pattern contributes to superior braking performance.
- Helps maintain control during sudden stops or emergency situations.

Cost Savings

- Long March tires are known for their long-term cost efficiency.



DL01
(Lug)

Item	Size	OD (Inch)	SW (Inch)	T/D X/32	Loading Index	Max Load (Lbs)	PSI	Speed Rating
SLMS054	215/75R17.5 16PR	30.3	8.3	19.5	135/133	4805/4540	125/125	J
SLMS055	225/70R19.5 14PR	32	8.9	19.5	128/126	3970/3750	110/110	J
SLMS056	235/75R17.5 18PR	31.5	9.2	19.5	143/141	6005/5675	125/125	J
SLMS057	245/70R17.5 18PR	31.2	9.8	20.8	143/141	6005/5675	127/127	J
SLMS058	245/70R19.5 16PR	33.2	9.8	20.8	135/133	4805/4540	120/120	J

Four-Layer Belt Structure

- Ensures stability by distributing ground pressure evenly.
- Enhances high-speed performance and durability.
- Provides better load heating resistance traction.
- Prevents irregular wear.
- Enhanced retreadability.

Lateral Block Tread Pattern

- Contributes to better traction and overall performance.

Fuel Efficiency

- Smartway approved design.
- Promotes even wear and enhances fuel efficiency.



SC820
(Premium Trailer)

Item	Size	OD (Inch)	SW (Inch)	T/D X/32	Loading Index	Max Load (Lbs)	PSI	Speed Rating
SLMS069	11R22.5 14PR	41.5	110	11.0	144/142	6175/5840	105	L
SLMS070	295/75R22.5 14PR	40.0	11.6	11.0	144/141	6175/5675	110	L

Specialized Tread Design

- Aggressive open-shoulder tread improves traction on both paved and unpaved roads.
- Zigzag grooves enhance grip and promote effective water evacuation.
- Large center tread blocks deliver better straight-line stability.
- Deep tread depth ensures extended mileage and slower wear rate.

Reinforced Casing Structure

- Robust sidewall construction provides extra resistance to cuts and abrasions.
- Steel belt reinforcement boosts durability and retread performance.
- Optimized contact patch promotes even load distribution under heavy loads.

Performance Efficiency

- Engineered for reduced rolling resistance and improved fuel economy.
- Delivers consistent performance in both wet and dry conditions.



A275
**(Premium Mixed Service
Chip and Cut)**

Item	Size	OD (Inch)	SW (Inch)	T/D X/32	Loading Index	Max Load (Lbs)	PSI	Speed Rating
SLMS066	11R22.5 16PR	41.5	11	24.0	146/143	6600/5995	120	L
SLMS068	11R24.5 16PR	43.5	11	24.0	149/146	7150/6600	120	M

Straight Rib Pattern

- Ensures high-speed stability and precise steering control.
- Provides low rolling resistance for better fuel efficiency.
- Delivers balanced performance on dry and wet roads.

Continuous Shoulder Design

- Promotes even wear and prevents irregular tread patterns.
- Improves heat dissipation to extend tire life.
- Enhances overall ride comfort.

Optimized Groove Arrangement

- Effectively channels water to reduce hydroplaning risk.
- Maintains stable ground contact.
- Improves safety and handling in wet conditions.

LM180
(All Position)



Item	Size	OD (Inch)	SW (Inch)	T/D X/32	Loading Index	Max Load (Lbs)	PSI	Speed Rating
SLMS074	385/65R22.5 24PR	42	14.7	11.2	164K	11000	130	K

Interlocking Block Pattern

- Provides strong grip and braking performance.
- Enhances traction on wet, muddy, or uneven roads.
- Reduces slippage and improves driving stability.

Wide Tread Design

- High load-bearing capacity, ideal for heavy-duty transport.
- Distributes ground pressure evenly to reduce irregular wear.
- Extends overall tire service life.

Stone-Ejecting Grooves

- Special grooves prevent stone retention.
- Protects the casing from punctures and damage.
- Keeps tread clean and maintains performance.



LM281

(Mixed Service Heavy Load)

Item	Size	OD (Inch)	SW (Inch)	T/D X/32	Loading Index	Max Load (Lbs)	PSI	Speed Rating
SLMS075	385/65R22.5 24PR	42	14.7	19	164K	11000	130	K

OUR CORE VALUES



PROFESSIONAL

Sutong has over 40 years of experience in the tire industry, serving as a global resource integrator and supply chain expert, with a dedicated team providing 24-hour service worldwide.



PRECISE

Sutong ensures 90-day delivery for overseas shipments, 5-day delivery from distribution centers, and 24-hour outbound for online orders, maintaining a 98% fill rate for precise and efficient service.



PERSONAL

Sutong customizes programs for each customer, treating them like family. We personalize all our services, deeply caring about our customers' success, because their success is our success.



33402 Highway 290, Hockley TX 77447
Tel: (713) 690-5500 Fax: (713) 690-5501