



SPECIALTY TIRE RADIAL

CARAWAY

Main Features

- ✓ Design: Symmetric tread pattern with multi-groove channels for enhanced wet traction and even wear.
- ✓ Application: Optimized for trailers handling high-load capacities in long-haul operations.
- ✓ Performance: Delivers stable handling, reduced rolling resistance, and excellent fuel efficiency.
- ✓ Durability: Reinforced sidewalls and robust construction ensure longevity and resistance to irregular wear.

ST202
(All-Steel STR)



Item	Size	OD (Inch)	SW (Inch)	T/D X/32	Load Index	Max Load (Lbs)	PSI
CWR1022	ST235/80R16 14PR	30.8	9.3	11.3	129/125M	4080/3640	110
CWR1023	ST235/80R16 16PR	30.8	9.3	11.3	130/126M	4190/3750	120
CWR1024	ST235/85R16 14PR	31.7	9.3	11.3	132/127M	4400/3860	110
CWR1025	ST235/85R16 16PR	31.7	9.3	11.3	133/128M	4540/3970	120
CWR1026	ST225/90R16 14PR	31.8	8.7	12.6	132/127M	4400/3860	110

Main Features

- ☑ Design: Wide footprint with deep tread grooves for maximum road contact and water dispersion.
- ☑ Application: Suitable for both regional and highway transport applications.
- ☑ Performance: Ensures smooth rides, enhanced load-bearing capability, and consistent performance.
- ☑ Durability: High-strength compound resists wear, ensuring long-lasting reliability.

SU805
(All-Steel STR)



Item	Size	OD (Inch)	SW (Inch)	T/D X/32	Load Index	Max Load (Lbs)	PSI
CWR1027	ST225/75R15 12PR	28.3	8.8	14.0	121/118M	3200/2910	95
CWR1028	ST225/75R15 14PR	28.3	8.8	14.0	123/119M	3420/3000	110

Main Features

☑ Design: Zigzag tread pattern for superior grip and reduced heat buildup.

☑ Application: Heavy-duty trailer tire designed for extended highway use.

☑ Performance: Provides enhanced traction and stability, even under heavy loads.

☑ Durability: Engineered with a robust carcass for puncture resistance and prolonged service life.

CT921

(Semi-Steel STR)



Item	Size	OD (Inch)	SW (Inch)	T/D X/32	Load Index	Max Load (Lbs)	PSI
CWT2010	ST175/80R13 6PR	24.0	7.0	9.2	91/87M	1360/1200	50
CWT2001	ST175/80R13 8PR	24.0	7.0	9.2	97/93M	1610/1430	65
CWT2011	ST205/75R14 6PR	26.1	8.0	9.2	100/96M	1760/1570	50
CWT2002	ST205/75R14 8PR	26.1	8.0	9.2	105/101M	2040/1820	65
CWT2012	ST215/75R14 6PR	26.7	8.5	9.2	102/98M	1870/1650	50
CWT2003	ST215/75R14 8PR	26.7	8.5	9.2	108/103M	2200/1930	65
CWT2004	ST205/75R15 6PR	27.1	8.0	9.2	101/97M	1820/1610	50
CWT2005	ST205/75R15 8PR	27.1	8.0	9.2	107/102M	2150/1870	65
CWT2013	ST205/75R15 10PR	27.1	8.0	9.2	111/106M	2400/2090	80
CWT2006	ST225/75R15 8PR	28.3	8.8	9.2	113/108M	2540/2200	65
CWT2007	ST225/75R15 10PR	28.3	8.8	9.2	117/112M	2830/2470	80
CWT2008	ST235/80R16 10PR	30.8	9.3	9.2	124/120M	3520/3080	80
CWT2014	ST235/80R16 12PR	30.8	9.3	9.2	126/122M	3740/3300	95
CWT2009	ST235/85R16 10PR	31.7	9.3	9.2	125/121M	3640/3200	80

CARAWAY