



PASSENGER & LIGHT TRUCK



HEMISPHERE

Main Features:

- ✓ **3D Sipes:** Offers higher linear elongation rate than 2D sipes, increasing grasping area on wet roads and enhancing wet performance.
- ✓ **Symmetrical Pattern:** Ensures uniform stress distribution, improving wear performance and comfort.
- ✓ **Lateral Shoulder Blocks:** Enhances shoulder stiffness, reduces rolling vibration, noise, and improves steering performance.



AETHON HP

Item	Size	UTQG	OD (Inch)	SW (Inch)	T/D X/32	Load/Speed Index	PSI	Max Loading
LH1221	215/55R17	700AA	26.3	8.9	9.5	94V	44	1477
LH1222	225/55R17	700AA	26.8	9.2	10.1	97H	44	1609
LH1223	205/65R16	700AA	26.5	8.2	9.5	95H	44	1521
LH1224	235/65R17	700AA	29.1	9.5	10.1	104H	44	1984
LH1225	235/65R18	700AA	30	9.5	10.1	106H	44	2094
LH1046	195/70R14	700AA	24.8	7.9	9.5	91H	44	1356
LH1047	185/60R15	700AA	23.7	7.4	9.5	84H	44	1102
LH1048	195/60R15	700AA	24.2	7.9	9.5	88H	44	1235
LH1049	185/65R15	700AA	24.5	7.4	9.5	88H	44	1235
LH1050	195/65R15	700AA	25.0	7.9	10.0	91H	44	1356
LH1051	205/65R15	700AA	25.5	8.2	9.5	94H	44	1477
LH1052	205/55R16	700AA	24.9	8.4	9.5	91H	44	1356
LH1053	205/60R16	700AA	25.7	8.2	9.5	92H	44	1389

Main Features:

- ✓ **3D Sipes:** Offers higher linear elongation rate than 2D sipes, increasing grasping area on wet roads and enhancing wet performance.
- ✓ **Symmetrical Pattern:** Ensures uniform stress distribution, improving wear performance and comfort.
- ✓ **Lateral Shoulder Blocks:** Enhances shoulder stiffness, reduces rolling vibration, noise, and improves steering performance.



AETHON HP

Item	Size	UTQG	OD (Inch)	SW (Inch)	T/D X/32	Load/Speed Index	PSI	Max Loading
LH1054	215/60R16	700AA	26.1	8.7	9.5	95H	44	1521
LH1055	225/60R16	700AA	26.6	9.0	10.1	98H	44	1653
LH1056	235/60R16	700AA	27.1	9.5	10.1	100H	44	1764
LH1057	215/65R16	700AA	27.0	8.7	9.5	98H	44	1653
LH1058	225/65R16	700AA	27.5	9.0	10.1	100H	44	1764
LH1059	235/65R16	700AA	28.0	9.5	10.1	103H	44	1929
LH1060	225/70R16	700AA	28.4	9.0	10.1	107H XL	50	2149
LH1061	235/55R17	700AA	27.2	9.7	10.1	99H	44	1709
LH1062	215/60R17	700AA	27.2	8.7	9.5	96H	44	1565
LH1063	225/60R17	700AA	27.6	9.0	10.1	99H	44	1709
LH1064	235/60R17	700AA	28.1	9.5	10.1	102H	44	1874
LH1065	225/65R17	700AA	28.5	9.0	10.1	102H	44	1874
LH1066	225/55R18	700AA	27.8	9.2	10.1	98H	44	1653

Main Features:

- ✓ **4 Longitudinal Grooves:** Improves wet braking and traction performance.
- ✓ **Variable Pitch Design:** Optimizes pitch ratio and arrangement to reduce noise and enhance handling.
- ✓ **Symmetrical Pattern:** Ensures uniform tire stress distribution, enhancing wear and comfort performance.
- ✓ **Strengthened Tire Bar:** Increases tread stiffness, boosting wear performance.
- ✓ **Arc and Straight Line Grooves:** Enhances wet braking capabilities.
- ✓ **Groove and Sipe Balance:** Improves heat dissipation, handling, and comfort.



AETHON 4X4 HP

Item	Size	UTQG	OD (Inch)	SW (Inch)	T/D X/32	Load/Speed Index	PSI	Max Loading
LH1067	205/70R15	480AB	26.3	8.2	10.1	95H	44	1565
LH1068	215/70R16	480AA	27.9	8.7	10.1	100H	44	1764
LH1069	235/70R16	480AA	29.0	9.5	10.1	106H	44	2094
LH1070	245/70R16	480AB	29.5	9.8	10.1	111H XL	50	2403
LH1071	265/70R16	480AA	30.6	11.1	10.1	112H	44	2469
LH1072	225/75R16	480AB	29.3	8.8	10.1	104H	44	1984
LH1073	235/55R17	480AA	27.2	9.7	9.7	103V XL	50	1929
LH1074	215/60R17	480AA	27.2	8.7	10.1	96H	44	1565
LH1075	225/60R17	480AA	27.6	9.0	10.1	99H	44	1709
LH1076	235/60R17	480AA	28.1	9.5	10.1	106V XL	50	2094
LH1077	235/65R17	480AA	29.1	9.5	10.1	108V XL	50	2205
LH1078	245/65R17	480AA	29.5	9.8	10.1	111H XL	50	2403

Main Features:

- ✓ **4 Longitudinal Grooves:** Improves wet braking and traction performance.
- ✓ **Variable Pitch Design:** Optimizes pitch ratio and arrangement to reduce noise and enhance handling.
- ✓ **Symmetrical Pattern:** Ensures uniform tire stress distribution, enhancing wear and comfort performance.
- ✓ **Strengthened Tire Bar:** Increases tread stiffness, boosting wear performance.
- ✓ **Arc and Straight Line Grooves:** Enhances wet braking capabilities.
- ✓ **Groove and Sipe Balance:** Improves heat dissipation, handling, and comfort.



AETHON 4X4 HP

Item	Size	UTQG	OD (Inch)	SW (Inch)	T/D X/32	Load/Speed Index	PSI	Max Loading
LH1079	265/65R17	480AA	30.6	10.7	10.1	112H	44	2469
LH1080	235/55R18	480AA	28.2	9.7	10.1	104V XL	50	1984
LH1081	255/55R18	480AA	29.0	10.4	9.7	109V XL	50	2271
LH1082	225/60R18	480AA	28.6	9.0	10.1	100H	44	1764
LH1083	235/60R18	480AA	29.1	9.5	10.1	107V XL	50	2149
LH1084	245/60R18	480AA	29.6	9.8	10.1	105V	44	2039
LH1085	265/60R18	480AA	30.5	10.7	10.1	110H	44	2337
LH1086	235/65R18	480AA	30.0	9.5	10.1	106H	44	2094
LH1226	255/65R18	480AA	31.1	10.2	10.1	111H	44	2403
LH1227	275/65R18	480AA	32.1	11.0	10.1	116H	44	2756
LH1228	275/60R20	480AA	33.0	11.0	10.1	115T	44	2679

Main Features:

- ✓ **Shoulder Reinforcement:** Provides better traction on soft ground and improves off-road performance with decorative pattern design.
- ✓ **Symmetric Pattern:** Optimizes tire grounding mark shape for balanced force, reducing abnormal wear and enhancing wear resistance.
- ✓ **Rolling Reinforcement:** Improves the rigidity of pattern pieces, enhancing control performance.



AETHON A/T

Item	Size	UTQG	OD (Inch)	SW (Inch)	T/D X/32	Load/Speed Index	PSI	Max Loading
LH1188	235/70R16	560AB	29.0	9.4	11.6	106T	44	2094
LH1181	235/75R15	560AB	28.9	9.3	11.6	109T XL	50	2271
LH1189	245/70R16	560AB	29.5	9.8	13.0	111T	50	2403
LH1185	245/75R16	560AB	30.5	9.8	13.0	111T	44	2403
LH1182	265/70R16	560AB	30.6	10.7	13.0	112T	44	2469
LH1173	265/70R17	560AB	31.7	10.7	13.2	115T	44	2679
LH1180	265/75R16	560AB	31.7	10.5	13.0	116T	44	2756
LH1176	275/55R20	560AB	31.9	11.2	11.0	113S	44	2535
LH1177	275/60R20	560AB	33.0	11.0	11.0	115T	44	2679
LH1187	275/65R18	560AB	32.1	11.0	13.0	116T	44	2756
LH1184	285/70R17	560AB	32.8	11.5	13.0	116T	44	2756
LH1191	LT215/85R16 10PR	/	30.4	8.5	13.6	115/112Q	80	2680/2470
LH1192	LT225/75R16 10PR	/	29.3	8.8	13.6	115/112Q	80	2680/2470
LH1190	LT235/75R15 6PR	/	28.9	9.3	13.6	104/101R	50	1985/1820

Main Features:

- ✓ **Shoulder Reinforcement:** Provides better traction on soft ground and improves off-road performance with decorative pattern design.
- ✓ **Symmetric Pattern:** Optimizes tire grounding mark shape for balanced force, reducing abnormal wear and enhancing wear resistance.
- ✓ **Rolling Reinforcement:** Improves the rigidity of pattern pieces, enhancing control performance.



AETHON A/T

Item	Size	UTQG	OD (Inch)	SW (Inch)	T/D X/32	Load/Speed Index	PSI	Max Loading
LH1194	LT235/80R17 10PR	/	31.8	9.3	13.6	120/117R	80	3085/2835
LH1193	LT235/85R16 10PR	/	31.7	9.3	13.6	120/116S	80	3042/2778
LH1195	LT245/70R17 10PR	/	30.6	9.8	14.7	119/116Q	80	3000/2755
LH1172	LT245/75R16 10PR	/	30.5	9.8	15.1	120/116Q	80	3042/2778
LH1196	LT245/75R17 10PR	/	31.5	9.8	14.7	121/118R	80	3195/2910
LH1186	LT265/70R17 10PR	/	31.7	10.7	14.7	121/118R	80	3195/2910
LH1198	LT265/70R18 10PR	/	32.6	10.7	14.7	124/121S	80	3525/3195
LH1183	LT265/75R16 10PR	/	31.7	10.5	14.7	123/120R	80	3417/3086
LH1174	LT275/65R18 10PR	/	32.1	11.0	14.7	123/120S	80	3415/3085
LH1178	LT275/65R20 10PR	/	34.1	11.0	14.7	126/123R	80	3750/3415
LH1175	LT275/70R18 10PR	/	33.2	11.0	14.7	125/122S	80	3640/3305
LH1179	LT285/55R20 10PR	/	32.4	11.7	15.7	122/119R	80	3305/3000
LH1197	LT285/70R17 10PR	/	32.8	11.5	15.7	121/118S	65	3195/2910
LH1171	31X10.50R15LT 6PR	/	30.5	10.6	14.7	109R	51	2270

Main Features:

- ✓ **Wide Center Groove:** Balances wet and wear performance for high-speed rides.
- ✓ **Variable Pitch Design:** Optimizes pitch ratio and arrangement to reduce noise and enhance handling performance.
- ✓ **Line and Z Sipe Design:** Improves handling and balances wear performance with scientific sipe density.
- ✓ **Deep Shoulder Grooves:** Enhances heat dissipation, improves high-speed durability, and increases shoulder drainage speed for better wet performance.



AETHON H/T

Item	Size	UTQG	OD (Inch)	SW (Inch)	T/D X/32	Load/Speed Index	PSI	Max Loading
LH1087	235/75R15	600AB	28.9	9.3	11.0	109T XL	50	2271
LH1088	255/70R16	600AB	30.1	10.2	11.6	111T	44	2403
LH1089	245/75R16	600AB	30.5	9.8	11.6	111T	44	2403
LH1091	245/70R17	600AB	30.6	9.8	11.6	110T	44	2337
LH1092	265/70R17	600AB	31.7	10.7	12.0	115T	44	2679
LH1093	265/50R20	600AB	30.5	10.9	11.6	111H XL	50	2403
LH1230	275/55R20	600AB	31.9	11.2	11.3	117T	50	2833
LH1094	LT225/75R16 10PR	/	29.3	8.8	13.2	115/112S	80	2680/2470
LH1095	LT245/75R16 10PR	/	30.5	9.8	13.2	120/116R	80	3042/2778
LH1096	LT265/75R16 10PR	/	31.7	10.5	13.2	123/120R	80	3415/3085
LH1097	LT215/85R16 10PR	/	30.4	8.5	13.2	115/112S	80	2680/2470
LH1098	LT235/85R16 10PR	/	31.7	9.3	13.2	120/116R	80	3042/2778
LH1100	LT245/75R17 10PR	/	31.5	9.8	13.2	121/118R	80	3195/2910
LH1229	LT275/65R18 10PR	/	32.1	11.0	13.2	123/120S	80	3415/2835

Main Features:

- ☑ **Strong Mud Traction:** Crossed horned block design provides strong traction on muddy and soft surfaces.
- ☑ **Linear Deformation:** Enhances ground contact under low tire pressure, offering strong climbing traction.
- ☑ **Mud Cutting Strip:** Removes sticky clay blocks, providing strong traction on muddy surfaces.
- ☑ **Shoulder Design:** Inner and outer tires have different patterns, offering more choices to customers.



AETHON R/T

Item	Size	UTQG	OD (Inch)	SW (Inch)	T/D X/32	Load/Speed Index	PSI	Max Loading
LH1211	LT285/70R17 10PR	/	32.8	11.5	17.6	121/118Q	80	3195/2910
LH1208	LT275/70R18 10PR	/	33.2	11.0	17.6	125/122Q	80	3640/3305
LH1209	LT275/60R20 10PR	/	33.0	11.0	17.6	123/120Q	80	3085/2835
LH1210	LT275/65R20 12PR	/	34.3	11.0	17.6	128/125Q	95	3640/3305
LH1202	LT305/55R20 12PR	/	33.5	12.4	17.6	125/122S	80	3305/3000
LH1231	LT265/70R17 10PR	/	31.7	10.7	14.7	121/118Q	80	3195/2910
LH1232	LT265/75R16 10PR	/	31.7	10.5	14.7	123/120Q	80	3415/3085
LH1233	LT275/65R18 10PR	/	32.1	11.0	17.6	123/120Q	80	3415/3085
LH1203	33X12.50R20LT 12PR	/	32.8	12.5	17.6	119Q	80	3000
LH1200	33X12.50R22LT 12PR	/	32.8	12.5	17.6	114Q	80	2600
LH1212	35X12.50R17LT 12PR	/	34.5	12.5	17.6	121Q	80	3195
LH1213	35X12.50R18LT 12PR	/	34.5	12.5	17.6	128Q	80	3970
LH1199	35X12.50R20LT 12PR	/	34.8	12.5	17.6	125Q	80	3640
LH1201	35X12.50R22LT 12PR	/	34.8	12.5	17.6	121Q	80	3195
LH1206	37X12.50R20LT 12PR	/	36.5	12.5	17.6	128Q	80	3970
LH1204	37X12.50R22LT 12PR	/	36.8	12.5	17.6	127Q	80	3860
LH1205	37X13.50R20LT 12PR	/	36.5	13.6	17.6	128Q	80	3970
LH1207	37X13.50R22LT 12PR	/	36.5	13.6	17.6	128Q	80	3970

Main Features:

- ✓ **4 Longitudinal Grooves:** Enhances wet braking and traction performance, ensuring safer driving in wet conditions.
- ✓ **Multiple Variable Pitch Design:** Optimizes pitch ratio and arrangement, reducing noise and enhancing overall handling performance.
- ✓ **Asymmetrical Pattern:** Ensures optimal distribution of tire stress, improving wear performance and ride comfort.
- ✓ **Strengthened Tire Bar:** Increases tread stiffness, enhancing durability and wear resistance.
- ✓ **Arc and Straight Line Groove Design:** Improves wet braking by efficiently channeling water away from the tire surface.
- ✓ **Groove and Sipe Balance Location:** Ensures effective heat dissipation, improving handling and comfort by maintaining optimal tire temperature.



AETHON UHP II

Item	Size	UTQG	OD (Inch)	SW (Inch)	T/D X/32	Load/Speed Index	PSI	Max Loading
LH1107	215/55R16	540AA	25.3	8.9	10.3	97W XL	50	1609
LH1117	225/50R17	480AA	25.9	9.2	10.3	98W XL	50	1653
LH1130	235/50R18	480AA	27.3	9.7	10.3	101W XL	50	1819

Main Features:

- ✓ 3d sipes increase tire contact on wet roads, improving traction and reducing braking distance.
- ✓ Unique shoulder cross grooves boost heat dissipation and drainage, enhancing durability and wet performance.
- ✓ Four longitudinal grooves deliver reliable wet braking and traction for added safety.
- ✓ Asymmetric tread pattern provides excellent drainage inside and strong grip outside for superior handling.



AETHON UHP III

Item	Size	UTQG	OD (Inch)	SW (Inch)	T/D X/32	Load/Speed Index	PSI	Max Loading
LH1214	235/40R19	480AA	26.4	9.5	9.2	96Y XL	42	1565
LH1215	245/40R19	480AA	26.7	9.8	9.2	98W XL	42	1653
LH1216	245/45R19	480AA	27.7	9.6	9.2	102W XL	42	1874
LH1217	235/55R19	480AA	29.2	9.7	9.2	105W	50	1874
LH1218	295/35R24	480AA	32.1	11.9	9.2	110V	50	2337
LH1219	305/35R24	480AA	32.4	12.3	9.2	112V	50	2469
LH1220	305/30R26	480AA	33.2	12.3	9.2	109W	50	2271

Main Features:

- ✓ **Asymmetric Tread Design:** Enhances grip and handling by providing superior drainage on the inner side and optimized traction on the outer side.
- ✓ **4 Wide Longitudinal Grooves:** Improves wet braking and reduces the risk of hydroplaning by efficiently channeling water away from the tire surface.
- ✓ **Reinforced Shoulder Blocks:** Increases shoulder stiffness for better cornering stability and steering response.
- ✓ **Variable Pitch Technology:** Reduces road noise for a quieter ride while maintaining a high level of handling performance.
- ✓ **Optimized Tread Pattern:** Balances wear performance and ensures even pressure distribution, enhancing durability and comfort.



AETHON UHP

Item	Size	UTQG	OD (Inch)	SW (Inch)	T/D X/32	Load/Speed Index	PSI	Max Loading
LH1111	215/45R17	540AA	24.6	8.4	10.3	91W XL	50	1356
LH1112	225/45R17	540AA	25.0	8.9	10.3	94W XL	50	1477
LH1114	245/45R17	540AA	25.7	9.6	10.3	99W XL	50	1709
LH1115	205/50R17	540AA	25.1	8.4	10.3	93W XL	50	1433
LH1116	215/50R17	540AA	25.5	8.9	10.3	95W XL	50	1521
LH1118	215/55R17	540AA	26.3	8.9	10.3	94W	50	1477
LH1119	225/55R17	540AA	26.8	9.2	10.3	101W XL	50	1819
LH1121	275/35R18	540AA	25.6	10.9	10.3	95W	50	1521
LH1122	215/40R18	540AA	24.8	8.6	10.3	89W XL	50	1279
LH1123	225/40R18	540AA	25.1	9.1	10.3	92W XL	50	1389
LH1126	225/45R18	540AA	25.9	8.9	10.3	95W XL	50	1521
LH1127	235/45R18	540AA	26.3	9.3	10.3	98W XL	50	1653

Main Features:

- ✓ **Asymmetric Tread Design:** Enhances grip and handling by providing superior drainage on the inner side and optimized traction on the outer side.
- ✓ **4 Wide Longitudinal Grooves:** Improves wet braking and reduces the risk of hydroplaning by efficiently channeling water away from the tire surface.
- ✓ **Reinforced Shoulder Blocks:** Increases shoulder stiffness for better cornering stability and steering response.
- ✓ **Variable Pitch Technology:** Reduces road noise for a quieter ride while maintaining a high level of handling performance.
- ✓ **Optimized Tread Pattern:** Balances wear performance and ensures even pressure distribution, enhancing durability and comfort.



AETHON UHP

Item	Size	UTQG	OD (Inch)	SW (Inch)	T/D X/32	Load/Speed Index	PSI	Max Loading
LH1128	245/45R18	540AA	26.7	9.6	10.3	100W XL	50	1764
LH1129	225/50R18	540AA	26.9	9.2	10.3	95W	50	1521
LH1131	235/55R18	540AA	28.1	9.6	10.3	104W XL	50	1984
LH1138	255/35R20	540AA	27.0	10.2	10.3	97W XL	50	1609
LH1139	275/35R20	540AA	27.6	10.9	10.3	102W XL	50	1874
LH1140	245/40R20	540AA	27.7	9.8	10.3	99W XL	50	1709
LH1142	245/45R20	540AA	28.7	9.6	10.3	103W XL	50	1929
LH1143	255/45R20	540AA	29.1	10.0	10.3	105W XL	50	2039
LH1144	275/45R20	540AA	29.8	10.7	10.3	110W XL	50	2535
LH1145	275/55R20	540AA	31.9	11.2	10.3	113V	50	2535
LH1150	285/45R22	540AA	32.1	11.2	10.3	114W XL	50	2601
LH1151	255/30R24	540AA	30.1	10.2	10.3	97W XL	50	1609

OUR CORE VALUES



PROFESSIONAL

Sutong has over 40 years of experience in the tire industry, serving as a global resource integrator and supply chain expert, with a dedicated team providing 24-hour service worldwide.



PRECISE

Sutong ensures 90-day delivery for overseas shipments, 5-day delivery from distribution centers, and 24-hour outbound for online orders, maintaining a 98% fill rate for precise and efficient service.



PERSONAL

Sutong customizes programs for each customer, treating them like family. We personalize all our services, deeply caring about our customers' success, because their success is our success.



33402 Highway 290, Hockley TX 77447
Tel: (713) 690-5500 Fax: (713) 690-5501