



PASSENGER & LIGHT TRUCK



ROADONE

Main Features:

- ☑ Four wide circumferential grooves minimize hydroplaning effectively.
- ☑ Symmetric tread pattern ensures a smooth, comfortable, and quiet driving experience.
- ☑ Solid center rib enhances handling stability.
- ☑ Optimized pitch sequence design reduces noise for a more pleasant ride.



CAVALRY A/S

Item	Size	LI/SS	UTQG	OD (Inch)	SW (Inch)	PSI	Max Load (Lbs)	T/D X/32
RL1171	175/70R13	82T	600AB	22.7	7.0	36	1047	9.7
RL1172	175/65R14	82T	600AB	23.0	7.0	36	1047	9.7
RL1335	185/65R14	86T	600AB	23.5	7.4	36	1168	9.7
RL1336	185/70R14	88T	600AB	24.3	7.4	36	1235	9.7
RL1338	195/50R15	82H	600AB	22.7	7.9	36	1047	10.7
RL1173	195/70R14	91T	600AB	24.8	7.9	36	1356	9.7
RL1337	185/65R15	88T	600AB	24.4	7.4	36	1235	9.7
RL1339	195/60R15	88H	600AB	24.2	7.9	36	1235	10.7
RL1340	195/65R15	91H	600AB	25.0	7.9	36	1356	10.7
RL1341	205/65R15	94H	600AB	25.5	8.2	36	1477	10.7
RL1178	225/70R15	100T	600AB	27.4	9.0	36	1765	11.0
RL1344	205/55R16	91H	600AB	24.9	8.4	36	1356	11.0
RL1343	205/60R16	92H	600AB	25.7	8.2	36	1389	11.0
RL1342	205/65R16	95H	600AB	26.5	8.2	36	1521	10.7
RL1345	215/60R16	95H	600AB	26.1	8.7	36	1521	11.0
RL1426	205/70R15	96T	600AB	26.3	8.2	36	1565	10.7
RL1427	215/70R15	98T	600AB	26.9	8.7	36	1653	10.7

Main Features:

- ☑ Four wide circumferential grooves minimize hydroplaning effectively.
- ☑ Symmetric tread pattern ensures a smooth, comfortable, and quiet driving experience.
- ☑ Solid center rib enhances handling stability.
- ☑ Optimized pitch sequence design reduces noise for a more pleasant ride.



CAVALRY A/S

Item	Size	LI/SS	UTQG	OD (Inch)	SW (Inch)	PSI	Max Load (Lbs)	T/D X/32
RL1428	225/60R16	98H	600AB	26.6	9.0	36	1653	11.0
RL1429	215/65R16	98H	600AB	27.0	8.7	36	1653	11.0
RL1430	225/65R16	100H	600AB	27.5	9.0	36	1765	11.0
RL1431	205/60R15	91H	600AB	24.7	8.2	36	1356	10.7
RL1473	185/70R13	86T	600AB	23.2	7.4	36	1168	9.7
RL1474	225/70R16	107H	600AB	28.4	9.0	42	2149	11.0
RL1475	245/70R16	107H	600AB	29.5	9.8	36	2149	11.0
RL1476	265/75R16	116T	600AB	31.7	10.5	36	2756	11.0
Below Items Are White Wall Tires								
RL1174	205/70R15	96T	600AB	26.3	8.2	36	1565	10.7
RL1175	205/75R15	97S	600AB	27.1	8.0	36	1609	10.7
RL1176	215/70R15	98T	600AB	26.9	8.7	36	1653	10.7
RL1177	215/75R15	100S	600AB	27.7	8.5	36	1765	10.7
RL1179	225/75R15	102S	600AB	28.3	8.8	36	1874	11.0
RL1180	235/75R15	105S	600AB	28.9	9.3	36	2039	11.0
RL1323	225/60R16	98H	600AB	26.6	9.0	36	1653	11.0

Main Features:

- ☑ Four wide circumferential grooves minimize hydroplaning effectively.
- ☑ Symmetric tread pattern ensures a smooth, comfortable, and quiet driving experience.
- ☑ Solid center rib enhances handling stability.
- ☑ Optimized pitch sequence design reduces noise for a more pleasant ride.



CAVALRY HP

Item	Size	LI/SS	UTQG	OD (Inch)	SW (Inch)	PSI	Max Load (Lbs)	T/D X/32
RL1181	215/65R15	100H	520AA	26.0	8.7	42	1765	9.7
RL1182	215/65R16	98H	520AA	27.0	8.7	36	1653	9.7
RL1183	225/60R16	98H	520AA	26.6	9.0	36	1653	10.7
RL1184	225/60R17	99H	520AA	27.6	9.0	36	1709	10.7
RL1185	235/55R17	99H	520AA	27.2	9.6	36	1709	10.7
RL1186	225/55R18	98H	520AA	27.8	9.2	36	1653	10.7
RL1352	195/55R15	85V	520AA	23.4	7.9	36	1135	9.7
RL1353	215/55R16	97H	520AA	25.3	8.9	36	1433	9.7
RL1354	185/60R15	84H	520AA	23.7	7.4	36	1102	9.7
RL1355	235/60R16	100H	520AA	27.1	9.4	36	1764	10.7
RL1432	235/65R16	103H	520AA	28.0	9.4	36	1929	10.7
RL1434	175/70R14	84T	520AA	23.7	7.0	36	1102	9.2

ROADONE

Main Features:

- ☑ Four wide circumferential grooves minimize hydroplaning effectively.
- ☑ Symmetric tread pattern ensures a smooth, comfortable, and quiet driving experience.
- ☑ Solid center rib enhances handling stability.
- ☑ Optimized pitch sequence design reduces noise for a more pleasant ride.



CAVALRY HP

Item	Size	LI/SS	UTQG	OD (Inch)	SW (Inch)	PSI	Max Load (Lbs)	T/D X/32
RL1435	215/60R15	94H	520AA	25.2	8.7	36	1477	9.7
RL1477	175/65R15	84H	520AA	24.0	7.0	36	1102	9.2
RL1479	215/55R17	94V	520AA	26.3	8.9	36	1477	9.7
RL1480	215/65R17	99H	520AA	28.0	8.7	36	1709	9.7
RL1481	225/45R17	94H	520AA	25.0	8.9	36	1356	9.6
RL1482	225/50R17	94V	520AA	25.9	9.2	36	1477	9.7
RL1483	225/55R16	95V	520AA	25.7	9.2	36	1521	9.7
RL1484	225/65R17	102H	520AA	28.5	9.0	36	1874	10.7
RL1485	225/55R17	97H	520AA	26.8	9.2	36	1609	10.7
RL1486	235/60R17	102H	520AA	28.1	8.4	36	1874	10.7
RL1487	235/65R17	104H	520AA	29.1	9.4	36	1984	10.7

ROADONE

Main Features:

- ☑ Directional pattern design ensures optimal ground contact, reducing braking distance on both wet and dry surfaces.
- ☑ Lug-type shoulder blocks enhance handling performance.
- ☑ Exterior rim flange protector safeguards wheels from curb damage.



CAVALRY UHP

Item	Size	LI/SS	UTQG	OD (Inch)	SW (Inch)	PSI	Max Load (Lbs)	T/D X/32
RL1369	205/50R16	91W	540AA	24.1	8.4	50	1356	10.3
RL1370	205/55R16	91V	540AA	24.9	8.4	50	1355	10.3
RL1371	225/50R16	92W	540AA	24.9	9.2	50	1388	10.3
RL1372	225/55R16	95W	540AA	25.7	9.2	50	1521	10.3
RL1374	205/45R17	88W	540AA	24.3	8.1	50	1235	10.3
RL1375	205/50R17	93W	540AA	25.1	8.4	50	1433	10.3
RL1376	215/45R17	91W	540AA	24.6	8.4	50	1356	10.3
RL1377	215/50R17	95W	540AA	25.5	8.9	50	1521	10.3
RL1378	215/55R17	94W	540AA	26.3	8.9	50	1477	10.3
RL1379	225/45R17	94W	540AA	25.0	8.9	50	1477	10.3
RL1380	225/55R17	101W	540AA	26.8	9.2	50	1819	10.3
RL1381	235/45R17	97W	540AA	25.4	9.3	50	1609	10.3
RL1382	245/45R17	99W	540AA	25.7	9.6	50	1709	10.3
RL1383	215/35R18	84W	540AA	23.9	8.6	50	1102	10.3
RL1384	215/40R18	89W	540AA	24.8	8.6	50	1279	10.3
RL1385	225/40R18	92W	540AA	25.1	9.1	50	1389	10.3
RL1386	225/45R18	95W	540AA	25.9	8.9	50	1521	10.3
RL1387	235/40R18	95W	540AA	25.4	9.5	50	1521	10.3
RL1388	235/45R18	98W	540AA	26.3	9.3	50	1653	10.3
RL1389	235/55R18	104W	540AA	28.1	9.6	50	1984	10.3
RL1390	245/40R18	97W	540AA	25.7	9.8	50	1609	10.3

Main Features:

- ☑ Directional pattern design ensures optimal ground contact, reducing braking distance on both wet and dry surfaces.
- ☑ Lug-type shoulder blocks enhance handling performance.
- ☑ Exterior rim flange protector safeguards wheels from curb damage.



CAVALRY UHP

Item	Size	LI/SS	UTQG	OD (Inch)	SW (Inch)	PSI	Max Load (Lbs)	T/D X/32
RL1391	245/45R18	100W	540AA	26.7	9.6	50	1764	10.3
RL1392	225/50R18	95W	540AA	26.9	9.2	50	1521	10.3
RL1393	275/35R18	95W	540AA	25.6	10.9	50	1521	10.3
RL1394	235/35R19	91W	540AA	25.5	9.5	50	1356	10.3
RL1395	265/30R19	93W	540AA	25.3	10.7	50	1433	10.3
RL1396	225/30R20	85W	540AA	25.4	9.1	50	1135	10.3
RL1397	225/35R20	90W	540AA	26.2	9.1	50	1521	10.3
RL1398	245/35R20	95W	540AA	26.8	9.8	50	1521	10.3
RL1399	255/35R20	97W	540AA	27.0	10.2	50	1609	10.3
RL1400	275/40R20	106W	540AA	28.7	10.9	50	2094	10.3
RL1401	275/45R20	110W	540AA	29.8	10.7	50	2535	10.3
RL1402	275/55R20	113V	540AA	31.9	11.2	50	2535	10.3
RL1403	245/40R20	99W	540AA	27.7	9.8	50	1709	10.3
RL1404	245/45R20	103W	540AA	28.7	9.6	50	1929	10.3
RL1405	255/45R20	105W	540AA	29.1	10.0	50	2039	10.3
RL1406	275/30R20	97W	540AA	26.5	10.9	50	1609	10.3
RL1407	275/35R20	102W	540AA	27.6	10.9	50	1874	10.3
RL1408	245/30R22	92W	540AA	27.8	9.8	50	1389	10.3
RL1409	265/35R22	102W	540AA	29.3	10.7	50	1874	10.3
RL1410	285/45R22	114W	540AA	32.1	11.2	50	2601	10.3
RL1411	305/40R22	114W	540AA	31.6	12.3	50	2601	10.3
RL1412	235/30R22	90V	540AA	27.6	9.3	50	1323	10.3
RL1413	255/30R24	97W	540AA	30.1	10.2	50	1609	10.3

Main Features:

- ☑ Directional Tread Pattern: Offers excellent aquaplaning resistance, enhanced handling, and reliable road grip at high speeds.
- ☑ enforced Shoulder Ribs: Improves shoulder stiffness for better handling, reduces vibration for added comfort, and minimizes noise.
- ☑ Four Longitudinal Grooves: Enhances wet braking and traction performance for safer driving in wet conditions.



CAVALRY UHP II

Item	Size	LI/SS	UTQG	OD (Inch)	SW (Inch)	PSI	Max Load (Lbs)	T/D X/32
RL1488	235/50R18	101W	400AA	24.3	9.7	42	1819	9.69

ROADONE

Main Features:

- ☑ 3d sipes increase tire contact on wet roads, improving traction and reducing braking distance.
- ☑ Unique shoulder cross grooves boost heat dissipation and drainage, enhancing durability and wet performance.
- ☑ Four longitudinal grooves deliver reliable wet braking and traction for added safety.
- ☑ Asymmetric tread pattern provides excellent drainage inside and strong grip outside for superior handling.



CAVALRY UHP III

Item	Size	LI/SS	UTQG	OD (Inch)	SW (Inch)	PSI	Max Load (Lbs)	T/D X/32
RL1507	235/40R19	96Y XL	480AA	26.4	9.5	42	1565	9.2
RL1508	245/40R19	98W XL	480AA	26.7	9.8	42	1653	9.2
RL1509	245/45R19	102W XL	480AA	27.7	9.6	42	1874	9.2

ROADONE

Main Features:

- ☑ Blocks pattern design enhances driving performance on various road surfaces.
- ☑ Grooves with large angles improve the tire's three-dimensional appearance while ensuring effective water drainage.
- ☑ Newly developed compounds meet performance needs for wear resistance, wet grip, and other key characteristics.



CAVALRY A/T

Item	Size	LI/SS	UTQG	OD (Inch)	SW (Inch)	PSI	Max Load (Lbs)	T/D X/32
RL1202	275/55R20	111S	520AB	31.9	11.2	35	2403	13.5
RL1203	275/60R20	114T	520AB	33.0	11.0	35	2601	13.5
RL1205	LT275/65R18 10PR	123/120S	--	32.1	11.0	80	3415/3085	16.0
RL1206	LT275/70R18 10PR	125/122S	--	33.2	11.0	80	3640/3305	16.0
RL1207	LT275/65R20 10PR	126/123S	--	34.1	11.0	80	3750/3415	16.0
RL1208	LT285/55R20 10PR	122/119S	--	32.4	11.7	80	3305/3000	16.0
RL1443	265/75R16	116T	520AB	31.7	10.5	36	2756	13.0
RL1444	235/75R15	109T	460AB	28.9	9.3	42	2271	13.9
RL1445	265/70R16	112T	520AB	30.6	10.7	36	2469	14.0
RL1446	LT265/75R16 10PR	123/120R	--	31.7	10.5	80	3417/3086	16.0
RL1447	P285/70R17	117T	520AB	32.8	11.5	36	2833	13.0
RL1448	245/75R16	111T	520AB	30.5	9.8	36	2403	13.0
RL1449	LT265/70R17 10PR	121/118R	--	31.7	10.7	80	3195/2910	16.0
RL1450	275/65R18	116T	520AB	32.1	11.0	36	2756	13.0
RL1451	235/70R16	106T	460AB	29.0	9.4	36	2094	13.9

ROADONE

Main Features:

- ☑ Blocks pattern design enhances driving performance on various road surfaces.
- ☑ Grooves with large angles improve the tire's three-dimensional appearance while ensuring effective water drainage.
- ☑ Newly developed compounds meet performance needs for wear resistance, wet grip, and other key characteristics.



CAVALRY A/T

Item	Size	LI/SS	UTQG	OD (Inch)	SW (Inch)	PSI	Max Load (Lbs)	T/D X/32
RL1452	245/70R16	111T	520AB	29.5	9.8	42	2403	13.9
RL1453	LT235/75R15 6PR	104/101R	--	28.9	9.3	50	1985/1820	13.9
RL1454	LT215/85R16 10PR	115/112Q	--	30.4	8.5	80	2680/2470	13.9
RL1455	LT225/75R16 10PR	115/112Q	--	29.3	8.8	80	2680/2470	13.9
RL1456	LT235/85R16 10PR	120/116Q	--	31.7	9.3	80	3042/2778	16.0
RL1457	LT235/80R17 10PR	120/117R	--	31.8	9.3	80	3085/2835	13.9
RL1458	LT245/70R17 10PR	119/116Q	--	30.6	9.8	80	3000	15.0
RL1459	LT245/75R17 10PR	121/118R	--	31.5	9.8	80	3195/2910	15.0
RL1460	LT285/70R17 8PR	121/118S	--	32.8	11.5	80	3195/2910	16.0
RL1461	LT265/70R18 10PR	124/121S	--	32.6	10.7	80	3525/3195	15.0
RL1462	LT265/60R20 10PR	121/118R	--	32.5	10.7	80	3195/2910	15.0
RL1463	35X12.50R20LT 10PR	121Q	520AB	34.5	12.5	65	3195	16.0
RL1468	265/70R17	115T	520AB	31.7	10.7	36	2679	13.9
RL1469	LT285/75R16 10PR	126/123R	--	32.8	11.3	80	3750/3415	16.0
RL1470	LT245/75R16 10PR	120/116Q	--	30.5	9.8	80	3042/2778	16.0
RL1471	31X10.50R15LT 6PR	109R	520AB	30.5	10.6	51	2270	16.0

ROADONE

Main Features:

- ☑ Four wide circumferential grooves enhance load capacity and significantly reduce the risk of aquaplaning.
- ☑ Optimized pattern pitch distribution improves driving comfort and reduces noise levels.
- ☑ Large pattern blocks on the shoulder boost traction and cornering performance.



CAVALRY H/T

Item	Size	LI/SS	UTQG	OD (Inch)	SW (Inch)	PSI	Max Load (Lbs)	T/D X/32
RL1209	235/75R15	109T	460AB	28.9	9.3	42	2271	12.2
RL1210	245/70R16	111T	500AB	29.5	9.8	36	2149	12.2
RL1211	245/75R16	111T	500AB	30.5	9.8	36	2403	12.2
RL1212	255/70R16	111T	500AB	30.1	10.2	36	2403	12.2
RL1213	265/75R16	116T	460AB	31.7	10.5	36	2756	12.2
RL1214	235/65R17	104T	460AB	29.1	9.4	36	1984	12.2
RL1215	245/65R17	107T	460AB	29.5	9.8	36	2149	12.2
RL1216	245/70R17	110T	500AB	30.6	9.8	36	2337	12.2
RL1217	265/65R17	112H	500AB	30.6	10.7	36	2469	12.2
RL1218	265/70R17	115T	500AB	31.7	10.7	36	2679	13.2
RL1219	LT225/75R16 10PR	115/112S	--	29.3	8.8	80	2680/2470	14.1

ROADONE

Main Features:

- ☑ Four wide circumferential grooves enhance load capacity and significantly reduce the risk of aquaplaning.
- ☑ Optimized pattern pitch distribution improves driving comfort and reduces noise levels.
- ☑ Large pattern blocks on the shoulder boost traction and cornering performance.



CAVALRY H/T

Item	Size	LI/SS	UTQG	OD (Inch)	SW (Inch)	PSI	Max Load (Lbs)	T/D X/32
RL1220	LT235/85R16 10PR	120/116R	--	31.7	9.3	80	3086/2755	14.1
RL1221	LT245/75R16 10PR	120/116R	--	30.5	9.8	80	3086/2755	14.1
RL1347	LT215/85R16 10PR	115/112S	--	30.4	8.5	80	2679/2469	14.1
RL1348	LT265/75R16 10PR	123/120R	--	31.7	10.5	80	3417/3086	14.1
RL1349	LT265/70R17 10PR	121/118R	--	31.7	10.7	80	3197/2910	14.1
RL1350	235/70R16	109T	500AB	29.0	9.4	36	2094	12.0
RL1351	265/70R16	112T	500AB	30.6	10.7	36	2469	12.0
RL1438	265/50R20	111V	460AB	30.5	10.9	42	2403	11.3
RL1439	275/55R20	117V	460AB	31.9	11.2	42	2833	11.3
RL1441	225/70R16	107T	500AB	28.4	9.0	42	2149	12.0
RL1442	LT265/70R18 10PR	124/121R	--	32.6	10.7	80	3525/3195	13.5

ROADONE

Main Features:

- ☑ 4 wide longitudinal grooves effectively evacuate water, enhancing wet traction and hydroplaning resistance.
- ☑ Continuous rib design improves tread stiffness and road contact, delivering stable handling and precise steering.
- ☑ Optimized tread compound and pattern promote even wear, extending service life and overall durability.



CAVALRY H/T II

Item	Size	LI/SS	UTQG	OD (Inch)	SW (Inch)	PSI	Max Load (Lbs)	T/D X/32
RL1491	LT235/65R16 10PR	121/119R	--	28.0	9.5	80	3195/3000	13.2

ROADONE

Main Features:

- ☑ Ideal for urban highways.
- ☑ Offers high handling performance with low noise.
- ☑ Varying pattern pitches significantly reduce noise, ensuring a quiet and comfortable ride.



CAVALRY 4X4 HP

Item	Size	LI/SS	UTQG	OD (Inch)	SW (Inch)	PSI	Max Load (Lbs)	T/D X/32
RL1333	225/60R17	99H	480AA	27.6	9.0	36	1709	10.7
RL1324	225/65R17	102H	480AA	28.5	9.0	36	1875	10.7
RL1334	225/55R18	98V	500AA	27.8	9.2	36	1653	10.2
RL1325	235/55R18	104V	480AA	28.1	9.6	42	1984	10.3
RL1329	245/60R18	105V	480AA	29.6	9.8	36	2039	10.7
RL1327	265/60R18	110H	480AA	31.1	10.2	36	2337	8.5
RL1326	265/65R18	114H	480AA	31.5	10.7	36	2601	10.7
RL1328	255/55R19	111V	480AA	30	10.4	42	2403	8.2
RL1330	245/50R20	102V	480AA	30	10.0	36	1874	8.7
RL1332	255/50R20	109V	480AA	30.1	10.4	42	2271	10.7
RL1331	265/50R20	111V	480AA	30.5	10.9	42	2403	10.7

ROADONE

Main Features:

- ☑ Primarily designed for muddy and rocky roads.
- ☑ Shallow central grooves and robust shoulder blocks improve puncture resistance and enhance the tire's self-cleaning ability.
- ☑ Wide pattern blocks deliver strong traction on unpaved surfaces.
- ☑ The unique design protects the sidewall from wear while maintaining an attractive appearance.



AETHON M/T

Item	Size	LI/SS	UTQG	OD (Inch)	SW (Inch)	PSI	Max Load (Lbs)	T/D X/32
AR1001	LT285/75R16 10PR	126/123Q	--	33.1	11.3	80	3750/3415	18.5
AR1002	LT265/70R17 10PR	121/118Q	--	31.9	10.7	80	3200/2910	18.4
AR1004	35X12.50R17LT 10PR	121Q	--	34.8	12.5	65	3197	18.5
AR1005	33X12.50R18LT 10PR	118Q	--	32.8	12.5	65	2910	18.5
AR1006	35X12.50R18LT 10PR	123Q	--	34.8	12.5	65	3415	18.4
AR1010	LT235/75R15 6PR	104/101Q	--	29.1	9.3	50	1985/1820	17.3
AR1013	LT235/85R16 10PR	120/116Q	--	31.7	9.3	80	3040/2780	17.3
AR1014	LT245/75R16 10PR	120/116Q	--	30.5	9.8	80	3040/2780	17.3
AR1017	LT265/75R16 10PR	123/120Q	--	31.9	10.5	80	3415/3085	18.5
AR1019	30X9.50R15LT 6PR	104Q	--	29.8	9.5	50	1985	17.3
AR1020	31X10.50R15LT 6PR	109Q	--	30.8	10.6	50	2340	18.5
AR1021	35X12.50R20LT 10PR	121Q	--	34.8	12.5	65	3197	16.0
AR1022	33X12.50R22LT 10PR	109Q	--	32.5	12.5	65	2270	20.2
AR1023	35X12.50R22LT 10PR	117Q	--	34.5	12.5	65	2835	20.2
AR1025	LT285/70R17 10PR	121/118Q	--	33	11.5	65	3200/2910	18.5

ROADONE

Main Features:

- ☑ Primarily designed for muddy and rocky roads.
- ☑ Shallow central grooves and robust shoulder blocks improve puncture resistance and enhance the tire's self-cleaning ability.
- ☑ Wide pattern blocks deliver strong traction on unpaved surfaces.
- ☑ The unique design protects the sidewall from wear while maintaining an attractive appearance.



AETHON M/T

Item	Size	LI/SS	UTQG	OD (Inch)	SW (Inch)	PSI	Max Load (Lbs)	T/D X/32
AR1027	LT315/75R16 10PR	127/124Q	--	34.8	12.3	65	3858/3527	14.6
AR1028	LT235/80R17 10PR	120/117Q	--	31.8	9.3	80	3086/2835	17.3
AR1029	LT275/70R18 10PR	125/122Q	--	33.2	11.0	80	3640/3305	18.5
AR1030	LT255/75R17 6PR	111/108Q	--	33.9	10.0	80	3415	18.5
AR1032	LT275/65R20 10PR	126/123P	--	34.1	11.0	80	3750	19.9
AR1034	37X13.50R20LT 10PR	127Q	--	36.5	13.6	65	3860	20.2
AR1035	37X13.50R22LT 10PR	123Q	--	36.5	13.6	65	3420	20.2
AR1037	35X12.50R24LT 10PR	111Q	--	34.7	12.5	65	2403	19.5
AR1038	37X13.50R24LT 10PR	120Q	--	36.8	13.5	65	3086	19.5
AR1039	37X13.50R26LT 10PR	117Q	--	36.8	13.5	65	2601	19.5
AR1040	33X12.50R20LT 10PR	114Q	--	32.5	12.5	65	2600	20.0
AR1052	33X12.50R18LT 12PR	122Q	--	32.8	12.5	80	3305	18.9
AR1053	33X12.50R20LT 12PR	119Q	--	32.8	12.5	80	3000	20.4
AR1054	33X12.50R22LT 12PR	114Q	--	32.8	12.5	80	2600	20.4
AR1055	35X12.50R18LT 12PR	128Q	--	34.8	12.5	80	3970	18.9
AR1056	35X12.50R20LT 12PR	125Q	--	34.8	12.5	80	3640	20.4
AR1057	35X12.50R22LT 12PR	121Q	--	34.8	12.5	80	3195	20.4
AR1058	37X13.50R20LT 12PR	128Q	--	36.8	13.6	80	3970	20.4
AR1059	37X13.50R22LT 12PR	128Q	--	36.8	13.6	80	3970	20.4

Main Features:

- ☑ Enhanced Mud Traction: The crossed horned block design ensures superior grip on muddy and soft terrains.
- ☑ Optimized Ground Contact: Linear deformation technology improves tire contact with the ground under low pressure, delivering exceptional climbing traction.
- ☑ Efficient Mud Removal: Mud-cutting strips effectively clear sticky clay, maintaining consistent traction in challenging conditions.



CAVALRY R/T

Item	Size	LI/SS	UTQG	OD (Inch)	SW (Inch)	PSI	Max Load (Lbs)	T/D X/32
RL1492	35X12.50R20LT 12PR	125Q	--	34.8	12.5	80	3640	17.6
RL1493	33X12.50R22LT 12PR	114Q	--	32.8	12.5	80	2600	17.6
RL1494	35X12.50R22LT 12PR	121Q	--	34.8	12.5	80	3195	17.6
RL1495	LT305/55R20 12PR	125/122S	--	33.5	12.4	80	3305/3000	17.6
RL1496	33X12.50R20LT 12PR	119Q	--	32.8	12.5	80	3000	17.6
RL1497	37x12.50R22LT 12PR	127Q	--	36.8	12.5	80	3860	17.6
RL1498	37x13.50R20LT 12PR	128Q	--	36.5	13.6	80	3970	17.6
RL1499	37x12.50R20LT 12PR	128Q	--	36.5	12.5	80	3970	17.6
RL1500	37x13.50R22LT 12PR	128Q	--	36.5	13.6	80	3970	17.6
RL1501	LT275/70R18 10PR	125/122Q	--	33.2	11	80	3640/3305	17.6
RL1502	LT275/60R20 10PR	123/120Q	--	33	11	80	3085/2835	17.6
RL1503	LT275/65R20 12PR	128/125R	--	34.3	11	95	3640/3305	17.6
RL1504	LT285/70R17 10PR	121/118Q	--	32.8	11.5	80	3195/2910	17.6
RL1505	35x12.50R17LT 12PR	121Q	--	34.5	12.5	80	3195	17.6
RL1506	35x12.50R18LT 12PR	128Q	--	34.5	12.5	80	3970	17.6
RL1535	33x12.50R24LT 12PR	106Q		32.8	12.6	80	2095	17.4
RL1536	35x12.50R24LT 12PR	116Q		32.8	12.4	80	2755	17.4
RL1537	37x13.50R24LT 12PR	124Q		36.8	13.6	80	3525	17.4
RL1538	37x13.50R26LT 12PR	117Q		36.8	13.6	65	2835	17.4

Main Features:

- ✓ Aggressive Tread Design: Large, interlocking blocks and deep grooves provide superior traction on off-road terrains, including mud, sand, and rocky surfaces.
- ✓ Self-Cleaning Channels: Tread voids and mud-ejecting strips efficiently expel debris and mud, maintaining consistent grip in challenging environments.
- ✓ Reinforced Sidewalls: Robust sidewall lugs enhance durability and resistance to punctures, ensuring reliable performance on rugged trails..
- ✓ Optimized Pressure Distribution: Advanced tread pattern promotes even ground contact, improving climbing capabilities and stability on uneven terrain.



AETHON M/T X

Item	Size	LI/SS	UTQG	OD (Inch)	SW (Inch)	PSI	Max Load (Lbs)	T/D X/32
AR1051	35X12.50R24LT 10PR	117Q	--	34.7	12.5	65	2833	19.5

Main Features:

- ✓ Advanced Rib Tread Pattern: Multi-rib design enhances straight-line stability and promotes smooth, controlled handling.
- ✓ Long-Wear Tread Compound: Specialized rubber resists abrasion and delivers extended mileage with even wear.
- ✓ Low Noise & Low Rolling Resistance: Optimized tread geometry reduces road noise and improves fuel efficiency.
- ✓ Heavy-Duty Highway Construction: Strong casing provides dependable load capacity and durability for regional and long-haul service.



AETHON H/T III

Item	Size	LI/SS	UTQG	OD (Inch)	SW (Inch)	PSI	Max Load (Lbs)	T/D X/32
RL1539	225/75R16C 10PR	--	--	29.3	8.8	83	3195/3085	13.2
RL1540	235/65R16C 10PR	--	--	28.0	9.5	83	3195/3000	12.0



OUR CORE VALUES



PROFESSIONAL

Sutong has over 40 years of experience in the tire industry, serving as a global resource integrator and supply chain expert, with a dedicated team providing 24-hour service worldwide.



PRECISE

Sutong ensures 90-day delivery for overseas shipments, 5-day delivery from distribution centers, and 24-hour outbound for online orders, maintaining a 98% fill rate for precise and efficient service.



PERSONAL

Sutong customizes programs for each customer, treating them like family. We personalize all our services, deeply caring about our customers' success, because their success is our success.



33402 Highway 290, Hockley TX 77447
Tel: (713) 690-5500 Fax: (713) 690-5501