



SPECIALTY TIRE RADIAL

SUPERCARGO

Main Features:

- » Sophisticated Tread Pattern: Engineered for excellent performance.
- » Quality Rubber: Designed for durability and longevity.
- » Reinforced Sidewalls: Enhanced protection against damage.
- » Excellent Traction: Suitable for multiple conditions.
- » Balanced Design: Promotes even wear and better handling.

Benefits:

- » Enhanced Safety: Reduces risk of slipping.
- » Durability: Longer lifespan, fewer replacements.
- » Stable Performance: Handles well under load.
- » All-Terrain Use: Suitable for various surfaces.
- » Cost-Effective: Long-lasting, providing better value.

SC126

(All Steel STR)



Item	Size	OD (Inch)	SW (Inch)	T/D X/32	Loading Index	Max Load (Lbs)	PSI	Speed Rating
PM2001	ST235/85R16 14PR	31.73	9.25	11.97	132/127	4400/3860	110	M
PM2002	ST235/80R16 14PR	30.79	9.25	11.97	129/125	4080/3640	110	M
PM2003	ST225/90R16 14PR	31.81	8.66	15.12	132/127	4400/3860	110	M
PM2004	ST235/85R16 16PR	31.73	9.25	11.97	133/128	4540/3970	120	M
PM2005	ST235/80R16 16PR	30.79	9.25	11.97	130/126	4190/3750	120	M

Main Features:

- » **Symmetric Rib Tread Design:** Optimized for consistent highway performance and smooth wear.
- » **High-Grade Rubber Compound:** Built for extended service life and improved resistance to abrasion.
- » **Steel-Belt Reinforced:** Offers added strength and structural integrity under load.
- » **Multi-Groove Channels:** Designed to enhance water evacuation and reduce hydroplaning.
- » **Stabilized Shoulder Blocks:** Improve cornering precision and reduce irregular wear.

Benefits:

- » **Reliable Handling:** Consistent road contact ensures dependable steering response.
- » **Long-Term Durability:** Designed to endure extended mileage with minimal tread wear.
- » **Improved Wet Traction:** Enhances safety in rainy conditions.
- » **Load-Ready Structure:** Support for heavier payloads.



ST506

(Semi-Steel STR)

Item	Size	OD (Inch)	SW (Inch)	T/D X/32	Loading Index	Max Load (Lbs)	PSI	Speed Rating
PM1034	ST175/80R13 6PR	24.02	6.97	9.4	91/87	1360/1200	50	M
PM1043	ST175/80R13 8PR	24.02	6.97	9.4	97/93	1610/1430	65	M
PM1033	ST205/75R14 6PR	26.14	7.99	10.1	100/96	1760/1570	50	M
PM1042	ST205/75R14 8PR	26.14	7.99	10.1	105/101	2040/1820	65	M
PM1032	ST215/75R14 6PR	26.69	8.5	10.1	102/98	1870/1650	50	M
PM1074	ST215/75R14 8PR	26.69	8.5	10.1	108/103	2200/1930	65	M
PM1031	ST205/75R15 6PR	27.13	7.99	10.1	101/97	1820/1610	50	M
PM1001	ST205/75R15 8PR	27.13	7.99	10.1	107/102	2150/1870	65	M
PM1073	ST205/75R15 10PR	27.13	7.99	10.1	111/106	2400/2090	80	M
PM1030	ST225/75R15 8PR	28.31	8.78	10.1	113/108	2540/2200	65	M
PM1002	ST225/75R15 10PR	28.31	8.78	10.1	117/112	2830/2470	80	M
PM1040	ST235/80R16 10PR	30.79	9.25	10.8	124/120	3520/3080	80	M
PM1041	ST235/80R16 12PR	30.79	9.25	10.8	126/122	3740/3300	95	M
PM1063	ST235/85R16 10PR	31.73	9.25	10.8	125/121	3640/3200	80	M
PM1060	ST235/85R16 12PR	31.73	9.25	10.8	128/124	3960/3520	95	M
PM1065	ST205/90R15 10PR	29.62	7.95	12.6	118/113	2910/2540	80	M