



SPECIALTY TIRE RADIAL

SYNERGY

Main Features:

- » Sophisticated Tread Pattern: Engineered for excellent performance.
- » Quality Rubber: Designed for durability and longevity.
- » Reinforced Sidewalls: Enhanced protection against damage.
- » Excellent Traction: Suitable for multiple conditions.
- » Balanced Design: Promotes even wear and better handling.

Benefits:

- » Enhanced Safety: Reduces risk of slipping.
- » Durability: Longer lifespan, fewer replacements.
- » Stable Performance: Handles well under load.
- » All-Terrain Use: Suitable for various surfaces.
- » Cost-Effective: Long-lasting, providing better value.

SP500

(All Steel STR)



Item	Size	OD (Inch)	SW (Inch)	T/D X/32	Loading Index	Max Load (Lbs)	PSI	Speed Rating
SY1083	ST235/85R16 14PR	31.7	9.3	13	132/127	4400/3860	110	M
SY2154	ST235/85R16 16PR	31.7	9.3	13	133/128	4540/3970	120	M
SY1102	ST235/80R16 14PR	30.8	9.3	13	129/125	4080/3640	110	M
SY2155	ST235/80R16 16PR	30.8	9.3	13	130/126	4190/3750	120	M
SY2146	ST225/90R16 14PR	31.8	8.7	14	132/127	4400/3860	120	M
SY2171	ST205/75R15 14PR	27.1	8.0	11	115/110	2680/2340	95	N
SY2172	ST225/90R16 16PR	31.8	8.7	14	133/128	4540/3970	115	M

Main Features:

- » **Symmetric Tread Pattern:** Ensures consistent performance and improved stability.
- » **High-Quality Rubber Compound:** Offers exceptional durability and resistance to wear.
- » **Enhanced Sidewall Construction:** Provides additional strength and protection against impacts.
- » **All-Season Traction:** Optimized for reliable grip in various weather conditions.
- » **Reinforced Shoulder Blocks:** Promotes even wear and better handling.

Benefits:

- » **Increased Safety:** Reduces the risk of hydroplaning and enhances road grip..
- » **Longevity:** Extended tread life reduces the need for frequent replacements.
- » **Enhanced Durability:** Better resistance to punctures and road hazards.
- » **Versatile Performance:** Suitable for both dry and wet conditions, including light snow.
- » **Value for Money:** Long-lasting performance provides excellent cost efficiency over time.

ST801

(Semi-Steel STR)



Item	Size	OD (Inch)	SW (Inch)	T/D X/32	Loading Index	Max Load (Lbs)	PSI	Speed Rating
SYT3013	ST175/80R13 8PR	24.02	6.97	8.3	97/93	1610/1430	65	M
SYT3003	ST205/75R14 8PR	26.14	7.99	8.3	105/101	2040/1820	65	M
SYT3006	ST205/75R15 8PR	27.13	7.99	8.3	107/102	2150/1870	65	M
SYT3012	ST205/75R15 10PR	27.13	7.99	8.3	111/106	2400/2090	80	M
SYT3014	ST215/75R14 8PR	26.69	8.50	8.3	108/103	2200/1930	65	M
SYT3007	ST225/75R15 8PR	28.31	8.78	8.3	113/108	2540/2200	65	M
SYT3008	ST225/75R15 10PR	28.31	8.78	8.3	117/112	2830/2470	80	M
SYT3009	ST235/80R16 10PR	30.79	9.25	8.3	124/120	3520/3080	80	M
SYT3015	ST235/85R16 10PR	31.70	9.25	8.3	128/124	3640/3200	80	M
SYT3018	ST205/75R14 10PR	26.10	8.00	9.0	109/104	2270/1984	80	M

OUR CORE VALUES



PROFESSIONAL

Sutong has over 40 years of experience in the tire industry, serving as a global resource integrator and supply chain expert, with a dedicated team providing 24-hour service worldwide.



PRECISE

Sutong ensures 90-day delivery for overseas shipments, 5-day delivery from distribution centers, and 24-hour outbound for online orders, maintaining a 98% fill rate for precise and efficient service.



PERSONAL

Sutong customizes programs for each customer, treating them like family. We personalize all our services, deeply caring about our customers' success, because their success is our success.



33402 Highway 290, Hockley TX 77447
Tel: (713) 690-5500 Fax: (713) 690-5501