3GPP TS 36.211 V14.7.0 (2018-06)

Technical Specification

3rd Generation Partnership Project; Technical Specification Group Radio Access Network; Evolved Universal Terrestrial Radio Access (E-UTRA); Physical channels and modulation (Release 14)





Keywords E-UTRA, radio, layer 1

3GPP

Postal address

3GPP support office address

650 Route des Lucioles - Sophia Antipolis Valbonne - FRANCE Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

1 a.x. + 00 1 00 0

Internet

http://www.3gpp.org

Copyright Notification

No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© 2018, 3GPP Organizational Partners (ARIB, ATIS, CCSA, ETSI, TSDSI, TTA, TTC). All rights reserved.

UMTSTM is a Trade Mark of ETSI registered for the benefit of its members 3GPPTM is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners LTETM is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners GSM® and the GSM logo are registered and owned by the GSM Association

Contents

Forew	vord	8
1	Scope	9
2	References	9
3	Symbols and abbreviations.	9
3.1	Symbols	
3.2	Abbreviations	
4	Frame structure	14
4.1	Frame structure type 1	
4.2	Frame structure type 2	
4.3	Frame structure type 3	
5	Uplink	18
5.1	Overview	18
5.1.1	Physical channels	18
5.1.2	Physical signals	18
5.2	Slot structure and physical resources	
5.2.1	Resource grid	
5.2.2	Resource elements	
5.2.3	Resource blocks	
5.2.4	Narrowbands and widebands	
5.2.5	Guard period for narrowband and wideband retuning	
5.3	Physical uplink shared channel	
5.3.1	Scrambling	
5.3.2	Modulation	
5.3.2A		
5.3.2A	J 11 0 0 1	
5.3.2A		
5.3.3	Transform precoding	
5.3.3A		
5.3.3A		
5.3.3A		
5.3.4	Mapping to physical resources	
5.4	Physical uplink control channel	
5.4.1	PUCCH formats 1, 1a and 1b	
5.4.2	PUCCH formats 2, 2a and 2b	
5.4.2A		
5.4.2B		
5.4.2C		
5.4.3	Mapping to physical resources	
5.5	Reference signals	
5.5.1	Generation of the reference signal sequence	
5.5.1.1		
5.5.1.2	1 50	
5.5.1.3	1 11 6	
5.5.1.4	1 11 6	
5.5.1.5		
5.5.2	Demodulation reference signal	
5.5.2.1	6	
5.5.2.1		
5.5.2.1		
5.5.2.2	<u> </u>	
5.5.2.2		
5.5.2.2		
5.5.3	Sounding reference signal	
5.5.3.1		
5.5.3.2	2 Mapping to physical resources	56

5.5.3.3	Sounding reference signal subframe configuration	
5.6	SC-FDMA baseband signal generation	
5.7	Physical random access channel	
5.7.1	Time and frequency structure	
5.7.2	Preamble sequence generation	
5.7.3	Baseband signal generation	73
5.8	Modulation and upconversion	74
6	Downlink	75
6.1	Overview	
6.1.1	Physical channels	
6.1.2	Physical signals	
6.2	Slot structure and physical resource elements	
6.2.1	Resource grid	
6.2.2	Resource elements	
6.2.3		
6.2.3.1	Resource blocks	
6.2.3.1	Virtual resource blocks of localized type	
6.2.4	Virtual resource blocks of distributed type	
6.2.4A	Resource-element groups	
	Enhanced Resource-Element Groups (EREGs)	
6.2.5	Guard period for half-duplex FDD operation	
6.2.6	Guard Period for TDD Operation	
6.2.7	Narrowbands and widebands	
6.2.8	Guard period for narrowband and wideband retuning	
6.3	General structure for downlink physical channels	
6.3.1	Scrambling	
6.3.2	Modulation	
6.3.3	Layer mapping	
6.3.3.1	Layer mapping for transmission on a single antenna port	
6.3.3.2	Layer mapping for spatial multiplexing	
6.3.3.3	Layer mapping for transmit diversity	
6.3.4	Precoding	
6.3.4.1	Precoding for transmission on a single antenna port	
6.3.4.2	Precoding for spatial multiplexing using antenna ports with cell-specific reference signals	
6.3.4.2.	$\boldsymbol{\varepsilon}$	
6.3.4.2.		
6.3.4.2.		
6.3.4.3	Precoding for transmit diversity	
6.3.4.4	Precoding for spatial multiplexing using antenna ports with UE-specific reference signals	
6.3.5	Mapping to resource elements	
6.4	Physical downlink shared channel	
6.4.1	Physical downlink shared channel for BL/CE UEs	
6.5	Physical multicast channel	
6.6	Physical broadcast channel	
6.6.1	Scrambling	
6.6.2	Modulation	
6.6.3	Layer mapping and precoding	
6.6.4	Mapping to resource elements	
6.7	Physical control format indicator channel	
6.7.1	Scrambling	
6.7.2	Modulation	
6.7.3	Layer mapping and precoding	
6.7.4	Mapping to resource elements	
6.8	Physical downlink control channel	
6.8.1	PDCCH formats	
6.8.2	PDCCH multiplexing and scrambling	
6.8.3	Modulation	
6.8.4	Layer mapping and precoding	
6.8.5	Mapping to resource elements	
6.8A	Enhanced physical downlink control channel	
6.8A.1	EPDCCH formats	
6.8A.2	Scrambling	104

6.8A.3	Modulation	104
6.8A.4	Layer mapping and precoding	104
6.8A.5	Mapping to resource elements	104
6.8B	MTC physical downlink control channel	105
6.8B.1	MPDCCH formats	105
6.8B.2	Scrambling	106
6.8B.3		
6.8B.4	Layer mapping and precoding	107
6.8B.5	11 6	
6.9	Physical hybrid ARQ indicator channel	
6.9.1	Modulation	
6.9.2	Resource group alignment, layer mapping and precoding	
6.9.3	Mapping to resource elements	112
6.10	Reference signals	
6.10.1	Cell-specific Reference Signal (CRS)	
6.10.1.	1 &	
6.10.1.	11 0	
6.10.2	MBSFN reference signals	
6.10.2.	1 &	
6.10.2.		
6.10.2.	1 8	
6.10.2.	11 0	
6.10.2.	11 6	
6.10.2.		
6.10.3	UE-specific reference signals associated with PDSCH	
6.10.3.	1 &	
6.10.3.	11 6	
6.10.3	8	
6.10.3	\mathcal{L}	
6.10.3	11 6	
6.10.4	Positioning reference signals	
6.10.4.	\mathcal{L}	
6.10.4.	11 6	
6.10.4.		
6.10.5	CSI reference signals	
6.10.5.	\mathcal{L}	
6.10.5.		
6.10.5.	- 6	
6.11	Synchronization signals	
6.11.1	Primary synchronization signal (PSS)	
6.11.1.	\mathcal{L}	
6.11.1.	11 8	
6.11.2	Secondary synchronization signal (SSS)	
6.11.2.	- 1 8	
6.11.2.	11 6	
6.11A	Discovery signal	
6.12	OFDM baseband signal generation.	
6.13	Modulation and upconversion	140
7	Generic functions	148
7.1	Modulation mapper	148
7.1.1	BPSK	
7.1.2	QPSK	148
7.1.3	16QAM	148
7.1.4	64QAM	
7.1.5	256QAM	151
7.2	Pseudo-random sequence generation	154
Q	Timing	154
	Timing	
8.1	Uplink-downlink frame timing	134
9	Sidelink	155
9.1	Overview	155

9.1.1	Physical channels	
9.1.2	Physical signals	
9.1.3	Handling of simultaneous sidelink and uplink/downlink transmissions	155
9.2	Slot structure and physical resources	156
9.2.1	Resource grid	156
9.2.2	Resource elements	156
9.2.3	Resource blocks	157
9.2.4	Resource pool	157
9.2.5	Guard period	
9.3	Physical Sidelink Shared Channel	
9.3.1	Scrambling	
9.3.2	Modulation	
9.3.3	Layer mapping	
9.3.4	Transform precoding	
9.3.5	Precoding	
9.3.6	Mapping to physical resources	
9.4	Physical Sidelink Control Channel	
9.4.1	Scrambling	
9.4.2	Modulation	
9.4.3	Layer mapping	
9.4.4	Transform precoding	
9.4.5	Precoding Precoding	
9.4.5 9.4.6	Mapping to physical resources	
9.4.0 9.5	Physical Sidelink Discovery Channel	
-	Scrambling	
9.5.1	6	
9.5.2	Modulation	
9.5.3	Layer mapping	
9.5.4	Transform precoding	
9.5.5	Precoding	
9.5.6	Mapping to physical resources	
9.6	Physical Sidelink Broadcast Channel	
9.6.1	Scrambling	
9.6.2	Modulation	
9.6.3	Layer mapping	
9.6.4	Transform precoding	
9.6.5	Precoding	
9.6.6	Mapping to physical resources	
9.7	Sidelink Synchronization Signals	
9.7.1	Primary sidelink synchronization signal	
9.7.1.1	Sequence generation	
9.7.1.2	Mapping to resource elements	
9.7.2	Secondary sidelink synchronization signal	
9.7.2.1	Sequence generation	
9.7.2.2	Mapping to resource elements	
9.8	Demodulation reference signals	
9.9	SC-FDMA baseband signal generation.	164
9.10	Timing	164
10 NI	Townson A LoT	165
	arrowband IoT	
10.1	Uplink	
10.1.1	Overview	
10.1.1.1	Physical channels	
10.1.1.2	Physical signals	
10.1.2	Slot structure and physical resources	
10.1.2.1	Resource grid	
10.1.2.2	Resource elements	
10.1.2.3	Resource unit	
10.1.3	Narrowband physical uplink shared channel	
10.1.3.1	Scrambling	
10.1.3.2	Modulation	
10.1.3.3	Layer mapping	
10 1 3 4	Transform precoding	167

Annex A	(informative): Change history	188
10.2.3	woodiation and appointersion	10/
10.2.8	Modulation and upconversion	
10.2.7.2.2	OFDM baseband signal generation	
10.2.7.2.1	Mapping to resource elements	
10.2.7.2.1	Sequence generation	
10.2.7.1.2	Narrowband secondary synchronization signal (NSSS)	
10.2.7.1.2	Mapping to resource elements	
10.2.7.1	Sequence generation	
10.2.7.1	Narrowband primary synchronization signal (NPSS)	
10.2.7	Synchronization signals	
10.2.6A.3	NPRS subframe configuration	
10.2.6A.2	Mapping to resource elements	
10.2.6A.1	Sequence generation	
10.2.6A	Narrowband positioning reference signal (NPRS)	
10.2.6.2	Mapping to resource elements	
10.2.6.1	Sequence generation	181
10.2.6	Narrowband reference signal (NRS)	179
10.2.5.5	Mapping to resource elements	
10.2.5.4	Layer mapping and precoding	
10.2.5.3	Modulation	
10.2.5.2	Scrambling	
10.2.5.1	NPDCCH formats	
10.2.5	Narrowband physical downlink control channel	
10.2.4.4	Mapping to resource elements	
10.2.4.3	Layer mapping and precoding	
10.2.4.2	Modulation	
10.2.4.1	Scrambling	
10.2.4	Narrowband physical broadcast channel	
10.2.3.4	Mapping to resource elements	
10.2.3.3	Layer mapping and precoding	
10.2.3.2	Modulation	
	Scrambling	
10.2.3		
10.2.2.3	Narrowband physical downlink shared channel	
10.2.2.2	Guard period for half-duplex FDD operation	
10.2.2.1	Resource elements	
10.2.2.1	Resource grid	
10.2.2	Slot structure and physical resource elements	
10.2.1.2	Physical signals	
10.2.1.1	Physical channels	
10.2.1	Overview	
	Downlink	
10.1.7	Modulation and upconversion	
10.1.6.2	Baseband signal generation	
10.1.6.1	Time and frequency structure	
10.1.6	Narrowband physical random access channel	172
10.1.5	SC-FDMA baseband signal generation	171
10.1.4.2	Mapping to physical resources	171
10.1.4.1.3	Group hopping	170
10.1.4.1.2	Reference signal sequence for $N_{\rm sc}^{\rm RU} > 1$	169
10.1.4.1.1	Reference signal sequence for $N_{\rm sc}^{\rm RU} = 1$	
10.1.4.1	Reference signal sequence	
10.1.4	Demodulation reference signal	
10.1.3.6	Mapping to physical resources	
10.1.3.5	Precoding	167