

Lecture 7:

Training Neural Networks

Where we are now...


Neural Networks

Linear score function:

$$f = Wx$$


2-layer Neural Network

$$f = W_2 \max(0, W_1 x)$$




Where we are now...

Convolutional Neural Networks




Where we are now...

Convolutional Layer




activation map




Where we are now...

Convolutional Layer



Convolution Layer







We stack these up to get a “new image” of size 28x28x6!

For example, if we had 6 5x5 filters, we'll get 6 separate activation maps:


Where we are now...

CNN Architectures



Where we are now...

Learning network parameters through optimization



[Landscape image](#) is [CC0 1.0](#) public domain
[Walking man image](#) is [CC0 1.0](#) public domain

```
# Vanilla Gradient Descent

while True:
    weights_grad = evaluate_gradient(loss_fun, data, weights)
    weights += - step_size * weights_grad # perform parameter update
```

Where we are now...

Mini-batch SGD

Loop:

1. **Sample** a batch of data
2. **Forward** prop it through the graph (network), get loss
3. **Backprop** to calculate the gradients
4. **Update** the parameters using the gradient


Today: Training Neural Networks

Overview

1. **One time set up:** activation functions, preprocessing, weight initialization, regularization, gradient checking
2. **Training dynamics:** babysitting the learning process, parameter updates, hyperparameter optimization
3. **Evaluation:** model ensembles, test-time augmentation, transfer learning

Activation Functions


Activation Functions



Activation Functions


Sigmoid

$$\sigma(x) = \frac{1}{1+e^{-x}}$$




tanh

$$\tanh(x)$$




ReLU

$$\max(0, x)$$



Leaky ReLU

$$\max(0.1x, x)$$




Maxout


$$\max(w_1^T x + b_1, w_2^T x + b_2)$$

ELU

$$\begin{cases} x & x \geq 0 \\ \alpha(e^x - 1) & x < 0 \end{cases}$$



Activation Functions




Sigmoid

$$\sigma(x) = 1/(1 + e^{-x})$$

- Squashes numbers to range [0,1]
- Historically popular since they have nice interpretation as a saturating “firing rate” of a neuron

Activation Functions





Sigmoid

$$\sigma(x) = 1/(1 + e^{-x})$$



- Squashes numbers to range $[0,1]$
- Historically popular since they have nice interpretation as a saturating “firing rate” of a neuron

3 problems:

1. Saturated neurons “kill” the gradients





$$\frac{\partial \sigma(x)}{\partial x} = \sigma(x) (1 - \sigma(x))$$



What happens when $x = -10$?

$$\frac{\partial \sigma(x)}{\partial x} = \sigma(x) (1 - \sigma(x))$$





What happens when $x = -10$?

$$\sigma(x) \approx 0$$

$$\frac{\partial \sigma(x)}{\partial x} = \sigma(x) (1 - \sigma(x)) = 0(1 - 0) = 0$$



$$\frac{\partial \sigma(x)}{\partial x} = \sigma(x) (1 - \sigma(x))$$



What happens when $x = -10$?

What happens when $x = 0$?

$$\frac{\partial \sigma(x)}{\partial x} = \sigma(x) (1 - \sigma(x))$$





What happens when $x = -10$?

What happens when $x = 0$?



What happens when $x = 10$?

$$\frac{\partial \sigma(x)}{\partial x} = \sigma(x) (1 - \sigma(x))$$

$$\sigma(x) \approx 1 \quad \frac{\partial \sigma(x)}{\partial x} = \sigma(x) (1 - \sigma(x)) = 1(1 - 1) = 0$$



$$\frac{\partial \sigma(x)}{\partial x} = \sigma(x) (1 - \sigma(x))$$




Why is this a problem?

If all the gradients flowing back will be zero and weights will never change

$$\frac{\partial \sigma(x)}{\partial x} = \sigma(x) (1 - \sigma(x))$$

Activation Functions



Sigmoid

$$\sigma(x) = 1/(1 + e^{-x})$$


- Squashes numbers to range $[0,1]$
- Historically popular since they have nice interpretation as a saturating “firing rate” of a neuron

3 problems:

1. Saturated neurons “kill” the gradients
2. Sigmoid outputs are not zero-centered

Consider what happens when the input to a neuron is always positive...


$$f\left(\sum_i w_i x_i + b\right)$$



What can we say about the gradients on **w**?

Consider what happens when the input to a neuron is always positive...

$$f\left(\sum_i w_i x_i + b\right)$$




What can we say about the gradients on **w**?

$$\frac{\partial L}{\partial w} = \sigma(\sum_i w_i x_i + b)(1 - \sigma(\sum_i w_i x_i + b))x \times upstream_gradient$$

Consider what happens when the input to a neuron is always positive...

$$f\left(\sum_i w_i x_i + b\right)$$




What can we say about the gradients on \mathbf{w} ?

We know that local gradient of sigmoid is always positive

$$\frac{\partial L}{\partial w} = \sigma(\sum_i w_i x_i + b)(1 - \sigma(\sum_i w_i x_i + b))x \times upstream_gradient$$

Consider what happens when the input to a neuron is always positive...

$$f\left(\sum_i w_i x_i + b\right)$$



What can we say about the gradients on \mathbf{w} ?


We know that local gradient of sigmoid is always positive

We are assuming x is always positive

$$\frac{\partial L}{\partial w} = \sigma(\sum_i w_i x_i + b)(1 - \sigma(\sum_i w_i x_i + b))x \times upstream_gradient$$

Consider what happens when the input to a neuron is always positive...

$$f\left(\sum_i w_i x_i + b\right)$$



What can we say about the gradients on **w**?

We know that local gradient of sigmoid is always positive


We are assuming x is always positive

So!! Sign of gradient **for all w_i** is the same as the sign of upstream scalar gradient!

$$\frac{\partial L}{\partial w} = \sigma\left(\sum_i w_i x_i + b\right)(1 - \sigma\left(\sum_i w_i x_i + b\right))x \times \text{upstream_gradient}$$

Consider what happens when the input to a neuron is always positive...

$$f\left(\sum_i w_i x_i + b\right)$$




What can we say about the gradients on \mathbf{w} ?

Always all positive or all negative :(

Consider what happens when the input to a neuron is always positive...

$$f\left(\sum_i w_i x_i + b\right)$$




What can we say about the gradients on **w**?

Always all positive or all negative :(

(For a single element! Minibatches help)

Activation Functions



Sigmoid


$$\sigma(x) = 1/(1 + e^{-x})$$

- Squashes numbers to range $[0,1]$
- Historically popular since they have nice interpretation as a saturating “firing rate” of a neuron

3 problems:

1. Saturated neurons “kill” the gradients
2. Sigmoid outputs are not zero-centered
3. $\exp()$ is a bit compute expensive


Activation Functions



$\tanh(x)$

- Squashes numbers to range $[-1,1]$
- zero centered (nice)
- still kills gradients when saturated :(

Activation Functions




ReLU
(Rectified Linear Unit)

- Computes $f(x) = \max(0, x)$
- Does not saturate (in +region)
- Very computationally efficient
- Converges much faster than sigmoid/tanh in practice (e.g. 6x)

[Krizhevsky et al., 2012]


Activation Functions



ReLU
(Rectified Linear Unit)

- Computes $f(x) = \max(0, x)$
- Does not saturate (in +region)
- Very computationally efficient
- Converges much faster than sigmoid/tanh in practice (e.g. 6x)
- Not zero-centered output



Activation Functions



ReLU
(Rectified Linear Unit)

- Computes $f(x) = \max(0, x)$
- Does not saturate (in +region)
- Very computationally efficient
- Converges much faster than sigmoid/tanh in practice (e.g. 6x)
- Not zero-centered output
- An annoyance:


hint: what is the gradient when $x < 0$?




What happens when $x = -10$?

What happens when $x = 0$?


What happens when $x = 10$?





Activation Functions

[Mass et al., 2013]
[He et al., 2015]




- Does not saturate
- Computationally efficient
- Converges much faster than sigmoid/tanh in practice! (e.g. 6x)
- **will not “die”.**

Leaky ReLU

$$f(x) = \max(0.01x, x)$$

Activation Functions

[Mass et al., 2013]
[He et al., 2015]



Leaky ReLU

$$f(x) = \max(0.01x, x)$$

- Does not saturate
- Computationally efficient
- Converges much faster than sigmoid/tanh in practice! (e.g. 6x)
- **will not “die”.**

Parametric Rectifier (PReLU)


$$f(x) = \max(\alpha x, x)$$

backprop into α (parameter)

Activation Functions

[Clevert et al., 2015]

Exponential Linear Units (ELU)



- All benefits of ReLU
- Closer to zero mean outputs
- Negative saturation regime compared with Leaky ReLU adds some robustness to noise

$$f(x) = \begin{cases} x & \text{if } x > 0 \\ \alpha (\exp(x) - 1) & \text{if } x \leq 0 \end{cases}$$


(Alpha default = 1)

- Computation requires $\exp()$

Activation Functions

[Klambauer et al. ICLR 2017]

Scaled Exponential Linear Units (SELU)



- Scaled version of ELU that works better for deep networks
- “Self-normalizing” property;
- Can train deep SELU networks without BatchNorm

$$f(x) = \begin{cases} \lambda x & \text{if } x > 0 \\ \lambda \alpha (e^x - 1) & \text{otherwise} \end{cases}$$

$$\alpha = 1.6732632423543772848170429916717$$

$$\lambda = 1.0507009873554804934193349852946$$

Maxout “Neuron”

[Goodfellow et al., 2013]

- Does not have the basic form of dot product -> nonlinearity
- Generalizes ReLU and Leaky ReLU
- Linear Regime! Does not saturate! Does not die!

$$\max(w_1^T x + b_1, w_2^T x + b_2)$$


Problem: doubles the number of parameters/neuron :(

TLDR: In practice:

- Use **ReLU**. Be careful with your learning rates
- Try out **Leaky ReLU / Maxout / ELU / SELU**
 - To squeeze out some marginal gains
- Don't use **sigmoid** or **tanh**

Data Preprocessing


Data Preprocessing



(Assume X [NxD] is data matrix,
each example in a row)

Remember: Consider what happens when the input to a neuron is always positive...

$$f\left(\sum_i w_i x_i + b\right)$$




What can we say about the gradients on \mathbf{w} ?

Always all positive or all negative :(

(this is also why you want zero-mean data!)


Data Preprocessing



(Assume X [NxD] is data matrix, each example in a row)


Data Preprocessing

In practice, you may also see **PCA** and **Whitening** of the data




Data Preprocessing

Before normalization: classification loss very sensitive to changes in weight matrix; hard to optimize



After normalization: less sensitive to small changes in weights; easier to optimize



TLDR: In practice for Images: center only


e.g. consider CIFAR-10 example with [32,32,3] images

- Subtract the mean image (e.g. AlexNet)
(mean image = [32,32,3] array)
- Subtract per-channel mean (e.g. VGGNet)
(mean along each channel = 3 numbers)
- Subtract per-channel mean and
Divide by per-channel std (e.g. ResNet)
(mean along each channel = 3 numbers)

Not common
to do PCA or
whitening

Weight Initialization

- Q: what happens when $W=\text{constant}$ init is used?



- First idea: **Small random numbers**
(gaussian with zero mean and $1e-2$ standard deviation)

```
W = 0.01 * np.random.randn(Din, Dout)
```

- First idea: **Small random numbers**
(gaussian with zero mean and $1e-2$ standard deviation)

```
W = 0.01 * np.random.randn(Din, Dout)
```

Works ~okay for small networks, but problems with deeper networks.

Weight Initialization: Activation statistics

```
dims = [4096] * 7      Forward pass for a 6-layer  
                        net with hidden size 4096  
hs = []  
x = np.random.randn(16, dims[0])  
for Din, Dout in zip(dims[:-1], dims[1:]):  
    W = 0.01 * np.random.randn(Din, Dout)  
    x = np.tanh(x.dot(W))  
    hs.append(x)
```


What will happen to the activations for the last layer?

Weight Initialization: Activation statistics

```
dims = [4096] * 7      Forward pass for a 6-layer
hs = []                net with hidden size 4096
x = np.random.randn(16, dims[0])
for Din, Dout in zip(dims[:-1], dims[1:]):
    W = 0.01 * np.random.randn(Din, Dout)
    x = np.tanh(x.dot(W))
    hs.append(x)
```

All activations tend to zero for deeper network layers

Q: What do the gradients dL/dW look like?




Weight Initialization: Activation statistics

```
dims = [4096] * 7      Forward pass for a 6-layer
hs = []                net with hidden size 4096
x = np.random.randn(16, dims[0])
for Din, Dout in zip(dims[:-1], dims[1:]):
    W = 0.01 * np.random.randn(Din, Dout)
    x = np.tanh(x.dot(W))
    hs.append(x)
```

All activations tend to zero for deeper network layers

Q: What do the gradients dL/dW look like?

A: All zero, no learning =



Weight Initialization: Activation statistics

```
dims = [4096] * 7    Increase std of initial
hs = []              weights from 0.01 to 0.05
x = np.random.randn(16, dims[0])
for Din, Dout in zip(dims[:-1], dims[1:]):
    W = 0.05 * np.random.randn(Din, Dout)
    x = np.tanh(x.dot(W))
    hs.append(x)
```


What will happen to the activations for the last layer?

Weight Initialization: Activation statistics

```
dims = [4096] * 7    Increase std of initial
hs = []              weights from 0.01 to 0.05
x = np.random.randn(16, dims[0])
for Din, Dout in zip(dims[:-1], dims[1:]):
    W = 0.05 * np.random.randn(Din, Dout)
    x = np.tanh(x.dot(W))
    hs.append(x)
```

All activations saturate

Q: What do the gradients look like?




Weight Initialization: Activation statistics

```
dims = [4096] * 7    Increase std of initial
hs = []              weights from 0.01 to 0.05
x = np.random.randn(16, dims[0])
for Din, Dout in zip(dims[:-1], dims[1:]):
    W = 0.05 * np.random.randn(Din, Dout)
    x = np.tanh(x.dot(W))
    hs.append(x)
```

All activations saturate

Q: What do the gradients look like?

A: Local gradients all zero, no learning =(



Weight Initialization: “Xavier” Initialization


```
dims = [4096] * 7          "Xavier" initialization:
hs = []                    std = 1/sqrt(Din)
x = np.random.randn(16, dims[0])
for Din, Dout in zip(dims[:-1], dims[1:]):
    W = np.random.randn(Din, Dout) / np.sqrt(Din)
    x = np.tanh(x.dot(W))
    hs.append(x)
```

Weight Initialization: “Xavier” Initialization

```
dims = [4096] * 7
hs = []
x = np.random.randn(16, dims[0])
for Din, Dout in zip(dims[:-1], dims[1:]):
    W = np.random.randn(Din, Dout) / np.sqrt(Din)
    x = np.tanh(x.dot(W))
    hs.append(x)
```

“Xavier” initialization:
 $\text{std} = 1/\sqrt{D_{\text{in}}}$

“Just right”: Activations are nicely scaled for all layers!




Weight Initialization: “Xavier” Initialization

```
dims = [4096] * 7
hs = []
x = np.random.randn(16, dims[0])
for Din, Dout in zip(dims[:-1], dims[1:]):
    W = np.random.randn(Din, Dout) / np.sqrt(Din)
    x = np.tanh(x.dot(W))
    hs.append(x)
```

“Xavier” initialization:
 $\text{std} = 1/\sqrt{D_{\text{in}}}$

“Just right”: Activations are nicely scaled for all layers!

For conv layers, D_{in} is $\text{filter_size}^2 * \text{input_channels}$



Weight Initialization: “Xavier” Initialization

```
dims = [4096] * 7
hs = []
x = np.random.randn(16, dims[0])
for Din, Dout in zip(dims[:-1], dims[1:]):
    W = np.random.randn(Din, Dout) / np.sqrt(Din)
    x = np.tanh(x.dot(W))
    hs.append(x)
```

“Xavier” initialization:
std = $1/\sqrt{D_{in}}$

“Just right”: Activations are nicely scaled for all layers!

For conv layers, D_{in} is $\text{filter_size}^2 * \text{input_channels}$

Let: $y = x_1 w_1 + x_2 w_2 + \dots + x_{D_{in}} w_{D_{in}}$

Weight Initialization: “Xavier” Initialization

```
dims = [4096] * 7
hs = []
x = np.random.randn(16, dims[0])
for Din, Dout in zip(dims[:-1], dims[1:]):
    W = np.random.randn(Din, Dout) / np.sqrt(Din)
    x = np.tanh(x.dot(W))
    hs.append(x)
```

“Xavier” initialization:
std = $1/\sqrt{D_{in}}$

“Just right”: Activations are nicely scaled for all layers!

For conv layers, D_{in} is $\text{filter_size}^2 * \text{input_channels}$

Let: $y = x_1 w_1 + x_2 w_2 + \dots + x_{D_{in}} w_{D_{in}}$

Assume: $\text{Var}(x_1) = \text{Var}(x_2) = \dots = \text{Var}(x_{D_{in}})$

Weight Initialization: “Xavier” Initialization

```
dims = [4096] * 7
hs = []
x = np.random.randn(16, dims[0])
for Din, Dout in zip(dims[:-1], dims[1:]):
    W = np.random.randn(Din, Dout) / np.sqrt(Din)
    x = np.tanh(x.dot(W))
    hs.append(x)
```

“Xavier” initialization:
std = $1/\sqrt{D_{in}}$

“Just right”: Activations are nicely scaled for all layers!

For conv layers, D_{in} is $\text{filter_size}^2 * \text{input_channels}$

Let: $y = x_1 w_1 + x_2 w_2 + \dots + x_{D_{in}} w_{D_{in}}$

Assume: $\text{Var}(x_1) = \text{Var}(x_2) = \dots = \text{Var}(x_{D_{in}})$

We want: $\text{Var}(y) = \text{Var}(x_i)$

Weight Initialization: “Xavier” Initialization

```
dims = [4096] * 7
hs = []
x = np.random.randn(16, dims[0])
for Din, Dout in zip(dims[:-1], dims[1:]):
    W = np.random.randn(Din, Dout) / np.sqrt(Din)
    x = np.tanh(x.dot(W))
    hs.append(x)
```

“Xavier” initialization:
std = $1/\sqrt{D_{in}}$

“Just right”: Activations are nicely scaled for all layers!

For conv layers, D_{in} is $\text{filter_size}^2 * \text{input_channels}$

Let: $y = x_1 w_1 + x_2 w_2 + \dots + x_{D_{in}} w_{D_{in}}$

Assume: $\text{Var}(x_1) = \text{Var}(x_2) = \dots = \text{Var}(x_{D_{in}})$

We want: $\text{Var}(y) = \text{Var}(x_i)$

$\text{Var}(y) = \text{Var}(x_1 w_1 + x_2 w_2 + \dots + x_{D_{in}} w_{D_{in}})$
[substituting value of y]

Weight Initialization: “Xavier” Initialization

```
dims = [4096] * 7
hs = []
x = np.random.randn(16, dims[0])
for Din, Dout in zip(dims[:-1], dims[1:]):
    W = np.random.randn(Din, Dout) / np.sqrt(Din)
    x = np.tanh(x.dot(W))
    hs.append(x)
```

“Xavier” initialization:
std = $1/\sqrt{D_{in}}$

“Just right”: Activations are nicely scaled for all layers!

For conv layers, D_{in} is $\text{filter_size}^2 * \text{input_channels}$

Let: $y = x_1 w_1 + x_2 w_2 + \dots + x_{D_{in}} w_{D_{in}}$

Assume: $\text{Var}(x_1) = \text{Var}(x_2) = \dots = \text{Var}(x_{D_{in}})$

We want: $\text{Var}(y) = \text{Var}(x_i)$

$$\begin{aligned}\text{Var}(y) &= \text{Var}(x_1 w_1 + x_2 w_2 + \dots + x_{D_{in}} w_{D_{in}}) \\ &= D_{in} \text{Var}(x_i w_i)\end{aligned}$$

[Assume all x_i, w_i are iid]

Weight Initialization: “Xavier” Initialization

```
dims = [4096] * 7
hs = []
x = np.random.randn(16, dims[0])
for Din, Dout in zip(dims[:-1], dims[1:]):
    W = np.random.randn(Din, Dout) / np.sqrt(Din)
    x = np.tanh(x.dot(W))
    hs.append(x)
```

“Xavier” initialization:
std = $1/\sqrt{D_{in}}$

“Just right”: Activations are nicely scaled for all layers!

For conv layers, D_{in} is $\text{filter_size}^2 * \text{input_channels}$

Let: $y = x_1 w_1 + x_2 w_2 + \dots + x_{D_{in}} w_{D_{in}}$

Assume: $\text{Var}(x_1) = \text{Var}(x_2) = \dots = \text{Var}(x_{D_{in}})$

We want: $\text{Var}(y) = \text{Var}(x_i)$

$$\begin{aligned}\text{Var}(y) &= \text{Var}(x_1 w_1 + x_2 w_2 + \dots + x_{D_{in}} w_{D_{in}}) \\ &= D_{in} \text{Var}(x_i w_i) \\ &= D_{in} \text{Var}(x_i) \text{Var}(w_i)\end{aligned}$$

[Assume all x_i, w_i are zero mean]

Weight Initialization: “Xavier” Initialization

```
dims = [4096] * 7
hs = []
x = np.random.randn(16, dims[0])
for Din, Dout in zip(dims[:-1], dims[1:]):
    W = np.random.randn(Din, Dout) / np.sqrt(Din)
    x = np.tanh(x.dot(W))
    hs.append(x)
```

“Xavier” initialization:
std = $1/\sqrt{D_{in}}$

“Just right”: Activations are nicely scaled for all layers!

For conv layers, D_{in} is $\text{filter_size}^2 * \text{input_channels}$

Let: $y = x_1 w_1 + x_2 w_2 + \dots + x_{D_{in}} w_{D_{in}}$

Assume: $\text{Var}(x_1) = \text{Var}(x_2) = \dots = \text{Var}(x_{D_{in}})$

We want: $\text{Var}(y) = \text{Var}(x_i)$

$$\begin{aligned}\text{Var}(y) &= \text{Var}(x_1 w_1 + x_2 w_2 + \dots + x_{D_{in}} w_{D_{in}}) \\ &= D_{in} \text{Var}(x_i w_i) \\ &= D_{in} \text{Var}(x_i) \text{Var}(w_i) \\ &[\text{Assume all } x_i, w_i \text{ are iid}]\end{aligned}$$

So, $\text{Var}(y) = \text{Var}(x_i)$ only when $\text{Var}(w_i) = 1/D_{in}$

Weight Initialization: What about ReLU?


```
dims = [4096] * 7      Change from tanh to ReLU
hs = []
x = np.random.randn(16, dims[0])
for Din, Dout in zip(dims[:-1], dims[1:]):
    W = np.random.randn(Din, Dout) / np.sqrt(Din)
    x = np.maximum(0, x.dot(W))
    hs.append(x)
```


Weight Initialization: What about ReLU?

```
dims = [4096] * 7      Change from tanh to ReLU
hs = []
x = np.random.randn(16, dims[0])
for Din, Dout in zip(dims[:-1], dims[1:]):
    W = np.random.randn(Din, Dout) / np.sqrt(Din)
    x = np.maximum(0, x.dot(W))
    hs.append(x)
```

Xavier assumes zero centered activation function

Activations collapse to zero again, no learning =(




Weight Initialization: Kaiming / MSRA Initialization

```
dims = [4096] * 7
hs = []
x = np.random.randn(16, dims[0])
for Din, Dout in zip(dims[:-1], dims[1:]):
    W = np.random.randn(Din, Dout) * np.sqrt(2/Din)
    x = np.maximum(0, x.dot(W))
    hs.append(x)
```

ReLU correction: $\text{std} = \sqrt{2 / \text{Din}}$

“Just right”: Activations are nicely scaled for all layers!



Proper initialization is an active area of research...

Understanding the difficulty of training deep feedforward neural networks

by Glorot and Bengio, 2010

Exact solutions to the nonlinear dynamics of learning in deep linear neural networks by Saxe et al, 2013

Random walk initialization for training very deep feedforward networks by Sussillo and Abbott, 2014

Delving deep into rectifiers: Surpassing human-level performance on ImageNet classification by He et al., 2015

Data-dependent Initializations of Convolutional Neural Networks by Krähenbühl et al., 2015



All you need is a good init, Mishkin and Matas, 2015

Fixup Initialization: Residual Learning Without Normalization, Zhang et al, 2019


The Lottery Ticket Hypothesis: Finding Sparse, Trainable Neural Networks, Frankle and Carbin, 2019

Training vs. Testing Error

Beyond Training Error



Early Stopping: Always do this



Stop training the model when accuracy on the validation set decreases
Or train for a long time, but always keep track of the model snapshot
that worked best on val


Model Ensembles

1. Train multiple independent models
2. At test time average their results

(Take average of predicted probability distributions, then choose argmax)

Enjoy 2% extra performance

How to improve single-model performance?



Regularization

Regularization: Add term to loss

$$L = \frac{1}{N} \sum_{i=1}^N \sum_{j \neq y_i} \max(0, f(x_i; W)_j - f(x_i; W)_{y_i} + 1) + \lambda R(W)$$

In common use:

L2 regularization

$$R(W) = \sum_k \sum_l W_{k,l}^2 \quad (\text{Weight decay})$$

L1 regularization



$$R(W) = \sum_k \sum_l |W_{k,l}|$$

Elastic net (L1 + L2)

$$R(W) = \sum_k \sum_l \beta W_{k,l}^2 + |W_{k,l}|$$

Regularization: Dropout

In each forward pass, randomly set some neurons to zero
Probability of dropping is a hyperparameter; 0.5 is common



Regularization: Dropout

```
p = 0.5 # probability of keeping a unit active. higher = less dropout
```

```
def train_step(X):
```

```
    """ X contains the data """
```

```
    # forward pass for example 3-layer neural network
```

```
    H1 = np.maximum(0, np.dot(W1, X) + b1)
```

```
    U1 = np.random.rand(*H1.shape) < p # first dropout mask
```

```
    H1 *= U1 # drop!
```

```
    H2 = np.maximum(0, np.dot(W2, H1) + b2)
```

```
    U2 = np.random.rand(*H2.shape) < p # second dropout mask
```


```
    H2 *= U2 # drop!
```

```
    out = np.dot(W3, H2) + b3
```

```
    # backward pass: compute gradients... (not shown)
```


```
    # perform parameter update... (not shown)
```

Example forward pass with a 3-layer network using dropout



Regularization: Dropout

How can this possibly be a good idea?




Forces the network to have a redundant representation;
Prevents co-adaptation of features



Regularization: Dropout

How can this possibly be a good idea?



Another interpretation:

Dropout is training a large **ensemble** of models (that share parameters).

Each binary mask is one model

An FC layer with 4096 units has
 $2^{4096} \sim 10^{1233}$ possible masks!

Only $\sim 10^{82}$ atoms in the universe...

Dropout: Test time

Dropout makes our output random!

$$\text{Output (label)} \quad y = f_W(\text{Input (image)} \quad x, \text{Random mask} \quad z)$$

Want to “average out” the randomness at test-time

$$y = f(x) = E_z[f(x, z)] = \int p(z) f(x, z) dz$$


But this integral seems hard ...

Dropout: Test time

Want to approximate
the integral

$$y = f(x) = E_z[f(x, z)] = \int p(z)f(x, z)dz$$

Consider a single neuron.




Dropout: Test time

Want to approximate
the integral

$$y = f(x) = E_z[f(x, z)] = \int p(z)f(x, z)dz$$

Consider a single neuron.

At test time we have: $E[a] = w_1x + w_2y$




Dropout: Test time

Want to approximate
the integral

$$y = f(x) = E_z[f(x, z)] = \int p(z)f(x, z)dz$$

Consider a single neuron.



At test time we have: $E[a] = w_1x + w_2y$


During training we have:
$$\begin{aligned} E[a] &= \frac{1}{4}(w_1x + w_2y) + \frac{1}{4}(w_1x + 0y) \\ &\quad + \frac{1}{4}(0x + 0y) + \frac{1}{4}(0x + w_2y) \\ &= \frac{1}{2}(w_1x + w_2y) \end{aligned}$$

Dropout: Test time

Want to approximate the integral

$$y = f(x) = E_z[f(x, z)] = \int p(z)f(x, z)dz$$

Consider a single neuron.



At test time we have: $E[a] = w_1x + w_2y$

During training we have:
$$\begin{aligned} E[a] &= \frac{1}{4}(w_1x + w_2y) + \frac{1}{4}(w_1x + 0y) \\ &\quad + \frac{1}{4}(0x + 0y) + \frac{1}{4}(0x + w_2y) \\ &= \frac{1}{2}(w_1x + w_2y) \end{aligned}$$

At test time, **multiply**
by dropout probability

Dropout: Test time

```
def predict(X):  
    # ensembled forward pass  
    H1 = np.maximum(0, np.dot(W1, X) + b1) * p # NOTE: scale the activations  
    H2 = np.maximum(0, np.dot(W2, H1) + b2) * p # NOTE: scale the activations  
    out = np.dot(W3, H2) + b3
```

At test time all neurons are active always

=> We must scale the activations so that for each neuron:

output at test time = expected output at training time

Dropout Summary

```
""" Vanilla Dropout: Not recommended implementation (see notes below) """
```

```
p = 0.5 # probability of keeping a unit active. higher = less dropout
```

```
def train_step(X):
```

```
    """ X contains the data """
```

```
    # forward pass for example 3-layer neural network
```

```
    H1 = np.maximum(0, np.dot(W1, X) + b1)
```

```
    U1 = np.random.rand(*H1.shape) < p # first dropout mask
```

```
    H1 *= U1 # drop!
```

```
    H2 = np.maximum(0, np.dot(W2, H1) + b2)
```

```
    U2 = np.random.rand(*H2.shape) < p # second dropout mask
```

```
    H2 *= U2 # drop!
```

```
    out = np.dot(W3, H2) + b3
```

```
    # backward pass: compute gradients... (not shown)
```

```
    # perform parameter update... (not shown)
```

```
def predict(X):
```

```
    # ensembled forward pass
```

```
    H1 = np.maximum(0, np.dot(W1, X) + b1) * p # NOTE: scale the activations
```

```
    H2 = np.maximum(0, np.dot(W2, H1) + b2) * p # NOTE: scale the activations
```

```
    out = np.dot(W3, H2) + b3
```

drop in train time

scale at test time

More common: “Inverted dropout”

```
p = 0.5 # probability of keeping a unit active. higher = less dropout

def train_step(X):
    # forward pass for example 3-layer neural network
    H1 = np.maximum(0, np.dot(W1, X) + b1)
    U1 = (np.random.rand(*H1.shape) < p) / p # first dropout mask. Notice /p!
    H1 *= U1 # drop!
    H2 = np.maximum(0, np.dot(W2, H1) + b2)
    U2 = (np.random.rand(*H2.shape) < p) / p # second dropout mask. Notice /p!
    H2 *= U2 # drop!
    out = np.dot(W3, H2) + b3

    # backward pass: compute gradients... (not shown)
    # perform parameter update... (not shown)

def predict(X):
    # ensembled forward pass
    H1 = np.maximum(0, np.dot(W1, X) + b1) # no scaling necessary
    H2 = np.maximum(0, np.dot(W2, H1) + b2)
    out = np.dot(W3, H2) + b3
```

test time is unchanged!

Regularization: A common pattern

Training: Add some kind of randomness

$$y = f_W(x, z)$$

Testing: Average out randomness (sometimes approximate)

$$y = f(x) = E_z[f(x, z)] = \int p(z)f(x, z)dz$$

Regularization: A common pattern

Training: Add some kind of randomness

$$y = f_W(x, z)$$

Testing: Average out randomness (sometimes approximate)


$$y = f(x) = E_z[f(x, z)] = \int p(z) f(x, z) dz$$

Example: Batch Normalization


Training:
Normalize using stats from random minibatches

Testing: Use fixed stats to normalize

Regularization: Data Augmentation



Regularization: Data Augmentation



Data Augmentation

Horizontal Flips




Data Augmentation

Random crops and scales

Training: sample random crops / scales

ResNet:

1. Pick random L in range $[256, 480]$
2. Resize training image, short side = L
3. Sample random 224×224 patch



Data Augmentation

Random crops and scales

Training: sample random crops / scales


ResNet:

1. Pick random L in range [256, 480]
2. Resize training image, short side = L
3. Sample random 224 x 224 patch

Testing: average a fixed set of crops

ResNet:

1. Resize image at 5 scales: {224, 256, 384, 480, 640}
2. For each size, use 10 224 x 224 crops: 4 corners + center, + flips



Data Augmentation

Color Jitter

Simple: Randomize
contrast and brightness



Data Augmentation

Color Jitter

Simple: Randomize
contrast and brightness



More Complex:

1. Apply PCA to all [R, G, B] pixels in training set
2. Sample a “color offset” along principal component directions
3. Add offset to all pixels of a training image

(As seen in [Krizhevsky et al. 2012], ResNet_{ed}, etc)



















Data Augmentation

Get creative for your problem!

Examples of data augmentations:

- translation
- rotation
- stretching
- shearing,
- lens distortions, ... (go crazy)

Automatic Data Augmentation

	Original	Sub-policy 1	Sub-policy 2	Sub-policy 3	Sub-policy 4	Sub-policy 5
Batch 1						
Batch 2						
Batch 3						
		ShearX, 0.9, 7 Invert, 0.2, 3	ShearY, 0.7, 6 Solarize, 0.4, 8	ShearX, 0.9, 4 AutoContrast, 0.8, 3	Invert, 0.9, 3 Equalize, 0.6, 3	ShearY, 0.8, 5 AutoContrast, 0.7, 3

Regularization: A common pattern

Training: Add random noise

Testing: Marginalize over the noise

Examples:

Dropout

Batch Normalization

Data Augmentation

Regularization: DropConnect

Training: Drop connections between neurons (set weights to 0)

Testing: Use all the connections



Examples:

Dropout

Batch Normalization

Data Augmentation

DropConnect



Regularization: Fractional Pooling

Training: Use randomized pooling regions

Testing: Average predictions from several regions

Examples:




Dropout

Batch Normalization

Data Augmentation

DropConnect

Fractional Max Pooling



Regularization: Stochastic Depth

Training: Skip some layers in the network

Testing: Use all the layer

Examples:

Dropout


Batch Normalization

Data Augmentation

DropConnect

Fractional Max Pooling

Stochastic Depth



Regularization: Cutout

Training: Set random image regions to zero

Testing: Use full image

Examples:

Dropout

Batch Normalization


Data Augmentation

DropConnect

Fractional Max Pooling

Stochastic Depth

Cutout / Random Crop



Works very well for small datasets like CIFAR,
less common for large datasets like ImageNet¹⁹

Regularization: Mixup

Training: Train on random blends of images

Testing: Use original images

Examples:

Dropout

Batch Normalization

Data Augmentation

DropConnect

Fractional Max Pooling


Stochastic Depth

Cutout / Random Crop

Mixup



Randomly blend the pixels of pairs of training images, e.g. 40% cat, 60% dog



CNN

Target label:
cat: 0.4
dog: 0.6

Regularization - In practice

Training: Add random noise

Testing: Marginalize over the noise

Examples:

Dropout

Batch Normalization

Data Augmentation

DropConnect

Fractional Max Pooling

Stochastic Depth

Cutout / Random Crop

Mixup

- Consider dropout for large fully-connected layers
- Batch normalization and data augmentation almost always a good idea
- Try cutout and mixup especially for small classification datasets

Choosing Hyperparameters

(without tons of GPUs)

Choosing Hyperparameters

Step 1: Check initial loss

Turn off weight decay, sanity check loss at initialization
e.g. $\log(C)$ for softmax with C classes

Choosing Hyperparameters

Step 1: Check initial loss

Step 2: Overfit a small sample

Try to train to 100% training accuracy on a small sample of training data (~5-10 minibatches); fiddle with architecture, learning rate, weight initialization

Loss not going down? LR too low, bad initialization

Loss explodes to Inf or NaN? LR too high, bad initialization

Choosing Hyperparameters

Step 1: Check initial loss

Step 2: Overfit a small sample

Step 3: Find LR that makes loss go down

Use the architecture from the previous step, use all training data, turn on small weight decay, find a learning rate that makes the loss drop significantly within ~ 100 iterations

Good learning rates to try: $1e-1$, $1e-2$, $1e-3$, $1e-4$

Choosing Hyperparameters

Step 1: Check initial loss

Step 2: Overfit a small sample

Step 3: Find LR that makes loss go down

Step 4: Coarse grid, train for ~1-5 epochs

Choose a few values of learning rate and weight decay around what worked from Step 3, train a few models for ~1-5 epochs.

Good weight decay to try: $1e-4$, $1e-5$, 0

Choosing Hyperparameters

Step 1: Check initial loss

Step 2: Overfit a small sample

Step 3: Find LR that makes loss go down

Step 4: Coarse grid, train for ~1-5 epochs

Step 5: Refine grid, train longer

Pick best models from Step 4, train them for longer (~10-20 epochs) without learning rate decay

Choosing Hyperparameters

Step 1: Check initial loss


Step 2: Overfit a small sample


Step 3: Find LR that makes loss go down


Step 4: Coarse grid, train for ~1-5 epochs

Step 5: Refine grid, train longer

Step 6: Look at loss and accuracy curves









Look at learning curves!

Training Loss



Train / Val Accuracy




Losses may be noisy, use a scatter plot and also plot moving average to see trends better


Cross-validation

We develop "command centers" to visualize all our models training with different hyperparameters

check out [weights and biases](#)



You can plot all your loss curves for different hyperparameters on a single plot



Don't look at accuracy or loss curves for too long!



Choosing Hyperparameters

Step 1: Check initial loss

Step 2: Overfit a small sample

Step 3: Find LR that makes loss go down

Step 4: Coarse grid, train for ~1-5 epochs


Step 5: Refine grid, train longer

Step 6: Look at loss and accuracy curves

Step 7: GOTO step 5

Random Search vs. Grid Search

*Random Search for
Hyper-Parameter Optimization
Bergstra and Bengio, 2012*



Summary

- Improve your training error:
 - Optimizers
 - Learning rate schedules
- Improve your test error:
 - Regularization
 - Choosing Hyperparameters

Summary

TLDRs

We looked in detail at:

- Activation Functions (use ReLU)
- Data Preprocessing (images: subtract mean)
- Weight Initialization (use Xavier/He init)
- Batch Normalization (use this!)
- Transfer learning (use this if you can!)