Main Question	Sub Questions	My questions	My Answers	Notes
H2. Who enforces the table edges? Example: the robot is at 4,2,EAST and the user types MOVE. The next square, 5,2, is off the table, so the move is ignored.				
	Which part knows the table size (0..4)?		Table itself as the table know it limit and so I recommend we should have a method in the table class that will tell us	
	Which part asks whether the new position is valid?		The Robot Commander	
	Which part decides to apply or ignore the move?		The Robot Commander	
	Does PLACE use the same check as MOVE?	May be we can inform the user that the reason why robot cannot move? What do think?	Yes both have have identitcal functionality for the edge i.e. when it is a table edge it both cases robot will not move and should not throw an error either and so it should shared the same code.	
H3. How is "not placed yet" represented? Example: the input is MOVE, then REPORT, then PLACE 0,0, NORTH.	Does a Robot object exist before PLACE?	Curious what is the reason for having Robot before PLACE command? I mean why woud we need to create it before hand? Want understand your reasoning behind your question?	We will only create a Robot when we want to start the placement of it right.	
	If so, what are its X, Y and F? (Not 0,0,NORTH, because that is a real position.)		If you agree with what I said that for no need for Robot to exists before place then this is not applicable.	
	Who checks "placed?" before MOVE, LEFT, RIGHT and REPORT?		The RobotCommander	
	After an invalid first PLACE (for example 9,9,NORTH), is the robot still unplaced?		**Part 1** so if the Robot is originally Placed at 4,2,NORTH and then another Place command is issue say PLACE (for example 9,9,NORTH) then the Robot will remain at Placed at 4,2, NORTH i.e. we will not move the Robot and will show message to the user with reason for not moving. **Part 2** If very first request to Place the Robot is PLACE (for example 9,9,NORTH) the robot will still remain unplaced and and we inform the user the reasoning. I am not suggesting to have a default in this case as the original requirement document does mention about default placement of the Robot in this case.	
H4. What does the parser do with bad input? Examples: HELLO, PLACE 1,2, PLACE A,B,NORTH, PLACE 1,2,UP, move, a blank line	What does the parser return for a bad line: nothing, an "invalid" result, or an error?		the bad line should be ignored and inform the user about the reason why it is ignored	
	Who decides what happens next: the parser or the Runner?		The runner will call the parser to valide the command and so command will send success or failure response to the runner and so it is the runner who decided what happens next	

	Does processing continue with the next line?	what do u mean by next line?	If you asking say original command was PLACE 1,0,East and the second line was move and then PLACE again but the bad one PLACE 1,2 and then another PLACE 3,2, North then what should happen when runner encounter the bad line? My answer is we should ignore the bad line and process the next Plane i.e PLACE 3,2,North.	One thing occured in my mind while writting this it contractdict with what I said above "should be ignored and inform the user about the reason why it is ignored" so just to be clear if the command is enter via command line then we show the message to the user so that user can enter the correct command. If the commands are provided in the file we can ingore the bad line and process the next command so that Robot execution in not interrpute. I am thinking we can still log the bad line just in case someone looking at the logs will know each steps that were executed along with the outcome. What do u think?
	Is anything printed? (J3/J6)		Report and warning both Printed on the console.	I suggest we also log the report and warning in file as well because want of user run the console app using the command in the file and want to check the status later in the day?
	Is move (lower case) valid? (J5)		Yes we should add support for any case lower or upper as we don't have control over what case user will use	
	Does the parser check table bounds, or only the format? PLACE 9,9, NORTH is well-formed but not allowed.		Parser only validate the format of the command. Table bounds are associated with the table as I answered in the very first question table should know it has reached the edge	
H5. How do "Command" and "Robot Commands" (RobotCommander) relate? Example: the line LEFT arrives.	Is a Command just data ("this is LEFT"), or does it act ("I turn the robot")?		Command only produces commad like PLACE(0,1, East), MOVE, LEFT, RIGHT and REPORT	
	Who holds the rule that LEFT turns NORTH into WEST: the Command, RobotCommander or Robot?		RobotCommander (aka as RobotOperator or RobotEngine) hold the rules and it changes state of the Robot	I see the Robot commander can created confusion for the completey new engineer i.e. they may think what is the difference between Command and RobotCommander and so to make it less confusing I would like to change the name of the RobotCommander to RobotOperator or RobotEngine. Feel free to select the best fit
	Does the Runner pass the Command to RobotCommander, or does the Command run itself?		Runner gets the command back from the CommandParser an then it passes it to the RobotCommander(aka as RobotOperator or RobotEngine)	
	If a new command (for example BACK) were added later, which parts would change?	Why would we need BACK?	I don't see a need for the BACK command because we can go back by changing he direction and click Move. But just to answer your question we will will need to make changes to most of the files i.e. Command Parser, RobotCommander (aka as RobotOperator or RobotEngine) with special rules for BACK, Direction, Robot, Unit tests, integration tests, specs and the documents	