FR

(1) Robot must not fall down in any case

(2) task dimension 5 x 5

(3) If there is potential of Robot falling down then it need to be prevented

(4) ~~Place~~

(5) PLACE X Y F

where PLACE is command which user will ~~type~~ ~~or~~ ~~set~~ could be selectable

X, Y are position of the robot on X axis & Y axis & F is the direction to which Robot should face (N, S, E, W)


(6) First command is the PLACE command

(7) After that other command like Move, LEFT, RIGHT & including PLACE can be given by the user in any order & the movement of the Robot should be execute accordingly.

(8) Move will move the Robot 1 unit forward in the direction where the Robot is facing

(9) Move should not change the facing direction of the Robot.

(10) LEFT & RIGHT will rotate the Robot direction to 90 degrees in the specified direction ~~Left or Right~~ Left or right. i.e. if the Robot originally facing e.g. East (→) then Left command will changing the direction of the Robot and so the Robot will face ↑ N.



Note:- this does not change the position of the robot i.e. the location where Robot is ~~pla~~ place at the time of submitting LEFT OR RIGHT command.

(11) Robot if not placed on the table then any command given will be ignored. Note Place command is not ignored

(12) When user type Report command & supply a ~~Report~~ command in the file system should print the current location & direction of the Robot

(13) If there is bad command in the file or the Command line it shoud no crash the application or stop user from executing next step. System should just ignore the bad command. use log the warning on the console & file file so that user know the reason