BATTERY PACK RANGES					
Application	Product Model	<b>Battery Description</b>	Cell Chemistry & Type	Max Voltage	Min Voltage
EV-2 Wheeler	HENMC4836	NMC48V 36Ah	NMC Cylindrical	54.6	36.4
EV-2 Wheeler	HENMC4840	NMC48V 40Ah	NMC Cylindrical	54.6	36.4
EV-2 Wheeler	HENMC4845	NMC48V 45Ah	NMC Cylindrical	54.6	36.4
EV-2 Wheeler	HENMC6025	NMC60V 25Ah	NMC Cylindrical	71.4	47.6
EV-2 Wheeler	HENMC6035	NMC60V 35Ah	NMC Cylindrical	71.4	47.6
EV-2 Wheeler	HENMC6040	NMC60V 40Ah	NMC Cylindrical	71.4	47.6
EV-2 Wheeler	HENMC7250	NMC72V 50Ah	NMC Cylindrical	84	56
EV-2/3 Wheeler	HENMC72150	NMC72V 150Ah	NMC Cylindrical	84	56
EV-2 Wheeler	HELFP4818	LFP 48V 18Ah	LFP Cylindrical	54	37.5
EV-2 Wheeler	HELFP4823	LFP 48V 23Ah	LFP Cylindrical	54	37.5
EV-2 Wheeler	HELFP4828	LFP 48V 28Ah	LFP Cylindrical	54	37.5
EV-2 Wheeler	HELFP6018	LFP 60V 18Ah	LFP Cylindrical	68.4	47.5
EV-2 Wheeler	HELFP6024	LFP 60V 24Ah	LFP Cylindrical	68.4	47.5
EV-2 Wheeler	HELFP6030	LFP 60V 30Ah	LFP Cylindrical	68.4	47.5
EV-2 Wheeler	HELFP6036	LFP 60V 36Ah	LFP Cylindrical	68.4	47.5
EV-2 Wheeler	HELFP7224	LFP 72V 24Ah	LFP Cylindrical	82.8	57.5
EV-2 Wheeler	HELFP7230	LFP 72V 30Ah	LFP Cylindrical	82.8	57.5
EV-2 Wheeler	HELFP7236	LFP 72V 36Ah	LFP Cylindrical	82.8	57.5