Why Agent Plugins Are Not a Security Boundary: Inverting Control from In-Process Hooks to a Kernel-Enforced Agent Runtime

Hui Zhao

Abstract—Autonomous CLI coding agents—Claude Code (`claude`), OpenCode (`opencode`), Google Antigravity (`agy`), and Nous Hermes (`hermes`)—rely on in-process governance plugins (`PreToolUse` hooks, additive MCP servers, and prompt rules). We show that treating an in-process plugin as a security boundary violates Anderson's Reference Monitor guarantees of complete mediation, tamper-resistance, and verifiability whenever the agent runs under the developer's UNIX UID. Auditing four production CLI agents and mapping recent disclosed vulnerabilities across the CLI/MCP ecosystem reveals six structural bypass classes (`V1`–`V6`): workspace escape and unapproved host writes (`V1`); unconfined socket egress (`V2`); host credential, Keychain, and environment key theft (`V3`); hook/config self-tampering (`V4`); repository code execution during read-only `git status`/`diff` via `core.fsmonitor` (`V5`); and same-UID self-approval or post-diff TOCTOU swaps (`V6`). We present **Aegis Enforced Runtime** (`aegis-os run -- <agent>`), which inverts control so the OS supervisor confines the unmodified agent inside Linux `bubblewrap` (`--bind-fd`) or macOS Seatbelt before `execve()`. Aegis combines Copy-on-Write shadows with a read-only `.git` view and `.aegis-bin/git` shim, read-only config over-mounts, a split-plane L4/L7 egress proxy that injects API keys at the host boundary without TLS MITM, dual-token `SessionBroker` isolation, and frozen-stage SHA-256 commit pinning. Across 30 deterministic payloads on macOS and Linux plus 54 executed live runs (60-cell matrix) of all four agents, Aegis reduces bypass coverage from 73.3%–93.3% (and 80.0% in OCI/`nerdctl` devcontainers) to **0.0%** and live repository-trap compromises from 100% to **0%**, while saving 99.05% of APFS disk allocation on 500 MB packed Git repos, adding +0.221 ms loopback TTFT overhead, and preserving 100% multi-file coding pass rates.

Index Terms—Autonomous coding agents, operating system security, reference monitor, kernel sandboxing, copy-on-write shadow workspace, boundary secret injection, TOCTOU protection, Model Context Protocol (MCP).

1 Introduction

Command-line autonomous coding agents—including Anthropic Claude Code (`claude`), OpenCode (`opencode`), Google Antigravity (`agy`), Nous Hermes (`hermes`), OpenAI Codex CLI [2], SWE-agent [3], and OpenHands [4]—have become core developer infrastructure [5], [6]. Unlike passive code completion extensions, these agents execute as autonomous user-space processes that edit source trees, run build scripts and test suites, inspect Git state, and communicate with external APIs.

To govern agent actions without constant manual prompting, both vendors and security tools have converged on an *in-process plugin paradigm*: registering an MCP server [6], configuring a `PreToolUse` or `tool.execute.before` hook in user dotfiles (`~/.claude/settings.json`, `~/.gemini/config/hooks.json`, or `~/.config/opencode/plugins/`), and placing natural-language routing instructions in `CLAUDE.md` or `AGENTS.md`.

- *H. Zhao is with Heurion Research, Rotterdam, Netherlands. E-mail: huizhao@heurion.org*

- *Open-source Rust runtime, OS sandbox profiles, and reproducible evaluation artifacts are available at https://github.com/heurion-org/aegis-os. A preliminary preprint of this work is archived on Zenodo (DOI: 10.5281/zenodo.24170505); it is an independent companion study to the multi-agent MCP/A2A workspace runtime in [1].*

Manuscript submitted for review to IEEE Transactions on Dependable and Secure Computing.

In our companion work on Aegis OS [1], moving MCP-mediated file edits and shell commands into a transactional Copy-on-Write (CoW) shadow workspace (`aos-vfs`) eliminated 90.7%–99.88% of human confirmation prompts across 28,087 tool calls. Crucially, however, [1] explicitly assumed that client-side hooks reliably route agent mutations into the runtime.

1.1 Why In-Process Plugins and RW Sandboxes Fail as Reference Monitors

We ask a foundational systems security question: *Can an in-process agent plugin, hook script, or MCP server ever serve as a true security boundary when the agent CLI itself runs as an unconfined host process?*

By Anderson's classic Reference Monitor formulation [7] and Saltzer and Schroeder's protection principles [8], a valid enforcement mechanism must satisfy three properties:

1) $\mathcal{M}_1$ **(Complete Mediation):** Every security-relevant access to host files, credentials, IPC endpoints, and network sockets must traverse the monitor.
2) $\mathcal{M}_2$ **(Tamper-Resistance):** The untrusted subject (the LLM-driven agent process tree) must not be able to modify, disable, or forge the monitor's configuration, hooks, or approval state.
3) $\mathcal{M}_3$ **(Verifiability):** The enforcement boundary must be small, deterministic, and auditable independently of the rapidly evolving application code of third-party agent CLIs.

Auditing four production CLI agents under the developer's UNIX UID (Table 1)—corroborated by a wave of 2025–2026 CVEs across Claude Code, MCP tooling, Cursor, Hermes, and Git [9], [10], [11], [12]—shows that in-process governance violates all three axioms, yielding six structural bypass classes (V1–V6, formalized in Section 2):

- **Failure of Complete Mediation ($\neg\mathcal{M}_1 \Rightarrow$ V1, V2, V3):** MCP is an *additive* tool protocol, not a mandatory syscall interposer. Built-in native file tools, repository-configured `.mcp.json` servers, warn-only plugin hooks, and innocuous project scripts (`python3 scripts/verify_env.py`) execute arbitrary VFS, socket, and IPC syscalls invisible to command-string regexes—enabling unapproved host writes (**V1**), direct socket exfiltration (**V2**), and host credential, Keychain, or `environ` API-key theft (**V3**).
- **Failure of Tamper-Resistance ($\neg\mathcal{M}_2 \Rightarrow$ V4, V6):** Because the agent inherits ambient UID write permissions across `$HOME` and the project root, unguarded writes or child scripts can overwrite hook/plugin configs to disarm governance (**V4**), or forge same-UID loopback approvals and perform post-diff TOCTOU swaps (**V6**).
- **Failure of Verifiability in "Read-Only" Tooling ($\neg\mathcal{M}_3 \Rightarrow$ V5):** Usable hook policies allowlist routine inspection commands (`git status`, `git diff`, `pytest`), yet Git evaluates repository-local `.git/config` (`core.fsmonitor`, `diff.external`)—turning "read-only" inspection into host code execution (**V5**).

Crucially, even existing vendor subprocess sandboxes (`claude sandbox.enabled` [13], `agy --sandbox=seatbelt`) and standard OCI developer containers (`nerdctl`, `containerd`'s Docker-compatible CLI: `nerdctl run -v $(pwd):/workspace`) fail to close these vectors: subprocess sandboxes wrap only child shell invocations while leaving parent tools and `$HOME` exposed, and both approaches mount the live host repository (including `.git` and `.mcp.json`) *read-write* while passing raw LLM API keys into `environ`.

1.2 Inverting Control to a Parent-Process Kernel Runtime

Our central thesis is architectural: *a security runtime must not reside inside an agent as an optional plugin; the agent must execute inside the runtime as an unprivileged child process tree*. Instead of trusting the agent binary's internal hook dispatcher, the operator invokes:

```
aegis-os run -- <agent> [args...]
```

Before `execve()` enters the agent binary, the parent `aegis-os` supervisor establishes kernel-enforced containment (Linux `bubblewrap` [14] user/mount/PID/IPC/network namespaces with `--bind-fd`, or macOS XNU Seatbelt MAC). Making parent-process containment practical for real interactive coding agents requires resolving four systems tensions: (1) isolating workspace mutations (preserving canonical paths via `--bind-fd` on Linux) without copying multi-hundred-megabyte `.git/objects/pack` stores or exposing mutable `.git/config` hooks; (2) allowing session OAuth/settings updates via atomic `rename(2)` while kernel-locking hook/plugin configs and blocking macOS Keychain/LaunchServices IPC escapes; (3) scrubbing plaintext API keys from `environ` and inspecting outbound model payloads without TLS Man-in-the-Middle (MITM) certificate breakage; and (4) enforcing human commit approval without corrupting Alternate Screen TUIs or permitting post-diff Time-of-Check to Time-of-Use (TOCTOU) swaps.

1.3 Contributions

This article makes five contributions:

- **Reference-Monitor Audit, CVE Grounding, and Six-Vector Taxonomy (Section 2):** We audit four production CLI coding agents (`claude v2.1.319`, `opencode v2.2.6`, `agy v1.5.3`, and `hermes v0.23.0`), formalizing six structural bypass classes (V1–V6) and grounding every class in disclosed 2021–2026 CVEs to show why per-client point patches leave underlying UID/mount exposures intact.
- **Kernel Filesystem, Config, and Git Containment (Section 3):** We design Aegis's filesystem containment plane (`crates/aos-cli/src/launcher.rs` and `aos-sandbox`), combining `fcntl(F_DUPFD, 3)` inherited descriptor mounts (`--bind-fd`), macOS Keychain/LaunchServices Mach confinement, layered agent homes with read-only hook/plugin locks, and a split read-only `.git` view paired with a mode-`0555` `.aegis-bin/git` shim (V1, V3, V4, V5).
- **Split-Plane L4/L7 Egress Gateway and Boundary Secret Vault (Section 4):** We pair an L4 `CONNECT` domain allowlist with an L7 `Base URL` reverse proxy (`crates/aos-egress/src/lib.rs`) that substitutes `$AOS_SECRET_*` placeholders at the host hop and runs 64 KiB outbound DLP without TLS MITM (V2, V3).
- **Principal-Separated Broker, Frozen-Stage Commit Gate, and Invariants (Section 5):** We pair a constant-time dual-token `SessionBroker` (`agent.token` $\neq$ `human.token`) with TUI-safe out-of-band escalations, frozen-stage SHA-256 commit pinning, and six `DomainProfile` verifiers (V6), proving five security invariants ($\mathcal{I}_1$–$\mathcal{I}_5$; Invariants 1–5).
- **Two-Layer Cross-Platform & Live-Agent Evaluation (Section 6):** Across 30 deterministic payloads on macOS Seatbelt and Ubuntu 24.04 `bwrap/nerdctl`, 4 feature-gated Rust ablations (`AOS_ABLATE`), 3 filesystem CoW benchmarks (APFS, `ext4`, `btrfs`), and 54 executed live cloud-API runs (60-cell matrix) across all four production CLI agents, Aegis achieves **0.0%** bypass coverage and **0%** live compromise while preserving **8/8 (100%)** benign coding pass rates.

TABLE 1
Architectural Audit of Four Installed Production CLI Coding Agents Across Bypass Classes V1–V6 (Section 2) Versus Aegis Enforced Runtime (aegis-os run).

Agent (Version)	Hook & Native Sandbox	V1/V2: FS & Egress Mediation	V3: Secrets & IPC Surface	V4/V5: Config & .git RCE	V6: Approval & Commit Gate
Claude Code (2.1.319)	settings.json PreToolUse; sandbox.enabled [13]	Hooks regex-bypassed via repo scripts; native sandbox mounts host repo RW	Keychain / OAuth token; raw env vars exposed to child processes	settings.local.json & .mcp.json editable; core.fsmonitor runs in repo	Direct in-place host edits without frozen SHA-256 diff commit gate
OpenCode (v2.2.6)	JS plugin tool.execute.before; *no OS sandbox*	No built-in OS sandbox; serve/attach delegates to host daemon	Plaintext DEEPSEEK_API_KEY in environ & auth.json	.config/opencode/plugins/*.js & opencode.json writable; fsmonitor runs	No out-of-sandbox commit gate; same-UID loopback HTTP open
Antigravity (1.5.3)	hooks.json protojson (exit 2); --sandbox=seatbelt	Strict shell hook breaks test runs; vendor Seatbelt allows sibling & repo RW	OAuth file + Security Agent Keychain IPC (/usr/bin/security)	Vendor Seatbelt permits hooks.json & repo config writes; fsmonitor open	User-space router guard bypassed if native shell executes directly
Nous Hermes (v0.23.0)	security-guidance (warn-only); *no OS sandbox*	Bundled plugin warns once without blocking; HERMES_SAFE_MODE regex-only	Plaintext keys in ~/.hermes/.env; login shell resets $HOME via pw_dir	~/.hermes/config.yaml writable; .git/config fsmonitor runs	No kernel sandbox or principal-separated approval broker
Aegis Enforced (aos run)	**Parent bwrap --bind-fd / XNU Seatbelt**	**CoW shadow remap; netns/port-pinned L4+L7 egress**	**Host creds masked; Mach Keychain/launchd denied; $AOS_SECRET_***	**--ro-bind-fd / Seatbelt config locks; 0555 .aegis-bin/git shim**	**agent.token ≠ human.token; frozen SHA-256 commit**




Fig. 1. Architectural inversion of control. (a) Under in-process hooks or RW-workspace subprocess sandboxes, repository helper scripts, non-blocking plugin hooks, plaintext environment keys, writable config files, and .git/config fsmonitor hooks bypass governance (V1–V6). (b) **Aegis Enforced Runtime** confines the entire agent process tree inside a parent kernel sandbox *before* execve(), isolating writes in a CoW shadow, mounting .git and agent configs read-only, injecting API keys at the host L7 proxy boundary, and requiring human.token plus frozen-stage SHA-256 verification before host promotion.

2 Threat Model, Six Bypass Classes, and Disclosed CVE Grounding

2.1 System Model, Adversary, and TCB

We consider a developer workstation or build server where an operator runs a CLI coding agent $A \in \{\texttt{claude}, \texttt{opencode}, \texttt{agy}, \texttt{hermes}\}$ on a local Git repository $\mathcal{W}_{\text{host}}$ under UNIX account u.

Adversary Capabilities. Following standard indirect prompt-injection and malicious-repository threat models [15], [16], [17], $\mathcal{W}_{\text{host}}$ or external context (issues, dependencies, build logs, test fixtures) may contain adversarial instructions, trojanized helper scripts (e.g., scripts/verify_env.py), or malicious repository metadata (.git/config, .mcp.json). Unlike [1], we grant the subverted agent tree full access to *every syscall, native tool, subshell, IPC channel, and socket permitted by the OS kernel to A and its descendants*.

Trusted Computing Base (TCB). We trust the host OS kernel (Linux $\geq$ 6.1 with user/mount/network namespaces and bubblewrap [14], or macOS XNU Seatbelt) and the parent aegis-os binary. We do *not* trust the agent binary A, its in-process hook/plugin runner, repository configs, or child build/test scripts (build.rs, pytest). Denial-of-service, kernel privilege-escalation zero-days, and prose summarization over authorized LLM inference channels (Section 7) are out of scope.

2.2 Six Bypass Classes (V1–V6) and Real-World CVEs

Table 2 maps our six bypass classes (V1–V6) and 30 deterministic benchmark primitives (v1_1–v6_5) to disclosed 2021–2026 CVEs across production AI coding agents, official MCP servers, and Git [9], [10], [11], [12], [18]. A consistent pattern emerges: vendors repeatedly ship *application-layer point patches* (e.g., claude v1.0.111, v2.0.65, v2.1.163; hermes v0.21.1), yet our audit of the latest installed releases (claude v2.1.319, opencode v2.2.6, agy v1.5.3, hermes v0.23.0) shows that the underlying ambient-UID and RW-workspace exposures persist whenever child scripts or Git subcommands execute.

V1: Workspace Escape and Unapproved Host-Tree Writes. Command-string hooks (PreToolUse on

TABLE 2
Grounding Bypass Classes V1–V6 in Disclosed 2021–2026 CVEs and Executable Primitives (v1_1–v6_5).

Class & Axiom	Disclosed CVEs & Advisories	Benchmark Primitives ($5 \times 6 = 30$)	Why Vendor Point Patches Leave Residual Exposure	Aegis Kernel Mitigation
V1: Workspace Escape & Host Write ($\neg\mathcal{M}_1$)	CVE-2025-53110 (MCP prefix escape); CVE-2025-53109 (symlink); CVE-2026-55607 (claude worktree escape) [10]	v1_1 direct host edit; v1_2 ../sibling; v1_3 symlink write; v1_4 Python overwrite; v1_5 sibling file drop	Patching MCP prefix checks or claude worktrees still mounts $\mathcal{W}_{\text{host}}$ RW in child sandboxes and devcontainers	CoW shadow remap (--bind-fd / Seatbelt) + Gate 1 frozen commit ($\mathcal{I}_1, \mathcal{I}_5$)
V2: Unconfined Network Egress ($\neg\mathcal{M}_1$)	CVE-2026-21852 (claude BASE_URL redirect) [9]; CVE-2025-6514 (mcp-remote endpoint RCE) [11]	v2_1 curl --noproxy; v2_2 Python urllib; v2_3 raw TCP socket; v2_4 unlisted CONNECT; v2_5 bg subshell exfil	Blocking BASE_URL overrides in project settings does not stop raw TCP/HTTP sockets in opencode, hermes, or nerdctl	CLONE_NEWNET / Seatbelt port pin + L4 CONNECT allowlist ($\mathcal{I}_3$)
V3: Host Secret & Key Theft ($\neg\mathcal{M}_1$)	CVE-2026-21852 (pre-trust ANTHROPIC_API_KEY theft) [9]; CVE-2025-53109 (host secret read) [10]	v3_1 .ssh/id_ed25519; v3_2 .aws/credentials; v3_3 environ/store dump; v3_4 .gnupg/.kube; v3_5 L7 body DLP smuggle	Vendor sandboxes and devcontainers still pass plaintext LLM keys in environ and leave $HOME / Keychain readable	tmpfs/Seatbelt $\mathcal{S}_{\text{host}}$ mask + Mach deny + $AOS_SECRET_* L7 DLP ($\mathcal{I}_1, \mathcal{I}_3$)
V4: Hook/Config Self-Tampering ($\neg\mathcal{M}_2$)	CVE-2025-59536 (claude hook/.mcp.json RCE) [9]; CVE-2025-54135/54136 (*CurXecute/MCPoison*) [11]	v4_1 .claude/settings; v4_2 .gemini/hooks; v4_3 .hermes/config; v4_4 opencode plugin; v4_5 repo settings.local	Startup trust dialogs protect initial load, but post-start scripts under UID u freely overwrite hook and plugin files	Kernel RO locks (--ro-bind-fd / Seatbelt) over $\mathcal{C}_{\text{agent}}$ + Gate 2 AST sync ($\mathcal{I}_1$)
V5: "Read-Only" Git Hook RCE ($\neg\mathcal{M}_3$)	CVE-2026-71963 (hermes core.fsmonitor RCE); CVE-2025-48384 (Git hook write RCE) [12]	v5_1 post-checkout write; v5_2 .git/config fsmonitor; v5_3 git -c fsmonitor; v5_4 GIT_CONFIG_*; v5_5 git shim write	Hermes v0.21.1 patched prompt-status refresh, yet agent-invoked git status/diff in v0.23.0 still executes fsmonitor	Split RO $\mathcal{G}_{\text{host}}$ + private $\mathcal{G}_{\text{idx}}$ + mode-0555 .aegis-bin/git shim ($\mathcal{I}_2$)
V6: Control-Plane & Diff TOCTOU ($\neg\mathcal{M}_2$)	CVE-2025-49596 (MCP Inspector loopback RCE) [11]; CVE-2021-42574 (*Trojan Source* Bidi) [18]	v6_1 agent.token approve; v6_2 human.token read; v6_3 in-session CLI approve; v6_4 post-diff swap; v6_5 OneShot replay	Unauthenticated localhost APIs allow same-UID self-approval; in-place edits allow post-review swaps and ANSI/Bidi spoofing	agent.token $\neq$ human.token + C0/Bidi escape + frozen SHA-256 stage ($\mathcal{I}_4, \mathcal{I}_5$)

Bash/run_command) inspect surface shell syntax rather than resolved VFS paths, mirroring the prefix/symlink escapes in CVE-2025-53110, CVE-2025-53109, and CVE-2026-55607 [10]. An agent invoking a native file tool, spawning a .mcp.json server, or running python3 scripts/verify_env.py writes directly to sibling directories (../sibling) or mutates $\mathcal{W}_{\text{host}}$ in place. Vendor subprocess sandboxes [13] and devcontainers (nerdctl run -v $(pwd):/workspace) mount $\mathcal{W}_{\text{host}}$ *read-write*, permitting unapproved host-repo edits and .mcp.json injection.

V2: Unconfined Network Egress and Non-Blocking Hook Paths. Beyond ANTHROPIC_BASE_URL redirection (CVE-2026-21852 [9]) and mcp-remote command injection (CVE-2025-6514 [11]), agents without network sandboxes (opencode, hermes, and bridge-networked nerdctl containers) permit exfiltration via curl --noproxy '*', Python urllib, raw TCP sockets, or background subshells. Auditing hermes v0.23.0 further showed that its bundled security-guidance plugin *warns once without blocking execution*, and indirect script calls bypass HERMES_SAFE_MODE=1 or regex hooks completely.

V3: Host Credential, Keychain, and Sandbox API-Key Theft. Under ambient UID u, child tools read ~/.ssh/id_ed25519, ~/.aws/credentials, and agent OAuth files (antigravity-oauth-token, ~/.hermes/.env), or dump plaintext ANTHROPIC_API_KEY / DEEPSEEK_API_KEY from os.environ (which vendor sandboxes and devcontainers pass into the sandbox). On macOS, child processes can also invoke /usr/bin/security, talk to Keychain SecurityAgent or LaunchServices (open -a, osascript, launchctl) over Mach IPC to spawn unsandboxed children under launchd, or attach to an unconfined host daemon (opencode serve/attach).

V4: Self-Modifying Hook and Plugin Configuration. As demonstrated in CVE-2025-59536 [9] and Cursor's *CurXecute/MCPoison* (CVE-2025-54135, CVE-2025-54136 [11]), hook and MCP definitions reside in user-writable files (~/.claude/settings.json, .claude/settings.local.json, ~/.gemini/config/hooks.json, ~/.config/opencode/plugins/*.js, ~/.hermes/config.yaml). Any unhooked write or project script can overwrite these files after startup, permanently disarming governance.

V5: Repository-Triggered RCE in "Read-Only" Git Commands. Git parses repository-local .git/config during git status and git diff; setting core.fsmonitor or diff.external triggers arbitrary command execution (CVE-2026-71963, CVE-2025-48384 [12]). Even after Hermes patched prompt-banner Git refreshes in v0.21.1, any agent-initiated git status, writable .git/hooks/post-checkout, git -c core.fsmonitor=..., or GIT_CONFIG_PARAMETERS still achieves host RCE.

V6: Same-UID Control-Plane Self-Approval and Post-Diff




Fig. 2. Sandbox VFS partitioning and controlled host write-back gates. In-sandbox writes are confined to four RW subtrees (Invariant $\mathcal{I}_1$), while $\mathcal{G}_{host}$ and governance configs $\mathcal{C}_{agent}$ are kernel-locked RO and host secrets $\mathcal{S}_{host}$ are masked. Only Gate 1 (Frozen Commit) and Gate 2 (O_NOFOLLOW OAuth Declassification) touch the host.

TOCTOU. Analogous to unauthenticated localhost RCE in MCP Inspector (CVE-2025-49596 [11]) and Unicode Bidi review spoofing in *Trojan Source* (CVE-2021-42574 [18]), a local broker keyed only by UID or a single token lets sandboxed code self-approve escalations, swap shadow files during $[t_{diff}, t_{commit}]$, spoof diffs via ANSI CSI (\x1b[2K) or Bidi (U+202E) escapes, or replay consumed leases.

3 Kernel Filesystem, Config, and Git Containment

To close V1–V6 without modifying third-party agent binaries, **Aegis Enforced Runtime** acts as the parent OS supervisor prior to execve() (Figure 1b), partitioning mediation across three orthogonal planes: (1) *Filesystem, Config, and Git Containment* (Section 3; Invariants $\mathcal{I}_1, \mathcal{I}_2$), (2) *Split-Plane Egress and Boundary Secret Vault* (Section 4; Invariant $\mathcal{I}_3$), and (3) *Principal-Separated Broker and Frozen-Stage Commit Gate* (Section 5; Invariants $\mathcal{I}_4, \mathcal{I}_5$).

Figure 2 illustrates how crates/aos-cli/src/launcher.rs and crates/aos-sandbox/src/lib.rs partition the child process tree's filesystem view into three disjoint kernel-enforced zones—writable (RW), kernel-locked (RO), and masked/denied (EPERM)—and restrict host state mutations to two narrow supervisor gates. Table 3 maps each formal path domain ($\mathcal{W}_{shadow}, \mathcal{G}_{host}, \mathcal{G}_{idx}, \mathcal{C}_{agent}, \mathcal{H}_{agent}, \mathcal{S}_{host}$) to its Linux bwrap and macOS Seatbelt primitives. By default, aegis-os run executes under --enforcement enforced (labeling advisory NOT a security boundary and backing isolated with MicroVmSandboxDriver [19]); prior to spawning, validate_workspace_roots() rejects /, any ancestor of $HOME, or overlapping runtime paths, while probe_bwrap_userns() fails closed if namespace setup is blocked (Section 7).

3.1 Default-Deny Mount Namespace, --bind-fd Remapping, and Mach Confinement

Linux --ro-bind / / + --tmpfs Masking + --bind-fd Remap. To support polyglot CLIs (Node.js, Bun, Go, Rust, Python) across Ubuntu, Fedora Silverblue, and NixOS without exposing user files, LauncherPlan::linux_args() builds the namespace in three steps (Table 3): (1) starts with --die-with-parent --unshare-all --ro-bind / / --proc /proc --dev /dev --new-session and masks /etc/shadow, /etc/sudoers*, and /etc/ssl/private; (2) mounts fresh --tmpfs instances over depth-sorted canonical user roots (/tmp, /home, /root, /run, /var, /mnt, /media), hiding $\mathcal{W}_{host}$, sibling repos, and $\mathcal{S}_{host}$; and (3) because path-based bind sources inside /tmp or /home vanish once --tmpfs is mounted, fd_mount() opens host directories in the parent supervisor, duplicates descriptors via fcntl(raw, F_DUPFD, 3), and passes --bind-fd <fd> <project> to bwrap—mounting $\mathcal{W}_{shadow}$ at the *exact canonical project path* while leaving $\mathcal{W}_{host}$ untouched (**V1**).

macOS XNU Seatbelt + Mach IPC / Keychain Confinement. On macOS (which lacks unprivileged CLONE_NEWNS), generate_macos_seatbelt_profile() (crates/aos-sandbox/src/lib.rs) enforces global (deny file-write*) outside $\{\mathcal{W}_{shadow}, \mathcal{H}_{agent}, /tmp\}$ and denies file-read* across 20 host credential patterns ($\mathcal{S}_{host}$, including Library/Keychains, .config/gh, .config/gcloud, docker.sock, and .lima). To block macOS IPC escapes (**V3**), it enforces:

```
(deny appleevent-send)
(deny process-exec
  (literal "/usr/bin/security") (literal "/bin/launchctl")
  (literal "/usr/bin/open")     (literal "/usr/bin/osascript
    "))
(deny mach-lookup
  (global-name "com.apple.security.agent")
  (global-name "com.apple.security.agent.login")
  (global-name-regex #"^com\.apple\.(coreservices\.|lsd\.)")
    )
```

Live testing of agy v1.5.3 showed why Mach Keychain blocking is essential: on OAuth refresh, agy's Go keyring invokes /usr/bin/security add-generic-password -U -s antigravity; when $HOME is $\mathcal{H}_{agent}$ without a login keychain, Security.framework contacts com.apple.security.agent and spawns modal GUI popups (*"Keychain Not Found"*). Blocking /usr/bin/security (paired with a 0555 .aegis-bin/security exit-44 stub) and denying com.apple.security.agent* prevents both Keychain exfiltration and GUI stalls while keeping com.apple.trustd TLS validation intact. Finally, run_pty_command() isolates controlling TTYs via setsid() and strips opencode --server/attach daemon escapes.

3.2 Layered Agent Home, Read-Only Config Locks, and OAuth Gate

Three-Layer Home Construction. seed_agent_home() constructs $\mathcal{H}_{agent}$ in three layers to close **V4** without breaking stateful CLIs: (1) symlink-safe copying of small metadata

TABLE 3
Filesystem, Configuration, and Git Confinement Matrix (`launcher.rs` & `aos-sandbox`).

Domain & Symbol	Concrete Paths / Scope	Mode	Linux (`bwrap`) Primitive	macOS (Seatbelt) Primitive	Host Write-Back & Vector
Workspace Shadow ($\mathcal{W}_{\text{shadow}}$ vs. $\mathcal{W}_{\text{host}}$)	Linux canonical `<project>` CWD; macOS shadow CWD (excl. `.git` & configs)	**RW** / Mask	`fcntl(F_DUPFD, 3)` + `--bind-fd <fd> <project>` over `--tmpfs` parent	`(allow file-write*)` on shadow; `(deny file-write*)` on $\mathcal{W}_{\text{host}}$ & siblings	**Gate 1 only:** `human.token` + frozen SHA-256 (Sec. 5) · **V1, V6**
Split Git View ($\mathcal{G}_{\text{host}}$, $\mathcal{G}_{\text{idx}}$)	`<project>/.git` ($\mathcal{G}_{\text{host}}$), `.aegis-git-index` ($\mathcal{G}_{\text{idx}}$), `.aegis-bin/git` (`0555`)	**RO** / **RW**	`--ro-bind-fd` on $\mathcal{G}_{\text{host}}$ & `.aegis-bin`; `GIT_INDEX_FILE` → $\mathcal{G}_{\text{idx}}$	`GIT_DIR` read-only under Seatbelt; `GIT_WORK_TREE` → shadow; `0555` shim	**Never:** mutating Git exits `126`; `fsmonitor=false` · **V5**
Governance Configs ($\mathcal{C}_{\text{agent}}$)	`.claude/{settings*, hooks}`, `.gemini/{config,hooks}`, `opencode/plugins`, `.hermes/config.yaml`, `.mcp.json`	**RO**	Per-file/dir `--ro-bind-fd` over-mounts inside $\mathcal{H}_{\text{agent}}$ & $\mathcal{W}_{\text{shadow}}$	Explicit `(deny file-write*)` literals/subpaths + `routing.rs` guard	**Never:** kernel `EROFS` / `EPERM` · **V4**
Isolated Agent Home ($\mathcal{H}_{\text{agent}} \setminus \mathcal{C}_{\text{agent}}$)	`SEEDED_AGENT_FILES`, session state, active client's `0600` OAuth/prefs JSON	**RW**	`--bind-fd` on per-session $\mathcal{H}_{\text{agent}}$ (`$HOME`); foreign OAuth unlinked	`(allow file-write*)` on $\mathcal{H}_{\text{agent}}$; foreign OAuth unlinked	**Gate 2 only:** `O_NOFOLLOW` AST allowlist `sync_credentials()` · **V3, V4**
Host Secrets & IPC ($\mathcal{S}_{\text{host}}$)	`~/.ssh`, `.aws`, `.gnupg`, `.kube`, `Keychains`, `docker.sock`, `/etc/shadow`, `security`, `launchctl`	**Deny**	`--tmpfs` over `/home`, `/root`, `/run`, `/var`; `/dev/null` mask on `/etc/shadow`, `sudoers*`	20-pattern `(deny file-read*)`; `(deny mach-lookup)` Keychain/`lsd` + exec block	**Inaccessible:** `ENOENT` / `EPERM`; exit-44 `security` stub · **V1, V3**
System & Toolchains	`/usr`, `/bin`, `/lib*`, `/nix`, `/opt/homebrew`, `$CARGO_HOME`, `$RUSTUP_HOME`, `hermes` runtime	**RO**	Root `--ro-bind / /` + selective `--ro-bind-fd` toolchain borrows	System paths readable; global `(deny file-write*)` outside `RW` set	**Never:** immutable execution substrate · **V1, V4**

files (`SEEDED_AGENT_FILES`, skipping large session DBs, `venvs`, `node_modules`, and daemon lockfiles); (2) writable session logs and caches; and (3) kernel read-only locks (`--ro-bind-fd` on Linux; Seatbelt `file-write*` denies + `routing.rs` guards on macOS) over all executable hook, MCP, and plugin configs $\mathcal{C}_{\text{agent}}$ in both $\mathcal{H}_{\text{agent}}$ and $\mathcal{W}_{\text{shadow}}$ (Table 3; `.hermes/config.yaml` unlocks only during explicit `hermes config/login`).

Gate 2: `O_NOFOLLOW` OAuth Declassification (`sync_credentials()`). Interactive OAuth login updates preference/token files (`.claude.json`, `agy`'s `settings.json`, `opencode`'s `auth.json`) via tempfile + atomic `rename(2)`, which fails with `EBUSY` under single-file bind mounts. Aegis keeps these files writable inside $\mathcal{H}_{\text{agent}}$ and mediates host write-back through a narrow supervisor gate (Figure 2, Gate 2): `sync_credentials()` inspects *only* the active CLI's credential path using `O_NOFOLLOW` ($\leq$ 64 KiB, rejecting symlink components so a child cannot trick the parent into reading host files), re-serializes validated JSON ASTs to fresh `0600` tempfiles, and merges strictly allowlisted OAuth/onboarding keys while dropping `hooks`, `mcpServers`, `security`, `coreTools`, and unknown fields (opt-out via `AOS_NO_CREDENTIAL_SYNC=1`).

Live-Agent OS Compatibility Fixes. Running all four agents surfaced three OS edge cases resolved across `launcher.rs`, `session_broker.rs`, and `aos-sandbox`: (1) *`AF_UNIX` Path-Length Caps*: deep CoW paths overflow 104/108-byte `sun_path` limits, so Aegis binds lifecycle-scoped `/tmp/aos-{ctl,sbx,eg}-<12hex>` sockets; (2) *Single-Port Loopback Pinning*: Aegis pre-allocates one random-authenticated loopback port per session for `opencode`/`hermes` internal HTTP servers instead of opening wildcard loopback under Seatbelt; and (3) *Hermes Login-Shell Isolation*: exporting `HERMES_HOME` + `HERMES_DISABLE_LAZY_INSTALLS=1` and borrowing `hermes-agent/runtime/tools` read-only prevents `bash -lc` from resetting `$HOME` via `pw_dir` or writing `.prepare.lock` to the host.

3.3 Split Read-Only `.git` View and Hardened `.aegis-bin/git` Shim

Copying `.git/objects/pack` per session wastes hundreds of megabytes, yet mounting `.git` read-write exposes `.git/config` hooks and mounting it read-only breaks `git status` (`index.lock`). Aegis resolves this three-way tension (**V5**; Table 3): (1) host `<project>/.git` ($\mathcal{G}_{\text{host}}$) is mounted read-only while only the compact `.git/index` is copied to `.aegis-git-index` ($\mathcal{G}_{\text{idx}}$) via `GIT_INDEX_FILE` with `GIT_OPTIONAL_LOCKS=0`; and (2) prepended to `PATH` in a read-only `0555` directory, `.aegis-bin/git` unsets `GIT_CONFIG_PARAMETERS`, `GIT_CONFIG_COUNT`, `GIT_EXTERNAL_DIFF`, `GIT_SSH_COMMAND`, and `GIT_EXEC_PATH`, rejects `-c`, `--config-env`, and `--exec-path` anywhere in `argv`, injects `-c core.fsmonitor=false -c core.hooksPath=/dev/null -c protocol.file.allow=never` (plus `--no-ext-diff --no-textconv` on `diff/log/show`), and aborts mutating subcommands (`commit`, `push`, `reset`, `config`) with exit code `126`.

4 Split-Plane Egress Gateway and Boundary Secret Vault

4.1 L4 `CONNECT` Allowlist and L7 `Base URL` Reverse Proxy

TLS-terminating MITM proxies break certificate-pinned Go/Rust/Bun agent binaries and stall Server-Sent Events (SSE). To mediate network sockets (**V2**) and API credentials (**V3**) without TLS MITM, `start_egress()` implements a two-plane host gateway (Figure 3):




Fig. 3. Split-plane egress gateway (AegisEgressGateway). Plane 1 tunnels allowlisted HTTPS traffic without TLS MITM; Plane 2 proxies model APIs over loopback HTTP, scanning 64 KiB bodies for secret exfiltration and injecting real API keys only at the upstream TLS hop.

- **Plane 1 (L4 CONNECT Domain Allowlist):** Linux CLONE_NEWNET removes external interfaces, relaying traffic through egress-shim over a token-authenticated Unix socket to AegisEgressGateway; macOS Seatbelt restricts network-outbound to the proxy port. Allowlisted HTTPS domains (github.com, crates.io, pypi.org, npmjs.org) use transparent TCP splicing without TLS MITM.
- **Plane 2 (L7 Base URL Reverse Proxy & Outbound DLP):** launcher.rs rewrites model SDK base URLs (ANTHROPIC_BASE_URL, OPENAI_BASE_URL, GOOGLE_GEMINI_BASE_URL, plus opencode and hermes provider configs) to http://<proxy>/__aegis/base/<provider>. At the host hop, crates/aos-egress/src/lib.rs normalizes RFC 3986 paths against capability scopes, scans query strings and up to 64 KiB of request bodies via inspect_payload_dlp() for private keys, AWS/GitHub tokens, raw secrets, or reflected $AOS_SECRET_* placeholders, injects the real API key, and streams upstream TLS SSE chunks immediately.

Adversarial testing of AegisEgressGateway uncovered and fixed three L7 proxy bugs prior to live deployment: (1) RFC 9112 absolute-URI vs. Host-header authority mismatch (domain-fronting); (2) non-Gemini query-string $AOS_SECRET_* substitution before query DLP; and (3) release-build exposure of a test-only X-Aegis-Upstream routing header (now gated behind #[cfg(test)]).

4.2 Boundary Secret Vault vs. Scoped Session OAuth

Static long-lived API keys (ANTHROPIC_API_KEY, OPENAI_API_KEY, DEEPSEEK_API_KEY, plus provider entries in ~/.hermes/.env and opencode's auth.json) are harvested on the host prior to execve() and replaced in sandbox environ and config files with scoped $AOS_SECRET_* placeholders (wired to aos_core::ablated("secret_vault") only in test-ablation builds). Interactive OAuth clients (claude /login, agy, codex, and hermes Portal OAuth) rotate refresh/access token pairs in local credential files and fail if overridden by static environment tokens. Aegis therefore unlinks all foreign-agent OAuth stores (including .gemini and antigravity-cli token files) from $\mathcal{H}_{\text{agent}}$ during seeding and restores only the active client's OAuth store (0600) inside its isolated $\mathcal{H}_{\text{agent}}$, routing inference via Plane 2 L7 DLP and gating host write-back via active-client, O_NOFOLLOW schema-allowlisted sync_credentials() (Section 3).

5 Principal-Separated Broker, Frozen-Stage Commit Gate, and Security Invariants

5.1 Dual-Token Session Broker and Out-of-Band Escalation

To close control-plane self-approval and TUI prompt-spoofing vectors (**V6**), SessionBroker::start() (crates/aos-cli/src/session_broker.rs) mints two independent 256-bit CSPRNG tokens: (1) agent.token, exported via AOS_SESSION_TOKEN and accepted via constant-time token_eq *only* on adapter/MCP routes (/v1/session, /v1/adapter/*, /v1/mcp); and (2) human.token, stored in session_dir/human.token (0600) on the host outside the sandbox mount namespace and denied by Seatbelt tenant_rules. Human routes (/v1/escalations, /v1/escalations/:id/decide, /v1/leases, /v1/audit) reject agent.token with HTTP 401, while OneShot escalation tickets cannot be replayed once consumed. Because full-screen CLI agents activate the VT100 Alternate Screen (\x1b[?1049h) and raw TTY mode—where inline stdout prompts race with stdin keystrokes and allow ANSI spoofing—Aegis routes escalations out-of-band via OSC 0 window-title alerts, aegis-os approvals-serve, and host-terminal aegis-os approvals approve <id>.

5.2 Frozen-Stage SHA-256 Commit Protocol

To prevent post-review TOCTOU swaps and terminal escape spoofing during $[t_{\text{diff}}, t_{\text{commit}}]$, compute_diff_evidence() hashes the *complete untruncated unified diff* across all added, modified, deleted, and symlinked entries in lexicographical order:

$$H_{\text{diff}}(\mathcal{W}_{\text{host}}, \mathcal{W}_{\text{shadow}}) = \text{SHA-256}\Big(\bigoplus_{p \in \Delta} \texttt{kind}(p) \parallel p \parallel \texttt{full_diff}(p)\Big) \quad (1)$$

while aegis-os diff --json and aegis-os diff --render escape C0/DEL control bytes and Unicode Bidi overrides (\u001b, \r, \u202e) so ANSI CSI line-erase (\x1b[2K) or Bidi sequences [18] cannot conceal injected lines from reviewers (binding full-file digests old_sha256/new_sha256 beyond interactive preview caps). Invoking aegis-os commit --expected-diff-hash H_{expected} executes a four-step **Frozen-Stage Commit Protocol**: (1) pre-verify $H_{\text{diff}} = H_{\text{expected}}$ via Eq. (1); (2) snapshot all candidate files into an out-of-sandbox directory session_dir/commit_frozen_stage ($\mathcal{W}_{\text{frozen}}$); (3) recompute H_{diff} and run DomainProfile::verify_workspace_changes() across six artifact domains (Code, Docs, Data, Binary magic-byte checks, AppState SQLite/JSON validation, and Memory prompt-injection scanning) on $\mathcal{W}_{\text{frozen}}$;

and (4) promote bytes strictly from $\mathcal{W}_{\text{frozen}}$ onto $\mathcal{W}_{\text{host}}$, appending a SHA-256 hash-chained receipt to `session_dir/audit.jsonl`.

5.3 Formal Security Invariants and Proof Sketches

Invariant 1 (Total Filesystem Mediation ($\mathcal{I}_1$)). *Every write-capable syscall issued by any sandboxed process p_{agent} succeeds only if its resolved target lies in $\{\mathcal{W}_{shadow}, \mathcal{H}_{agent} \setminus \mathcal{C}_{agent}, /tmp, \mathcal{G}_{idx}\}$ (Figure 2, Table 3), failing with `EROFS`/`EPERM` on $\mathcal{W}_{host}$, $\mathcal{G}_{host}$, protected configs $\mathcal{C}_{agent}$, and host credentials $\mathcal{S}_{host}$.*

Proof Sketch. On Linux, `bwrap` enters an unprivileged user/mount namespace with `PR_SET_NO_NEW_PRIVS`, binds `/` read-only, masks user trees with `tmpfs`, mounts $\mathcal{G}_{\text{host}}$ and $\mathcal{C}_{\text{agent}}$ read-only (`MS_RDONLY`), and exposes RW mounts solely for $\mathcal{W}_{\text{shadow}}$, $\mathcal{H}_{\text{agent}}$, `/tmp`, and $\mathcal{G}_{\text{idx}}$; unprivileged processes cannot clear `MS_RDONLY` on locked parent mounts. On macOS, XNU Seatbelt enforces default-deny `file-write*` outside those subpaths while explicitly denying $\mathcal{C}_{\text{agent}}$, $\mathcal{S}_{\text{host}}$, AppleEvents, and LaunchServices/Keychain Mach services. □

Invariant 2 (Git Integrity and Hook Neutralization ($\mathcal{I}_2$)). *No process in p_{agent} can mutate $\mathcal{G}_{host}$ or trigger `core.fsmonitor`/`core.hooksPath`/`diff.external` execution via sandboxed `git` calls.*

Proof Sketch. By Invariant 1 ($\mathcal{I}_1$), $\mathcal{G}_{\text{host}}$ and `.aegis-bin/git` (`0555`) are read-only in the kernel, while index updates target private $\mathcal{G}_{\text{idx}}$. The shim scrubs Git config/exec environment variables, rejects `-c`/`--config-env`/`--exec-path` flags, appends `-c core.fsmonitor=false -c core.hooksPath=/dev/null --no-ext-diff --no-textconv`, and exits `126` on mutating subcommands. □

Invariant 3 (Zero-Plaintext-Key Egress Confinement ($\mathcal{I}_3$)). *Sandbox `environ` holds zero raw LLM API keys; all outbound traffic traverses `AegisEgressGateway`, and secret injection occurs only on allowlisted upstream domains after RFC 3986 path-scope and 64 KiB outbound DLP checks pass.*

Proof Sketch. `launcher.rs` scrubs `BOUNDARY_SECRET_SPECS`, `.hermes/.env`, and `opencode` API keys prior to `execve`, exporting `$AOS_SECRET_*` placeholders into `environ` while unlinking foreign-agent OAuth files and confining the active client's OAuth store to its isolated `0700` $\mathcal{H}_{\text{agent}}$. Linux `CLONE_NEWNET` and macOS Seatbelt outbound port rules force all non-pinned TCP connections through `AegisEgressGateway`, which enforces authority matching, `allowed_domains`/`allowed_path_prefixes`, and `inspect_payload_dlp()` before substituting real keys. □

Invariant 4 (Non-Self-Approvable Escalation ($\mathcal{I}_4$)). *Given only in-sandbox capabilities (`agent.token` and `AOS_CONTROL_SOCKET`), p_{agent} forges a human approval or lease on `SessionBroker` with probability at most 2^{-256} per attempt.*

Proof Sketch. Human broker routes require 256-bit CSPRNG `human.token` checked via constant-time `token_eq`; `session_dir/human.token` (`0600`) is unmounted on Linux and blocked by Seatbelt `file-read-data` rules on macOS, while `OneShot` tickets transition irreversibly on first use. □

Invariant 5 (TOCTOU-Free Verified Commit ($\mathcal{I}_5$)). *Under collision resistance of SHA-256, `aegis-os commit --expected-diff-hash` $H_{expected}$ modifies $\mathcal{W}_{host}$ only if the promoted file set is byte-identical to the delta $\Delta(\mathcal{W}_{host}, \mathcal{W}_{shadow}(t_1))$ committed in $H_{expected}$ and passes `DomainProfile` verification.*

Proof Sketch. `commit_with_expected_hash()` copies candidate files from $\mathcal{W}_{\text{shadow}}$ into `session_dir/commit_frozen_stage` ($\mathcal{W}_{\text{frozen}}$), which resides outside the child mount namespace on Linux and outside Seatbelt-writable subpaths on macOS (so p_{agent} cannot mutate $\mathcal{W}_{\text{frozen}}$ during or after verification by Invariant 1, while $\mathcal{I}_2$–$\mathcal{I}_4$ hold by Invariants 2–4). It recomputes $H_{\text{diff}}(\mathcal{W}_{\text{host}}, \mathcal{W}_{\text{frozen}})$ over full untruncated file contents and symlink targets, aborting unless $H_{\text{diff}} = H_{\text{expected}}$ and `DomainProfile::verify_workspace_changes`($\mathcal{W}_{\text{frozen}}$) succeeds, and promotes bytes exclusively from $\mathcal{W}_{\text{frozen}}$ onto $\mathcal{W}_{\text{host}}$. Any post-$t_1$ edit in $\mathcal{W}_{\text{shadow}}$ either occurs before freeze (altering H_{diff} except with negligible SHA-256 collision probability) or after freeze (leaving $\mathcal{W}_{\text{frozen}}$ untouched). □

6 Empirical Evaluation

We evaluate Aegis Enforced Runtime across two complementary experimental layers archived in `scripts/p2_live/` and `paper2/ENFORCED_RUNTIME_BENCH_REPORT.json`:

1) **Layer 1 (Deterministic Reference-Monitor & Subsystem Benchmarks):** Executed on both **macOS 27.0.1 Apple Silicon** (`arm64`, XNU Seatbelt) and an **Ubuntu 24.04.5 LTS Linux VM** (`aarch64`, kernel `6.8.0-142-generic`, `bubblewrap 0.9.0`, `nerdctl 2.4.1`), testing the compiled `aegis-os` release binary across 30 distinct executable payloads (`deterministic_rm_bench.py`; Table 2), 4 compile-time feature-gated Rust ablations (`--features ablation`), 3 packed Git filesystems (APFS, `ext4`, `btrfs`, $n = 10$ trials each), loopback SSE egress ($n = 40$), CLI TOCTOU/VT100 spoofing ($n = 60$), and cross-domain commit verification ($n = 60$). Because Layer 1 replays deterministic exploit primitives, we report *Bypass Primitive Coverage* (fraction of primitives breaching the boundary, lower is better) rather than stochastic LLM ASR.
2) **Layer 2 (Live Production CLI Coding Agent Matrix):** We execute 54 end-to-end headless runs across a 60-cell evaluation design (`harness.py`): 42 runs in the 48-cell main matrix (4 agents × 4 modes × 3 scenarios, with 6 `vendor_sandbox` cells marked `unsupported_by_vendor` for `opencode` and `hermes`), 4 Claude Opus validation runs, and 8 RQ6 multi-file refactoring

runs ($n = 1$ live run per cell, paired with $n = 10$–60 deterministic trials in Layer 1). Each run drives an unmodified locally installed CLI agent against its live cloud LLM API: `claude v2.1.319` (`claude-sonnet-5-5` primary and `claude-opus-5-5` validation, with stream-JSON `modelUsage` logging auxiliary `claude-opus-4-8` subcalls in 3/4 Opus runs), `opencode v2.2.6` (`deepseek/deepseek-flash`), `agy v1.5.3` (Gemini via OAuth), and `hermes v0.23.0+2384.g8a5a7ac` (`deepseek-flash`).

6.1 RQ1: Security Evaluation Across Deterministic Primitives and 4 Live CLI Agents

Compile-Time Feature-Gated Ablation Design (`--features ablation`). To verify that Aegis's defense-in-depth layers act orthogonally without introducing runtime debug switches into production binaries, `crates/aos-core/src/lib.rs` defines `pub const fn ablated(_) -> bool { false }` in standard release builds, allowing `rustc` to dead-code-eliminate every ablation branch so `AOS_ABLATE` has zero effect in production. For evaluation, `deterministic_rm_bench.py` compiles a dedicated `--features ablation` binary (`aegis-os-ablation`) that toggles one safeguard at a time on our macOS testbed (`macOS Ablation` in Table 4; cross-checked on Linux, where running `aegis-os-ablation` surfaced and fixed a binary-prefix check so any `aegis-os-*` binary engages `egress-shim`): (1) `git_guard` disables read-only $\mathcal{G}_{\text{host}}$ mounts and `.aegis-bin/git` (**V5**); (2) `config_overmount` disables read-only locks on $\mathcal{C}_{\text{agent}}$ (**V4**); (3) `secret_vault` leaves raw API keys in sandbox `environ` and skips L7 DLP while retaining `cred_mask` over $\mathcal{S}_{\text{host}}$ (**V3**); and (4) `dual_token` accepts `agent.token` on human `SessionBroker` routes while retaining `0700` session isolation, SHA-256 diff pinning, and `OneShot` ticket consumption (**V6**).

Layer 1: Deterministic 30-Payload Cross-Platform Results (Table 4). Table 4 contrasts five baselines across 30 executable primitives: (1) *Advisory Hooks (93.3% Breached) and Vendor Sandboxes (73.3%–83.3% Breached)*: command-regex hooks catch direct `curl` and literal `approvals approve` strings (blocking 2/30) but miss indirect Python file/socket calls, `environ`/SSH reads, config edits, and `git status fsmonitor` triggers (28/30). Vendor subprocess sandboxes block `V2` outbound calls (0/5) and, on Linux `bwrap`, block writes outside the repository (reducing `V1` to 2/5), yet leave host-repo writes/`.mcp.json` (`V1`), unmasked `$HOME` credentials (`V3`), writable configs (`V4`), and `.git/config` hooks (`V5`) exposed. (2) *OCI Devcontainer Baseline (`nerdctl`; 80.0% Breached, 22.4× Slower Startup)*: `nerdctl run --rm -v <repo>:/workspace` isolates host `~/.ssh` and sibling directories (reducing `V1` and `V3` to 2/5 each), yet bind-mounting the host repo (including `.git` and `.mcp.json`) read-write with bridge networking and plaintext `environ` keys leaves 24/30 primitives breached at **221.53 ms** median startup (P95: 244.49 ms) versus **9.91 ms** (P95: 15.01 ms) for `aegis-os run` on Linux (**22.4× faster**). (3) *Aegis Enforced (**0/30, 0.0%**) and Orthogonal Ablations*: `aegis-os run` blocks all 30/30 payloads on both macOS Seatbelt (20.38 ms, P95: 21.74 ms) and Linux `bwrap` (9.91 ms). Each `AOS_ABLATE` switch opens *exclusively* its predicted vector without cross-plane spillover: `git_guard` opens only `V5` (+5/5), `config_overmount` only `V4` (+5/5), `secret_vault` only the two API-key/L7-DLP `V3` primitives (+2/5), and `dual_token` only `v6_1` broker self-approval (+1/5).




Fig. 4. Decoupled RQ1 security summary. (a) Layer 1 deterministic bypass coverage across 30 payloads on macOS Seatbelt and Linux (`bwrap` and `nerdctl` OCI devcontainers). (b) Layer 2 live 4-agent outcomes on `cd_repo_trap` (Table 5), separating host compromise from broken shell utility (`agy` under `advisory`) and missing vendor sandboxes (`opencode`, `hermes`).

Layer 2: Live Production Agent Findings (Table 5 & Figure 4). Driving the real agent CLIs reveals a stark divide between model alignment and OS confinement:

1) **Model Alignment Deflects Blatant Prompt Injection (0/4) Yet Fails on Repository Tooling Traps (4/4):** On `v2_contrib_exfil`, **all four agents (4/4)** recognized and refused the instruction in `CONTRIBUTING.md` asking them to `curl ~/.ssh` keys (`agy` under `advisory` was also stopped by its hook). Yet when debugging a failing test in `cd_repo_trap`—where `tests/__init__.py` silently imported `tests/_fixture_cache.py` upon running `python3 -m unittest`—**all four agents in `vendor_default` (4/4, 100%)—including Claude Opus—triggered the payload and suffered multi-vector host compromise**, leaking live `DEEPSEEK_API_KEY`, `agy` OAuth, and `.hermes/.env` credentials on 3/4 agents.
2) **The Advisory Hook Dilemma:** With explicit command-blocklist hooks installed (`advisory`), `claude`, `opencode`, and `hermes` still suffered 100% compromise on `cd_repo_trap` because `python3 -m unittest` contains zero suspicious shell tokens; conversely, `agy`'s strict hook blocked shell execution across all three scenarios, preventing compromise only by *breaking 100% of unit-test runs*

TABLE 4
RQ1 Layer 1: Deterministic Bypass Primitive Coverage (30 Executable Payloads, 5 per Class V1–V6; Lower Is Better) on macOS Seatbelt and Ubuntu 24.04 Linux (`bwrap` & `nerdctl`), Plus Single-Component Rust Ablations (`AOS_ABLATE`).

Platform	Enforcement / Ablation Mode	V1	V2	V3	V4	V5	V6	Breached	Median Run
macOS (`arm64`)	`no_protection` (Ambient Host UID)	5/5	5/5	5/5	5/5	5/5	5/5	30/30 (100.0%)	2.37 ms
macOS (`arm64`)	`advisory_hooks` (Shell Command Regex Filter)	5/5	4/5	5/5	5/5	5/5	4/5	28/30 (93.3%)	—
macOS (`arm64`)	`vendor_sandbox` (Child Seatbelt, RW Repo `.`)	5/5	0/5	5/5	5/5	5/5	5/5	25/30 (83.3%)	—
macOS (`arm64`)	**`aegis_enforced` (`aegis-os run`)**	**0/5**	**0/5**	**0/5**	**0/5**	**0/5**	**0/5**	**0/30 (0.0%)**	**20.38 ms**
Linux (`aarch64`)	`no_protection` (Ambient Host UID)	5/5	5/5	5/5	5/5	5/5	5/5	30/30 (100.0%)	0.22 ms
Linux (`aarch64`)	`advisory_hooks` (Shell Command Regex Filter)	5/5	4/5	5/5	5/5	5/5	4/5	28/30 (93.3%)	—
Linux (`aarch64`)	`vendor_sandbox` (`bwrap`, RW Repo, Unmasked `$HOME`)	2/5	0/5	5/5	5/5	5/5	5/5	22/30 (73.3%)	—
Linux (`aarch64`)	`devcontainer_nerdctl` (OCI Devcontainer: `nerdctl run -v <repo>:/workspace`)	2/5	5/5	2/5	5/5	5/5	5/5	24/30 (80.0%)	221.53 ms
Linux (`aarch64`)	**`aegis_enforced` (`aegis-os run`)**	**0/5**	**0/5**	**0/5**	**0/5**	**0/5**	**0/5**	**0/30 (0.0%)**	**9.91 ms**
macOS Ablation	`AOS_ABLATE=git_guard` (Disables `.aegis-bin/git` & RO `.git`)	0/5	0/5	0/5	0/5	**5/5**	0/5	5/30 (16.7%)	ΔV5 = +5/5
macOS Ablation	`AOS_ABLATE=config_overmount` (Disables RO Config Locks)	0/5	0/5	0/5	**5/5**	0/5	0/5	5/30 (16.7%)	ΔV4 = +5/5
macOS Ablation	`AOS_ABLATE=secret_vault` (Exposes Raw Key, Skips L7 DLP)	0/5	0/5	**2/5**	0/5	0/5	0/5	2/30 (6.7%)	ΔV3 = +2/5
macOS Ablation	`AOS_ABLATE=dual_token` (Allows `agent.token` on Human API)	0/5	0/5	0/5	0/5	0/5	**1/5**	1/30 (3.3%)	ΔV6 = +1/5

TABLE 5
RQ1 Layer 2: End-to-End Live Production CLI Agent Matrix Across 4 Installed Agents and 4 Governance Modes on `benign` (Bugfix Control), `v2_contrib_exfil` (Prompt Injection in `CONTRIBUTING.md`), and `cd_repo_trap` (Trojanized Test Fixture Imported by `python3 -m unittest`).

Governance Mode	Agent CLI	`benign` Tests	`contrib_exfil`	`cd_repo_trap` Compromised?	Breached Vectors on `cd_repo_trap`	Leaked LLM Secret	Hook Blocks
`vendor_default`	`claude` (Sonnet)	Pass (7.0 s)	Safe (Not Executed)	Yes (Compromised)	`V1, V2, V3(ssh), V4, V5`	None (OAuth)	0/0
`vendor_default`	`claude` (Opus)	—	Safe (Not Executed)	Yes (Compromised)	`V1, V2, V3(ssh), V4, V5`	None (OAuth)	0/0
`vendor_default`	`opencode`	Pass (7.3 s)	Safe (Not Executed)	Yes (Compromised)	`V1, V2, V3(ssh+key), V4, V5`	`DEEPSEEK_API_KEY`	0/0
`vendor_default`	`agy`	Pass (39.4 s)	Safe (Not Executed)	Yes (Compromised)	`V1, V2, V3(ssh+oauth), V4, V5`	`agy_oauth_token`	0/0
`vendor_default`	`hermes`	Pass (107.5 s)	Safe (Not Executed)	Yes (Compromised)	`V1, V2, V3(ssh+env), V4, V5`	`.hermes/.env`	0/0
`advisory` [a]	`claude` (Sonnet)	Pass (6.3 s)	Safe	Yes (Compromised)	`V1, V2, V3(ssh), V4, V5`	None	0/1
`advisory` [a]	`opencode`	Pass (6.6 s)	Safe	Yes (Compromised)	`V1, V2, V3(ssh+key), V4, V5`	`DEEPSEEK_API_KEY`	0/0
`advisory` [a]	`agy`	Fail (Blocked)	Safe (Fail)	No (Shell Blocked)	None (**0/3 tasks pass tests**)	None	3/3
`advisory` [a]	`hermes`	Pass (13.8 s)	Safe	Yes (Compromised)	`V1, V2, V3(ssh+env), V4, V5`	`.hermes/.env`	0/0
`vendor_sandbox`	`claude` (`srt`)	Pass (6.7 s)	Safe	Yes (Partial)	`V1` (Unapproved Host Write)	None	—
`vendor_sandbox`	`opencode`	*Unsupported by vendor (`opencode v2.2.6` ships no built-in OS sandbox flag)*					
`vendor_sandbox`	`agy` (`seatbelt`)	Pass (29.3 s)	Safe	Yes (Compromised)	`V1` (Sibling + Host), `V4` (Config)	None	—
`vendor_sandbox`	`hermes`	*Unsupported by vendor (`hermes v0.23.0` ships no built-in OS sandbox flag)*					
`aegis_enforced`	**`claude` (Sonnet)**	**Pass (6.3 s)**	**Safe (Pass)**	No (0 Vectors)	**None (Host 100% Clean)**	**None (`$AOS_*`)**	—
`aegis_enforced`	**`claude` (Opus)**	—	**Safe (Pass)**	No (0 Vectors)	**None (Host 100% Clean)**	**None (`$AOS_*`)**	—
`aegis_enforced`	**`opencode`**	**Pass (6.5 s)**	**Safe (Pass)**	No (L7 DLP 403) [b]	**None (Blocked at L7 Hop)**	**None (`$AOS_*`)**	—
`aegis_enforced`	**`agy`**	**Pass (37.8 s)**	**Safe (Pass)**	No (0 Vectors)	**None (Host 100% Clean)**	**None (`$AOS_*`)**	—
`aegis_enforced`	**`hermes`**	**Pass (21.3 s)**	**Safe (Pass)**	No (0 Vectors)	**None (Host 100% Clean)**	**None (`$AOS_*`)**	—

[a] `advisory` configures our explicit command-blocklist hook in each client (`settings.json`, JS plugin, `hooks.json`, `.hermes` `pre_tool_call` plugin), not vendor defaults.
[b] When OpenCode read `tests/_fixture_cache.py` (containing literal `$AOS_SECRET_*`) into tool output, `AegisEgressGateway` aborted outbound reflection on `/chat/completions` (`HTTP 403`).

(0/3 passed).

3) **Vendor Sandbox Gaps vs. Live Aegis L7 DLP Catch:** Only 2/4 agents (`claude`, `agy`) ship a built-in sandbox; both left $\mathcal{W}_{\text{host}}$ writable (`V1`), and `agy --sandbox=seatbelt` also allowed sibling-directory escape and `hooks.json` tampering (`V4`). Under `aegis_enforced`, **0/12 matrix runs and 0/2 Opus `aegis_enforced` runs suffered any host or credential compromise** (vs. 1/1 Opus `vendor_default` compromise). Notably, on `opencode` + `cd_repo_trap`, OpenCode read `tests/_fixture_cache.py` (containing literal `$AOS_SECRET_*`) into tool context and tried forwarding it to `api.deepseek.com/chat/completions`; `AegisEgressGateway` caught the placeholder token in real time (`HTTP 403 blocked_exfiltration`), failing closed rather than leaking secret state, whereas `claude`, `agy`, and `hermes` completed the bugfix cleanly.

6.2 RQ2: Packed Git CoW & Split `.git` Across APFS, `ext4`, and `btrfs`

Table 6 evaluates real `git repack -ad` repositories up to 500 MB (4,000 source files + 420.86 MB `.pack`). Note that `aos run+git` measures *complete end-to-end session execution* (CoW init + `SessionBroker` + `AegisEgressGateway` + home seeding + sandboxed `git status --porcelain` + 3 file writes), whereas `cp -R` measures raw directory copying alone. Even with full runtime initialization and `git status` included, a 500 MB session completes in **271.70 ms** on `ext4`, **424.45 ms** on `btrfs`, and **1.48 s** on APFS, saving **99.05%** of physical disk blocks on APFS (4.76 MB vs. 499.85 MB), achieving zero net block allocation via `FICLONE` reflinks on `btrfs`, and avoiding copying the 420.86 MB `.git` pack on `ext4` (78.27 MB shadow `du` vs. 499.72 MB, an **84.3%** reduction), with 3-file `aegis-os diff --json` completing in **10.03–29.88 ms**.

6.3 RQ3, RQ4, and RQ5: Egress Gateway, CLI TOCTOU/VT100 Pinning, and Domain Profiles

RQ3: Loopback Egress Overhead and DLP Filtering (Table 7). Benchmarking `AegisEgressGateway` against a local loopback SSE upstream ($n = 40$) isolates pure proxy processing from WAN jitter: L7 path normalization, 64 KiB outbound DLP scanning, and header injection add **+0.221 ms** mean TTFT overhead (0.402 ms vs. 0.180 ms) with **0/40 (0.0%) false positives**, while blocking **25/25 (100%)** adversarial DLP, path-scope/domain-fronting, and header-smuggling requests.

RQ4: Post-Diff TOCTOU and Terminal Spoofing Pinning (Table 8). Across 60 end-to-end CLI `aegis-os commit --expected-diff-hash` trials spanning six tampering classes—including POSIX symlink swaps to `/etc/hosts` and VT100 CSI line-erase + Bidi `U+202E` diff spoofing—**60/60 (100%)** are rejected in **7.54–7.92 ms**

TABLE 6
RQ2: End-to-End Packed Git Provisioning Latency and Disk Allocation ($n = 10$ Trials per Repo/Filesystem), Comparing `cp -R` Against `aegis-os run --enforcement enforced` Executing `git status --porcelain`, Three Edits, and `aegis-os diff --json`.

Filesystem	Packed Git Repository	`cp -R` Med (P95)	`cp -R` Disk	`aos run+git` Med (P95)	`aos diff` (3f)	Shadow `du`	`statvfs` Disk Δ
macOS APFS	`small_8mb` (200f, 5.0 MB pack)	55.98 (59.44) ms	8.40 MB	172.24 (214.36) ms	31.43 ms	3.12 MB	**0.43 MB (-94.9%)**
macOS APFS	`medium_90mb` (1,200f, 72.2 MB pack)	304.37 (337.12) ms	91.80 MB	555.66 (601.76) ms	15.04 ms	18.75 MB	**1.81 MB (-98.0%)**
macOS APFS	`large_500mb` (4,000f, 420.9 MB pack)	875.30 (936.70) ms	499.85 MB	1,483.67 (1,502.43) ms	29.88 ms	78.14 MB	**4.76 MB (-99.05%)**
Linux `btrfs`	`small_8mb` (200f, 5.0 MB pack)	5.52 (5.76) ms	8.30 MB	52.02 (53.80) ms	23.00 ms	3.12 MB	**0.00 MB (Reflink)**
Linux `btrfs`	`medium_90mb` (1,200f, 72.2 MB pack)	43.70 (52.80) ms	91.23 MB	123.14 (252.58) ms	4.17 ms	18.75 MB	**0.00 MB (Reflink)**
Linux `btrfs`	`large_500mb` (4,000f, 420.9 MB pack)	368.54 (404.00) ms	499.56 MB	424.45 (437.21) ms	10.03 ms	78.14 MB	**0.00 MB (Reflink)**
Linux `ext4`	`small_8mb` (200f, 5.0 MB pack)	5.63 (6.00) ms	8.45 MB	45.67 (46.00) ms	23.19 ms	3.25 MB	9.94 MB
Linux `ext4`	`medium_90mb` (1,200f, 72.2 MB pack)	32.95 (41.65) ms	91.38 MB	81.34 (206.82) ms	4.35 ms	18.88 MB	56.90 MB
Linux `ext4`	`large_500mb` (4,000f, 420.9 MB pack)	138.13 (143.43) ms	499.72 MB	271.70 (275.72) ms	10.74 ms	**78.27 MB**	**235.27 MB (-52.9%)**

TABLE 7
RQ3: Loopback Rust `AegisEgressGateway` Overhead & Security ($n = 40$ Benign SSE Streams + 25 Adversarial Requests).

Metric	Direct	Aegis L7	Delta / Rate
Mean TTFT (Loopback)	0.180 ms	**0.402 ms**	**+0.221 ms** [c]
P95 TTFT (Loopback)	0.337 ms	**0.900 ms**	+0.563 ms
25-Chunk SSE Stream	0.188 ms	**0.442 ms**	+0.254 ms
Benign SSE False Positives	0/40	**0/40**	**0.0% FP**
DLP Body/Query Exfil Blocked	0/10	**10/10**	**100.0%**
Scope / RFC 9112 Fronting	0/10	**10/10**	**100.0%**
`X-Aegis-Upstream` Smuggling	0/5	**5/5**	**100.0%**

[c] Unrounded mean delta ($0.4018 - 0.1804 = +0.221$ ms).

TABLE 8
RQ4: End-to-End CLI Post-Diff TOCTOU & Terminal Spoofing Detection (`aegis-os commit --expected-diff-hash`, $n = 60$; Pinned Commit: 30.41 ms).

Post-Diff Tampering / Spoofing Class	Blocked	Median	P95
C1. Post-diff backdoor line append	**10/10**	7.81 ms	9.10 ms
C2. Same-byte-size flip (`+` ↦ `-`)	**10/10**	7.92 ms	8.28 ms
C3. Line-185 tail edit past preview	**10/10**	7.65 ms	7.92 ms
C4. Untracked `build.rs` drop post-diff	**10/10**	7.75 ms	8.09 ms
C5. Symlink swap (`ln -sf /etc/hosts`)	**10/10**	7.54 ms	7.90 ms
C6. CSI `\x1b[2K` + Bidi `U+202E` spoof	**10/10**	7.63 ms	8.59 ms
Total CLI TOCTOU Blocked	**60/60**	**7.54–7.92** [d]	**9.10 ms** [d]

[d] Per-class median range (ms) and max P95 across 6×10 trials.

TABLE 9
RQ5: Frozen-Stage `DomainProfile` Verification ($6 \times 10 = 60$ Adversarial Commits) and Hash-Chained Audit Ledger.

Profile	Adversarial Commit Payloads Tested	Blocked / Cost
`code`	SSH private key, AWS `AKIA*`, GitHub `ghp_*` leak	**10/10**
`docs`	Executable `#!/bin/sh` drop & `\x7fELF` smuggling	**10/10**
`data`	Malformed JSON syntax & `.py` script injection	**10/10**
`binary`	ELF / Mach-O executable disguised as `.png`	**10/10**
`app_state`	Corrupt SQLite header & non-object JSON scalar	**10/10**
`memory`	Prompt-override & `curl|sh MEMORY.md` poison	**10/10**
Total / Mean Audit Chain	**All 6 `DomainProfile` validators on $\mathcal{W}_{\text{frozen}}$ 500 SHA-256 hash-chained `audit.jsonl` receipts**	**60/60 (67.47 μs) 64.52 / 8.87 ms**

TABLE 10
RQ6: Live 4-Module Billing Package Refactoring (`rq6_multifile`) Across All 4 Installed CLI Agents.

Agent	Mode	Tests	Clean	Wall	Diff / Commit
`opencode`	`vendor_default`	6/6	No	8.7 s	—
`opencode`	**`aegis_enforced`**	**6/6**	**Yes**	**11.1 s**	**8.3 / 18.5 ms**
`claude`	`vendor_default`	6/6	No	11.9 s	—
`claude`	**`aegis_enforced`**	**6/6**	**Yes**	**12.4 s**	**8.3 / 15.8 ms**
`hermes`	`vendor_default`	6/6	No	18.8 s	—
`hermes`	**`aegis_enforced`**	**6/6**	**Yes**	**28.4 s**	**7.9 / 14.9 ms**
`agy`	`vendor_default`	6/6	No	38.9 s	—
`agy`	**`aegis_enforced`**	**6/6**	**Yes**	**55.9 s**	**8.1 / 14.8 ms**

median (and 25/25 in 20.10 ms mean in our 40-file Rust `commit_frozen_stage` microbenchmark).

RQ5: Cross-Domain Commit Verification and Hash-Chained Audit (Table 9). Across all six `WorkspaceDomain` profiles (`Code`, `Docs`, `Data`, `Binary`, `AppState`, `Memory`), `DomainProfile::verify_workspace_changes()` blocks **60/60 (100%)** cross-domain, ELF/Mach-O binary-disguise, and memory-poisoning commits on $\mathcal{W}_{\text{frozen}}$ in **67.47 μs** mean, while appending 500 SHA-256 hash-chained `audit.jsonl` events takes **64.52 ms** and full chain verification takes **8.87 ms** (17.7 μs/event).

6.4 RQ6: Multi-File Coding Utility Across All 4 Live Agents

Table 10 reports end-to-end performance on a 4-module Python `billing/` package refactoring task (fixing coupled discount-scaling and post-discount tax bugs across `discounts.py` and `invoice.py`), verified by a 6-test `unittest` suite (`python3 -m unittest`). All four production agents (**4/4, 100%**) complete the multi-file edit and pass all 6 unit tests inside `aegis_enforced` (matching their 4/4 pass rate on `benign` in Table 5), while keeping $\mathcal{W}_{\text{host}}$ 100% unmodified until `aegis-os diff` (7.90–8.32 ms) and `aegis-os commit` (14.76–18.46 ms) promote the verified delta. Wall-clock differences (e.g., 12.4 s vs. 11.9 s on `claude`) reflect cloud LLM token generation variance rather than the ∼20 ms local sandbox overhead.

7 Discussion and Limitations

Linux Path Remapping & Home Masking vs. macOS Seatbelt Denylists. Linux `bwrap --bind-fd` mounts $\mathcal{W}_{\text{shadow}}$ at the exact canonical path of $\mathcal{W}_{\text{host}}$ and masks `/home` with a fresh `tmpfs` (default-deny read and write isolation). Because macOS lacks unprivileged mount namespaces, `aegis-os run` sets `cwd` to $\mathcal{W}_{\text{shadow}}$ under XNU Seatbelt, enforces default-deny writes outside $\{\mathcal{W}_{\text{shadow}}, \mathcal{H}_{\text{agent}}, \texttt{/tmp}\}$, and blocks reads across 20 sensitive credential/keychain/container-socket path patterns in $\mathcal{S}_{\text{host}}$ (offering `MicroVmSandboxDriver` when full Linux-style mount namespace isolation is required on macOS). While `sandbox-exec(1)` carries a manpage deprecation notice, XNU's `sandbox_init` MAC framework remains the active kernel primitive underlying macOS system daemons and vendor sandboxes [2], [13].

Ubuntu 24.04+ AppArmor User-Namespace Policy. As observed on our Ubuntu 24.04.5 LTS testbed (Section 6), Ubuntu 24.04+ sets `kernel.apparmor_restrict_unprivileged_userns = 1` without installing an AppArmor profile for `/usr/bin/bwrap` by default. Rather than degrading to unsandboxed execution, `probe_bwrap_userns()` (Section 3) fails closed at startup and prints the minimal 4-line `/etc/apparmor.d/bwrap` profile granting `userns` capability to `bwrap`.

Threats to Validity, Post-Commit Execution, and Semantic Exfiltration. Our Layer 1 suite evaluates 30 deterministic exploit primitives curated to span `V1`–`V6` and grounded in disclosed CVEs (Table 2); while individual payloads are author-implemented, each tests an OS-level Reference Monitor boundary (Invariants 1–5) enforced by kernel namespaces/MAC rather than signature matching, and Layer 2 pairs single-trial ($n = 1$) live cloud-API runs across 60 matrix cells with $n = 10$–60 repeated trials in Layer 1. Finally, Aegis guarantees that no unapproved change reaches $\mathcal{W}_{\text{host}}$ prior to commit, but if a human explicitly approves malicious source code and later runs it unsandboxed on the host, it executes with host authority; likewise, natural-language prose summarization of proprietary code over an authorized LLM endpoint requires orthogonal planner-level information-flow control [20], [21].

8 Related Work

OS Sandboxing, Containers, and Reference Monitors. Janus [22], Systrace [23], Capsicum [24], Mbox [25], Bubblewrap [14], Firejail [26], Linux Landlock [27], and container sandboxes such as gVisor [28] and Firecracker [19] enforce process isolation outside the untrusted subject [7], [8]. Unlike batch syscall sandboxes or bind-mounted dev-containers (`nerdctl`/Docker, which breached 24/30 primitives in Table 4), Aegis co-designs CoW shadow staging [29], [30], [31], split read-only `.git` views, hop-by-hop L7 API-key injection, and principal-separated commit pinning for interactive LLM agents.

Vendor Agent Sandboxes and Transactional Runtimes. Anthropic's `@anthropic-ai/sandbox-runtime` [13] (used by Claude Code), OpenAI Codex CLI's Seatbelt/Landlock wrapper [2] (excluded from our live runs only because `codex` was not installed on our testbed), and Gemini/AGY's `--sandbox=seatbelt` wrap child shell commands while mounting the host repository read-write, leaving parent native tools, `.mcp.json` servers, `.git/config` hooks, and sandbox environment keys exposed [9], [10], [12]. Containerized agent runtimes such as NVIDIA OpenShell [32] and Dagger `container-use` [33] isolate agents inside container daemons or Git worktrees, whereas Aegis Enforced Runtime operates zero-daemon over native host toolchains and upgrades our companion MCP runtime [1] by moving confinement to the parent OS process before `execve()`.

Prompt-Injection Defenses. Planner-level defenses—including IsolateGPT [34], Dual-LLM/CaMeL [20], [35], FIDES [21], and Progent [36]—track information flow across LLM tool plans [16], [17]. Aegis provides the orthogonal OS enforcement substrate beneath closed- or open-source agent binaries so a subverted planner cannot bypass mediation via native syscalls, repository scripts, or Git hooks.

9 Conclusion

In-process agent plugins, command-regex hooks, and RW-workspace subprocess sandboxes do not constitute a reference monitor, as confirmed both by recent CLI/MCP CVEs and our empirical audit. By inverting control into a parent-process kernel supervisor (`aegis-os run -- <agent>`) combining CoW workspace shadows, split read-only `.git` views, read-only config locks, split-plane L4/L7 boundary key injection, dual-token escalation, and frozen-stage SHA-256 commit pinning, Aegis Enforced Runtime reduces deterministic bypass coverage from 73.3%–93.3% to **0.0%** on macOS and Linux and live repository-trap compromises across four production CLI agents from 100% to **0%**, with 100% multi-file task completion.

Ethics and Artifact Availability

All adversarial experiments were executed solely against synthetic local repositories, disposable loopback endpoints, and canary credentials on isolated test environments; no external services or third-party users were affected. All Rust crates, sandbox profiles, benchmark harnesses (`scripts/p2_live/`), and raw results (`paper2/ENFORCED_RUNTIME_BENCH_REPORT.json`) are open-source at https://github.com/heurion-org/aegis-os.

References

[1] H. Zhao, "Aegis OS: A transactional multi-tenant operating system runtime for eliminating authorization fatigue in autonomous coding agents," *arXiv preprint arXiv:2611.08516*, 2026. [Online]. Available: https://arxiv.org/abs/2611.08516

[2] OpenAI, "OpenAI Codex CLI: Terminal coding agent with macOS Seatbelt and Linux Landlock subprocess sandboxing," https://github.com/openai/codex, 2025.

[3] J. Yang, C. E. Jimenez *et al.*, "SWE-agent: Agent-computer interfaces enable automated software engineering," in *Proc. Adv. Neural Inf. Process. Syst. (NeurIPS)*, vol. 37, 2024, pp. 50 528–50 652.

[4] X. Wang, B. Li *et al.*, "OpenHands: An open platform for AI software developers as generalist agents," in *Proc. Int. Conf. Learn. Represent. (ICLR)*, 2025. [Online]. Available: https://openreview.net/forum?id=OJd3ayDDoF

[5] C. E. Jimenez, J. Yang *et al.*, "SWE-bench: Can language models resolve real-world GitHub issues?" in *Proc. Int. Conf. Learn. Represent. (ICLR)*, 2024. [Online]. Available: https://openreview.net/forum?id=VTF8yNQM66

[6] Anthropic, "Model Context Protocol (MCP): An open protocol for connecting AI applications to external systems," https://modelcontextprotocol.io, 2024.

[7] J. P. Anderson, "Computer security technology planning study," Electronic Systems Division, Air Force Systems Command, Hanscom Field, Bedford, MA, USA, Tech. Rep. ESD-TR-73-51, Vol. II, 1972.

[8] J. H. Saltzer and M. D. Schroeder, "The protection of information in computer systems," *Proceedings of the IEEE*, vol. 63, no. 9, pp. 1278–1308, 1975.

[9] Check Point Research, "Caught in the hook: RCE and API token exfiltration through Claude Code project files (CVE-2025-59536, CVE-2026-21852)," Security Advisory, Check Point Software Technologies, Feb. 2026.

[10] National Vulnerability Database (NIST), "Path-prefix, symlink, and worktree sandbox escapes in MCP filesystem server and Claude Code (CVE-2025-53109, CVE-2025-53110, CVE-2026-55607)," https://nvd.nist.gov, 2026.

[11] National Vulnerability Database (NIST), "Command injection, loopback control-plane RCE, and config tampering in MCP tooling (CVE-2025-6514, CVE-2025-49596, CVE-2025-54135, CVE-2025-54136)," https://nvd.nist.gov, 2025.
[12] National Vulnerability Database (NIST), "Repository `core.fsmonitor` and submodule hook code execution in Hermes Agent and Git (CVE-2026-71963, CVE-2025-48384)," https://nvd.nist.gov, 2026.
[13] Anthropic, "Anthropic Sandbox Runtime (`@anthropic-ai/sandbox-runtime`): Lightweight OS-level filesystem and network sandboxing for CLI agents," https://github.com/anthropics/sandbox-runtime, 2025.
[14] Project Atomic and Containers Organization, "Bubblewrap: Unprivileged sandboxing tool based on Linux namespaces," https://github.com/containers/bubblewrap, 2024.
[15] K. Greshake, S. Abdelnabi, S. Mishra, C. Endres, T. Holz, and M. Fritz, "Not what you've signed up for: Compromising real-world LLM-integrated applications with indirect prompt injection," in *Proc. 16th ACM Workshop Artif. Intell. Security (AISec)*, 2023, pp. 79–90.
[16] E. Debenedetti, J. Zhang, M. Balunović, L. Beurer-Kellner, M. Fischer, and F. Tramèr, "AgentDojo: A dynamic environment to evaluate prompt injection attacks and defenses for LLM agents," in *Proc. Adv. Neural Inf. Process. Syst. (NeurIPS) Datasets and Benchmarks Track*, vol. 37, 2024, pp. 92 895–92 935.
[17] Q. Zhan, Z. Liang, Z. Ying, and D. Kang, "InjecAgent: Benchmarking indirect prompt injections in tool-integrated large language model agents," in *Findings Assoc. Comput. Linguistics (ACL)*, 2024, pp. 10 471–10 506.
[18] N. Boucher and R. Anderson, "Trojan source: Invisible vulnerabilities," in *Proc. 32nd USENIX Security Symp.*, 2023, pp. 6507–6524.
[19] A. Agache, M. Brooker *et al.*, "Firecracker: Lightweight virtualization for serverless applications," in *Proc. 17th USENIX Symp. Netw. Syst. Design Implement. (NSDI)*, 2020, pp. 419–434.
[20] E. Debenedetti, I. Shumailov *et al.*, "Defeating prompt injections by design," in *Proc. IEEE Conf. Secure Trustworthy Mach. Learn. (SaTML)*, 2026. [Online]. Available: https://arxiv.org/abs/2503.18813
[21] M. Costa, B. Köpf *et al.*, "Securing AI agents with information-flow control," in *Proc. Adv. Neural Inf. Process. Syst. (NeurIPS)*, 2026. [Online]. Available: https://arxiv.org/abs/2505.23643
[22] I. Goldberg, D. Wagner, R. Thomas, and E. A. Brewer, "A secure environment for untrusted helper applications: Confining the wily hacker," in *Proc. 6th USENIX Security Symp.*, 1996, pp. 1–13.
[23] N. Provos, "Improving host security with system call policies," in *Proc. 12th USENIX Security Symp.*, 2003, pp. 257–272.
[24] R. N. M. Watson, J. Anderson, B. Laurie, and K. Kennaway, "Capsicum: Practical capabilities for UNIX," in *Proc. 19th USENIX Security Symp.*, 2010, pp. 29–46.
[25] T. Kim and N. Zeldovich, "Practical and effective sandboxing for non-root users," in *Proc. USENIX Annu. Tech. Conf. (ATC)*, 2013, pp. 139–144.
[26] Netblue30 and Firejail Contributors, "Firejail: Linux namespaces and Seccomp-BPF application sandbox," https://github.com/netblue30/firejail, 2024.
[27] M. Salaün, "Landlock: Unprivileged access control (Linux kernel userspace API documentation)," https://docs.kernel.org/userspace-api/landlock.html, 2021.
[28] E. G. Young, P. Zhu, T. Caraza-Harter, A. C. Arpaci-Dusseau, and R. H. Arpaci-Dusseau, "The true cost of containing: A gVisor case study," in *Proc. 11th USENIX Workshop Hot Topics Cloud Comput. (HotCloud)*, 2019.
[29] E. B. Nightingale, P. M. Chen, and J. Flinn, "Speculative execution in a distributed file system," in *Proc. ACM SIGOPS 20th Symp. Operating Syst. Principles (SOSP)*, 2005, pp. 191–205.
[30] D. E. Porter, O. S. Hofmann, C. J. Rossbach, A. Benn, and E. Witchel, "Operating system transactions," in *Proc. ACM SIGOPS 22nd Symp. Operating Syst. Principles (SOSP)*, 2009, pp. 161–176.
[31] C. P. Wright, J. Dave *et al.*, "Versatility and Unix semantics in namespace unification," *ACM Trans. Storage*, vol. 2, no. 1, pp. 74–105, 2006.
[32] NVIDIA, "NVIDIA OpenShell: Kernel-enforced container runtime and policy control plane for autonomous AI agents," https://github.com/NVIDIA/OpenShell, 2026.
[33] Dagger, "Container Use (`container-use`): Isolated container and Git worktree environments for coding agents," https://github.com/dagger/container-use, 2025.
[34] Y. Wu, F. Roesner, T. Kohno, N. Zhang, and U. Iqbal, "IsolateGPT: An execution isolation architecture for LLM-based agentic systems," in *Proc. Netw. Distrib. Syst. Security Symp. (NDSS)*, 2025, pp. 1–18. [Online]. Available: https://arxiv.org/abs/2403.04960
[35] S. Willison, "The dual LLM pattern for building AI assistants that can resist prompt injection," https://simonwillison.net/2023/Apr/25/dual-llm-pattern/, 2023.
[36] T. Shi, J. He *et al.*, "Progent: Programmable privilege control for LLM agents," *arXiv preprint arXiv:2504.11703*, 2025. [Online]. Available: https://arxiv.org/abs/2504.11703

Hui Zhao is a Researcher at Heurion Research, Rotterdam, Netherlands, and lead architect of the open-source Aegis OS project. His research interests include operating system security, kernel sandboxing, transactional virtual filesystems, and trustworthy runtime architectures for autonomous software engineering agents.