

HTML – Simple HTML web page

`<!DOCTYPE HTML>`
`<html>`
`<head>`
`<title>My Page Title!</title>`
`</head>`
`<body>`

Tags

Title is the browser tab title

Also in head is the `<meta>` tag which gives info about the webpage

meta charset gives the page character encoding

`<h1>Introduction</h1>`
`<p>`This is a simple HTML web page. The content here is part of a ‘paragraph’. Web browser will lay out this text and introduce line breaks so the text fits nicely in the browser window.`</p>`

`</body>`
`</html>`

`<meta name = "description"
content = "A description of the site goes here">`

swap out name for property and use og:description to support Meta Open Graph Data i guess...

HTML – Basic Tags

the html lang attribute tells the page language

- `<html></html>` - Surround entire document
- `<head></head>` - Surround header material (titles, css info, etc.)
`<br>` puts content on new line
- `<body></body>` - Contains the main content of the page
- `<p></p>` - Hold a single paragraph that the browser will typeset.
- `<h1></h1>`, `<h2></h2>`, ... - Hold a heading line that is used to mark sections of a document for the reader

elements go inside one another via nesting

just close the inner element before the outer one

to add a fun picture in the browser tab (aka favicon) - it will be the displayed icon when a user bookmarks your site

```
<link rel="icon" href="favicon.ico" type="image/x-icon" />
```

the href can be a link to what ever you use and type is image / your image type (image / gif for gifs)

****only firefox supports gif tho****

HTML – More basic tags

- Links – These mark a hyperlink around link text. When click by user, browser loads the page in the HREF attribute.
- Format `<A HREF="url target">Text for link</A>`
 - Only 'Text for link' will show up on page.
- Target attribute, indicates which window/tab should be used for the linked page
 - **target="_self"** – Default. Place the content in the current tab
 - **target="_blank"** – Place the content in a newly created tab

HTML – More basic tags

- `<IMG>` - Will display an image
 - Image file must be in a popular graphics format (gif, jpg, png, etc)
 - Format :

`<IMG src="url for image file" width=#, height=#, alt="Text to display">`

img does NOT require a closing tag

HTML – More on Links

- *href* attribute
 - This can be any URI or local file
 - URI should include protocol, server, and path
 - Local file can be specified with an absolute or relative path
- Content can be text OR an image. Ex:

`<A HREF=http://target.com/path/file.html>`

`<IMG src="small_pic.jpg">`

`</A>    email: <a href="mailto:email@email.com">email</a>`

- *title* attribute
 - Used to provide descriptive text.
 - Text is displayed when cursor is hovered over link

HTML – More on Links

- Links can target ‘bookmarks’ created with the *id* attribute on a tag
- Will scroll to the section marked with the named id

`<script src="my-js-file.js" defer></script>`

some_web_page.html:

...
`<h2 id="MoreStyles">`
...

Inner link:

`<A HREF="#MoreStyles">Go to MoreStyles section</A>`

defer makes sure all HTML is loaded for the script to work

nest an image tag in anchor tag to make image a link

file link `<a href="/file.ext" download>` `<-- (file needs to be in same directory)`

From another_web_page.html:

...
`<A HREF=http://someserver.com/some\_web\_page.html#MoreStyles>See info on Styles</A>`

`<link rel="stylesheet" href="my-css-file.css" />`

links to an internal stylesheet and goes in the head tag

HTML - Lists

- Supports:
 - `<UL></UL>` - Unordered List
 - `<OL></OL>` - Ordered List
 - `<LI></LI>` - Encloses a single list item

HTML – Example: Lists

```
<!DOCTYPE html>
<html>
<body>
```

```
<h2>Unordered List</h2>
```

```
<ul>
  <li>Coffee</li>
  <li>Tea</li>
  <li>Milk</li>
</ul>
```

```
<h2>Ordered List</h2>
```

```
<ol>
  <li>Coffee</li>
  <li>Tea</li>
  <li>Milk</li>
</ol>
```

```
</body>
</html>
```

A navmenu is just an
unordered list of links

Unordered List

- Coffee
- Tea
- Milk

Ordered List

1. Coffee
2. Tea
3. Milk

HTML – Adding styles to lists

- UL takes a style attribute to customize the list
 - list-style-type
 - circle
 - square
 - disc
 - none

HTML – Example: Styled lists

```
<!DOCTYPE html>
<html>
<body>
<h2>Unordered List with Disc Bullets</h2>
<ul style="list-style-type:disc;">
  <li>Coffee</li>
  <li>Tea</li>
  <li>Milk</li>
</ul>
</body>
</html>
```

```
<!DOCTYPE html>
<html>
<body>
<h2>Unordered List with Square Bullets</h2>
<ul style="list-style-type:square;">
  <li>Coffee</li>
  <li>Tea</li>
  <li>Milk</li>
</ul>
</body>
</html>
```

Unordered List with Disc Bullets

- Coffee
- Tea
- Milk

Unordered List with Square Bullets

- Coffee
- Tea
- Milk

description lists <dl></dl> look like terms in a dictionary

<dt>term</dt>

<dd>definition</dd>

HTML – Formatting Tags

- `<b></b>` - Bold text
- `<strong></strong>` - Important text (similar to bold)
- `<i></i>` - Italic text
- `<em></em>` - Emphasized text (similar to Italic)
- `<mark></mark>` - Marked text
- `<small></small>` - Small text
- `<del></del>` - Deleted text (stroked text)
- `<ins></ins>` - Inserted text
- `<sub></sub>` - Subscript text
- `<sup></sup>` - Superscript text

em is better for screen readers

HTML – Example: Formatting Tags

<!DOCTYPE html>

<html>

<body>

<blockquote> with a cite attribute will make a hanging quote

<cite> will make a piece of text italic as a source of a quote

<p>This text is normal.</p>

<p>This text is bold.</p>

<p><i>This text is italic.</i></p>

<p>This text is emphasized.</p>

<p>This text is strong.</p>

<p><mark>This text is marked.</mark></p>

<p><small>This text is small.</small></p>

<p>This text is deleted.</p>

<p><ins>This text is inserted.</ins></p>

<p>This text is ^{superscripted.}</p>

<p>This text is _{subscripted.}</p>

</body> <abbr></abbr> for abbreviations (use title attribute for description)

</html>

This text is normal.

This text is bold.

This text is italic.

This text is emphasized.

This text is strong.

This text is marked.

This text is small.

~~This text is deleted.~~

This text is inserted.

This text is ^{superscripted}.

This text is _{subscripted}.

q with a cite attribute will make a quote that has " .." around it

HTML - Comments

- Comments are contained in '`<!-- -->`'
- Example:

`<!-- This is a comment and does not affect rendering of the page at all -->`