



REBOL Programming For The Absolute Beginner

By: Nick Antonaccio

Updated: 3-24-2010

The new official URL for this tutorial is <http://re-bol.com/>

An old version of this tutorial is available at http://musiclessonz.com/rebol_tutorial-old.html

Be sure to see the [68 YouTube video tutorials](#) that cover this material (10 hours of video).

A simple introductory [tutorial application for children](#) is also available.

Contents:

[1. Introducing REBOL](#)

[2. How This Tutorial Is Organized](#)

[3. Getting Started: Downloading and Installing REBOL, Hello World](#)

[4. An Amazingly Tiny Demo and Some Simple Examples](#)

[4.1 Opening REBOL Directly to the Console](#)

[5. Some Perspective for Absolute Beginners](#)

[6. A Quick Summary of the REBOL Language](#)

[6.1 Built-In Functions and Basic Syntax](#)

[6.2 More Basics: Word Assignment, I/O, Files, Built-In Data Types and Native Protocols](#)

[6.3 GUIs \(Program Windows\)](#)

[6.4 Blocks, Series, and Strings](#)

[6.5 Conditions](#)

[6.6 Loops](#)

[6.7 User Defined Functions and Imported Code](#)

[6.8 Quick Review and Synopsis](#)

[6.9 A Telling Comparison](#)

[7. More Essential Topics](#)

[7.1 Built-In Help and Online Resources](#)

[7.2 Saving and Running REBOL Scripts](#)

[7.3 "Compiling" REBOL Programs - Distributing Packaged .EXE Files](#)

[7.4 Embedding Binary Resources and Using REBOL's Built In Compression](#)

[7.5 Running Command Line Applications](#)

[7.6 Responding to Special Events in a GUI - "Feel"](#)

[7.7 Common REBOL Errors, and How to Fix Them](#)

[8. EXAMPLE PROGRAMS - Learning How All The Pieces Fit Together](#)

[8.1 Little Email Client](#)

[8.2 Simple Web Page Editor](#)

[8.3 Card File](#)

[8.4 Little Menu Example](#)

[8.5 Loops and Conditions - A Simple Data Storage App](#)

[8.6 FTP Chat Room](#)

[8.7 Image Effector](#)

[8.8 Guitar Chord Diagram Maker](#)

[8.9 Shoot-Em-Up Video Game](#)

[8.10 Listview Multi Column Data Grid Example](#)

[8.11 Thumbnail Maker](#)

[9. Additional Topics](#)

[9.1 Objects](#)

[9.2 Ports](#)

[9.3 Parse \(REBOL's Answer to Regular Expressions\)](#)

[9.4 2D Drawing, Graphics, and Animation](#)

[9.5 Using Animated GIF Images](#)

[9.6 3D Graphics with r3D](#)

[9.7 Multitasking](#)

[9.8 Using DLLs and Shared Code Files in REBOL](#)

[9.9 Web Programming and the CGI Interface](#)

[9.10 WAP - Cell Phone Browser CGI Apps](#)

[9.11 REBOL as a Browser Plugin](#)

[9.12 Using Databases](#)

[9.13 Menus](#)

[9.14 Multi Column GUI Text Lists \(Data Grids\)](#)

[9.15 RebGUI](#)

[9.16 Creating PDF files using pdf-maker.r](#)

[9.17 Creating .swf Files with REBOL/Flash](#)

[9.18 Rebcode](#)

9.19 Useful REBOL Tools
9.20 6 REBOL Flavors
9.21 Bindology, Dialects, Metaprogramming and Other Advanced Topics
10. REAL WORLD CASE STUDIES - Learning To Think In Code
10.1 Case 1 - Scheduling Teachers
10.2 Case 2 - A Simple Image Gallery CGI Program
10.3 Case 3 - Days Between Two Dates Calculator
10.4 Case 4 - Simple Search
10.5 Case 5 - A Simple Calculator Application
10.6 Case 6 - A Backup Music Generator (Chord Accompaniment Player)
10.7 Case 7 - FTP Tool
10.8 Case 8 - Jeopardy
10.9 Case 9 - Creating a Tetris Game Clone
10.10 Case 10 - Scheduling Teachers, Part Two
10.11 Case 11 - An Online Member Page CGI Program
10.12 Case 12 - A CGI Event Calendar
10.13 Case 13 - Ski Game, Snake Game, and Space Invaders Shootup
10.14 Case 14 - Media Player (Wave/Mp3 Jukebox)
10.15 Case 15 - Creating the REBOL "Demo"
10.16 Case 16 - Guitar Chord Chart Printer
10.17 Case 17 - Web Site Content Management System (CMS), Sitebuilder.cgi
10.18 Case 18 - A GUI Playing Card Framework (Creating a Freecell Clone)
10.19 Case 19 - Downloading Directories - A Server Spidering App
10.20 Case 20 - Vegetable Gardening
10.21 Case 21 - An Additional Teacher Automation Project
11. Other Scripts
12. Learning More About REBOL - IMPORTANT DOCUMENTATION LINKS
13. Beyond REBOL
14. Appendix 1: A REBOL Song

1. Introducing REBOL







What is REBOL? Why use it?

- REBOL is a uniquely small and productive development tool that can be used to create powerful **desktop software**, dynamic CGI **web site** and server applications, rich distributed *browser plugin* applications, mobile apps, and more. REBOL's blend of capability, compact size, ease of use, cross-platform functionality, and variety of interpreter platforms enable it to gracefully replace many common tools such as Java, Python, Visual Basic, C, C++, PHP, Perl, Ruby, Javascript, toolkits such as wxWidgets, graphic/multimedia platforms such as Flash, DBMSs such as Access, MySQL, and SQLite, a variety of system utilities, and more, all with one simple paradigm. Despite its broad usefulness, REBOL is far **easier** to implement than any other comparable tool.
- REBOL is **ultra compact**. Its uncompressed file size is about 1/2 Meg on most platforms. It can be downloaded, installed, and put to use on all supported operating systems in *less than a minute*, even over a slow dialup connection.
- REBOL can also be used immediately, without installation, on over 40 operating systems as a lightweight file manager, text editor, calculator, database manager, email client, ftp client, news reader, image viewer/editor, OS shell, and more. You can use it as a simple utility program with a familiar interface to common computing activities, on just about any computer, even if you're unfamiliar with the operating system.
- REBOL includes *GUI, network, graphics, sound, database, image manipulation, math, parsing, compression, CGI decoding, secure network services, text editing, and other functions built-in*. **No external modules, tool kits, or IDEs are required for any essential functionality.**
- REBOL is **easy** enough for absolute beginners and average computer users to operate immediately, but *powerful and rich* enough for a wide variety of complex professional work.
- REBOL has useful *built-in help* for all available functions and language constructs.
- REBOL is supported by a friendly and knowledgeable community of [active developers](#) around the world.
- REBOL is available in both **free** and supported commercial versions. The free version can be used to create commercial applications, with very few license restrictions. Part of the REBOL language is open source, and that code is available directly in the interpreter. The closed components *are kept in an escrow account*, in case the Rebol Technologies company ever goes out of business (source code escrow licenses are available for those who use it in critical work).
- REBOL has a facility for ultra fast performance using "Rebcode", which can be optimized like assembly language, but works the same way across all supported hardware and operating systems (using the exact same code).
- REBOL was created by [Carl Sassenrath](#), who developed the Amiga operating system executive in 1985 (the first preemptive multitasking OS kernel for personal computers). REBOL has been in commercial use since its first release in 1998, and a 3rd major release of the language is in active development as of 2009.
- REBOL is a modern, multi paradigm development tool (procedural, object oriented, and functional),

but its [unique syntax](#) goes well beyond traditional approaches to computer language design. REBOL code is typically ***much shorter and more readable*** than other languages, and REBOL is often ***far more productive*** than other development tools (very often, *dramatically* so). ***There's absolutely no simpler solution for cross-platform GUI creation, anywhere*** (the code for a complete program window with a button is simply: `view layout [button]`). But that just scratches the surface. REBOL has a striking ability to simplify difficult computing tasks of all types, with straightforward, high level *code dialects*. No other development tool is as adept at creating practical *domain specific languages*. On a more basic level, the storage/manipulation/transfer of all data is managed by a *single ubiquitous code structure*. Arrays, lists, tables, and even sizable databases of mixed text, code, and binary data are all stored using one consistent "block" syntax. Blocks are created simply by surrounding any list of data with square brackets. Like everything else in REBOL, the format is extremely simple, but it enables many powerful features for searching, sorting, comparing, dissecting, evaluating, storing, retrieving, transferring and otherwise manipulating information of all types. Common network protocols and data values are also natively usable in REBOL. You can read and write data directly to/from web servers, email accounts, databases, and more, add/subtract time, date, and other values automatically, manipulate XML, HTML, CSV and other formats natively, display and apply effects to images, play sounds, etc., all without any preparation, complex formatting, or use of any external library code. REBOL has a built in, powerful "parse" dialect which elegantly replaces the need for regular expressions in most cases. The list of such practical features is long, but REBOL is not built from simple gimmicks - it's a deep and powerful tool. Because so many practical computing elements are all built into REBOL, and interact *natively*, the learning curve required to ***get real work done*** is *much* easier than in other development environments. No other language includes such straightforward and versatile mechanisms for accomplishing the most basic work of computers - managing data of all types.

- REBOL is small, practical, portable, extremely productive, and *different* than the typical mess of modern computing tools. It does *not* rely on a large stack of disparate technologies to accomplish useful computing goals. All it's features exist inside one *tiny* downloadable executable that *anyone* can get running, on just about any computer, in less than a minute. It can be used as anything from compact utility application to powerful professional development environment. Even average computer users with absolutely no coding experience can learn to create *real, useful and powerful* REBOL scripts very quickly.

Here are a few screen shots of examples covered in this tutorial:



Downloadable Windows executables of these programs are available at:

http://musiclessonz.com/rebol_tutorial/examples

2. How This Tutorial Is Organized

There are 5 main parts to this text:

1. **Fundamentals:**
The first sections cover how to use the REBOL interpreter (typing in the console, creating scripts, navigating built-in help, creating .exe's, etc.), basic language constructs and syntax (variables, functions, data types, conditions, loops, i/o, etc.), and the fundamentals of creating GUI program windows (~65 pages).
2. **Examples:**
11 fully documented programs which demonstrate, line by line, how the above fundamentals are put together to form complete applications (~35 pages).
3. **Other Important Topics:**
Graphics, animation, 3D, using databases, accessing DLLs and the OS API, web site CGI programming, writing multitasking code, 3rd party tool kits, parse, objects, ports, and more (~100 pages).
4. **Real World Case Studies:**
21 full case studies covering how a wide variety of complete desktop, network, and web site applications were conceived and created using REBOL. This section demonstrates, step by step, how each of the examples grew from concept to final design using outlines, pseudo code, and detailed finished code. Each example demonstrates a variety of practical REBOL concepts, code patterns, and tools, and helps guide you towards "thinking in REBOL" (~230 pages).
5. **Additional Scripts and Resources:**
More code and resources to help complete your understanding of REBOL and continue learning.

This tutorial is less than 450 pages, yet it covers the REBOL language from the ground up, fully documents the creation of *more than 50 applications*, and contains *many* additional short scripts and useful concepts. Links to other online documentation resources are provided to more fully learn many topics, but no third party reference materials are required to understand any example in this text, even if you've never programmed a line of code before. If you're familiar with other programming languages, be prepared to think about coding in ways that are a bit different from your accustomed patterns. You won't find the *typical* explanations of object oriented programming, modules, pointers, arrays, string management, regular expressions, or other common topics in this text. That's because REBOL's design provides straightforward solutions to reduce or eliminate the need for many complex syntax structures and coding techniques you may know. Every step of the way through this tutorial, you'll pick up practical approaches to easily achieve computing goals of all types. By learning REBOL, you'll learn to get many things *done* more quickly and easily than you can with any other tool. Enjoy!

3. Getting Started: Downloading and Installing REBOL, Hello World

The REBOL interpreter is a program that runs on your computer. It translates written text in the REBOL language syntax ("source code") to instructions the computer understands. To get the free REBOL interpreter, go to:

<http://rebol.com/view-platforms.html>

For Microsoft Windows, download the rebview.exe file - just click the link with your mouse and save it to your hard drive. If you want to run REBOL on any other operating system (Macintosh, Linux, etc.), just select, download and run the correct file for your computer. It works the same way on every operating system. You can use the stand-alone versions on just about any desktop machine. Upload the correct interpreter [version](#) to your web server and you can also execute REBOL CGI programs directly on your web site. You can also install a [plugin version](#) to run full REBOL desktop applications directly on pages in a web browser.

Once you've got the tiny REBOL desktop interpreter downloaded, installed, and running on your computer (Start -> Programs -> REBOL -> REBOL View), *click the "Console" icon*, and you're ready to start typing in REBOL programs. To run your first example, type the following line into the REBOL interpreter, and then press the [Enter] (return) key on your keyboard:

```
alert "Hello world!"
```

Before going any further, give it a try. [Download](#) REBOL and type in the code above to see how it works. It's extremely simple and literally takes just a few seconds to install. To benefit from this tutorial, type or

paste each code example into the REBOL interpreter to see what happens.

Install Notes:

To enable REBOL/View *console* support in Ubuntu Linux, follow these instructions:

1. Download the tar.gz file for Linux x86 - Fedora (Kernel 2.6).
2. Open with archive manager (default).
3. Look in the rebol-276 folder (or whatever version you've downloaded).
4. Select and extract the "rebview" file into Ubuntu's HOME directory (the parent of the Ubuntu folder in the file system, or /home/ubuntu/ at the command line). In some versions, the file name is "rebol" instead of "rebview".
5. Open a terminal window (Applications -> Accessories -> Terminal)
6. Type "./rebview" (without the quotes), or "./rebol", depending on the version you've downloaded.

On some versions of Linux, you may need to run "./rebview +i" to install the required libs.

4. An Amazingly Tiny Demo and Some Simple Examples

Many of the examples programs in this tutorial are available as downloadable Windows executables, at:

http://musiclessonz.com/rebol_tutorial/examples

To whet your appetite, here's an example that demonstrates just how potent REBOL code can be. The following script contains 10 useful programs in *LESS THAN HALF A PRINTED PAGE OF CODE*:

1. FREEHAND PAINT: Draw and save graphic images
2. SNAKE GAME: Eat the food, avoid hitting the walls and yourself
3. TILE PUZZLE, "15": Arrange the tiles into alphabetical order
4. CALENDAR: Save and view events for any date
5. VIDEO: Live webcam *video* viewer (*not* just a static image)
6. IPS: Display your LAN and WAN IP addresses
7. EMAIL: Read emails from any pop account
8. DAY CALCULATOR: Count the days between 2 selected dates
9. PLAY SOUNDS: Browse your computer for wave files to play
10. FTP TOOL: Web site editor (browse folders on your web server, click files to edit and save changes back to your server, create and edit new files, etc.)

This example is 100% native REBOL code. No external libraries, images, GUI components, or other resources of any kind are imported or called. It runs on Windows, Mac, Linux, and any other OS supported by REBOL/View. To run it, just [download](#) the tiny REBOL interpreter and copy/paste the code below into the console (a Windows .exe is also available [here](#)):

```
REBOL[title:"Demo"]p: :append kk: :pick r: :random y: :layout q: 'image
z: :if gg: :to-image v: :length? g: :view k: :center-face ts: :to-string
tu: :to-url sh: :show al: :alert rr: :request-date co: :copy g y[style h
btn 150 h"Paint"[g/new k y[s: area black 650x350 feel[engage: func[f a e][
z a = 'over[p pk: s/effect/draw e/offset sh s]z a = 'up[p pk 'line]]]
effect[draw[line]]b: btn"Save"[save/png %a.png gg s al"Saved 'a.png"]btn
"Clear"[s/effect/draw: co[line]sh s]]h"Game"[u: :reduce x: does[al join{
SCORE: }[v b]unview]s: gg y/tight[btn red 10x10]o: gg y/tight[btn tan
10x10]d: 0x10 w: 0 r/seed now b: u[q o((r 19x19)* 10)+ 50x50]q s((r
19x19)* 10)+ 50x50)]g/new k y/tight[c: area 305x305 effect[draw b]rate 15
feel[engage: func[f a e][z a = 'key[d: select u['up 0x-10 'down 0x10 'left
-10x0 'right 10x0]e/key]z a = 'time[z any[b/6/1 < 0 b/6/2 < 0 b/6/1 > 290
b/6/2 > 290][x]z find(at b 7)b/6[x]z within? b/6 b/3 10x10[p b u[q s(last
b)]w: 1 b/3:((r 29x29)* 10)]n: co/part b 5 p n(b/6 + d)for i 7(v b)1[
either(type?(kk b i)= pair!)[p n kk b(i - 3)][p n kk b i]]z w = 1[clear(
back tail n)p n(last b)w: 0]b: co n sh c]]do[focus c]]h"Puzzle"[al{
Arrange tiles alphabetically:]g/new k y[origin 0x0 space 0x0 across style
p button 60x60[z not find[0x60 60x0 0x-60 -60x0]face/offset - x/offset[
exit]tpt: face/offset face/offset: x/offset x/offset: tpt]p"O"p"N"p"M"p"L"
return p"K"p"J"p"I"p"H"return p"G"p"F"p"E"p"D"return p"C"p"B"p"A"x: p
white edge[size: 0]]h"Calendar"[do bx:[z not(exists? %s)[write %s "" ]rq:
rr g/new k y[h5 ts rq aa: area ts select to-block(find/last(to-block read
s)rq)rq btn"Save"[write/append %s rejoin[rq] {"aa/text"} "]unview do bx]]
]h"Video"[wl: tu request-text/title/default"URL:"join"http://tinyurl.com"
"/m54ltm"g/new k y[image load wl 640x480 rate 0 feel[engage: func[f a e][
```

```

z a = 'time[f/image: load wl show f]]]]h"IPs"[parse read tu join"http://"
"guitarz.org/ip.cgi"[thru<title>copy my to</title>]i: last parse my none
al ts rejoin["WAN: "i" -- LAN: "read join dns:// read dns://]]h"Email"[
g/new k y[mp: field"pop://user:pass@site.com"btn"Read"[ma: co]]foreach i
read tu mp/text[p ma join i"^/^/^/^/^/^/"editor ma]]]]h"Days"[g/new k y[
btn"Start"[sd: rr]btn"End"[ed: rr db/text: ts(ed - sd)show db]text{Days
Between:}db: field]]h"Sounds"[ps: func[sl][wait 0 rg: load sl wf: 1 sp:
open sound:// insert sp rg wait sp close sp wf: 0]wf: 0 change-dir
%/c/Windows/media do wl:[wv: co]]foreach i read %.[z %.wav = suffix? i[p
wv i]]]g/new k y[ft: text-list data wv[z wf <> 1[z error? try[ps value][al
>Error"close sp wf: 0]]]btn"Dir"[change-dir request-dir do wl ft/data: wv
sh ft]]]h{FTP}[g/new k y[px: field"ftp://user:pass@site.com/folder/"[
either dir? tu va: value[f/data: sort read tu va sh f][editor tu va]]f:
text-list[editor tu join px/text value]btn"?"][al{Type a URL path to browse
(nonexistent files are created). Click files to edit.}]]]]

```

That's the entire application - all 10 programs. Go ahead, give it a try. [Download](#) the REBOL interpreter and copy/paste the code above into the console. It only takes a few seconds. By the end of this tutorial you'll know exactly how all that code works, and much more...

4 - Several Basic Examples

The above example is obfuscated to demonstrate just how malleable and compact REBOL code can be. The following examples represent more typical, readable REBOL code. This first example demonstrates how to create a basic GUI program window (the size info in this example is optional):

```
view layout [size 500x400]
```

Here's a program window with a text area and a button:

```
view layout [area btn "Click Me"]
```

In this example, the button does something when clicked:

```

view layout [
  area
  btn "Click Me" [alert "You can type in the square area."]
]

```

The following example demonstrates how the button can be made to save any text typed into the area, to a file on the hard drive:

```

view layout [
  a: area
  btn "Save" [
    write %reboltut.txt a/text
    alert "Saved"
  ]
]

```

Here's a little text editor application that builds on the idea above. You can likely get a sense of how it works just by glancing through the code:

```

view layout [
  hl "Text Editor:"
  f: field 600 "filename.txt"
  a: area 600x350
  across

```

```

    btn "Load" [
        f/text: request-file
        show f
        a/text: read to-file f/text
        show a
    ]
    btn "Save" [
        write to-file request-file/save/file f/text a/text
        alert "Saved"
    ]
]

```

Here's an email client you can use to read and send emails to/from any pop/smtp server:

```

view layout[
    h1 "Send:"
    btn "Server settings" [
        system/schemes/default/host: request-text/title "SMTP Server:"
        system/schemes/pop/host:      request-text/title "POP Server:"
        system/schemes/default/user: request-text/title "SMTP User Name:"
        system/schemes/default/pass: request-text/title "SMTP Password:"
        system/user/email: to-email request-text/title "Your Email Addr:"
    ]
    a: field "user@website.com"
    s: field "Subject"
    b: area
    btn "Send"[
        send/subject to-email a/text b/text s/text
        alert "Sent"
    ]
    h1 "Read:"
    f: field "pop://user:pass@site.com"
    btn "Read" [editor read to-url f/text]
]

```

As you can see, REBOL is typically very easy to read and write.

4.1 Opening REBOL Directly to the Console

Before typing in or pasting any more code, adjust the following option in the REBOL interpreter: click the "User" menu in the graphic *Viewtop* that opens by default with REBOL, and uncheck "Open Desktop On Startup". That'll save you the trouble of clicking the "Console" button every time you start REBOL.

5. Some Perspective for Absolute Beginners

This tutorial moves at a pace quick enough to satisfy experienced developers, but because REBOL's learning curve is different from other programming languages, it can also be understood clearly by beginners. If you're reading this text as a novice programmer, it can be helpful to understand a few basic concepts that provide perspective about learning to program. First:

*Essentially, all computers do is let users input, store, retrieve, organize, share/transfer, manipulate, alter, view and otherwise deal with **data** in useful ways.*

So, everything you'll do when writing code basically involves manipulating text, numbers, and/or binary data (photos, music, etc.). The fundamental components used to deal with data haven't changed too dramatically in the past few decades. They've simply improved in speed, capacity, and interface. In the current state of modern computing, data is typically input, manipulated, and returned via graphical user interfaces such as program windows, web forms displayed in browsers, and other keyboard/mouse driven "GUI"s. Data is saved on local hard drives and storage devices (CDs, thumb drives, etc.) and on remote web servers, and is typically transferred via local networks and Internet connections. Images, sounds, video, and other types of multimedia data are contained in standardized file formats, and graphic data is displayed using standard mathematical techniques. Knowing how to control those familiar computing elements to allow users to manipulate data, is the goal of learning to program. It doesn't matter whether you're interested in writing business applications to work with inventory and scheduling (text and number data), programs to alter web pages (text and image data), programs to play/edit music (binary data), programs to broadcast video across the Internet (rapidly transferred sequential frames of binary data), programs to control robotic equipment,

compute scientific equations, play games, etc... They all require learning to input, manipulate, and return *data* of some sort. You can do all those things with REBOL, and once you've done it in one language, it's easier to do with other programming tools.

REBOL allows programmers to *quickly* build graphic interfaces to input and return all common types of data. It can *easily* manipulate text, graphics, and sounds in useful ways, and it provides *simple* methods to save, retrieve, and share data across all types of hardware, networks, and the Internet. That makes it a great way to begin learning how to program. By learning REBOL, you'll learn about all the fundamental structures and concepts in programming: variables, functions, data types, conditional operations, loops, objects, etc. You'll also learn about important topics such as user interface design, algorithmic thinking, working with databases, the operating system API, CGI, and more. Those topics all share conceptual and technical similarities, regardless of language, and *you'll need to learn to think in those terms* to write computer programs, even in a language that's as easy to learn as REBOL. Despite its ease of use, REBOL is an extremely powerful tool. For years it has been used by professionals in enterprise level work around the world. You may never need to learn another programming language.

If you've never done any real "programming" before, the first part of this text may seem a bit technical. Don't be put off. There is no other language with a faster learning curve than REBOL - you'll begin to see the big picture within a few days. Working through this tutorial, you'll gradually build recognition of REBOL language idioms and practical code patterns, by example. The first part of the tutorial will be a whirlwind introduction to many of the fundamental language elements. Just take it all in, and if you really want to learn, *be sure to type in, or at least copy/paste, each example into the REBOL interpreter*. Reading through the code *isn't* enough.

6. A Quick Summary of the REBOL Language

6.1 Built-In Functions and Basic Syntax

As with any modern programming language, to use REBOL, you need to learn how to use **"functions"**. Functions are words that perform actions. Function words are followed by data **"parameters"** (also called "arguments"). Paste these functions into the REBOL interpreter to see how they work:

```
alert "Alert is a function. THIS TEXT IS ITS PARAMETER."
request "Are you having fun yet?"
editor "Edit this text."
browse http://rebol.com
```

Some functions don't require any data parameters, but do produce **"return"** values. Try these functions in the interpreter. They each return a value selected by the user:

```
request-pass
request-date
request-color
request-file
```

The return values output by the above functions can be used in your programs to accomplish useful goals. The file name output by the "request-file" function, for example, could be used to determine which data gets opened and manipulated in your program. The data returned by the "request-pass" function can be used to control access to selected data.

Many functions have **optional or limited parameters/return values**. These options, called "refinements", are specified by the "/" symbol. Try these variations of the "request-pass" function to see how they each perform differently:

```
request-pass/only
request-pass/user "username"
request-pass/title "The 'title' refinement sets this header text."
request-pass/offset/title 10x100 "'offset' repositions the requester."
```

Some functions take **multiple arguments**. The "rejoin" function returns the joined ("concatenated") text arguments inside brackets. *Concatenation is very important in all types of programming* - you will see this function in use often:

```
rejoin ["Hello " "there" "!" ]
```

6.1.1 Understanding Return Values and the Order of Evaluation

In REBOL, you can put as many functions as you want on one line, and *they are all evaluated strictly from left to right*. Functions are grouped together automatically with their required data parameter(s). The following line contains two alert functions:

```
alert "First function" alert "Second function"
```

Rebol knows to look for one parameter after the first alert function, so it uses the next piece of data on that line as the argument for that function. Next on the line, the interpreter comes across another alert function, and uses the following text as it's data parameter.

In the following line, the first function "request-pass/offset/title" requires *two parameters*, so REBOL uses *the next two items on the line* ("10x100" and "title") as its arguments. After that's complete, the interpreter comes across another "alert" function, and uses the following text, "Processing", as its argument:

```
request-pass/offset/title 10x100 "title" alert "Processing"
```

IMPORTANT: In REBOL, the return values (output) from one function can be used directly as the arguments (input) for other functions. Everything is simply evaluated from left to right. In the line below, the "alert" function takes *the next thing on the line as it's input parameter*, which in this case is *not a piece of data*, but a *function which returns some data* (the concatenated text returned by the "rejoin" function):

```
alert rejoin ["Hello " "there" "!" ]
```

To say it another way, the value returned above by the "rejoin" function is passed to (used as a parameter by) the "alert" function. Parentheses can be used to clarify which expressions are evaluated and passed as parameters to other functions. The parenthesized line below is treated by the REBOL interpreter exactly the same as the line above - it just lets you see more clearly what data the "alert" function puts on screen:

```
alert ( rejoin ["Hello " "there" "!" ] )
```

Perhaps the hardest part of getting started with REBOL is understanding the order in which functions are evaluated. The process can appear to work backwards at times. In the example below, the "editor" function takes the next thing on the line as it's input parameter, and edits that text. In order for the editor function to begin its editing operation, however, it needs a text value to be returned from the "request-text" function. The first thing the user sees when this line runs, therefore, is the text requester. That appears backwards, compared to the way it's written:

```
editor (request-text)
```

Always remember that lines of REBOL code are evaluated from left to right. If you use the return value of one function as the argument for another function, the execution of the whole line will be held up until the necessary return value is processed.

Any number of functions can be written on a single line, with return values cascaded from one function to the next:

```
alert ( rejoin ( ["You chose: " ( request "Choose one:" ) ] ) )
```

The line above is typical of common REBOL language syntax. There are three functions: "alert", "rejoin",

and "request". In order for the first alert function to complete, it needs a return value from "rejoin", which in turn needs a return value from the "request" function. The first thing the user sees, therefore, is the request function. After the user responds to the request, the selected response is rejoined with the text "You chose:", and the joined text is displayed as an alert message. Think of it as reading "display (the following text joined together ("you chose" (an answer selected by the user)))". To complete the line, the user must first answer the question.

To learn REBOL, it's essential to first memorize and recognize REBOL's many built-in function words, along with the parameters they accept as input, and the values which they return as output. When you get used to reading lines of code as functions, arguments, and return values, read from left to right, the language will quickly begin to make sense.

It should be noted that in REBOL, math expressions are evaluated from *left to right* like all other functions. There is no "order of precedence", as in other languages (i.e., multiplication doesn't automatically get computed before addition). To force a specific order of evaluation, enclose the functions in parentheses:

```
print (10 + 12) / 2      ; 22 / 2 = 11 (same as without parentheses)
print 10 + (12 / 2)     ; 10 + 6 = 16
```

REBOL's left to right evaluation is simple and consistent. Parentheses can be used to clarify the flow of code, if ever there's confusion.

6.1.2 White Space

Unlike other languages, REBOL *does not require any line terminators* between expressions (functions, parameters, etc.), and you can insert empty white space (tabs, spaces, newlines, etc.) as desired into code. Text after a semicolon and before a new line is treated as a comment (ignored entirely by the interpreter). The code below works exactly the same as the previous example. *Notice that tabs are used to indent the block of code inside the square brackets* and that the contents of the brackets are spread across multiple lines. This helps group the code together visually, but it's not required:

```
alert rejoin [
    "You chose: "           ; 1st piece of joined data
    (request "Choose one:") ; 2nd piece of joined data
]
```

ONE CAVEAT: parameters for most functions should begin on the same line as the function word. The following example will *not* work properly because the rejoin arguments' opening brackets need to be on the same line as the rejoin function:

```
alert rejoin                ; This does NOT work.
[                            ; Put this bracket on the line above.
    "You chose: "
    (request "Choose one:")
]
```

If you want to comment out a large section of code, simply surround it with curly braces:

```
{
    This line doesn't do anything.
    This line also does nothing.
    This line is ignored too.
}
```

6.2 More Basics: Word Assignment, I/O, Files, Built-In Data Types and Native Protocols

In REBOL, the colon (":") symbol is used to assign word labels ("variables") to values:

```
person: "John"
```

Now, the word label "person" can be used anywhere (without the colon), to represent the text "John". Notice that the variable "person" has been rejoined with some other text below:

```
alert rejoin ["The person's name is " person]
```

Word labels are NOT case sensitive:

```
alert person
alert PERSON
alert PeRson

; to the REBOL interpreter, all three lines above are the same
```

In this next example, the word "filename" is assigned to *the value returned by the request-file function* (a file chosen by the user):

```
filename: request-file
```

Now, the label "filename" can be used to represent the *file selected above*:

```
alert rejoin ["You chose " filename]
```

REBOL is a bit different from other programming languages in that word labels can be assigned to *anything*: numbers, text strings, binary data, arrays, lists, hash tables, functions, and even executable blocks of code. At this point, just be aware that when you see the colon symbol, a word label is being assigned to some value.

The "ask" function is a simple way to get some text data from a user at the interpreter's command line (similar to "request-text", but without using a pop-up requester):

```
ask "What is your name? "
```

In the example below, the variable "name" is assigned to *the text returned by the ask function* (i.e., entered by the user). Again, the parentheses are not required - they're just there to clarify the grouping together of the 'ask' function with its text argument:

```
name: (ask "What is your name? ")
```

Now you can use the variable word "name" to represent whatever text the user typed in response to the above question.

The "print" function is a simple way to display text data at the interpreter's command line:

```
print rejoin ["Good to meet you " name]
```

The "prin" function prints consecutive text elements right next to each other (not on consecutive lines):

```
prin "All " prin "on " prin "one " print "line." print "On another."
```

Multi-line formatted text is enclosed in curly braces ("{}"), instead of quotes:

```
print {
    Line 1
    Line 2
    Line 3
}
```

Quotes and curly braces can be used interchangeably on a single line:

```
print {"text"}
print "{text}"
```

You can print a carriage return using the word "newline" or the characters ^/

```
print rejoin ["This text if followed by a carriage return." newline]
print "This text if followed by a carriage return.^/"
```

Clear the screen using "newpage":

```
prin newpage
```

The "write" function saves data to a file. It takes **two parameters**: a file name to write to, and some data to write to that file.

```
write %/C/YOURNAME.txt name
```

NOTE: in REBOL, the percent character ("%") is used to represent local files. Because REBOL can be used on many operating systems, and because those operating systems all use different syntax to refer to drives, paths, etc., REBOL uses the universal format: %/drive/path/path/.../file.ext . For example, "%/c/windows/notepad.exe" refers to "C:\Windows\Notepad.exe" in Windows. REBOL converts that syntax to the appropriate operating system format, so that your code can be written once and used on every operating system, without alteration. The following 2 functions convert REBOL file format to your operating system's format, and visa versa:

```
to-local-file %/C/YOURNAME.txt
to-rebol-file "C:\YOURNAME.txt"
```

You can *write data to a web site* (or any other connected protocol) using the exact same write syntax that is used to write to a file (be sure to use an appropriate username and password for your web site ftp account):

```
write ftp://user:pass@website.com/name.txt name
```

The "read" function reads data from a file:

```
print (read %/C/YOURNAME.txt)
```

REBOL has a built-in text editor that can also read, write, and manipulate text data:

```
editor %/c/YOURNAME.txt
```

You can read data straight from a web server, an ftp account, an email account, etc. using the same format. Many Internet protocols are built right into the REBOL interpreter. They're understood natively, and REBOL knows exactly how to connect to them without any preparation by the programmer:

```
editor http://rebol.com                ; Reads the content of the
                                        ; document at this URL.
editor pop://user:pass@website.com    ; Reads all emails in this
                                        ; POP inbox.
editor clipboard://                    ; Reads data that has
                                        ; been copied/pasted to
                                        ; the OS clipboard.
print read dns://msn.com               ; Displays the DNS info
                                        ; for this address.
print read nntp://public.teranews.com  ; (Hit the [ESC] key to stop
                                        ; this Usenet listing.)

; NOTE: The editor reads, AND allows you to SAVE EDITS back to the server:
editor ftp://user:pass@website.com/public_html/index.html
```

Transferring data between devices connected by any supported protocol is easy - *just read and write*:

```
; read data from a web site, and paste it into the local clipboard:
write clipboard:// (read http://rebol.com)    ; afterward, try pasting into
                                              ; your favorite text editor

; read a page from one web site, and write it to another:
write ftp://user:pass@website2.com (read http://website1.com)

; again, notice that the "write" function takes TWO parameters
```

Sending email is just as easy, using a similar syntax:

```
send user@website.com "Hello"
send user@website.com (read %file.txt)        ; sends an email, with
                                              ; file.txt as the body
```

The **"/binary"** modifier is used to read or write binary (non-text) data. *You'll use read/binary and write/binary to read and write images, sounds, videos and other non-text files:*

```
write/binary %/c/bay.jpg read/binary http://rebol.com/view/bay.jpg
```

For clarification, remember that the write function takes two parameters. The first parameter above is `"/c/bay.jpg"`. The second parameter is the binary data read from `http://rebol.com/view/bay.jpg`:

```
write/binary (%/c/bay.jpg) (read/binary http://rebol.com/view/bay.jpg)
```

The "load" and "save" functions also read and write data, but in the process, *automatically format* certain data types for use in REBOL. Try this:


```

; assign the word "picture" to the image "load"ed from a given URL:

picture: load http://rebol.com/view/bay.jpg

; save the image to a given file name, and automatically convert it
; to .png format;

save/png %/c/picture.png picture

; show it in a GUI window (much more about this in the next section):

view layout [image load %/c/picture.png]

```

"Load" and "save" are used to conveniently manage certain types of data in formats directly usable by REBOL (images, sounds, DLLs, certain native data structures, etc. can be loaded and used immediately). You'll use "read" and "write" more commonly to store and retrieve typical types of data, exactly byte for byte, to/from a storage medium, when no conversion or formatting is necessary.

REBOL automatically knows how to perform appropriate computations on times, dates, IP addresses, coordinate values, and other common types of data:

```

print 3:30am + 00:07:19      ; increment time values properly
print now                    ; print current date and time
print now + 0:0:30           ; print 30 seconds from now
print now - 10               ; print 10 days ago
print 23x54 + 19x31          ; easily add coordinate pairs
print 192.168.1.1 + 000.000.000.37 ; easily increment ip addresses
view layout [image picture effect [flip]] ; apply effects to image types

```

REBOL also natively understands how to use URLs, email addresses, files/directories, money values, tuples, hash tables, sounds, and other common values in expected ways, *simply by the way the data is formatted*. You don't need to declare, define, or otherwise prepare such types of data as in other languages - just use them.

To determine the type of any value, use the "type?" function:

```

some-text: "This is a string of text"      ; strings of text go between
type? some-text                             ; "quotes" or {curly braces}

an-integer: 3874904                         ; integer values are just pos-
type? an-integer                            ; itive/negative whole numbers

a-decimal: 7348.39                          ; decimal numbers are recognized
type? a-decimal                            ; by the decimal point

web-site: http://musiclessonz.com           ; URLs are recognized by the
type? web-site                             ; http://, ftp://, etc.

email-address: user@website.com             ; email values are in the
type? email-address                        ; format user@somewebsite.domain

the-file: %/c/myfile.txt                    ; files are preceded by the %
type? the-file                             ; character

bill-amount: $343.56                        ; money is preceded by the $
type? bill-amount                          ; symbol

html-tag: <br>                               ; tags are places between <>
type? html-tag                             ; characters

binary-info: #{ddeedd}                     ; binary data is put between
type? binary-info                          ; curly braces and preceded by
                                           ; the pound symbol

image: load http://rebol.com/view/bay.jpg ; REBOL can even automatically

```

```

type? image                                ; recognize the data type of
                                           ; most common image formats.

a-sound: load %/c/windows/media/tada.wav  ; And sounds too!
a-sound/type

```

Data types can be specifically "cast" (created, or assigned to different types) using "to-(type)" functions:

```

numbr: 4729                                ; The label 'numbr now represents the integer
                                           ; 4729.
strng: to-string numbr                     ; The label 'strng now represents a piece of
                                           ; quoted text made up of the characters
                                           ; "4729". Try adding strng + numbr, and
                                           ; you'll get an error.

; This example creates and adds two coordinate pairs. The pairs are
; created from individual integer values, using the "to-pair" function:

x: 12 y: 33 q: 18 p: 7
pair1: to-pair rejoin [x "x" y]           ; 12x33
pair2: to-pair rejoin [q "x" p]           ; 18x7
print pair1 + pair2                       ; 12x33 + 18x7 = 30x40

; This example builds and manipulates a time value using the "to-time"
; function:

hour: 3
minute: 45
second: 00
the-time: to-time rejoin [hour ":" minute ":" second] ; 3:45am
later-time: the-time + 3:00:15
print rejoin ["3 hours and 15 seconds after 3:45 is " later-time]

; This converts REBOL color values (tuples) to HTML colors and visa versa:

to-binary request-color
to-tuple #{00CD00}

```

REBOL has many built-in helper functions for dealing with common data types. Another way to create pair values is with the "as-pair" function. You'll see this sort of pair creation commonly in games which plot graphics at coordinate points on the screen:

```

x: 12 y: 33 q: 18 p: 7
print (as-pair x y) + (as-pair q p)      ; much simpler!

```

Built-in network protocols, native data types, and consistent language syntax for reading, writing, and manipulating data allow you to perform common coding chores easily and intuitively in REBOL. Remember to type or paste every example into the REBOL interpreter to see how each function and language construct operates.

6.3 GUIs (Program Windows)

Graphic user interfaces ("GUI"s) are easier to create in REBOL than in any other language. The functions "view" and "layout" are used together to display GUIs. *The parameters passed to the layout function are enclosed in brackets.* Those brackets can include identifiers for all types of GUI elements ("widgets"):

```

view layout [btn] ; creates a GUI with a button

view layout [field] ; creates a GUI with a text input field

view layout [text "REBOL is really pretty easy to program"]

view layout [text-list] ; a selection list

```

```
view layout [
  button
  field
  text "REBOL is really pretty easy to program."
  text-list
  check
]
```

In REBOL, widgets are called "styles", and the entire GUI dialect is called "VID". You can adjust the visual characteristics of any style in VID by following it with appropriate modifiers:

```
view layout [
  button red "Click Me"
  field "Enter some text here"
  text font-size 16 "REBOL is really pretty easy to program." purple
  text-list 400x300 "line 1" "line 2" "another line"
  check yellow
]
```

The size of your program window can be specified by either of these two formats:

```
view layout [size 400x300]
view layout/size [] 400x300

; both these lines do exactly the same thing
```

A variety of functions are available to control the alignment, spacing, and size of elements in a GUI layout:

```
view layout [
  size 500x350
  across
  btn "side" btn "by" btn "side"
  return
  btn "on the next line"
  tab
  btn "over a bit"
  tab
  btn "over more"
  below
  btn 160 "underneath" btn 160 "one" btn 160 "another"
  at 359x256
  btn "at 359x256"
]
```

VERY IMPORTANT: You can have widgets perform functions when clicked, or when otherwise activated. Just put the functions inside another set of brackets *after* the widget. This is how you get your GUIs to 'do something' (using the fundamentals introduced in the previous section):

```
view layout [button "click me" [alert "You clicked the button."]]

view layout [btn "Display Rebol.com HTML" [editor read http://rebol.com]]

view layout [btn "Write current time to HD" [write %time.txt now/time]]

; The word "value" refers to data contained in a currently activated
; widget:

view layout [
  text "Some action examples. Try using each widget:"
  button red "Click Me" [alert "You clicked the red button."]
```

```

    field 400 "Type some text here, then press [Enter] on your keyboard" [
        alert value
    ]
    text-list 400x300 "Select this line" "Then this line" "Now this one" [
        alert value
    ]
    check yellow [alert "You clicked the yellow check box."]
    button "Quit" [quit]
]

```

To react to right-button mouse clicks on a widget, put the functions to be performed inside a *second* set of brackets after the widget:

```

view layout [
    btn "Right Click Me" [alert "left click"][alert "right click"]
]

```

You can assign keyboard shortcuts (keystrokes) to any widget, so that pressing the key reacts the same way as activating the GUI widget:

```

view layout [
    btn "Click me or press the 'A' key on your keyboard" #"a" [
        alert "You just clicked the button OR pressed the 'A' key"
    ]
]

```

You can assign a *word label* to any widget, and refer to data and properties of that widget by its label. The "text" property is especially useful:

```

view layout [
    page-to-read: field "http://rebol.com"
    ; page-to-read/text now refers to the text contained in that field
    btn "Display HTML" [editor read (to-url page-to-read/text)]
]

```

You can also *set* various properties of a widget using its assigned label. When the "Edit HTML Page" button is clicked below, the text of the multi-line area widget is set to contain the text read from the given URL. The "show" function in the example below is *very* important. It must be used to update the GUI display any time a widget property is changed (if you ever create a GUI that doesn't seem to respond properly, the first thing to check is that you've used a "show" function to properly update any changes on screen):

```

view layout [
    page-to-read: field "http://rebol.com"
    the-html: area 600x440
    btn "Download HTML Page" [
        the-html/text: read (to-url page-to-read/text)
        ; try commenting out the following line to see what happens:
        show the-html
    ]
]

```

Below are two more examples of the above code pattern (getting and setting a widget's text property) - it's a very important idiom in REBOL GUIs. In the first example, the variable "f" is assigned to the field widget, then the variable "t" is assigned to the text contained in that field. In the second example, "t" is assigned the text contained in the f1 field, then the text in f2 is set to "t" - again, *all using the colon symbol*. Note the use of the "show" function to update the display:

```

view layout [

```

```

f: field
btn "Display Variable" [

; When the button is pressed, set the variable
; "t" to hold the text currently in the field
; above, then alert the contents of that variable:

    t: f/text
    alert t
]

view layout [
    f1: field
    btn "Display Variable" [

        ; Set the variable "t" to the text contained
        ; in the f1 field above:

        t: f1/text

        ; Now CHANGE the text in the f2 below to
        ; to equal the text stored in variable "t":

        f2/text: t
        show f2
    ]
    f2: field
]

; You GET the text from a widget by assigning a VALUE to equal the
; widget's text property. You SET/CHANGE the text of a widget by
; assigning THE TEXT PROPERTY of that widget to equal a value.

```

The "offset" of a widget holds its coordinate position. It's another useful property, especially for GUIs which involve movement:

```

view layout [
    size 600x440
    jumper: button "click me" [
        jumper/offset: random 580x420
        ; The "random" function creates a random value within
        ; a specified range. In this example, it creates a
        ; random coordinate pair within the range 580x420,
        ; every time the button is clicked. That random value
        ; is assigned to the position of the button.
    ]
]

```

The "style" function is very powerful. It allows you to assign a specific widget definition, *including all its properties and actions*, to any word label you choose. Any instance of that word label is thereafter treated as a replication of the entire widget definition:

```

view layout [
    size 600x440
    style my-btn btn green "click me" [
        face/offset: random 580x420
    ]
    ; "my-btn" now refers to all the above code
    at 254x84 my-btn
    at 19x273 my-btn
    at 85x348 my-btn
    at 498x12 my-btn
    at 341x385 my-btn
]

```

REBOL is great at dealing with all types of common data - not just text. You can easily display photos and other graphics in your GUIs, play sounds, display web pages, etc. Here's some code that downloads an image from a web server and displays it in a GUI - notice the "view layout" functions again:

```
view layout [image (load http://rebol.com/view/bay.jpg)]
```

The "image" widget inside the brackets displays a picture (.bmp, .jpg, .gif, .png) in the GUI. The "load" function downloads the image to be displayed.

REBOL can apply many built-in effects to images:

```
view layout [image (load http://rebol.com/view/bay.jpg) effect [Emboss]]
view layout [image (load http://rebol.com/view/bay.jpg) effect [Flip 1x1]]
; The parentheses are not required:
view layout [image load http://rebol.com/view/bay.jpg effect [Grayscale]]
; There are MANY more built-in effects.
```

You can impose images onto most types of widgets:

```
view layout [area load http://rebol.com/view/bay.jpg]
; Use the "fit" effect to stretch or shrink the size of the image to that
; of the widget:
view layout [area load http://rebol.com/view/bay.jpg effect [Fit]]
view layout [button load http://rebol.com/view/bay.jpg effect [Fit]]
view layout [field load http://rebol.com/view/bay.jpg effect [Fit Emboss]]
; You can still type into the field and area widgets, as usual.
```

You can apply colors directly to images, just like any other widget. Notice that you can perform calculations directly on color values:

```
view layout [image load http://rebol.com/view/bay.jpg yellow]
view layout [image load http://rebol.com/view/bay.jpg (yellow / 2)]
view layout [image load http://rebol.com/view/bay.jpg (yellow + 0.0.132)]
```

Color gradients (fades from one color to another) are also simple to apply to any widget:

```
view layout [area effect [gradient red blue]]
view layout [
  size 500x400
  backdrop effect [gradient 1x1 tan brown]
  box effect [gradient 123.23.56 254.0.12]
  box effect [gradient blue gold/2]
]
```

You can assign a word label to any layout of GUI widgets, and then display those widgets simply by using the assigned word:

```
gui-layout1: [button field text-list]
view layout gui-layout1
```


You can save any GUI layout as an image, using the "to-image" function. *This enables a built in screen shot mechanism*, and also allows you to easily create/save/manipulate new images using any of the graphic capabilities in REBOL:

```
; assign the label "picture" to an image of a layout:

picture: to-image layout [
    page-to-read: field "http://rebol.com"
    btn "Display HTML"
]

; save it to the hard drive as a .png file:

save/png %c/layout.png picture
```

Here are some other GUI elements used in REBOL's "VID" layout language:

```
view layout [
    backcolor white
    h1 "More GUI Examples:"
    box red 500x2
    bar: progress
    slider 200x16 [bar/data: value show bar]
    area "Type here"
    drop-down
    across
    toggle "Click" "Here" [print value]
    rotary "Click" "Again" "And Again" [print value]
    choice "Choose" "Item 1" "Item 2" "Item 3" [print value]
    radio radio radio
    led
    arrow
    return
    text "Normal"
    text "Bold" bold
    text "Italic" italic
    text "Underline" underline
    text "Bold italic underline" bold italic underline
    text "Serif style text" font-name font-serif
    text "Spaced text" font [space: 5x0]
    return
    h1 "Heading 1"
    h2 "Heading 2"
    h3 "Heading 3"
    h4 "Heading 4"
    tt "Typewriter text"
    code "Code text"
    below
    text "Big" font-size 32
    title "Centered title" 200
    across
    vtext "Normal"
    vtext "Bold" bold
    vtext "Italic" italic
    vtext "Underline" underline
    vtext "Bold italic underline" bold italic underline
    vtext "Serif style text" font-name font-serif
    vtext "Spaced text" font [space: 5x0]
    return
    vh1 "Video Heading 1"
    vh2 "Video Heading 2"
    vh3 "Video Heading 3"
    vh4 "Video Heading 3"
    label "Label"
    below
    vtext "Big" font-size 32
    banner "Banner" 200
```

```
]

```

Here's a list of all the built in widgets (remember, in REBOL's VID language, widgets are called "styles"):

```
probe extract svv/vid-styles 2

```

Here's a list of the changeable attributes ("facets") available to all widgets:

```
probe remove-each i copy svv/facet-words [function? :i]

```

And here's a list of available layout words:

```
probe svv/vid-words

```

That's just the tip of the iceberg. With REBOL, even absolute beginners can create nice looking, powerful graphic interfaces in minutes. See <http://rebol.com/docs/easy-vid.html> and <http://rebol.com/docs/view-guide.html> for more information. Here's a little game that demonstrates common GUI techniques (this whole program was presented earlier in the demo app, in a more compact format without any comments. It's tiny.):

```
; Create a GUI that's centered on the user's screen:

view center-face layout [

    ; Define some basic layout parameters. "origin 0x0"
    ; starts the layout in the upper left corner of the
    ; GUI window. "space 0x0" dictates that there's no
    ; space between adjacent widgets, and "across" lays
    ; out consecutive widgets next to each other:

    origin 0x0 space 0x0 across

    ; The section below creates a newly defined button
    ; style called "piece", with an action block that
    ; swaps the current button's position with that of
    ; the adjacent empty space. That action is run
    ; whenever one of the buttons is clicked:

    style piece button 60x60 [

        ; The line below checks to see if the clicked button
        ; is adjacent to the empty space. The "offset"
        ; refinement contains the position of the given
        ; widget. The word "face" is used to refer to the
        ; currently clicked widget. The "empty" button is
        ; defined later (at the end of the GUI layout).
        ; It's ok that the empty button is not yet defined,
        ; because this code is not evaluated until the
        ; the entire layout is built and "view"ed:

        if not find [0x60 60x0 0x-60 -60x0
            ] (face/offset - empty/offset) [exit]

        ; In English, that reads 'subtract the position of
        ; the empty space from the position of the clicked
        ; button (the positions are in the form of
        ; Horizontal x Vertical coordinate pairs). If that
        ; difference isn't 60 pixels on one of the 4 sides,
        ; then don't do anything.' (60 pixels is the size of
        ; the "piece" button defined above.)

        ; The next three lines swap the positions of the

```

```

    ; clicked button with the empty button.

    ; First, create a variable to hold the current
    ; position of the clicked button:

    temp: face/offset

    ; Next, move the button's position to that of the
    ; current empty space:

    face/offset: empty/offset

    ; Last, move the empty space (button), to the old
    ; position occupied by the clicked button:

    empty/offset: temp
]

; The lines below draw the "piece" style buttons onto
; the GUI display. Each of these buttons contains all
; of the action code defined for the piece style above:

piece "1"   piece "2"   piece "3"   piece "4" return
piece "5"   piece "6"   piece "7"   piece "8" return
piece "9"   piece "10"  piece "11"  piece "12" return
piece "13"  piece "14"  piece "15"

; Here's the empty space. Its beveled edge is removed
; to make it look less like a movable piece, and more
; like an empty space:

empty: piece 200.200.200 edge [size: 0]
]
```

Advanced users may be interested in understanding why the two words "view" and "layout" are used to create GUIs. Those functions represent two complete and separate language dialects in REBOL. The "view" function is a front end to the lower level graphic compositing engine and user interface system built into REBOL. "Layout" is a higher level function that simply assembles view functions required to draw and manipulate common GUI elements. Understanding how the two operate under the hood is helpful in understanding just how deep, compact, and powerful the REBOL language and dialecting design is. For more information, see <http://rebol.com/docs/view-system.html>.

6.4 Blocks, Series, and Strings

In REBOL, all *multiple pieces of grouped data items* are stored in "blocks". Blocks are delineated by starting and ending brackets:

```
[ ]
```

Data items in blocks are *separated by white space*. Here's a block of text items:

```
["John" "Bill" "Tom" "Mike"]
```

Blocks were snuck in earlier as multiple text arguments passed to the "rejoin" function, and as brackets used to delineate GUI code passed to the 'view layout' functions:

```
rejoin ["Hello " "there!"]
view layout [button "Click Me" [alert "Hello there!"]]
```

Blocks are actually the fundamental structure used to organize REBOL *code*. You'll find brackets throughout the language syntax to delineate functions, parameters, and other items. In the next section of this tutorial, you'll see more about functions and control structures that use brackets to separate grouped

items of code. This section will cover how *data* can be grouped into blocks.

The key concept to understand with blocks is that they are used to hold *multiple* pieces of data. Like any other variable data, blocks can be assigned word labels:

```
some-names: ["John" "Bill" "Tom" "Mike"]

; "some-names" now refers to all 4 of those text items

print some-names
```

Blocks of text data (lists) can be displayed in GUIs, using the "text-list" widget:

```
view layout [text-list data (some-names)]
```

The "append" function is used to add items to a block:

```
append some-names "Lee"
print some-names

append gui-layout1 [text "This text was appended to the GUI block."]
view layout gui-layout1
```

The "foreach" function is used to do something to/with each item in a block:

```
foreach item some-names [alert item]
```

The "remove-each" function can be used to remove items from a block that match a certain criteria:

```
remove-each name some-names [find name "i"]

; removes all names containing the letter "i" - returns ["John" "Tom"]
```

Empty data blocks are created with the "copy" function. *"Copy" assures that blocks are erased and defined without any previous content.* You'll use "copy" whenever you need to create an empty block:

```
; Create a new empty block like this:

empty-block: copy []

; NOT like this:

empty-block: []
```

Here's a very typical example that uses a block to save text entered into the fields of a GUI. When the "Save" button is pressed, the text in each of the fields is appended to a new empty block, then that whole block is saved to a text file. To later retrieve the saved values, the block is loaded from the text file, and its items assigned back to the appropriate fields in the GUI:

```
view gui: layout [

    ; label some text fields:

    field1: field
```

```

field2: field
field3: field

; add a button:

btn "Save" [

    ; when the button is clicked, create a new empty block:

    save-block: copy []

    ; add the text contained in each field to the block:

    append save-block field1/text
    append save-block field2/text
    append save-block field3/text

    ; save the block to a file:

    save %save.txt save-block
    alert {SAVED -- Now try running this script again, and load
          the data back into the fields.}
]

; another button:

btn "Load" [

    ; load the saved block:

    save-block: load %save.txt

    ; set the text in each field to the contents of the block:

    field1/text: save-block/1
    field2/text: save-block/2
    field3/text: save-block/3

    ; update the GUI display:

    show gui
]
]

```

After running the script above, open the save.txt file with a text editor, and you'll see it contains the text from the fields in the GUI. You can edit the save.txt file with your text editor, then click the "Load" button, and the edited values will appear back in the GUI. You'll use blocks regularly to store and retrieve *multiple pieces* of data in this way, using text files.

6.4.1 Series Functions

In REBOL, blocks can be automatically treated as lists of data, called "series", and manipulated using built-in functions that enable searching, sorting, and otherwise organizing the blocked data:

```

some-names: ["John" "Bill" "Tom" "Mike"]

sortednames: sort some-names           ; sort alphabetically/ordinally

print first sortednames                 ; displays the first item ("Bill")

print sortednames/1                     ; ALSO displays the first item ("Bill")
                                         ; (just an alternate syntax)

print pick sortednames 1                 ; ALSO displays the first item ("Bill")
                                         ; (another alternate syntax)

find some-names "John"                  ; SEARCH for "John" in the block,
                                         ; set a position marker after that
                                         ; item - a very important function

```

```

find/last some-names "John"      ; search for "John" backwards from
                                   ; the end of the block

select some-names "John"         ; search for "John" in the block
                                   ; and return the Next item.

reverse sortednames              ; reverse the order of items in the
                                   ; block

length? sortednames              ; COUNT items in the block - important

head sortednames                 ; set a position marker at the
                                   ; beginning of the block

next sortednames                 ; set a position marker at the next
                                   ; item in the block

back sortednames                 ; set a position marker at the
                                   ; previous item in the block

last sortednames                 ; set a position marker at the last
                                   ; item in the block

tail sortednames                 ; set a position marker after the
                                   ; last item in the block

at sortednames x                  ; set a position marker at the x
                                   ; numbered item in the block

skip sortednames x                ; set a position marker x items
                                   ; forward or backward in the block

extract sortednames 3             ; collect every third item from the
                                   ; block

index? sortednames                ; retrieves position number of the
                                   ; currently marked item in the block

insert sortednames "Lee"          ; add the name "Lee" at the current
                                   ; position in the block

append sortednames "George"       ; add "George" to the tail of the block
                                   ; and set position marker to the head

remove sortednames                ; remove the item at the currently
                                   ; marked position in the block

remove find sortednames "Mike"    ; ... find the "Mike" item in the
                                   ; block and remove it

change sortednames "Phil"         ; change the item at the currently
                                   ; marked position to "Phil"

change third sortednames "Phil"   ; change the third item to "Phil"

poke sortednames 3 "Phil"         ; another way to change the third item
                                   ; to "Phil"

copy/part sortednames 2           ; get the first 2 items in the block

clear sortednames                 ; remove all items in the block after
                                   ; the currently marked position

replace/all sortednames "Lee" "Al" ; replace all occurrences of "Lee" in
                                   ; the block with "Al"

both: join some-names sortednames ; concatenate both blocks together

intersect sortednames some-names  ; returns the items found in both
                                   ; blocks

```



```

difference sortednames some-names ; returns the items that are NOT
                                   ; found in BOTH blocks

exclude sortednames some-names    ; returns the items in sortednames that
                                   ; are NOT also in some-names

union sortednames some-names      ; returns the items found in both
                                   ; blocks, ignoring duplicates

unique sortednames                ; returns all items in the block,
                                   ; with duplicates removed

empty? sortednames                ; returns true if the block is empty

write %/c/names.txt some-names    ; write the block to the hard drive
                                   ; as raw text data

save %/c/nameess.txt some-names   ; write the block to the hard drive
                                   ; as native REBOL formatted code

```

Learning to use series functions is *absolutely fundamental* to using REBOL. They will be covered by example throughout this text. See <http://www.rebol.com/docs/dictionary.html> for a list of additional series functions. For more information and examples, be sure to read sections 6 and 7 from [the REBOL/Core Users Guide](#) by Carl Sassenrath.

6.4.2 REBOL Strings

In REBOL, a "string" is simply a series of characters. If you have experience with other programming languages, this can be one of the sticking points in learning REBOL. REBOL's solution is actually a very powerful, easy to learn and consistent with the way other operations work in the language. Proper string management simply requires a good understanding of series. Take a look at the following examples to see how to do a few common operations:

```

the-string: "abcdefghijklmnopqrstuvwxyz"

; Left String: (get the left 7 characters of the string):

copy/part the-string 7

; Right String: (Get the right 7 characters of the string):

copy at tail the-string -7

; Mid String 1: (get 7 characters from the middle of the string,
; starting with the 12th character):

copy/part (at the-string 12) 7

; Mid String 2: (get 7 characters from the middle of the string,
; starting 7 characters back from the letter "m"):

copy/part (find the-string "m") -7

; Mid String 3: (get 7 characters from the middle of the string,
; starting 12 characters back from the letter "t"):

copy/part (skip (find the-string "t") -12) 7

; 3 different ways to get just the 7th character:

the-string/7
pick the-string 7
seventh the-string

; Change "cde" to "123"

replace the-string "cde" "123"

; Several ways to change the 7th character to "7"

```

```

change (at the-string 7) "7"
poke the-string 7 #"7" ; the pound symbol refers to a single character
poke the-string 7 (to-char "7") ; another way to use single characters
print the-string

; Remove 15 characters, starting at the 3rd position:

remove/part (at the-string 3) 15
print the-string

; Insert 15 characters, starting at the 3rd position:

insert (at the-string 3) "cdefghijklmnopq"
print the-string

; Insert 3 instances of "--" at the beginning of the string:

insert/dup head the-string "-- " 3
print the-string

; Replace every instance of "-- " with " ":

replace/all the-string "-- " " "
print the-string

; Remove spaces from a string (type "? trim" to see all its refinements!):

trim the-string
print the-string

; Get every third character from the string:

extract the-string 3

; Get the ASCII value for "c" (ASCII 99):

to-integer third the-string

; Get the character for ASCII 99 ("c"):

to-char 99

; Convert the above character value to a string value:

to-string to-char 99

; Convert any value to a string:

to-string now
to-string $2344.44
to-string to-char 99
to-string system/locale/months

; An even better way to convert values to strings:

form now
form $2344.44
form to-char 99
form system/locale/months ; convert blocks to nicely formed strings

; Convert strings to a block of characters:

the-block: copy []
foreach item the-string [append the-block item]
probe the-block

```

REBOL's series functions are very versatile. Often, you can devise several ways to do the same thing:

```

; Remove the last part of a URL:

the-url: "http://website.com/path"
clear at the-url (index? find/last the-url "/")
print the-url

; Another way to do it:

the-url: "http://website.com/path"
print copy/part the-url (length? the-url)-(length? find/last the-url "/")

```

(Of course, REBOL has a built-in helper function to accomplish the above goal, directly with URLs):

```

the-url: http://website.com/path
print first split-path the-url

```

There are a number of additional functions that can be used to work specifically with string series. Run the following script for an introduction:

```

string-funcs: [
  build-tag checksum clean-path compress debase decode-cgi decompress
  dehex detab dirize enbase entab import-email lowercase mold parse-xml
  reform rejoin remold split-path suffix? uppercase
]
echo %string-help.txt ; "echo" saves console activity to a file
foreach word string-funcs [
  print "_____ ^/"
  print rejoin ["word: " uppercase to-string word] print ""
  do compose [help (to-word word)]
]
echo off
editor at read %string-help.txt 4

```

See <http://www.rebol.com/docs/dictionary.html> and <http://rebol.com/docs/core23/rebolcore-8.html> for more information about the above functions.

6.4.3 Indentation

Blocks often contain other blocks. Such compound blocks are typically indented with consecutive tab stops. *Starting and ending brackets are normally placed at the same indentation level.* This is conventional in most programming languages, because it makes complex code easier to read, by grouping things visually. For example, the compound block below:

```

big-block: [[may june july] [[1 2 3] [[yes no] [monday tuesday friday]]]]

```

can be written as follows to show the beginnings and endings of blocks more clearly:

```

big-block: [
  [may june july]
  [
    [1 2 3]
    [
      [yes no]
      [monday tuesday friday]
    ]
  ]
]
probe first big-block

```

```
probe second big-block
probe first second big-block
probe second second big-block
probe first second second big-block
probe second second second big-block
```

Indentation is not required, but it's very helpful.

6.4.4 More About Why/How Blocks are Useful

IMPORTANT: In REBOL, blocks can contain mixed data of *ANY* type (text and binary items, embedded lists of items (other blocks), variables, etc.):

```
some-items: ["item1" "item2" "item3" "item4"]
an-image: load http://rebol.com/view/bay.jpg
append some-items an-image

; "some-items" now contains 4 text strings, and an image!

; You can save that entire block of data, INCLUDING THE BINARY
; IMAGE data, to your hard drive as a SIMPLE TEXT FILE:

save/all %some-items.txt some-items

; to load it back and use it later:

some-items: load %some-items.txt
view layout [image fifth some-items]
```

Take a moment to examine the example above. REBOL's block structure works in a way that is dramatically easy to use compared to other languages and data management solutions (much more simply than most database systems). It's a very flexible, simple, and powerful way to store data in code! The fact that blocks can hold all types of data using one simple syntactic structure is a fundamental reason it's easier to use than other programming languages and computing tools. You can save/load block code to the hard drive as a simple text file, send it in an email, display it in a GUI, compress it and transfer it to a web server to be downloaded by others, transfer it directly over a point-to-point network connection, or even convert it to XML, encrypt, and store parts of it in a secure multiuser database to be accessed by other programming languages, etc...

Remember, all programming, and computing in general, is essentially about storing, organizing, manipulating, and transferring data of some sort. REBOL makes working with all types of data very easy - *just put any number of pieces of data, of any type, in between two brackets, and that data is automatically searchable, sortable, storable, transferable, and otherwise usable in your programs.*

6.4.5 Evaluating Variables in Blocks: Compose, Reduce, Pick and More

You will often find that you want to refer to an item in a block by its index (position number), as in the earlier 'some-items' example:

```
view layout [image some-items/5]
```

You may not, however, always know the specific index number of the data item you want to access. For example, as you insert data items into a block, the index position of the last item changes (it increases). You can obtain the index number of the last item in a block simply by determining the number of items in the block (the position number of the last item in a block is always the same as the total number of items in the block). In the example below, that index number is assigned the variable word "last-item":

```
last-item: length? some-items
```

Now you can use that variable to pick out the last item:

```
view layout [image (pick some-items last-item)]

; In our earlier example, with 5 items in the block, the
; line above evaluates the same as:

view layout [image (pick some-items 5)]
```

You can refer to other items by adding and subtracting index numbers:

```
alert pick some-items (last-item - 4)
```

There are several other ways to do the exact same thing in REBOL. The "compose" function allows variables in parentheses to be evaluated and inserted as if they'd been typed explicitly into a code block:

```
view layout compose [image some-items/(last-item)]

; The line above appears to the interpreter as if the following
; had been typed:

view layout [image some-items/5]
```

The "compose" function is *very useful* whenever you want to refer to data at variable index positions within a block. The "reduce" function can also be used to produce the same type of evaluation. Function words in a reduced block should begin with the tick (') symbol:

```
view layout reduce ['image some-items/(last-item)]
```

Another way to use variable values explicitly is with the ":" format below. This code evaluates the same as the previous two examples:

```
view layout [image some-items/:last-item]
```

Think of the colon format above as the opposite of setting a variable. As you've seen, the colon symbol placed *after* a variable word *sets* the word to equal some value. A colon symbol placed *before* a variable word *gets* the value assigned to the variable, and inserts that value into the code as if it had been typed explicitly.

You can use the "index?" and "find" functions to determine the index position(s) of any data you're searching for in a block:

```
index-num: index? (find some-items "item4")
```

Any of the previous 4 formats can be used to select the data at the determined variable position:

```
print pick some-items index-num
print compose [some-items/(index-num)]
print reduce [some-items/(index-num)]
; no function words are used in the block above, so no ticks are required
print some-items/:index-num
```

Here's an example that displays variable image data contained in a block, using a foreach loop. The "compose" function is used to include dynamically changeable data (image representations), as if that data had been typed directly into the code:

```

photo1: load http://rebol.com/view/bay.jpg
photo2: load http://rebol.com/view/demos/palms.jpg

; The REBOL interpreter sees the following line as if all the code
; representing the above images had been typed directly in the block:

photo-block: compose [(photo1) (photo2)]

foreach photo photo-block [view layout [image photo]]

```

Block concepts may seem a bit vague at this point. The practical application of block structures will be presented much more thoroughly, by example, throughout this tutorial, and clarification about the usefulness of blocks will come from seeing them in working code. For additional detailed information about using blocks and series functions see <http://www.rebol.com/docs/core23/rebolcore-6.html>.

6.5 Conditions

6.5.1 If

Conditions are used to manage program flow. The most basic conditional evaluation is "if":

```

if (this expression is true) [do this block of code]
; parentheses are not required

```

Math operators are typically used to perform conditional evaluations: = < > <> (equal, less-than, greater-than, not-equal):

```

if now/time > 12:00 [alert "It's after noon."]

```

Here's an example that gets a username and password from the user, tests that data using an "if" evaluation, and alerts the user if the response is correct:

```

userpass: request-pass/title "Type 'username' and 'password'"
if (userpass = ["username" "password"]) [alert "Welcome back!"]

```

6.5.2 Either

"Either" is an if/then/else evaluation that chooses between two blocks to evaluate, based on whether the given condition is true or false. Its syntax is:

```

either (condition) [
    block to perform if the condition is true
][
    block to perform if the condition is false
]

```

For example:

```

either now/time > 8:00am [
    alert "It's time to get up!"
][
    alert "You can keep on sleeping."
]

userpass: request-pass
either userpass = ["username" "password"] [

```



```

    alert "Welcome back!"
  ][
    alert "Incorrect user/password combination!"
  ]

```

6.5.3 Switch

The "switch" evaluation chooses between numerous functions to perform, based on multiple evaluations. Its syntax is:

```

switch/default (main value) [
  (value 1) [block to execute if value 1 = main value
  (value 2) [block to execute if value 2 = main value]
  (value 3) [block to execute if value 3 = main value]
  ; etc...
] [default block of code to execute if none of the values match]

```

You can compare as many values as you want against the main value, and run a block of code for each matching value:

```

favorite-day: request-text/title "What's your favorite day of the week?"

switch/default favorite-day [
  "Monday"    [alert "Monday is the worst! The work week begins..."]
  "Tuesday"   [alert "Tuesdays and Thursdays are both ok, I guess..."]
  "Wednesday" [alert "The hump day - the week is halfway over!"]
  "Thursday"  [alert "Tuesdays and Thursdays are both ok, I guess..."]
  "Friday"    [alert "Yay! TGIF!"]
  "Saturday"  [alert "Of course, the weekend!"]
  "Sunday"    [alert "Of course, the weekend!"]
] [alert "You didn't type in the name of a day!"]

```

6.5.4 Case

You can choose between *multiple evaluations* of any complexity using the "case" structure. If none of the cases evaluate to true, you can use any true value to trigger a default evaluation:

```

name: "john"
case [
  find name "a" [print {Your name contains the letter "a"}]
  find name "e" [print {Your name contains the letter "e"}]
  find name "i" [print {Your name contains the letter "i"}]
  find name "o" [print {Your name contains the letter "o"}]
  find name "u" [print {Your name contains the letter "u"}]
  true [print {Your name doesn't contain any vowels!}]
]

for i 1 100 1 [
  case [
    (0 = modulo i 3) and (0 = modulo i 5) [print "fizzbuzz"]
    0 = modulo i 3 [print "fizz"]
    0 = modulo i 5 [print "buzz"]
    true [print i]
  ]
]

```

By default, the case evaluation automatically exits once a true evaluation is found (i.e., in the name example above, if the name contains more than one vowel, only the first vowel will be printed). To check all possible cases before ending the evaluation, use the /all refinement:

```

name: "brian"

```

```

found: false
case/all [
  find name "a" [print {Your name contains the letter "a"} found: true]
  find name "e" [print {Your name contains the letter "e"} found: true]
  find name "i" [print {Your name contains the letter "i"} found: true]
  find name "o" [print {Your name contains the letter "o"} found: true]
  find name "u" [print {Your name contains the letter "u"} found: true]
  found = false [print {Your name doesn't contain any vowels!}]
]

```

6.5.5 Multiple Conditions: "and", "or", "all", "any"

You can check for more than one condition to be true, using the "and", "or", "all", and "any" words:

```

; first set some initial values all to be true:

value1: value2: value3: true

; then set some additional values all to be false:

value4: value5: value6: false

; The following prints "both true", because both the first
; condition AND the second condition are true:

either ( (value1 = true) and (value2 = true) ) [
  print "both true"
] [
  print "not both true"
]

; The following prints "both not true", because the second
; condition is false:

either ( (value1 = true) and (value4 = true) ) [
  print "both true"
] [
  print "not both true"
]

; The following prints "either one OR the other is true"
; because the first condition is true:

either ( (value1 = true) or (value4 = true) ) [
  print "either one OR the other is true"
] [
  print "neither is true"
]

; The following prints "either one OR the other is true"
; because the second condition is true:

either ( (value4 = true) or (value1 = true) ) [
  print "either one OR the other is true"
] [
  print "neither is true"
]

; The following prints "either one OR the other is true"
; because both conditions are true:

either ( (value1 = true) or (value4 = true) ) [
  print "either one OR the other is true"
] [
  print "neither is true"
]

; The following prints "neither is true":

```

```
either ( (value4 = true) or (value5 = true) ) [
  print "either one OR the other is true"
] [
  print "neither is true"
]
```

For comparisons involving more items, you can use "any" and "all":

```
; The following lines both print "yes", because ALL comparisons are true.
; "All" is just shorthand for the multiple "and" evaluations:

if ((value1 = true) and (value2 = true) and (value3 = true)) [
  print "yes"
]

if all [value1 = true value2 = true value3 = true] [
  print "yes"
]

; The following lines both print "yes" because ANY ONE of the comparisons
; is true. "Any" is just shorthand for the multiple "or" evaluations:

if ((value1 = true) or (value4 = true) or (value5 = true)) [
  print "yes"
]

if any [value1 = true value4 = true value5 = true] [
  print "yes"
]
```

6.6 Loops

6.6.1 Forever

"Loop" structures provide programmatic ways to methodically repeat actions, manage program flow, and automate lengthy data processing activities. The "forever" function creates a simple repeating loop. Its syntax is:

```
forever [block of actions to repeat]
```

The following code uses a forever loop to continually check the time. It alerts the user when 60 seconds has passed. *Notice the "break" function, used to stop the loop:*

```
alarm-time: now/time + :00:60
forever [if now/time = alarm-time [alert "1 minute has passed" break]]
```

Here's a more interactive version using some info provided by the user. Notice how the forever loop, if evaluation, and alert arguments are indented to clarify the grouping of related parameters:

```
event-name: request-text/title "What do you want to be reminded of?"
seconds: to-integer request-text/title "Seconds to wait?"
alert rejoin [
  "It's now " now/time ", and you'll be alerted in "
  seconds " seconds."
]
alarm-time: now/time + seconds
forever [
  if now/time = alarm-time [
    alert rejoin [
      "It's now " alarm-time ", and " seconds
```

```

        " seconds have passed.  It's time for: " event-name
    ]
    break
]

```

Here's a forever loop that displays/updates the current time in a GUI:

```

view layout [
    timer: field
    button "Start" [
        forever [
            set-face timer now/time
            wait 1
        ]
    ]
]

```

6.6.2 Loop

The "loop" function allows you to repeatedly evaluate a block of code, a specified number of times:

```

loop 50 [print "REBOL is great!"]

```

6.6.3 Repeat

Like "loop", the "repeat" function allows you to repeatedly evaluate a block of code, a specified number of times. It *additionally* allows you to specify a counter variable which is automatically incremented each time through the loop:

```

repeat count 50 [print rejoin ["This is loop #: " count]]

```

The above code does the same thing as:

```

count: 0
loop 50 [
    count: count + 1
    print rejoin ["This is loop #: " count]
]

```

6.6.4 For

"For" loops allow you to control repetition patterns that involve consecutively changing values. You specify a start value, end value, incremental value, and a variable name to hold the current value during the loop. Here's the "for" loop syntax:

for {variable word to hold current value} {starting value} {ending value} {incremental value} [block of code to perform, which can use the current variable value]

For example:

```

for counter 1 10 1 [print counter]
; starts on 1 and counts to 10 by increments of 1

for counter 10 1 -1 [print counter]
; starts on 10 and counts backwards to 1 by increments of -1

```

```

for counter 10 100 10 [print counter]
; starts on 10 and counts to 100 by increments of 10

for counter 1 5 .5 [print counter]
; starts on 1 and counts to 5 by increments of .5

for timer 8:00 9:00 0:05 [print timer]
; starts at 8:00am and counts to 9:00am by increments of 5 minutes

for dimes $0.00 $1.00 $0.10 [print dimes]
; starts at 0 cents and counts to 1 dollar by increments of a dime

for date 1-dec-2005 25-jan-2006 8 [print date]
; starts at December 12, 2005 and counts to January 25, 2006
; and by increments of 8 days

for alphabet #"a" #"z" 1 [print alphabet]
; starts at the character a and counts to z by increments of 1 letter

```

Notice that REBOL properly increments dates, money, time, etc.

This "for" loop displays the first 5 file names in the current folder on your hard drive:

```

files: read %.
for count 1 5 1 compose [print files/(count)]

```

Notice the "compose" word used in the for loop. "files/1" represents the first item in the file list, "files/2" represents the second, and so on. The first time through the loop, the code reads as if [print files/1] had been typed in manually, etc.

The following "for" loop displays all the files in the current folder:

```

files: read %.
filecount: length? files
for count 1 filecount 1 compose [print files/(count)]

```

6.6.5 Foreach (very important!)

The "foreach" function lets you easily loop through a block of data. Its syntax is:

foreach {variable name referring to each consecutive item in the given block} [given block] [block of functions to be executed upon each item in the given block, using the variable name to refer to each successive item]

This example prints the name of every file in the current directory on your hard drive:

```

folder: read %.
foreach file folder [print file]

```

This line reads and prints each successive message in a user's email box:

```

foreach mail (read pop://user:pass@website.com) [print mail]

```

Here's a slightly more complex foreach example:

```

; define a block of text items:

```

```

some-names: ["John" "Bill" "Tom" "Mike"]

; define a variable used to count items in the block:

count: 0

; go through each item in the block:

foreach name some-names [

    ; increase the counter variable by 1, for each item:

    count: count + 1

    ; print the count number, and the associated text item:

    print rejoin ["Item " count ": " name]

]

```

Here's an example in which an empty block is created and data is appended using a foreach loop. The data is then converted to a text string and displayed in a GUI:

```

; define a block of text items:

some-names: ["John" "Bill" "Tom" "Mike"]

; create another new, empty block:

data-block: copy []

; define a variable used to count items in the block:

count: 0

; go through each item in the block:

foreach name some-names [

    ; increase the counter variable by 1, for each item:

    count: count + 1

    ; for each item, add some rejoined text to the originally empty block:

    append data-block rejoin ["Item " count ": " name newline]

]

; convert the newly created block to a string, and show it in a
; GUI text area widget:

view layout [area (to-string data-block)]

```

You can select multiple values from a block during each iteration of a foreach loop, using the following format:

```

users: [
    "John Smith" "123 Tomline Lane Forest Hills, NJ" "555-1234"
    "Paul Thompson" "234 Georgetown Pl. Peanut Grove, AL" "555-2345"
    "Jim Persee" "345 Pickles Pike Orange Grove, FL" "555-3456"
    "George Jones" "456 Topforge Court Mountain Creek, CO" ""
    "Tim Paulson" "" "555-5678"
]

; Use the following format to get 3 consecutive values from the above
; block, each time through the loop:

```

```

foreach [name address phone] users [
  print rejoin [
    "^/Name:      " name          ; gets 1 value from the block
    "^/Address:   " address       ; gets the next value from the block
    "^/Phone:     " phone         ; gets a third value from the block
  ]
]

```

You will use the foreach function *very often* in REBOL code. It will be demonstrated many times, by example, throughout this tutorial.

6.6.6 Forall and Forskip

"Forall" loops through a block, incrementing the marked index number of the series as it loops through:

```

some-names: ["John" "Bill" "Tom" "Mike"]

foreach name some-names [print index? some-names] ; index doesn't change
forall some-names [print index? some-names] ; index changes

foreach name some-names [print name]
forall some-names [print first some-names] ; same effect as line above

```

"Forskip" works like forall, but skips through the block, jumping a periodic number of elements on each loop:

```

some-names: ["John" "Bill" "Tom" "Mike"]
forskip some-names 2 [print first some-names]

```

6.6.7 While and Until

The "while" function repeatedly evaluates a block of code while the given condition is true. While loops are formatted as follows:

```

while [condition] [
  block of functions to be executed while the condition is true
]

```

This example counts to 5:

```

x: 1 ; create an initial counter value
while [x <= 5] [
  alert to-string x
  x: x + 1
]

```

In English, that code reads:

```

"x" initially equals 1.
While x is less than or equal to 5, display the value of x,
then add 1 to the value of x and repeat.

```

Some additional "while" loop examples:

```

while [not request "End the program now?"] [
  alert "Select YES to end the program."
]

```

```

]
; "not" reverses the value of data received from
; the user (i.e., yes becomes no and visa versa)

alert "Please select today's date"
while [request-date <> now/date] [
    alert rejoin ["Please select TODAY's date. It's " now/date]
]

while [request-pass <> ["username" "password"]] [
    alert "The username is 'username' and the password is 'password'"
]

```

"Until" loops are similar to "while" loops. They do everything in a given block, repeatedly, *until* the last expression in the block evaluates to true:

```

x: 10
until [
    print rejoin ["Counting down: " x]
    x: x - 1
    x = 0
]

```

The example below uses several loops to alert the user to feed the cat, every 6 hours between 8am and 8pm. It uses a for loop to increment the times to be alerted, a while loop to continually compare the incremented times with the current time, and a forever loop to do the same thing every day, continuously. Notice the indentation:

```

forever [
    for timer 8:00am 8:00pm 6:00 [
        while [now/time <= timer] [wait :00:01]
        alert rejoin ["It's now " now/time ". Time to feed the cat."]
    ]
]

```

6.7 User Defined Functions and Imported Code

REBOL's built-in functions satisfy many fundamental needs. To achieve more complex or specific computations, you can create your own function definitions.

Data and function words contained in blocks can be evaluated (their actions performed and their data values assigned) using the "do" word. **Because of this, any block of code can essentially be treated as a function.** That's a powerful key element of the REBOL language design:

```

some-actions: [
    alert "Here is one action."
    print "Here's a second action."
    write %/c/anotheraction.txt "Here's a third action."
]

do some-actions

```

New function words can also be defined using the "does" and "func" words. "Does" is included directly after a word label definition, and forces a block to be evaluated every time the word is encountered:

```

more-actions: does [
    alert "4"
    alert "5"
    alert "6"
]

```



```
; now to use that function, just type the word label:
more-actions
```

Here's a useful function to clear the command line screen in the REBOL interpreter.

```
cls: does [prin "^(1B)[J"]
cls
```

The "func" word creates an executable block in the same way as "does", but additionally allows you to pass your own specified parameters to the newly defined function word. The first block in a func definition contains the name(s) of the variable(s) to be passed. The second block contains the actions to be taken. Here's the "func" syntax:

```
func [names of variable(s) to be passed] [
    actions to be taken with those variables
]
```

This function definition:

```
sqr-add-var: func [num1 num2] [print square-root (num1 + num2)]
```

Can be used as follows. *Notice that no brackets, braces, or parentheses are required to contain the data arguments.* Data parameters simply follow the function word, on the same line of code:

```
sqr-add-var 12 4      ; prints "4", the square root of 12 + 4 (16)
sqr-add-var 96 48     ; prints "12", the square root of 96 + 48 (144)
```

Here's a simple function to display images:

```
display: func [filename] [view layout [image load to-file filename]]
display (request-file)
```

By default, the last value evaluated by a function is returned when the function is complete:

```
concatenate: func [string1 string2] [join string1 string2]

string3: concatenate "Hello " "there."
print string3
```

By default, values used inside functions are treated as *global*, which means that if any variables are changed inside a function, they will be changed throughout the rest of your program:

```
x: 10

change-x-globally: func [y z] [x: y + z]

change-x-globally 10 20
print x
```

You can change this default behavior, and specify that any value be treated as *local* to the function (not changed throughout the rest of your program), by using the `/local` refinement:

```
x: 10

change-x-locally: func [y z /local x] [x: y + z]

change-x-locally 10 20      ; inside the function, x is now 30
print x                     ; outside the function, x is still 10
```

You can specify refinements to the way a function operates, simply by preceding optional operation arguments with a forward slash ("`/`"):

```
compute: func [x y /multiply /divide /subtract] [
  if multiply [return x * y]
  if divide   [return x / y]
  if subtract [return x - y]
  return x + y
]

compute/multiply 10 20
compute/divide 10 20
compute/subtract 10 20
compute 10 20
```

The `"help"` function provides usage information for any function, including user defined functions:

```
help for
help compute
```

You can include documentation for any user defined function by including a text string as the first item in it's argument list. This text is included in the description displayed by the help function:

```
doc-demo: func ["This function demonstrates doc strings"] [help doc-demo]
doc-demo
```

Acceptable data types for any parameter can be listed in a block, and doc strings can also be included immediately after any parameter:

```
concatenate-string-or-num: func [
  "This function will only concatenate strings or integers."
  val1 [string! integer!] "First string or integer"
  val2 [string! integer!] "Second string or integer"
] [
  join val1 val2
]

help concatenate-string-or-num
concatenate-string-or-num "Hello " "there." ; this works correctly
concatenate-string-or-num 10 20             ; this works correctly
concatenate-string-or-num 10.1 20.3         ; this creates an error
```

6.7.1 Importing Code

You can `"do"` a module of code contained in any text file, *as long as it contains the minimum header `"REBOL []"`* (this includes HTML files and any other files that can be read via REBOL's built-in protocols). For example, if you save the previous functions in a text file called `"myfunctions.r"`:

```
REBOL [] ; THIS HEADER TEXT MUST BE INCLUDED AT THE TOP OF ANY REBOL FILE

sqr-add-var: func [num1 num2] [print square-root (num1 + num2)]
display: func [filename] [view layout [image load filename]]
cls: does [prin "^(1B)[J"]
```

You can import and use them in your current code, as follows:

```
do %myfunctions.r

; now you can use those functions just as you would any other
; native function:

sqr-add-var
display
cls
```

Here's an example function that plays a .wave sound file. Save this code as C:\play_sound.r:

```
REBOL [title: "play-sound"] ; you can add a title to the header

play-sound: func [sound-file] [
    wait 0
    ring: load sound-file
    sound-port: open sound://
    insert sound-port ring
    wait sound-port
    close sound-port
]
```

Then run the code below to import the function and play selected .wav files:

```
do %/c/play_sound.r

play-sound %/C/WINDOWS/Media/chimes.wav
play-sound to-file request-file/file %/C/WINDOWS/Media/tada.wav
```

Imported files can contain data definitions and any other executable code, including that which is contained in additional nested source files imported with the "do" function. Any code or data contained in a source file is evaluated when the file is "do"ne.

6.8 Quick Review and Synopsis

The list below summarizes some key characteristics of the REBOL language. Knowing how to put these elements to use constitutes a fundamental understanding of how REBOL works:

1. To start off, REBOL has hundreds of built-in function words that perform common tasks. As in other languages, function words are typically followed by passed parameters. Unlike other languages, passed parameters are placed immediately after the function word and are *not* necessarily enclosed in parenthesis. To accomplish a desired goal, functions are arranged in succession, one after another. The value(s) returned by one function are often used as the argument(s) input to another function. Line terminators are not required at any point, and all expressions are evaluated in left to right order, then vertically down through the code. Empty white space (spaces, tabs, newlines, etc.) can be inserted as desired to make code more readable. Text after a semicolon and before a new line is treated as a comment. You can complete significant work by simply knowing the predefined functions in the language, and organizing them into a useful order.
2. REBOL contains a rich set of conditional and looping structures, which can be used to manage program flow and data processing activities. If, switch, while, for, foreach, and other typical structures are supported.
3. Because many common types of data values are automatically recognized and handled natively by REBOL, calculating, looping, and making conditional decisions based upon data content is

straightforward and natural to perform, without any external modules or toolkits. Numbers, text strings, money values, times, tuples, URLs, binary representations of images, sounds, etc. are all automatically handled. REBOL can increment, compare, and perform proper computations on most common types of data (i.e., the interpreter automatically knows that 5:32am + 00:35:15 = 6:07:15am, and it can automatically apply visual effects to raw binary image data, etc.). Network resources and Internet protocols (http documents, ftp directories, email accounts, dns services, etc.) can also be accessed natively, just as easily as local files. Data of any type can be written to and read from virtually any connected device or resource (i.e., "write %file.txt data" works just as easily as "write ftp://user:pass@website.com data", using the same common syntax). The percent symbol ("%") and the syntax "%(//drive)/path/path/.../file.ext" are used cross-platform to refer to local file values on any operating system.

4. Any data or code can be assigned a word label. The colon character (":") is used to assign word labels to constants, variable values, evaluated expressions, functions, and data/action blocks of any type. Once assigned, variable words can be used to represent all of the data and/or actions contained in the given expression, block, etc. Just put a colon at the end of a word, and thereafter it represents all the following actions and/or data. That forms a significant part of the REBOL language structure, and is the basis for its flexible natural language dialecting abilities.
5. Multiple pieces of data are stored in "blocks", which are delineated by starting and ending brackets ("[]"). Blocks can contain data of *any* type: groups of text strings, arrays of binary data, collections of actions (functions), other enclosed blocks, etc. Data items contained in blocks are separated by white space. Blocks can be automatically treated as lists of data, called "series", and manipulated using built-in functions that enable searching, sorting, ordering, and otherwise organizing the blocked data. Data and function words contained in blocks can be evaluated (their actions performed and their data values assigned) using the "do" word. New function words can also be defined using the "does" and "func" words. "Does" forces a block to be evaluated every time its word label is encountered. The "func" word creates an executable block in the same way as "does", but additionally allows you to pass your own specified parameters to the newly defined function word. You can "do" a module of code contained in a text file, as long as it contains the minimum header "rebol[]". Blocks are also used to delineate most of the syntactic structures in REBOL (i.e., in conditional evaluations, function definitions, etc.).
6. The syntax "view layout [block]" is used to create basic GUI layouts. You can add graphic widgets to the layout simply by adding widget identifier words to the enclosed block: "button", "field", "text-list", etc. Color, position, spacing, and other facet words can be added after each widget identifier. Action blocks added immediately after any widget will perform the enclosed functions whenever the widget is activated (i.e., when the widget is clicked with a mouse, when the enter key pressed, etc.). Path refinements can be used to refer to items in the GUI layout (i.e., "face/offset" refers to the position of the selected widget face). Those simple guidelines can be used to create useful GUIs for data input and output, in a way that's native (doesn't require any external toolkits) and much easier than any other language.

6.9 A Telling Comparison

To provide a quick idea of how much easier REBOL is than other languages, here's a short example. The following code to create a basic program window with REBOL was presented earlier:

```
view layout [size 400x300]
```

It works on every type of computer, in exactly the same way.

Code for the same simple example is presented below in the popular programming language "C++". It does the exact same thing as the REBOL one-liner above, except it only works in Microsoft Windows. If you want to do the same thing on a Macintosh computer, you need to memorize a completely different page of C++ code. The same is true for Unix, Linux, Beos, or any other operating system. You have to learn enormous chunks of code to do very simple things, and those chunks of code are different for every type of computer. Furthermore, you typically need to spend a semester's worth of time learning very basic things about coding format and fundamentals about how a computer 'thinks' before you even begin to tackle useful basics like the code below:

```
#include <windows.h>

/* Declare Windows procedure */
LRESULT CALLBACK WindowProcedure (HWND, UINT, WPARAM, LPARAM);

/* Make the class name into a global variable */
char szClassName[ ] = "C_Example";

int WINAPI
```

```

WinMain (HINSTANCE hThisInstance,
         HINSTANCE hPrevInstance,
         LPSTR lpszArgument,
         int nFunsterStil)

{
    HWND hwnd;
    /* This is the handle for our window */
    MSG messages;
    /* Here messages to the application are saved */
    WNDCLASSEX wincl;
    /* Data structure for the windowclass */

    /* The Window structure */
    wincl.hInstance = hThisInstance;
    wincl.lpszClassName = szClassName;
    wincl.lpfnWndProc = WindowProcedure;
    /* This function is called by windows */
    wincl.style = CS_DBLCLKS;
    /* Catch double-clicks */
    wincl.cbSize = sizeof (WNDCLASSEX);

    /* Use default icon and mouse-pointer */
    wincl.hIcon = LoadIcon (NULL, IDI_APPLICATION);
    wincl.hIconSm = LoadIcon (NULL, IDI_APPLICATION);
    wincl.hCursor = LoadCursor (NULL, IDC_ARROW);
    wincl.lpszMenuName = NULL;
    /* No menu */
    wincl.cbClsExtra = 0;
    /* No extra bytes after the window class */
    wincl.cbWndExtra = 0;
    /* structure of the window instance */
    /* Use Windows's default color as window background */
    wincl.hbrBackground = (HBRUSH) COLOR_BACKGROUND;

    /* Register window class. If it fails quit the program */
    if (!RegisterClassEx (&wincl))
        return 0;

    /* The class is registered, let's create the program */
    hwnd = CreateWindowEx (
        0,
        /* Extended possibilities for variation */
        szClassName,
        /* Classname */
        "C_Example",
        /* Title Text */
        WS_OVERLAPPEDWINDOW,
        /* default window */
        CW_USEDEFAULT,
        /* Windows decides the position */
        CW_USEDEFAULT,
        /* where the window ends up on the screen */
        400,
        /* The programs width */
        300,
        /* and height in pixels */
        HWND_DESKTOP,
        /* The window is a child-window to desktop */
        NULL,
        /* No menu */
        hThisInstance,
        /* Program Instance handler */
        NULL
        /* No Window Creation data */
    );

    /* Make the window visible on the screen */
    ShowWindow (hwnd, nFunsterStil);

    /* Run the message loop.
       It will run until GetMessage() returns 0 */

```

```

while (GetMessage (&messages, NULL, 0, 0))
{
    /* Translate virtual-key messages
       into character messages */
    TranslateMessage(&messages);
    /* Send message to WindowProcedure */
    DispatchMessage(&messages);
}

/* The program return-value is 0 -
   The value that PostQuitMessage() gave */
return messages.wParam;
}

/* This function is called by the Windows
   function DispatchMessage() */

LRESULT CALLBACK
WindowProcedure (HWND hwnd, UINT message,
                WPARAM wParam, LPARAM lParam)
{
    switch (message)
    /* handle the messages */
    {
        case WM_DESTROY:
            PostQuitMessage (0);
            /* send a WM_QUIT to the message queue */
            break;
        default:
            /* for messages that we don't deal with */
            return DefWindowProc (hwnd, message,
                                wParam, lParam);
    }

    return 0;
}

```

Yuck. Back to REBOL...

7. More Essential Topics

7.1 Built-In Help and Online Resources

The "help" function displays required syntax for any REBOL function:

```
help print
```

"?" is a synonym for "help":

```
? print
```

The "what" function lists all built-in words:

```
what
```

Together, those two words provide a built-in reference guide for the entire core REBOL language. Here's a script that saves all the above documentation to a file. Give it a few seconds to run:

```
echo %words.txt what echo off    ; "echo" saves console activity to a file
echo %help.txt
```

```

foreach line read/lines %words.txt [
  word: first to-block line
  print "_____ ^/"
  print rejoin ["word: " uppercase to-string word] print ""
  do compose [help (to-word word)]
]
echo off
editor at read %help.txt 4

```

You can use help to search for defined words and values, when you can't remember the exact spelling of the word. Just type a portion of the word (hitting the *tab* key will also show a list of words for automatic *word completion*):

```

? to-          ; shows a list of all built-in type conversions
? reques       ; shows a list of built-in requester functions
? "load"       ; shows all words containing the characters "load"
? "?"          ; shows all words containing the character "?"

```

Here are some more examples of ways to search for useful info using help:

```

? datatype!    ; shows a list of built-in data types
? function!    ; shows a list of built-in functions
? native!      ; shows a list of native (compiled C code) functions
? char!        ; shows a list of built-in control characters
? tuple!       ; shows a list of built-in colors (RGB tuples)
? .gif         ; shows a list of built-in .gif images

```

You can view the *source code* for built-in "mezzanine" (non-native) functions with the "source" function. There is a *huge volume* of REBOL code accessible right in the interpreter, and all of the mezzanine functions were created by the language's designer, Carl Sassenrath. Studying mezzanine source is a great way to learn more about advanced REBOL code patterns:

```

source help
source request-text
source view
source layout
source ctx-viewtop ; try this: view layout [image load ctx-viewtop/13]

```

7.1.1 The REBOL System Object, and Help with GUI Widgets

"Help system" displays the contents of the REBOL system object, which contains many important settings and values. You can explore each level of the system object using path notation, like this:

```

? system/console/history ; the current console session history
? system/options
? system/locale/months
? system/network/host-address

```

You can find info about all of REBOL's GUI components in "system/view/VID":

```

? system/view/VID

```

The system/view/VID block is so important, REBOL has a built-in short cut to refer to it:

```
? svv
```

You'll find a list of REBOL's GUI widgets in "svv/vid-styles". Use REBOL's "editor" function to view large system sections like this:

```
editor svv/vid-styles
```

Here's a script that neatly displays all the words in the above "svv/vid-styles" block:

```
foreach i svv/vid-styles [if (type? i) = word! [print i]]
```

Here's a more concise way to display the above widgets, using the ["extract"](#) function:

```
probe extract svv/vid-styles 2
```

This script lets you browse the object structure of each widget:

```
view layout [
  text-list data (extract svv/vid-styles 2) [
    a/text: select svv/vid-styles value
    show a focus a
  ]
  a: area 500x250
]
```

REBOL's GUI layout words are available in "svv/vid-words":

```
? svv/vid-words
```

The following script displays all the images in the svv/image-stock block:

```
b: copy []
foreach i svv/image-stock [if (type? i) = image! [append b i]]
v: copy [] foreach i b [append v reduce ['image i]]
view layout v
```

The changeable attributes ("facets") available to all GUI widgets are listed in "svv/facet-words":

```
editor svv/facet-words
```

Here's a script that neatly displays all the above facet words:

```
b: copy []
foreach i svv/facet-words [if (not function? :i) [append b to-string i]]
view layout [text-list data b]
```

Some GUI widgets have additional facet words available. The following script displays all such functions, and their extra attributes:


```

foreach i (extract svv/vid-styles 2) [
  x: select svv/vid-styles i
  ; additional facets are held in a "words" block:
  if x/words [
    prin join i ": "
    foreach q x/words [
      if not (function? :q) [prin join q " "]
    ]
    print ""
  ]
]

```

To examine the function(s) that handle any of the additional facets for the widgets above, type the path to the widget's "words" block, i.e.:

```
svv/vid-styles/TEXT-LIST/words
```

For more information on system/view/VID, see <http://www.mail-archive.com/rebol-bounce@rebol.com/msg01898.html> and <http://www.rebol.org/ml-display-message.r?m=rmlHJNC>.

It's important to note that you can SET any system value. Just use a colon, like when assigning variable values:

```
system/user/email: user@website.com
```

Familiarity with the system object yields many useful tools.

7.1.2 Viewtop Resources

The REBOL desktop that appears by default when you run the view.exe interpreter can be used as a gateway into a world of "Rebsites" that developers use to share useful code. Surfing the public rebsites is a great way to explore the language more deeply. All of the code in the rebol.org archive, and much more, is available on the rebsites. When typing at the interpreter console, the "desktop" function brings up the REBOL desktop (also called the "Viewtop"):

```
desktop
```

Click the "REBOL" or "Public" folders to see hundreds of interesting demos and useful examples. Source code for every example is available by right-clicking individual program icons and selecting "edit". You don't need a web browser or any other software to view the contents of Rebsites - the Viewtop and all its features are part of the REBOL executable. You can learn volumes about the REBOL language using *only* the resources built directly into the 600k interpreter!

For detailed, categorized, and cross-referenced information about built-in functions, see the REBOL Dictionary website, found in the REBOL desktop folder REBOL->Tools (an HTML version is also available at <http://www.rebol.com/docs/dictionary.html>).

7.1.3 Online Documentation, The Mailing List and The AltME Community Forum

If you can't find answers to your REBOL programming questions using built-in help and resources, the first place to look is <http://rebol.com/docs.html>. Googling online documentation also tends to provide quick results, since the word "REBOL" is uncommon.

To ask a question directly of other REBOL developers, you can join the community mailing list by sending an email to rebol-request@rebol.com, with the word "subscribe" in the subject line. Use your normal email program, or just paste the following code into your REBOL interpreter (be sure your email account settings are set up correctly in REBOL):

```
send rebol-request@rebol.com "subscribe"
```

You can also ask questions of numerous gurus and regular users in [AltME](#), a messaging program which makes up the most active forum of REBOL users around the world. [Rebol.org](#) maintains a searchable history of several hundred thousand posts from both the mailing list and AltME, along with a rich script archive. The REBOL user community is friendly, knowledgeable and helpful, and you will typically find answers to just about any question already in the archives. Unlike other programming communities, *REBOL does not have a popular web based support forum*. AltME is the primary way that REBOL developers interact. If you want to speak with others, you must [download the AltME program](#) and set up a user account (it's fast and easy to do). Just follow the instructions at <http://www.rebol.org/aga-join.r>.

7.2 Saving and Running REBOL Scripts

So far in this tutorial, you've been typing or copying/pasting code snippets directly into the REBOL interpreter. As you begin to work with longer examples and full programs, you'll need to save your scripts for later execution. *Whenever you save a REBOL program to a text file, the code must begin with the following bit of header text:*

```
REBOL [ ]
```

That header tells the REBOL interpreter that the file contains a valid REBOL program. You can optionally document any information about the program in the header block. The "title" variable in the header block is displayed in the title bar of GUI program windows:

```
REBOL [
  title: "My Program"
  author: "Nick Antonaccio"
  date: 29-sep-2009
]
view layout [text 400 center "Look at the title bar."]
```

The code below is a web cam video viewer program. Type in or copy/paste the complete code source below into a text editor such as Windows Notepad or REBOL's built-in text editor (type "editor none" at the REBOL console prompt). Save the text as a file called "webcam.r" on your C:\ drive.

```
REBOL [title: "Webcam Viewer"]

; try http://www.webcam-index.com/USA/ for more webcam links.

temp-url: "http://209.165.153.2/axis-cgi/jpg/image.cgi"
while [true] [
  webcam-url: to-url request-text/title/default "Web cam URL:" temp-url
  either attempt [webcam: load webcam-url] [
    break
  ] [
    either request [
      "That webcam is not currently available." "Try Again" "Quit"
    ] [
      temp-url: to-string webcam-url
    ] [
      quit
    ]
  ]
]
resize-screen: func [size] [
  webcam/size: to-pair size
  window/size: (to-pair size) + 40x72
  show window
]
window: layout [
  across
  btn "Stop" [webcam/rate: none show webcam]
```

```

    btn "Start" [
        webcam/rate: 0
        webcam/image: load webcam-url
        show webcam
    ]
    rotary "320x240" "640x480" "160x120" [
        resize-screen to-pair value
    ]
    btn "Exit" [quit] return
    webcam: image load webcam-url 320x240
    with [
        rate: 0
        feel/engage: func [face action event][
            switch action [
                time [face/image: load webcam-url show face]
            ]
        ]
    ]
]
view center-face window

```

Once you've saved the webcam.r program to C:\, you can run it in any one of the following ways:

1. **If you've already installed REBOL on your computer, just double-click your saved ".r" script file** (find the C:\webcam.r file icon in your file explorer (click My Computer -> C: -> webcam.r)). By default, during REBOL's initial installation, all files with a ".r" extension are associated with the interpreter. They can be clicked and run *as if they're executable programs, just like ".exe" files*. The REBOL interpreter automatically opens and executes any selected ".r" text file. This is the most common way to run REBOL scripts, and it works the same way on all major graphic operating systems. If you want other people to be able to run your scripts, just have them download and install the tiny REBOL interpreter - it only takes a few seconds.
2. Use the built-in editor in REBOL. Type "editor %c/webcam.r" at the interpreter prompt, or type "editor none" and copy/paste the script into the editor. *Pressing F5 in the editor will automatically save and run the script*. This is a convenient way to work with scripts, and enables REBOL to be its own simple, self contained IDE.
3. Type "do %c/webcam.r" into the REBOL interpreter.
4. Scripts can be run at the command line. In Windows, copy rebol.exe and webcam.r to the same folder (C:\), then click Start -> Run, and type "C:\rebol.exe C:\webcam.r" (or open a DOS box and type the same thing). Those commands will start the REBOL interpreter and do the webcam.r code. You can also create a text file called webcam.bat, containing the text "C:\rebol.exe C:\webcam.r" . Click on the webcam.bat file in Windows, and it'll run those commands. In Unix, you can also run scripts at scheduled times with Cron. Just enter the path to the script.
5. Use a program such as [XpackerX](#) to package and distribute the program. XpackerX allows you to wrap the REBOL interpreter and webcam.r program into a single executable file that has a clickable icon, and automatically runs both files. That allows you to create a single file executable Windows program that can be distributed and run like any other application. Just click it and run... (this technique is covered in the next section).
6. Buy the commercial "SDK" version of REBOL, which provides the most secure method of packaging REBOL applications.

VERY IMPORTANT: To turn off the default security requester that continually asks permission to read/write the hard drive, type "secure none" in the REBOL interpreter, and then run the program with "do {filename}". Running "C:\rebol.exe -s {filename}" does the same thing . The "-s" launches the REBOL interpreter without any security features turned on, making it behave like a typical Windows program.

7.3 "Compiling" REBOL Programs - Distributing Packaged .EXE Files

The REBOL.exe interpreter is tiny and does not require any installation to operate properly. By packaging it, your REBOL script(s), and any supporting data file(s) into a single executable with an icon of your choice, [XpackerX](#) works like a REBOL 'compiler' that produces regular Windows programs that look and act just like those created by other compiled languages. To do that, you'll need to create a text file in the following format (save it as "template.xml"):

```

<?xml version="1.0"?>
<xpackerdefinition>
  <general>
    <!--shown in taskbar -->
    <appname>your_program_name</appname>
  </general>
</xpackerdefinition>

```

```

    <exepath>your_program_name.exe</exepath>
    <showextractioninfo>>false</showextractioninfo>
    <!-- <iconpath>c:\icon.ico</iconpath> -->
</general>
<files>
  <file>
    <source>your_rebol_script.r</source>
    <destination>your_rebol_script.r</destination>
  </file>
  <file>
    <source>C:\Program Files\rebol\view\Rebol.exe</source>
    <destination>rebol.exe</destination>
  </file>
  <!--put any other data files here -->
</files>
<!-- $FINDEXE, $TMPRUN, $WINDIR, $PROGRAMDIR, $WINSYSDIR -->
<onrun>$TMPRUN\rebol.exe -si $TMPRUN\your_rebol_script.r</onrun>
</xpackerdefinition>

```

Just download the free XpackerX program and alter the above template so that it contains the filenames you've given to your script(s) and file(s), and the correct path to your REBOL interpreter. Run XpackerX, and it'll spit out a beautifully packaged .exe file that requires no installation. Your users do *not* need to have REBOL installed to run this type of executable. To them it appears and runs just like any other native compiled Windows program. What actually happens is that every time your packaged .exe file runs, the REBOL interpreter and your script(s)/data file(s) are unzipped into a temporary folder on your computer. When your script is done running, the temporary folder is deleted.

Most modern compression (zip) applications have an "sfx" feature that allows you to create .exe packages from zip files. You can create a packaged REBOL .exe in the same way as XpackerX using just about any sfx packaging application (there are dozens of freeware zip/compression applications that can do this - use the one you're most familiar with). There is an explanation of how to use the NSIS install creator to make REBOL .exe's [here](#).

To create a self-extracting REBOL executable for Linux, first create a .tgz file containing all the files you want to distribute (the REBOL interpreter, your script(s), any external binary files, etc.). For the purposes of this example, name that bundle "rebol_files.tgz". Next, create a text file containing the following code, and save it as "sh_commands":

```

#!/bin/sh
SKIP=`awk '/^__REBOL_ARCHIVE__/{ print NR + 1; exit 0; }' $0`
tail +$SKIP $0 | tar xz
exit 0
__REBOL_ARCHIVE__

```

Finally, use the following command to combine the above script file with the bundled .tgz file:

```
cat sh_commands rebol_files.tgz > rebol_program.sh
```

The above line will create a single executable file named "rebol_program.sh" that can be distributed and run by end users. The user will have to set the file permissions for rebol_program.sh to executable before running it ("chmod +x rebol_program.sh"), or execute it using the syntax "sh rebol_program.sh".

7.4 Embedding Binary Resources and Using REBOL's Built In Compression

The following program can be used to encode external files (images, sounds, DLLs, .exe files, etc.) so that they can be included within the *text* of your program code. Use "load (data)" to make use of any text data created by this program:

```

REBOL [Title: "Simple Binary Embedder"]

system/options/binary-base: 64
file: to-file request-file/only
data: read/binary file

```

```
editor data
```

The example below uses a text representation of the image at <http://musiclessonz.com/test.png>, encoded with the program above:

```
picture: load 64#{
iVBORw0KGgoAAAANSUHEUgAAAFUAAABkCAIAAAB4sesFAAAAE3RFWHRTb2Z0d2Fy
ZQBSRUJPTC9WaWV3j9kWeAAAAU1JREFUeJzt1zEOgzAQBHkaT7s2ryZUUZoYRz4t
e9xsSzTjEXIktqP3trspCpPo7z36e4/+3qO/9y76t/qjn3766V/oj4jBb86nUyZP
lM7kidKZPFE6kydq/Pjxq/nSElGv3qv50vj/o59++hNQm6Z93+P3zqefAw12Fyqh
v/ToX+4Pt0ubiNKZPFE6Ux5q/O/436lkh6affvrpp38ZRT/99Ov6+f4tPPqX+8Ps
/meidCZPlM7kidKZPFE6kydKZ/JE6UyeKJ3JE6UzeaJ0Jk+UzuSJ0pk8UTMmn8L
j/71/nC7tIkonekLdXm9dafSmeinn376D/rpp5/+vv1GqBkT37+FR/9yf7hd2kSU
zuSJ0pk8UTqTJ0pn8kTpTJ4onckTpTN5onQmT5TO5InSmTxROpMnasbE92/h0b/Q
//jR33v09x79vUd/73XvfwNmVzlr+eOLmgAAAABJRu5ErkJggg==
}
view layout [image picture]
```

The program below allows you to *compress* and embed files in your code. **This program will be referred to many times throughout the tutorial.** Save it to a .r file so that it can be run later:

```
REBOL [Title: "Binary Resource Embedder"]

system/options/binary-base: 64
file: to-file request-file/only
if not file [quit]
uncompressed: read/binary file
compressed: compress to-string uncompressed
editor compressed
alert rejoin ["Uncompressed size: " length? uncompressed
" bytes. Compressed size: " length? compressed " bytes."]
```

To use the compressed version of data created by the program above, use the following code:

```
to-binary decompress {compressed data}
```

For example:

```
image-compressed: load to-binary decompress 64#{
eJzrDPBz5+WS4mJgYOD19HAJAAtL/GRgydTiygKzm7Z9WACnhEteIkuD8tJLyxKJU
hiBXJ38f/bDM1PL+m2IVDAzsFz1dHEMq5ry9u3Gi jKcAy0Fh3kVzn/0XmRW5WXGV
sUF25EOmKwrSjrrF9v89o//u+cs/IS75763Tv7ZO/5qt//p63LXle9fEV0fu/7ap
7m0qZRIJf+2DmGZOVER5MQiz+ntzJix6kKnJ6CNio6va0Nm0fCmLQeCHLVMY1Ljm
TRM64HLwMpGK/334Hf4n+vkn+1pr9md7jAVsYv+X8Z3Z+M/yscIX/j32H7sl/0j3
KK+of/CX8/X63sV1w51WqNj1763MjOS/xcccX8hzzFtXDwyXL9f/P19/f0vxx4f2
OuCaHfmZDwID+P7Hso/5snw8m+qevH1030pG4kr8fhNC4f/34Z89ov+vHe4vAeut
SsdqX8T/OYUCv9iblr++f67R8pp9ukzLv8YHL39tL07o+3peknlh/dDVBgzLU/d3
9te/Lki4cNgBmA6/1o+J/RPdzty8Rr5y94/tfOxsX6/r8xJK0/UW9v1H93/9oAzR
e09yKIUBVbT9/br/U/m7x6CU98VAAJS2ZPPF/197eEDhtfs9vX9rDzc6/v3qzUyo
nJA/dz76Y77tHw+w3gXlBEMpDKihza/+7/o/c3+DU54tDwsobR2/fXR/qYXBiv8T
t3eDEmpA/d9LDAASK0y/tnz+H/Ynmt78Elvti71AKA6pouxz/X7v+uR045ZFdRE6x
1q21pG7NiSzx1f5R40pvvdNn+oB1P4Onq5/L0qeEJgCemFy1KQgAAA==
}
view layout [image image-compressed]
```

7.5 Running Command Line Applications

The "call" function executes commands in your computer's operating system (i.e., DOS and Unix commands). The example below opens Windows' Notepad to edit the "C:\YOURNAME.txt" text file created

earlier (leaving out the /show option runs the program in a hidden window):

```
call/show "notepad.exe c:\YOURNAME.txt"
```

This next example opens Windows' Paint program to edit an image we downloaded earlier in the tutorial:

```
call/show "mspaint.exe c:\bay.jpg"
```

Here's an example that embeds an executable program into the code, decompresses, and writes the program to the hard drive, and then runs it with the call function:

```
program: load to-binary decompress 64#{
eJztF1lsU2X03K4VqJsrrkZJp6OzchhFJsx8qDB9od1fHdIO6ds7AgJX2jtttyey/p
vWUjJuNnmNhMibzwaCSLi+EBE1ziGikBGh0BSYTwwAMme9Dk4kgkgsiKcj3nu7es
QrKFhMUQOcn5+c7fd875+vXe27FJAg4AbIiGAQwWIwZMEbqTcmODN5xRdmRi6aoy
Z83YogngLlaNtV+s6kV7q9Ke1Heu9LYqQTxt7e/v97UqLcLuqKJIvriShnAIOJ0r
gXvPn+StlDAF5dyzHLwAdlw4TZ1Mm7oQvWdu7jKLslsxBc4KQ30bb9bMHF3F/D5j
MFAHEIbHD+cwb88s9riSEIjvK7EKogZs//bxAvQmYlqM5JsOUwHPWFgEAYDTvqTp
eYdy1Fn5Sh/O96h9nLrrDcD4IpQm7UOkWL/nt6M1qMvxxrk1+GVWS7xqWalzdZqGz
9rbyD5ehpmnl+ezt3M/RSPe7Q9/ajeh5+9Ztm3vKh9xom7SaimLUR18C2JKf+Kg2
APoJwzDOuiAF+hHU/pHXryObdLyP+y2kEhx7UaLfo0gq/RJa60/n88Ndrpz7FmqG
u5bk3L8zwdWXc0+jdOYXkn4lnYfW++/qOPLyDz7BfH3jTXVnplx949inhPvnSgw/
8RSIHM7P8PdsUYtxlxskONE+o/u7EkNElMbpCuRKUhtjmLH/iHbDQQ7DHqL77zbb
oQxeRa9duBQHkrj+HnIdr7y/e178AvmmnHt5VQAmA59/EZ8QsJAY7EURJvMu2x
KipYj2CaEToYve2eYYiwl4rWY6jN8RWF5XtsuWSyh07aJG8XXQFkNdWYIqIHK8nH
8FOSFJmoteEfzfQEo1SNPCPW2/BTjWK1uXkp9dDDegjrDqpkAutiJhNp4ma3qUrx
MG6dqkyFMQ2ExQmaxgU2c/07D2ZJsCz3Q68Xh76Cvac2pZwi8jCO8rIZd4jieiLmc
uHxmsEMelvMBZJf0YY8Pda95yH5p+tWrI86XMZbTE5a1gVlXFKyryeowp0Cy4WF+
hdSrWGP26N008hW4Xns6/OBS7MnUVHoK0osoTV+22qF56c95qKdtZBzB66J/imSc
/Rmsg/KDdHfBA903RrZWByD/qPf1KTCwze3y2KCBn9vnp4ExoItiwr11zvncqg6+
oXGV//XVa5qCzXxL6M3ZfBfMZyFPBvywgD3FGDjLnGV183o4T+HJAZ/PFxWTqrcj
GxerHljRqyL9sWXxqU2/nkHki1H4HDkvJem7vZooeLdnNU2R10K34G1XdgveTmE7
vmv7fNDcFY1u3ABpNa5J6rZd9MouqGpjw6z1GLXn6vDxV/s9o1cYvcroNUanGP2J
UZ3RG4zeZPQ2o3cY/YtRqCdqZ3Qho6WMuhitYHQZ0pr6mRr21Zvv03VFuuMoX0Gd
VqT7BlupKFoXw8eo/8yynUR+HvEa4g3EPxEXYuwSxOWIaxADiGHEBKKGeADxCOIx
alwXke81zh/ut0OdG0LtjQ2+hCSBzLUKWoeSyErC+pickIQgfAmhgaSG319xPEvo
ioQ6Ld9D0CL04ddZQuknaxA4W1hRtXeySa0DXWM7BHjDFhHkhLUKYs2cJTcrA0H4
mmtXYgk+m1GVTBBosVVbXJGDsNTWKexIqpQ4aWYqgbps4LPCDFNMPcLYXQpldrC
g0bcVhKcKcQ220DqyB4PTHYKWSzVgCGsw/LBEGHwsjYLZR2zRTMxWZUwfaFwOaot
SXVXTiULM9V/ZeuSMw/UxW/s4KOF6W2GNjmp8Uo6rci8ImSZRVLxG+1hZWghr1v6
/4F/ABcSiGQAEAAA
}
write/binary %program.exe program
call/show %program.exe
```

The "call" function has many options that allow you to monitor, control, and make use of output from external command line applications. Type "help call" into the REBOL interpreter for an introduction. For more information, see <http://rebol.com/docs/shell.html>.

7.6 Responding to Special Events in a GUI - "Feel"

REBOL's simple GUI syntax makes it easy for widgets to respond to mouse clicks. As you've seen, you can simply put the block of code you want evaluated immediately after the widget that activates it:

```
view layout [btn "Click me" [alert "Thank you for the click :)]]
```

But what if you want your GUI to respond to events other than a mouse click directly on a widget? What if, for example, you want the program to react whenever a user clicks *anywhere* on the GUI screen (in a paint program, for example), or if you want a widget to do something after a certain amount of time has passed, or if you want to capture clicks on the GUI close button so that the user can't accidentally shut down an

important data screen. That's what the "feel" object and "insert-event-func" function are used for.

Here's an example of the basic feel syntax:

```
view layout [
  text "Click, right-click, and drag the mouse over this text." feel [
    engage: func [face action event] [
      print action
      print event/offset
    ]
  ]
]
```

The above code is often shortened using "f a e" to represent "face action event":

```
view layout [
  text "Mouse me." feel [
    engage: func [f a e] [
      print a
      print e/offset
    ]
  ]
]
```

You can respond to specific events as follows:

```
view layout [
  text "Mouse me." feel [
    engage: func [f a e] [
      if a = 'up [print "You just released the mouse."]
    ]
  ]
]
```

This example demonstrates how to combine full screen mouse detection with normal mouse clicks on widgets. To do this, an invisible box the same size as the screen, with a feel event attached, is used for full screen detection. Then, other widgets are simply placed on top of it, starting over at the window origin:

```
print "Click anywhere in the window, then click the text."
view center-face layout [
  size 400x200
  box 400x200 feel [
    engage: func [f a e] [
      print a
      print e/offset
    ]
  ]
  origin
  text "Click me" [print "Text clicked"] [print "Text right-clicked"]
  box blue [print "Box clicked"]
]
```

You can also assign timer events to any widget, as follows:

```
view layout [
  text "This text has a timer event attached." rate 00:00:00.5 feel [
    engage: func [f a e] [
      if a = 'time [print "1/2 second has passed."]
    ]
  ]
]
```

```
    ]
  ]
```

Here's a button with a time event attached (a rate of "0" means don't wait at all). Every 0 seconds, when the timer event is detected, the offset (position) of the button is updated. This creates animation:

```
view layout/size [
  mover: btn rate 0 feel [
    engage: func [f a e] [
      if a = 'time [
        mover/offset: mover/offset + 5x5
        show mover
      ]
    ]
  ]
] 400x400
```

Here's a little shooting game that uses a timer event to automate the movement of GUI graphics around the screen, check for collisions, and control other game operations:

```
REBOL [title: "VID Shooter"]

score: 0  speed: 20  fire: false
do game: [
  view center-face layout [
    size 600x440
    at 270x0 text join "Score: " score
    at 280x440 x: box 2x20 yellow
    at (as-pair 0 (random 300) + 30) y: btn 50x20 red "Enemy"
    at 280x420 z: btn 50x20 blue "Player"
    box 0x0 #"l" [z/offset: z/offset + 10x0 show z]
    box 0x0 #"k" [z/offset: z/offset + -10x0 show z]
    box 0x0 #" " [
      if fire = false [
        fire: true
        x/offset: as-pair z/offset/1 440
      ]
    ]
  ]
  box 0x0 rate speed feel [
    engage: func [f a e] [
      if a = 'time [
        y/offset: y/offset + 5x0
        if y/offset/1 > 600 [
          y/offset: as-pair -10 ((random 300) + 30)
        ]
        show y
        if fire = true [x/offset: x/offset + 0x-20]
        if x/offset/2 < 0 [
          x/offset/2: 440
          fire: false
        ]
        show x
        if within? x/offset y/offset 50x25 [
          alert "Kablammmmm!!!"
          score: score + 1
          speed: speed + 5
          fire: false
          unview
          do game
        ]
      ]
    ]
  ]
]
]
```


By updating the offset of a widget every time it's clicked, you can enable drag-and-drop operations:

```
view layout/size [
  text "Click and drag this text" feel [
    ; remember f="face", a="action", e="event":
    engage: func [f a e] [
      ; first, record the coordinate at which the mouse is
      ; initially clicked:
      if a = 'down [initial-position: e/offset]
      ; if the mouse is moved while holding down the button,
      ; move the position of the clicked widget the same amount
      ; (the difference between the initial clicked coordinate
      ; recorded above, and the new current coordinate determined
      ; whenever a mouse move event occurs):
      if find [over away] a [
        f/offset: f/offset + (e/offset - initial-position)
      ]
      show f
    ]
  ]
] 600x440
```

Feel objects and event functions can be included right inside a style definition. The definition below allows you to easily create multiple GUI widgets that can be dragged around the screen. "movestyle" is defined as a block of code that's later passed to a widget's "feel" object, and is therefore included in the overall style definition (the remove and append functions have been added here to place the moved widget on top of other widgets in the GUI (i.e., to bring the dragged widget to the visual foreground)). You can add this "feel movestyle" code to any GUI widget to make it drag-able:

```
movestyle: [
  engage: func [f a e] [
    if a = 'down [
      initial-position: e/offset
      remove find f/parent-face/pane f
      append f/parent-face/pane f
    ]
    if find [over away] a [
      f/offset: f/offset + (e/offset - initial-position)
    ]
    show f
  ]
]

view layout/size [
  style moveable-object box 20x20 feel movestyle
  ; "random 255.255.255" represents a different random
  ; color for each piece:
  at random 600x400 moveable-object (random 255.255.255)
  at random 600x400 moveable-object (random 255.255.255)
  at random 600x400 moveable-object (random 255.255.255)
  at random 600x400 moveable-object (random 255.255.255)
  at random 600x400 moveable-object (random 255.255.255)
  text "This text and all the boxes are movable" feel movestyle
] 600x440
```

The "detect" function inside a feel block is useful for constantly checking events. The following program constantly checks for mouse movements, and if the mouse is ever positioned over the button, the button is moved to a random position. This technique can be useful, for example, in video games controlled by mouse movement:

```
view center-face layout [
  size 600x440
  at 270x209 b: btn "Click Me!" feel [
    detect: func [f e] [
      ; The following line checks for any mouse movement:
```

```

        if e/type = 'move [
            ; This line checks if the mouse position is within the
            ; coordinates of the button (i.e., touching the button):
            if (within? e/offset b/offset 59x22) [
                ; If so, move the button to a random position:
                b/offset: b/offset + ((random 50x50) - (random 50x50))
                ; Check if the button has been moved off screen:
                if not within? b/offset -59x-22 659x462 [
                    ; If so, move back to the center of the window:
                    b/offset: 270x209
                ]
                ; Update the screen:
                show b
            ]
        ]
    ]
    ; When using the detect function, always return the event:
    e
]
]
]

```

To handle global events in a GUI such as resizing and closing, "insert-event-func" is useful. The following example checks for resize events:

```

insert-event-func [
    either event/type = 'resize [
        alert "I've been resized"
        none ; return this value when you don't want to
              ; do anything else with the event.
    ][
        event ; return this value if the specified event
              ; is not found
    ]
]

view/options layout [text "Resize this window."] [resize]

```

You can use that technique to adjust the window layout, and specifically reposition widgets when a screen is resized:

```

insert-event-func [
    either event/type = 'resize [
        stay-here/offset:
            stay-here/parent-face/size - stay-here/size - 20x20
        show stay-here
        none ; return this value when you don't want to
              ; do anything else with the event.
    ][
        event ; return this value if the specified event
              ; is not found
    ]
]

view/options layout [
    stay-here: text "Resize this window."
] [resize]

```

To remove an installed event handler, use "remove-event-func". The following example captures three consecutive close events, and then removes the event handler, allowing you to close the GUI on the 4th try:

```

count: 1
evtfunc: insert-event-func [
    either event/type = 'close [
        if count = 3 [remove-event-func :evtfunc]
    ]
]

```

```

        count: count + 1
        none
    ][
        event
    ]
]

view layout [text "Try to close this window 4 times."]

```

For more information about handling events see <http://www.rebol.com/how-to/feel.html>, <http://www.codeconscious.com/rebol/view-notes.html>, and <http://www.rebol.com/docs/view-system.html>.

7.7 Common REBOL Errors, and How to Fix Them

Listed below are solutions to a variety of common errors you'll run into when first experimenting with REBOL:

1) ***** Syntax Error: Script is missing a REBOL header** - Whenever you "do" a script that's saved as a file, it must contain at least a minimum required header at the top of the code. Just include the following text at the beginning of the script:

```
REBOL [ ]
```

2) ***** Syntax Error: Missing] at end-of-script** - You'll get this error if you don't put a closing bracket at the end of a block. You'll see a similar error for unclosed parentheses and strings. The code below will give you an error, because it's missing a "]" at the end of the block:

```
fruits: ["apple" "orange" "pear" "grape"
print fruits
```

Instead it should be:

```
fruits: ["apple" "orange" "pear" "grape"]
print fruits
```

Indenting blocks helps to find and eliminate these kinds of errors.

3) ***** Script Error: request expected str argument of type: string block object none** - This type of error occurs when you try to pass the wrong type of value to a function. The code below will give you an error, because REBOL automatically interprets the website variable as a URL, and the "alert" function requires a string value:

```
website: http://rebol.com
alert website
```

The code below solves the problem by converting the URL value to a string before passing it to the alert function:

```
website: to-string http://rebol.com
alert website
```

Whenever you see an error of the type "expected _____ argument of type: ____ ____ ____ ...", you need to convert your data to the appropriate type, using one of the "to-(type)" functions. Type "? to-" in the REBOL interpreter to get a list of all those functions.

4) ***** Script Error: word has no value** - Miss-spellings will elicit this type of error. You'll run into it any time

you try to use a word that isn't defined (either natively in the REBOL interpreter, or by you, in previous code):

```
wrod: "Hello world"
print word
```

5) If an error occurs in a "view layout" block, and the GUI becomes unresponsive, type "unview" at the interpreter command line and the broken GUI will be closed. To restart a stopped GUI, type "do-events". To break out of any endless loop, or to otherwise stop the execution of any errant code, just hit the [Esc] key on your keyboard.

6) "*** User Error: Server error: tcp 550 Access denied - Invalid HELO name (See RFC2821 4.1.1.1)" and "*** User Error: Server error: tcp -ERR Login failed.", among others, are errors that you'll see when trying to send and receive emails. To fix these errors, your mail server info needs to be set up in REBOL's user settings. The most common way to do that is to edit your mail account info in the graphic Viewtop or by using the "set-net" function (<http://www.rebol.com/docs/words/wset-net.html>). You can also set everything manually - this is how to adjust all the individual settings:

```
system/schemes/default/host: your.smtp.address
system/schemes/default/user: username
system/schemes/default/pass: password
system/schemes/pop/host: your.pop.address
system/user/email: your.email@site.com
```

7) Here's a quirk of REBOL that doesn't elicit an error, but which can cause confusing results, especially if you're familiar with other languages:

```
unexpected: [
    empty-variable: ""
    append empty-variable ""
    print empty-variable
]

do unexpected
do unexpected
do unexpected
```

The line:

```
empty-variable: ""
```

doesn't re-initialize the variable to an empty state. Instead, every time the block is run, "empty-variable" contains the previous value. In order to set the variable back to empty, as intended, use the word "copy" as follows:

```
expected: [
    empty-variable: copy ""
    append empty-variable ""
    print empty-variable
]

do expected
do expected
do expected
```

8) Load/Save, Read/Write, Mold, Reform, etc. - another point of confusion you may run into initially with REBOL has to do with various words that read, write, and format data. When saving data to a file on your hard drive, for example, you can use either of the words "save" or "write". "Save" is used to store data in a

format more directly usable by REBOL. "Write" saves data in a raw, 'unREBOLized' form. "Load" and "read" share a comparable relationship. "Load" reads data in a way that is more automatically understood and put to use in REBOL code. "Read" opens data in exactly the format it's saved, byte for byte. Generally, data that is "save"d should also be "load"ed, and data that's "write"ed should be "read". For more information, see the following REBOL dictionary entries:

<http://rebol.com/docs/words/wload.html>

<http://rebol.com/docs/words/wsav.html>

<http://rebol.com/docs/words/wread.html>

<http://rebol.com/docs/words/wwrite.html>

Other built-in words such as "mold" and "reform" help you deal with text in ways that are either more human-readable or more natively readable by the REBOL interpreter. For a helpful explanation, see <http://www.rebol.net/cookbook/recipes/0015.html>.

9) Order of precedence - REBOL expressions are *always* evaluated from left to right, regardless of the operations involved. If you want specific mathematical operators to be evaluated first, they should either be enclosed in parenthesis or put first in the expression. For example, to the REBOL interpreter:

```
2 + 4 * 6
```

is the same as:

```
(2 + 4) * 6 ; the left side is evaluated first
== 6 * 6
== 36
```

This is contrary to other familiar evaluation rules. In many languages, for example, multiplication is typically handled before addition. So, the same expression:

```
2 + 4 * 6
```

is treated as:

```
2 + (4 * 6) ; the multiplication operator is evaluated first
== 2 + 24
== 26
```

Just remember, evaluation is always left to right, without exception.

10) You may run into problems when copying/pasting interactive console scripts directly into the REBOL interpreter, especially when the code contains functions such as "ask", which require a response from the user before the remainder of the script is evaluated (each line of the script simply runs, as the pasting operation completes, without any response from the user, leaving necessary variables unassigned). To fix such interactivity problems when copying/pasting console code into the interpreter, simply wrap the entire script in square brackets and then "do" that block: *do [...your full script code...]*. This will force the entire script to be loaded before any of the code is evaluated. If you want to run the code several times, simply assign it a word label, and then run the word label as many times as needed: *do x: [...your full script code...]* *do x do x do x* This saves you from having to paste the code more than once. Another effective option, especially with large scripts, is to run the code from the clipboard using *"do read clipboard://"*. This performs *much* faster than watching large amounts of text paste into the console.

7.7.1 Trapping Errors

There are several simple ways to keep your program from crashing when an error occurs. The words "error?" and "try" together provide a way to check for and handle expected error situations. For example, if no Internet connection is available, the code below will crash abruptly with an error:

```
html: read http://rebol.com
```

The adjusted code below will handle the error more gracefully:

```
if error? try [html: read http://rebol.com] [
    alert "Unavailable."
]
```

The word "attempt" is an alternative to the "error? try" routine. It returns the evaluated contents of a given block if it succeeds. Otherwise it returns "none":

```
if not attempt [html: read http://rebol.com] [
    alert "Unavailable."
]
```

To clarify, "error? try [block]" evaluates to true if the block produces an error, and "attempt [block]" evaluates to false if the block produces an error.

For a complete explanation of REBOL error codes, see: <http://www.rebol.com/docs/core23/rebolcore-17.html>.

8. EXAMPLE PROGRAMS - Learning How All The Pieces Fit Together

The examples in this section demonstrate how REBOL code is put together to create complete programs. The code is heavily commented to provide line-by-line explanations of how each element works. The recommended way to run the examples is to install REBOL on your computer, paste the code for each program into a text editor, save the code file as "(program_name).r" and then double click the icon for the text file you've created. With REBOL installed, any file with a ".r" extension will automatically run as if it's an .exe program. Downloadable Windows executables and screen shots of these examples are available at:

http://musiclessonz.com/rebol_tutorial/examples

Be sure to check out the hundreds of additional code examples available directly from rebsites on the desktop of the REBOL interpreter!

8.1 Little Email Client

The first example is a complete graphical email client that can be used to read and send messages:

```
; Every program requires a minimum header:

REBOL [Title: "Little Email Client"]

; The line below creates the program's GUI window:

view layout [

    ; This line adds a text label to the GUI:

    h1 "Send Email:"

    ; This line adds a button to the GUI:
```

```

btn "Server settings" [

    ; When the button is clicked, the following lines are run.
    ; These lines set all the email user account information
    ; required to send and receive email. The settings are gotten
    ; from the user with the "request-text" function, and assigned
    ; to their appropriate locations in REBOL's system object:

    system/schemes/default/host: request-text/title "SMTP Server:"
    system/schemes/pop/host:      request-text/title "POP Server:"
    system/schemes/default/user: request-text/title "SMTP User Name:"
    system/schemes/default/pass: request-text/title "SMTP Password:"
    system/user/email: to-email request-text/title "Your Email Addr:"

]

; This line creates a text entry field, containing the default text
; "recipient@website.com". The variable word "address" is assigned to
; this widget:

address: field "recipient@website.com"

; Heres another text entry field, for the email subject line:

subject: field "Subject"

; This line creates a larger, multi-line text entry area for the body
; text of the email:

body: area "Body"

; Here's a button displaying the word "send". The functions inside
; its action block are executed whenever the button is clicked:

btn "Send" [

    ; This line does most of the work. It uses the REBOL "send"
    ; function to send the email. The send function, with its
    ; "/subject" refinement accepts three parameters. It's passed the
    ; current text contained in each field labeled above (referred to
    ; as "address/text" "body/text" and "subject/text"). The
    ; "to-email" function ensures that the address text is treated as
    ; an email data value:

    send/subject (to-email address/text) body/text subject/text

    ; This line alerts the user when the previous line is complete:

    alert "Message Sent."

]

; Here's another text label:

h1 "Read Email:"

; Here's another text entry field. The user's email account info is
; entered here.

mailbox: field "pop://user:pass@site.com"

; This last button has an action block that reads messages from a
; specified mailbox. It only takes one line of code:

btn "Read" [

    ; The "to-url" function ensures that the text in the mailbox field
    ; is treated as a URL. The contents of the mailbox are read and
    ; displayed using REBOL's built-in text editor:

    editor read to-url mailbox/text

]

```

```
]
```

Here's the same code, without comments - it's very simple. Try pasting it directly into the REBOL interpreter:

```
REBOL [Title: "Little Email Client"]
view layout [
  h1 "Send Email:"
  btn "Server settings" [
    system/schemes/default/host: request-text/title "SMTP Server:"
    system/schemes/pop/host:    request-text/title "POP Server:"
    system/schemes/default/user: request-text/title "SMTP User Name:"
    system/schemes/default/pass: request-text/title "SMTP Password:"
    system/user/email: to-email request-text/title "Your Email Addr:"
  ]
  address: field "recipient@website.com"
  subject: field "Subject"
  body: area "Body"
  btn "Send" [
    send/subject to-email address/text body/text subject/text
    alert "Message Sent."
  ]
  h1 "Read Email:"
  mailbox: field "pop://user:pass@site.com"
  btn "Read" [
    editor read to-url mailbox/text
  ]
]
```

8.2 Simple Web Page Editor

The following program can be used to load, edit, and save HTML files (or any other text file) directly to/from a live web server or to/from a drive on your local computer. It requires 14 lines of code:

```
REBOL [Title: "Web Page Editor"] ; required header

; Create a GUI window:

view layout [

  ; Here's a text entry field containing a generic URL address for
  ; the page to be edited. The label "page-to-read" is assigned to
  ; this widget:

  page-to-read: field 600 "ftp://user:pass@website.com/path/page.html"

  ; Here's a multi-line text field to hold and edit the HTML
  ; downloaded from the above URL. The label "the-html" is assigned
  ; to it:

  the-html: area 600x440

  ; The "across" words lays out the next buttons on the same line:

  across

  ; Here's a button to download and display the HTML at the URL given
  ; above:

  btn "Download HTML Page" [

    ; When the button is clicked, read the HTML at the URL above,
    ; insert it into the multi-line text area (by setting the text
    ; property of that field to the downloaded text), and update the
    ; display:
  ]
]
```



```

        the-html/text: read (to-url page-to-read/text)
        show the-html
    ]

; Here's another button to read and display text from a local file:

btn "Load Local HTML File" [

    ; When the button is clicked, read the HTML from a file selected
    ; by the user, insert it into the multi-line text area, and update
    ; the display:

    the-html/text: read (to-file request-file)
    show the-html
]

; Here's another button.  When clicked, the edited contents of the
; multi-line text area are saved back to the URL:

btn "Save Changes to Web Site" [
    write (to-url page-to-read/text) the-html/text
]

; Here's another button to write the edited contents of the multi-
; line text area to a local file selected by the user:

btn "Save Changes to Local File" [
    write (to-file request-file/save) the-html/text
]
]
```

8.3 Card File

This is the quintessential simple text field storage application. It can be used as shown here, to save contact information, but by adjusting just a few lines of code and text labels, it could be easily adapted to store recipes, home inventory information, or any other type of related pages of data.

```

REBOL [title: "Card File"]

; The line below writes a new empty data file to the hard drive, if it
; doesn't already exist.  If the file DOES already exist, then this
; function simply writes an empty string to it (i.e., leaves the file
; alone):

write/append %data.txt ""

; This line loads all saved records from the database file:

database: load %data.txt

; Here's the GUI window:

view center-face gui: layout [

    ; Here's a text label to instruct the user:

    text "Load an existing record:"

    ; This text list displays an alphabetically sorted list of the
    ; names found in the database (every forth item).  The number
    ; pair indicates the widget's pixel size:

    name-list: text-list blue 400x100 data (sort extract database 4) [

        ; The following line is included to avoid potential errors.
        ; When an item in the text list is clicked, we first check that
        ; the selected data (represented by the word "value") is NOT

```

```

; equal to nothing.  If so, exit the widget's action block
; (the "return" word quits the text-list's action routine):

if value = none [return]

; The following code finds the selected name in the loaded
; database.  The display fields in the GUI are then set
; to show the found name, and each of the 3 items after
; it in the database (name = field 1, address = field 2,
; phone = field 3, notes = field 4):

marker: index? find database value
n/text: pick database marker
a/text: pick database (marker + 1)
p/text: pick database (marker + 2)
o/text: pick database (marker + 3)

; Update the display to show the changed text fields (notice
; the "gui" label defined above - it refers to the entire GUI
; layout):

show gui
]

; Here are the text display fields, and some text labels to show
; what should be typed into each field:

text "Name:"      n: field 400
text "Address:"   a: field 400
text "Phone:"     p: field 400
text "Notes:"     o: area 400x100

; The "across" word adds widgets to the GUI next to one another,
; instead of beneath one another, which is the default behavior
; (the following 3 buttons will appear next to each other):

across

; Here's a GUI button to let the user save the contents of the
; text fields to the database:

btn "Save" [

; When this button is clicked, make sure the required field
; contains some text.  If not, notify the user, and then exit
; this button's routine (the "return" word quits the save
; button's action block):

if n/text = "" [alert "You must enter a name." return]

; Now run through every forth item in the database to check if
; the name already exists.  If so, give the user the option to
; overwrite that record.  If they respond yes, delete the old
; record from the database ("remove/part" deletes 4 items at
; the location where the selected name is found).  If the user
; responds no, escape out of the save button's routine:

if find (extract database 4) n/text [
  either true = request "Overwrite existing record?" [
    remove/part (find database n/text) 4
  ] [
    return
  ]
]

; Now update the database with the new data, and write it to
; the hard drive.  The "repnd" function appends the evaluated
; variables inside the brackets (in this case a block of 4
; separate text strings contained in the GUI fields) to the
; database:

save %data.txt repnd database [n/text a/text p/text o/text]

```

```

        ; Update the text-list to show the added record:

        name-list/data: sort (extract copy database 4)
        show name-list
    ]

    ; This button allows the user to clear the screen and enter a
    ; new record:

    btn "Delete" [

        ; When this button is clicked, the code below gives the user
        ; the option to delete the selected record.  If the user
        ; selects "yes", the "remove/part" function deletes 4 items
        ; from the database, at the location where the selected name
        ; is found.  The database is saved, and the text fields are
        ; cleared ("do-face" runs the action block of the
        ; "clear-button" widget above, to clear the GUI fields), then
        ; the name list is updated:

        if true = request rejoin ["Delete " n/text "?"] [
            remove/part (find database n/text) 4
            save %data.txt database
            do-face clear-button 1
            name-list/data: sort (extract copy database 4)
            show name-list
        ]
    ]

    clear-button: btn "New" [

        ; When this button is clicked, set the text of each field to an
        ; empty string:

        n/text: copy ""
        a/text: copy ""
        p/text: copy ""
        o/text: copy ""

        ; As always, when any on data in the GUI is changed, the
        ; screen must be updated:

        show gui
    ]
]

```

Here's the whole program, without comments:

```

REBOL [title: "Card File"]

write/append %data.txt ""
database: load %data.txt

view center-face gui: layout [
    text "Load an existing record:"
    name-list: text-list blue 400x100 data sort (extract database 4) [
        if value = none [return]
        marker: index? find database value
        n/text: pick database marker
        a/text: pick database (marker + 1)
        p/text: pick database (marker + 2)
        o/text: pick database (marker + 3)
        show gui
    ]
    text "Name:"          n: field 400
    text "Address:"       a: field 400
    text "Phone:"         p: field 400
    text "Notes:"         o: area 400x100
]

```

```

across
btn "Save" [
  if n/text = "" [alert "You must enter a name." return]
  if find (extract database 4) n/text [
    either true = request "Overwrite existing record?" [
      remove/part (find database n/text) 4
    ] [
      return
    ]
  ]
  save %data.txt repend database [n/text a/text p/text o/text]
  name-list/data: sort (extract copy database 4)
  show name-list
]
btn "Delete" [
  if true = request rejoin ["Delete " n/text "?"] [
    remove/part (find database n/text) 4
    save %data.txt database
    do-face clear-button 1
    name-list/data: sort (extract copy database 4)
    show name-list
  ]
]
clear-button: btn "New" [
  n/text: copy ""
  a/text: copy ""
  p/text: copy ""
  o/text: copy ""
  show gui
]
]

```

8.4 Little Menu Example

A module that produces full blown menus with all the bells and whistles is available at <http://www.rebol.org/library/scripts/menu-system.r> (covered later in this tutorial). Here's a simpler homemade example that can be included in your programs to provide basic menu functionality. It's constructed using only raw, native REBOL GUI components:

```

REBOL [Title: "Simple Menu Example"]

; "center-face" centers the GUI window:

view center-face gui: layout [

  size 400x300
  at 100x100 H3 "You selected:"
  display: field

  ; Here's the menu. Make sure it goes AFTER other GUI code.
  ; If you put it before other code, the menu will appear be-
  ; hind other widgets in the GUI. The menu is basically just
  ; a text-list widget, which is initially hidden off-screen
  ; at position -200x-200. When an item in the list is
  ; clicked upon, the action block for the text-list runs
  ; through a conditional switch structure, to decide what to
  ; do for the chosen item. The code for each option first
  ; re-hides the menu by repositioning it off screen (at
  ; -200x-200 again). For use in your own programs, you can
  ; put as many items as you want in the list, and the action
  ; block for each item can perform any actions you want.
  ; Here, each option just updates the text in the "display"
  ; text entry field, created above. Change, add to, or
  ; delete the "item1" "item2" and "quit" elements to suit
  ; your needs:

  origin 2x2 space 5x5 across
  at -200x-200 file-menu: text-list "item1" "item2" "quit" [
    switch value [

```

```

        "item1" [
            face/offset: -200x-200
            show file-menu
            ; PUT YOUR CODE HERE:
            set-face display "File / item1"
        ]
        "item2" [
            face/offset: -200x-200
            show file-menu
            ; PUT YOUR CODE HERE:
            set-face display "File / item2"
        ]
        "quit" [quit]
    ]
]

; The menu initially just appears as some text choices at
; the top of the GUI. When the "File" menu is clicked,
; the action block of that text widget repositions the
; text-list above, so that it appears directly underneath
; the File menu ("face/offset" is the location of the
; currently selected text widget). It disappears when
; clicked again - the code checks to see if the text-list
; is positioned beneath the menu. If so, it repositions
; it out of sight.

at 2x2
text bold "File" [
    either (face/offset + 0x22) = file-menu/offset [
        file-menu/offset: -200x-200
        show file-menu
    ][
        file-menu/offset: (face/offset + 0x22)
        show file-menu
    ]
]

; Here's an additional top level menu option. It provides
; just a single choice. Instead of opening a text-list
; widget with multiple options, it simply ensures that the
; other menu is closed (re-hidden), and then runs some code.

text bold "Help" [
    file-menu/offset: -200x-200
    show file-menu
    ; PUT YOUR CODE HERE:
    set-face display "Help"
]
]

```

8.5 Loops and Conditions - A Simple Data Storage App

One of the most important applications of loop structures is to step through lists of data. By stepping through elements in a block, loops can be used to process and perform actions on each item in a given data series. This technique is used in all types of programming, and it's a cornerstone of the way programmers think about working with tables of data (such as those found in databases). Because many programs work with lists of data, you'll very often come across situations that require the use of loops. Thinking about how to put looping structures to use is a fundamental part of learning to write code in any language. The example below demonstrates several ways in which you'll see loops commonly put to use.

```

REBOL [title: "Loops and Conditions - a Simple Data Storage App"]

; First, a small user database is defined. It's organized
; into a block structure: the "users" block contains 5
; blocks, which each contain 5 items of information for
; each user. Blank items are represented with empty quotes.

users: [
    ["John" "Smith" "123 Toleen Lane" "Forest Hills, NJ" "555-1234"]

```

```

["Paul" "Thompson" "234 Georgetown Pl." "Peanut Grove, AL" "555-2345"]
["Jim" "Persee" "345 Portman Pike" "Orange Grove, FL" "555-3456"]
["George" "Jones" "456 Topforge Court" "Mountain Creek, CO" ""]
["Tim" "Paulson" "" "" "555-5678"]
]

```

```

; This program does not have a GUI. Instead, it's a text
; based "console" program. Since there's no GUI, we need
; to format the output so that it's got a nice layout on the
; screen. Here's a little function that uses a loop to draw
; a line. It prints 65 dashes next to each other, and then
; a carriage return. We'll use those lines to help print
; nicely formatted output:

```

```

draw-line: does [loop 65 [prin "-"] print ""]

```

```

; Note that this is not the most efficient way to draw a line
; of characters, because the program needs to run through
; the loop every time a line is drawn. You'll see some
; flicker on the screen every time this happens, because
; the computer has to run through the "prin" function 65
; times for each line. Although it only takes a fraction of
; a second on a modern computer, it's still quite noticeable.
; It would be faster, instead, to build a block of characters
; once, and then print that block, as follows:

```

```

;
;       a-line: copy []
;       loop 65 [append a-line "-"]
;       ; remove the spaces and turn it
;       ; into a string of characters:
;       a-line: trim to-string a-line
;       ; now you can print "a-line"
;       ; anywhere you need it:
;       print a-line
;

```

```

; The inefficient code above is left in this example to
; demonstrate a point about how the coding thought process
; can dramatically effect the performance of programs you
; create. That's especially true for programs that perform
; complex loops on large lists of data. The more efficient
; line printing function is implemented in another example
; following this one, to demonstrate the difference in its
; effectiveness.

```

```

; Next is a small function that prints out all of the data
; in the database. It uses a foreach loop to cycle through
; each block of user data, and then it prints a line
; displaying each element in the block (items numbered 1-5
; in each block). This creates a nicely formatted display:

```

```

print-all: does [
  foreach user users [
    draw-line
    print rejoin ["User:      " user/1 " " user/2]
    draw-line
    print rejoin ["Address:   " user/3 " " user/4]
    print rejoin ["Phone:     " user/5]
    print newline
  ]
]

```

```

; The following code uses a forever loop to continually
; request a choice from the user. It uses several foreach
; loops to pull information from the data block, and a
; conditional "switch" structure to decide how to respond
; to the user's request. The "switch" inside a forever
; loop is a common design in command line programs:

```

```

forever [
  ; First, print some nice formatting and display info:

```

```

prin "^ (1B)[J" ; this code clears the screen.

print "Here are the current users in the database:^/"
; The "^/" at the end of the line above prints a newline.

draw-line ; run the function defined above

; Now print the list of user names. A foreach loop is
; used to get the first and last name of each user in the
; database. The first name is item 1 in each block, and
; the last name is item 2 in each block. So for each
; block in the database, "user/1" and "user/2" are
; printed:

foreach user users [prin rejoin [user/1 " " user/2 " "]]
print ""
draw-line

; print some instructions:

prin "Type the name of a user below "
print "(part of a name will perform search):^/"
print "Type 'all' for a complete database listing."
print "Press [Enter] to quit.^/"

; Now ask the user for a choice:

answer: ask {What person would you like info about? }
print newline

; Decide what to do with the user's response:

switch/default answer [

    ; If they typed "all", execute the "print-all"
    ; function defined earlier:

    "all" [print-all]

    ; If they typed the [Enter] key alone (""), print a
    ; goodbye message, and end the program. Note that
    ; "ask" is used to display the message, instead of
    ; "print". This allows the program to wait for the
    ; user to press a key before ending the program:

    "" [ask "Goodbye! Press [Enter] to end." quit]

    ; If neither of the choices above were selected, the
    ; default block below is executed (this is the last
    ; part of the switch structure):

    ][

    ; This section starts by creating a "flag" variable,
    ; which is used to track whether or not the user's
    ; choice has been found in the database - the word
    ; "found" is initially set to false to indicate that
    ; the user name has not yet been found:

    found: false

    ; Next, a foreach loop steps through each user block
    ; in the database:

    foreach user users [

        ; If the entered user name is found in the
        ; database (either the first or last name), the
        ; info for that user is printed out in a nicely
        ; formatted display, and the "found" flag is set
        ; to true. The "rejoin" action is used to join
        ; the first name and last name, and is used in

```

```

        ; conjunction with the "find" action to check
        ; whether the user's answer matches any part of
        ; the names in the database (when you run this
        ; code, try entering single characters, or a
        ; part of a name, to see what happens).

        if find rejoin [user/1 " " user/2] answer [
            draw-line
            print rejoin ["User:      " user/1 " " user/2]
            draw-line
            print rejoin ["Address:   " user/3 " " user/4]
            print rejoin ["Phone:    " user/5]
            print newline
            found: true
        ]

        ; If the "found" variable is still false after
        ; looping through the entire user database, then the
        ; user name was not found in the database. Print a
        ; message to that effect:

        if found <> true [    ; "<>" means "not equal to"
            print "That user is not in the database!^/" ]

        ; Wait for a user response, and then continue again at
        ; the beginning of the forever loop:

        ask "Press [ENTER] to continue"
    ]

```

Here's the entire program without the comments. Try to follow the program flow on your own. NOTE: In this version, the inefficient "draw-line" function is replaced by the suggested "print a-line" routine above. As a result, you'll see a dramatic reduction in screen flicker:

```

Rebol []
users: [
    ["John" "Smith" "123 Tomline Lane" "Forest Hills, NJ" "555-1234"]
    ["Paul" "Thompson" "234 Georgetown Pl." "Peanut Grove, AL" "555-2345"]
    ["Jim" "Persee" "345 Pickles Pike" "Orange Grove, FL" "555-3456"]
    ["George" "Jones" "456 Topforge Court" "Mountain Creek, CO" "" ]
    ["Tim" "Paulson" "" "" "555-5678"]
]
a-line: copy [] loop 65 [append a-line "-"]
a-line: trim to-string a-line
print-all: does [
    foreach user users [
        print a-line
        print rejoin ["User:      " user/1 " " user/2]
        print a-line
        print rejoin ["Address:   " user/3 " " user/4]
        print rejoin ["Phone:    " user/5]
        print newline
    ]
]
forever [
    prin "^(1B)[J"
    print "Here are the current users in the database:^/"
    print a-line
    foreach user users [prin rejoin [user/1 " " user/2 " " ]]
    print "" print a-line
    prin "Type the name of a user below "
    print "(part of a name will perform search):^/"
    print "Type 'all' for a complete database listing."
    print "Press [Enter] to quit.^/"
    answer: ask {What person would you like info about? }
    print newline
    switch/default answer [

```



```

"all"      [print-all]
""         [ask "Goodbye!  Press any key to end." quit]
][
found: false
foreach user users [
    if find rejoin [user/1 " " user/2] answer [
        print a-line
        print rejoin ["User:      " user/1 " " user/2]
        print a-line
        print rejoin ["Address:   " user/3 " " user/4]
        print rejoin ["Phone:    " user/5]
        print newline
        found: true
    ]
]
if found <> true [
    print "That user is not in the database!^/"
]
ask "Press [ENTER] to continue"
]

```

For some perspective, here's a GUI version of the same program that demonstrates how GUI and command line programming styles differ. Notice how much of the data handling is managed by the built-in GUI tools in the language, rather than by homemade loops:

```

REBOL [title: "Loops and Conditions - Data Storage App - GUI Example"]

users: [
    ["John" "Smith" "123 Tomline Lane" "Forest Hills, NJ" "555-1234"]
    ["Paul" "Thompson" "234 Georgetown Pl." "Peanut Grove, AL" "555-2345"]
    ["Jim" "Persee" "345 Pickles Pike" "Orange Grove, FL" "555-3456"]
    ["George" "Jones" "456 Topforge Court" "Mountain Creek, CO" ""]
    ["Tim" "Paulson" "" "" "555-5678"]
]
user-list: copy []
foreach user users [append user-list user/1]
user-list: sort user-list

view display-gui: layout [
    h2 "Click a user name to display their information:"
    across
    list-users: text-list 200x400 data user-list [
        current-info: []
        foreach user users [
            if find user/1 value [
                current-info: rejoin [
                    "FIRST NAME:  " user/1 newline newline
                    "LAST NAME:    " user/2 newline newline
                    "ADDRESS:     " user/3 newline newline
                    "CITY/STATE:  " user/4 newline newline
                    "PHONE:      " user/5
                ]
            ]
        ]
        display/text: current-info
        show display show list-users
    ]
    display: area "" 300x400 wrap
]

```

8.6 FTP Chat Room

This example is a simple chat application that lets users send instant text messages back and forth across the Internet. It includes password protected access for administrators to erase chat contents. It also allows users to pause activity momentarily, and requires a username/password to continue ["secret" "password"]. The chat "rooms" are created by dynamically creating, reading, appending, and saving text files via ftp (to

use the program, you'll need access to an available ftp server: ftp address, username, and password. Nothing else needs to be configured on the server).

```

REBOL [title: "FTP Chat Room"]

; The following line gets the URL of a text file on the user's web server
; to use for the chat. The ftp username, password, domain, and filename
; must be entered in the format shown:

webserver: to-url request-text/title/default {
    URL of text file on your server:} "ftp://user:pass@site.com/chat.txt"

; The following line gets the user's name:

name: request-text/title "Enter your name:"

; In the following line, the word "cls" is assigned to a function
; definition which clears the screen:

cls: does [prin "^(1B)[J"]

; The following line writes some text to the webserver file (obtained
; above), indicating that the user has entered the chat. The "/append"
; refinement adds to the existing text in the webserver file (as opposed
; to erasing what's already there). Using "rejoin", the text written to
; the webserver is the combined value of the user's name, some static
; text, the current date and time, and a carriage return:

write/append webserver rejoin [now ": " name " has entered the room.^\n"]

; Now the program uses a "forever" loop to continually wait for user
; input, and to do appropriate things with that input:

forever [

    ; First, read the messages that are currently in the "webserver" text
    ; file, and assign the variable word "current-chat" to that text:

    current-chat: read webserver

    ; Clear the screen using the function word defined above:

    cls

    ; Display a greeting and some instructions:

    print rejoin [
        "-----"
        newline {You are logged in as: } name newline
        {Type "room" to switch chat rooms.} newline
        {Type "lock" to pause/lock your chat.} newline
        {Type "quit" to end your chat.} newline
        {Type "clear" to erase the current chat.} newline
        {Press [ENTER] to periodically update the display.} newline
        "-----" newline
    ]

    print rejoin ["Here's the current chat text at: " webserver newline]
    print current-chat

    ; In the line below, the "ask" function is used to get some text from
    ; the user. The returned text (the text entered by the user) is
    ; assigned the label "entered-text", and concatenated with the user's
    ; name and the text " says: ". This prepares it to be added to the
    ; webserver file and displayed in the chat. Notice that the user
    ; must first respond to the "ask" function, before the rejoin
    ; evaluation can occur:

    sent-message: copy rejoin [
        name " says: "

```

```

    entered-text: ask "You say:  "
]

; The "switch" structure below is used to check for commands in the
; text entered by the user.  If the user enters "quit", "clear",
; "room", or "lock", appropriate actions occur:

switch/default entered-text [

    ; If the user typed "quit", stop the forever loop (exit the
    ; program):

    "quit" [break]

    ; If the user typed "clear", erase the current text chat.  But
    ; first, ask user for the administrator username/password (using
    ; the "request-pass" function):

    "clear" [

        ; "if/else" does the same thing as "either" (deprecated):

        if/else request-pass = ["secret" "password"] [
            write webserver ""
        ] [
            alert {
                You must know the administrator password to clear
                the room!
            }
        ]
    ]

    ; If the user typed "room", request a new FTP address, and run
    ; some code that was presented earlier in the program, using the
    ; newly entered "webserver" variable, to effectively change chat
    ; "rooms":

    "room" [

        ; Add a message the chat file, indicating that the user has
        ; left the chat:

        write/append webserver rejoin [
            now ": " name " has left the room." newline
        ]

        ; Get the URL of a new chat text file (the new room address).
        ; Use the old address as the default displayed URL:

        webserver: to-url request-text/title/default {
            New Web Server Address:} to-string webserver

        ; Display a message in the newly chosen chat text file,
        ; showing that the user has entered the chat:

        write/append webserver rejoin [
            now ": " name " has entered the room." newline
        ]
    ]

    "lock" [

        ; Display a message to the user that the program will be
        ; paused:

        alert {The program will now pause for 5 seconds.
            You'll need the correct username and password
            to continue.
        }

        ; Assign a variable to the time 5 seconds from now:

```

```

    pause-time: now/time + 5

    ; Don't go on until the user gets the password right:
    forever [

        ; First, wait 5 seconds:

        if now/time = pause-time [

            ; The while loop below continually asks the user for
            ; a password, until correct:

            while [
                request-pass <> ["secret" "password"]
            ][
                alert "Incorrect password - look in the source!"
            ]

            ; After the user has entered the correct username and
            ; password, exit the forever loop and continue with
            ; the program:

            break
        ]
    ]

    ][

        ; The following line is the default case for the switch structure:
        ; as long as the entered message is not blank ([Enter]), write the
        ; entered message to the web server (append it to the current chat
        ; text):

        if entered-text <> "" [
            write/append webserver rejoin [sent-message newline]
        ]
    ]

    ; When the "forever" loop is exited, do the following:

    cls print "Goodbye!"
    write/append webserver rejoin [now ": " name " has closed chat." newline]
    wait 1

```

The bulk of this program runs within the "forever" loop, and uses the conditional "switch" structure to decide how to respond to user input (as in the "Loops and Conditions - A Simple Data Storage App" example). This is a classic outline that can be adjusted to match a variety of generalized situations in which the computer repeatedly waits for and responds to user interaction at the command prompt.

8.7 Image Effector

The next application creates a GUI interface, downloads and displays an image from the Internet, allows you to apply effects to it, and lets you save the effected image to the hard drive. In the mix, there are several routines which get data, and alert the user with text information.

```

; A header is still required, even if a title isn't included:

REBOL []

; The following line creates a short list of image effects that are built
; into REBOL, and assigns the variable word "effect-types" to the block:

effect-types: [
    "Invert" "Grayscale" "Emboss" "Blur" "Sharpen" "Flip 1x1" "Rotate 90"
    "Tint 83" "Contrast 66" "Luma 150" "None"

```

```

]

; The code below imports the simple "play-sound" function created earlier
; in the tutorial. For this to work correctly, the play_sound.r file
; should be saved to C:\. The either condition checks to see if the file
; exists. If so, it runs the code and sets a variable that we'll use
; later to decide whether or not to play a sound. If the file doesn't
; exist, the variable is simply set to false:

either exists? %/c/play_sound.r [
    do %/c/play_sound.r
    sound-available: true
][
    sound-available: false
]

; The line below asks user for the URL of a new image (with a default
; location), and assigns that address to the word "image-url":

image-url: to-url request-text/title/default {
    Enter the URL of an image to use:} trim {
    http://rebol.com/view/demos/palms.jpg}

; Now a GUI block will be constructed, to be display later using
; "view layout":

gui: [

    ; This first line horizontally aligns all the following GUI widgets,
    ; so they appear next to each other in the layout (the default
    ; behavior in REBOL is to align elements vertically):

    across

    ; This line changes the spacing of consecutive widgets so they're on
    ; top of each other:

    space -1

    ; The following code displays the program menu, using a "choice"
    ; button widget (a menu-select type of button built into REBOL).
    ; The button is 160 pixels across, and is placed at the uppermost,
    ; leftmost pixel in the GUI (0x0) using the built-in word "at".

    at 20x2 choice 160 tan trim {
        Save Image} "View Saved Image" "Download New Image" trim {
            -----} "Exit" [

        ; This is the action block for the choice selector. It contains
        ; various functions to be performed, based on the choice selected
        ; by the user. Conditional "if" evaluations are used to determine
        ; which actions to perform. This could have been done with less
        ; code, using a "switch" structure. "If" was used, however, to
        ; demonstrate that there are always alternate ways to express
        ; yourself in code - just like in spoken language:

        if value = "Save Image" [

            ; Request a filename to save the image as (defaults to
            ; "c:\effectedimage.png"):

            filename: to-file request-file/title/file/save trim {
                Save file as:} "Save" %/c/effectedimage.png

            ; Save the image to hard drive:

            save/png filename to-image picture

        ]

        if value = "View Saved Image" [

```

```

        ; Request a file name from the user (defaults to
        ; "c:\effectedimage.png"):

view-filename: to-file request-file/title/file {
    View file:} "" %c/effectedimage.png

        ; Read the selected image from the hard drive and
        ; display it in a new GUI window:

view/new center-face layout [image load view-filename]

    ]

if value = "Download New Image" [

    ; Ask for the location of a new image, and assign the entered
    ; URL the word label "new-image":

new-image: load to-url request-text/title/default trim {
    Enter a new image URL} trim {
    http://www.rebol.com/view/bay.jpg}

    ; Replace the old image with the new one:

picture/image: new-image

    ; Update the GUI display:

show picture

]

if value = "-----" [] ; don't do anything

if value = "Exit" [

    ; If the variable we set earlier indicates that sound is
    ; available, play a little closing sound:

if sound-available = true [
    play-sound %c/windows/media/tada.wav
]

    ; Exit the program:

quit

]

]

; Here's another choice button which simply displays a little "about"
; message:

choice tan "Info" "About" [
    alert "Image Effector - Copyright 2005, Nick Antonaccio"
]

; The following line vertically aligns all successive GUI widgets -
; the opposite of "across":

below

; Spread out the following widgets by 5 pixels:

space 5

; Put 2 pixels of blank space before the next widget:

pad 2

; This box widget draws a line 550 pixels wide, 1 pixel tall (just a
; cosmetic separator):

```

```

box 550x1 white

; Put some more space before the next widget:

pad 10

; Here's a big text header for the GUI:

vhl "Double click each effect in the list on the right:"

; Advance to the next row in the GUI, and then begin arranging
; successive widgets across the screen again:

return across

; Load the image entered at the beginning of the program, and give it
; a label:

picture: image load image-url

; The code below creates a text-list widget and assigns a block of
; actions to it, to be run whenever the user clicks on an item in the
; list. The first line assigns the word "current-effect" to the value
; which the user has selected from the list. The second line applies
; that effect to the image (the words "to-block" and "form" are
; required for the way effects are applied syntactically. The third
; line displays the newly effected image. The "show" word is _very_
; important. It needs to be used whenever a GUI element is updated:

text-list data effect-types [
    current-effect: value
    picture/effect: to-block form current-effect
    show picture
]

]

; The following line displays the gui block above. "/options [no title]"
; displays the window without a title bar (so it can't be moved around),
; and "center-face" centers the window on the screen:

view/options center-face layout gui [no-title]

```

8.8 Guitar Chord Diagram Maker

This program creates, saves, and prints collections of guitar chord fretboard diagrams. It demonstrates some common and useful file, data, and GUI manipulation techniques, including the drag-and-drop "feel" technique, used here to slide the pieces around the screen. It also demonstrates the very important technique of printing output to HTML, and then previewing in a browser (to be printed on paper, uploaded to a web site, etc.). This is a useful cross-platform technique that can be used to view and print formatted hard copies of REBOL data:

```

REBOL [Title: "Guitar Chord Diagram Maker"]

; Load some image files which have been embedded using the "binary
; resource embedder" script from earlier in the tutorial:

fretboard: load 64#{
iVBORw0KGgoAAAANSUHEUgAAAFUAAABkCAIAAAB4sesFAAAACXBIWXMAAAASTAAAL
EWEAmpwYAAAA2U1EQVR4nO3YQQqDQBAF0XTIwXtuNjfrLITs0rowGqbqbrWxEEL+
RFU9wJ53v8DN7Gezn81+NvvZXv3liLjmPX6n/4NL//72s9l/QGbWd5m53dbc8/kR
uv5RJ/QvzH42+9nsZ7OfzX62nfOPzZzzyNUxxh8+ghfVHo94/rM49y+b/Wz2s9nP
Zj+b/WzuX/cvmfuXzX42+9nsZ7OfzX4296/718z9y2Y/m/1s9rPZz2Y/m/vX/Uvm
/mWzn81+NvvZ7Gezn8396/412/n+y6N/f/vZ7Gezn81+tjenRWXD3TC8nAAAAABJ
RU5ErkJggg==
}

barimage: load 64#{

```

```
iVBORw0KGgoAAAANSUHEUGAAAAoAAAAFCAIAAAABtV02fAAAAACXBIWXMAAAStAAAL
EWEAmpwYAAAAHElEQVR4nGNsaGhgGL6AaaAdQFsw6r2hDIa59wCf/AGKgZU3RwAA
AABJRU5ErkJggg==
}
```

```
dot: load 64#{
iVBORw0KGgoAAAANSUHEUGAAAAoAAAAKCAIAAAACUFjqAAAAACXBIWXMAAAStAAAL
EWEAmpwYAAAAFE1EQVR4nGNsaGhgWA2Y8MiNYGka22EB1PG3fjQAAAAASUVORK5C
YII=
}
```

```
; The following lines define the GUI design. The routine below was
; defined in the section about "feel":
```

```
movestyle: [
  engage: func [f a e] [
    if a = 'down [
      initial-position: e/offset
      remove find f/parent-face/pane f
      append f/parent-face/pane f
    ]
    if find [over away] a [
      f/offset: f/offset + (e/offset - initial-position)
    ]
    show f
  ]
]
```

```
; With that defined, adding "feel movestyle" to any widget makes it
; movable within the GUI. It's very useful for all sorts of graphic
; applications. If you want to pursue building graphic layouts that
; respond to user events, learning all about how "feel" works in REBOL
; is very important. See the URL above for more info.
```

```
gui: [

  ; Make the GUI background white:

  backdrop white

  ; Show the fretboard image, and resize it (the saved image is
  ; actually only 85x100 pixels):

  currentfretboard: image fretboard 255x300

  ; Show the bar image, resize it, and make it movable. Notice the
  ; "feel movestyle". That's what enables the dragging:

  currentbar: image barimage 240x15 feel movestyle

  ; Some text instructions:

  text "INSTRUCTIONS:" underline
  text "Drag dots and other widgets onto the fretboard."
  across
  text "Resize the fretboard:"

  ; "tab" aligns the next GUI element with a predefined column spacer:

  tab

  ; The rotary button below lets you select a size for the fretboard.
  ; In the action block, the fretboard image is resized, and then the
  ; bar image is also resized, according to the value chosen. This
  ; keeps the bar size proportioned correctly to the fretboard image.
  ; After each resize, the GUI is updated to actually display the
  ; changed image. The word "show" updates the GUI display. This
  ; needs to be done whenever a widget is changed within a GUI. Be
  ; aware of this - not "show"ing a changed GUI element is an easily
  ; overlooked source of errors:

  rotary "255x300" "170x200" "85x100" [
```



```

        currentfretboard/size: to-pair value show currentfretboard
    switch value [
        "255x300" [currentbar/size: 240x15 show currentbar]
        "170x200" [currentbar/size: 160x10 show currentbar]
        "85x100" [currentbar/size: 80x5 show currentbar]
    ]
]

return

; The action block of the button below requests a filename from the
; user, and then saves the current fretboard image to that filename:

button "Save Diagram" [
    filename: to-file request-file/save/file "1.png"
    save/png filename to-image currentfretboard
]

tab

; The action block of the button below prints out a user-
; selected set of images to an HTML page, where they can be
; viewed together, uploaded the Internet, sent to a printer,
; etc.

button "Print" [

    ; Get a list of files to print:

    filelist: sort request-file/title "Select image(s) to print:"

    ; Start creating a block to hold the HTML layout to be printed,
    ; and give it the label "html":

    html: copy "<html><body>"

    ; This foreach loop builds an HTML layout that displays each of
    ; the selected images:

    foreach file filelist [
        append html rejoin [
            {}
        ]
    ]

    ; The following line finishes the HTML layout:

    append html [</body></html>]

    ; Now the variable "html" contains a complete HTML document that
    ; can be written to the hard drive and opened in the default
    ; browser. The code below accomplishes that:

    write %chords.html trim/auto html
    browse %chords.html

]

; Each of the following loops puts 50 movable dots onto the GUI, all at
; the same locations. This creates three stacks of dots that the user
; can move around the screen and put onto the fretboard. There are three
; sizes to accommodate the resizing feature of the fretboard image.
; Notice the "feel movestyle" code at the end of each line. Again,
; that's what makes the each of the dots draggable:

loop 50 [append gui [at 275x50 image dot 30x30 feel movestyle]]
loop 50 [append gui [at 275x100 image dot 20x20 feel movestyle]]
loop 50 [append gui [at 275x140 image dot 10x10 feel movestyle]]

; The following loops add some additional draggable widgets to the GUI:

```

```

loop 6 [append gui [at 273x165 text "X" bold feel movestyle]]
loop 6 [append gui [at 273x185 text "O" bold feel movestyle]]

view layout gui

```

8.9 Shoot-Em-Up Video Game

This is a very simple graphic shoot-em-up which demonstrates important concepts required to make many types of 2D video games:

```

REBOL [title: "VID Shooter"]

; First, we'll set some initial values for variables that will be used
; throughout the game. The "random/seed now/time" function ensures that
; random generated numbers will be truly random:

score: 0    speed: 10    lives: 5    fire: false    random/seed now/time

; This line provides the user with some instructions:

alert "[SPACE BAR: fire] | [K: move left] | [L: move right]"

; When certain events occur, we'll want to reload a completely fresh
; game screen. A simple way to do that is to label the entire section
; of GUI code, unview the existing GUI, and then run that entire section
; of code again. Here, we'll label the section "game", and run it
; initially with the "do" function. You could also use this technique
; to implement a "play again" feature, for example. To do that, you'd
; simply wrap the entire program in a block, label it, and "do" it at
; the very beginning of the code. To play again, just do the label
; again:

do game: [

    ; Here's the game window:

    view center-face layout [

        ; Set some layout properties:

        size 600x440
        backdrop black

        ; Display a simple text scoreboard:

        at 246x0 info: text tan rejoin ["Score: " score " Lives: " lives]

        ; For this game we'll use some generic buttons and boxes for
        ; graphics, but we could just as easily use images of any type
        ; (simply embed the images in code using the binary embedder
        ; program, label each image, and then use the "image" word to
        ; display them). In the code below, the yellow box labeled "x"
        ; is the missile, the orange button labeled "y" is the moving
        ; target being shot at, and the blue button labeled "z" is the
        ; player's graphic. Notice that the target graphic is placed at
        ; an initial coordinate 50 pixels off to the left of the GUI,
        ; and at a random height between 30 and 330 pixels. The
        ; "as-pair" function combines the two numbers into a coordinate:

        at 280x440 x: box 2x20 yellow
        at (as-pair -50 (random 300) + 30) y: btn 50x20 orange
        at 280x420 z: btn 50x20 blue

        ; The following boxes are invisible, as a result of their "0x0"
        ; size. They exist here solely to perform actions when certain
        ; keys are pressed by the user (each box has a separate key
        ; assigned - their action blocks will execute whenever those
        ; keys are pressed by the user). Notice that when the box
        ; assigned to the "l" key is activated, it moves the player

```

```

; graphic 10 pixels to the right. The "k" key moves the player
; left, and the space bar is used to set some variables that
; will be used below to fire a missile:

box 0x0 #"l" [z/offset: z/offset + 10x0 show z]
box 0x0 #"k" [z/offset: z/offset + -10x0 show z]
box 0x0 #" " [

    ; The "fire" variable is used to track whether or not
    ; a missile is currently in the air. When the space
    ; bar is pressed by the user, the following code is
    ; only run when a missile ISN'T currently moving:

    if fire = false [

        ; Set the missile currently firing flag to true:

        fire: true

        ; Set the missile position to be centered on the
        ; player graphic, at the bottom of the screen:

        x/offset: as-pair (z/offset/1 + 25) 440
    ]
]

; This box is also invisible. It's only purpose is to enable a
; feel-engage-time routine. The box has a rate set to our
; "speed" variable, and the feel-engage routine checks for a
; given amount of time to pass. Every time that occurs (the
; number of times per second indicated by the "speed" variable),
; the enclosed block of code is run. In effect, this works
; exactly like a forever loop, but WITHOUT stopping any of the
; other operations in the game:

box 0x0 rate speed feel [
    engage: func [f a e] [
        if a = 'time [

            ; If the "fire" variable is currently set to true,
            ; move the missile up 30 pixels:

            if fire = true [x/offset: x/offset + 0x-30]

            ; If the missile reaches the top of the screen,
            ; move it back down to the bottom (out of sight
            ; below the bottom edge of the GUI), and set
            ; the flag variable to false so that it stops
            ; moving:

            if x/offset/2 < 0 [x/offset/2: 440 fire: false]

            ; Update the display:

            show x

            ; The code below moves the target piece. The
            ; random X and Y portions of the coordinate move
            ; the graphic generally from left to right, but
            ; in a slightly unpredictable path that is a bit
            ; harder to shoot at:

            y/offset: y/offset + as-pair
                ((random 20) - 5) ((random 10) - 5)

            ; Check if the target has made it all the way over
            ; to the right side of the screen:

            if y/offset/1 > 600 [

                ; If so, decrease the number of lives by one:

```

```

lives: lives - 1

; If no more lives are available, notify the user
; and end the game:

if lives = 0 [
    alert join "GAME OVER!!! Final Score: " score
    quit
]

; Otherwise, notify the user and refresh the
; screen (this automatically updates the score
; board and resets the graphics to new starting
; positions):

    alert "-1 Life!"    unview    do game
]

; Update the display:

show y

; Now that the graphics have been moved, check for
; a collision between the missile and the target
; (if the target and missile starting points are
; within the specified distance):

if within? x/offset (y/offset - 5x5) 60x30 [

    ; If a collision has occurred, notify the user,
    ; adjust the score and speed, set the fire
    ; flag to false, and refresh the game screen:

    alert "Ka-blamm!!! "
    score: score + 1    speed: speed + 5    fire: false
    unview    do game
]

]

]

]

```

8.10 Listview Multi Column Data Grid Example

This example uses the listview module found at <http://www.hmkdesign.dk/rebol/list-view/list-view.r>. The listview module handles all the main work of displaying, sorting, filtering, altering, and manipulating data, with a familiar user interface that's easy to program. Documentation is available at <http://www.hmkdesign.dk/rebol/list-view/list-view.html>.

Clicking on a column header in the example below sorts the data by the selected column, ascending or descending. Clicking the diamond in the upper right hand corner returns the data to its unsorted order. Selecting a row of data with the mouse allows each cell to be edited directly. Because inline editing is possible, no additional GUI widgets are required for data input/output. That makes the listview module a very powerful tool which is useful in a wide variety of situations.

```
REBOL [title: "Listview Data Grid"]

; The function below watches for the GUI close button, to keep
; the program from being shut down accidentally. The code was
; adjusted from an example at:
; http://www.rebolforces.com/view-faq.html

evt-close: func [face event] [
  either event/type = 'close [
    inform layout [
      across
      Button "Save Changes" [
        ; when the save button is clicked, a backup data
```

```

        ; file is automatically created:
        backup-file: to-file rejoin ["backup_" now/date]
        write backup-file read %database.db
        save %database.db theview/data quit
    ]
    Button "Lose Changes" [quit]
    Button "CANCEL" [hide-popup]
] none ] [
event
]
]
insert-event-func :evt-close

; Download and import/run ("do") the list-view.r module:

if not exists? %list-view.r [write %list-view.r read
    http://www.hmkdesign.dk/rebol/list-view/list-view.r
]
do %list-view.r

; The following conditional evaluation checks to see if a
; database file exists. If not, it creates a file with
; some empty blocks:

if not exists? %database.db [write %database.db {[[]]}]

; Now the stored data is read into a variable word:

database: load %database.db

; Here's the guts of the program. Be sure to read the
; list-view documentation to see how the widget works.

view center-face gui: layout [
    h3 {To enter data, double-click any row, and type directly
        into the listview. Click column headers to sort:}
    theview: list-view 775x200 with [
        data-columns: [Student Teacher Day Time Phone
            Parent Age Payments Reschedule Notes]
        data: copy database
        tri-state-sort: false
        editable?: true
    ]
    across
    button "add row" [theview/insert-row]
    button "remove row" [
        if (to-string request-list "Are you sure?"
            [yes no]) = "yes" [
            theview/remove-row
        ]
    ]
    button "filter data" [
        filter-text: request-text/title trim {
            Filter Text (leave blank to refresh all data):}
        if filter-text <> none [
            theview/filter-string: filter-text
            theview/update
        ]
    ]
    button "save db" [
        backup-file: to-file rejoin ["backup_" now/date]
        write backup-file read %database.db
        save %database.db theview/data
    ]
]
]

```

This example downloads the list-view module from the Internet, and then imports it from the hard drive. The following lines require that there is either an Internet connection available, or that the list-view.r module already exists on the user's hard drive:

```

if not exists? %list-view.r [write %list-view.r read
    http://www.hmkdesign.dk/rebol/list-view/list-view.r
]
do %list-view.r

```

If you want to use the list-view.r module in a script, without having to download it or include it a separate file (so that no external dependencies are required to run the script), you can replace the above lines with the following code. The following code *is* the list-view.r file, compressed using "compress read http://www.hmkdesign.dk/rebol/list-view/list-view.r":

```

do decompress #{
789CCD3D6B73E3C871DFF52BE6369592F67629905A9F73A6B2A7B2EFEC8E557
2AE738A96221551031142181040D8092B8A9FC97FCD474F7BCBA07038ADA3B3B
E6D56909CCABA7BBA75FD333FCB75FFEE28FBF538B33A5FE54F5B59EAB377FFE
CD77EA77BFF9FE4F933FFFE697FFA17E552CF51B28FD558585FF58575D3F79AC
F4D3650B2F7FBEEFD74D3B578B37BFD6DBB67A50BFAF1E0A5DABDFB6504D6F3B
BD7D9343B56F9BDDA1ADEED63DF47E359D7EF55EC1DF9FAA89F5F5EF7FABBD3
5D75B7C521BE6D75D1EB728EA55F4D665793AB9FC1DBEFE01DBDFAE9643A9B5C
CDE0D59F75DB55CD76AEA697D3CBABAFE1CDEFAA250E3757FF0D0F4AFDE2FBEF
D4C5D3D3D365B383D7CDBE5DEACBA6BDCB6A53ADCB6EBB72621F2E77EBDD5B6A
F5EF9D5645AF0E505F354F5B059378B88492FF81FFFF75DFEE1A1AE05FF456B7
45AD76E68D428C2042D453D5AFD5A6D81ED40AE6B16F75A7564DABF650A7DA2A
C0EA2576F487A6F760FE695D411D40AC827F8BC7A2AA8BDB1A619853F1BAEF77
F32CC379AC370F25E1E9B27CC85A7DDBD499A74426690218D39B4615DB52F5BA
EB9705CCF787765E428FAEF36609DDB59A7509B3DB140FBA6C965738E30DE0F0
F3A7D03FF79FD972DD6FEACF6B3A013AF44D7BF8FCC17D0F1608A4F4AFCDAB39
2D2EA5BED740F71FDC717E969F9D75FDA1AE3EE96C53C02A6BA97F6AB0AA740D
CBE7177FFC4FC38C66E00EAAC25279BE9AD2A32EEFE01109465FD5C294CF9E67
4AAF567A098BF4BCBAD58FB08C974D8DABFBEA27B0CACCFF3975317C4FAF57CD
161A6F9BADA6C75DD1167620FCAA164F6DB1BB99AB555177DA74B4AA8BBB0E10
4480ABEBE8BDD5A56A352C9EAD6AB693FD76D52CF71D30D86EDFDB165AD7B6D3
65FF3CE9F5739FE9B2EAD56D050C6F26ACA08BB22D9E60A8FD7609BD830853C5
B257B05E735745A96AA58ABA560B605FAA714ED3EAD46DDD2C1F6EE85D665EE5
2AB452AC60AE76D5F281D7343DFDF337808B65514FF0C9B7CCCFE4BFA5EE09DB
1E614A358FBA152FF4F6AE4072451301EA6C7B3695FA71AEEE748F2B713537F0
00CAA1CE24FEAECED9836FDF01BB2CD7D4359F69895290BF008080AF80E5F45F
F6456D70A4904DBFCCC284D562BFAD51DA1375F2A8036413A069B66D26DDBA79
A22EF2A886E9710980027A9AD5AAD3D05733A117664C4240668AA2C6BE57F69E
0F80388E60024ED836FDC44E8A8DFEF2E083D999BE6C276B40834145D7172D54
4EBE9EF321635CA841577A5B8A16F3410BF56AA4A5D12611C7BF3FE843CC18B0
0889E06C2CCF93C478C05DA0B463C41BA0B0BF8FEA1FDEFCD7E4CD00A382E506
70C3B2D7CFC089B8FC138CBFD5C349E1A78695D5AF6F469AC420E05250AB0C06
A9BAF584A69A980DA068A42148B663AD4E40B9141E3962D5C93F75DEE97A7566
CA480FE0DB97D48011D62448F1AB9FB2D50633608802D6BF91460A358EB6DF0B
6043B0BDCE6BBDEA9D2AB8AD8BE5C3590F015B29F8404BDE95B90726801BA8A
F4B62DB64102EE8AAA9D29FC7BA5B21A458E6AD50EDE5C0539B39BC1C8801F56
D7955C214CCF891298C2128C54B5707846CB0D2ACE32EC1BFEECC184F60D901CB
AEB0EC0ACB2A3024617DF7601201404537C1CEA18383A79B6A197A56FBBAB654
62EA72ABD9235374F8D50F6F5404D307CD63EB50B1024540A4EFD78AA019628
8EC019BB7ECC108AC952FB59505F7E56AC2E6958D7A06D9EEC0AC065411A3B51
543FF22500E353E78139A2D579ADBE47D1D5374DADFA6A37B27AAEDD572B4D08
AEF056D124091898172C0754E1386C59F4C5B5AA9BED1DC8DD667FB70E6D72D1
DEB49D23136BFE7E25D06DBB9F87CE79DD6BB009EAE26015231FC9F58EEC11DB
11A336422FF9023919987355FEC8EC615029308116D404451108F5B0922D4780
83B440003FAA733230ECF7A2063F039E39F1A5FDB4906C01E3A04C4517E48678
6C5D959AC46CCC3F25C377C43DB05AE67EBD9EA64B18ED784F82B194F80029B2
6E5DAD62AD4BA800C0417E832538D934A5464C6CF6755FA991F7B852621BC154
45C64A16401FBA9C80A4DE6FA4EA19DA66D0C0CA5B12876047EF61C2D63C8C20
1AEA3A03F86258A01C8A13255285C31868DA7878BBC41CC6E76B3E40D3C1FB7C
685779741E8518A47B18EEE8349C49319842B2769A8992A0C6CF4EC1396265B3
F0F52AAE6B5DE297523E22FE2719D92EC1A5075963586988BA8899527F48E34
E66BAA5F0DAAC7101DD3D2BC0E703294B6465727C8C1D5B7C302D3E202AE6C7E
1892ECB845878A0298B2AB6EABBAEA0FA0AB9461695528E43F80B05096B76F01
BFBAEFABED9D0279026F9BB6ACB6A0F8B0D527DD36D09769F5D4ECC1695E178F
9A6A3E633B57E9BDEAF6E8D07560F0FD945AD8EEA3468774A30FCF5368D46378
CA34D075B5B15040ABAD06371DF1EA56E135859B6E8B4EDB89811EEF804F6A5D
1FC09167B3E8A82621B8734380BAC3316E01E5A0C43072A61E4D84EFF2F2122A
B560FA57184E6BF5535B010CCD8AC020610CCF6D417643DBEC016DB1A9FF1253

```

0FC58BF5EA8792084898CD86CD9BBA9C5844CC5F12C5B1F21F679A11971C3FC6
2D77961559FC43AB8ABF068B2A9EB6D3B6A11F7C33D2575C34E82F02DD982FE9
6234188CC2DFEFD4A2450F83D011A935F20CFBAC6CF6A0DE27CB1A293270DA53
96C6005B29854CE4307D53D77C76290FCE2162A40914BD20A89C99B42A85D992
1BF50FF81AD82D273A82F41759095C3BE32E2146A7DC1B442E9EAB5FFDFCDB5F
7277705D8238873F93DB7E6BBEAC2A30DFFDD3B269B7DA96D65D4F7F262B0C2F
764B68A94BEEBB18A7F1C314BD4B034659B5FD01FD38E8D41AC5F89A50C71A8E
0423A7CF53E759CE7E32BDB4FFC7F14933F96B0A21BC574D59BEB7D2E73D88A2
E5C31D08846D6986A5E01C389B2C64A9AEAEE0DF0FF0FFD554CDBE867FA730CA
D7533EA20877960D88A08535F3705E18B76C3BEB037760A417E1C1B4EC76C512
24F9C4F600D2AE2D6D0D2A47D181C47322C60AA9C42B60C06AA9DD3B2814712
B27327D1B02B29AF4C90883FAF7551A2DFE69E3D19B0F15355F66B78E9FEDD3D
FB57A21E460BE09DFD2714451EA12FE80F3BCD2B3A478EFBF8655BDCFL1E755D5
33A601866BEA1ABA2778E6C8E293B536FB49369A0153F2D0AE2786E9A69C04C4
533C9EE011ED31081A0698CF2B8181562013C03D300EB66B99C38F9C402B9A55
5C4FCC3C78BD60557828E815DAD748DAA25B824B087FB60DBEB735820D8E753A
985DADADED8D7641B06B0DB083568E1179479E0CBE5F7AB0668A2D78B4BEA7AF
87EB1B57406818E60012C01802AE529899E5830AC39FBD9E60012337185DDB3E
3069C096779E85C6F55F3CA64D1D74970DC5AB12D06B14B7571782DB802ACDD3
0D0301390CB51217713D182E456BF8DF8AAACEED0F57A93B9A2CC44417EFC685A
B1240368821EBE67946AB323BC19B7DFB8B6CDED3DE0FC8BDC3976A6A67E3635
8D00B390D1046CFDC00F2BD68C948799C06351EFB5FD3E658BC58DDE7DCA9DE8
EE3EA9FD0EA071513EC26D2C3C0DC2A109AD0858CCADCE1764368096C9D9F085
E5A028463457914982032455B30B8E0F43B7731545652DB1A901ED019168BE71
B063549F74387ED19B1DA837921F14EE777B466635C05B9884D54EDBE2B1BA33
162A228BA4F699957250DBF0AE208D0B789B31409881890B4BA5459F60E1D97D
C6E2210497F351C3CA083ECB2CC4210DF2199D77AD7E044FE74E7350E8253C67
DD43B523CA077E60CD8C394B3CC06AD21F1B7B22D670ABE1D3DC4D2E5426BEC9
171EC2E45CFC4C8FE286194CE8F3CE5C733581A1830565D5368260FC4EE674BA
165B7D87DE4E34E724FEB6A0EFFE8E118181021B9948CCF39DC40C6B6807409F
F8E638AE60C94B039B0CA15091DBB1B2E2098460E025CDE0117AC4FCEC8834CE
CFA4B35F5A8C0CC085503C6C62FEFDA9241A92274D9131B40A1C48CF00DDF63E
E84A3133E79378960739B64293F9668C18E8AE582CF1419CA524442522E5C637
74C2D020011110C942B22C3986AC85967AF7E68D159F5444115CBB3B445B1F45
DF23CA7153268496785CA971E6B9EB5CA24720250CE2E722DA5AE3CDC7C5C40B
D0D467D7185AA76885896C204B6816F2C0221E1B6A566AB9060B887044639890
09E86B1B13DAB8584EB7D3CB6A552DCF184060FE16308752AF0A30032795AAD4
93B23C073A1BDEA9BB8961B8208E1273F17112CBC481A45110DDF536F76C0C64
DA156D87012BC7ED92F7597E83EFD75A3BE5153B138AE0943B4606DD8E7B6EA
3168B5D9C36AB8B586EFAEAE2815E9F6A0BE668DCD8C9D0B65FE1502C8E3C95A
74A6EF2FD48587E79DFA1AD44778CE32F5F5DBB7AC9327675B9ACF7EDB5771C0
C186172DFE9F4419347F8241645CE909D0E0464C8A3FC4CB1AD882B2AF688582
58DB217291BD040676BAE8D5BDA74E620FC42DAE0D2C422ACFE6F7A2821FCB32
5E0992B332CB371ECF8FB8DD6F025117B80B43CBD070C05D36C772B76D5A61ED
28A4042D2AF5D1E16C9065E11C38CFE7D76A59EBA28546CB624F296FEA767FF7
45DC8E057A39D72B3961117A11159964B6EBC46B22F9C28A3C63E1C29C6F982F
61340FD9E4B45A2B34B0D9AE2D17246CFD71A33320049D7A87F42A22339FEE22
57D508AC8AC61F59F9CCED65A30201B878E5110BDEC2D77F990F39AC088EDF61
B01C99CD2B68EEDD767833B40622D43DF72D98F699A1309F8EF74D69E311FC6B
0E08D62033C180F121AD8C7DAD0CEC608DE22EAEAD3EA82B8FEF0017D79CC0DD
DA7182D0CDE958C3D0B33E3781015BEAF9CAC9F5A6D5C572AD7618D1B3992DB0
AE761939A038771B0004D599B9E01A59330EA1C695F3DD4596965D18C69F264E
76695D47795918440CF56E071577454DFC30693BE5AED4FAF061DAF9822FC7C0
AB2BD1E7C0D4A0CDFE68044669320DA6ECC549B60AB7DB22B2707EADB6A8E131
C6C22C9484C0712D6C7A99CB9E5B10FF2C5B698EF513670C58F73C9A550A7801
35233B6754D7AB60D5CFB0DC1203B0488065A5AECE07A66A6C63FB67261E1306
32DFB5065A9F47B2292E268BE27829C622BC07C2B229B8B91D7AA8A5B01C1AD6
BE2AF11ABA6C5D0D56C74C0DCA2ED0B18542E3BB7917E62DD4F60F9CF1FD4BF5
CF293770C0E7173878D4390BFFA4C761E2D7B063C213B125B19C5BB61925EBDE
B1E132EBBD8761596D13B2B5A222D40061163A584CD9EAC7C964EA8255655378
EB40A7D5C40260D65F212DD56AE061FD888934D269B983395525F33E141E0950
6BD5AACCA833B1EC2CD020F25ACA44B6CF6BDC47F05E86CC51764ACB7A23CE2D
C128412E144988B1D9B622BE27CC1EAB149652693371298D060B028B88A9055A
F630F7A706B733845AE425C6BB37BEC052A62E79E57E6EF7334838F019216ECD
EEA009AA50DA6E46CE13A2296B8B27836DCC1DED5C90A562C94D481943211548
83EDA1692457AA32BDCCC7177F3ED45B0407C70560DFBA15946492D35E3BBC34
FBCBC45A3030BCC817FC4D6A870FE506470771B3C2A473B4C9B7C5C687992AB5
020F9E6121E82E2C988B7C2CA9908D491645336C151C49088B39EDB954E5B303
E0251F0864E0C0CF21B51C99E88620B89EB9A5684CBE2A9B2FCD42476A8477C3
DDEDDAD98DACC947DE8B410646FC4FDA755DFC75A7E7E7C418213929371356EF
B55389498BCD5934ABB2769E5B81F9629874189628EEF839A6C4EFE873F4FA4E
B75F2894015FE4E935FB43576BE40E792916BDE7ABD487851856088B769E045D

550A0C5A0CE14C6E949BDE88D783C539E1E0F8663D0E47C2D4DA39E0B3B6434B
874D84362CC54C705B1C98ADB8055F6B7F4B4E8E15B62673890285F495B58141
61C8A26D8B0328A7AAAF800005A6440D5ECD22638D32BF5CF6D884F1F8C0EB34
C30B0C3798028E683610D87E600D5E415738BC7F31A317720551CBC0EBAC7168
C63C2E33865732DC9F357FF7DBEA2F6006D02AF26143E7DC1A86054C7B12F91C
3026EBB0EA541A089B625BEDF6F56093E7FA69ADB78ACE7850ECAE51C56EA781
7188B2A815BAF783F01625B35486951FB6CDD3F6CC420EFA85897F162EC06966
A5D63B91836AB7A4C82B256EA56F4E397F2114987094A9DE95BACACD300C7B16
0B0E0AEC273FB222A8DC34C4D08C33508C056769E31345507C7187D26E72922D
C2359F053A48152F70722660F84B436C332D2F78CCAC5E237D52BA32B299B266
5B9BE88430503B3C1185275C089F0BB40878166FBC8FC71640E5E271F0850F51
F4CE584889AB53064D1C476384907E2292C3BE49C84A41282BD88241CC082199
96A68A35CC04F19B353CDDE4F095E5DE882BECAE38AD2561240A52A38F4CE61B
2333C321D9B7AFA5D57124F9436DCC4B37091461DF44B96DEE0446B949309CA8
C0AD014FC8BCD084B5F07B1834F82E79C7F4CFD10883E7DF57D96A6776ADE33
BF0181F1FD0B7243003E60CA48A362266BA57C01E60847E39106626E73F58A45
3304C546390C3C0696FF5DF00A160EB93D6525E91A8B1202D1F0FCE974E99B5D
208EEA37BBD74BC401950C70B188526C41052B07C70FA20EC6B72A61C41A0B3C
1897041561973F55800E99A1E2332D7E54996769312EF3E88899957C562187DC
1C2FAEB1D28D211A530586299DE3EF2403F504FC69867E993F5FCDA77C4E824F
47E660D394D3E7426C6ADA8277EA4D2A3735675AC5873C38BF28E3418B7E5C7B
1749A0FAA1813DB8B229A381B5676CDCE819C50DB198B2F56CD8758E5CE92B7DD
68B7E36FBC729927E5162FB7070377894805338209E6E15249AC6CBEB6DD58AC
7020D85919559FCDFD1439432797A544BAD3DDE9840E11CF922E1057C3C1BDB3
21AA45225665F3F386F915CC8BE3397C30A0B75D9CCD5236A28AD844BC568F55
B707C8305B2D913CE113C8BD7EB65C8A94B2AC22AD2F80CDC714831B50BAD3E1
D9811F2ABF007320034793D21BD155C90E6FD597917AF2F5CD56A2A5CEB8AB18
9DAD10994700076E56A177679289F91BE33E1063924CB299D150946012B266A0
35E74F244A2C6C16836C5FE34F4B2843BFE65E0A02C2C12642FCA307C04238CD
4891A6CEE3B15302C41F6DB44103494D966EECBC94B2A76305FCB02CDBE37D91
3A7E5222E627D57B847D778C34428A3A1727829920F5960C3757CD5405C924B0
3C1CE597875DB9D52772C1CFAC4752E1166AE9F6932830ADB4DFD190F9DE5671
82392C93E473B99C43028CF062995D938A4A0524CACCFEA32EA5B29D9BDAB380
B854969E066C22774E17E178E4FE47F380F8345FB7DB0AC6F2656F5A8325F9C
FF61BFB9D56D8EAF29C45FE6A22711715C48F8C73D4F8FD95826C4E717068723
5C0F03B2C930B71F405662684874408E45FC7214027FC0A772795282BD727429
C4F18263F2C5C34B67278008E608050D7E82AA3A37572A78E7909F1C89B33B2C
EF8D4AE3646249A8C73D4F3B10CF32E1D62C71E1EA98DC7701EE792296B452C9
A18CC8853629EEB25FAE69DF05A551A7F63B9EB04467A0CC150B8538CB6A8E25
893CB5E8FA0CFC981B1B245AF3D0353B50951AC31E02E015B99149679FAEA697
F67F26C5DB08B2D13354B3A367A8D8112A09F628C429AC9849B83C92085B5702
5D43608E4D6AB53201EB10DCC413294F32B8ACB7E6100521109F9ED6783E74D7
D487BB66AB3E3C7FA5FEE979F613359B3D7F95AB555DA50C49B29EC879227E08
D728C834109F2ECBF2A1C82202E0D5479EB1131FABA75A0EEFC619269480381
8C394994D9C5D99E58CD62062FEC8A7788E8A8D08BCDA691CC16FB3B1235DCED
C1E38011910677C888C32CEEC80B6344220FB3A246EE38210618BDD522CA2147
9D1BAE8148DE0171C269DAE86590586B963B45F45F0FB3A7D6E9E4293619BBD3
662E0A434C0A3E1AA49033C0792DC76E897A2E5B5F1CAA4A9E759747CC44963F
26C9B3D291E636E530D4CB1751C32102F00384B2E96A6EB91C3922363AF65866
9CFA421102B3D7D2FD4E088821837003C02DDF124C3735CA06045C1431A4021
298EAAEE3CF1A1F45C6622000C63016BF19EE47BB23E47FDDC5F312C5C74D5099
5278ECCE99780A8610A0EFB2E8CC71546F98DA673ED2F71F643A8AA9D9E4C853
3301D31355F20C88ADB248CC43E87D0B86BBF6DECEE9FA3CA81DB0EFCDD4F867
9810A1F9E75A129C978E98177F3BCD732A070EB8E35416F416BA4F0570A6BA5F
7B3380CE7EC7088A586F516F2F2DB6E309C8EE33B62CFEDF79946E327895C53F
9B82FD320D0C66E360AFE0A7976E6C93A41F879DB22729A849BD6058C408D373
7740DE2DC4936BD22D0E27A2C344E258524874619D2352946206D07B3FCC8769
B4BD65E03D2E6573BE89EE13F03EEB2ACA9D32EEB0BF92C0BF0F171760F254A2
D0A4BE7EA344BEEAF0AE04AC928CD971E20CA0727045E35A4F3631CA29033306
1043B9EB0D4400402C9191D06ADF4C4ABDAC36C06E33958DD44A98FCEC0208B2
3CA2595EAB6F8B7A89592FDA5CE3B36B9B9D6EEB43387333081E5852456E9585
CE15632C510A430F0914CD150B4985065FAA0B8A4C3FE359DF656BC2D4CF6F8F
2EAC231435DC98202815847B30CC55BFF0658C6AF69A8C74D4262294B95380DF
33C0AF2BCA8FB0AFA5D00849F9ED1E434AFA38893BE06F73A42FAE00A9249629
513A28798BDBB96D9039C3C4E4725B2AC83B3B82F4CDCC18F13D6AAE2B41BDB8
F400A545C977885C06B5BD5AC35D28E086CD17C2D4C5E1FDFFE4614008B2383D3
7CE1A77AC8D5D9708E073F9DCC9D29E4B790940DB27F8D4A0A99071CB34D666E
88C753769EA3D59B45FE4699FFDE29275C07F3F2B340D9CE261140C0847D363F
D9A078AE00A4F367F9D64CC46FC8FABE9E5F85D735CBE12FAB478CDE8BA5C8DA
BD65180AB75BF20E180CD978378E73176BC72C74BD0B5394160FF3D4E4049A24
C2317ACB639F830D82F9405E244F1B470B3B0A05B3B80D5E0410401B179C815F
0601D3D4360648A58FAEE3E01F6B8F81C9182A94E16AC5D1215DDA744A4173A


```

0B44C6432701F10B77330F7B3761B5638327488D49DDD85D9CBA41A3059EC174
EA76E2EC4DD8A484118A43B3EFB31E2F09F2E72EECA52E74EB187D93A7EB1B7F
B9D2867ED801CCF5B6E93ABA4148AB29D83BA5BA70FC3475170B6587B75CC6BC
669F132F27F27288A784C76D4018B9D19EA5552C2E2E6C02E8297B9CEE8AF613
E04C812B6CC7AE557A1B351733879A5359211D3B245630141F1CEAF68047F09F
0740DD70B68700DCC8607593E0EC24E5DDD551C35DED3CA1B96D7A496C100CE8
CC7B4BDC21BE6284FE26DC3E4E3684B938CC98110BFA472C549A5DD43BBA71FC
22226134A4AFDECB532BC5FD8E81B8A82C360C643023664EB33C5DEFC6297039
391866AB31AEB7A42D6912F56C5FC6A43A27F66ED59038CF0941C96E28129917
D7E682CB0298A279C0AD6AB44F2F2F2F55853BFF7A0336F11A89D753B3ED3970
5B4919327D43BC62B1115C9F607132859B2538289260FCDE24016130D68F5E12
42671812DBBDB2B615D78B5C1C334EB88F99BBE8C8E510ECC51E073FABCE12C5
EC3484E1ED4EE281898867F5A6FC24DEC849445256F66A6D33F4E0F021BD662F
A354D944C8E9874FEA07D969C61EB6C684E5D0F064EF1032470F112D9E7F317D
66ED7028BCE77006915BE6369BC25FD5FD6AF56674A6DBAC948A8D25D9BD4279
71C96D35725AFB6845FA69189444E8C599E993ECFD2DE5A226BDB8C274639418B
B2081D3F283E32197F4011955F42FBE6128A1CAF47F7911017FFD62C91468F0B
EC452E486DE4452C5CBC0B228ED80E73F030C9F0661E3CC79642328B9C4B562B
F5C55D96B1D2C45B356FF8A1DA4EE3B593FEB64B71F7A5B703F91D98D28CB56
DD7EB7031292D4A72546DCCFC0323CCE226546B2D958D9D25DD5A11E14B8E094
CE4363A121B8B037ED90187FB257148338DF14DBE24E2BF30B01F67783FCE599
78B930ABBBAA4DF1FB387663BB56A9B0D9DD1F189BAAD06389650B969F15663BA
D5A7061FC2A30E80999FE4118CA47C053E3672F646258E69870D032C7A27CE88
F35F352247801F8B26D78588CD6FB35E3A7D11AD5B42F05C3DC8BB0F5E6FF98C
5AB9C376E3762E7422564454780F168C1328713BE62D5F18A4E0C1FA2FA1C0A5
324E822D1F3576D9825E8724F6706C9D207EEF990A20240EB7B42C6E0D0FBF53
F7CE1B7A0790A406F04702FD28C221B3275B1D77A1F598DC3FBD7A6D4C0FA1F
D47E69F7EF5E0A9141FBA389E1AC9A4D114F148D5DD6C1B0E5978ACA64D74FD
F88A3628553EAA9897CCE7B4DD5539BB23E3EAF0430C7414D6C8D8674F4D12EED
4C928D6D8EFCAB710F7DFE60AAA4CE469F363A8DF31934B5908FD2153FE96D79
FCF09BF1E4EFO354AF8021DDFFA91CC54E2AFCBDD2ECF55CFD778C7190A2FCCA
6E7B4D8379F0E64896A92B3CF91F374F8A6D160F39A60A53E2DB0B5CFB0554D8
F4F2672F4869BC77AD2EEE68F01BB09C283534D13968F987C1F505665493E87C
0AC2EF333A6D3156683610EF33F6E357DE547A318DD97CA2E3E02966F309E90F
6A48CFD13EC7BA1B76319ADC556DC0D0BCB1F31C51BF6E83DB7A4A36AF31C9A1
836447FEE9613D74B4F3767171EF3C2833B2D9AD51C0947114CF7D08507561AA
A72B9D2A901C51937958496CDF67C90C8DF039F2334A7CCC6491BB5A3E59C842
5847BAB8E8FD5D4DF16F28DE7BF9E3EDB5D9576FD1C41E41B45BDDE11ECCD181
D3F61A4D96FD289E885F0C71028BABC1DB9B306376873F37190FACF026E40FEA
CDE5E5E59B14100B391CFBB13E51EDA8CC89B236AC91CD2FED272BD7DADBEA5D
D499F77F702D8B3B9D7C9B68574FB91F8CE5E1597E5AC216B3E89559E3E9081E
17E52C5469F60747829532403A7AC82058FDEC22753301EB52F1CB9AA36E5E19
92F1B93FE4F2BA5CBB74842699DB4BC4A02C908BE46F05BF9C5A2E458BDB90F3
FB08C6F989B6120C1B5F444C11F8D89D3B21A12D31342697AD128ECE77708259
95915E83E18053BE8882F212744A328B21E730F0C4F1D9689C2A0505CCBAAEEC
A55A3CCF7CC10B6437831D0409ACA1E345FAE7CC1C835AE039ACA3BC1D4F182D
45BA50BAAEAFD36722EB614019F21203A9029B266483B381C9954AB6BF3FBF12E
B7342D1106EE7733769BDDF806D6F1A5E6CE738CAC37897C374498E2EB174E1E
4FC9F49998D25D7DD8213D8A5ADBCBFEE4DE3A0703E4E387A86151DEEFBB7E98
BF11FF480BDA1FE2AA2096397218141EC766480A8DED26F6D3994E86452AF214
E41DC926FD31456044F590E6324279D795E49DA459586CC12D04AD547438E1A8
707848067FE8C8FEEF8ECA446D2EA6CF138C91316E01A6E22C10DB8D17B3E7E9
EB1AE0B190573598BC6E88B1132DFEABE334BF5DE95E881A2E62166568BC2EC3
5D1E3C58477B73E62F9A16738CDBDA63ABE6ADB928D59FEB8661CDB924CBFA89
7B1DF88657E2AE3FEA810F3308FCBB94499F3EC92BF39B56E2B38FB875257E31
96D241F19761DCC656986F7E969FFD1F598CCF767B840000
}

```

8.11 Thumbnail Maker

This program resizes and arranges a list of image files into a single preview image. The screen shot image sheet at the beginning of this tutorial was created using this application.

```

REBOL [Title: "Thumbnail Maker"]

; Create a little GUI to allow the user to adjust image settings:

view center-face layout [

```

```

text "Resize input images to this height:"
height: field "200"

text "Create output mosaic of this width:"
width: field "600"

text "Space between thumbnails:"
padding-size: field "30"

text "Color between thumbnails:"
btn "Select color" [background-color: request-color/color white]

text "Thumbnails will be displayed in this order:"
the-images: area
across
btn "Select images" [
    ; Select some files:
    some-images: request-file/title trim/lines {Hold
        down the [CTRL] key to select multiple images:} ""

    ; Error check:
    if some-images = none [return]

    ; Show the selected files in the area widget above, with
    ; each file on a new line:
    foreach single-image some-images [
        append the-images/text single-image
        append the-images/text "^/"
    ]
    show the-images
]

; This button creates the output thumbnail mosaic:
btn "Create Thumbnail Mosaic" [
    ; Set sizing variables to the values entered in the GUI:

    y-size: to-integer height/text
    mosaic-size: to-integer width/text
    padding: to-integer padding-size/text

    ; Set the background color (white if none selected):

    if error? try [background-color: to-tuple background-color][
        background-color: white
    ]

    ; The list of images that will be resized is stored in a block
    ; labeled "images". The "parse" function is covered later in
    ; this tutorial. The following code simply separates each line
    ; item in the text area above, and returns a block of all the
    ; items:

    images: copy parse/all the-images/text "^/"

    ; Error check:
    if empty? images [alert "No images selected." break]

    ; The output image will be created from a "view layout" GUI block.
    ; That block will be labeled "mosaic" and will contain all the
    ; resized image data and layout formatting needed to create the
    ; thumbnail image. We'll start building that block by
    ; including the background color, spacing, and "across" words
    ; needed to layout the GUI. Because the block contains some
    ; variables, we'll use the "compose" function to evaluate them
    ; (treat them as if they'd been typed in explicitly):

    mosaic: compose [
        backcolor (background-color) space (padding) across
    ]
]

```

```

; Next, we'll use a foreach loop to go through the list of images,
; read and resize each image, and add the resized image data to
; the mosaic block. The variable "picture" will be used to refer
; to each image as the loop progresses through each item in the
; list:

foreach picture images [

    ; Give the user some feedback with a litte message:

    flash rejoin ["Resizing " picture "..."]

    ; Read the image data, and assign it the variable label
    ; "original":

    original: load to-file picture

    ; After the data is done loading, erase the message above:

    unview

    ; We can refer to the size of the original image using the
    ; format "orginal/size". That returns width and height
    ; values in the form of an XxY pair. To refer to the height
    ; (Y) value only, we can use the format "original/size/2"
    ; (the second element in the pair). If the height of the
    ; original image is larger than the "y-size" variable set at
    ; the beginning of the program, we'll resize the image so
    ; it fits that height, and append the resized image data to
    ; the "mosaic" block. Otherwise, we'll simply append the
    ; original image to the block. We're also going to include
    ; the "image" word, because the "mosaic" block needs to
    ; include all the functions and data needed to create a view
    ; layout GUI window:

    ; If the original image is taller than the prescribed height:

    either original/size/2 > y-size [

        ; Figure a percentage amount the width needs to be
        ; resized:

        new-x-factor: y-size / original/size/2

        ; Calculate the width of the new image size, and assign
        ; that value to the variable "new-x-size":

        new-x-size: round original/size/1 * new-x-factor

        ; Create the resized image by using the "layout" function
        ; (as in "view layout"). Specify a new size for the
        ; image by rejoining the "new-x-size" variable above with
        ; the "y-size" value specified earlier, and convert that
        ; value to a pair. Create a new image from that layout
        ; using the "to-image" function, and assign it to the
        ; variable "new-image":

        new-image: to-image layout/tight [
            image original as-pair new-x-size y-size
        ]

        ; Next, append the resized image data to the "mosaic"
        ; block. We'll compose the block because we want the
        ; new-image data to be included as if it was typed in
        ; explicitly. The word "image" also needs to be included
        ; because that's needed to show an image in a view layout
        ; block:

        append mosaic compose [image (new-image)]

    ]
]

```

```

        ; Here's the second part of the "either" condition above.
        ; If the height of the original is less than the "y-size"
        ; variable, simply append the original image to the
        ; "mosaic" block:

        append mosaic compose [image (original)]
    ]

    ; As the current foreach loop stands, each resized image is
    ; simply added to the "mosaic" layout from left to right. We
    ; need to check the size of the "mosaic" layout every time we
    ; add an image. If the layout is wider than the width we set
    ; at the beginning of the program (the "mosaic-size"
    ; variable), we need to insert a "return" word into the
    ; "mosaic" GUI layout block:

    ; Create a temporary layout of the "mosaic" block:

    current-layout: layout/tight mosaic

    ; If the width of the current layout is larger than the
    ; prescribed width, insert the "return" word BEFORE the
    ; current resized image. A tick mark is put onto the 'return
    ; word so that the actual unevaluated text "return" is
    ; appended to the mosaic block. "back back tail" puts the
    ; "return" word in the correct place in the layout block:

    if current-layout/size/1 > mosaic-size [
        insert back back tail mosaic 'return
    ]

]

; Prompt the user for a file name to save the final "mosaic"
; layout image:

filename: to-file request-file/file/save "mosaic.png"

; Create an image from the final "mosaic" layout block, and save
; that image to the file name above:

save/png filename (to-image layout mosaic)

; Show the user the saved image:

view/new layout [image load filename]

]

```

You can use this program to quickly resize collections of photos for email, web sites, etc.

9. Additional Topics

9.1 Objects

Objects are code structures that allow you to encapsulate and replicate code. They can be thought of as code *containers* which are easily copied and modified to create multiple versions of similar code and/or duplicate data structures. They're also used to provide context and namespace management features (i.e., to avoid assigning the same variable words and/or function names to different pieces of code in large projects).

Object "prototypes" define a new object container. To create an original object prototype in REBOL, use the following syntax:

```
label: make object! [object definition]
```

The object definition can contain functions, values, and/or data of any type. Below is a blank user account object containing 6 variables which are all set to equal "none"):

```
account: make object! [
  first-name: last-name: address: phone: email-address: none
]
```

The account definition above simply wraps the 6 variables into a container, or *context*, called "account".

You can refer to data and functions within an object using refinement ("/path") notation:

```
object/word
```

In the account object, "account/phone" refers to the phone number data contained in the account. You can make changes to elements in an object as follows:

```
object/word: data
```

For example:

```
account/phone: "555-1234"
account/address: "4321 Street Place Cityville, USA 54321"
```

Once an object is created, you can view all its contents using the "help" function:

```
help object
? object

; "?" is a synonym for "help"
```

If you've typed in all the account examples so far into the REBOL interpreter, then:

```
? account
```

displays the following info:

```
ACCOUNT is an object of value:
  first-name      none!      none
  last-name       none!      none
  address         string!    "4321 Street Place Cityville, USA 54321"
  phone           string!    "555-1234"
  email-address   none!      none
```

You can obtain a list of all the items in an object using the format "first (object label)":

```
first account
```

The above line returns *[self first-name last-name address phone email-address]*. The first item in the list is always "self", and for most operations, you'll want to remove that item. To do that, use the format **"next first (object label)"**:

```
next first account
```

To iterate through every item in an object, you can use a foreach loop on the above values:

```
foreach item (next first account) [print item]
```

To get the values referred to by individual word labels in objects, use "get in":

```
get in account 'first-name
get in account 'address

; notice the tick mark
```

The following example demonstrates how to access and manipulate every value in an object:

```
count: 0
foreach item (next first account) [
  count: count + 1
  print rejoin ["Item " count ": " item]
  print rejoin ["Value: " (get in account item) newline]
]
```

Once you've created an object prototype, you can *make a new object based on the original definition*:

```
label: make existing-object [
  values to be changed from the original definition
]
```

This behaviour of copying values based on previous object definitions (called "inheritance") is one of the main reasons that objects are useful. The code below creates a new account object labeled "user1":

```
user1: make account [
  first-name: "John"
  last-name: "Smith"
  address: "1234 Street Place Cityville, USA 12345"
  email-address: "john@hisdomain.com"
]
```

In this case, the phone number variable retains the default value of "none" established in the original account definition.

You can *extend* any existing object definition with new values:

```
label: make existing-object [new-values to be appended]
```

The definition below creates a new account object, redefines all the existing variables, and appends a new variable to hold the user's favorite color.

```
user2: make account [
  first-name: "Bob"
  last-name: "Jones"
```

```

address: "4321 Street Place Cityville, USA 54321"
phone: "555-1234"
email-address: "bob@mysite.net"
favorite-color: "blue"
]

```

"user2/favorite-color" now refers to "blue".

The code below creates a duplicate of the user2 account, with only the name and email changed:

```

user2a: make user2 [
  first-name: "Paul"
  email-address: "paul@mysite.net"
]

```

"? user2a" provides the following info:

```

USER2A is an object of value:
first-name      string!  "Paul"
last-name       string!  "Jones"
address         string!  "4321 Street Place Cityville, USA 54321"
phone           string!  "555-1234"
email-address    string!  "paul@mysite.net"
favorite-color  string!  "blue"

```

You can include functions in your object definition:

```

complex-account: make object! [
  first-name:
  last-name:
  address:
  phone:
  none
  email-address: does [
    return to-email rejoin [
      first-name "_" last-name "@website.com"
    ]
  ]
  display: does [
    print ""
    print rejoin ["Name:      " first-name " " last-name]
    print rejoin ["Address:   " address]
    print rejoin ["Phone:    " phone]
    print rejoin ["Email:     " email-address]
    print ""
  ]
]

```

Note that the variable "email-address" is initially assigned to the result of a function (which simply builds a default email address from the object's first and last name variables). You can override that definition by assigning a specified email address value. Once you've done that, the email-address function no longer exists *in that particular object* - it is overwritten by the specified email value.

Here are some implementations of the above object. Notice the email-address value in each object:

```

user1: make complex-account []

user2: make complex-account [
  first-name: "John"
  last-name: "Smith"
  phone: "555-4321"
]

```

```

]

user3: make complex-account [
  first-name: "Bob"
  last-name: "Jones"
  address: "4321 Street Place Cityville, USA 54321"
  phone: "555-1234"
  email-address: "bob@mysite.net"
]

```

To print out all the data contained in each object:

```
user1/display user2/display user3/display
```

The display function prints out data contained in each object, and in each object the same variables refer to different values (the first two emails are created by the email-address function, and the third is assigned).

Here's a small game in which multiple character objects are created from a duplicated object template. Each character can store, alter, and print its own separately calculated position value based on one object prototype definition:

```

REBOL []

hidden-prize: random 15x15
character: make object! [
  position: 0x0
  move: does [
    direction: ask "Move up, down, left, or right: "
    switch/default direction [
      "up" [position: position + -1x0]
      "down" [position: position + 1x0]
      "left" [position: position + 0x-1]
      "right" [position: position + 0x1]
    ] [print newline print "THAT'S NOT A DIRECTION!"]
    if position = hidden-prize [
      print newline
      print "You found the hidden prize. YOU WIN!"
      print newline
      halt
    ]
    print rejoin [
      newline
      "You moved character " movement " " direction
      ". Character " movement " is now "
      hidden-prize - position
      " spaces away from the hidden prize. "
      newline
    ]
  ]
]

character1: make character[]
character2: make character[position: 3x3]
character3: make character[position: 6x6]
character4: make character[position: 9x9]
character5: make character[position: 12x12]
loop 20 [
  prin "^(1B)[J"
  movement: ask "Which character do you want to move (1-5)? "
  if find ["1" "2" "3" "4" "5"] movement [
    do rejoin ["character" movement "/"move"]
    print rejoin [
      newline
      "The position of each character is now: "
      newline newline
      "CHARACTER ONE: " character1/position newline
      "CHARACTER TWO: " character2/position newline
    ]
  ]
]

```



```

        "CHARACTER THREE: " character3/position newline
        "CHARACTER FOUR:  " character4/position newline
        "CHARACTER FIVE:  " character5/position
    ]
    ask "^/Press the [Enter] key to continue."
]
]
```

You could, for example, extend this concept to create a vast world of complex characters in an online multi-player game. All such character definitions could be built from one base character definition containing default configuration values.

9.1.1 Namespace Management

In this example the same words are defined two times in the same program:

```

var: 1234.56
bank: does [
    print ""
    print rejoin ["Your bank account balance is: $" var]
    print ""
]

var: "Wabash"
bank: does [
    print ""
    print rejoin [
        "Your favorite place is on the bank of the: " var]
    print ""
]

bank
```

There's no way to access the bank account balance after the above code runs, because the "bank" and "var" words have been overwritten. In large coding projects, it's easy for multiple developers to unintentionally use the same variable names to refer to different pieces of code and/or data, which can lead to accidental deletion or alteration of values. That potential problem can be avoided by simply wrapping the above code into separate objects:

```

money: make object! [
    var: 1234.56
    bank: does [
        print ""
        print rejoin ["Your bank account balance is: $" var]
        print ""
    ]
]

place: make object! [
    var: "Wabash"
    bank: does [
        print ""
        print rejoin [
            "Your favorite place is on the bank of the: " var]
        print ""
    ]
]
```

Now you can access the "bank" and "var" words in their appropriate object contexts:

```

money/bank
place/bank
```

```
money/var
place/var
```

The objects below make further use of functions and variables contained in the above objects. Because the new objects "deposit" and "travel" are made from the "money" and "place" objects, they *inherit* all the existing code contained in the above objects:

```
deposit: make money [
  view layout [
    button "Deposit $10" [
      var: var + 10
      bank
    ]
  ]
]

travel: make place [
  view layout [
    new-favorite: field 300 trim {
      Type a new favorite river here, and press [Enter]} [
      var: value
      bank
    ]
  ]
]
```

Learning to use objects is important because much of REBOL is built using object structures. As you've seen earlier in the section about built-in help, the REBOL "system" object contains many important interpreter settings. In order to access all the values in the system object, it's essential to understand object notation:

```
get in system/components/graphics 'date
```

The same is true for GUI widget properties and many other features of REBOL.

For more information about objects, see:

<http://rebol.com/docs/core23/rebolcore-10.html>
http://en.wikibooks.org/wiki/REBOL_Programming/Language_Features/Objects
http://en.wikipedia.org/wiki/Prototype-based_programming

9.2 Ports

REBOL "ports" provide a single way to handle many types of data input and output. They enable access to a variety of data sources, and allow you to control them all in a consistent way, using standard REBOL series functions. You can open ports to POP email boxes, FTP directories, local text files, TCP network connections, keyboard input buffers, and more, and also use them to output data such as sounds and console interactions. Once a port is opened to a data source, the data contained in the port can be treated as a sequential list of items which can be traversed, arranged, searched, sorted, and otherwise organized/manipulated, all using series functions such as those covered earlier in this text (foreach, find, select, reverse, length?, head, next, back, last, tail, at, skip, extract, index?, insert, append, remove, change, poke, copy/part, clear, replace, join, intersect, difference, exclude, union, unique, empty?, write, save, etc.).

In some cases, there are other native ways to access data contained in a given port, typically with "read" and "write" functions. In such cases, port access simply provides finer control of the data (dealing with email and file data are examples of such cases). In other cases, ports provide the primary interface for accessing data in the given data source (TCP sockets and other network protocols are examples).

Ports are created using the "open" function, and are typically assigned a word label when created:

```
my-files: open ftp://user:pass@site.com/public_html/
```

After opening the above port, the files in the FTP directory can be traversed sequentially or by index, using series functions:

```
print first my-files
print length? my-files
print pick my-files ((length? my-files) - 7) ; 7th file from the end

; etc ...
```

To change the marked index position in a port, re-assign the port label to the new index position:

```
my-files: head my-files
  print index? my-files
  print first my-files
my-files: next my-files
  print index? my-files
  print first my-files
my-files: at my-files 10
  print index? my-files
  print first my-files
```

To close the connection to data contained in a port, use the "close" function:

```
close my-files
```

It is of course possible to read and write directly to/from the folder in the above examples without manually opening a port:

```
print read ftp://user:pass@site.com/public_html/
write ftp://user:pass@site.com/public_html/temp.txt (read %temp.txt)
```

The difference between opening a port to the above files, and simply reading/writing them is that the port connection offers more specific access to and control of individual files. The "get-modes" and "set-modes" functions can be used to set various properties of files:

```
my-file: open %temp.txt
set-modes port [
  world-read: true
  world-write: true
  world-execute: true
]
close my-file
```

More benefits of port control are easy to understand when dealing with email accounts. All the email in a given account can be accessed by simply reading it:

```
print read pop://user:pass/site.com
```

If, for example, there are 10000 messages in the above email account, the above action could take a very long time to complete. Even to simply read one email from the above account, the entire account needs to be read:

```
print second read pop://user:pass/site.com
```

A much better solution is to open a port to the above data source:

```
my-email: open pop://user:pass/site.com
```

Once the above port is open, each of the individual emails in the given POP account can be accessed *separately*, without having to download any other emails in the account:

```
print second my-email ; no download of 10000 emails required
```

And you can jump around between messages in the account:

```
my-email: head my-email
  print first my-email      ; prints the 1st email in the box
my-email: next my-email
  print first my-email      ; prints the 2nd email in the box
my-email: at my-email 4
  print first my-email      ; prints the 5th email in the box
my-email: head my-email
  print first my-email      ; prints email #1 again
; etc...
```

You can also *remove* email messages from the account:

```
my-email: head my-email
  remove my-email ; removes the 1st email
```

Internally, REBOL actually deals with most types of data sources as ports. The following line:

```
write/append %temp.txt "1234"
```

Is the same as:

```
temp: open %temp.txt
append temp "1234"
close temp
```

REBOL ports are *objects*. You can see all the properties of an open port, using the "probe" function:

```
temp: open %temp.txt
probe temp
close temp
```

From the *very important* example above, you can see that various useful properties of the port data can be accessed using a consistent syntax:

```
temp: open %temp.txt
```

```
print temp/date
print temp/path
print temp/size

close temp
```

The *state/inBuffer* and *state/outBuffer* are particularly important values in any port. Those items are where *changes to data contained in the port are stored, until the port is closed or updated*. Take a close look at this example:

```
; First, create a file:

write %temp.txt ""

; That file is now empty:

print read %temp.txt

; Open the above file as a port:

temp: open %temp.txt

; Append some text to it:

append temp "1234"

; Display the text to be saved to the file:

print temp/state/inBuffer

; The appended changes have NOT yet been saved to the file because the
; port has not yet been closed or updated:

print read %temp.txt

; Either "update" or "close" can be used to save the changes to the file:

update temp

; The "update" function has forced the appended data to be written to
; the file, but has NOT yet closed the port:

print read %temp.txt

; We can still navigate the port contents and add more data to it:

temp: head temp
insert temp "abcd"

; Display the text to be saved to the file:

print temp/state/inBuffer

; Those changes have not yet been saved to the file:

print read %temp.txt

; Closing the port will save changes to the file:

close temp

; Here are the saved changes:

print read %temp.txt

; And additional changes can no longer be made:
```

```
append temp "1q2w3e4r" ; (error)
```

Ports can be opened with a variety of refinements to help deal with data appropriately. "Help open" displays the following list:

```
/binary - Preserves contents exactly.
/string  - Translates all line terminators.
/direct  - Opens the port without buffering.
/seek    - Opens port in seek mode without buffering.
/new      - Creates a file. (Need not already exist.)
/read    - Read only. Disables write operations.
/write   - Write only. Disables read operations.
/no-wait  - Returns immediately without waiting if no data.
/lines   - Handles data as lines.
/with    - Specifies alternate line termination. (Type: char string)
/allow   - Specifies the protection attributes when created. (Type: block)
/mode    - Block of above refinements. (Type: block)
/custom  - Allows special refinements. (Type: block)
/skip    - Skips a number of bytes. (Type: number)
```

Several of those options will be demonstrated in the following example applications.

9.2.1 Console Email Application

The following email program opens a port to a selected email account and allows the user to navigate through messages, read, send, delete, and reply to emails. It runs entirely at the command line - no VID GUI components or View graphics are required. You can store configuration information for as many email accounts as you'd like in the "accounts" block, and easily switch between them at any point in the program:

```
REBOL [Title: "Console Email"]

accounts: [
  ["pop.server" "smtp.server" "username" "password" you@site.com]
  ["pop.server2" "smtp.server2" "username" "password" you@site2.com]
  ["pop.server3" "smtp.server3" "username" "password" you@site3.com]
]

empty-lines: "^/"
loop 400 [append empty-lines "^/"] ; # of lines it takes to clear screen
cls: does [prin {^(1B)[J]}]
a-line:{-----}

select-account: does [
  cls
  print a-line
  forall accounts [
    print rejoin ["^/" index? accounts ": " last first accounts]
  ]
  print join "^/" a-line
  selected: ask "^/Select an account #: "
  if selected = "" [selected: 1]
  t: pick accounts (to-integer selected)
  system/schemes/pop/host: t/1
  system/schemes/default/host: t/2
  system/schemes/default/user: t/3
  system/schemes/default/pass: t/4
  system/user/email: t/5
]

send-email: func [/reply] [
  cls
  print rejoin [a-line "^/^/Send Email:^/^/" a-line]
  either reply [
    print join ["^/^/Reply-to: " addr: form pretty/from]
  ] [
    addr: ask "^/^/Recipient Email Address: "
  ]
]
```

```

either reply [
  print join "^/Subject: " subject: join "re: " form pretty/subject
] [
  subject: ask "^/Email Subject: "
]
print {^/Body (when finished, type "end" on a seperate line):^/}
print join a-line "^/"
body: copy ""
get-body: does [
  body-line: ask ""
  if body-line = "end" [return]
  body: rejoin [body "^/" body-line]
  get-body
]
get-body
if reply [
  rc: ask "^/Quote original email in your reply (Y/n)? "
  if ((rc = "yes") or (rc = "y") or (rc = "")) [
    body: rejoin [
      body
      "^/^/--- Quoting " form pretty/from ":^/"
      form pretty/content
    ]
  ]
]
print rejoin ["^/" a-line "^/^/Sending..."]
send/subject to-email addr body subject
cls
print "Sent^/"
wait 1
]
read-email: does [
  pretty: none
  cls
  print "One moment..."
  ; THE FOLLOWING LINE OPENS A PORT TO THE SELECTED EMAIL ACCOUNT:
  mail: open to-url join "pop://" system/user/email
  cls
  while [not tail? mail] [
    print "Reading...^/"
    pretty: import-email (copy first mail)
    either find pretty/subject "****SPAM****" [
      print join "Spam found in message #" length? mail
      mail: next mail
    ][
      print empty-lines
      cls
      prin rejoin [
        a-line
        {^/The following message is #} length? mail { from: }
        system/user/email {^/} a-line {^/^/}
        {FROM:      } pretty/from {^/}
        {DATE:      } pretty/date {^/}
        {SUBJECT:   } pretty/subject {^/^/} a-line
      ]
      confirm: ask "^/^/Read Entire Message (Y/n): "
      if ((confirm = "y") or (confirm = "yes") or (confirm = "")) [
        print join {^/^/} pretty/content
      ]
      print rejoin [
        {^/} a-line {^/}
        {^/[ENTER]:  Go Forward (next email)^/}
        {^/      "b":  Go Backward (previous email)^/}
        {^/      "r":  Reply to current email^/}
        {^/      "d":  Delete current email^/}
        {^/      "q":  Quit this mail box^/}
        {^/ Any #:  Skip forward or backward this # of messages}
        {^/^/} a-line {^/}
      ]
      switch/default mail-command: ask "Enter Command: " [
        "" [mail: next mail]
        "b" [mail: back mail]

```

```

        "r" [send-email/reply]
        "d" [
            remove mail
            cls
            print "Email deleted!^/"
            wait 1
        ]
        "q" [
            close mail
            cls
            print "Mail box closed!^/"
            wait 1
            break
        ]
    ] [mail: skip mail to-integer mail-command]
    if (tail? mail) [mail: back mail]
]
]

; begin the program:

select-account

forever [
    cls
    print a-line
    print rejoin [
        {^/"r": Read Email^/}
        {^/"s": Send Email^/}
        {^/"c": Choose a different mail account^/}
        {^/"q": Quit^/}
    ]
    print a-line
    response: ask "^/Select a menu choice: "
    switch/default response [
        "r" [read-email]
        "s" [send-email]
        "c" [select-account]
        "q" [
            cls
            print "DONE!"
            wait .5
            quit
        ]
    ] [read-email]
]

```

9.2.2 Network Ports

One important use of ports is for transferring data via network connections (TCP and UDP "sockets"). When writing a network application, you must choose a specific port number through which data is to be transferred. Potential ports range from 0 to 65535, but many of those numbers are reserved for specific types of applications (email programs use port 110, web servers use port 80 by default, etc.). To avoid conflicting with other established network applications, it's best to choose a port number between 49152 and 65535 for small scripts. A list of reserved port numbers is available [here](#).

Network applications are typically made up of two or more separate programs, each running on different computers. Any computer connected to a network or to the Internet is assigned a specific "IP address", notated in the format xxx.xxx.xxx.xxx. The numbers are different for every machine on a network, but most home and small business machines are normally in the IP range "192.168.xxx.xxx". You can obtain the IP address of your local computer with the following REBOL code:

```
read join dns:// (read dns://)
```

"Server" programs open a chosen network port and wait for one or more "client" programs to open the same port and then insert data into it. *The port opened by the server program is referred to in a client*

program by combining the IP address of the computer on which the server runs, along with the chosen port number, each separated by a colon symbol (i.e., 192.168.1.2:55555).

The following simple set of scripts demonstrates how to use REBOL ports to transfer one line of text from a client to a server program. This example is intended to run on a single computer, for demonstration, so the word "localhost" is used to represent the IP address of the server (that's a standard convention used to refer to any computer's own local IP address). If you want to run this on two separate computers connected via a local area network, you'll need to obtain the IP address of the server machine (use the code above), and replace the word "localhost" with that number:

Here's the SERVER program. Be sure to run it *before* starting the client, or you will receive an error:

```
; Open network port 55555, in line mode (this mode expects full lines
; of text delineated by newline characters):

server: open/lines tcp://:55555

; Wait for a connection to the above port:

wait server

; Assign a label to the first connection made to the above port:

connection: first server

; Get the data which has been inserted into the above port object:

data: first connection

; Display the inserted data:

alert rejoin ["Text received: " data]

; Close the server

close server
```

Here's the CLIENT. Run it in a *separate* instance of the REBOL interpreter, after the above program has been started:

```
; Open the port created by the server above (replace "localhost" with
; an IP address if running these scripts on separate machines):

server-port: open/lines tcp://localhost:55555

; Insert some text into the port:

insert server-port "Hello Mr. Watson."

; Close the port:

close server-port
```

Typically, servers will continuously wait for data to appear in a port, and repeatedly do something with that data. The scripts below extend the above example with forever loops to continuously send, receive, and display messages transferred from client(s) to the server. This type of loop forms the basis for most peer-to-peer and client-server network applications. Type "end" in the client program below to quit both the client and server.

Here's the server program (run it first):

```
server: open/lines tcp://:55555          ; Open a TCP network port.
print "Server started...^/"              ;
connection: first wait server             ; Label the first connection.
```

```

forever [
  data: first connection          ; Get a line of data.
  print rejoin ["Text received: " data] ; Display it.
  if find data "end" [
    close server                  ; End the program if the
    print "Server Closed"         ; client user typed "end".
    halt
  ]
]

```

Here's the client program. Run it only *after the server program has been started*, and in a separate instance of the REBOL interpreter (or on a separate computer):

```

server-port: open/lines tcp://localhost:55555 ; Open the server port.
forever [
  user-text: ask "Enter some text to send: "
  insert server-port user-text                ; Transfer the data.
  if user-text = "end" [
    close server-port                         ; End the program if the
    print "Client Closed"                     ; user typed "end".
    halt
  ]
]

```

It's important to understand that REBOL servers like the one above can interact independently with more than one simultaneous client connection. The "connection" definition waits until a new client connects, and returns a port representing that first client connection. Once that occurs, "connection" refers to the port used to accept data transferred by the already connected client. If you want to add more simultaneous client connections during the forever loop, simply define another "first wait server". Try running the server below, then run two simultaneous instances of the above client:

```

server: open/lines tcp://:55555 ; Open a TCP network port.
print "Now start TWO clients..."
connection1: first wait server ; Label the first connection.
connection2: first wait server ; Label the second connection.
forever [
  data1: first connection1 ; Get a line of client1 data
  data2: first connection2 ; Get a line of client2 data
  print rejoin ["Client1: " data1]
  print rejoin ["Client2: " data2]
  if find data1 "end" [
    close server ; End the program if the
    print "Server Closed" ; client user typed "end".
    halt
  ]
]

```

Here's an example that demonstrates how to send data back and forth (both directions), between client and server. Again, run both programs in separate instances of the REBOL interpreter, and be sure to start the server first:

```

; Server:

print "Server started...^/"
port: first wait open/lines tcp://:55555
forever [
  user-text: ask "Enter some text to send: "
  insert port user-text
  if user-text = "end" [close port print "^/Server Closed^/" halt]
  wait port
  print rejoin ["^/Client user typed: " first port "^/"]
]

; Client:

```

```

port: open/lines tcp://localhost:55555
print "Client started...^/"
forever [
    user-text: ask "Enter some text to send: "
    insert port user-text
    if user-text = "end" [close port  print "^/Client Closed^/"  halt]
    wait port
    print rejoin ["^/Server user typed: " first port "^/"]
]

```

The following short script combines many of the techniques demonstrated so far. It can act as either server or client, and can send messages (one at a time), back and forth between the server and client:

```

do [
    either find ask "Server or client? " "s" [
        port: first wait open/lines tcp://:55555 ; server
    ] [
        port: open/lines tcp://localhost:55555 ; client
    ]
    forever [
        insert port ask "Send: "
        print join "Received: "first wait port
    ]
]

```

The following script is a complete GUI network instant message application. Unlike the FTP Chat Room presented earlier, the text in this application is sent directly between two computers, across a network socket connection (users of the FTP chat room never connect directly to one another - they simply connect to a universally available third party FTP server):

```

view layout [
    btn "Set client/server" [
        ip: request-text/title/default trim {
            Server IP (leave EMPTY to run as SERVER):
        } (to-string read join dns:// read dns://)
        either ip = "" [
            port: first wait open/lines tcp://:55555 z: true ; server
        ] [
            port: open/lines rejoin [tcp:// ip ":55555"] z: true
        ]
    ]
    r: area rate 4 feel [
        engage: func [f a e] [
            if a = 'time and value? 'z [
                if error? try [x: first wait port] [quit]
                r/text: rejoin [form x newline r/text] show r
            ]
        ]
    ]
    f: field "Type message here..."
    btn "Send" [insert port f/text]
]

```

Here's an even more compact version (probably the shortest instant messenger program you'll ever see!):

```

view layout [ across
    q: btn "Serve"[focus g p: first wait open/lines tcp://:8 z: 1]text"OR"
    k: btn "Connect"[focus g p: open/lines rejoin[tcp:// i/text ":8"]z: 1]
    i: field form read join dns:// read dns:// return
    r: area rate 4 feel [engage: func [f a e][if a = 'time and value? 'z [
        if error? try [x: first wait p] [quit]
        r/text: rejoin [x "^/" r/text] show r
    ]]] return
]

```

```

g: field "Type message here [ENTER]" [insert p value focus face]
]

```

And here's an extended version of the above script that uploads your chosen user name, WAN/LAN IP, and port numbers to an FTP server, so that that info can be shared with others online (which enables them to find and connect with you). Connecting as server uploads the user info and starts the application in server mode. Once that is done, others can click the "Servers" button to retrieve and manually enter your connection info (IP address and port), to connect as client. By using different port numbers and user names, multiple users can connect to other multiple users, anywhere on the Internet:

```

server-list: ftp://username:password@yoursite.com/public_html/im.txt ;edit
view layout [ across
  q: btn "Serve" [
    parse read http://guitarz.org/ip.cgi[thru<title>copy p to</title>]
    parse p [thru "Your IP Address is: " copy pp to end]
    write/append server-list rejoin [
      b/text " " pp " " read join dns:// read dns://" " j/text "^/"
    ]
    focus g p: first wait open/lines join tcp:// j/text z: 1
  ] text "OR"
  k: btn "Connect" [
    focus g p: open/lines rejoin [tcp:// i/text j/text] z: 1
  ]
  b: field 85 "Username"
  i: field 98 form read join dns:// read dns://
  j: field 48 ":8080" return
  r: area rate 4 feel [engage: func [f a e][if a = 'time and value? 'z [
    if error? try [x: first wait p] [quit]
    r/text: rejoin [x "^/" r/text] show r
  ]]] return
  g: field "Type message here [ENTER]" [insert p value focus face]
  tabs 181 tab btn "Servers" [print read server-list]
]

```

If you want to run scripts like these between computers connected to the Internet by broadband routers, you'll likely need to learn how to "forward" ports from your router to the IP address of the machine running your server program. In most situations where a router connects a local home/business network to the Internet, only the router device has an IP address which is visible on the Internet. The computers themselves are all assigned IP addresses that are *only accessible within the local area network*. Port forwarding allows you to send data coming to the IP address of the router (the IP which is visible on the Internet), on a unique port, to a specific computer inside the local area network. A full discussion of port forwarding is beyond the scope of this tutorial, but it's easy to learn how to do - just type "port forwarding" into Google. You'll need to learn how to forward ports on *your particular brand and model of router*.

With any client-server configuration, only the server machine needs to have an exposed IP address or an open router/firewall port. The client machine can be located behind a router or firewall, without any forwarded incoming ports.

Another option that enables network applications to work through routers is "VPN" software. Applications such as [hamachi](#), [comodo](#), and [OpenVPN](#) allow you to connect two separate LAN networks across the Internet, and treat all the machines as if they are connected locally (connect to any computer in the VPN using a local IP address, such as 192.168.1.xxx). VPN software also typically adds a layer of security to the data sent back and forth between the connected machines. The down side of VPN software is that data transmission can be slower than direct connection using port forwarding (the data travels through a third party server).

9.2.3 Peer-to-Peer Instant Messenger

The following text message example contains line by line documentation of various useful coding techniques. For instructions, see the help documentation included in the code.

```

REBOL [Title: "Peer-to-Peer Instant Messenger"]

; The following line sets a flag variable, used to mark whether or not
; the two machines have already connected. It helps to more gracefully
; handle connection and shutdown actions throughout the script:

```

```

connected: false

; The code below traps the close button (just a variation of the routine
; used in the earlier listview example). It assures that all open ports
; are closed, and sends a message to the remote machine that the
; connection has been terminated. Notice that the lines in the disconnect
; message are sent in reverse order. When they're received by the other
; machine, they're printed out one at a time, each line on top of the
; previous - so it appears correctly when viewed on the other side:

insert-event-func closedown: func [face event] [
  either event/type = 'close [
    if connected [
      insert port trim {
        *****
        AND RECONNECT.
        YOU MUST RESTART THE APPLICATION
        TO CONTINUE WITH ANOTHER CHAT,
        THE REMOTE PARTY HAS DISCONNECTED.
        *****
      }
      close port
      if mode/text = "Server Mode" [close listen]
    ]
    quit
  ] [event]
]

view/new center-face gui: layout [
  across
  at 5x2 ; this code positions the following items in the GUI

  ; The text below appears as a menu option in the upper
  ; left hand corner of the GUI. When it's clicked, the
  ; text contained in the "display" area is saved to a
  ; user selected file:

  text bold "Save Chat" [
    filename: to-file request-file/title/file/save trim {
      Save file as:} "Save" %/c/chat.txt
    write filename display/text
  ]

  ; The text below is another menu option. It displays
  ; the user's IP address when clicked. It relies on a
  ; public web server to find the external address.
  ; The "parse" command is used to extract the IP address
  ; from the page. Parse is covered in a separate
  ; dedicated section later in the tutorial.

  text bold "Lookup IP" [
    parse read http://guitarz.org/ip.cgi [
      thru <title> copy my-ip to </title>
    ]
    parse my-ip [
      thru "Your IP Address is: " copy stripped-ip to end
    ]
    alert to-string rejoin [
      "External: " trim/all stripped-ip " "
      "Internal: " read join dns:// read dns://
    ]
  ]

  ; The text below is a third menu option. It displays
  ; the help text when clicked.

  text bold "Help" [
    alert {
      Enter the IP address and port number in the fields
      provided. If you will listen for others to call you,
      use the rotary button to select "Server Mode" (you

```

```

    must have an exposed IP address and/or an open port
    to accept an incoming chat). Select "Client Mode" if
    you will connect to another's chat server (you can do
    that even if you're behind an unconfigured firewall,
    router, etc.). Click "Connect" to begin the chat.
    To test the application on one machine, open two
    instances of the chat application, leave the IP set
    to "localhost" on both. Set one instance to run as
    server, and the other as client, then click connect.
    You can edit the chat text directly in the display
    area, and you can save the text to a local file.
  }
]
return

; Below are the widgets used to enter connection info.
; Notice the labels assigned to each item. Later, the
; text contained in these widgets is referred to as
; <label>/text. Take a good look at the action block
; for the rotary button too. Whenever it's clicked,
; it either hides or shows the other widgets. When in
; server mode, no connection IP address is needed - the
; application just waits for a connection on the given
; port. Hiding the IP address field spares the user some
; confusion.

lab1: h3 "IP Address:" IP: field "localhost" 102
lab2: h3 "Port:" portspec: field "9083" 50
mode: rotary 120 "Client Mode" "Server Mode" [
  either value = "Client Mode" [
    show lab1 show IP
  ][
    hide lab1 hide IP
  ]
]

; Below is the connect button, and the large action block
; that does most of the work. When the button is clicked,
; it's first hidden, so that the user isn't tempted to
; open the port again (that would cause an error). Then,
; a TCP/IP port is opened - the type (server/client) is
; determined using an "either" construct. If an error
; occurs in either of the port opening operations, the
; error is trapped and the user is alerted with a message -
; that's more graceful and informative than letting the
; program crash with an error. Notice that the IP
; address and port info are gathered from the fields above.
; If the server mode is selected (i.e., if the "mode" button
; above isn't displaying the text "Client Mode"), then the
; the TCP ports are opened in listening mode - waiting
; for a client to connect. If the client mode is selected,
; an attempt is made to open a direct connection to the IP
; address and port selected.

cnnct: button red "Connect" [
  hide cnnct
  either mode/text = "Client Mode" [
    if error? try [
      port: open/direct/lines/no-wait to-url rejoin [
        "tcp://" IP/text ":" portspec/text]
      ][alert "Server is not responding." return]
    ][
      if error? try [
        listen: open/direct/lines/no-wait to-url rejoin [
          "tcp://" portspec/text]
        wait listen
        port: first listen
      ][alert "Server is already running." return]
    ]
  ]

; After the ports have been opened, the text entry field
; is highlighted, and the connection flag is set to true.

```

```

; Focusing on the text entry field provides a nice visual
; cue to the user that the connection has been made, but
; it's not required.

focus entry
connected: true

; The forever loop below continuously waits for data to
; appear in the open network connection. Whenever data
; is inserted on the other side, it's copied and
; appended to the current text in the display area, and
; then the display area is updated to show the new text.

forever [
  wait port
  foreach msg any [copy port []] [
    display/text: rejoin [
      ">>> "msg newline display/text]
    ]
  show display
]

; Below are the display area and text entry fields. Notice
; the labels assigned to each. The "return"s just put each
; widget on a new line in the GUI (because the layout mode
; is set to "across" above).

return display: area "" 537x500
return entry: field 428 ; the numbers are pixel sizes

; The send button below does some more important work.
; First, it checks to see if the connection has been made
; (using the flag set above). If so, it inserts the text
; contained in the "entry" field above into the open TCP/IP
; port, to be picked up by the remote machine - if the
; connection has been made, the program on the other end
; is waiting to read any data inserted into that port.
; After sending the data across the network connection,
; the text is appended to the local current text display
; area, and the display is updated:

button "Send Text" [
  if connected [
    insert port entry/text focus entry
    display/text: rejoin [
      "<<< " entry/text newline display/text]
    show display
  ]
]

show gui do-events ; these are required because the "/new"
; refinement is used above.

```

9.2.4 Transferring Binary Files Through TCP Network Sockets:

These 2 scripts based on <http://www.rebol.net/cookbook/recipes/0058.html>, by Carl Sassenrath (edited and condensed here), demonstrate how to transfer binary files directly between any two networked computers (across a TCP socket connection), using ports. Sending binary files is different from sending text in that the length of the file must be transmitted before sending the file. That must be done so that the receiving code knows when the complete file has been transmitted. The sending script below appends the file length information, and the file name, to the data being sent. The receiving script searches for that information, then receives the specified amount of binary data and saves it to a file when complete:

```

REBOL [Title: "Server/Receiver"]

p: ":8000" ; port #
print "receiving"

```

```

data: copy wait client: first port: wait open/binary/no-wait join tcp:// p
info: load to-string copy/part data start: find data #"
remove/part data next start
while [info/2 > length? data] [append data copy client]
write/binary (to-file join "transferred-" (second split-path info/1)) data

insert client "done" wait client close client close port print "Done" halt

REBOL [Title: "Client/Sender"]

ip: "localhost" p: ":8000" ; IP address and port #
print "sending"

data: read/binary file: to-file request-file
server: open/binary/no-wait rejoin [tcp:// ip p]
insert data append remold [file length? data] #"
insert server data

wait server close server print "Done" halt

```

Here's a more compact example that demonstrates how to create and send an image from one computer to another:

```

; server/receiver - run first:

if error? try [port: first wait open/binary/no-wait tcp://:8] [quit]
mark: find file: copy wait port #"
length: to-integer to-string copy/part file mark
while [length > length? remove/part file next mark] [append file port]

view layout [image load file]

; client/sender - run after server (change IP address if using on 2 pcs):

save/png %image.png to-image layout [box blue "I traveled through ports!"]

port: open/binary/no-wait tcp://127.0.0.1:8 ; adjust this IP address
insert file: read/binary %image.png join 1: length? file #"
insert port file

```

The following program is a walkie-talkie push-to-talk type of voice over IP application. It's extremely simple - it just records sound from mic to .wav file, then transfers the wave file to another IP (where the same program is running), for playback. Sender and receiver open in separate processes, and both run in forever loops to enable continuous communication back and forth. As it stands, this is a MS Windows only application. The code which handles the sound recording is discussed in more detail in the section of this tutorial about DLLs:

```

REBOL [Title: "Intercom (VOIP Messenger)"]

write %wt-receiver.r {
  REBOL []
  print join "Receiving at " read join dns:// read dns://
  if error? try[c: first t: wait open/binary/no-wait tcp://:8000][quit]
  s: open sound://
  forever [
    d: copy wait c
    if error? try [i: load to-string copy/part d start: find d #""] [
      print "^lclient closed" close t close c close s wait 1 quit
    ]
    remove/part d next start
    while [i/2 > length? d] [append d copy c]
    write/binary (to-file join "t-" (second split-path i/1))
      decompress to-binary d
    insert s load %t-r.wav wait s
  ]
}

```



```

    ]
  }
  launch %wt-receiver.r

  lib: load/library %winmm.dll
  mciExecute: make routine! [c [string!] return: [logic!]] lib "mciExecute"

  if (ip: ask "Connect to IP (none = localhost): ") = "" [ip: "localhost"]
  if error? try [s: open/binary/no-wait rejoin [tcp:// ip ":8000"]] [quit]

  mciExecute "open new type waveaudio alias buffer1 buffer 4"
  forever [
    x: ask "^lPress [ENTER] to start sending sound (or 'q' to quit): "
    if find x "q" [close s free lib break]
    ; if (ask "^lPress [ENTER] to send sound ('q' to quit): ") = "q"[quit]
    mciExecute "record buffer1"
    ask "^l*** YOU ARE NOW RECORDING SOUND *** Press [ENTER] to send: "
    mciExecute join "save buffer1 " to-local-file %r.wav
    mciExecute "delete buffer1 from 0"
    data: compress to-string read/binary %r.wav
    insert data append remold [%r.wav length? data] #"
    insert s data
  ]

```

Here's a more compact version of the above application, with hands-free operation enabled (several obfuscated versions of this script can be found at the end of this tutorial - likely the most compact VOIP programs you'll find anywhere):

```

REBOL [title: "VOIP"] do [write %ireceive.r {REBOL [
  if error? try [port: first wait open/binary/no-wait tcp://:8] [quit]
  wait 0 speakers: open sound://
  forever [
    if error? try [mark: find wav: copy wait port #"] [quit]
    i: to-integer to-string copy/part wav mark
    while [i > length? remove/part wav next mark] [append wav port]
    insert speakers load to-binary decompress wav
  ]] launch %ireceive.r
  lib: load/library %winmm.dll
  mci: make routine! [c [string!] return: [logic!]] lib "mciExecute"
  if (ip: ask "Connect to IP (none = localhost): ") = "" [ip: "localhost"]
  if error? try [port: open/binary/no-wait rejoin [tcp:// ip ":8"]] [quit]
  mci "open new type waveaudio alias wav"
  forever [
    mci "record wav" wait 2 mci "save wav r" mci "delete wav from 0"
    insert wav: compress to-string read/binary %r join 1: length? wav #"
    if 1 > 4000 [insert port wav] ; squelch (don't send) if too quiet
  ]
]]

```

For more information on ports, see <http://www.rebol.com/docs/core23/rebolcore-14.html>, <http://stackoverflow.com/questions/1291127/rebol-smallest-http-server-in-the-world-why-first-wait-listen-port>, and <http://www.rebol.net/docs/async-ports.html>.

9.3 Parse (REBOL's Answer to Regular Expressions)

The "parse" function is used to import and convert organized chunks of external data into the block format that REBOL recognizes natively. It also provides a means of dissecting, searching, comparing, extracting, and acting upon organized information within unformatted text data (similar to the pattern matching functionality implemented by regular expressions in other languages).

The basic format for parse is:

```
parse <data> <matching rules>
```

Parse has several modes of use. The simplest mode just splits up text at common delimiters and converts

those pieces into a REBOL block. To do this, just specify "none" as the matching rule. Common delimiters are spaces, commas, tabs, semicolons, and newlines. Here are some examples:

```
text1: "apple orange pear"
parsed-block1: parse text1 none

text2: "apple,orange,pear"
parsed-block2: parse text2 none

text3: "apple      orange                pear"
parsed-block3: parse text3 none

text4: "apple;orange;pear"
parsed-block4: parse text4 none

text5: "apple,orange pear"
parsed-block5: parse text5 none

text6: {"apple","orange","pear"}
parsed-block6: parse text6 none

text7: {
apple
orange
pear
}
parsed-block7: parse text7 none
```

To split files based on some character other than the common delimiters, you can specify the delimiter as a rule. Just put the delimiter in quotes:

```
text: "apple*orange*pear"
parsed-block: parse text "*"

text: "apple&orange&pear"
parsed-block: parse text "&"

text: "apple    &    orange&pear"
parsed-block: parse text "&"
```

You can also include mixed multiple characters to be used as delimiters:

```
text: "apple&orange*pear"
parsed-block: parse text "&*"

text: "apple&orange*pear"
parsed-block: parse text "*&" ; the order doesn't matter
```

Using the "splitting" mode of parse is a great way to get formatted tables of data into your REBOL programs. Splitting the text below by carriage returns, you run into a little problem:

```
text: {      First Name
              Last Name
              Street Address
              City, State, Zip}

parsed-block: parse text "^/"

; ^/ is the REBOL symbol for a carriage return
```

Spaces are included in the parsing rule by default (parse automatically splits at all empty space), so you get

a block of data that's more broken up than intended:

```
[ "First" "Name" "Last" "Name" "Street" "Address" "City,"
  "State," "Zip" ]
```

You can use the `/all` refinement to eliminate spaces from the delimiter rule. The code below:

```
text: {      First Name
            Last Name
            Street Address
            City, State, Zip}

parsed-block: parse/all text "^/"
```

converts the given text to the following block:

```
[ " First Name" "      Last Name" "      Street Address"
  "      City, State, Zip" ]
```

Now you can trim the extra space from each of the strings:

```
foreach item parsed-block [trim item]
```

and you get the following parsed-block, as intended:

```
[ "First Name" "Last Name" "Street Address" "City, State, Zip" ]
```

Parse is commonly used to convert spreadsheet data into REBOL blocks. In Excel, Open Office, and other spreadsheet programs, you can export all the columns of data in a worksheet by saving it as a CSV formatted ("comma separated value") .csv text file. People often put various bits of descriptive text, labels and column headers into spreadsheets to make them more readable:

```

;
      TITLE
      DESCRIPTION

      Header1

Category1  data    data    data    Notes...
           data    data    data
           data    data    data

      Header2

Category2  data    data    data    Notes...
           data    data    data
           data    data    data

      Header3

Category3  data    data    data    Notes...
           data    data    data
           data    data    data
           data    data    data
```

The following code turns the exported CSV spreadsheet data into a nice useable REBOL block, with group heading data added to each line:

```
; Read and parse the CSV formatted file:

filename: %filename.csv
data: copy []
lines: read/lines filename
foreach line lines [
    append/only data parse/all line ","
]

; Add headers from sections of the spreadsheet to each line item:

info: copy ""
foreach line data [
    either find "Header" line/1 [
        info: line/1
    ][
        append line info
    ]
]

; Remove the unwanted descriptive header lines:

remove-each line data [find "Header" line/1/1]
remove-each line data [
    (line/3 = "TITLE") or (line/3 = "DESCRIPTION")
]
```

Pattern Matching Mode:

You can use parse to check whether any specific data exists within a given block. To do that, specify the rule (matching pattern) as the item you're searching for. Here's an example:

```
parse ["apple"] ["apple"]

parse ["apple" "orange"] ["apple" "orange"]
```

Both lines above evaluate to true because they match exactly. IMPORTANT: By default, as soon as parse comes across something that doesn't match, the entire expression evaluates to false, EVEN if the given rule IS found one or more times in the data. For example, the following is false:

```
parse ["apple" "orange"] ["apple"]
```

But that's just default behavior. You can control how parse responds to items that don't match. Adding the words below to a rule will return true if the given rule matches the data in the specified way:

1. "any" - the rule matches the data zero or more times
2. "some" - the rule matches the data one or more times
3. "opt" - the rule matches the data zero or one time
4. "one" - the rule matches the data exactly one time
5. an integer - the rule matches the data the given number of times
6. two integers - the rule matches the data a number of times included in the range between the two integers

The following examples are all true:

```
parse ["apple" "orange"] [any string!]
parse ["apple" "orange"] [some string!]
parse ["apple" "orange"] [1 2 string!]
```

You can create rules that include multiple match options - just separate the choices by a "|" character and enclose them in brackets. The following is true:

```
parse ["apple" "orange"] [any [string! | url! | number!]]
```

You can trigger actions to occur whenever a rule is matched. Just enclose the action(s) in parentheses:

```
parse ["apple" "orange"] [any [string!
    (alert "The block contains a string.") | url! | number!]]
```

You can skip through data, ignoring chunks until you get to, or past a given condition. The word "to" ignores data UNTIL the condition is found. The word "thru" ignores data until JUST PAST the condition is found. The following is true:

```
parse [234.1 $50 http://rebol.com "apple"] [thru string!]
```

The real value of pattern matching is that you can search for and extract data from unformatted text, in an organized way. The word "copy" is used to assign a variable to matched data. For example, the following code downloads the raw HTML from the REBOL homepage, ignores everything except what's between the HTML title tags, and displays that text:

```
parse read http://rebol.com [
    thru <title> copy parsed-text to </title> (alert parsed-text)
]
```

The following code extends the example above to provide the useful feature of displaying the external ip address of the local computer. It reads <http://guitarz.org/ip.cgi>, parses out the title text, and then parses that text again to return only the IP number. The local network address is also displayed, using the built in dns protocol in REBOL:

```
parse read http://guitarz.org/ip.cgi [
    thru <title> copy my-ip to </title>
]
parse my-ip [
    thru "Your IP Address is: " copy stripped-ip to end
]
alert to-string rejoin [
    "External: " trim/all stripped-ip " "
    "Internal: " read join dns:// read dns://
]
```

Here's a useful example that removes all comments from a given REBOL script (any part of a line that begins with a semicolon ";"):

```
code: read to-file request-file

parse/all code [any [
    to #";" begin: thru newline ending: (
        remove/part begin ((index? ending) - (index? begin))) :begin
    ]
]

editor code
```

For more about parse, see the following links:

<http://www.codeconscious.com/rebol/parse-tutorial.html>
<http://www.rebol.com/docs/core23/rebolcore-15.html>
http://en.wikibooks.org/wiki/REBOL_Programming/Language_Features/Parse
<http://www.rebolforces.com/zine/rzine-1-06.html#sect4>.

9.4 2D Drawing, Graphics, and Animation

With REBOL's "view layout" ("VID") dialect you can easily build graphic user interfaces that include buttons, fields, text lists, images and other GUI widgets, but it's not meant to handle general purpose graphics or animation. For that purpose, REBOL includes a built-in "draw" dialect. Various drawing functions allow you to make lines, boxes, circles, arrows, and virtually any other shape. Fill patterns, color gradients, and effects of all sorts can be easily applied to drawings.

Implementing draw functions typically involves creating a 'view layout' GUI, with a box widget that's used as the viewing screen. "Effect" and "draw" functions are then added to the box definition, and a block is passed to the draw function which contains more functions that actually perform the drawing of various shapes and other graphic elements in the box. Each draw function takes an appropriate set of arguments for the type of shape created (coordinate values, size value, etc.). Here's a basic example of the draw format:

```
view layout [box 400x400 effect [draw [line 10x39 322x211]]]
; "line" is a draw function
```

Here's the exact same example indented and broken apart onto several lines:

```
view layout [
  box 400x400 effect [
    draw [
      line 10x39 322x211
    ]
  ]
]
```

Any number of shape elements (functions) can be included in the draw block:

```
view layout [
  box 400x400 black effect [
    draw [
      line 0x400 400x50
      circle 250x250 100
      box 100x20 300x380
      curve 50x50 300x50 50x300 300x300
      spline closed 3 20x20 200x70 150x200
      polygon 20x20 200x70 150x200 50x300
    ]
  ]
]
```

Color can be added to graphics using the "pen" function. Shapes can be filled with color, with images, and with other graphic elements using the "fill-pen" function. The thickness of drawn lines is set with the "line-width" function:

```
view layout [
  box 400x400 black effect [
    draw [
      pen red
      line 0x400 400x50
      pen white
      box 100x20 300x380
      fill-pen green
      circle 250x250 100
      pen blue
    ]
  ]
]
```

```

        fill-pen orange
        line-width 5
        spline closed 3 20x20 200x70 150x200
        polygon 20x20 200x70 150x200 50x300
    ]
]

```

Gradients and other effects can be easily applied to the elements:

```

view layout [
    box 400x220 effect [
        draw [
            fill-pen 200.100.90
            polygon 20x40 200x20 380x40 200x80
            fill-pen 200.130.110
            polygon 20x40 200x80 200x200 20x100
            fill-pen 100.80.50
            polygon 200x80 380x40 380x100 200x200
        ]
        gradmul 180.180.210 60.60.90
    ]
]

```

Drawn shapes are automatically anti-aliased (lines are smoothed), but that default feature can be disabled:

```

view layout [
    box 400x400 black effect [
        draw [
            ; with default smoothing:
            circle 150x150 100
            ; without smoothing:
            anti-alias off
            circle 250x250 100
        ]
    ]
]

```

9.4.1 Animation

Animations can be created with draw by changing the coordinates of image elements. The fundamental process is as follows:

1. Assign a word label to the box in which the drawing takes place (the word "scrn" is used in the following examples).
2. Create a new draw block in which the characteristics of the graphic elements (position, size, etc.) are changed.
3. Assign the new block to "{yourlabel}/effect/draw" (i.e., "scrn/label/draw: [changed draw block]" in this case).
4. Display the changes with a "show {yourlabel}" function (i.e., "show scrn" in this case).

Here's a basic example that moves a circle to a new position when the button is pressed:

```

view layout [
    scrn: box 400x400 black effect [draw [circle 200x200 20]]
    btn "Move" [
        scrn/effect/draw: [circle 200x300 20] ; replace the block above
        show scrn
    ]
]

```

Variables can be assigned to positions, sizes, and/or other characteristics of draw elements, and loops can

be used to create smooth animations by adjusting those elements incrementally:

```
pos: 200x50
view layout [
  scrn: box 400x400 black effect [draw [circle pos 20]]
  btn "Move Smoothly" [
    loop 50 [
      ; increment the "y" value of the coordinate:
      pos/y: pos/y + 1
      scrn/effect/draw: copy [circle pos 20]
      show scrn
    ]
  ]
]
```

Animation coordinates (and other draw properties) can also be stored in blocks:

```
pos: 200x200
coords: [70x346 368x99 143x45 80x125 237x298 200x200]

view layout [
  scrn: box 400x400 black effect [draw [circle pos 20]]
  btn "Jump Around" [
    foreach coord coords [
      scrn/effect/draw: copy [circle coord 20]
      show scrn
      wait 1
    ]
  ]
]
```

Other data sources can also serve to control movement. In the next example, user data input moves the circle around the screen. Notice the use of the "feel" function to update the screen every 10th of a second ("rate 0:0:0.1"). Since feel is used to watch, wait for, and respond to window events, you'll likely need it in many situations where animation is used, such as in games:

```
pos: 200x200
view layout [
  scrn: box 400x400 black rate 0:0:0.1 feel [
    engage: func [face action event] [
      if action = 'time [
        scrn/effect/draw: copy []
        append scrn/effect/draw [circle pos 20]
        show scrn
      ]
    ]
  ] effect [ draw [] ]
  across
  btn "Up" [pos/y: pos/y - 10]
  btn "Down" [pos/y: pos/y + 10]
  btn "Right" [pos/x: pos/x + 10]
  btn "Left" [pos/x: pos/x - 10]
]
```

Here's a very simple paint program that also uses the feel function. Whenever a mouse-down action is detected, the coordinate of the mouse event ("event/offset") is added to the draw block (i.e., a new dot is added to the screen wherever the mouse is clicked), and then the block is shown:

```
view layout [
  scrn: box black 400x400 feel [
    engage: func [face action event] [
      if find [down over] action [
```



```

        append scrn/effect/draw event/offset
        show scrn
    ]
    if action = 'up [append scrn/effect/draw 'line]
]
] effect [draw [line]]
]

```

A useful feature of draw is the ability to easily scale and distort images simply by indicating 4 coordinate points. The image will be altered to fit into the space marked by those four points:

```

view layout [
    box 400x400 black effect [
        draw [
            image logo.gif 10x10 350x200 250x300 50x300
            ; "logo.gif" is built into the REBOL interpreter
        ]
    ]
]

```

Here's an example that incorporates the image scaling technique above with some animation. IMPORTANT: In the following example, the coordinate position calculations occur *inside the draw block*. Whenever such evaluations occur inside a draw block (i.e., when values are added or subtracted to a variable coordinate position, size, etc.), a "reduce" or "compose" function must be used to evaluate those values. Notice the tick mark (') next to the "image" function. Function words inside a reduced block need to be marked with that symbol to evaluate correctly:

```

pos: 300x300
view layout [
    scrn: box pos black effect [
        draw [image logo.gif 0x0 300x0 300x300 0x300]
    ]
    btn "Animate" [
        for point 1 140 1 [
            scrn/effect/draw: copy reduce [
                'image logo.gif
                (pos - 300x300)
                (1x1 + (as-pair 300 point))
                (pos - (as-pair 1 point))
                (pos - 300x0)
            ]
            show scrn
        ]
        for point 1 300 1 [
            scrn/effect/draw: copy reduce [
                'image logo.gif
                (1x1 + (as-pair 1 point))
                (pos - 0x300)
                (pos - 0x0)
                (pos - (as-pair point 1))
            ]
            show scrn
        ]
        ; no "reduce" is required below, because no calculations
        ; occur in the draw block - they're just static coords:
        scrn/effect/draw: copy [
            image logo.gif 0x0 300x0 300x300 0x300
        ]
        show scrn
    ]
]

```

Here's another example of a draw block which contains evaluated calculations, and therefore requires "reduce"d evaluation:

```

view layout [
  scrn: box 400x400 black effect [draw [line 0x0 400x400]]
  btn "Spin" [
    startpoint: 0x0
    endpoint: 400x400
    loop 400 [
      scrn/effect/draw: copy reduce [
        'line
        startpoint: startpoint + 0x1
        endpoint: endpoint - 0x1
      ]
      show scrn
    ]
  ]
]

```

The useful little paint program at <http://rebol.org/cgi-bin/cgiwrap/rebol/view-script.r?script=paintplus.r> consists of only 238 lines of code. Take a look at it to see how efficient REBOL's draw code is:

```

url: http://rebol.org/cgi-bin/cgiwrap/rebol/download-a-script.r?
script: "script-name=paintplus.r"
do rejoin [url script]
paint none []

```

For more information about built-in shapes, functions, and capabilities of draw, see <http://www.rebol.com/docs/draw-ref.html>, <http://www.rebol.com/docs/draw.html>, <http://translate.google.com/translate?hl=en&sl=fr&u=http://www.rebolfrance.info/org/articles/login11/login11.htm>, <http://www.rebolforces.com/zine/rzine-1-05.html>, <http://www.rebolforces.com/zine/rzine-1-06.html> (updated code for these two tutorials is available at <http://mail.rebol.net/maillist/msg39100.html>). A nice, short tutorial demonstrating how to build multi-player, networked games with draw graphics is available at <http://www.nwlink.com/~ecotope1/reb/easy-draw.r> (a clickable rebsite version is available in the REBOL Desktop -> Docs -> Easy Draw).

9.5 Using Animated GIF Images

Another easy way to work with animations in REBOL is with the "anim" style in GUIs. Anim takes a series of still image frames, and plays them in order as an animation with a given rate. The basic format is:

```

view layout [
  speed: 10
  anim rate (speed) [%image1.gif %image2.gif etc...]
]

```

The following script will convert an animated .gif into a folder filled with individual frame images:

```

REBOL []

gif-anim: load to-file request-file
make-dir %./frames/
count: 1

for count 1 length? gif-anim 1 [
  save/png rejoin [
    %./frames/ "your_file_name-" count ".png"
  ] pick gif-anim count
]

```

This next script will convert a directory of images (such as above, or any other series of images) into an embeddable block of REBOL code. It looks for all the images named [%your_file_name-1.* your_file_name-2.* etc...]:

```

REBOL []

system/options/binary-base: 64
file-list: read %./frames/
anim-frames-block: copy []
foreach file file-list [
    ; Unique portion of file names for your image frames go here.
    ; Leave out this check if you instead want to convert all
    ; files in the directory:
    if find to-string file "your_file_name-" [
        print file
        uncompressed: read/binary file
        compressed: compress to-string uncompressed
        append anim-frames-block compressed
    ]
]

editor anim-frames-block

```

Here's some sample output:

```

anim-frames-block: [64#{
eJxz93SzsEwMZwhn+M4AAglg3ACmGsCsBjDnPxj/B1P/waz/YM4oGAXDBij+ZAHT
OiAClCfyOf4zCHLIeGxYcLCZQ1gr5sSGhYfbBZS95nhsXHS0W8I4686JjYuP9ys4
d8l4blpycrJG8KqYk5uWnp5ukHxqjufmZWdnWxs/OsPJcODOPLtKprUcW9TPLXJT
V7LdFZIZuMx/Ll/rrJcK3NZ1ztd6SpVCG+L363EsXpCTvhmtovzVCWurr7R6jG7
rzZarKFpd8XTS77Z1/Xu7Qn+vunr6+/v725rqv6nm/Oj4Or2Ll7jvDUOa8+e6FX3
3uYjbPz0fN/RKjbeWcU+Z5do2qfN2lWaelnXfbveKwkz7ytLqu0qBK6Xed1cyfhG
TC58xeujhyuF422FXxQeOPybbRlnzbbP18+khtXvu/H95Ns7Gzdv5ZtfavX64fjZ
crf/d6xPvV7Xm7PZ1/x/ueXm/nXrOfVZKyZ+DL8nt85zhWzqu8LPosvPyYZEdW8
QrJjvjdj3TOFJuXQFVEVEl0iC9L49pVJjvZcnR7XLn/w+ux64XUpizrvbF0R1PFx
4QvB3s29OxLyLb9tW9Cj9+vEol5NLk+5ia7vLB74GvxbETxZRklSqI+HyWNpR7ri
VbkJtreOp05nF10/EeGW9C01/RqjmVrF3l7PZxnfPStvl2qxsjBYAwBolvdW2AQA
AA==
} 64#{
eJxz93SzsEwMZwhn+M4AAglg3ACmGsCsBjDnPxj/B1P/waz/YM4oGAXDBij+ZAHT
OiAClCfyOf4zMHLIeGxYcLCZQ1gr5sSGhYfbBZS95nhsXHS0W8I4686JjYuP9ys4
d8l4blpycrJG8KqYk5uWnp5ukHxqjufmZWdnW6hqBUwQfnxuvkPltxaJLSsuLOtT
ZWPdIPzSaal3vZUth6nWhZUsq7NsrUqzQ9f47K17qyWmdW1T2txFsreLdW/Pydu6
rXe2mHrsYuf3j86uLn95Z1/Qf6ZnWeUGD2e38V/3WVOh9viYkfzh3Fymb1Iap+oq
P7OUKH64och2tsisGfkvTy7nXi6nG/nl1dGZzLv3RQt8On3c19zy7e8stbyDCxtf
h0rLZBZuKjyYFrV6jsLdZ8xr99lGi3wueRLuGN6+zsGq7MW1700y/hHle4o/PhP8
5Xt+397f3z88Pj3ff/++v79/vGdnYbAGAJfEqNM/BAAA
} 64#{
eJxz93SzsEwMZwhn+M4AAglg3ACmGsCsBjDnPxj/B1P/waz/YM4oGAXDBij+ZAHT
OiAClCfyOf4zMHLIeGxYcLCZQ1gr5sSGhYfbBZS95nhsXHS0W8I4686JjYuP9ys4
d8l4blri2cIVNC+GU2Hp6elcEX0tnsbLfPpNs++9mTE57fRcyepfJZxfFgUsdNWU
s51l8ihoma+8XatU6cOQVaHCca6zQh+GrYv1rWOVnvgxrxzUo/POzrz2JmpuLuu+
vuntT+9ML316T3VWuf79HXX/t/GuKTJIPBj5UWf7bzB0fko75frwVGzPlffIRA934
tpiQp8809Zq3q84pL3qwq593uZ621dus61NCJ097K/714b713tflbAv03jfnmv/v
264t3wu2Hn0r9973y6uiy2aq1235hJeef35hovexONmK8jc3rzapXLeL03r+6cXl
1fHn9+39/f3D49Pz/ffv+/v7x+fX98/v3///1NWFgZrALxatNdHBAAA
} 64#{
eJxz93SzsEwMZwhn+M4AAglg3ACmGsCsBjDnPxj/B1P/waz/YM4oGAXDBij+ZAHT
OiAClCfyOf4zMHLIeGxYcLCZQ1gr5sSGhYfbBZS95nhsXHS0W8I4686JjYuP9ys4
d8l4blpycrJG8KqYk5uWnp5ukHxKZMWCZWdnSuW+urOSId1lnkP+rx6JLS8C2l0n
y6XO2PLyUovvXDtTCdNXV5pC18YtnRn68tq6qOVNX6tKdW4uT+ud5sv9RTt6Xt79
Vz3a4Stu7Cq7+OitZ/i7i3tza5n4tCo+3JzWdniTz5oIlcfHNOVXt2pWqp87VaPv
LZf1413C3s7pdmKys0rSL88PZGbbe+vzvalrY3+/PV32+sCubRtnnd0rkJdwj/0h
0wyemh2p644UC7f17H778NGh3vO6fKbGX1/f2Jx9/9ze3d/fPzjczSvrvv2/Pz88v
Lq+Oj7dTYLAGANdbpyswBAAA
} 64#{
eJxz93SzsEwMZwhn+M4AAglg3ACmGsCsBjDnPxj/B1P/waz/YM4oGAXDBij+ZAHT
OiAClCfyOf4zMHLIeGxYcLCZQ1gr5sSGhYfbBZS95nhsXHS0W8I4686JjYuP9ys4
d8l4blpycrJG8KqYk5uWnp5ukHxqjufmZWdnWxs/unNy8/Lz8x2auWR/BTveXOWi
Khe7y2S147KaiVamXAPZV5b4rnWSXBVVO3RB3OF/PN7X1G9usjnfDxd12dpz2/IK
D339VZZ3fVfZ2kdnd5uqx++t+/9tqvaM1WfXh3IrT7sz/jHxaHim0zWtSqOnM6a9
FDtbU26cfkDPvrlNcldm6kVTh22Lv5alaYfm5C+qu3OrNPfa+tzj13Ijv+XemZzI

```

```

zv9n+oq7Kye6f9+js2Fz5IFZx4PK+MR+JSy/sTn7/rm9u7+/f3C4m/m7pACDNQAX
yZ/iJgQAAA==
} 64#{
eJxz93SzsEwMZwhn+M4AAglg3ACmGsCsBjDnPxj/B1P/waz/YM4oGAXDBij+ZAHT
OiAClCfYOf4zMHLIEGxYcLCZQ1gr5sSGhYfbBZS95nhsXHS0W8I4686JjYuP9ys4
d814blpycrJG8KqYk5uWendyiezhkdy8zHemsfm9O5LG6m7zHGqjWKRcM07MY+h4
Z/IrYGXWmp65dq2rAl6FrGjB3fUKuB12DrPvVqs2gFvwlelHZ/ku3qadvSilMP7
9kqW653fWvay6ezq67rxS6r/P1qjPWPdG4Nu/N+/rvyh9/iYt7zzNs0So6enpi2M
cuuRNlp3qJH/d6hNlEnY+eXS0916w0qzLq+PPP7s98yy3N2Fp5+dvTtVN781qf77
u5XTi3wfHpyVj51TnX3xfsHkeDe98qrS11catc/PK7D+/u74fnNpHv19e35+fnF5
dfz5fXt/f//w+PR8//37/v5mYGJisAYARqapGj4EAAA=
} 64#{
eJxz93SzsEwMZwhn+M4AAglg3ACmGsCsBjDnPxj/B1P/waz/YM4oGAXDBij+ZAHT
OiAClCfYOf4zMHLIEGxYcLCZQ1gr5sSGhYfbBZS95nhsXHS0W8I4686JjYuP9ys4
d81oBjYyMaj5ToqJNHjqOV0zsq/156RnnjPlcq9t6Zy8+Nx8w+okFq8vywK6XDv1
ZGdNeR7Uyb9oUY7X55dH2INX7trCZbr62oIYsa+vv65mRDRHs05rrRR7GLU09+K+
v5LmD++sKuW/d3R2+YO4fbUn//G+MV+bsKpF9JzvnSKDx/vbhJ3DTkbo3j5coB2v
F72z4MzWubrBbLJWl25fWuZv7/d6y4q0bdMNj6udub7mzYnGuVV+v6qK8k/sl/We
17Nb/+Ojyv5ytX0yFq/2LnRdfW3P79ef515b73/9nFRGSVPJ00c2fXwsf9685y1d
7B9ft/fu53ei/f3/5xnVtie8f33/P79wEKATeNBA4tYxoNGDrUVD5p4zF48aBZW
00h0ZGRksAYAd264o18EAAA=
} 64#{
eJxz93SzsEwMZwhn+M4AAglg3ACmGsCsBjDnPxj/B1P/waz/YM4oGAXDBij+ZAHT
OiAClCfYOf4zMHLIEGxYcLCZQ1gr5sSGhYfbBZS95nhsXHS0W8I4686JjYuP9ys4
d814blpycrJG8KqYk5tUvV5YialeG5edqBtPjSnpWBy/0YDCvDvwwsXh7Q6TL5
ki1UYGbQMv65Wq2nAl6FrApd++vIrA8HmRc4smbxni59cH294d46Vu2tOQc3OzDO
cc2+ujZiZ9zjc6mvr+hFNGV+/rt31bUX9xuTtybFWllsTFzXI5uv6xO2yXe3m669
nrf1xrAzDaLqX9bc2Jx8aVZ90bWcWYZXr6xj39+W++NT4K1VuZ9LeqPfpM2cWHj8
ytmQHx/u79b9zsf3e9un5iOth/QkYnd9fHvy/fSydbW15e8PBbYHLreJ+1Oyvld1
cX5tVe2Li+94t/X7y9b9Wf5y4mx3u5919d/Orr1+s8jyovr9ZFypjollXGYvHjQL
uGk8bBEJy3jYKpG24mGbTNmLh+0KbRqPOcTYWBisAbfrxM90BAAA
} 64#{
eJxz93SzsEwMZwhn+M4AAglg3ACmGsCsBjDnPxj/B1P/waz/YM4oGAXDBij+ZAHT
OiAClCfYOf4zMHLIEGxYcLCZQ1gr5sSGhYfbBZS95nhsXHS0W8I4686JjYuP9ys4
d814blpycrJG8KqYk5uWnp5ukHxqjufmZWdnWxRHhRwIfu46z6Hx1xSJLSsuLOtT
1XLdFfDy0mItFu5t4xfOayKWMt04NRVretrAvc3yWqVrTm/LnqlUuusba9Ct6aL
ctQ4mL+9syT3+JHWG0+Nd/fVpXxm88p8Q8y+G17/q511667sZjP7S0drqm7UHP/T
UrJ7Lnc/2zFFOXudlNWYg9uzvs6yO1NgEj29V3RXH2/1tztTthVv91t52+zdvcXZ
zPZ/rb99OKfvLF+vu+d50Xaju3b3bSutnj+fsTx4/sra6pK3N9fed2Op/2uR/OZ5
+/pQf7GKiJ37t1b905I3LVw7s//St1W7NgW8f/11+41qZr6O+MxvjuH3m3jMXjxo
FnDTeNgiEpbxsFUibUViGyMjgzUAhlm/D2keAAA=
} 64#{
eJxz93SzsEwMZwhn+M4AAglg3ACmGsCsBjDnPxj/B1P/waz/YM4oGAXDBij+ZAHT
OiAClCfYOf4zMHLIEGxYcLCZQ1gr5sSGhYfbBZS95nhsXHS0W8I4686JjYuP9ys4
d814blpycrJGcFnIagdVr2kGybtEJDernZmpnfscqp9P48bn5tvr/ZKSuPAPY4Koo
Fzvry8OgZb6Sdq1Sog9DZjJlh/16mLz2ZeDfU3c3SuClwzQm+RwsC6bqOC7JOrwo
Vnv72uht1gfbeK0n6MWtKW/8pbrj2/uI7QU/F9Vmf14XmbfnolxpjW1R3GGbyXZb
a3ZufLY619b5H8+vnNRL8z7K6ciWbnG80B7Y3SZrrZF7bVN+ee6q6uKr9/ZFM8/X
qfnx7s6xYpGr+s7oPXRwzEx83qes6svaa+v/nOortUp9fX9ve7j/ux8fp3x61rjY
vLZ6b+iNDpsPre/915a86itjv21cXGKk5p+Wx+fVM3K9CK15v7MtwZ1L74RCAP+b
xsMWkbCMh60SaSsetsmUvXjYrtCm8ahDZVrGo06NPFEBBmsAOJHARHoEAAA=
} 64#{
eJxz93SzsEwMZwhn+M4AAglg3ACmGsCsBjDnPxj/B1P/waz/YM4oGAXDBij+ZAHT
OiAClCfYOf4zMHLIEGxYcLCZQ1gr5sSGhYfbBZS95nhsXHS0W8I4a8uKBYvd+6Wd
i/54bFp8YjKf9yqTzk2ph6ZqxZ4S4dj87Mw00+J7IjM3Pz/Xalv674jElecXJrom
yq3NKFbwWC4/PSiE68FB511May/1aJkuClobLhqyV2pa9vUp8SeZBLjL1t7cZDM7
S9ViukrMlPCNYj2V5Y1B03x/7/uzu3RpQqsJL5tdjYFhyIF8yfehWT82Rmz3VxXf
9rvi0+VJs8zdv81sLYo/NK2b699pqS93r20wLu/lrTbNvbYt3/rcWmv9x5f2prb7
1VZbvHxwrPOln94u8+IzB/XV+/VsTEpfX15pn+9Xbf316b2J1cHP+6psKhc/43zk
d99Cs/qrxW17eW3N17Jfplaff17zb2/Rjz8/v8uWMf1aGt/IobbiQROP2YshzQJu
Gg9bRMiYhrZKpK142CZT9uJhu0KbxqMOLWk7Eh0YrAGyBMCKdgQAAA=
} 64#{
eJxz93SzsEwMZwhn+M4AAglg3ACmGsCsBjDnPxj/B1P/waz/YM4oGAXDBij+ZAHT
OiAClCfYOf4zMHLIEGxYcLCZQ1gr5sSGhYfbBZS95nhsXHS0W8I4686JjYuP9ys4
d814blpycrJG8KqYk5uWnp5ukHxqjufmZb79XEWvrlROfnRuvn21F4tXS0OFNptu
JttVBisuzfURtJsrdfXBLEWhnHFLZ5VqX18V18lnImW6JmWt/yamD1ofHG9tZbi0
TLV6ytrbOwqeHkrNctePaiypntX7u+z9rTml7OIxWiZrbhy2kbbm45IsTDrevTDu
GM/PgptrkzWj360qcfhi9nLH+b09VUA3Z62zPN+zNkLt7fvt+eK21tHf8w40Jv7S
Oxv148Pxxg73y1898t4h4Pnvh9rh5c9S+XjZbH/5+757K7y/22bc716+Lzn168ln4
db/1917kfwwbOH+6/zzLD8ez7p/X9/u1/d+fiEq2+Joe3owHjRxqKx408Zi9eNAs
4KbxsEUKLONhq0SaqaCDNQAYMLy/ZgQAAA==

```

```
}1
```

And here's an example of how to write the files in that block back to the hard drive and display them in a GUI:

```
; Write files:

count: 1
make-dir %./frames/
for count 1 length? anim-frames-block 1 [
  write/binary rejoin [
    %./frames/ "frame-" count ".gif"
  ] to-binary decompress pick anim-frames-block count
]

; Create file list, with frames in numerical order:

file-list: read %./frames/
animation-frames: copy []
for count 1 length? file-list 1 [
  append animation-frames rejoin [
    %./frames/ "frame-" count ".gif"
  ]
]

; Display that file list as an animation:

view layout [
  anim: anim rate 10 frames animation-frames
]
```

Here's an example that combines the above animated GIF files with normal GUI animation:

```
view center-face layout [
  size 625x415
  backcolor black
  anim: anim rate 10 frames load animation-frames
  btn "Run Animation" [
    for counter 0 31 1 [
      anim/offset: anim/offset + (as-pair counter 0)
      show anim wait .05
    ]
    for counter 0 24 1 [
      anim/offset: anim/offset + (as-pair 0 counter)
      show anim wait .05
    ]
    for counter 0 31 1 [
      anim/offset: anim/offset + (as-pair (negate counter) 0)
      show anim wait .05
    ]
    for counter 0 24 1 [
      anim/offset: anim/offset + (as-pair 0 (negate counter))
      show anim wait .05
    ]
  ]
]
```

9.6 3D Graphics with r3D

The "r3D" modeling engine by Andrew Hoadley is built entirely from native REBOL 2D draw functions. It demonstrates the significantly powerful potential of draw. The examples below show some of what you can accomplish with r3D:

```
do http://www.rebol.net/demos/BF02D682713522AA/i-rebot.r
do http://www.rebol.net/demos/BF02D682713522AA/histogram.r
do http://www.rebol.net/demos/BF02D682713522AA/objective.r
```

The r3D engine is small. Here's the entire module in compressed, embeddable format (this is all just standard REBOL code compressed into a more compact format). To enable 3D graphics in your REBOL programs, just include this text in your code (paste it, or "do" it from a file). If you'd like to read and learn from the pure REBOL code that makes up this module, see the examples above (the r3D module is included in those examples as regular text code):

```
do to-string decompress 64#{
eJzdPGtT28iWn+Nf0cOXsTMkYkGXznL1bBMzEtQSnjPMAipqSpTboRpa8kmwv37P
Od0tdethOzNTu1VLJUTqPu9XP5VR/8Pwmj002NhPA37KdML7cqfBzhfpcxTD63no
xfyFfYwL+Ar6PnK48SPwLnm7R3sHTQeG43GGbuI5qvYf3pOWdNtsc7BweEuMzER
6jOPZ36C2MxP2DOP+WTFnmInTlM3y6Yx5yyaMvfZiZ/4Lksj5oQrNgd+gBBNUscP
/fCJOcwFbgiZPgOZJJqmL07MGTBwQo85SRK5vgMkmRe5ixkPUyDfllM/4Alrps+c
7dxKpJ0W8fG4EzA/ZNinutiLDyZYpCzmSRr7LtLYBR5+6AYLDwVRAIE/8yUPJEB2
SJDsIgE1UNhdNos8f4r/ctJtvpgeFvK8yzwfiU8WKTQm20jyELCELvtRzBIEBEJD
B9lJ5VzCXDX+MzRrqm0FHF+eY5mpjZgqekiDoEpJxwvAsshH+D6b+6m2IYI0ygI
ohdUz41Cz0etk1N03hg6nUm05KSRCHYypSCwEAN9Mc8dLLuSZwfkN3BpNuANZnY0
lWUIEkhBnzWafCZRzExLWq7R0J87LPb4dX42/mozwa37PNo+HVW2b+EOL2F951d
9m0w/jj8MmYAMTq/Gd+x4RU7v7lj/zW4udx1/e+fR/3bWzYcscGnz9eDPrQNbi6u
v1wObv5gHwAPmNwMx+x68GkwBrrjIfGU1Ab9W6T3qT+6+Aiv5x8G14Px3S67Goxv
kOwVOD1nn89H48HF1+vzEfv8ZfR5eNsHCS4F5ZvBzdUIePU/9W/Ge8Ab21j/K7yw
24/n19fE7fwL6DAiKS+Gn+9Ggz8+jtnH4fV1Hxo/9EG48w/XfcENVLU4Ph982mWX
55/O/wABgQ90DIHQiCC1jN8+9qkJWJ7Dn4vxYHiDylwMb8YjeN0FXUfjDPXb4LYP
OTwa3KJlRkZD4IB2BQW03gOm/fDmpI/ooNVN5wAQvn+57efSXpPr4HaLcqqA+9R
Dwn/1R+qP1BDwpSCJra99syBrHrdilmbiUeK0SXEOQRc4E9iJ141zpCrG3OoFZCH
0ynUoxDyYDWXqQaFKZ1G8YxSO2k0kLDvAYyfrk5ZA2qm9gPVk3kf40+bNP7S506
QGWnAsBiy21Jgqs9BG38JJXu6CF0mpNm5EO4tINQJsB6BT1LB6sAZvg88kfHjy1C
H0w3jWXNcB2oUs40EftYg8ddf+YEvzyyHQ/LCIJg2XJCyG9ZNYo021Bfw19TqF4p
86m2vPE4Yr/8stN4NO1GLzH3FkDsQTeSVL/WkOq9115rAZDKPmiH/z7SIIzmJZcH
YMAaoc6p+LHDCqMJK3w0rZVsgXZjWCSiWDRoKAvHVTwTWXQ3WXQlRpwHd12Dd17De
JJJa0eJWRv5eto7rv6g13vz5IH1WUJq4T1Jms+tYyUFRHYmyCaYLDpg51L2Tm960M
uo7C3VbG3ZCZjaG/F2xTmtqdBlBp0ftNMW6YO45gFsK/GwY3jKoEhKrnB06CwiYk
5QCeqGKc1ElwiIYWN0ogsYMFtwgLmpG4eGDFq1ARKt4gNZSQCmRdfG155JqG116
brYF51aNKTLRZJuOW4tQJ1CFPe8Me94V7fk3DXqXGfROM+hdZtA706Cyu6R811Kp
rdLmbCtCS0PftUqOuFtjyWqrmVVGPLEMKSeaf+AHe8zO95rdrzP7HhfZcd7Xe/7
lqmJw0W0nZEUab7RPEU3bIWgno3IhDLE254fc1qVGHa9hAka/jxMgsj9gVXsK816
bIbTAViD4CCdoWilmwY41xf1bzFnBewvczVtmjkrMZGnZV1Ogr+6fA6rDyeGeT0P
cLAHIQS9fSAD0/pXrI9sRb/f8LeqRPRYS102EGdasCjiiE2dr1Wd+ObGUZLM4wh8
mLInkRYbyWAFHICncZzh2jdtzJS41EIKZ+LgSFxOj1OR8PprMOcxcxbw7GrcbSY
2Fi85BwR4hQd1BYDmBELoulPBWL6/IwWADZ5dMZTmEgyXEHa4HNYTePqDlwqgkIk
oCLzZxr9GUTRjz+dNKdmxJX+oyD0QEHXP2aBLFx5u5jALAccV8WmqMg/FVUQUiD0
/1ZUFbTYt346xooUOj8dcUUK9t+Nvln3ddY1om5m5WEX61QGQMyTRZDmMyl8OxUb
Pg8CEFZk3HGf2YPDJsxl3iORzYR15nMOQ4TAzJ1gjnQOew8C7Fst9htrTsRLj15c
8XJCL54Es1s5biWhjk7oUCdkHRIUuqlqArZ04MggYBkEeJUeUjQBY4NAXyBwqBF4
NJR61EyuBhrw4d12fzi7cLnGg9lcm+WzOTSZPiz6tc6xZb9Kcusc9T8upSucemZ
rOzv66/mIGKNYuz2/sCRiLzGVCXDw8LiP5+WpPwZFOGghj+HXRE6wDKFVag5dRRKo
m9Lufhrsv5wqkZti6SkVAcclasNwWvgPRHZDNrZhtReAwoyqglTuoJdqqho03Hs
rIzYWPIYN/2SQvGfddcFCiLx120yXkBqXDylfSYriiCxH3Vfl7Qj9dxoBlWQt4vV
i9aqUP1TY6hk1ALZKBiNag5+ZxbrvnYleHVtE1PUWbcdCJi9wa+n9Pk/NQYqEn3a
AoWxF8ffmGI8BAikfPib58RqQ0rNB2isOPsPdqAniVJY28kyY98PfdyIXSGO9rKF
RWnniHaH/RgURDFWRn+c5C25LtcFBrOinJBIRjAnF2QyXRxJuKyCvAWCLDOG9BAP
jEi1FrTn6I5MbhVMRnlnnYyDPN6c5TmNiJApsz9aJ1rfrDSH/BWkDTieLmiSCQNK
gx+b++4PPW4EY01Kyo7lpz7VaH+nMhq3GD7PWIYOcVoIyKxals0zqD0z/R78PcFn
SBqoJrP9Q3w5wF+Avo+tR/iCsBYCY+sxviCwdZitUaC0wMzxp+QGf4GfIFmxLGGV
97ims/SDjoyWID9Fe3t75SWJQEcPizg9Vi6S01TsNhXGyops56NA8YcUey+UXQd0
ICltINLdgnR+67fw45+w7fjbG/A38d+Ev0k/+7HstkpnZUGQ06zRbJIL94UsYp41
WrrUcqS19Kj1unVi7QyvU8KzS3iHCq9RQOtpQEclNKmfyc8qIR6XEE/K/OwaNflw
6Q+TX7dGUA0xkyGWXJUROiWRoqkjdgRI0CshSsNUyH5UJYIhhuDQKfnLLvmrW2H3
Tik+7FJ8IF6jgGeVDG+XDNGtiCurZHe7bAeTYbcGsVO2s8nRrPG0UzazybFXQpSC
VWdaBsvDEuZJnaw2sazi9LxAJxyPl7WkZzU1Wmh6XFNWZN6rwKkG6mxBoq5uyiCv
6bXX41pb8K2tt1vwXY+7XqNehXfKpmm6kTjxSfrFoIyn3PlYXV0lrW4pDaleKQ9h
WVqRUN1S5huohxlqsvZbdimlrIqivOBqlXGPY7gnFVztWsxuOa0KXLulEnfLmUW4
m+q2Va5X1bR6FaXbqqhZ1Ur0N1ZvArSr7DG9ZehZDqpkMUqLgitFk2UUuJM61JOy
cyyD6VFZXMtWAssAnBtOjsnDKyOVR6MQMOqsMZ9cfcGAOV1ZZ414JVelgWvikXuKy
w0Diqmru4d7wzA/hmfrg/ZQ1Zf1RdUGMGHmKNGUFyvo7pX7b6LdL/V2jv9vK1664
```

```

xqd7Y8vIx+tfeNYhl3OcNnASusmRCStvAfBURcdQnX9etVL3UL3h0ASg90iNtYob
DIWVXL4EVHsOXpTKNWRzR0XbMV3+zI6pEmlpkTuWarMT3jvivaPebffut9TKTd/X
/uvSNKRkledAlAM+2dQk6rcqCooNYCsXKhK5FSTI92zpXq5XtdOobCXOfk3YQ+zKm
BX7eBcl/L5yYt+M0SiFCmkshl3KHK5Q6iJhsmcce555g0KaMcbKBGbgf40bUVO
IClDPJvJpM6fFW+K27XyXMaNlmoq02zBay2AMR9Fmd0jqnTpFJFP+Wz7TbnBaiV
7Wo5bOP2fFNslDgClUwhWiayxdifrtglUUEpqWyg6OJuNvk/L8lWPtnDfZJ7nGZ
BlOtQHiYmGtuRxlOyWzly6jK73yRL/STKF+4P9/Zaj3LNXkmkva5zcNI9r+slnC
KGzT/be/aR8cwtbZyJ8y2vHdwz3fzzFexFOig+AkGZPi9n/KvR2lvSONAbTVgEjn
wf+olVHWNXYXls9OV3+65OJG5wprYn5A6wh95d0FdNcqWrAXPwjYE4zQZvFecX8Q
IdqPz2s/ElJL/zaZ2lFvaRZQjngwLmbJY4YKuGwKxJFgn0hWj2GkPIwPBLMOxJZk
6o82WD6ozTESlmzKSotmh3FMnsYx8ziOyOi9mntl36PJsnCOuKxliatP7C7womZW
w+bsLlWaxsu/hWvD4HQ/5HsxgxyHdzxG8MDxohnvCzdG1GJo8hLFgWcGqbhBa7bB
hOrf8sZMATZcOsmT/wYxgZPuyolxmjyK2S0+dTz8oIAH4rcQACqPEz4FPFLXITig
slnIOXA79iIB8u172Wse0gKlVbcplW9k7iKZiMiQILtBDLm4pzKF7a4CNLhRgN+d
5Nh2TvkTol+QNPapiym+YPKNpMpRz/Lr3OLCsJpEhBiKGLg6mTsunnfh7d5ldq9Z
qq6oEI2vgHrKcUEggiueoOC/BTS8rgUWfyAdXSjs8cNpRjHo+GHCOoyCg0IyVad+
u8xpEawscIkYf1r4SqeICd0Te4CfJjwleA6AspD0Qi3arqD5RtLitBECbmEs5wlk
ZiVElxdftzjWtpYys3W8sp3ysM6Ri6NJFqWELVKu44lVazvxZ7igU6lA0mcK6wml
4kkvjGcwCs+htCdRLKxVTAs2I+5CKY8q4zwV82aqHm9msIgg2wXEMeqHxbmmnlN
zg9xvhot0gCvJyZ0Bw/vEdCHNVBz0mcnlEeX9LUMkmNFQxUPvH+FVhimcgFg6LX2
cJX/qHHH8U+nOnES7jHwIQlBn/5AuCQbmSGNNnLU+D02atB+VZao6c8MldkEYGC8
6NaOg9lyuyoftrnKIEJtzQkmdYSSwsWy7BGXtpsmc7mFv2GV3fOAvy8LclvyFTV
6YxMzR0ZqgVSmLJnJyS1rzHEB18wAyRUH7LpVR3eI4kMf2mdiolbho7dUNNyieB4l
RO4yHOQRaOxGMfzyWpbjop1EwUjUyg0taBkQnSIEGDjnn4O689PyJT3NFWXiFO4I
TcUw3qc7QGo2ZQBIjVQlfgOPTaPyY/qlv09Z2zqAH+liJ8zXaWvjXl1MPOTQ1PNo
wHZqYTslWLsWlJzGzQ7lcatQdItmuaQulhSDPZvrlyVlLRVrI7my0YV7X7fOs6y+
bzN7gsJ/gYwfPaQL4F49p8KFkKrjsXGSIjkiKMKQIG60CEWovq3LVRgtIy/CVaHr
LmLcGFV1NB9wxEapRPLEXYhJj6esqanxHtYPPbmOTWqkzSAnE9pJULNItTcggsH
xVzmVw1lW33mkLK+/KBW5CbnHn1JCstbXB1RI5TMAIqJnmfYlHJHJr4mspAjAlUC
S8A8eEwwKbww/m/MMlJdn2octZEAZKdu9jved8pzU+ixDbeKZ9ldJoosvPRht5Hy
Flo2Trg2cwAz0FUgX36JYHDUI8uMlULWGSgohD0lV64TkUluMD+gEyrqlR/gzLpP
YhKBEuZSeqMqJQXLEkqV7NnCX6bOb8xJ2piPtMrFVay5UWtao+AuSqcshwxjYC5C
IRUPwOVgz9po12ZeDd5LxYfYfklHhdQIZbGF9rW8aXue01x5eXZmX7Kdzt0mdTzcf
E5mR4WL2lV7h4Uq19D0oxqgm83IxiXxwFXqV2lTFnr2yGSxe3nAmLMCth8Y7yAsp
Bbjh93+xx0FG6Hj3Tiyedz5QeNMWVQprCobd+J38jrZtQfOnh0z5d0r004y0GEyh
XS50VLut2j1qkhd3649bloKysfMniGbzoHfZUKbG0mSGX56oFmqi2D1lPclozh1h
7NzKxT0s4X/hkPz+AdBio7bcmGNNyhXlV+JRCwpa+JmtNtHBURclrbctaHX0Kb80
huqz9TiGCIg4qZwpzNRTWYRZlCcsNji3Gpg3k9nvmcMAKvddgV0dlMmwDopY6s5X
2aNGv8w4KqOuonMGYWZJ2uiYVN9vieLLLVtndRth+7q0uYirat25RlyHFDpaNLz
6PirPGJdh1SUAkLSSsqAKT0YqHYdteH4riJihUL5+ZoFHv474QU/9TRQyH+SkhGm
+XV8sEohZpFohXHKFVnfYNWka1PFZTuLEjgk/Zm9Q9oyxEovZga02mti1IH/P8aI
T6CO+jilCZM0hiUHOJ3OnuhTYg9mUBPczXmOXnB/AUJl4sPIG/vgR7x1HkCcnQmi
iTpCWEAQ7bfbDhx5EL3AwIrRxl+dEPdAoikSw2isXylIZNy4RylHtpdvX56xmwi/
bcfGZDHH/2kd5vugkNrP2cuCWPy/B9AYR4snCFebtsVxnANX0jBHwzdnjQYq1Za7
fvKi9lm2AKTXvNY+0BGDZeyS5+3tqo72+p46WupvJY9iR3t9T94hA07oKEILJv4h
qIoJ6QuuHl8gzTExEvCc9dihKQ68d4yWDrQcFVqOmG20NBxYXGg5Zl2jPQstVUJL
D/jpLcdA57DQcljAsoc/XWixM1606vsfGt6vyUFIAAA=
}

```

Here's a simple example that demonstrates the basic syntax and use of R3D. Be sure to do the code above before running this example:

```

Transx: Transy: Transz: 300.0           ; Set some camera
Lookatx: Lookaty: Lookatz: 100.0       ; positions to
                                         ; start with.

do update: does [
    world: copy []                     ; This "update" function is where
    append world reduce [              ; everything is defined.
        reduce [cube-model (r3d-scale 100.0 150.0 125.0) red]
    ]                                   ; Add your 3D objects inside this "append".
    camera: r3d-position-object        ; A red 'cube' 100x150x125 pixels is added.
    reduce [Transx Transy Transz]
    reduce [Lookatx Lookaty Lookatz]
    [0.0 0.0 1.0]
    RenderTriangles: render world camera r3d-perspective 250.0 400x360
    probe RenderTriangles              ; This line demonstrates what's going on
]                                       ; under the hood. You can eliminate it.

view layout [

```

```

scrn: box 400x360 black effect [draw RenderTriangles] ; basic draw
across return
slider 60x16 [Transx: (value * 600 - 300.0) update show scrn]
slider 60x16 [Transy: (value * 600 - 300.0) update show scrn]
slider 60x16 [Transz: (value * 600) update show scrn]
slider 60x16 [Lookatx: (value * 400 - 200.0) update show scrn]
slider 60x16 [Lookaty: (value * 400 - 200.0) update show scrn]
slider 60x16 [Lookatz: (value * 200 ) update show scrn]
1

```

R3D works by rendering 3D images to native REBOL 2D draw functions, which are contained in the "RenderTriangles" block above. R3D provides basic shape structures and a simple language interface to create and view those images in a REBOL application. It automatically adjusts lighting and other characteristics of images as they're viewed from different perspectives. To see how the rendering of images is converted into simple REBOL draw functions, watch the output of the "probe RenderTriangles" line in the REBOL interpreter as you adjust the sliders above. It displays the list of draw commands used to create each image in the moving 3D world.

In the example above, slider widgets are used to adjust values in the animation. Those values could just as easily be controlled by loops or other forms of data input. In the example below, the values are adjusted by keystrokes assigned to empty text widgets (use the "asdfghqwertz" keys to move the cube):

```

Transx: Transy: Transz: 2.0
Lookatx: Lookaty: Lookatz: 1.0
do update: does [
  world: copy []
  append world reduce [
    reduce [cube-model (r3d-scale 100.0 150.0 125.0) red]
  ]
  Rendered: render world
  r3d-position-object
  reduce [Transx Transy Transz]
  reduce [Lookatx Lookaty Lookatz]
  [0.0 0.0 1.0]
  r3d-perspective 360.0 400x360
]
view layout [
  across
  text "" #"a" [Transx: (Transx + 10) update show scrn]
  text "" #"s" [Transx: (Transx - 10) update show scrn]
  text "" #"d" [Transy: (Transy + 10) update show scrn]
  text "" #"f" [Transy: (Transy - 10) update show scrn]
  text "" #"g" [Transz: (Transz + 10) update show scrn]
  text "" #"h" [Transz: (Transz - 10) update show scrn]
  text "" #"q" [Lookatx: (Lookatx + 10) update show scrn]
  text "" #"w" [Lookatx: (Lookatx - 10) update show scrn]
  text "" #"e" [Lookaty: (Lookaty + 10) update show scrn]
  text "" #"r" [Lookaty: (Lookaty - 10) update show scrn]
  text "" #"t" [Lookatz: (Lookatz + 10) update show scrn]
  text "" #"y" [Lookatz: (Lookatz - 10) update show scrn]
  at 20x20
  scrn: box 400x360 black effect [draw Rendered]
]

```

The r3D module can work with models saved in native .R3d format, and the "OFF" format (established by the GeomView program at <http://www.geom.uiuc.edu/projects/visualization/>. See <http://local.wasp.uwa.edu.au/~pbourke/dataformats/oogl/#OFF> for a description of the OFF file format). A number of OFF example objects are available at <http://www.mpi-sb.mpg.de/~kettner/proj/obj3d/>.

To understand how to create/import and manipulate more complex 3D shapes, examine the way objects are designed inside the "update" function in each of Andrew's three examples. Here's a simplified variation of Andrew's objective.r example that loads .off models from the hard drive. Be sure to do the r3D module code above before running this example, and then try downloading and loading some of the example .off files at the web site above:

```
RenderTriangles: []
```



```

view layout [
  scrn: box 400x360 black effect [draw RenderTriangles]
  across return
  slider 60x16 [Transx: (value * 600 - 300.0) update show scrn]
  slider 60x16 [Transy: (value * 600 - 300.0) update show scrn]
  slider 60x16 [Transz: (value * 600) update show scrn]
  slider 60x16 [Lookatx: (value * 400 - 200.0) update show scrn]
  slider 60x16 [Lookaty: (value * 400 - 200.0) update show scrn]
  slider 60x16 [Lookatz: (value * 200 ) update show scrn]
  return btn "Load Model" [
    model: r3d-load-OFF load to-file request-file
    modelsize: 1.0
    if model/3 [modelsize: model/3]
    if modelsize < 1.0 [ modelsize: 1.0 ]
    defaultScale: 200.0 / modelsize
    objectScaleX: objectScaleY: objectScaleZ: defaultscale
    objectRotateX: objectRotateY: objectRotateZ: 0.0
    objectTranslateX: objectTranslateY: objectTranslateZ: 0.0
    Transx: Transy: Transz: 300.0
    Lookatx: Lookaty: Lookatz: 200.0
    modelWorld: r3d-compose-m4 reduce [
      r3d-scale objectScaleX objectScaleY objectScaleZ
      r3d-translate
        objectTranslateX objectTranslateY objectTranslateZ
      r3d-rotateX objectRotateX
      r3d-rotateY objectRotateY
      r3d-rotateZ objectRotateZ
    ]
    r3d-object: reduce [model modelWorld red]
    do update: does [
      world: copy []
      append world reduce [r3d-object]
      camera: r3d-position-object
        reduce [Transx Transy Transz]
        reduce [Lookatx Lookaty Lookatz]
        [0.0 0.0 1.0]
      RenderTriangles:
        render world camera r3d-perspective 250.0 400x360
    ]
    update show scrn
  ]
]

```

Like most REBOL solutions, r3D is a brilliantly simple, compact, and powerful design that doesn't require any external toolkits. It's pure REBOL, and it's really amazing!

9.6.1 Several 3D Scripts Using Raw REBOL Draw Dialect

The following short script is a compacted version of Gregory Pecheret's "ebuc-cube" (from <http://www.rebol.net/demos/download.html>). It demonstrates some simple 3d techniques using only native REBOL draw functions (no 3rd party library required). It's relatively easy to understand, manipulate, and use to create your own basic 3D graphics:

```

z: 10 h: z * 12 j: negate h c: as-pair z * 5 z * 5 l: z * 4 w: z * 20
img: to-image layout [box effect [draw [pen logo.gif circle c l]]]
q: make object! [x: 0 y: 0 z: 0]
cube: [[h h j] [h h h] [h j j] [h j h] [j h j] [j h h] [j j j] [j j h]]
view center-face layout [
  f: box 400x400 rate 0 feel [engage: func [f a e] [
    b: copy [] q/x: q/x + 5 q/y: q/y + 8 q/z: q/z + 3
    repeat n 8 [
      p: reduce pick cube n ; point
      zx: (p/1 * cosine q/z) - (p/2 * sine q/z) - p/1
      zy: (p/1 * sine q/z) + (p/2 * cosine q/z) - p/2
      yx: (p/1 + zx * cosine q/y) - (p/3 * sine q/y) - p/1 - zx
      yz: (p/1 + zx * sine q/y) + (p/3 * cosine q/y) - p/3
      xy: (p/2 + zy * cosine q/x) - (p/3 + yz * sine q/x) - p/2 - zy
      append b as-pair (p/1 + yx + zx + w) (p/2 + zy + xy + w)
    ]
  ]
]

```

```

f/effect: [draw [
    fill-pen 255.0.0.100 polygon b/6 b/2 b/4 b/8
    image img b/6 b/5 b/1 b/2
    fill-pen 255.159.215.100 polygon b/2 b/1 b/3 b/4
    fill-pen 54.232.255.100 polygon b/1 b/5 b/7 b/3
    fill-pen 0.0.255.100 polygon b/5 b/6 b/8 b/7
    fill-pen 248.255.54.100 polygon b/8 b/4 b/3 b/7
]]
show f
]]
]

```

Here's a version that reshapes and moves the 3D cube in, out and around the screen:

```

g: 12 i: 5 h: i * g j: negate h w: 0 v2: v1: 1 ; sizes/positions
img: to-image layout [box 200.200.200.50 center logo.gif]
q: make object! [x: 0 y: 0 z: 0]
cube: [[h h j] [h h h] [h j j] [h j h] [j h j] [j h h] [j j j] [j j h]]
view center-face layout/tight [
    f: box 500x450 rate 0 feel [engage: func [f a e] [
        b: copy [] q/x: q/x + 3 q/y: q/y + 3 ; q/z: q/z + 3 ; spinning
        repeat n 8 [
            if w > 500 [v1: 0] ; w: xy pos v1: xy direction
            if w < 0 [v1: 1]
            either v1 = 1 [w: w + 1] [w: w - 1]
            if j > (g * i * 2) [v2: 0] ; j: z pos (size) v2: z direction
            if j < g [v2: 1]
            either v2 = 1 [h: h - 1] [h: h + 1] j: negate h
            p: reduce pick cube n ; point
            zx: p/1 * cosine q/z - (p/2 * sine q/z) - p/1
            zy: p/1 * sine q/z + (p/2 * cosine q/z) - p/2
            yx: (p/1 + zx * cosine q/y) - (p/3 * sine q/y) - p/1 - zx
            yz: (p/1 + zx * sine q/y) + (p/3 * cosine q/y) - p/3
            xy: (p/2 + zy * cosine q/x) - (p/3 + yz * sine q/x) - p/2 - zy
            append b as-pair (p/1 + yx + zx + w) (p/2 + zy + xy + w)
        ]
    ]
    f/effect: [draw [
        image img b/6 b/5 b/1 b/2
        fill-pen 255.0.0.50 polygon b/6 b/2 b/4 b/8
        fill-pen 255.159.215.50 polygon b/2 b/1 b/3 b/4
        fill-pen 54.232.255.50 polygon b/1 b/5 b/7 b/3
        fill-pen 0.0.255.50 polygon b/5 b/6 b/8 b/7
        fill-pen 248.255.54.50 polygon b/8 b/4 b/3 b/7
    ]]
    show f
]]
]

```

And here's a little 3D game, with sound, based on the above code:

```

REBOL [title: "Little 3D Game"]

beep-sound: load to-binary decompress 64#{
eJwBUQKu/VJjRkZJAgAAV0FWRWZtdCAQAAAAQABABERAAARKwAAAQAIAGRhdGE1
AgAA0d3f1cGadFQ+T2Z9jn1lsjm8T2uNsM/j7Midc05PWGh4eXVrXE5DQEZumsTn
4M2yk3hiVU9fxc+GcFU8KkNmj7rR3+HYroJbPUpfdoqAbldBP0ZWbpW62OvRrohK
WlleaHB2dW9bRz0lWYWy3OHbyrKobVNCVGp/jXpgRC48Vnievtfm6MCUaUUVLWW1/
fXNkUkdCRlN7ps3r3cSkgm1fWFhmdH2AaVA6LElwnMja4dzNpHtXPuxje45/aVA5
PUtif6TG3uvMpHtXU1lkend2cGVURT0+ZJC84+HUvaGCZ1NIWm6AinVaQCtAX4Wu
yt3k37aJYEBKXXOHf3FdSEJET2KJsdPr1reUcGJbW2FsdXl2YUs5MFF7qdPe3tO+
mHNUP1Bnfo59ZEkyPFFukbTR5OvGm3BMTVlpent1aVpMQ0FJcZ3I6uHMsJB2YlZR
YXJ/hW5UOypEaJK90+Dg1qyBWjxKYHeLgG1WPz9HWHXKYvNnr0KyFYVhZX2pydnVu
Wkc7NlyHtN3h2sivjGxTRFZrgI15X0MtPVh7oshZ5ua+kmdES1tvgn5zY1BGQ0hW
fqjO69vBoX9rXl1aaHV9fmhPOi1Lcp/K2+DayaF4Vj1NY3uNfmhONjxLZIKnyODr
yqJ4VFFYZHN3dm5iUUM9QGATv+Th0rqdf2VTSltvgI10WT4rQGCIssze5N60iF8/
s110h39vW0ZBRFF1jLPU69W1kG1gW1xiYHkwb1ECAA=

```

```

}
alert {
  Try to click the bouncing REBOLs as many times as possible in
  30 seconds. The speed increases with each click!
}
do game: [
  speaker: open sound://
  g: 12 i: 5 h: i * g j: negate h x: y: z: w: sc: 0 v2: v1: 1 o: now
  img1: to-image layout [backcolor brown box red center logo.gif]
  img2: to-image layout [backcolor aqua box yellow center logo.gif]
  img3: to-image layout [backcolor green box tan center logo.gif]
  cube: [[h h j][h h h][h j j][h j h][j h j][j h h][j j j][j j h]]
  view center-face layout/tight [
    f: box white 550x550 rate 15 feel [engage: func [f a e] [
      if a = 'time [
        b: copy [] x: x + 3 y: y + 3 ; z: z + 3
        repeat n 8 [
          if w > 500 [v1: 0] if w < 50 [v1: 1]
          either v1 = 1 [w: w + 1] [w: w - 1]
          if j > (g * i * 1.4) [v2: 0] if j < 1 [v2: 1]
          either v2 = 1 [h: h - 1] [h: h + 1] j: negate h
          p: reduce pick cube n
          zx: p/1 * cosine z - (p/2 * sine z) - p/1
          zy: p/1 * sine z + (p/2 * cosine z) - p/2
          yx: (p/1 + zx * cosine y) - (p/3 * sine y) - p/1 - zx
          yz: (p/1 + zx * sine y) + (p/3 * cosine y) - p/3
          xy: (p/2 + zy * cosine x) - (p/3 + yz * sine x) - p/2 - zy
          append b as-pair (p/1 + yx + zx + w) (p/2 + zy + xy + w)
        ]
        f/effect: [draw [
          image img1 b/6 b/2 b/4 b/8
          image img2 b/6 b/5 b/1 b/2
          image img3 b/1 b/5 b/7 b/3
        ]]
        show f
        if now/time - o/time > :00:20 [
          close speaker
          either true = request [
            join "Time's Up! Final Score: " sc "Again" "Quit"
          ] [do game] [quit]
        ]
      ]
      if a = 'down [
        xblock: copy [] yblock: copy []
        repeat n 8 [
          append xblock first pick b n
          append yblock second pick b n
        ]
        if all [
          e/offset/1 >= first minimum-of xblock
          e/offset/1 <= first maximum-of xblock
          e/offset/2 >= first minimum-of yblock
          e/offset/2 <= first maximum-of yblock
        ]
        insert speaker beep-sound wait speaker
        sc: sc + 1
        t1/text: join "Score: " sc
        show t1
        if (modulo sc 3) = 0 [f/rate: f/rate + 1]
        show f
      ]
    ]
  ]
  at 200x0 t1: text brown "Click the bouncing REBOLs!"
]
]

```

9.7 Multitasking

"Threads" are a feature of modern operating systems that allow multiple pieces of code to run concurrently,

without waiting for the others to complete. Without threads, individual portions of code must be evaluated in consecutive order. Unfortunately, REBOL does not implement a formal mechanism for threading at the OS level, but *does* contain built-in support for asynchronous network port and services activity. See <http://www.rebol.net/docs/async-ports.html>, <http://www.rebol.net/docs/async-examples.html>, <http://www.rebol.net/rebervices/services-start.html>, and <http://www.rebol.net/rebervices/quick-start.html> for more information.

The following technique provides an alternate way to evaluate other types of code in a multitasking manner:

1. Assign a rate of 0 to a GUI item in a 'view layout' block.
2. Assign a "feel" detection to that item, and put the actions you want performed simultaneously inside the block that gets evaluated every time a 'time event' occurs.
3. Stop and start the evaluation of concurrently active portions of code by assigning a rate of "none" or 0, respectively, to the associated GUI item.

The following is an example of a webcam viewer which creates a video stream by repeatedly downloading and displaying images from a given webcam URL. To create a moving video effect, the process of downloading each image must run without stopping (i.e., in some sort of unending "forever" loop). But for a user to control the stop/start of the video flow (by clicking a button, for example), the interpreter must be able to check for user events that occur outside the forever loop. By running the repeated download using the technique outlined above, the program can continue to respond to other events while continuously looping the download code:

```
webcam-url: http://209.165.153.2/axis-cgi/jpg/image.cgi
view layout [
  btn "Start Video" [
    webcam/rate: 0
    webcam/image: load webcam-url
    show webcam
  ]
  btn "Stop Video" [webcam/rate: none show webcam]
  return
  webcam: image load webcam-url 320x240 rate 0 feel [
    engage: func [face action event][
      if action = 'time [
        face/image: load webcam-url show face
      ]
    ]
  ]
]
```

Here's an example in which two webcam video updates are treated as separate processes. Both can be stopped and started as needed:

```
webcam-url: http://209.165.153.2/axis-cgi/jpg/image.cgi
view layout [
  across
  btn "Start Camera 1" [
    webcam/rate: 0
    webcam/image: load webcam-url
    show webcam
  ]
  btn "Stop Camera 1" [webcam/rate: none show webcam]
  btn "Start Camera 2" [
    webcam2/rate: 0
    webcam2/image: load webcam-url
    show webcam2
  ]
  btn "Stop Camera 2" [webcam2/rate: none show webcam2]
  return
  webcam: image load webcam-url 320x240 rate 0 feel [
    engage: func [face action event][
      if action = 'time [
        face/image: load webcam-url show face
      ]
    ]
  ]
]
```

```

webcam2: image load webcam-url 320x240 rate 0 feel [
  engage: func [face action event][
    if action = 'time [
      face/image: load webcam-url show face
    ]
  ]
]
]

```

Unfortunately, this technique is not asynchronous. Each piece of event code is actually executed consecutively, in an alternating pattern, instead of simultaneously. Although the effect is similar (even indistinguishable) in many cases, the evaluation of code is not concurrent. For example, the following example adds a time display to the webcam viewer. You'll see that the clock is not updated every second. That's because the image download code and the clock code run alternately. The image download must be completed *before* the clock's 'time action can be evaluated. Try stopping the video to see the difference:

```

webcam-url: http://209.165.153.2/axis-cgi/jpg/image.cgi
view layout [
  btn "Start Video" [
    webcam/rate: 0
    webcam/image: load webcam-url
    show webcam
  ]
  btn "Stop Video" [webcam/rate: none show webcam]
  return
  webcam: image load webcam-url 320x240 rate 0 feel [
    engage: func [face action event][
      if action = 'time [
        face/image: load webcam-url show face
      ]
    ]
  ]
  clock: field to-string now/time/precise rate 0 feel [
    engage: func [face action event][
      if action = 'time [
        face/text: to-string now/time/precise show face
      ]
    ]
  ]
]
]

```

One solution to achieving truly asynchronous activity is to simply write the code for one process into a separate file and run it in a separate REBOL interpreter process using the "launch" function:

```

write %async.r {
  REBOL []
  view layout [
    clock: field to-string now/time/precise rate 0 feel [
      engage: func [face action event][
        if action = 'time [
          face/text: to-string now/time/precise show face
        ]
      ]
    ]
  ]
}

launch %async.r
; REBOL will NOT wait for the evaluation of code in async.r
; to complete before going on:

webcam-url: http://209.165.153.2/axis-cgi/jpg/image.cgi
view layout [
  btn "Start Video" [
    webcam/rate: 0
    webcam/image: load webcam-url

```

```

        show webcam
    ]
    btn "Stop Video" [webcam/rate: none show webcam]
    return
    webcam: image load webcam-url 320x240 rate 0 feel [
        engage: func [face action event][
            if action = 'time [
                face/image: load webcam-url show face
            ]
        ]
    ]
]

```

The technique above simply creates two totally separate REBOL programs from within a single code file. If such programs need to interact, share data, or respond to interactive activity states, they can communicate via tcp network port, or by reading/writing data via a shared storage device.

9.8 Using DLLs and Shared Code Files in REBOL

"Dll"s in Windows, "So" files in Linux, and "Dylib" on Macs are *libraries of functions* that can be shared among different programming languages. Shared code libraries are used to *extend the capabilities of a language with new functions*. They allow you to accomplish goals which aren't possible (or which are otherwise complicated) using the native functions built into the language. Most of the executable code, *and all the potential capabilities*, of most operating systems is contained in such files. Third party code libraries are also available to make easy work of complex tasks such as multimedia programming, 3d game programming, specialized hardware control, etc. To use DLLs and shared code files in REBOL, you'll need to download version 2.76 or later of the REBOL interpreter (rebview.exe). If you're using any of the beta versions from <http://www.rebol.net/builds/>, use either rebview.exe or rebcmdview.exe to run the examples in this section.

Using the format below, you can access and use the functions contained in most DLLs, *as if they're native REBOL functions*:

```

lib: load/library %TheNameOfYour.DLL

; "TheFunctionNameInsideTheDll" is loaded from the Dll and converted
; into a new REBOL function called "your-rebol-function-name":

your-rebol-function-name: make routine! [
    return-value: [data-type!]
    first-parameter [data-type!]
    another-parameter [data-type!]
    more-parameters [and-their-data-types!]
    ...
] lib "TheFunctionNameInsideTheDll"

; When the new REBOL function is used, it actually runs the function
; inside the Dll:

your-rebol-function-name parameter1 parameter2 ...

free lib

```

The first line opens access to the functions contained in the specified Dll. The following lines convert the function contained in the Dll to a format that can be used in REBOL. To make the conversion, a REBOL function is labeled and defined (i.e., "your-rebol-function-name" above), and a block containing the labels and types of parameters used and values returned from the function must be provided ("[return: [integer!]]" and "first-parameter [data-type!] another-parameter [data-type!] more-parameters [and-their-data-types!]" above). The name of the function, as labeled in the Dll, must also be provided immediately after the parameter block ("TheFunctionNameInsideTheDll" above). The second to last line above actually executes the new REBOL function, using any appropriate parameters you choose. When you're done using functions from the Dll, the last line is used to free up the Dll so that it's closed by the operating system.

Here are some examples:

```

REBOL [ ]

```

```

; The "kernel32.dll" is a standard dll in all Windows installations:

lib: load/library %kernel32.dll

; The "beep" function is contained in the kernel32.dll library.
; We'll create a new REBOL function called "play-sound" that
; actually executes the "beep" function in kernel32.dll. The
; "beep" function takes two integer parameters (pitch and
; duration values), and returns an integer value:

play-sound: make routine! [
    return: [integer!] pitch [integer!] duration [integer!]
] lib "Beep"

; (Beep returns a value of zero if the function does not complete
; successfully. Otherwise it returns a nonzero number).

; Now we can use the "play-sound" function AS IF IT'S A NATIVE
; REBOL FUNCTION:

for hertz 37 3987 50 [
    print rejoin ["The pitch is now " hertz " hertz."]
    play-sound hertz 50
]

free lib
halt

```

The following example demonstrates how to record sounds (with the microphone attached to your computer) using the Windows MCI API. When complete, the recorded sound is played back using a native REBOL sound port:

```

; Various mci functions are included in the winmm.dll library.
; We'll create a new REBOL function called "mciExecute" that
; allows us to run MCI functions in winmm.dll. This function
; function takes one string parameter (a text string written
; in MCI function syntax), and returns an integer value (true
; if the function is successful, false if it fails):

lib: load/library %winmm.dll
mciExecute: make routine! [
    command [string!]
    return: [logic!]
] lib "mciExecute"

; Get a file name from the user, which will be used to save the
; recorded sound:

file: to-local-file to-file request-file/save/title/file "Save as:" {
    } %rebol-recording.wav

; Open an MCI buffer and begin the recording:

mciExecute "open new type waveaudio alias buffer1 buffer 6"
mciExecute "record buffer1"

ask "RECORDING STARTED (press [ENTER] when done)...^/"

; Stop recording and save the sound to the wave file selected above:

mciExecute "stop buffer1"
mciExecute join "save buffer1 " file

; Close the DLL:

free lib

print "Recording complete. Here's how it sounds:^/"

```

```

; Play back the sound:

insert port: open sound:// load to-rebol-file file wait port close port
print "DONE.^/"

halt

```

The next example demonstrates how to play AVI video files, again using the Windows API "mciExecute" from winmm.dll. A demo video is downloaded from the Internet and played two times - once with default settings, and a second time at a given location on screen at twice the original recorded speed. The video codec in the demo video is MS-CRAM (Microsoft Video 1), and the audio format is PCM. For more information about mciExecute commands, Google "multimedia command strings" and see [http://msdn.microsoft.com/en-us/library/dd743572\(VS.85\).aspx](http://msdn.microsoft.com/en-us/library/dd743572(VS.85).aspx):

```

; These lines open the winmm.dll and define the "mciExecute" function
; in REBOL:

lib: load/library %winmm.dll
mciExecute: make routine! [c [string!] return: [logic!]] lib "mciExecute"

; These lines download a demo video:

if not exists? %test.avi [
    flash "Downloading test video..."
    write/binary %test.avi read/binary http://re-bol.com/test.avi
    unview
]
video: to-local-file %test.avi

; The lines run the mciExecute function with the commands needed to
; play the video:

mciExecute rejoin ["OPEN " video " TYPE AVIVIDEO ALIAS thevideo"]
mciExecute "PLAY thevideo WAIT"
mciExecute "CLOSE thevideo"

mciExecute rejoin ["OPEN " video " TYPE AVIVIDEO ALIAS thevideo"]
mciExecute "PUT thevideo WINDOW AT 200 200 0 0" ; at 200x200
mciExecute "SET thevideo SPEED 2000" ; play twice a fast
mciExecute "PLAY thevideo WAIT"
mciExecute "CLOSE thevideo"

; These lines clean up:

free lib
quit

```

The next example uses the "dictionary.dll" from <http://www.reelmedia.org/pureproject/archive411/dll/Dictionary.zip> to perform a spell check on text entered at the REBOL command line. There are two functions in the dll that are required to perform a spell check - "Dictionary_Load" and "Dictionary_Check":

```

REBOL []

check-me: ask "Enter a word to be spell-checked: "

lib: load/library %Dictionary.dll

; Two new REBOL functions are created, which actually run the
; Dictionary_Load and Dictionary_Check functions in the DLL:

load-dic: make routine! [
    a [string!]
    return: [none]
] lib "Dictionary_Load"

```



```

check-word: make routine! [
  a [string!]
  b [integer!]
  return: [integer!]
] lib "Dictionary_Check"

; This line runs the Dictionary_Load function from the DLL:

load-dic ""

; This line runs the Dictionary_Check function in the DLL, on
; whatever text was entered into the "check-me" variable above:

response: check-word check-me 0

; The Dictionary_Check function returns 0 if there are no errors:

either response = 0 [
  print "No spelling errors found."
] [
  print "That word is not in the dictionary."
]

free lib
halt

```

The following example plays an mp3 sound file using the DLL at <http://musiclessonz.com/mp3.dll>. Of course, that DLL could be compressed and embedded in the code to eliminate the necessity of downloading the file:

```

REBOL []

write/binary %mp3.dll read/binary http://musiclessonz.com/mp3.dll
lib: load/library %mp3.dll

; the "playfile" function is loaded from the Dll, and converted
; to a new REBOL "play-mp3" function:

play-mp3: make routine! [a [string!] return: [none]] lib "playfile"

; Then an mp3 file name is requested from the user, which is played
; by the "playfile" function in the Dll:

file: to-local-file to-string request-file
play-mp3 file

print "Done playing, Press [Esc] to quit this program: "
free lib

```

The next example uses the "AU3_MouseMove" function from the DLL version of [Autolt](#), to move the mouse around the screen. Autolt contains a wide variety of functions to programatically push buttons, type text, select menu items, choose items from lists, control the mouse, etc. in any existing program window, as if those actions had been performed by a user clicking and typing on screen. Learning the other functions in the Autolt language can be very helpful in customizing and automating existing Windows applications:

```

REBOL []

if not exists? %AutoItDLL.dll [
  write/binary %AutoItDLL.dll
  read/binary http://musiclessonz.com/rebol_tutorial/AutoItDLL.dll
]

lib: load/library %AutoItDLL.dll
move-mouse: make routine! [
  return: [integer!] x [integer!] y [integer!] z [integer!]
] lib "AUTOIT_MouseMove"

```

```

print "Press the [Enter] key to see your mouse move around the screen."
print "It will move to the top corner, and then down diagonally to"
ask "position 200x200:  "

for position 0 200 5 [
    move-mouse position position 10
    ; "10" refers to the speed of the mouse movement
]

free lib
print "^/Done.^/"
halt

```

This example uses DLL functions from the native Windows API to eliminate the default 'REBOL - ' text at the top of the GUI window:

```

REBOL []

; First, load the necessary dll:

user32.dll: load/library %user32.dll

; Then define the Windows API functions you'll need:

get-focus: make routine! [return: [int]] user32.dll "GetFocus"

set-caption: make routine! [
    hwnd [int]
    a [string!]
    return: [int]
] user32.dll "SetWindowTextA"

; Next, create your GUI - be sure to use 'view/new', so that it doesn't
; appear immediately (start the GUI later with 'do-events', after you've
; changed the title bar below):

view/new center-face layout [
    backcolor white
    text bold "Notice that there's no 'Rebol - ' in the title bar above."
    text "New title text:"
    across
    f: field "Tada!"
    btn "Change Title" [
        ; These functions change the text in the title bar:
        hwnd: get-focus
        set-caption hwnd f/text
    ]
    btn "Exit" [
        ; Be sure to close the dll when you're done:
        free user32.dll
        quit
    ]
]

; Once you've created your GUI, run the Dll functions to replace the
; default text in the title bar:

hwnd: get-focus
set-caption hwnd "My Title"

; Finally, start your GUI:

do-events

```

Here's a slightly more versatile version of the above script. You can add it to the top of any existing GUI script, and it will remove the default "REBOL -" text from *all* GUI title bars, including alerts and requestors:

```

title-text: "My Program"
if system/version/4 = 3 [
  user32.dll: load/library %user32.dll
  get-tb-focus: make routine! [return: [int]] user32.dll "GetFocus"
  set-caption: make routine! [
    hwnd [int]
    a [string!]
    return: [int]
  ] user32.dll "SetWindowTextA"
  show-old: :show
  show: func [face] [
    show-old [face]
    hwnd: get-tb-focus
    set-caption hwnd title-text
  ]
]

```

The following application demonstrates how to use the Windows API to view video from a local web cam, to save snapshots in BMP format, and to change the REBOL GUI window title:

```

REBOL []

; First, open the Dlls that contain the Windows API functions we want
; to use (to view webcam video, and to change window titles):

avicap32.dll: load/library %avicap32.dll
user32.dll: load/library %user32.dll

; Create REBOL function prototypes required to change window titles:
; (These functions are found in user32.dll, built in to Windows.)

get-focus: make routine! [return: [int]] user32.dll "GetFocus"
set-caption: make routine! [
  hwnd [int] a [string!] return: [int]
] user32.dll "SetWindowTextA"

; Create REBOL function prototypes required to view the webcam:
; (also built in to Windows)

find-window-by-class: make routine! [
  ClassName [string!] WindowName [integer!] return: [integer!]
] user32.dll "FindWindowA"
sendmessage: make routine! [
  hwnd [integer!] val1 [integer!] val2 [integer!] val3 [integer!]
  return: [integer!]
] user32.dll "SendMessageA"
sendmessage-file: make routine! [
  hwnd [integer!] val1 [integer!] val2 [integer!] val3 [string!]
  return: [integer!]
] user32.dll "SendMessageA"
cap: make routine! [
  cap [string!] child-val1 [integer!] val2 [integer!] val3 [integer!]
  width [integer!] height [integer!] handle [integer!]
  val4 [integer!] return: [integer!]
] avicap32.dll "capCreateCaptureWindowA"

; Create the REBOL GUI window:

view/new center-face layout/tight [
  image 320x240
  across
  btn "Take Snapshot" [
    ; Run the dll functions that take a snapshot:
    sendmessage cap-result 1085 0 0
    sendmessage-file cap-result 1049 0 "scrshot.bmp"
  ]
  btn "Exit" [
    ; Run the dll functions that stop the video:

```

```

        sendmessage cap-result 1205 0 0
        sendmessage cap-result 1035 0 0
        free user32.dll
        quit
    ]
]

; Run the Dll functions that reset our REBOL GUI window title:
; (eliminates "REBOL - " in the title bar)

hwnd-set-title: get-focus
set-caption hwnd-set-title "Web Camera"

; Run the Dll functions that show the video:

hwnd: find-window-by-class "REBOLWind" 0
cap-result: cap "cap" 1342177280 0 0 320 240 hwnd 0
sendmessage cap-result 1034 0 0
sendmessage cap-result 1077 1 0
sendmessage cap-result 1075 1 0
sendmessage cap-result 1074 1 0
sendmessage cap-result 1076 1 0

; start the GUI:

do-events

```

For more information about DLLs and the Windows API, see:

<http://rebol.com/docs/library.html>
http://en.wikipedia.org/wiki/Dynamic_Link_Library
<http://www.math.grin.edu/~shirema1/docs/DLLsinREBOL.html>
<http://www.borland.com/devsupport/borlandcpp/patches/BC52HLP1.ZIP>
<http://www.allapi.net/downloads/apiguide/agsetup.exe>
<http://www.activevb.de/rubriken/apiviewer/index-apiviewereng.html>
<http://msdn.microsoft.com/library/>

Remember, whenever you use any Dll or code created by another programmer, be absolutely sure to check, and follow, the licensing terms by which it's distributed.

9.9 Web Programming and the CGI Interface

In "CGI" web applications, HTML forms on a web site act as the user interface (GUI) for scripts that run on a web server. Users typically type text into fields, select choices from drop down lists, click check boxes, and otherwise enter data into form widgets on a web page, and then click a "submit" button when done. The submitted data is transferred to, and processed by, a script that you've stored at a specified URL (Internet address) on your web server. Data output from the script is then sent back to the user's browser and displayed on screen as a dynamically created web page. CGI programs of that sort, running on web sites, are among the most common types of computer application in contemporary use. PHP, Python, Java, PERL, and ASP are popular languages used to accomplish similar Internet programming tasks, but if you know REBOL, you don't need to learn them. REBOL's CGI interface makes Internet programming very easy.

In order to create REBOL CGI programs, you need an available web server. A web server is a computer attached to the Internet, which constantly runs a program that stores and sends out web page text and data, when requested from an Internet browser running on another computer. The most popular web serving application is [Apache](#). Most small web sites are typically run on shared web server hosting accounts, rented from a data center for a few dollars per month (see <http://www.lunarpages.com/> - they're REBOL friendly). While setting up a web server account, you can register an available *domain name* (i.e., [www.yourwebsitename.com](#)). When web site visitors type your ".com" domain address into their browser, they see files that you've created and saved into a publicly accessible file folder on your web server computer.

In order for REBOL CGI scripts to run, the REBOL interpreter must be [installed](#) on your web server. To do that, download from [rebol.com](#) the correct version of the REBOL interpreter for the operating system on which your web server runs (most often some type of Linux). Upload it to your user path on your web server, and **set the permissions to allow it to be executed** (typically "755"). Ask your web site host if you don't understand what that means. <http://rebol.com/docs/cgi1.html#section-2.2> has some basic information about how to install REBOL on your server. If you don't have an online web server account, you can

download a full featured free Apache web server package that will run on your local Windows PC, from <http://www.uniformserver.com/>.

9.9.1 HTML

In order to create any sort of CGI application, you need to understand a bit about HTML. HTML is the layout language used to format text and GUI elements on all web pages. HTML is not a programming language - it doesn't have facilities to process or manipulate data. It's simply a markup format that allows you to shape the visual appearance of text, images, and other items on pages viewed in a browser.

In HTML, items on a web page are enclosed between starting and ending "tags":

```
<STARTING TAG>Some item to be included on a web page</ENDING TAG>
```

There are tags to effect the layout in every possible way. To bold some text, for example, surround it in opening and closing "strong" tags:

```
<STRONG>some bolded text</STRONG>
```

The code above appears on a web page as: **some bolded text**.

To italicize text, surround it in `< i >` and `< / i >` tags:

```
<i>some italicized text</i>
```

That appears on a web page as: *some italicized text*.

To create a table with three rows of data, do the following:

```
<TABLE border=1>
  <TR><TD>First Row</TD></TR>
  <TR><TD>Second Row</TD></TR>
  <TR><TD>Third Row</TD></TR>
</TABLE>
```

Notice that every

```
<opening tag>
```

in HTML code is followed by a corresponding

```
</closing tag>
```

Some tags surround all of the page, some tags surround portions of the page, and they're often nested inside one another to create more complex designs.

A minimal format to create a web page is shown below. Notice that the title is nested between "head" tags, and the entire document is nested within "HTML" tags. The page content seen by the user is surrounded by "body" tags:

```
<HTML>
  <HEAD>
    <TITLE>Page title</TITLE>
```

```

</HEAD>
<BODY>
    A bunch of text and <i>HTML formatting</i> goes here...
</BODY>
</HTML>

```

If you save the above code to a text file called "yourpage.html", upload it to your web server, and surf to <http://yourwebserver.com/yourpage.html>, you'll see in your browser a page entitled "Page title", with the text "A bunch of text and *HTML formatting* goes here...". All web pages work that way - this tutorial is in fact just an HTML document stored on the author's web server account. Click View -> Source in your browser, and you'll see the HTML tags that were used to format this document.

9.9.2 HTML Forms and Server Scripts - the Basic CGI Model

The following HTML example contains a "form" tag inside the standard HTML head and body layout. Inside the form tags are a text input field tag, and a submit button tag:

```

<HTML>
  <HEAD><TITLE>Data Entry Form</TITLE></HEAD>
  <BODY>
    <FORM ACTION="http://yourwebserver.com/your_rebol_script.cgi">
      <INPUT TYPE="TEXT" NAME="username" SIZE="25">
      <INPUT TYPE="SUBMIT" NAME="Submit" VALUE="Submit">
    </FORM>
  </BODY>
</HTML>

```

Forms can contain tags for a variety of input types: multi-line text areas, drop down selection boxes, check boxes, etc. See http://www.w3schools.com/html/html_forms.asp for more information about form tags.

You can use the data entered into any form by pointing the *action* address to the URL at which a specific REBOL script is located. For example, "FORM ACTION="http://yourwebserver.com/your_rebol_script.cgi" in the above form could point to the URL of the following CGI script, which is saved as a text file on your web server. When a web site visitor clicks the submit button in the above form, the data is sent to the following program, which in turn does some processing, and *prints output directly to the user's web browser*. NOTE: Remember that in REBOL *curly brackets are the same as quotes*. Curly brackets are used in all the following examples, because they allow for multiline content and they help improve readability by clearly showing where strings begin and end:

```

#!/home/your_user_path/rebol/rebol -cs
REBOL []
print {content-type: text/html^/}
; the line above is the same as: print "content-type: text/html^/"
submitted: decode-cgi system/options/cgi/query-string

print {<HTML><HEAD><TITLE>Page title</TITLE></HEAD><BODY>}
print rejoin [{Hello } second submitted {!}]
print {</BODY></HTML>}

```

In order for the above code to actually run on your web server, a working REBOL interpreter must be installed in the path designated by "/home/your_user_path/rebol/rebol -cs".

The first 4 lines of the above script are basically stock code. Include them at the top of every REBOL CGI script. Notice the "decode-cgi" line - it's the key to retrieving data submitted by HTML forms. In the code above, the decoded data is assigned the variable name "submitted". The submitted form data can be manipulated however desired, and *output is then returned to the user via the "print" function*. That's important to understand: *all data "print"ed by a REBOL CGI program appears directly in the user's web browser* (i.e., to the web visitor who entered data into the HTML form). The printed data is typically laid out with HTML formatting, so that it appears as a nicely formed web page in the user's browser.

Any normal REBOL code can be included in a CGI script - you can perform any type of data storage, retrieval, organization, and manipulation that can occur in any other REBOL program. The CGI interface just allows your REBOL code to run online on your web server, and for data to be input/output via web pages which are also stored on the web server, accessible by any visitor's browser.

9.9.3 A Standard CGI Template to Memorize

Most short CGI programs typically *print an initial HTML form to obtain data from the user*. In the initial printed form, the *action address typically points back to the same URL address as the script itself*. The script examines the submitted data, and if it's empty (i.e., no data has been submitted), the program prints the initial HTML form. Otherwise, it manipulates the submitted data in way(s) you choose and then prints some output to the user's web browser in the form of a new HTML page. Here's a basic example of that process, using the code above:

```
#!/home/your_user_path/rebol/rebol -cs
REBOL []
print {content-type: text/html^/}
submitted: decode-cgi system/options/cgi/query-string

; The 4 lines above are the standard REBOL CGI headers.
; The line below prints the standard HTML, head and body
; tags to the visitor's browser:

print {<HTML><HEAD><TITLE>Page title</TITLE></HEAD><BODY>}

; Next, determine if any data has been submitted.
; Print the initial form if empty. Otherwise, process
; and print out some HTML using the submitted data.
; Finally, print the standard closing "body" and "html"
; tags, which were opened above:

either empty? submitted [
  print {
    <FORM ACTION="http://yourwebserver.com/this_rebol_script.cgi">
    <INPUT TYPE="TEXT" NAME="username" SIZE="25">
    <INPUT TYPE="SUBMIT" NAME="Submit" VALUE="Submit">
    </FORM>
    </BODY></HTML>
  }
] [
  print rejoin [{Hello } second submitted {!}]
  print {</BODY></HTML>}
]
```

Using the above standard outline, you can include any required HTML form(s), along with all executable code and data required to make a complete CGI program, all in one script file. *Memorize it.*

9.9.4 Examples

Here's a REBOL CGI form-mail program that prints an initial form, then sends an email to a given address containing the user-submitted data:

```
#!/home/youruserpath/rebol/rebol -cs
REBOL []
print {content-type: text/html^/}
submitted: decode-cgi system/options/cgi/query-string

; the following account info is required to send email:

set-net [from_address@website.com smtp.website.com]

; print a more complicated HTML header:

print read %template_header.html

; if some form data has been submitted to the script:

if not empty? submitted [
  sent-message: rejoin [
    newline {INFO SUBMITTED BY WEB FORM} newline newline
    {Time Stamp: } (now + 3:00) newline
    {Name: } submitted/2 newline
  ]
]
```

```

        {Email: } submitted/4 newline
        {Message: } submitted/6 newline
    ]

    send/subject to_address@website.com sent-message "FORM SUBMISSION"

    html: copy {}
    foreach [var value] submitted [
        repend html [<TR><TD> mold var </TD><TD> mold value </TD></TR>]
    ]
    print {<font size=5>Thank You!</font> <br><br>
        The following information has been sent: <BR><BR>}
    print rejoin [{Time Stamp: } now + 3:00]
    print {<BR><BR><table>}
    print html
    print {</table>}
    ; print a more complicated HTML footer:
    print read %template_footer.html
    quit
]

; if no form data has been submitted, print the initial form:

print {
    <CENTER><TABLE><TR><TD>
    <BR><strong>Please enter your info below:</strong><BR><BR>
    <FORM ACTION="http://yourwebserver.com/this_rebol_script.cgi">
    Name: <BR> <INPUT TYPE="TEXT" NAME="name"><BR><BR>
    Email: <BR> <INPUT TYPE="TEXT" NAME="email"><BR><BR>
    Message: <BR>
    <TEXTAREA cols=75 name=message rows=5></TEXTAREA> <BR><BR>
    <INPUT TYPE="SUBMIT" NAME="Submit" VALUE="Submit">
    </FORM>
    </TD></TR></TABLE></CENTER>
}
print read %template_footer.html

```

The template_header.html file used in the above example can include the standard required HTML outline, along with any formatting tags and static content that you'd like, in order to present a nicely designed page. A basic layout may include something similar to the following:

```

<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
<HTML><HEAD><TITLE>Page Title</TITLE>
<META http-equiv=Content-Type content="text/html;
    charset=windows-1252">
</HEAD>
<BODY bgColor=#000000>
<TABLE align=center background="" border=0
    cellpadding=20 cellspacing=2 height="100%" width="85%">
<TR>
<TD background="" bgColor=white vAlign=top>

```

The footer closes any tables or tags opened in the header, and may include any static content that appears after the CGI script (copyright info, logos, etc.):

```

</TD>
</TR>
</TABLE>
<TABLE align=center background="" border=0
    cellpadding=20 cellspacing=2 width="95%">
<TR>
<TD background="" cellpadding=2 bgColor=#000000 height=5>
<P align=center><FONT color=white size=1>Copyright © 2009
    Yoursite.com. All rights reserved.</FONT>
</P>
</TD>

```



```

</TR>
</TABLE>
</BODY>
</HTML>

```

The following example demonstrates how to automatically build lists of days, months, times, and data read from a file, using dynamic loops (foreach, for, etc.). The items are selectable from drop down lists in the printed HTML form:

```

#!/home/youruserpath/rebol/rebol -cs
REBOL []
print {content-type: text/html^/}
submitted: decode-cgi system/options/cgi/query-string

print {<HTML><HEAD><TITLE>Dropdown Lists</TITLE></HEAD><BODY>}

if not empty? submitted [
  print rejoin [{NAME SELECTED: } submitted/2 {<BR><BR>}]
  selected: rejoin [
    {TIME/DATE SELECTED: }
    submitted/4 { } submitted/6 {, } submitted/8
  ]
  print selected
  quit
]

; If no data has been submitted, print the initial form:

print {<FORM ACTION="http://yourwebserver.com/your_rebol_script.cgi">
  SELECT A NAME:  <BR> <BR>}
names: read/lines %users.txt
print {<select NAME="names">}
foreach name names [prin rejoin [{<option>} name]]
print {</option> </select> <br> <br>}

print { SELECT A DATE AND TIME: }
print rejoin [{(today's date is } now/date {} } <BR><BR>]

print {<select NAME="month">}
foreach m system/locale/months [prin rejoin [{<option>} m]]
print {</option> </select>}

print {<select NAME="date">}
for daysinmonth 1 31 1 [prin rejoin [{<option>} daysinmonth]]
print {</option> </select>}

print {<select NAME="time">}
for time 10:00am 12:30pm :30 [prin rejoin [{<option>} time]]
for time 1:00 10:00 :30 [prin rejoin [{<option>} time]]
print {</option> </select> <br> <br>}

print {<INPUT TYPE="SUBMIT" NAME="Submit" VALUE="Submit"></FORM>}

```

The "users.txt" file used in the above example may look something like this:

```

nick
john
jim
bob

```

Here's a simple CGI program that displays all photos in the current folder on a web site, using a foreach loop:

```

#!/home/path/public_html/rebol/rebol -cs

```

```

REBOL [title: "Photo Viewer"]
print {content-type: text/html^/}
print {<HTML><HEAD><TITLE>Photos</TITLE></HEAD><BODY>}
print read %template_header.html

folder: read %.
count: 0
foreach file folder [
  foreach ext [".jpg" ".gif" ".png" ".bmp"] [
    if find file ext [
      print [<BR> <CENTER>]
      print rejoin [{}]
      print [</CENTER>]
      count: count + 1
    ]
  ]
]
print {<BR>}
print rejoin [{Total Images: } count]
print read %template_footer.html

```

Notice that there's no "submitted: decode-cgi system/options/cgi/query-string" code in the above example. That's because the above script doesn't make use of any data submitted from a form.

Here's a simple but powerful script that allows you to type REBOL code into an HTML text area, and have that code execute directly on your web server. The results of the code are then displayed in your browser. This essentially functions as a remote console for the REBOL interpreter on your server. You can use it to run REBOL code, or to call shell programs directly on your web site - very powerful! *DO NOT run this on your web server if you're concerned at all about security!*

```

#! /home/path/public_html/rebol/rebol276 -cs
REBOL [Title: "CGI Remote Console"]
print {content-type: text/html^/}
print {<HTML><HEAD><TITLE>Console</TITLE></HEAD><BODY>}
submitted: decode-cgi system/options/cgi/query-string

; If no data has been submitted, print form to request user/pass:

if ((submitted/2 = none) or (submitted/4 = none)) [
  print {
    <STRONG>W A R N I N G - Private Server, Login Required:</STRONG>
    <BR><BR>
    <FORM ACTION="./console.cgi">
    Username: <INPUT TYPE=text SIZE="50" NAME="name"><BR><BR>
    Password: <INPUT TYPE=text SIZE="50" NAME="pass"><BR><BR>
    <INPUT TYPE="SUBMIT" NAME="Submit" VALUE="Submit">
    </FORM>
  }
  quit
]

; If code has been submitted, print the output:

entry-form: [
  print {
    <CENTER><FORM METHOD="get" ACTION="./console.cgi">
    <INPUT TYPE=hidden NAME=submit_confirm VALUE="command-submitted">
    <TEXTAREA COLS="100" ROWS="10" NAME="contents"></TEXTAREA><BR><BR>
    <INPUT TYPE="SUBMIT" NAME="Submit" VALUE="Submit">
    </FORM></CENTER></BODY></HTML>
  }
]

if submitted/2 = "command-submitted" [
  write %commands.txt join "REBOL[]" submitted/4
  ; The "call" function requires REBOL version 2.76:
  call/output/error
    {/home/path/public_html/rebol/rebol276 -qs commands.txt}
    %conso.txt %conse.txt

```

```

do entry-form
print rejoin [
  {<CENTER>Output: <BR><BR>}
  {<TABLE WIDTH=80% BORDER="1" CELLPADDING="10"><TR><TD><PRE>}
  read %conso.txt
  {</PRE></TD></TR></TABLE><BR><BR>}
  {Errors: <BR><BR>}
  read %conse.txt
  {</CENTER>}
]
quit
]

; Otherwise, check submitted user/pass, then print form for code entry:

username: submitted/2 password: submitted/4
either (username = "user") and (password = "pass") [
  ; if user/pass is ok, go on
][
  print "Incorrect Username/Password." quit
]

do entry-form

```

Upload the script to your server, rename it "console.cgi", set it to executable, and change the path to your REBOL interpreter (2 places in the script). Then try running the following example code:

```

print 352 + 836
? system/locale/months
call "ls -al"

```

Here's an example that allows users to check attendance at various weekly events, and add/remove their names from each of the events. It stores all the user information in a flat file (simple text file) named "jams.db":

```

#! /home/path/public_html/rebol/rebol -cs
REBOL [title: "event.cgi"]
print {content-type: text/html^/}
print {<HTML><HEAD><TITLE>Event Sign-Up</TITLE></HEAD><BODY>}

jams: load %jam.db

a-line: [] loop 65 [append a-line "-"]
a-line: trim to-string a-line

print {
  <hr> <font size=5>" Sign up for an event:"</font> <hr><BR>
  <FORM ACTION="http://yourwebsite.com/cgi-bin/event.cgi">
  Student Name:
  <input type=text size="50" name="student"><BR><BR>
  ADD yourself to this event:
  <select NAME="add"><option>"<option>"all"
}
foreach jam jams [prin rejoin [{<option>} jam/1]]
print {
  </option> </select> <BR> <BR>
  REMOVE yourself from this event:
  <select NAME="remove"><option>"<option>"all"
}
foreach jam jams [prin rejoin [{<option>} jam/1]]
print {
  </option> </select> <BR> <BR>
  <INPUT TYPE="SUBMIT" NAME="Submit" VALUE="Submit">
  </FORM>
}

```

```

print-all: does [
  print [<br><hr><font size=5>]
  print " Currently scheduled events, and current attendance:"
  print [</font><br>]
  foreach jam jams [
    print rejoin [a-line {<br>} jam/1 {BR} a-line {<br>}]
    for person 2 (length? jam) 1 [
      print jam/:person
      print {<br>}
    ]
    print {<br>}
  ]
  print {</BODY></HTML>}
]

submitted: decode-cgi system/options/cgi/query-string

if submitted/2 <> none [
  if ((submitted/4 = "") and (submitted/6 = "")) [
    print {
      <strong> Please try again. You must choose an event.</strong>
    }
    print-all
    quit
  ]
  if ((submitted/4 <> "") and (submitted/6 <> "")) [
    print {
      <strong> Please try again. Choose add OR remove.</strong>
    }
    print-all
    quit
  ]
  if submitted/4 = "all" [
    foreach jam jams [append jam submitted/2]
    save %jam.db jams
    print {
      <strong> Your name has been added to every event:</strong>
    }
    print-all
    quit
  ]
  if submitted/6 = "all" [
    foreach jam jams [
      if find jam submitted/2 [
        remove-each name jam [name = submitted/2]
        save %jam.db jams
      ]
    ]
    print {
      <strong> Your name has been removed from all events:</strong>
    }
    print-all
    quit
  ]
  foreach jam jams [
    if (find jam submitted/4) [
      append jam submitted/2
      save %jam.db jams
      print {
        <strong> Your name has been added to the selected event:
        </strong>
      }
      print-all
      quit
    ]
  ]
  found: false
  foreach jam jams [
    if (find jam submitted/6) [
      if (find jam submitted/2) [
        remove-each name jam [name = submitted/2]
        save %jam.db jams
      ]
    ]
  ]
]

```

```

        print {
            <strong>
                Your name has been removed from the selected event:
            </strong>
        }
        print-all
        quit
        found: true
    ]
]
]
if found <> true [
    print {
        <strong> That name is not found in the specified event!</strong>
    }
    print-all
    quit
]
]
print-all

```

Here is a sample of the "jam.db" data file used in the above example:

```

["Sunday September 16, 4:00 pm - Jam CLASS"
 "Nick Antonaccio" "Ryan Gaughan" "Mark Carson"]
["Sunday September 23, 4:00 pm - Jam CLASS"
 "Nick Antonaccio" "Ryan Gaughan" "Mark Carson"]
["Sunday September 30, 4:00 pm - Jam CLASS"
 "Nick Antonaccio" "Ryan Gaughan" "Mark Carson"]

```

Here's a simple web site bulletin board program:

```

#! /home/path/public_html/rebol/rebol -cs
REBOL [title: "Jam"]
print {content-type: text/html^/}
print read %template_header.html
; print {<HTML><HEAD><TITLE>Bulletin Board</TITLE></HEAD><BODY>}

bbs: load %bb.db

print {
    <center><table border=1 cellpadding=10 width=600><tr><td>
    <center><strong><font size=4>
    Please REFRESH this page to see new messages.
    </font></strong></center>
    }

print-all: does [
    print {<br><hr><font size=5> Posted Messages: </font> <br><hr>}
    foreach bb (reverse bbs) [
        print rejoin [
            {<BR>Date/Time: } bb/2 {
            {<BR>Name: } bb/1 {<BR><BR>} bb/3 {<BR><BR><HR>}
        ]
    ]
]

submitted: decode-cgi system/options/cgi/query-string

if submitted/2 <> none [
    entry: copy []
    append entry submitted/2
    append entry to-string (now + 3:00)
    append entry submitted/4

```

```

    append/only bbs entry
    save %bb.db bbs
    print {<BR><strong>Your message has been added: </strong><BR>}
}

print-all

print {
    <font size=5> Post A New Public Message:</font><hr>
    <FORM ACTION="http://website.com/bb/bb.cgi">
    <br> Your Name: <br>
    <input type=text size="50" name="student"><BR><BR>
    Your Message: <br>
    <textarea name=message rows=5 cols=50></textarea><BR><BR>
    <INPUT TYPE="SUBMIT" NAME="Submit" VALUE="Post Message">
    </FORM>
    </td></tr></table></center>
}
print read %template_footer.html

```

Here's an example data file for the program above:

```

[
  [
    "Nick Antonaccio"
    "8-Nov-2006/4:55:59-8:00"
    {
      WELCOME TO OUR PUBLIC BULLETIN BOARD.
      Please keep the posts clean cut and on topic.
      Thanks and have fun!
    }
  ]
]

```

The default format for REBOL CGI data is "GET". Data submitted by the GET method in an HTML form is displayed in the URL bar of the user's browser. If you don't want users to see that data displayed, or if the amount of submitted data is larger than can be contained in the URL bar of a browser, the "POST" method should be used. To work with the POST method, the action in your HTML form should be:

```
<FORM METHOD="post" ACTION="./your_script.cgi">
```

You must also use the "read-cgi" function below to decode the submitted POST data in your REBOL script. This example creates a password protected online text editor, with an automatic backup feature:

```

#!/home/path/public_html/rebol/rebol -cs
REBOL []
print {content-type: text/html^/}
print {<HTML><HEAD><TITLE>Edit Text Document</TITLE></HEAD><BODY>}

; submitted: decode-cgi system/options/cgi/query-string

; We can't use the normal line above to decode, because
; we're using the POST method to submit data (because data
; from the textarea may get too big for the GET method).
; Use the following standard function to process data from
; a POST method instead:

read-cgi: func [/local data buffer][
  switch system/options/cgi/request-method [
    "POST" [
      data: make string! 1020
      buffer: make string! 16380
      while [positive? read-io system/ports/input buffer 16380][
        append data buffer
      ]
    ]
  ]
]

```

```

        clear buffer
    ]
    ]
    "GET" [data: system/options/cgi/query-string]
]
data

submitted: decode-cgi read-cgi

; if document.txt has been edited and submitted:

if submitted/2 = "save" [
    ; save newly edited document:
    write to-file rejoin ["/" submitted/6 "/document.txt"] submitted/4
    print ["Document Saved."]
    print rejoin [
        {<META HTTP-EQUIV="REFRESH" CONTENT="0;
          URL=http://website.com/folder/}
        submitted/6 {">}
    ]
    quit
]

; if user is just opening page (i.e., no data has been submitted
; yet), request user/pass:

if ((submitted/2 = none) or (submitted/4 = none)) [
    print {
        <strong>W A R N I N G - Private Server, Login Required:
        </strong><BR><BR>
        <FORM ACTION="/edit.cgi">
        Username: <input type=text size="50" name="name"><BR><BR>
        Password: <input type=text size="50" name="pass"><BR><BR>
        <INPUT TYPE="SUBMIT" NAME="Submit" VALUE="Submit">
        </FORM>
    }
    quit
]

; check user/pass against those in userlist.txt,
; end program if incorrect:

userlist: load %userlist.txt
folder: submitted/2
password: submitted/4
response: false
foreach user userlist [
    if ((first user) = folder) and (password = (second user)) [
        response: true
    ]
]
if response = false [print {Incorrect Username/Password.} quit]

; if user/pass is ok, go on...

; backup (before changes are made):

cur-time: to-string replace/all to-string now/time {;} {-}
document_text: read to-file rejoin [{./} folder {/document.txt}]
write to-file rejoin [
    {./} folder {/} now/date {_} cur-time {.txt}] document_text

; note the POST method in the HTML form:

prin {
    <strong>Be sure to SUBMIT when done:</strong><BR><BR>
    <FORM method="post" ACTION="/edit.cgi">
    <INPUT TYPE=hidden NAME=submit_confirm VALUE="save">
    <textarea cols="100" rows="15" name="contents">
}
;

```

```

; The following line is what we want to do, but it won't work for
; HTML documents which contain <textarea>s
;
; print document_text
;
; The following line fixes the problem:
;
prin replace/all document_text {</textarea>} {&lt;\textarea&gt;}
print {</textarea><BR><BR>}
print rejoin [{<INPUT TYPE=hidden NAME=folder VALUE="" folder ">}]
print {<INPUT TYPE="SUBMIT" NAME="Submit" VALUE="Submit">}
print {</FORM>}
print {</BODY></HTML>}

```

The following is a generic form handler that can be used to save GET or POST data to a text file. It's a useful replacement for generic form mailers, and makes the data much more accessible later by other scripts:

```

#!/home/path/public_html/rebol/rebol -cs
REBOL []
print {content-type: text/html^/}

read-cgi: func [/local data buffer][
  switch system/options/cgi/request-method [
    "POST" [
      data: make string! 1020
      buffer: make string! 16380
      while [positive? read-io system/ports/input buffer 16380][
        append data buffer
        clear buffer
      ]
    ]
    "GET" [data: system/options/cgi/query-string]
  ]
  data
]
submitted: decode-cgi read-cgi

print {
  <HTML><HEAD><TITLE>Your Form Has Been Submitted</TITLE></HEAD>
  <BODY><CENTER><TABLE border=0 cellPadding=10 width="80%"><TR><TD>
}

entry: rejoin [[^/ "Time Stamp:" ] {"} form (now + 3:00) {^/}]
foreach [title value] submitted [
  entry: rejoin [entry { } {"} mold title {" } mold value {^/}]
]
append entry {]^/}
write/append %submitted_forms.txt entry

html: copy ""
foreach [title value] submitted [
  repond html [
    <TR><TD width=20%> mold title </TD><TD> mold value </TD></TR>
  ]
]

print rejoin [
  {
    <FONT size=5>Thank You! The following information has been
    submitted: </FONT><BR><BR>Time Stamp:
  }
  now + 3:00 {<BR><BR><TABLE border=1 cellPadding=10 width="100%">}
  html {</TABLE><BR>}
  {
    To correct any errors or to submit forms for additional people,
    please click the [BACK] button in your browser, make any
    changes, and resubmit the form. You'll hear from us shortly.
    Thank you!<BR><BR><CENTER><FONT size=1>
  }
]

```



```

        Copyright © 2009 This Web Site. All rights reserved.</FONT>
    </CENTER></TD></TR></CENTER></BODY></HTML>
    }
}
quit

```

Here's a basic form example that could be processed by the above script. You can add as many text, textareas, and other form items as desired, and the script will save all the submitted data (the action link in the form below assumes that the script above is saved in the text file named "form.cgi"):

```

<FORM action="form.cgi">
  Name:<BR><INPUT type="TEXT" name="name"><BR><BR>
  Email:<BR><INPUT type="TEXT" name="email"><BR><BR>
  Message:<BR>
    <TEXTAREA cols="75" rows="5" name="message">
  </TEXTAREA><BR><BR>
  <INPUT type="SUBMIT" name="Submit" value="Submit">
</FORM>

```

The script below can be used on a desktop PC to easily view all the forms submitted at the script above. It provides nice GUI navigation, message count, sort by any data column, etc.:

```

REBOL [title: "CGI form submission viewer"]

sort-column: 4 ; even numbered cols contain data (2nd col is time stamp)
signups: load http://yoursite.com/submitted_forms.txt
do create-list: [
  name-list: copy []
  foreach item signups [append name-list (pick item sort-column)]
]
view center-face layout [
  the-list: text-list 600x150 data name-list [
    foreach item signups [
      if (pick item sort-column) = value [
        dt: copy ""
        foreach [label data] item [
          dt: rejoin [
            dt newline label " " data
          ]
        ]
        a/text: dt
        show a
      ]
    ]
  ]
  a: area 600x300 across
  btn "Sort by..." [
    sort-column: to-integer request-text/title/default {
      Data column to list:} "4"
    do create-list
    the-list/data: name-list
    show the-list
  ]
  tab text join (form length? signups) " entries."
]

```

Here's another script that removes the title columns and reduces the form data into a usable format. Possibilities with managing form data like this are endless:

```

submissions: load http://yoursite.com/submitted_forms.txt
do create-list: [
  data: copy []
  foreach block submissions [append/only data (extract/index block 2 4)]
]

```

```

datastring: copy {}
foreach block data [
    datastring: join datastring "[^/"
    foreach item block [datastring: rejoin [datastring item newline]]
    datastring: join datastring "]"^/^/"
]
editor datastring
]

```

The following example demonstrates how to upload files to your web server using the [decode-multipart-form-data](#) function by Andreas Bolka:

```

#! /home/path/public_html/rebol/rebol -cs
REBOL [Title: "HTTP File Upload"]
print {content-type: text/html^/}
print {<HTML><HEAD><TITLE>File Upload</TITLE></HEAD>}
print {<BODY><br><br><center><table width=95% border=1>}
print {<tr><td width=100%><br><center>}

read-cgi: func [/local data buffer][
    switch system/options/cgi/request-method [
        "POST" [
            data: make string! 1020
            buffer: make string! 16380
            while [positive? read-io system/ports/input buffer 16380][
                append data buffer
                clear buffer
            ]
        ]
        "GET" [data: system/options/cgi/query-string]
    ]
    data
]

submitted: read-cgi

if submitted/2 = none [
    print {
        <FORM ACTION="./upload.cgi"
        METHOD="post" ENCTYPE="multipart/form-data">
        <strong>Upload File:</strong><br><br>
        <INPUT TYPE="file" NAME="photo"> <br><br>
        <INPUT TYPE="submit" NAME="Submit" VALUE="Upload">
        </FORM>
        <br></center></td></tr></table></BODY></HTML>
    }
    quit
]

decode-multipart-form-data: func [
    p-content-type
    p-post-data
    /local list ct bd delim-beg delim-end non-cr non-lf non-crlf mime-part
] [
    list: copy []
    if not found? find p-content-type "multipart/form-data" [return list]
    ct: copy p-content-type
    bd: join "---" copy find/tail ct "boundary="
    delim-beg: join bd crlf
    delim-end: join crlf bd
    non-cr: complement charset reduce [ cr ]
    non-lf: complement charset reduce [ newline ]
    non-crlf: [ non-cr | cr non-lf ]
    mime-part: [
        ( ct-dispo: content: none ct-type: "text/plain" )
        delim-beg ; mime-part start delimiter
        "content-disposition: " copy ct-dispo any non-crlf crlf
        opt [ "content-type: " copy ct-type any non-crlf crlf ]
        crlf ; content delimiter
    ]
]

```

```

        copy content
        to delim-end crlf ; mime-part end delimiter
        ( handle-mime-part ct-dispo ct-type content )
    ]
    handle-mime-part: func [
        p-ct-dispo
        p-ct-type
        p-content
        /local tmp name value val-p
    ] [
        p-ct-dispo: parse p-ct-dispo {;=}
        name: to-set-word (select p-ct-dispo "name")
        either (none? tmp: select p-ct-dispo "filename")
            and (found? find p-ct-type "text/plain") [
                value: content
            ] [
                value: make object! [
                    filename: copy tmp
                    type: copy p-ct-type
                    content: either none? p-content [none][copy p-content]
                ]
            ]
        either val-p: find list name
            [change/only next val-p compose [(first next val-p) (value)]]
            [append list compose [(to-set-word name) (value)]]
    ]
    use [ct-dispo ct-type content] [
        parse/all p-post-data [some mime-part "---" crlf]
    ]
    list
]

; After the following line, "probe cgi-object" will display all parts of
; the submitted multipart object:

cgi-object: construct decode-multipart-form-data
            system/options/cgi/content-type copy submitted

; Write file to server using the original filename, and notify the user:

the-file: last split-path to-file copy cgi-object/photo/filename
write/binary the-file cgi-object/photo/content
print {
    <strong>UPLOAD COMPLETE</strong><br><br>
    <strong>Files currently in this folder:</strong><br><br>
}
folder: sort read %.
foreach file folder [
    print [rejoin [{<a href="."> file {">} file {</a><br>}}]]
]
print {<br></td></tr></table></BODY></HTML>}

; Alternatively, you could forward to a different page when done:
;
; wait 3
; refresh-me: {
;     <head><title></title>
;     <META HTTP-EQUIV="REFRESH" CONTENT="0; URL=./index.cgi"></head>
; }
; print refresh-me

```

This variation of the upload script allows you to select the directory to which files are uploaded:

```

#! /home/path/public_html/rebol/rebol -cs
REBOL [Title: "HTTP File Upload"]
print {content-type: text/html^/}
print {<HTML><HEAD><TITLE>File Upload</TITLE></HEAD>}
print {<BODY><br><br><center><table width=95% border=1>}
print {<tr><td width=100%><br><center>}

```

```

read-cgi: func [/local data buffer][
  switch system/options/cgi/request-method [
    "POST" [
      data: make string! 1020
      buffer: make string! 16380
      while [positive? read-io system/ports/input buffer 16380][
        append data buffer
        clear buffer
      ]
    ]
    "GET" [data: system/options/cgi/query-string]
  ]
  data
]

submitted: read-cgi

if submitted/2 = none [
  print {
    <FORM ACTION="./upload.cgi"
    METHOD="post" ENCTYPE="multipart/form-data">
    <strong>Upload File:</strong><br><br>
    <INPUT TYPE="file" NAME="photo"> <br><br>
    <INPUT TYPE="text" NAME="path" SIZE="35"
      VALUE="/home/path/public_html/">
    <INPUT TYPE="submit" NAME="Submit" VALUE="Upload">
    </FORM>
    <br></center></td></tr></table></BODY></HTML>
  }
  quit
]

decode-multipart-form-data: func [
  p-content-type
  p-post-data
  /local list ct bd delim-beg delim-end non-cr non-lf non-crlf mime-part
] [
  list: copy []
  if not found? find p-content-type "multipart/form-data" [return list]
  ct: copy p-content-type
  bd: join "--" copy find/tail ct "boundary="
  delim-beg: join bd crlf
  delim-end: join crlf bd
  non-cr: complement charset reduce [ cr ]
  non-lf: complement charset reduce [ newline ]
  non-crlf: [ non-cr | cr non-lf ]
  mime-part: [
    ( ct-dispo: content: none ct-type: "text/plain" )
    delim-beg ; mime-part start delimiter
    "content-disposition: " copy ct-dispo any non-crlf crlf
    opt [ "content-type: " copy ct-type any non-crlf crlf ]
    crlf ; content delimiter
    copy content
    to delim-end crlf ; mime-part end delimiter
    ( handle-mime-part ct-dispo ct-type content )
  ]
  handle-mime-part: func [
    p-ct-dispo
    p-ct-type
    p-content
    /local tmp name value val-p
  ] [
    p-ct-dispo: parse p-ct-dispo {;=}
    name: to-set-word (select p-ct-dispo "name")
    either (none? tmp: select p-ct-dispo "filename")
      and (found? find p-ct-type "text/plain") [
        value: content
      ] [
        value: make object! [
          filename: copy tmp
          type: copy p-ct-type
        ]
      ]
  ]
]

```

```

        content: either none? p-content [none][copy p-content]
    ]
    either val-p: find list name
    [change/only next val-p compose [(first next val-p) (value)]]
    [append list compose [(to-set-word name) (value)]]
]
use [ct-dispo ct-type content] [
    parse/all p-post-data [some mime-part "--" crlf]
]
list
]

cgi-object: construct decode-multipart-form-data
system/options/cgi/content-type copy submitted

the-file: last split-path to-file copy cgi-object/photo/filename
write/binary the-file cgi-object/photo/content
print {
    <strong>UPLOAD COMPLETE</strong><br><br>
    <strong>Files currently in this folder:</strong><br><br>
}
folder: sort read to-file cgi-object/path
current-folder: rejoin at
foreach file folder [
    print [rejoin [
        {<a href="http://site.com/"> (at cgi-object/path 28) file {>}
        ; convert path to URL
        file "</a><br>"
    ]]
]
print {<br></td></tr></table></BODY></HTML>}

```

Here's a script that demonstrates how to push download a file to the user's browser:

```

#!/home/path/public_html/rebol/rebol -cs
REBOL []
submitted: decode-cgi system/options/cgi/query-string
root-path: "/home/path"

; if no data has been submitted, request file name:

if ((submitted/2 = none) or (submitted/4 = none)) [
    print "content-type: text/html^/"
    print [<STRONG>"W A R N I N G - "]
    print ["Private Server, Login Required:</STRONG><BR><BR>"]
    print [<FORM ACTION="./download.cgi">]
    print [" Username: " <INPUT TYPE=text SIZE="50" NAME="name"><BR><BR>]
    print [" Password: " <INPUT TYPE=text SIZE="50" NAME="pass"><BR><BR>]
    print [" File: " <BR><BR>]
    print [<INPUT TYPE=text SIZE="50" NAME="file" VALUE="/public_html/">]
    print [<BR><BR>]
    print [<INPUT TYPE="SUBMIT" NAME="Submit" VALUE="Submit">]
    print [</FORM>]
    quit
]

; check user/pass, end program if incorrect:

username: submitted/2 password: submitted/4
either (username = "user") and (password = "pass) [
    ; if user/pass is ok, go on
][
    print "content-type: text/html^/"
    print "Incorrect Username/Password." quit
]

print rejoin [
    "Content-Type: application/x-unknown"

```

```

newline
"Content-Length: "
(size? to-file join root-path submitted/6)
newline
"Content-Disposition: attachment; filename="
(second split-path to-file submitted/6)
newline
]

data: read/binary to-file join root-path submitted/6
data-length: size? to-file join root-path submitted/6
write-io system/ports/output data data-length

```

9.9.5 A Complete Web Server Management Application

This final script makes use of several previous examples, and some additional code, to form a complete web server management application. It allows you to list directory contents, upload, download, edit, and search for files, execute OS commands (chmod, ls, mv, cp, etc. - any command available on your web server's operating system), and run REBOL commands directly on your server. Edited files are automatically backed up into an "edit_history" folder on the server before being saved. No configuration is required for most web servers. Just save this script as "web-tool.cgi", upload it *and* the REBOL interpreter into the same folder as your web site's index.html file, set permissions (chmod) to 755, then go to <http://yourwebsite/web-tool.cgi>.

THIS SCRIPT CAN POSE A MAJOR SECURITY THREAT TO YOUR SERVER. It can potentially enable anyone to gain control of your web server and everything it contains. DO NOT install it on your server if you're at all concerned about security, or if you don't know how to secure your server yourself.

The first line of this script must point to the location of the REBOL interpreter on your web server, and you must use a version of REBOL which supports the "call" function (version 2.76 is recommended). By default, the REBOL interpreter should be uploaded to the same path as this script, that folder should be publicly accessible, and you must *upload the [correct version](#) of REBOL for the operating system on which your server runs*. IN THIS EXAMPLE, THE REBOL INTERPRETER HAS BEEN RENAMED "REBOL276".

```

#! ./rebol276 -cs
REBOL [Title: "REBOL CGI Web Site Manager"]

;-----
; Upload this script to the same path as index.html on your server, then
; upload the REBOL interpreter to the path above (the same path as the
; script, by default).  CHMOD IT AND THIS SCRIPT TO 755.  Then, to run the
; program, go to www.yoursite.com/this-script.cgi .
;-----

; YOU CAN EDIT THESE VARIABLES, _IF_ NECESSARY (change the quoted values):

; The user name you want to use to log in:

    set-username:  "username"

; The password you want to use to log in:

    set-password:  "password"

;-----

; Do NOT edit these variables, unless you really know what you're doing:

doc-path: to-string what-dir
script-subfolder: find/match what-dir doc-path
if script-subfolder = none [script-subfolder: ""]

;-----

; Get submitted data:

selection: decode-cgi system/options/cgi/query-string

read-cgi: func [/local data buffer][

```

```

switch system/options/cgi/request-method [
  "POST" [
    data: make string! 1020
    buffer: make string! 16380
    while [positive? read-io system/ports/input buffer 16380][
      append data buffer
      clear buffer
    ]
  ]
  "GET" [data: system/options/cgi/query-string]
]
the-data: data
data

]
submitted: read-cgi
submitted-block: decode-cgi the-data

; -----

; This section should be first because it prints a different header
; for a push download (not "content-type: text/html^/"):

if selection/2 = "download-confirm" [
  print rejoin [
    "Content-Type: application/x-unknown"
    newline
    "Content-Length: "
    (size? to-file selection/4)
    newline
    "Content-Disposition: attachment; filename="
    (second split-path to-file selection/4)
    newline
  ]

  data: read/binary to-file selection/4
  data-length: size? to-file selection/4
  write-io system/ports/output data data-length
  quit
]

; -----

; Print the normal HTML headers, for use by the rest of the script:

print "content-type: text/html^/"
print {<HTML><HEAD><TITLE>Web Site Manager</TITLE></HEAD><BODY>}

; -----

; If search has been called (via link on main form):

if selection/2 = "confirm-search" [
  print rejoin [
    {<center><a href=".">
      (second split-path system/options/script) {?name=} set-username
      {&pass=} set-password {">Back to Web Site Manager</a></center>}
  ]
  print {<center><table border="1" cellpadding="10" width=80%><tr><td>}
  print [<CENTER><TABLE><TR><TD>]
  print rejoin [
    {<FORM ACTION="."> (second split-path system/options/script)
    {"> Text to search for: <BR> <INPUT TYPE="TEXT" SIZE="50">
    {NAME="phrase"><BR><BR>Folder to search in: <BR>}
    {<INPUT TYPE="TEXT" SIZE="50" NAME="folder" VALUE="} what-dir
    {" ><BR><BR><INPUT TYPE=hidden NAME=perform-search }
    {VALUE="perform-search"><INPUT TYPE="SUBMIT" NAME="Submit" }
    {VALUE="Submit"></FORM></TD></TR></TABLE></CENTER>}
    {</td></tr></table></center></BODY></HTML>}
  ]
  quit
]
]

```

```

;-----

; If edited file text has been submitted:

if submitted-block/2 = "save" [

    ; Save newly edited document:
    write (to-file submitted-block/6) submitted-block/4
    print {<center><strong>Document Saved:</strong>
        <br><br><table border="1" width=80% cellpadding="10"><tr><td>}
    prin [<center><textarea cols="100" rows="15" name="contents">]
    prin replace/all read (
        to-file (replace/all submitted-block/6 "%2F" "/" )
    ) "</textarea>" "<\textarea>"
    print [</textarea></center>]
    print rejoin [
        {</td></tr></table><br><a href="."}
        (second split-path system/options/script) {?name=} set-username
        {&pass=} set-password {">Back to Web Site Manager</a></center>}
        {</BODY></HTML>}
    ]
    quit
]

;-----

; If upload link has been clicked, print file upload form:

if selection/2 = "upload-confirm" [
    print rejoin [
        {<center><a href="."}
        (second split-path system/options/script) {?name=} set-username
        {&pass=} set-password {">Back to Web Site Manager</a></center>}
    ]
    print {<center><table border="1" cellpadding="10" width=80%><tr><td>}
    print {<center>}

    ; If just the link was clicked - no data submitted yet:

    if selection/4 = none [
        print rejoin [
            {<FORM ACTION="."} (second split-path system/options/script)
            {" METHOD="post" ENCTYPE="multipart/form-data">
                <strong>Upload File:</strong><br><br>
                <INPUT TYPE=hidden NAME=upload-confirm
                VALUE="upload-confirm">
                <INPUT TYPE="file" NAME="photo"> <br><br>
                Folder: <INPUT TYPE="text" NAME="path" SIZE="35"
                VALUE=""> what-dir {">
                <INPUT TYPE="submit" NAME="Submit" VALUE="Upload">
            }</FORM>
            <br></center></td></tr></table></center></BODY></HTML>}
        ]
        quit
    ]
]

;-----

; If upload data has been submitted:

if (submitted/2 = #"-" ) and (submitted/4 = #"-" ) [

    ; This function is by Andreas Bolka:

    decode-multipart-form-data: func [
        p-content-type
        p-post-data
        /local list ct bd delim-beg delim-end non-cr
        non-lf non-crlf mime-part
    ] [
        list: copy []

```



```

if not found? find p-content-type "multipart/form-data" [
    return list
]
ct: copy p-content-type
bd: join "--" copy find/tail ct "boundary="
delim-beg: join bd crlf
delim-end: join crlf bd
non-cr:      complement charset reduce [ cr ]
non-lf:      complement charset reduce [ newline ]
non-crlf:    [ non-cr | cr non-lf ]
mime-part: [
    ( ct-dispo: content: none ct-type: "text/plain" )
    delim-beg ; mime-part start delimiter
    "content-disposition: " copy ct-dispo any non-crlf crlf
    opt [ "content-type: " copy ct-type any non-crlf crlf ]
    crlf ; content delimiter
    copy content
    to delim-end crlf ; mime-part end delimiter
    ( handle-mime-part ct-dispo ct-type content )
]
handle-mime-part: func [
    p-ct-dispo
    p-ct-type
    p-content
    /local tmp name value val-p
] [
    p-ct-dispo: parse p-ct-dispo {;=}
    name: to-set-word (select p-ct-dispo "name")
    either (none? tmp: select p-ct-dispo "filename")
        and (found? find p-ct-type "text/plain") [
            value: content
        ] [
            value: make object! [
                filename: copy tmp
                type: copy p-ct-type
                content: either none? p-content [none][copy p-content]
            ]
        ]
    either val-p: find list name
        [
            change/only next val-p compose [
                (first next val-p) (value)
            ]
        ]
        [append list compose [(to-set-word name) (value)]]
    use [ct-dispo ct-type content] [
        parse/all p-post-data [some mime-part "--" crlf]
    ]
    list
]

; After the following line, "probe cgi-object" will display all parts
; of the submitted multipart object:

cgi-object: construct decode-multipart-form-data
    system/options/cgi/content-type copy submitted

; Write file to server using the original filename, and notify the
; user:

the-file: last split-path to-file copy cgi-object/photo/filename
write/binary
    to-file join cgi-object/path the-file
    cgi-object/photo/content
print rejoin [
    {<center><a href=".">}
    (second split-path system/options/script) {?name=} set-username
    {&pass=} set-password {">Back to Web Site Manager</a></center>}
]
print {
    <center><table border="1" width=80% cellpadding="10"><tr><td>

```

```

        <strong>UPLOAD COMPLETE</strong><br><br></center>
        <strong>Files currently in this folder:</strong><br><br>
    }
    change-dir to-file cgi-object/path
    folder: sort read what-dir
    foreach file folder [
        print [
            rejoin [
                {<a href="."> (second split-path system/options/script)
                {?editor-confirm=editor-confirm&thefile=}
                what-dir file {>(edit)</a> }
                {<a href="."> (second split-path system/options/script)
                {?download-confirm=download-confirm&thefile=}
                what-dir file {>} "(download)</a> "
                {<a href="."> (find/match what-dir doc-path) file
                {>} file {</a><br>}
            ]
        ]
    ]
    print {</td></tr></table></center></BODY></HTML>}
    quit
]

;-----

; If no data has been submitted, print form to request user/pass:

if ((selection/2 = none) or (selection/4 = none)) [
    print rejoin [{
        <STRONG>W A R N I N G - Private Server, Login Required:</STRONG>
        <BR><BR>
        <FORM ACTION="."> (second split-path system/options/script) {>
        Username: <INPUT TYPE=text SIZE="50" NAME="name"><BR><BR>
        Password: <INPUT TYPE=text SIZE="50" NAME="pass"><BR><BR>
        <INPUT TYPE="SUBMIT" NAME="Submit" VALUE="Submit">
        </FORM></BODY></HTML>
    }]
    quit
]

;-----

; If a folder name has been submitted, print file list:

if ((selection/2 = "command-submitted") and (
    selection/4 = "call {^/^/^/^/}")
) [
    print rejoin [
        {<center><a href=".">
        (second split-path system/options/script) {?name=} set-username
        {&pass=} set-password {>Back to Web Site Manager</a></center>}
    ]
    print {<center><table border="1" cellpadding="10" width=80%><tr><td>}
    print {<strong>Files currently in this folder:</strong><br><br>}
    change-dir to-file selection/6
    folder: sort read what-dir
    foreach file folder [
        print rejoin [
            {<a href="."> (second split-path system/options/script)
            {?editor-confirm=editor-confirm&thefile=}
            what-dir file {>} "(edit)</a> "
            {<a href="."> (second split-path system/options/script)
            {?download-confirm=download-confirm&thefile=}
            what-dir file {>} "(download)</a> "
            {<a href="."> (find/match what-dir doc-path) file {>} file
            {</a><br>}
        ]
    ]
    print {</td></tr></table></center></BODY></HTML>}
    quit
]

```

```

;-----

; If editor has been called (via a constructed link):

if selection/2 = "editor-confirm" [

    ; backup (before changes are made):

    cur-time: to-string replace/all to-string now/time ":" "-"
    document_text: read to-file selection/4
    if not exists? to-file rejoin [
        doc-path script-subfolder "edit_history/"
    ] [
        make-dir to-file rejoin [
            doc-path script-subfolder "edit_history/"
        ]
    ]
    write to-file rejoin [
        doc-path script-subfolder "edit_history/"
        to-string (second split-path to-file selection/4)
        "--" now/date "-" cur-time ".txt"
    ] document_text

    ; note the POST method in the HTML form:

    print rejoin [
        {<center><strong>Be sure to SUBMIT when done:</strong>}
        {<BR><BR><FORM method="post" ACTION=".">}
        (second split-path system/options/script) {">}
        {<INPUT TYPE=hidden NAME=submit_confirm VALUE="save">}
        {<textarea cols="100" rows="15" name="contents">}
        (replace/all document_text "</textarea>" "<\textarea>")
        {</textarea><BR><BR><INPUT TYPE=hidden NAME=path VALUE="}
        selection/4
        {"><INPUT TYPE="SUBMIT" NAME="Submit" VALUE="Submit">}
        </FORM></center></BODY></HTML>}
    ]
    quit
]

;-----

; If search criteria has been entered:

if selection/6 = "perform-search" [
    phrase: selection/2
    start-folder: to-file selection/4
    change-dir start-folder
    ; found-list: ""

    recurse: func [current-folder] [
        foreach item (read current-folder) [
            if not dir? item [
                if error? try [
                    if find (read to-file item) phrase [
                        print rejoin [
                            {<a href=".">}
                            (second split-path system/options/script)
                            {?editor-confirm=editor-confirm&theitem=}
                            what-dir item {">(edit)</a> }
                            {<a href=".">}
                            (second split-path system/options/script)
                            {?download-confirm=download-confirm&theitem=}
                            what-dir item {">(download)</a> "}
                            phrase {" found in: }
                            {<a href="."> (find/match what-dir doc-path)
                            item {">} item {</a><BR>}
                        ]
                    ; found-list: rejoin [
                    ; found-list newline what-dir item
                    ; ]
                ]
            ]
        ]
    ]
]

```

```

        ] [print rejoin ["error reading " item]]
    ]
    foreach item (read current-folder) [
        if dir? item [
            change-dir item
            recurse %.\
            change-dir %..\
        ]
    ]
]

print rejoin [
    {<center><a href=".">
    (second split-path system/options/script) {?name=} set-username
    {&pass=} set-password {">Back to Web Site Manager</a></center>}
]
print {<center><table border="1" cellpadding="10" width=80%><tr><td>
print rejoin [
    {<strong>SEARCHING for " } phrase { " in } start-folder
    {</strong><BR><BR>}
]
recurse %.\
print {<BR><strong>DONE</strong><BR>}
print {</td></tr></table></center></BODY></HTML>}
; save %found.txt found-list
quit
]

;-----

; This is the main entry form, used below:

entry-form: [
    print rejoin [
        {<CENTER><strong>current path: </strong>} what-dir
        {<FORM METHOD="get" ACTION=".">
        (second split-path system/options/script) {">}{<INPUT TYPE=hidden>
        { NAME=submit_confirm VALUE="command-submitted">}
        {<TEXTAREA COLS="100" ROWS="10" NAME="contents">}
        {call {^/^/^/^/}</textarea><BR><BR>}
        {List Files: <INPUT TYPE=text SIZE="35" NAME="name" VALUE="}
        what-dir {"><INPUT TYPE="SUBMIT" NAME="Submit" VALUE="Submit">}
        {
            <A HREF="."> (second split-path system/options/script)
            {?upload-confirm=upload-confirm">upload</A> } ; leave spaces
            {<A HREF="."> (second split-path system/options/script)
            {?confirm-search=confirm-search">search</A>}
        {</FORM><BR></CENTER>}
    ]
]

;-----

; If code has been submitted, print the output, along with an entry form):

if ((selection/2 = "command-submitted") and (
selection/4 <> "call {^/^/^/^/}") and ((to-file selection/6) = what-dir))[
    write %commands.txt join "REBOL[ ]^/" selection/4
    ; The "call" function requires REBOL version 2.76:
    call/output/error
        ".\rebol276 -qs commands.txt"
        %conso.txt %conse.txt
    do entry-form
    print rejoin [
        {<CENTER>Output: <BR><BR>}
        {<TABLE WIDTH=80% BORDER="1" CELLPADDING="10"><TR><TD><PRE>}
        read %conso.txt
        {</PRE></TD></TR></TABLE><BR><BR>}
        {Errors: <BR><BR>}
        read %conse.txt
        {</CENTER></BODY></HTML>}
    ]
]

```

```

quit
]
;-----

if ((selection/2 = "command-submitted") and (
  selection/4 <> "call {^/^/^/^/}") and (
  (to-file selection/6) <> what-dir)
) [
  print rejoin [
    {<center><a href= "./}
    (second split-path system/options/script) {?name=} set-username
    {&pass=} set-password {">Back to Web Site Manager</a></center>}
  ]
  print {
    <center><table border="1" cellpadding="10" width=80%><tr><td>
      <center>
        You must EITHER enter a command, OR enter a file path to list.<BR>
        Please go back and try again (refresh the page if needed).
      </center>
    </td></tr></center></BODY></HTML>
  }
  quit
]
;-----

; Otherwise, check submitted user/pass, then print form for code entry:

username: selection/2 password: selection/4
either (username = set-username) and (password = set-password) [
  ; if user/pass is ok, go on
][
  print "Incorrect Username/Password. </BODY></HTML>" quit
]

do entry-form
print {</BODY></HTML>}

```

Be sure to see the following links for more insight about REBOL CGI programming:

<http://rebol.com/docs/cgi1.html>
<http://rebol.com/docs/cgi2.html>
<http://rebol.com/docs/cgi-bbs.html>
<http://www.rebol.net/cookbook/recipes/0045.html>

To create web sites using a PHP-like version of REBOL that runs in a web server written entirely in REBOL, see:

<http://cheyenne-server.org/> (binaries are available for Windows, Mac, and Linux).
<http://cheyenne-server.org/docs/rsp-api.html> - documentation for the "RSP" (REBOL server pages) API.

9.10 WAP - Cell Phone Browser CGI Apps

Most cell phone service providers offer data options which allow users to access information on the Internet. If you use a "smart phone", your data package likely allows you to access normal web pages using a browser program that runs on your phone (with varying degrees of rendering success). Most average cell phones, however, come only with a "WAP" browser that allows you to access only very light mobile versions of web sites, and provides information in a format specifically accessible only by cell phones. Using WAP mobile sites, you can check email in Google, Yahoo, and other accounts, read news, get weather and traffic reports, manage Ebay transactions, etc. WAP versions of sites, accessible on normal cell phones are not renditions of the normal HTML sites created or interpreted by your phone, but are instead entirely separate versions of each site, created and managed on the web server by the web site creators, and simply accessed by WAP phone browsers.

You can create your own WAP CGI applications, to be accessed by any phone with a WAP browser, using REBOL. WAP scripts are just as easy to create as normal CGI web scripts. Instead of HTML, however, you simply need to format the output of your scripts using WAP ("Wireless Application Protocol") syntax. Reference information about WAP tags ("WML") can be found at
http://www.w3schools.com/WAP/wml_reference.asp

Here's a basic WAP CGI script which demonstrates the stock code required in all your REBOL WAP scripts. The first 5 lines should be memorized. You'll need to copy them verbatim to the beginning of every WAP script you create. The last lines demonstrate some other important WAP tags. Notice that the wml tag basically replaces the html tag from normal HTML. Every WAP page also contains card tags, which basically replace the head and body tags in normal HTML. This script prints the current time in a WAP browser. *Remember to set the permissions of (chmod) any WAP CGI script to 755:*

```
#!/./rebol276 -cs
REBOL []
prin {Content-type: text/vnd.wap.wml^/^/}
prin {<?xml version="1.0" encoding="iso-8859-1"?>^/}
prin {<!DOCTYPE wml PUBLIC "-//WAPFORUM//DTD WML 1.1//EN"
"http://www.wapforum.org/DTD/wml_1.1.xml">^/}

; The lines above are standard headers for any WAP CGI script. The
; lines below print out the standard tags needed to print text on a
; WAP page. Included inside the wml, card and p (paragraph) tags is
; one line that prints the current time:

print {<wml><card id="1" title="Current Time"><p>}
print now
print {</p></card></wml>}
quit
```

The following nearly identical script converts text data output by another script on the web site to WAP format, so that it can be read on small cell phone browsers. Because WAP syntax is a bit more strict than HTML, some HTML tags must be removed (replaced) from the source script output. You must be careful to strip out unnecessary tags and characters in text formatted for display in cell phones. Most WAP browsers will simply display an error if they encounter improperly formatted content:

```
#!/./rebol276 -cs
REBOL []
prin {Content-type: text/vnd.wap.wml^/^/}
prin {<?xml version="1.0" encoding="iso-8859-1"?>^/}
prin {<!DOCTYPE wml PUBLIC "-//WAPFORUM//DTD WML 1.1//EN"
"http://www.wapforum.org/DTD/wml_1.1.xml">^/}

print {<wml><card id="1" title="Wap Page"><p>}
prin replace/all (read http://site.com/page.cgi) {</BODY> </HTML>} {}
print {</p></card></wml>}
quit
```

Here's a bit more useful version of the above script which allows users to specify the file to be converted, right in the URL of WAP page (i.e., if this script is at site.com/wap.cgi, and the user wants to read page.txt in their WAP browser, then the URL would be "http://site.com/wap.cgi?page.txt"):

```
#!/./rebol276 -cs
REBOL []
submitted: decode-cgi system/options/cgi/query-string
prin {Content-type: text/vnd.wap.wml^/^/}
prin {<?xml version="1.0" encoding="iso-8859-1"?>^/}
prin {<!DOCTYPE wml PUBLIC "-//WAPFORUM//DTD WML 1.1//EN"
"http://www.wapforum.org/DTD/wml_1.1.xml">^/}
print {<wml><card id="1" title="Wap Page"><p>}

; The line below joins the web site URL with the submitted page,
; reads it, and parses it, up to some indicated marker text, so
; that only the text before the marker text is displayed:

parse read join http://site.com/ submitted/2 [
  thru submitted/2 copy p to "some marker text"
]
prin p

print {</p></card></wml>}
```

```
quit
```

Here's a version of the above script that lets users select a document to be converted and displayed. This code makes use of select and option tags, which work like HTML dropdown boxes in forms. It also demonstrates how to use anchor, go and postfield tags to submit form data. These work like the "action" in HTML forms. Variable labels for information entered by the user are preceded by a dollar symbol ("\$"), and the variable name is enclosed in parentheses (i.e., the \$(doc) variable below is submitted to the wap.cgi program). The anchor tag creates a clickable link that makes the action occur:

```
#!/./rebol -cs
REBOL []
submitted: decode-cgi system/options/cgi/query-string
prin {Content-type: text/vnd.wap.wml^/^/}
prin {<?xml version="1.0" encoding="iso-8859-1"?>^/}
prin {<!DOCTYPE wml PUBLIC "-//WAPFORUM//DTD WML 1.1//EN"
"http://www.wapforum.org/DTD/wml_1.1.xml">^/}

; If no data has been submitted, do this by default:

if submitted/2 = none [

    ; Print some standard tags:

    print {<wml><card id="1" title="Select Doc"><p>}

    ; Get a list of subfolders and display them in a dropdown box:

    folders: copy []
    foreach folder read %./docs/ [
        if find to-string folder {} [append folders to-string folder]
    ]
    print {Doc: <select name="doc">}
    foreach folder folders [
        folder: replace/all folder {} {}
        print rejoin [{<option value="} folder {">} folder {</option>}]
    ]
    print {</select>}

    ; Create a link to submit the chosen folder, then close the tags
    ; from above:

    <anchor>
        <go method="get" href="wap.cgi">
            <postfield name="doc" value="$(doc)"/>
        </go>
        Submit
    </anchor>}
    print {</p></card></wml>}
    quit
]

; If some data has been submitted, read the selected doc:

print rejoin [{<wml><card id="1" title="} submitted/2 {"><p>}]

parse read join http://site.com/docs/ submitted/2 [
    thru submitted/2 copy p to "end of file"
]
prin p

print {</p></card></wml>}
quit
```

This script breaks up the selected text document into small (130 byte) chunks so that it can be navigated more quickly. Each separate card is displayed as a different page in the WAP browser, and anchor links are provided to navigate forward and backward between the cards. For the user, paging through data in this way tends to be *much* faster than scrolling through long results line by line:

```

#!./rebol276 -cs
REBOL []
submitted: decode-cgi system/options/cgi/query-string
prin {Content-type: text/vnd.wap.wml^/^/}
prin {<?xml version="1.0" encoding="iso-8859-1"?>^/}
prin {<!DOCTYPE wml PUBLIC "-//WAPFORUM//DTD WML 1.1//EN"
"http://www.wapforum.org/DTD/wml_1.1.xml">^/}

count: 0
p: read http://site.com/folder.txt
print {<wml>}
for skip p 130 [

    ; Create a counter, to appear as each card title, then print links
    ; to go forward and backward between the cards:

    count: count + 1
    print rejoin [{<card id="} count {" title="page-} count {"><p>}]
    print rejoin [
        {<anchor>Next<go href="#" (count + 1) {"/></anchor>}
    ]
    print rejoin [{<anchor>Back<prev/></anchor>}]

    ; Print 130 characters in each card:

    print copy/part p 130
    print {</p></card>}
]
print {</wml>}
quit

```

This next script combines the techniques explained so far, and allows the user to *select a file* on the web server, using a dropdown box, and displays the selected file in 130 byte pages:

```

#!./rebol276 -cs
REBOL []
submitted: decode-cgi system/options/cgi/query-string
prin {Content-type: text/vnd.wap.wml^/^/}
prin {<?xml version="1.0" encoding="iso-8859-1"?>^/}
prin {<!DOCTYPE wml PUBLIC "-//WAPFORUM//DTD WML 1.1//EN"
"http://www.wapforum.org/DTD/wml_1.1.xml">^/}

if submitted/2 = none [
    print {<wml><card id="1" title="Select Teacher"><p>}
    ; print {Name: <input name="name" size="12"/>}
    folders: copy []
    foreach folder read %./Teachers/ [
        if find to-string folder {/} [append folders to-string folder]
    ]
    print {Teacher: <select name="teacher">}
    foreach folder folders [
        folder: replace/all folder {/} {}
        print rejoin [
            {<option value="} folder {">} folder {</option>}
        ]
    ]
    print {</select>}
    <anchor>
        <go method="get" href="wap.cgi">
            <postfield name="teacher" value="$(teacher)"/>
        </go>
        Submit
    </anchor>}
    print {</p></card></wml>}
    quit
]

count: 0

```



```

parse read join http://site.com/folder/ submitted/2 [
  thru submitted/2 copy p to "past students"
]
print {<wml>}

for skip p 130 [
  count: count + 1
  print rejoin [
    {<card id="} count {" title="} submitted/2 "-" count {"><p>}
  ]
  print rejoin [
    {<anchor>Next<go href="#" (count + 1) {"/></anchor>}
  ]
  print rejoin [{<anchor>Back<prev/></anchor>}]
  print copy/part p 130
  print {</p></card>}
]
print {</wml>}
quit

```

Finally, this script allows users to select a file, and enter some text to be saved in that file, using the input tag:

```

#!./rebol276 -cs
REBOL []
submitted: decode-cgi system/options/cgi/query-string
prin {Content-type: text/vnd.wap.wml^/^/}
prin {<?xml version="1.0" encoding="iso-8859-1"?>^/}
prin {<!DOCTYPE wml PUBLIC "-//WAPFORUM//DTD WML 1.1//EN"
"http://www.wapforum.org/DTD/wml_1.1.xml">^/}

if submitted/2 = none [
  print {<wml><card id="1" title="Select Teacher"><p>}
  print {Insert Text: <input name="thetext" size="12"/>}
  folders: copy []
  foreach folder read %./Teachers/ [
    if find to-string folder {/} [
      append folders to-string folder
    ]
  ]
  print {Teacher: <select name="teacher">}
  foreach folder folders [
    folder: replace/all folder {/} {}
    print rejoin [
      {<option value="} folder {">} folder {</option>}
    ]
  ]
  print {</select>}
  <anchor>
    <go method="get" href="wapinsert.cgi">
      <postfield name="teacher" value="$(teacher)"/>
      <postfield name="thetext" value="$(thetext)"/>
    </go>
    Submit
  </anchor>}
  print {</p></card></wml>}
  quit
]

chosen-file: rejoin [%./Teachers/ submitted/2 "/schedule.txt"]
adjusted-file: read/lines chosen-file
insert next next next adjusted-file submitted/4
write/lines chosen-file adjusted-file

count: 0
parse read join http://site.com/folders/ submitted/2 [
  thru submitted/2 copy p to "past students"
]
print {<wml>}

```

```

for skip p 130 [
  count: count + 1
  print rejoin [
    {<card id="} count {" title="} submitted/2 "-" count {"><p>}
  ]
  print rejoin [
    {<anchor>Next<go href="#" (count + 1) {"></anchor>}
  ]
  print rejoin [{<anchor>Back<prev/></anchor>}]
  print copy/part p 130
  print {</p></card>}
]
print {</wml>}
quit

```

This script allows users to read email messages from any POP server, on their cell phone:

```

#!./rebol276 -cs
REBOL []
submitted: decode-cgi system/options/cgi/query-string
prin {Content-type: text/vnd.wap.wml^/^/}
prin {<?xml version="1.0" encoding="iso-8859-1"?>^/}
prin {<!DOCTYPE wml PUBLIC "-//WAPFORUM//DTD WML 1.1//EN"
"http://www.wapforum.org/DTD/wml_1.1.xml">^/}

accounts: [
  ["pop.server" "smtp.server" "username" "password" you@site.com]
  ["pop.server2" "smtp.server2" "username" "password" you@site2.com]
  ["pop.server3" "smtp.server3" "username" "password" you@site3.com]
]

if ((submitted/2 = none) or (submitted/2 = none)) [
  print {<wml><card id="1" title="Select Account"><p>}
  print {Account: <select name="account">}
  forall accounts [
    print rejoin [
      {<option value="} index? accounts {">}
      last first accounts {</option>}
    ]
  ]
  print {</select>}
  <select name="readorsend">
    <option value="readselect">Read</option>
    <option value="sendinput">Send</option>
  </select>
  <anchor>
    <go method="get" href="wapmail.cgi">
      <postfield name="account" value="{(account)"/>
      <postfield name="readorsend" value="{(readorsend)"/>
    </go>
    Submit
  </anchor>}
  print {</p></card></wml>}
  quit
]

if submitted/4 = "readselect" [
  t: pick accounts (to-integer submitted/2)
  system/schemes/pop/host: t/1
  system/schemes/default/host: t/2
  system/schemes/default/user: t/3
  system/schemes/default/pass: t/4
  system/user/email: t/5
  prin {<wml><card id="1" title="Choose Message"><p>}
  prin rejoin [{<setvar name="account" value="} submitted/2 {">}]
  prin {<select name="chosenmessage">}
  mail: read to-url join "pop://" system/user/email
  foreach message mail [

```

```

        pretty: import-email message
        if (find pretty/subject "****SPAM****") = none [
            replace/all pretty/subject {""} {}
            replace/all pretty/subject {&} {}
            prin rejoin [
                {<option value="}
                pretty/subject
                {">}
                pretty/subject
                {</option>}
            ]
        ]
    ]
    print {</select>}
    <anchor>
        <go method="get" href="wapmail.cgi">
            <postfield name="subroutine" value="display"/>
            <postfield name="chosenmessage" value="$(chosenmessage)"/>
            <postfield name="account" value="$(account)"/>
        </go>
        Submit
    </anchor>
    </p></card></wml>}
    quit
]

if submitted/2 = "display" [
    t: pick accounts (to-integer submitted/6)
    system/schemes/pop/host: t/1
    system/schemes/default/host: t/2
    system/schemes/default/user: t/3
    system/schemes/default/pass: t/4
    system/user/email: t/5
    prin {<wml><card id="1" title="Display Message"><p>}
    mail: read to-url join "pop://" system/user/email
    foreach message mail [
        pretty: import-email message
        if pretty/subject = submitted/4 [
            replace/all pretty/content {""} {}
            replace/all pretty/content {&} {}
            replace/all pretty/content {3d} {}
            ; prin pretty/content
            ; The line above often causes errors - we need to strip
            ; out HTML tags:
            strip: copy ""
            foreach item (load/markup pretty/content) [
                if ((type? item) = string!) [strip: join strip item]
            ]
            prin strip
        ]
    ]
    print {</p></card></wml>}
    quit
]

```

Creating WAP versions of your REBOL CGI scripts is a fantastic way to provide even more universal access to your important data.

9.11 REBOL as a Browser Plugin

REBOL interpreters exist not only for an enormous variety of operating systems, but also as plugins for several popular browsers (Internet Explorer and many Mozilla variations, including Opera). That means that you can embed the REBOL interpreter directly into a web page, and have complete, complex REBOL programs run right *inside* pages of your web site (in a way similar to Flash and Java, and useful like Javascript code). This provides a nice alternative to CGI programming for any type of application that runs appropriately in the stand-alone view.exe interpreter (i.e., for games, multimedia applications, and rich graphic/GUI applications of all types). Since the browser plugin runs typical REBOL code in the same way as the downloadable view.exe interpreter, you can run code directly on your web pages, without making any changes.

To use the plugin on a web page, just include the necessary object code on your page, as in the following example. Be sure to change the URL of the script you want to run, the size of the window you want to create, and other parameters as needed. You can download the rebolb7.cab file, upload it to your own site, and run it from there, if you prefer (be aware that there are several different versions:

"http://www.rebol.com/plugin/rebolb5.cab#Version=0,5,0,0",

"http://www.rebol.com/plugin/rebolb6.cab#Version=0,6,0,0", and

"http://www.rebol.com/plugin/rebolb7.cab#Version=1,0,0,0" - use version 7 unless you have a specific reason not to). If you use your own copy, be sure to change the URL of the cab file in the following example:

```
<HTML><HEAD><TITLE>REBOL Plugin Test</TITLE></HEAD><BODY><CENTER>

<OBJECT ID="REBOL" CLASSID="CLSID:9DDFB297-9ED8-421d-B2AC-372A0F36E6C5"
  CODEBASE="http://www.rebol.com/plugin/rebolb7.cab#Version=1,0,0,0"
  WIDTH="500" HEIGHT="400">
  <PARAM NAME="LaunchURL" VALUE="http://yoursite.com/test_plugin.r">
  <PARAM NAME="BgColor" VALUE="#FFFFFF">
  <PARAM NAME="Version" VALUE="#FFFFFF">
  <PARAM NAME="BgColor" VALUE="#FFFFFF">
</OBJECT>

</CENTER></BODY></HTML>
```

Here's an example script that could be run at the "http://yoursite.com/test_plugin.r" link referenced in the code above. You can replace this with *any* valid REBOL code, and have it run directly in your browser:

```
REBOL []
view layout [
  size 500x400
  btn "Click me" [alert "Plugin is working!"]
]
```

You can see the above example running at http://re-bol.com/test_plugin.html. The above script must be run in Internet Explorer on MS Windows. In order to use the plugin in Mozilla based browsers (Firefox, Opera, etc.), the following code must be pasted into your HTML page:

```
<HTML><HEAD><TITLE>REBOL Plugin Test</TITLE></HEAD><BODY><CENTER>

<OBJECT ID="REBOL_IE" CLASSID="CLSID:9DDFB297-9ED8-421d-B2AC-372A0F36E6C5"
  CODEBASE="http://re-bol.com/rebolb7.cab#Version=1,0,0,0"
  WIDTH="500" HEIGHT="400" BORDER="1" ALT="REBOL/Plugin">
  <PARAM NAME="bgcolor" value="#ffffff">
  <PARAM NAME="version" value="1.2.0">
  <PARAM NAME="LaunchURL" value="http://re-bol.com/test_plugin.r">
  <embed name="REBOL_Moz" type="application/x-rebol-plugin-v1"
    WIDTH="500" HEIGHT="400" BORDER="1" ALT="REBOL/Plugin"
    bgcolor="#ffffff"
    version="1.2.0"
    LaunchURL="http://re-bol.com/test_plugin.r"
  >
</embed>
</OBJECT>

<script language="javascript" type="text/javascript">
var plugin_name = "REBOL/Plugin for Mozilla";
function install_rebol_plugin_mozilla() {
  if (navigator.userAgent.toLowerCase().indexOf("msie") == -1) {
    if (InstallTrigger) {
      xpi={'REBOL/Plugin for Mozilla':'http://re-bol.com/mozb2.xpi'};
      InstallTrigger.install(xpi, installation_complete);
    }
  }
}
function installation_complete(url, status) {
  if (status == 0) location.reload();
}
```

```

}
function is_mozilla_plugin_installed() {
    if (window.navigator.plugins) {
        for (var i = 0; i < window.navigator.plugins.length; i++) {
            if (window.navigator.plugins[i].name == plugin_name)
                return true;
        }
    }
    return false;
}
if (!is_mozilla_plugin_installed()) install_rebol_plugin_mozilla();
</script>

</CENTER></BODY></HTML>

```

You can see the above script working at http://re-bol.com/plugin_test_mozilla.html.

For more information about the REBOL plugins, see <http://www.rebol.com/plugin/install.html> and <http://home.comcast.net/~rebolore/plugin-guide.pdf>.

9.12 Using Databases

Databases manage all the difficult details of searching, sorting, and otherwise manipulating large amounts of data, quickly and safely in a multiuser environment. MySQL is a free, open source database system used in many web sites and software projects. ODBC is a common interface that allows programmers to connect to many other types of databases. The most recent releases of REBOL, along with all commercial versions, have built-in native access to MySQL, ODBC, and other database formats. You can also download a free MySQL protocol module that runs in every free version of REBOL, from <http://softinnov.org/rebol/mysql.shtml>. A free module for the postgres database system is also available at that site.

To explore database concepts and techniques in this section, we'll use the open source MySQL module above because it provides access to a powerful and popular database solution which works even in old and unusual versions of REBOL.

Most web hosting accounts come with MySQL already installed. See your web host account instructions to learn how to access it (you need a web address, database name, user name, and password). To get a free, simple-to-install web server package for Windows that includes MySQL, go to <http://www.uniformserver.com/>. That program enables you to easily install a web server with MySQL pre-configured on your local computer. It's useful if you don't have access to a web server on the Internet, or if you want to create multiuser applications which use MySQL on a local network.

To use the REBOL MySQL module above, unpack the compressed "rip" file available at the link above. This step only needs to be done the first time you use the package on a given computer:

```
do mysql-107.rip
```

Every time you access a MySQL database, you need to "do" the module that was unpacked in the step above:

```
do %mysql-r107/mysql-protocol.r

; At the time of this writing, 1.07 was the most current version of
; the mysql module. Update the numbers in the previous two lines
; of code to reflect the current version number you've downloaded.
```

Next, enter the database info (location, username, and password), as in the instructions at <http://softinnov.org/rebol/mysql-usage.html>:

```
db: open mysql://username:password@yourwebsite.com/yourdatabasename
```

In MySQL and other databases, data is stored in "tables". Tables are made up of columns of related information. A "Contacts" table, for example, may contain name, address, phone, and birthday columns. Each entry in the database can be thought of as a row containing info in each of those column fields:

name	address	phone	birthday
John Smith	123 Toleen Lane	555-1234	1972-02-01
Paul Thompson	234 Georgetown Place	555-2345	1972-02-01
Jim Persee	345 Portman Pike	555-3456	1929-07-02
George Jones	456 Topforge Court		1989-12-23
Tim Paulson		555-5678	2001-05-16

"SQL" statements let you work with data stored in the table. Some SQL statements are used to create, destroy, and fill columns with data:

```
CREATE TABLE table_name          ; create a new table of information
DROP TABLE table_name           ; delete a table
INSERT INTO table_name VALUES (value1, value2,...)
INSERT INTO Contacts
    VALUES ('Billy Powell', '5 Binlow Dr.', '555-6789', '1968-04-19')
INSERT INTO Contacts (name, phone)
    VALUES ('Robert Ingram', '555-7890')
```

The SELECT statement is used to retrieve information from columns in a given table:

```
SELECT column_name(s) FROM table_name
SELECT * FROM Contacts
SELECT name,address FROM Contacts
SELECT DISTINCT birthday FROM Contacts ; returns no duplicate entries
; To perform searches, use WHERE.  Enclose search text in single
; quotes and use the following operators:
; =, <>, >, <, >=, <=, BETWEEN, LIKE (use "%" for wildcards)
SELECT * FROM Contacts WHERE name='John Smith'
SELECT * FROM Contacts WHERE name LIKE 'J%'
SELECT * FROM Contacts WHERE birthday LIKE '%72%' OR phone LIKE '%34'
SELECT * FROM Contacts
    WHERE birthday NOT BETWEEN '1900-01-01' AND '2010-01-01'
; IN lets you specify a list of data to match within a column:
SELECT * FROM Contacts WHERE phone IN ('555-1234','555-2345')
SELECT * FROM Contacts ORDER BY name ; sort results alphabetically
SELECT name, birthday FROM Contacts ORDER BY birthday, name DESC
```

Other SQL statements:

```
UPDATE Contacts SET address = '643 Pine Valley Rd.'
    WHERE name = 'Robert Ingram' ; alter or add to existing data
DELETE FROM Contacts WHERE name = 'John Smith'
DELETE * FROM Contacts
ALTER TABLE - change the column structure of a table
CREATE INDEX - create a search key
DROP INDEX - delete a search key
```

To integrate SQL statements in your REBOL code, enclose them as follows:

```
insert db {SQL command}
```

To retrieve the result set created by an inserted command, use:

```
copy db
```

You can use the data results of any query just as you would any other data contained in REBOL blocks. To retrieve only the first result of any command, for example, use:

```
first db
```

When you're done using the database, close the connection:

```
close db
```

Here's a complete example that opens a database connection, creates a new "Contacts" table, inserts data into the table, makes some changes to the table, and then retrieves and prints all the contents of the table, and closes the connection:

```
REBOL []

do %mysql-protocol.r
db: open mysql://root:root@localhost/Contacts
; insert db {drop table Contacts} ; erase the old table if it exists
insert db {create table Contacts (
    name          varchar(100),
    address        text,
    phone          varchar(12),
    birthday       date
)}
insert db {INSERT into Contacts VALUES
    ('John Doe', '1 Street Lane', '555-9876', '1967-10-10'),
    ('John Smith', '123 Toleen Lane', '555-1234', '1972-02-01'),
    ('Paul Thompson', '234 Georgetown Pl.', '555-2345', '1972-02-01'),
    ('Jim Persee', '345 Portman Pike', '555-3456', '1929-07-02'),
    ('George Jones', '456 Topforge Court', '', '1989-12-23'),
    ('Tim Paulson', '', '555-5678', '2001-05-16')}
insert db "DELETE from Contacts WHERE birthday = '1967-10-10'"
insert db "SELECT * from Contacts"
results: copy db
probe results
close db
halt
```

Here's a shorter coding format that can be used to work with database tables quickly and easily:

```
read join mysql://user:pass@host/DB? "SELECT * from DB"
```

For example:

```
foreach row read rejoin [mysql://root:root@localhost/Contacts?
    "SELECT * from Contacts"] [print row]
```

Here's a GUI example:

```
results: read rejoin [
    mysql://root:root@localhost/Contacts? "SELECT * from Contacts"]
```

```

view layout [
  text-list 100x400 data results [
    string: rejoin [
      "NAME:      " value/1 newline
      "ADDRESS:   " value/2 newline
      "PHONE:     " value/3 newline
      "BIRTHDAY:  " value/4
    ]
    view/new layout [
      area string
    ]
  ]
]

```

For a more detailed explanation about how to set up MYSQL, how to use the SQL language syntax, and other related topics, see http://musiclessonz.com/rebol_tutorial.html#section-27.

To use SQLite in REBOL, see <http://www.dobeash.com/sqlite.html>.

To use ODBC in REBOL, see <http://www.rebol.com/docs/database.html>.

For a useful open source SQL database system created entirely in native REBOL, see <http://www.dobeash.com/rebdb.html>.

The following additional database management systems ("DBMS"s) are also available for REBOL:

<http://www.tretbase.com/forum/index.php>
<http://www.fys.ku.dk/~niclasen/nicomdb/>
<http://www.rebol.net/cookbook/recipes/0012.html>
<http://www.cs.unm.edu/~whip/>
<http://www.garret.ru/dybase.html>
<http://www.rebol.org/view-script.r?script=sql-protocol.r>
<http://www.rebol.org/view-script.r?script=db.r>

Be sure to search rebol.org for more information and code related to databases.

9.13 Menus

One oddity about Rebol's GUI dialect is that it doesn't incorporate a native way to create standard menus. Users typically click buttons or text choices directly in REBOL GUIs to make selections. The "request-list" function and the GUI "choice" widget are short and simple substitutes which provide menu-like functionality. The menu example shown earlier in this tutorial can also be useful, but it doesn't look or operate in the typical way users expect. The popular REBOL GUI tool called [RebGUI](#) has a simple facility for creating basic menus, which can be useful.

For full blown menus with all the bells and whistles, animated icons, appropriate look-and-feel for various operating systems, and every possible display option, a module has been created to easily provide that capability: <http://www.rebol.org/library/scripts/menu-system.r>. Here's a minimal example demonstrating its use:

```

do-thru http://www.rebol.org/library/scripts/menu-system.r
menu-data: [edit: item "Menu" menu [item "Item1" item "Item2"]]
simple-style: [item style action [alert item/body/text]]

view center-face layout/size [
  at 2x2 menu-bar menu menu-data menu-style simple-style
] 400x500

```

Here's a typical example that demonstrates the basic syntax for common menu layouts:

```

REBOL [ ]

; You can download the menu-system.r script to your hard drive:

```



```

if not exists? %menu-system.r [write %menu-system.r (
    read http://www.rebol.org/library/scripts/menu-system.r)]

; If you're packaging your program into an .exe file, be sure to
; include the menu-system.r script in your package:

do %menu-system.r

; Here's how to create a menu layout:
; The "menu-data" block contains all the top level menus.
; Items in each of those menus go into separate "menu" blocks.
; Submenus are simply items with their own additional "menu" blocks.
; Use "---" for separator lines:

menu-data: [
    file: item "File" menu [item "Open" item "Save" item "Quit"]
    edit: item "Edit" menu [
        item "Item 1"
        item "Item 2" <ctrl-q>
        ---
        item "Submenu..." menu [
            item "Submenu Item 1"
            item "Submenu Item 2"
            item "Submenu Item 3" menu [
                item "Sub-Submenu Item 1"
                item "Sub-Submenu Item 2"
            ]
        ]
        ---
        item "Item 3"
    ]
    icons: item "Icons" menu [
        item "Icon Item 1" icons [help.gif stop.gif]
        item "Icon Item 2" icons [info.gif exclamation.gif]
    ]
]

; Each menu selection can now run any code you want.
; Just use the "switch" structure below:

basic-style: [item style action [
    switch item/body/text [
        ; put any code you want, in each block:
        case "Open" [
            the-file: request-file
            alert rejoin ["You opened: " the-file]
        ]
        case "Save" [
            the-file: request-file/save
            alert rejoin ["You saved to: " the-file]
        ]
        case "Quit" [
            if (request/confirm "Really Quit?") = true [quit]
        ]
        case "Item 1" [alert "Item 1 selected"]
        case "Item 2" [alert "Item 2 selected"]
        case "Item 3" [alert "Item 3 selected"]
        case "Submenu Item 1" [alert "Submenu Item 1 selected"]
        case "Submenu Item 2" [alert "Submenu Item 2 selected"]
        case "Submenu Item 3" [alert "Submenu Item 3 selected"]
        case "Sub-Submenu Item 1" [alert "Sub-Submenu Item 1 selected"]
        case "Sub-Submenu Item 2" [alert "Sub-Submenu Item 2 selected"]
        case "Icon Item 1" [alert "Icon Item 1 selected"]
        case "Icon Item 2" [alert "Icon Item 2 selected"]
    ]
]]

; The following lines need to be added to eliminate a potential problem
; closing down:

evt-close: func [face event] [either event/type = 'close [quit] [event]]
insert-event-func :evt-close

```

```
; Now put the menu in your GUI, as follows:

view center-face layout [
  size 400x500
  ; use this stock code:
  at 2x2 menu-bar menu menu-data menu-style basic-style
]
```

The demo at <http://www.rebol.org/library/scripts/menu-system-demo.r> shows off many more advanced features of the module.

Below is an intermediate example with explanations of the most important features. It also includes some stock code to display menus with a standard MS Windows style (OS specific appearance). The menu module has been compressed and embedded directly into the script, using "compress read <http://www.rebol.org/library/scripts/menu-system.r>" (so that the module does not need to be downloaded or included as a separate file):

```
REBOL [Title: "Menu Example"]

; The following line imports the compressed menu module.

do decompress #{
789CED7DED761B3792E8EFEB740343F24AD4D5352EC24C3331E1F59A213258E
E548B233191EDE735A64536A9B6433ECA64566BD8F71DFF7A2AAF0D9F8E82645
27D9DD602672B31B28140A8542A150285C745F9CBF62BD078CA78BECE6B62C3A
8CFD27FE847492CF567378CDF606FBCE8E0E0293BB99D6745992553D69D16E9
58653D1E8F19662DD83C2DD2F9C774F8F881FA7A910E79A97976BD28B37CCA92
E9902D8A94655356E48BF920C537D7D93499AFD8289F4F8A47EC2E2B6F593EC7
7FF345C914AC493ECC46D92001488F58324FD92C9D4FB2B24C876C36CF3F6643
FE50DE2625FF937268E3717E974D6FD8209F0E3328546858507A92961D8DE9FF
AB225BB07C24B11CE4439E7F5194BC8D65C2B1871A92EBFC237C12A45290789A
E66536481FF16C59C1C61C28C032F08056DB48F29A07E3249BA4F3C7319478D5
06B5244ABCF5C30547D38315DB165A8C5A6D821BE683C5249D9689ECDB36EFB6
9C679AB34952A6F32C1917BA67B05F01BAD922ABB1AFD30C0B43A6693249013B
78D68DB9CDC7439E619AEB4C9C266561B5923788E0E7F38223B262D729301D6F
5ACED2E990BF4D81BF386293BC4C19118FC3E09033CEBD16AC11CF44E42AF251
79076C23F9B298A503E0470E2003769D03274E89278B02DBA6205D7D7776C92E
CF5F5EFD7C7CD165FCF9CDC5F9BBB3D3EE297BF10BFFD86527E76F7EB938FBF6
BB2BF6DDF9ABD3EEC5253B7E7DCADFBE8EBA387BFF1F6EAFCE252C1DA39BEE410
7630C3F1EB5F58F75F6F2EBA9797ECFC829DFDF8E6D51907CA6BB9387E7D75D6
BD7CC4CE5E9FBC7A7B7AF6FADB478C0362AFCFAF74035F9DFD7876C5F35F9D3F
422CDCF2ECFC25FBB17B71F21DFF79FCE2ECD5D9D52F58F1CBB3ABD750E94B5E
AB1605ECCDF1C5D5D9C9DB57C717ECCDB8B37E7975D060D3E3DBB3C79757CF6
63F7F431C787E3C0BAEFBAFAFD8E577C7AF5E55DAAFA09DFFFCBA7B01AD32A9
C05E7439D6C72F5E75B16A68FFE9D945F7E40A1AAA9F4E386D39C2AF1E697097
6FBA2767F0A6FBAF2E6FE6F1C52F8F04F0CBEE4F6F796EFE919D1EFF78FC2D6F
F55E53AAF17E3C797BD1FD115AC34975F9F6C5E5D5D9D5DBAB2EFBF6FCFC143B
E5B27BF1EEEC840315E9F4F8EA18ABE6653919D57B4E86F38B5F000A341049FD
88FDFC5D97BFBF00AA21198EA17D979C1C275766360E8D53C7C0513780BDEE7E
FBEAECDBEEEB932E643B07703F9F5D76F779CF9C5D42060E1BE8F8F331AFFC2D
36037AE42DEF3BDD172F6D167E841DC8CE5EB2E3D3771CD8A92CC5BBFCF24CF0
09D2E3E43B41D4C73BAC2E6175FFF5A0FFE0C1A05CB6B86459F059094673BA2C
F95CF5C0CA57DC26C3FCAE954D929BB483934A0FE69F92E19BBE98DB20E1EB0E
2B5645994EDAF90C655D9BC468EB3A29B44C0B67E9B0AF9EA86CA2CE719E0CF9
EBBFFDE783ECD8BF38BB831FBEBC98F797A7DF9F6B6FBF6863FBD809FC73F
9D1CFF02FF8EBE69FFFD161E5E4CBE7F7571F0D371FBEEB47DFCE6E1CD838F49
7A051F4EFEF5E2ECE77FFDC89F0AF8FDAA7BD73D9ECCEEB0F48B2F2FBEBF7AFB
F6BBC39F7E7A7BF2DB2FDFAEDE24C9F827FEE1ECF5F70F2EBA2FDFA6AFE7C383
5FBBE777EF8FDFBE181E9F9E9E7D7F7AF64BF2EF9FDFBCFF7E74F9EFC5717E74
FD53B6BAFEE1877FBE9AFCFAF6B78B41F7F0EADFE70FDF7ED91D3D78F3F4EFA7
776F57DF9DDCFDF0EDAF372FF2C1CB7CF1F0EED5CDEDEDACFC1DD9FBBF7DFFE
38FB707EFDD5ABF4F8CDCDC9AFBF7DDF3DBC7C77F9E4E3FBEF6F2E0E8BE3F70F
7EFEF7F7B7C7CB9BF7DF1497072F3ECE9E941F3EBE990C96CBB47BD25EFDB67A
F26A79F8F1F8F8E555FBFB7BF1F5FBE6FBFB3DCDAEFFFF5DD3552A83B7EF9E0
EAC3E5E2A7C9C9C983FF6AD41FD8AB7697E0AF3EF1C92029789F8F16D301EB7D
4CC68B14DEA405E78B820BF0019F8956B3F479FB2E9F0F59C7CC40C581E55A45
65BFA5C02D9B48CB5C1C2649364A06E96E817918E481D9E46079C0391CBE80
5E7EFD3E1D945FF4597B9C0F9231E5E1F82EC625AF5F8F2A78DFC1326D7854EF
```

D59B0E3B3CE069897F6B878F7F3C8911C0EBEE60852D441BAAF0D567E141C504
55154024758536AFCF5F775B45324AE92B02E323349F978345B9432F590FFFFF9
82CFDE23F48BBE394293E98AF512AE48521603481F08DB7750981665321DA4AD
7C2451D0D3A3CA7AB8BB75D968DF8945F66E58A65A8CFCD35F17D99C4FF25C
AB290AB6078893CA729715E9FEE31D054714939D29B016E57AC0375F08BC8C76
40134CF58151E9E7029AF5691799E519BB01993595F5ED025F5AF946F9623A7C
CE461957CE9050950202A3BEC04D9575A8E6658DA6090B4CD3BBD61014E0B13B
2AA66C31CDA65C911CF36E1B72A52C9D30CAFB78C7ECEB49F2219503FB6396DE
F13F43F8AF4563675DBC3061C33B04FA9A8FB90F5F704EE2150864FB9BC04C87
20E307F9389F77583A1AF16E94FFF2AA801B9AC1B1D96134A2B908071B676DBB
A7D3742C5A8143127E57F8091267DF7972277B809A28204B89038DEF7B8A4282
6F1DD135ED19D768A765CB120756E691CC299A1E000AC9CAD861B36CF0A15A18
B9E21FFFC47FDB30C1B7930157D38953ABFFD9F37D90B6D8D135A4530F1C1F44
8E6887E8A41F3905AAC4E2ED063D3F9B3EA7EF6D415FBE286AD1E3736A0CB604
C59D4B18DD4A08733799195FA253EF9CB60765E2BACBA7C991025EB6DDF18F6
86FC3619C5CABF73CABFE0A8850A1AE866350969A1273E41ADDE2CC9E65F68DC
883B2D44B8202F531A66BA093D374B47FD44BEEA1DB1C33ED5FACCCB4D95C254
CD4355F8A02F7A0EDFB30A8FD9AC00F9841CA8BEE66B47BEDE2BB3B468231D31
5BD1EE2058174AC695D9B6D01E235020DB63CC56034A0EB5FB81BACE87ABF688
ABD91D16C30AB23D866C11088A4E7108ED1A3A213C2E9A920618413617C287B4
D2243F049E2DD0240940F77C14405D8B009CD5A030387F83683A725E57014036
7F619B858385EB1A8279EAF9CEC81681658289C00A83A9CAEC695EB274322B57
CF231C43C32124AF91F72466837C32CB8B43D4CD35960E603111B991449A1DD
4EDA4B8A1648547660A00A734F7BC55A6CAF48C19467EAE7B5441034DD676D76
B41FD509F79A82F242E93B6FFB81E90B92F543B02D6ABE9E91E915405C094C06
1FFC6A9FCB8638DB4237B626C9FC8398CB08CEBAA9022F99CFF3BB4DE11913B9
42CE525CF4744BC07BE56236AEACAC1452505AB1B5BB4EB1F3B9030D12AC8F43
3AA55E90693C6B779E0CB33C32381A0C2F93045C9F48A76C0F5BBBCF1744E371
CB7C31C8E68371CABE5E7EC3BE74190E49CA7CAC1869C0E036057D617B0D8866
311B33CEA669EB2E1B96B7EC887E0C92192B7E5D80091A7FBFCF613380AB82E3
2850C8CBEE434F96A7978C80E8F964FB59EE5FBCF5E2F6A36DE9CF5B07813DE
2B16D72ED3DD5B02477966968F5737F9342EFAA4D8355A835277C9A52EFBC679
BD0269CA3F1DD648D41858DE5521B04F3E07D887B5F2FFFE44A859DCE1F24872
590C9535D2CE3B02AD69D7B435CF364E56EC16EF38F7C714533165FFDD84C6D
2C442AF345712BE5F9E6A962A0B15EE19ACFBF60EBC227D912C043B4840F1A34
959BB62B488126B5A7E9DD3D90F7266504CA26937498719A8E57B473067866D3
9BFBFA2FFF4A0D53DFB163A0C0DD661552566F0B1E28ED7A31EE482130B509F3
A769369CE5B3166E617BA78E7ECFB51A89DD651800FED902B815C7120E12A891
CFC0D3A11CF26BB5BB5F5305FEBA6715768BA382659C261FD32D08575B26BD02
A81EE9BA98A27C4D87C2EE027E0583319FC65D99E5015BD130EE87677F7BAC6F
2149BB15B2BBE403E9FED854F5AEEF9F418C69D1370FDDCC022CE51F90DF36E51
D5B502EAF906AA39171AF968A40C6B6A45105BE6DA393BAC9C2FFC16655F8A82
2D3A86810F467C7B964CC3B047F93C4D06B7ACC8AEC7E0C182206A146F29256B
113689292BD805C45A5E3B6D35C922C2025E5F9DA2EACD3C5FCCF466910024FA
123F468105A4910737AB1347C9B8A8EF456469B3B8BBD8673ECD4FB572FDB597
C36E6A0E89AC5F0DBD4EFEAA0C38AFE685032F19A08F131ADE6D761543729E73
0CF89CC47B89D73E2FC1D348F09E8D4D608216153C63BB1C024D794ABAD81364
3F2AC05DEA8EC876B2F6BA7DED75B24BF048E7892D0E25E6FC03C26596E0AC0E
963FDCA9296EB351793F8D073AD3943A882CB4CDE6AFBD8D835CE62C00BF9B
12C69D1B54817A3A6423BFB54F30D6BDE831CC8D49A80F1E88C36865196D2BB1
DD221D8F02EBA5980110F8BFA2CD78F6B1F1C7753207F8E606A0FA6D307DB198
C1C24A7D521F404F11DBB98E320B0D0B037D3B04DB4CBE5B57908AB256E37693E
22DB7A6817D46AA0264868CB524A1E2CDB501930048B516F4CC6422E216377B9
9A3A6D95790B57A935659AEF78421AE58345D19EE62D3504FC23CC1D073652D6
66604C67F9DC88621D23C28E234592095C3B6A752893E0A845C729AE0AD6ED19
43AA33C343AA54DA9CA2BCB513703DB65B1BD7ED36E982462DF66B1B1EB902E9
F7B1BAD880EB4D26751A4388369BA4ED2FE97FFF353B4963EFD25D73143672AF
EAC5B1CF1EB2BD83E521FB0F9129FB2DD6FD4D0BA65BEF41BF9AC1845ECF790
C06B080783C1985CB56C23B852FD6154EE8B1156DB7E9C5051AE130990FDBE4
C165CF43E49965BB66A90553DF193BB019DCDCB72A9EA09A6DC2DB76FA98D076
FCB6F003C74EDEC7E8F5209C4CD4EAE8CF4001AF47DD9F03354C8A587F342281
A495EDED908D5466AD2DDF370D9332D9668772C1B855FE206B1A78447518380C
74D88794FF11BB9BEB57046628F043C7A3571B4EC7CEEC414892BCD4EEB6AC87
361EC2722D932835D702B5A1499512116E7BF0B00B62F01C0AC9FE5A1F035A48
B2E04479BDC8C6436BAA549F775EC037E530F98895F94D8AAA091E6B03854CE9
85300D1686FEE6B167EF24A8D2C0971DE38023CCBF958C70CC0DDFC303429AA7
4536044BFA545781C718C8295D3AAAEFC8021C2B9E7F5A66A32C9DEB221C046F
204DC9827E6611F83CCFF0E00595118674AB556DA21569287CA9EF1AB295AED3
61D63A09DFD3040858DBEF499000062E400DCB303ED8C54D3989E348BAF0BBEB
7461B0E818C04D43869B5F398057F24B0767772743F884BA55086380AF88E1B5
9C9BF55C35897228647C3994B365C7AE36ECC6A9FD297D45BC6E89A603580053
E921D9A9345FBEF7345F7A41FA8AF8D1B0BD238D6E190AE73BDF6E0B328BE1FC

EAB568B9E4D2C508C770310B57CC66B8A57A8B39FEA8AA94A047B0945B974113
6F29CB55D42A5A35B80597E1243087191CF07517D04A66920013D9B42F80CA48
87100CC9B743C784313F9745E23B40F1CB22E5F7EF5F7DB88B0F01DB66571447
96890061A3C02114AC0F5575CCAE99B4DCC3AF8F1E1F7EF5CDE3C3A75F8668D8
2C5167EAF30DC8D8F73401D0211476B83C723A58A02F5611A6AE1EB0DA2A23AD
CB30B0FCDD1D27AB7C51B66843A4CA27AFF0235959CC89D39E0FFD3317BEAD9C
2BA0E37C3859EA4E12B37FCFE4BA2215C06C84F389CFC805D4EEED0ACE619FD8
EE7582FFB45AAD3EDB8BD0D94A519356C71E51F694594DF67E6807B666784B2B
AF6BCC685404952825340BA5D2A24AECAED3CD640E828A94F196719DCC3E3162
11EAB47C56C2AF16A9327BC17A31B7702614C737CB9C5129FCE947D9EFE3063D
BB4B26BE608590CC2EC2ECD2B2429C4A68586A8B2F6DA1DF109978DF4905ABA6
FF20ADDB8790FC8484BEDC2DC6C8BBCD49290A0031C5E35FE4C4E4AFC7FB32BC
C50B498F2F88BC31BD898D2C485AC5219B1296DD801774BD65D2AC525075A84E
3E9C25B29B56DFDB15FB911A0FA1057C725EF56BB0F3EF746E4E9ADE2EA8F030
7FC0BF45DF04089E93FE24E4D927705BC6DFB3A4BC857F3743D95A55C0F97859
5F140A24C2834E1E47A4AB990865D6C32009DCB8876F71A66276AB0DE306F5A
81D4011B648F7F15478D10DEF318A11B1037DE4DE4FEDE000CA4BD08ACFDF8D7
3F1CFE7DBA234A4221C22379EAC5927970731340FB7EA92D04011E1103498040
FCA2408A002912EE270AAC65FB5AA2609371BD81F8587F6CAF293C7E2751103F
70584DF16EBA9F2830607986AAF9F50F87BF4D51609130200ACC4E6235B131B4
6A141007E691C834DF46761173484C02E2EC43E9165D718F3750A95F0FCA3CD
788245A09E894125D81F0C88EB5155DA34054137558276A5D9B44163FFB0B62A
2BAB1A807B08693F0C26D26234791ACD6DD8BC8AA93268A51436A2E0F79AAE52
751986CA908D52EE5285BEB3CDD9028C99F72112194B8336D91891B0EA358824
ECB221936C8C4858D5E64402746B26830DB9CD26E6E7E7B8F08C700F6EB01BF1
F93922DC08BF9CC0A67136F8CC5DD86820C7C7F11FFDD818D86597C94DDABFBC2
BAFB2E9AE17FD7C94B458EAA99C58C2D20DFC64F8060D81E42C09FEE6504EA89
53479FC481813ABA24B3993C45D1A62867BB9345B948C6F5A76DCCA2782484CA
3714ECE6C9927C345AB3D1587FD41E0769371FB11E98BBE9F88EB5EA1B67C202
DE788CE843427526A938DE950EABAD7C379F42A15D38EE850F2BAE437FC2D35F
EC5383D2A31114C27346F000BE579F1A1C3BEAAF4316D1917229B97D298EE66A
08526C1B191B682BE4E930CAE66A05BE7122270C7099127B6DE423415BA7AAB2
C0618C4AFA4B63D72D361B3ACC8AE47A8C9C9A4EE1A9914A2AF88F803C63124A
C45864A6863B03A1E334FA496D268A09ED41ED10C20CC9F0FDA2103BB7EE16FF
317E65D24B496CF062DC120A273E17BEC6655ECA48A860EF5E4CD221BB5E395B
BE543EB6B9AB1998A2F5E03B30A56342A51813A8569828088F6A8F8481119210
063D010C7A0218F4C461D003C2A0471521B5C199CA5052F57734021D8D4147A3
D05138740C24ECD091F2C42B524610D0420D43F1D1213B2014D208C88300FB72
118FA7BA22D9EC435DAEDB4E8BE27E70DCAC4FA05208A4D5E373773FCE063772
0E1A1AC76C7DD39241C6C3AF96875FB9390CEA4E92A5F19B1E45FCDBDAE05966
40BDC3469DEDA262F42EA2A2198EA9905E1D2F7341F620D789B3126ADF8EF5BE
5A3E610F8D58C6F88DCB551553370226ECD6A45A5F73A87A9D3864CD48A99313
99A59AAAB155ADC2EE17F78D1E77D8475A16E0A36017412BB96BE9A138FF2408
1E72658DB2ADF382661431D28C00701D37AB44133E928AC15B924D1693160642
A68D6D2F91D48068AFCC3A0C88EEFCE32121695F0203333610B4D6DB32418B20
B63121EDC12080923829B4A2AE35280AA18C0CA4318491CB46D4921810270E92
871791C6514CC5E4020767B2231F3C2F2537A16F5D8BDBC6EB6B234F8E90BC
D6624E341A73DB51D015F8EDF3454500EB32347CAB2835A7BB3938CDDE7CC844
70C6CA1468026810EF18492163487399E2D168DA4B43A7682FA1359236F84BB5
157F491AE10F2D8DF0A7F60AFC932818C66831085191459AEACB8E4915DE20E2
9ECFA78468C9B1F40B38359E971DB357C2A303321A1DE69DA45446B3335D1E32
23B679B10B9141B54C907B5955F054D37406BB0027BD411A7F6B8DB2162CC1BF
32D49C9F0246610B9860F750614B8E43610B182F6C9077CD89B9D9D8AF889575
457804850AEFC7917DEA10B5716A82747C263065ADEE0A6DB837BAE3CB268557
6661359756253ACDA851FA9B12A663CB1F3545D8AA50DF95C6F2CC112DB84DF8
F843BB3C46EE5348E84205E11A899AF38EBA59045F3AD72B28BF54AF3BBBCB08D
0A8BAAD13D5666F2A69499D18952A28A97ED14E321AF976C4DED126FE782771D
89E8E2D1C1F20F9B3EC37C151A19F4305D40232708ACD6ABEFE2ADF76C157DAB
9EAB6431C871C062F9E07E2E8205673349DA29B3FE5C5B7C6AD25F6B3E627E0
557B83E1826C7ACC228ECA61B6C27456E76258D70FD3FC5A925C9CD0984BC682
6F22B6EBCA642F2AC327684E42A57DED8E53CE49E4719BA2953E9F1355DBF0D4
07C00A82385A5039C1E58FA6AEFD275622964AAFF79471A6EA7DC39EF6112E18
D4A0520BC326F1BB03516363D162DDCC91E8B12A602A22240431A8F1D89C7620
386CB0548B7DC94B0582B4064B3DDCA8941743CF590F56E12A8013BA89E3FF40
060AB6431C871C062F9E07E2E8205673349DA29B3FE5C5B7C6AD25F6B3E627E0
AFC750DA137E0FABFE5CC90C2B62C614C34AAD306262A801A69EEB478C202A9C
C5CBCC7B26850E27C568E22D42A153B8D8C9C7543F8268DADDEE3C867A493218
A4EAB455E8829F36E5124D51906E52C2B683873FE869304E93B978C6CBBEC4F3
9F2862C0DA49F3C6321DDC271CA7D5073B976959C02564181D106605DC6B28D8
5EF6387D8C752D4AFE136F3115ABACDD42DEAC8741382D789E73C8BAAE2B3561
E6C0CE2C9FDA1170C073132E7E01FF4D9A2C335ECD4D3A87F9F20D7C848262A9
974C5777B7299F2C304E92B857B59CA7691525445D4CBE045BCFA83B27F051B4

72E83650E3E7B97F06D1D0BC5E352BDADE9D8405FCD5E7FEE157657F8A17C204
E83E370882871A087BF8EB292448D5B890D3146923A192B827098F9E7C66DC3C
BE10E27596F315EBF1CA647FD15917DF1C093371E5804DB59C2D4C5C18428530
8EDAA8F35B6E71EB97405C5CF3719B262AC610142FDAF314C35011059D7A8739
D9213AE6602093431DCA728755C8B036709C7A49F501D0A818D54B043C6FE40F
3A755C96C9E03655D10680B23866D2255CC13CBD41B255224F6100CAA7A5B49
7AF0426ECFB865FE91ABF4DDEAF885C7215EAC6B45C5AA8EDECA5D7A7EDC7E04
BCF2B98E42C4A7FD39EFD95D8D04E87C640C66EC7FD4771D59CB8F519DF8B6B
832B446A5FA760C8623B67487A11D44BBC448D9C2EF485B5D6027B3887C3CAF0
2C258F1BD72B1941F8B10A4C7A69839C71799112D01DFC11868967D01C98D43E
71D79B6A1FDB1BA6A364312ECD4064EDC4BE10194E363B4B979F61B170BD6277
B7D900FB749E8E00EB5C459AC093DA31D909CB2CD55B05FB98CDC139C710A6CE
ACA2C40E8D4E0C96698E268AA28ADF604462F8E43EE58B08BEEA11C040F043C1
339EF9B622CB1079D74E459C6217C7106795E2C031AAA1F202486223F8DBC7B6
55841F7E70EB14ECA5EA9CE2DD9D9E3A81A39C3A89CDE0AFB74EFC60D7D916DC
14B20EF62C49AB0F4BC668D777FB4A38136CD64F84BC0B1952B58FAE133E5369
7A19B486AFEB92DB20DB56A8166A49EC36243FC96484936774ADAD12B85E8C22
F7F820116A5DD74C1B9FBC85541BC6372B2AAC9AC1C235DE1618BB0131EF80B0
AB5C91CA5FC53D88AC0EF29F20F6DCE0DA180A75B4D41801418216478AF2F8A2
E738C4097E09D1BBA6878528EFC8320DF0ECC84252A00B3D4CBC65E1B33090FE
EADC353BB7492857E18758150A6CE775FB78A7B9CCA94EAF162550584742F39B
F21E52A030E608A3209CD090732D6279364D89EF02B79EA615CD1A43AE2A65CA
7458CB4A9F82DD64552C181F407FEEA57183056DD7AB14E07ABD8CF3C2B2D9D
462A30785DF8050F1CB05A95C68CADE1E879121B77E4B4420C23273E8D55ADB1
C1832169C0E6845DE663141D2255C4251999D15137E38BDFCF5A62868373AC25
A8F88B85AF752F538869221C62C56EF38C452474F13F97D06410B23677344A40
E80E7B07CDBA2F9D2DBB4288CE348CC2A4FE9F26FC22E4135828027A68E7D28F
26F520FD7A83A41C54EC6FF730D5DCCF50F359CC34B4655C6FA4F9CB38F3A730
CE8406825F5D263BA7A32CC7D7E0B689860608762FB48219024AEC3A783471D1
875E48F40D60358124BAD30B09BF21520D20C9F5BA1F5221B3D541F21DB278A0
7FBA920678E23A99DB3B65C6DE19EF072D91E8C212E3ABFE666BB855326D96DC
D9610FC4043EE5D3F16ABF66B6A8C2136D35833A4A9906AF6B670A264DD1FD10
9B0B50B2FB906052F0CB6A24284F8A4DA79FC738FF97C4FF4BE263FA5398E371
67138EDE0563CACA5B383685220AF707BF901400162FE1220FB87A9AA9BD3B31
E4387D8AE92E9F7126B3713A819B55866C95965FEC0444A74CBFCF0C4642627B
F398056F0BB399056F0B739A0D6FE399AD492C605F52B39EE91554B910069C3A
F0335C8FD24AE12D3FA5C9D0E71856FCC83E6955C95C50EDE469AF88471C5BD
41DCD0D20357A8F86C83B68CB1BCDB4BBEABF81CE1D75051E997E62F4A5F8365
653C677F59339AB3674A33E7B66C48ABC4E796F71F3A1C55B7FB21BA7D367D2E
BC9104A9CCCB6A9449CE3EBCE19F5465C52D58CA35A8DDBF15A13D98CCB6300D
C61D6BC1CB3D8D432D1E1EFD5BA087DB36C3B527943A51112DC8F645FF716A64D
40ECD5212C7CCF827778A1E9AD87CBEEC58CA13285BE67784E635CB6F00B3CC0
4597E840D61A67702745A32BCEFC1472A9E47F835105FCC00D6F166A8185BC81
281DC86B84ACB6CDDDB174046ADF53A3BDDFF18CC1CD9D0DA9C4A067719E7BB11
93ED2E17D8CE09DDE72C82BBEFC17A008619BAFDEF8A58DEBB4AF12CF66BEE80
B7857245CDD912CE12A6BCBE6F0B2970371B72015DAEA81FD19B213464550E83
7914A2768E6D0DD34393E6AE13BDD02DB8A8B29DE9928DDEF7FFF24D7996A1B
DFF6949DA66BA266C20B1222D2C99E7D0A488B29FACECB2EEFE98E37F08DEDD9
6523333BEBD957555627ABE83C8477316E5B60BC03A0855EA13C0275906EE8C6
350E2C5F9040359242A48A1657BF928DA4EACD8392943482C54DADD1C9769C26
1FD76524234520CFF96C20BCC42B7B7B565EC15ACE461B36A794B765EA4B369B
2B25D834753EE915FC12BD88753E12915C78AF55BAC4B8ACBE7A9DA0B8ACB863
92F9BE8C563BC23419A8B7E810DE66294A31A1283867BA00C35DB13AA47589D7
F91F56911FFD07FCE49ADD1AE8D7F334F9D026631CB3C7B6499B8E230322C224
D63CF430F6B58F5C8F85ADC266065F1BD591E2CA66B1B7DDD1A3B8160590DF82
ECAD756D4EE4D60C4254785A021FB37C51F81B23393B5D96F384E5A07956DB67
FDC07CC2A051D50C881F9342699631D915AEC2A2A7765B43462A527204AFFABC
20F691515747F508A2F124FCE375FB412C5D8FE50A458872206BC7D39B0694A9
184861281667504F3556A121D9FD28DC2BF1AFC7090FDF6F27795607A67CC3BE
7372DCDD66E3D08226BC04B661C36CA7492A877AD3358FDD057E2CB1796E2744
D6E7C6D465D81BF02D8EE2107E7E3948EDB4FB3CD4326F8AC946187A41A982E3
F2F7912856C7F5D7171CEBCA0A2BFD2538FED70B0E7346FB33CA0D1CA75B901B
516B1EC9A6B5958BBB7932633B3FC3DFA4944A6399CFF0566E1F5F193AA150A5
632B9550CF7828197605DF40DF88E227D33D353DB7373CE442FAF642DA572F24
44EF63D815ECB6D68CF079D9203CB36F830FFE7B747D659A0C31C51A5D6F77F9
E036991BFD6E957299006E20A7FD55BC54180AB33D4EB3D7E7AFBBFBA6C30FA4
0ABB60E61EFCB557DEDA9BA6AAA249F6C4198680F89AC0DBAD7E51C116B04E4
016D15C323B9FA56A0B82EE0A1B9CCEFF696EF7496DCC2A6CD82832BD4598D19F
BF342F4DF373E1AF8B64FC9C2D3851E6B87F83BDA67FDA203CD787540D553239
63E33EC24AB07EC87C019F3758E4C7A686DF67C52F950CA76157176FBB58235C
4D3A1EAF644E5728DB56C66A7B41AB8C6C59627BAB3184D4EF7FB003B75FEB52
03B856AC222674B4C1389BC957D5E4A51DD8905B60A0B6776D4D527870E16DEA

DB20201ECC5A201E1A6DB4DB40BBE2F44ED7720B7B9E6B23FACF67AC252A42B7
091FD06DA0FE8F676CCFE900910FE08B57FB7D97F0A2664FD5B658371637D416
0EE0798825110D2308A5F34E354293250249461473DFF1572E811B0C938E8FC5
1B40D27B1E5670A02A7F3BBEC19ECD2091A9DB6A892C49E310A6E5F47EA43190
ABB6316A08346ECCD6B8C5ED992AA02061BC3CE3725F0C1E66A38841DE0D0020
CC1A4CA146FD7A74BC2F43B8E220D066DDEEDA11E3C2F46386191A51B01127EA
F1850E187E3A5238A62059637E2EB863FA4C0008DB011AD3A728D399FF1247BD
3050A2226CDB909C80F9F584249409CFA746AB0C850656BE8D56B7D66CB542B5
61AB71C6F4B75A11B0766DE5AB0A9295CBDCE2E65A418515D54FDA4B0DADC6E0
5BA1DC6DD9DEF54AF02D7ABC82FBF084AF1652AEFD26937C312DF982089C2C93
F9AA6E7166AB8D2AA7DC9CB71139CDC17F165B0495F225C2F42635EF48F0B8FE
0ED371993090220CBA38B4E6C36C143918F21AC2078B194C12B665CA7B3B7C2A
FB01D7CDB00E12E816B705D7FD325515D74DCCC46B0DD3CA00A98E0DD190CF3A
C22181575B83A18FE4FD4790BCF58EB955FA362D20E6A0DAEC2D66CE629B19F9
D712385BEDBFC6415A406FDE70B26452AA4D7DD874BB0B05B9F95DC997692CC
5A1FD255DCE23401B3CC9075DF755F5FB57FE8FE127790161EA3F88F362EF14A
426206EB27174B339768367D80D86C5CB67AE4089646112342D6802F276EA9F1
7F6FF3494A7FD011155FE3135899F87F7D7454451F4F3BF5AB187AD4158B9076
F44624892F7A23D9CC50C0D3550FFEE6CA38EFE0BFFC4E68C6184F3DEE6A094
64E44DD1D362CBC4EB32EABC88847ED99D630CDF672C7E27A13499119A51BF46
A78584379C099B795B7574DBC18F412AA38472AABAD7A5F0BA3ADE9A67DA0C8
6B3B68D093E92EE1F97BE1701EEBD8A1FFB6C3A4771B519A0528B0F7B79DFFFB
E38E9173BFA6536AACB9084AD573B92C6B343AAF61BF39B79CDD4E05E240B2A
0C3381FE2E1FE161E76755C1567A222D06C98C8257A89EF076C4EE381D954C67
DC0F76D92E04AF2866C92055DA6D94EBB83FBF1D945A966E2D3ABF22CB2AB67
F3025204B0949D8D019BAE5131C008731D8CC58E286D6D4500A3445F07B0D85F
AB05ACE78B75003720054C3F6B612CF7976A3A4F1FEB0A323D4663174E96B65F
A56E81D887222450C07BD1432881FB4ED7DDFF6C7266EC816C3C9C8A368E88C1
AB96081C2DF39A07A2E193FAE01E988193BF7466C67F6298144C3C1AA74FDC30
ABA4473B90A7CD2CC38875B44240081886E8AC726087AD9225229D9D7C55F162
7D6C68535054D17ECCFC5530ABB8D170972BFC830FAD326FE1DCE06417AEFFB5
6622B92CB7286B7B5275C478519F6DF7CD8E9485213DD847C9B5D3EFAA3FFB17
D95225C63989CB5FFE7FD2DB50A8E1633FA07A43F27F71CE11FC795574F3849C
C52E1145ADE7AE5B055E58A0FB82503BA2A72F7065DEB01996CAF8B688C73FFAD
1B58444464EBB9027F344E6E78AEDE284BC7C30AA224199947F64152D124521D
2AC2FC6E23436757E92C29DD3E8BB70617E635D1FC199DC43B7261E2D882AD1F
683FECB027EC0F4B36FF92B78245EF7B5D76B6E564D3EE36E163A383F7ABF03E
A65D1BB2CD098B1CEE3FFC6131EF29E29F0C6EB81D98B2CDEA8E08160A546A32
AB773F0212DE20D911505BF8CBAFF08BB3D73D3EB1A4785A71769B4C1663F6E5
5113D3BBE8A1A64807D1AD698DC43298C1EE91A06A35D61166482639C4146245
5DDA115E56095BB186155D9E35EBB5359BA39A458322D62C82680FFF70DB20AD
BBA08444E3727DFAF6ABFFB91A32DDEE63CE4CEAB3BE10890C52182651C47701
34AA57292B2DC4BAB108CAF242C6DDE04C7899552E2EAA46B6D3B72599971611
F6955D09CC651CAC37541C6A99487212B6EF696ACB09C832CEE0179AB498BEE7
C8A21F15366632156F5C4C68EA74AE68BDF1DCAE14767622E93A89C066E46321
87443240D217A79B55411514C229485F8205C1D4904D6F3A6E41F12558E3D0C0
D4AE714898060AD2D6B0AF207C89145431339C8274C99448EEC208FCCCC8E5A
2190F12558505D04EF1494D7D8070AD2FD53BE1AE94BB046E37AE80EBBDFB4AD
E1A966DC1F9E71E7F256F04378706517D2CA2494FAE22794BCEA8B686C16945F
021446B83C7F22AF11BE846B54E59C1AE14B888B7CA3457DC197A125EE3D0488
77E6F4C88BDECD3C196620CA0E97877092A3843BEAC71F7D07563C52E36879D4
4466980B1E70CB1C26F3611B4FD0230D7A74992E0726A77F4241A933BBD7102D
2A80912D55BE7AD2448460439B888BE051E08A74902A088E091F518F9E3E7DFC
D513FEFF3E0BE61184F7ECDEBA52C5AA50900B9FE14F00822B5E22F9D6101B91
A1D6A0365B0884590547754FDE5F7CB43CE0D37176C37B8A4CEC1FE5AF016D35
487249425D8F213634FDE5B45FE19FB5A4E44C8660B9B3F2182B6500B238852
AA97CFB39B8CE3F1940FB74932C7E76C3A4405077C3BC00AFE1CEA8B90434BC2
CF5DDB268284695162D017F91886E1E1DF8FE03F63B830C5EC56E6DD0CE50E33
7FF4E3766B6B3828DF03A1A6DB6B77081A4CC110BD4183DD8D6F8790F9AB98F
EA7D49D1348B72354ED1CE0662C4D0A9D9304BC0B0F638A490EF9C52065AE240
D41D84553C624959CEB36BB8EFED11AE0F08C1425C2D5A0975B5F3421EE7B0A2
2F1776D4C8D0A282A3714C66277C0DCD13D52032462D89B04DB3DC88938999F8
E84853B39DF8DB68E8B1994F85074F448078D1ECC7DE9B5331278515D75ABDEA
3EC39827AE4B67B16BE48DEBD12D6A884868F44C77FE86927F21A4977BD42271
65AC89A1B9A0A92C525C9ECD042FB09EB8A5020122F97E7F33587555A703D955
DAE189626714095C1AABF5025F21A14F790BD192CC251E1F1F9C5569AC6DA5DD
90FCA67CBA8765577077EEBDDF13F3D10A09788C7859440EFDCA4C56C0C8BFA
BDA095C24B2BB7849018B5A46A826AEAC8CAE3861442082E418966F57F712F
A9FDC4FFDB954B59A3FD2AFAED2746411BD7A080D27EF156455E9880AE83114E
54063ABB38BB7C22130BFF578AAEBDF0C6A774A2A4239B0487C03C13741644EC
C81991CFB4112B966F1C09EB94EFD3DA6DEEA16BC39083E23F7771F0F47D1C39
CAC64802CCB156BF88C1FAB938931063BD719E0C9BE4A706484E363E6C87A985

6127C24492A2E3AC6CC967C558DBE02BBF362A933F34A9B09F115C71B736EBED
E1EFFD90E3804B02BB5A24081DF06B280B8B46A36F2B83AFD998B3567742015D
5FAC0893D49FB16D4ABB763A7D9D16E2F2CA685E7D73AA78182BCDAA70B3BF47
C8EF836B2C10BD70954D6ADF6DEC545D4FD1B4DEBB570A3B19AF51B2D9681C146
23D8F51B0D284504F8069C1024CC16B8C16D846AC8FABD1744740B3DE847D41D
83887ADC8F774B5DA0074E7CDCFCC11DA0593DCEE95B247F632DF18F50120DC3
8C97205A49F4835A4716883D1A4D0AB12BDB5C004A83EE3A6228169B0996771D
EB0D5F0CA4D3E84D66C2CE439124D416A8BDEC34EE488C5D8BE8B12E599F1E58
996209331977232A4FA6637C57A87B29B85681260CEBD2167A198DE2E0ACDAD7
5BB6D7AEC05D9A88D6683A570818722BADA51766A0FBE8F06898CF6077C9BF78
2E0DB8CBA64338A3E31CE0B309472628610EDA66DA793347D3E0755A30BA168D
F32BA7E6D4B857651D7889BAEDE0FEB8D961FF772ED2A29C670315AF08BE6A42
4E922599C8CCCB16E028880670CE9B055D00E74304DD2DAE9D4CD2619694E978
55DB66153B5C41B7050859DBE8DE61CB9487264DC453381509B35ED57E677CED
B027CB2D38C04902C9D07E925E4409A475DFE275856A277C476A4548C9B3F41D
7D9A58FC35C1EB0FFD020DB4BF6904F298747216CC11FBA85C790C99485C7F5
EE91AAF0F0E0DD3D92473ACBB1DD8B8D83C697872BBA2480739C403E772EA79
456C3585A74F4F2E3B951ADA4B9F74956DC157C48B66FB3CDD6E9530223798AC
60BD0958CF5CD632C34899014FEE951EB23D4157986090279F1B04D8DF00DE91
60F050CBDAABFDC54F2D01CE6D5E3A4FF5423B65D55B68DC106B1203ABE8821
1DB64A0BB754252E8659C7FD53AB86A87513696B1322FAC0F8C9EABB76C7A4A2
43C1695E43C02A4FEAAA98B9A3571D01F17838460D0139ABC31375EA29B6EFC0
E52FBCFDA3672F376C0B53AE6D3A3252A78A8D37A64F9F3970CD3026EB403562
8CF43D1B2CA6B03266210DC91E706106F2A88EA59836C385D64EC9763539E792
866DC0847657AF6492156C060F6620F82BFB54F83C09A560DD64B799BC2C69B3
BF5979AF280922A9C057674E99BCA1152A0B9D502C5C940A89113B451709C5D5
71AB33A03C14E1C04C02EB284A5283681FCA2F6D76E40A6882C727097680CF9E
0C91C5B0A929F42BC3548F4F63C4FAEE141B593D21F8E49FA6DACA7FAFC7ECA6
4621478BAFE94BA3E94BBB5B44BD2D0F13DB048903B65BD132DB18A06BBF4299
954599558532EB4A2CB3BF6D38266EBED3539F031B0392CB2BF0CE02EECED59E
6945B5E6899BDD9DDAAD498897A98BA8D64C070B6A028E12618F19A93E1B63CE
582FF2596D96CF16B3B6200A5E77888B1DB1D65D2BB937FCA8AAE46D427C15DD
13F10BE4B15CDB76D2C8CEE44B644F29577044AE3D498AD20A6D8E8BC86BB8C6
134F47603CDB4A7050FBC09BF92974620E00DA39A55BBFE39B48A7049CD70D0E
AEA2A38CA7289D3C810398A34DC8E524E4929B74ABD72CED5C828B94B830B5C4
9B3DC78BB4607BE9321D804B181BE4C354DEA5BA5B488F64BC9CCDE104E7DAE1
3E732F1AE60A1799A4F08867462629B86ED007116BD7AE5D27F053A03674B1B2
0FD57AA25E4172A277F47B0177D68E3C3C4BB645BAAC065A277C41A0991DF8C7
292DA6A274322B57CF290C72E0D25C48C39C5D83575DC7A435DB05C6F1E6C7C1
EB8FD91B084C8CBE938BEB36D8AA343658DF5A7670AF7FE5E1D7DF3C3EFC6E0
F1E1FD0FAB1195D5360FF9C9493091F4B3B57C96D3E497698B0211D4A0F70F2
8395F210C36290DD25EC0F6B9C9D330F5219A750552CEAEAF004060571E21000
A52BA51E1787F2FC10753F522F99DF14FAC9EFA3DE122E750041488886102A87
ABA770B19A8B25ED1A5070644FA8996D0B1F41C55075F2C0F1A05CD2ED8DA855
CB200DEEF0924790DDFCE2627B9FCA8DAE24E4D5097DD2D7FE8AFC97F05774CA
61B00BDA46923302DEEA5DE840DFD28A4BB116F063283A919EA582A353380402
4A7E18C10914894BB871F9C231127E3C7BF84E9E9FC7EFA21FFA61E34BF043C4
594665513B6F1A0972B8896FA242125D82F79CAB28ED420AC0D13DF2076EA444
504916267535093540C590879F7541D8AB8976C5744F372A84D78F33DC15246A
C5B785CD244F19C8FADADE1350BE241DF2EBDCF11B2B6CDA6FFF89F2DB4711AA
1CF61B818AFBC9C9E44A0CDE781C8D4EBC82CD2A31195111976672397DE1BC08
F7C5BBF1E0AB69838106297C0F86998CF156CEB3E94D6CABDB4C883F283EB19D
6E33C56DB5B8F98EB3DF1A5BEF0E3E345D0AEA8B56A1CC6A0E82AB2A1D669E93
683E9C94AA639E076E52D093E2D48AF34BF0E33A11C782CA5CCBB76B6326EB22
85C08D0926C0B6DC111C32E0276144C6D28651392A44E5048DE050F2A8A73649
96BA907F0622EA516EC1546185FB26DC2F16E5CC1A8C30A7724FD3C87B9F0E73
B369425B3B8074699A26B533E7D990268B7199C9D857F0EC212D7830CBB522AE
A9AFC71F425DC03B6F96E151B40FEC30D24D38ADD00847C768526979A986446A
12016C031343DCB4005EE8D2DB056C073EE3026AEBBEF53FAD510E0E964787D5
7BF0F4EAC67714F0ABD869BF3E0BAD85CCF38336B50CEF2BE7F81B1C28350381
C88551706D66F8B619AA829AE8D5FC7F74B47C5A59D5E9A86B95806B32C9B867
06EB71D59ACD72AE56E34237C8832440A6640292AEDB38053D2734E9554C90E8
6C1D6269A31CC1FDC73FC10E968C31FE859F6F0392D746907AFC1E5842791755
FDB639BEEE38033382116E2A604DB043D6AA9EA25078B1BE2AF810E2D30B640E
37120D3C8D028C8A6B8E1001DD56D65B4CC710A0AC057352BF7A41395E6F1E97
1503AE04F011418312AC77F882EAA1906562E9175F0EC9DAC2734E1840EEBF98
D94C14D9B925884028D6A35CAF568A88D1B79C844446BC2D8CF52A2F3A54650D
2921E9827C79D5D9127521D5531852E47C58B88AB8533324C98332D21D445D6E
C0BA9084E89CA66DF2388DA38F16DB5A98B020C2CBBCD261469C6F50940CB552
4036A9F4DE8A68035152D14D70A65DD3DE6658DAEE6368A3597CAB86366578C2
6A7C8627F810303C25D3C16D2E8309852684901989E2F218488BD498C725A39
3E67142F84168582B3E9155F124C9810A4683EDAD9091DC0AA2A2E14AA62958E

```

C77C983E6418D302C35A043097E1B4508AB761F5C776AFCBD880AA865A3B7C82
BE7DAC073EAB078FF9FF409D1DB7F4CF593E5EDDE453F674F935579BF89F6F96
87315F76A1277DBD3CFC3A2CABAD2580B1FDCB5AECE860D972AFD753D069588A
6D675A449B0B58010BF82508433AAD7C58E2F44AA838DF457960218EE606C89
0D4381A3E1FCC0F64C6710FA00FE457B075CABB4E8B0CF0971E889FF22536399
125D064012EB8107FDFF0F1217899678240100
}

```

```

; Note that there are two menus in the following
; block. The "file" menu is indented and spread
; across several lines. The edit menu is all on
; one line. Notice that you can place action blocks
; after each menu item, to be performed whenever the
; menu item is selected - as with the [print "You
; chose Item 1"] block below:

```

```

menu-data: [
  file: item "File"
    menu [
      new: item "Item 1" [print "You chose Item 1"]
      open: item "Item 2" ; icons [1.png 2.png]
      ---
      recent: item "Look In Here..."
        menu [
          item "WIN A PRIZE!"
          item "Try door number two"
        ]
      ---
      exit: item <Ctrl-Q> "Exit"
    ]
  edit: item "Edit" menu [item "copy" item "paste"]
]

```

```

; Most of the style definition below is totally optional.
; It's designed to look like a native Microsoft menu. The
; example at
; http://www.rebol.org/library/scripts/menu-system-demo.r
; contains many more examples of menu styles and options.
; The only part that's required in the example below is
; the action block in the "item style" section. Everything
; else serves only to adjust the cosmetic appearance of the
; menu:

```

```

winxp-menu: layout-menu/style copy menu-data xp-style: [
  menu style edge [size: 1x1 color: 178.180.191 effect: none]
    color white
    spacing 2x2
    effect none
  item style
    font [name: "Tahoma" size: 11 colors: reduce [
      black black silver silver]]
    colors [none 187.183.199]
    effects none
    edge [size: 1x1 colors: reduce [none 178.180.191]
      effects: []]
    action [

      ; Change the lines below to fit your needs.
      ; You can use the action block of each item
      ; in the switch structure to run your own
      ; functions. "item/body/text" refers to the
      ; selected menu item. This does the exact same
      ; thing as including a code block for each item
      ; in the menu definition above (i.e., you can
      ; put the [quit] block after the "exit" item
      ; above, and it will perform the same way -
      ; just like the "[print "You chose Item 1"]"
      ; block after the "new" item above).

      switch/default item/body/text [
        "exit" [quit]
        "WIN A PRIZE!" [alert "You win!"]

```



```

        "Try door number two" [alert "Bad choice :("]
    ] [print item/body/text] ; default thing to do
]

; The following function traps the GUI close event. This
; must be included whenever the menu module is used, or a
; portion of the application will continue to run after being
; shut down.

evt-close: func [face event] [
    either event/type = 'close [quit] [event]
]
insert-event-func :evt-close

; And finally, here's the user interface:

window: layout [

    size 400x500

    ; The line below shows the winxp style menu:

    at 2x2 app-menu: menu-bar menu menu-data menu-style xp-style

    ; THE LINE BELOW SHOWS THE SAME MENU, WHENEVER THE BUTTON
    ; IS CLICKED:

    at 150x200 btn "Menu Button" [
        show-menu/offset window winxp-menu
        0x1 * face/size + face/offset - 1x0
    ]

]

view center-face window

```

9.14 Multi Column GUI Text Lists (Data Grids)

REBOL's built-in "text-list" GUI widget is very simple to use, but it can only display one column of data:

```
view layout [text-list data (system/locale/months)]
```

REBOL does have a built-in "list" widget for multiple column "data grid" displays, but it's a bit more complex to use than the text-list widget. Earlier in this text, Henrik Mikael Kristensen's [listview](#) module was introduced as a simple solution for creating multiple column data grid displays. It works well, but requires you to include a third party module. With a little knowledge and practice, you'll find that REBOL's built-in list widget can be very powerful and easy to use. In it's simplest form, the native list widget takes a size parameter, and 2 additional block parameters:

```
list (size) [GUI widget layout block] data [block(s) of data to display]
```

The "(size)" parameter is an XxY pair indicating the pixel size of the overall list widget. The "[GUI widget layout block]" is a layout of standard VID widgets used to display *each row of data in the grid*. The GUI elements in this block are *replicated* to display each consecutive row of data in the grid. The GUI layout block typically contains the word "across" (because these widgets are used to display *rows* of data), and it typically includes size parameters for each widget. The "data" block is made up of rows of information to be displayed in the grid. Each row of data is contained in a separate interior block:

```
view layout [
    list 220x100 [across text 100 text 100] data [
        ["row 1, column 1" "row 1, column 2"]
        ["row 2, column 1" "row 2, column 2"]
        ["row 3, column 1" "row 3, column 2"]
    ]
]
```

```

        ["row 4, column 1" "row 4, column 2"]
    ]
]

```

The GUI block can contain other standard facet modifiers such as colors and spacing:

```

view layout [
    list 200x100 [across space 0 text red 100 text blue 100] data [
        ["row 1, column 1" "row 1, column 2"]
        ["row 2, column 1" "row 2, column 2"]
        ["row 3, column 1" "row 3, column 2"]
        ["row 4, column 1" "row 4, column 2"]
    ]
]

```

The GUI block does *not* need to be comprised of only text fields. You can display the rows of data on widgets of *any type*:

```

view layout [
    list 304x100 [across space 0 button 150 button 150] data [
        ["row 1, column 1" "row 1, column 2"]
        ["row 2, column 1" "row 2, column 2"]
        ["row 3, column 1" "row 3, column 2"]
        ["row 4, column 1" "row 4, column 2"]
    ]
]

```

IMPORTANT: You can make widgets in the list perform actions, just like in any other "view layout" code:

```

view layout [
    list 304x100 [
        across space 0
        button 150 [alert face/text] ; When clicked, alert the text
        button 150 [alert face/text] ; contained on the button's face.
    ] data [
        ["row 1, column 1" "row 1, column 2"]
        ["row 2, column 1" "row 2, column 2"]
        ["row 3, column 1" "row 3, column 2"]
        ["row 4, column 1" "row 4, column 2"]
    ]
]

```

This means that creating *user editable* cells is very simple - just reassign the text of the clicked face, then update the display:

```

view layout [
    list 304x92 [
        across space 0
        btn 150 [face/text: request-text/default face/text show face]
        btn 150 [face/text: request-text/default face/text show face]
    ] data [
        ["row 1, column 1" "row 1, column 2"]
        ["row 2, column 1" "row 2, column 2"]
        ["row 3, column 1" "row 3, column 2"]
        ["row 4, column 1" "row 4, column 2"]
    ]
]

```

Unintentional visual artifacts can be caused by the caret (cursor) in text widgets. To eliminate them, simply focus and unfocus the widget after updating the display:

```

view gui: layout [
  list 304x84 [
    across space 0
    text 150 [
      face/text: request-text/default face/text
      show gui focus face unfocus face
    ]
    text 150 [
      face/text: request-text/default face/text
      show gui focus face unfocus face
    ]
  ] data [
    ["row 1, column 1" "row 1, column 2"]
    ["row 2, column 1" "row 2, column 2"]
    ["row 3, column 1" "row 3, column 2"]
    ["row 4, column 1" "row 4, column 2"]
  ]
]

```

Notice that the number of rows contained in the data block does not affect the number of rows displayed. The list always shows as *many rows as will fit in the overall pixel size of the widget* (we'll attend to this issue later...):

```

view layout [
  list 304x100 [across space 0 button 150 button 150] data [
    ["row 1, column 1" "row 1, column 2"]
  ]
]

view layout [
  list 304x100 [across space 0 button 150 button 150] data [
    ["row 1, column 1" "row 1, column 2"]
    ["row 2, column 1" "row 2, column 2"]
    ["row 3, column 1" "row 3, column 2"]
    ["row 4, column 1" "row 4, column 2"]
    ["row 5, column 1" "row 5, column 2"]
    ["row 6, column 1" "row 6, column 2"]
    ["row 7, column 1" "row 7, column 2"]
  ]
]

```

You can resize lists to stretch and fit resizable GUI windows:

```

insert-event-func [
  either event/type = 'resize [
    li/size: gui/size - 40x40
    t1/size: t2/size: as-pair (round (li/size/1 / 2)) 19
    show li unview view gui
    none
  ][event]
]
view/options gui: layout [
  li: list 220x110 [across t1: text 100 t2: text 100] data [
    ["row 1, column 1" "row 1, column 2"]
    ["row 2, column 1" "row 2, column 2"]
    ["row 3, column 1" "row 3, column 2"]
    ["row 4, column 1" "row 4, column 2"]
  ]
] [resize]

```

Here's one way to stretch and/or shrink all the cells to fit inside a resizable list:

```

gui-size: 220x110 li-size: 100x19

```

```

gui-block: [
  li: list li-size [
    across
    text first (li-size / 2) ; (1/2 the width of the list widget)
    text first (li-size / 2)
  ] data [
    ["row 1, column 1" "row 1, column 2"]
    ["row 2, column 1" "row 2, column 2"]
    ["row 3, column 1" "row 3, column 2"]
    ["row 4, column 1" "row 4, column 2"]
  ]
]
insert-event-func [
  either event/type = 'resize [
    li-size: gui/size - 40x40
    unview
    view/options gui: layout gui-block [resize]
    none
  ][event]
]
view/options gui: layout gui-block [resize]

```

Of course, you can assign a label to any properly formatted data block, and display it later in a list widget:

```

x: [
  ["row 1, column 1" "row 1, column 2"]
  ["row 2, column 1" "row 2, column 2"]
  ["row 3, column 1" "row 3, column 2"]
  ["row 4, column 1" "row 4, column 2"]
]

view layout [list 220x100 [across text 100 text 100] data x]

```

That allows you to build and display multi-column lists very easily:

```

x: copy []
for i 1 12 1 [
  some-info: copy []
  append some-info (pick system/locale/months i)
  append some-info (pick system/locale/days i)
  append/only x some-info
]

view layout [list 220x240 [across text 100 text 100] data x]

```

Here's a resizable version of the script above, which has user editing enabled for the first column only:

```

x: copy []
for i 1 12 1 [
  some-info: copy []
  append some-info (pick system/locale/months i)
  append some-info (pick system/locale/days i)
  append/only x some-info
]
gui-size: 220x110 li-size: 100x19
gui-block: [
  li: list li-size [
    across
    text first (li-size / 2) [
      face/text: request-text/default face/text ; enable user edit
      show face focus face unfocus face
    ]
    text first (li-size / 2)
  ] data x
]

```

```

]
insert-event-func [
  either event/type = 'resize [
    li-size: gui/size - 40x40
    unview
    view/options gui: layout gui-block [resize]
    none
  ][event]
]
view/options gui: layout gui-block [resize]

```

You can collect the entire block of user-edited data using the following code:

```
editor second second get in (list-widget-label) 'subfunc
```

For example:

```

view layout [
  the-list: list 304x100 [
    across space 0
    info 150 [face/text: request-text/default face/text show face]
    info 150 [face/text: request-text/default face/text show face]
  ] data [
    ["row 1, column 1" "row 1, column 2"]
    ["row 2, column 1" "row 2, column 2"]
    ["row 3, column 1" "row 3, column 2"]
    ["row 4, column 1" "row 4, column 2"]
  ]
  btn "Display Current Data" [
    editor second second get in the-list 'subfunc
  ]
]

```

This can be used to save and load all data in the list to files, or otherwise put to use. That makes the widget very useful for data management of all types! Take a look at this script to see one way to save and load data:

```

x: copy [
  ["row 1, column 1" "row 1, column 2"]
  ["row 2, column 1" "row 2, column 2"]
  ["row 3, column 1" "row 3, column 2"]
  ["row 4, column 1" "row 4, column 2"]
]
do qq: [view layout [
  the-list: list 304x100 [
    across space 0
    info 150 [face/text: request-text/default face/text show face]
    info 150 [face/text: request-text/default face/text show face]
  ] data x
  across
  btn "Save" [
    save to-file request-file/save
    second second get in the-list 'subfunc
    show the-list
  ]
  btn "Load" [
    x: copy load to-file request-file
    unview do qq
  ]
]]

```

9.14.1 The "Supply" Function

To enable more versatile list displays, the "data" block can be replaced with a "supply" function. "Supply" works much like a "for" loop that iterates through each row of widgets in the displayed GUI list. The "supply" function automatically creates 2 new variables which are automatically incremented each time through the rows in the list:

1. "count": the current ROW in the list
2. "index": the current COLUMN in the current row

You can use the "count" and "index" variables to select sequential values from a block of data, using the "pick" function (in the same way as in a for loop). Typically, this is used to set the "/text" property of each widget in every row.

In the following example, every row in the list contains a single text widget. The supply function runs through each row, and sets the text property of the widget's face to be one item from the "x" block (a list of months). The loop automatically increments the "count" variable to display each of the months:

```
x: copy system/locale/months

view layout [
  list 200x300 [text 200] supply [
    face/text: pick x count
  ]
]
```

This example loops through a list of files read from the current directory:

```
x: read %.

view layout [
  list 200x400 [text 200] supply [face/text: pick x count]
]
```

You can use the "count" variable to change properties of each widget face. In this example, the color property of alternate rows is changed (one color is assigned to even counted rows, another to odd rows):

```
x: read %.

view layout [
  list 200x400 [text 200] supply [
    either even? count [face/color: white][face/color: tan]
    face/text: pick x count
  ]
]
```

You can apply actions to any widget in a list, just as you can with any other widget. Clicking on any file name in the list below will open that file in the editor:

```
x: read %.

view layout [
  list 200x400 [
    text 200 [editor to-file face/text]
  ] supply [
    face/text: pick x count
  ]
]
```

You can use the "count" variable in the supply function to build *multi-column* lists from 2 or more separate data blocks (multi column grids *are* the whole point of learning to use the list widget):

```

x: copy system/locale/months
y: copy system/locale/days

view layout [
  list 250x400 [across t1: text 50 t2: text 100 t3: text 100] supply [
    t1/text: count
    t2/text: pick x count
    t3/text: pick y count
  ]
]

```

The next example uses both the "count" and "index" variables to loop through a block with 2 columns of data. *Understanding this format is the basis for all the most complex list layouts you'll need.* Take special notice of the first line in the supply block. Once all the data from the "x" block has been looped through, if there are more rows in the list display, the index value will go past the length of the data block, and cause an error. To avoid this, you simply check if the picked value is "none", and apply a value of none to the face/text, then exit the loop:

```

x: copy []
for i 1 12 1 [
  append/only x reduce [
    pick system/locale/months i
    pick system/locale/days i
  ]
]

view layout [
  list 400x400 [across text 200 text 200] supply [
    if none? q: pick x count [face/text: none exit]
    face/text: pick q index
  ]
]

```

To help clarify the above format, here's the same example with a third row added:

```

x: copy []
for i 1 12 1 [
  append/only x reduce [
    i
    pick system/locale/months i
    pick system/locale/days i
  ]
]

view layout [
  list 250x300 [
    across
    text 50
    text 100
    text 100
  ] supply [
    if none? q: pick x count [face/text: none exit]
    face/text: pick q index
  ]
]

```

Here's an example of the directory reading example from earlier, but with two columns of data displayed (file name and size). Clicked file names still bring up the editor:

```

y: read %.
x: copy []
foreach i y [append/only x reduce [i (size? to-file i)]]

```

```

view layout [
  list 300x400 [
    across
    text 200 [editor to-file face/text]
    text 100
  ] supply [
    if none? q: pick x count [face/text: none exit]
    face/text: pick q index
  ]
]

```

The following example demonstrates how to add a slider to scroll through items in a large data block:

```

x: copy [] for i 1 397 1 [append x i]

slider-pos: 0
view layout [
  across
  the-list: list 240x400 [text 200] supply [
    count: count + slider-pos
    face/text: pick x count
  ]
  slider 16x400 [
    slider-pos: (length? x) * value
    show the-list
  ]
]

```

Here's the above slider technique applied to the earlier directory reading example:

```

x: read %.

slider-pos: 0
view layout [
  across
  the-list: list 300x400 [
    text 200 [editor to-file face/text]
  ] supply [
    count: count + slider-pos
    face/text: pick x count
  ]
  slider 16x400 [
    slider-pos: (length? x) * value
    show the-list
  ]
]

```

Here's the 2 column version of the directory reading script, with a slider attached. Be aware that clicking on any file name still reads and edits that file:

```

y: read %.
x: copy []
foreach i y [append/only x reduce [i (size? to-file i)]]

slider-pos: 0
view layout [
  across
  the-list: list 300x400 [
    across
    text 200 [editor to-file face/text]
    text 100
  ] supply [
    count: count + slider-pos
    if none? q: pick x count [face/text: none exit]
  ]
]

```



```

        face/text: pick q index
    ]
    slider 16x400 [
        slider-pos: (length? x) * value
        show the-list
    ]
]

```

Here's another refinement of the above script, with a third column added. The look of this display is changed by adding a line between each row (the line is drawn using a box widget), and by changing the color and font of the text:

```

y: read %.
c: 0
x: copy []
foreach i y [append/only x reduce [(c: c + 1) i (size? to-file i)]]

slider-pos: 0
view layout [
    across space 0
    the-list: list 400x400 [
        across 0 space 0x0
        text 50 purple
        text 250 bold [editor read to-file face/text]
        text 100 red italic
        return box green 400x1
    ] supply [
        count: count + slider-pos
        if none? q: pick x count [face/text: none exit]
        face/text: pick q index
    ]
    slider 16x400 [
        slider-pos: (length? x) * value
        show the-list
    ]
]

```

This example by Carl Sassenrath demonstrates a basic 4 column display:

```

REBOL []

db: [
    [ "000" "Ian Fleming" "ian" 31-Dec-2003 ]
    [ "007" "James Bond" "jb" 1-Jan-2004 ]
    [ "001" "M" "m" 2-Jan-2004 ]
    [ "ABC" "Miss Money Penny" "missm" 3-Jan-2004 ]
    [ "008" "Pierce Brosnan" "pb" 4-Jan-2004 ]
    [ "009" "George Lazenby" "gl" 5-Jan-2004 ]
    [ "010" "Roger Moore" "rm" 6-Jan-2004 ]
]
sld-cnt: 0
view lst1: layout [across space 0x0
    style text text [alert form face/user-data]
    list 406x100 [
        across space 0x0 text 36 text 100 text 120 text 150
    ] supply [
        face/text: none face/user-data: none
        count: count + sld-cnt
        record: pick db count
        if not record [exit]
        n: pick [1 2 3 4] index
        face/text: pick record n
        face/user-data: record
    ]
    scl1: scroller 16x100 [
        value: to-integer value * length? db
    ]
]

```

```

        if value <> sld-cnt [sld-cnt: value show lst1]
    ]
]

```

The following example demonstrates how to enable users to add and remove data from a list display. Notice that after adjusting the content of your original data block and then "show"ing the list, the displayed grid is automatically updated with the new data:

```

x: copy []
for i 1 10 1 [
    append/only x reduce [form random 1000 form random 1000]
]

slider-pos: 0
view layout [
    across
    the-list: list 220x240 [across text 100 text 100] supply [
        count: count + slider-pos
        if none? q: pick x count [face/text: none exit]
        face/text: pick q index
    ]
    slider 16x240 [
        slider-pos: (length? x) * value
        show the-list
    ]
    return
    btn "Remove" [remove head x show the-list]
]
btn "Add" [
    insert/only head x reduce [form random 1000 form random 1000]
    show the-list
]
]

```

To save user-edited contents of a GUI list created with the "supply" function, you need to use the following "set-it" code when iterating through the supply function with "count" and "index" (the "second second get in (list-widget-label) 'subfunc" trick only works for lists created using the "data" function):

```

x: copy [
    ["row 1, column 1" "row 1, column 2"]
    ["row 2, column 1" "row 2, column 2"]
    ["row 3, column 1" "row 3, column 2"]
    ["row 4, column 1" "row 4, column 2"]
]
do qq: [view gui: layout [
    the-list: list 304x100 [
        across space 0
        info 150 [face/text: request-text/default face/text show gui]
        info 150 [face/text: request-text/default face/text show gui]
    ] supply [
        either count > length? x [face/text: "" face/image: none] [
            the-list/set-it face x index count
        ]
    ]
    across
    btn "Save" [
        save to-file request-file/save x
    ]
    btn "Load" [
        x: copy load to-file request-file
        unview do qq
    ]
]
]]

```

Be sure to see <http://www.rebol.org/view-script.r?script=list-supply-how-to.r>, <http://www.rebol.org/view->

[script.r?script=vid-usage.r](http://www.rebol.org/view-script.r?script=vid-usage.r), <http://www.rebol.org/view-script.r?script=list-scroll-demo.r>, and <http://www.pat665.free.fr/gtk/rebol-view.html#sect19>, for more about lists.

9.14.2 Creating Home Made Multi Column Data Grids

As it turns out, it can actually be easier and more versatile to roll your own data grids using native VID components, than it is to use the "list" widget. The following examples are based on the concept at <http://www.rebol.org/view-script.r?script=presenting-text-in-columns.r>. In every example, a forskip loop is used to build a visual grid of GUI widgets. The loop inserts individual text items from a data block onto each widget's face. For large lists, these example run slowly, but they can be useful for creating reasonably small displays.

The first example creates a random block of two columns of data, labeled "x". Then, a forskip loop is used to assemble a layout block of field widgets, with each row of fields containing 2 consecutive text items from the data block. That GUI block is then displayed on a pane inside a box widget, which is itself displayed inside the layout of the main window. A scroller widget is added to scroll the visible portion of the grid layout. This is accomplished by adjusting the offset of the pane which contains the whole layout of field widgets. IMPORTANT: notice that each cell in this grid is *user editable* (simply because each cell is displayed using a standard VID field widget). Also notice that the data is converted to a string with the "form" function, because fields can only display text.

```
x: copy [] for i 1 179 1 [append x reduce [i random "abcd"]]

grid: copy [across space 0] ; the GUI block containing the grid of fields
forskip x 2 [append grid compose [field (form x/1)field (form x/2)return]]
view center-face layout [across
  g: box 400x200 with [pane: layout/tight grid pane/offset: 0x0]
  scroller [g/pane/offset/y: g/size/y - g/pane/size/y * value show g]
]
```

The next example demonstrates how to take two columns of data (blocks) and combine them into a single block that can be displayed using the layout above. First, the size of the longest block is determined using the "max" function, and a for loop is run to add consecutive items from each of the source blocks, in groups of 2, to the destination block. If either column runs out of data, blank strings are added to the rest of the destination block as column place holders.

```
x: copy []
block1: copy system/locale/months block2: copy system/locale/days
for i 1 (max length? block1 length? block2) 1 [
  append x either g: pick block1 i [g] [""]
  append x either g: pick block2 i [g] [""]
]

grid: copy [across space 0]
forskip x 2 [append grid compose [field (form x/1)field (form x/2)return]]
view center-face layout [across
  g: box 400x200 with [pane: layout/tight grid pane/offset: 0x0]
  scroller [g/pane/offset/y: g/size/y - g/pane/size/y * value show g]
]
```

The next example demonstrates how to change the look of the grid layout, and *how to obtain a block containing all the data displayed in the grid, including user edits*. To clarify visual separation of row data, an alternating color is assigned to each row in the grid. This is handled using a "remainder" function to check for even numbered rows. For every 4 pieces of text in the data block (every 2 displayed rows), the color is set to white. Otherwise, it's set to wheat. The most important part of this example is the line which collects all the data contained in each face of the displayed grid, and builds a block ("q") to store it.

```
x: copy [] for i 1 179 1 [append x reduce [i random "abcd"]]

grid: copy [origin 0x0 across space 0x0]
forskip x 2 [
  color: either (remainder ((index? x) - 1) 4) = 0 [white][wheat]
  append grid compose [
    field 180 (form x/1) (color) edge none
    field 180 (form x/2) (color) edge none return
  ]
]
```

```

    ]
  ]
  view center-face layout [
    across space 0
    g: box 360x200 with [pane: layout grid pane/offset: 0x0]
    scroller[g/pane/offset/y: g/size/y - g/pane/size/y * value / 2 show g]
    return box 1x10 return ; just a spacer
    btn "Get Data Block (INCLUDING USER EDITS)" [
      q: copy [] foreach face g/pane/pane [append q face/text] editor q
    ]
  ]
]

```

The next example demonstrates a number of features that really make the grid malleable and useful for entering, editing, and storing columns of data. First, the look is adjusted by changing the edges of each field style. To enable all the new features, an "update" function is created to run the line of code from the previous example which creates the "q" block of data from text displayed in every cell of the grid. In every case, the data is collected and stored in the variable "q", and the desired operation is performed on that block (adding and removing rows or data, extracting vertical columns of data, saving and loading the data to/from files on the hard drive, etc.). After the data block has been changed by an operation, the entire layout is unviewed and rebuilt using the new data (i.e., the "q" data is reassigned to the initial "x" block). The code is rerun by labeling the entire script "qq" and using the "do" function to re-evaluate it. The final button demonstrates how to collect and display a history of user edits.

```

x: copy [] for i 1 179 1 [append x reduce [i random "abcd"]]

update: does [q: copy [] foreach face g/pane/pane [append q face/text]]
do qq: [grid: copy [across space 0]
for skip x 2 [append grid compose [
  field (form x/1) 40 edge none
  field (form x/2) 260 edge [size: 1x1] return
]]
view center-face gui: layout [across space 0
  g: box 300x290 with [pane: layout/tight grid pane/offset: 0x0]
  slider 16x290 [
    g/pane/offset/y: g/size/y - g/pane/size/y * value show g
  ]
  return btn "Add" [
    row: (to-integer request-text/title "Insert at Row #:") * 2 - 1
    update insert at q row [" " ""] x: copy q unview do qq
  ]
  btn "Remove" [
    row: (to-integer request-text/title "Row # to delete:") * 2 - 1
    update remove/part (at q row) 2 x: copy q unview do qq
  ]
  btn "Col 1" [update editor extract q 2]
  btn "Col 2" [update editor extract/index q 2 2]
  btn "Save" [update save to-file request-file/save q]
  btn "Load" [x: load to-file request-file do qq]
  btn "History" [
    m: copy "ITEMS YOU'VE EDITED:^^/" update for i 1 (length? q) 1 [
      if (to-string pick x i) <> (to-string pick q i) [
        append m rejoin [pick x i " " pick q i newline]
      ]
    ] editor m
  ]
]
]

```

This final example clarifies how to add additional columns, how to use GUI widgets other than fields to display the data (text widgets, in this case), how to make the widgets perform any variety of actions, and how to get data from the grid when not every widget has text on its face. It also demonstrates some additional changes to the look of the grid.

```

x: copy [] for i 1 99 1 [append x reduce [i random 99x99 random "abcd"]]

grid: copy [origin 0x0 across space 0x0]
for skip x 3 [
  append grid compose [

```

```

        b: box 520x26 either (remainder((index? x)- 1)6)= 0 [white][beige]
        origin b/offset
        text bold 180 (form x/1)
        text 120 center blue (form x/2) [alert face/text]
        text 180 right purple (form x/3) [face/text: request-text] return
        box 520x1 green return
    ]
]
view center-face layout [
    across space 0
    g: box 520x290 with [pane: layout grid pane/offset: 0x0]
    scroller 16x290 [
        g/pane/offset/y: g/size/y - g/pane/size/y * value / 2 show g
    ]
    return box 1x10 return ; just a spacer
    btn "Get Data Block" [
        q: copy []
        foreach face g/pane/pane [
            if face/style = 'text [append q face/text]
        ]
        editor q
    ]
]

```

These examples are useful for lists that contain ~1000 or fewer rows of data. For displays with grids larger than that, one of REBOL's other listview options should be used.

9.15 RebGUI

REBOL's VID dialect ("view layout []"), is one of the language's most attractive features. The ability to create GUI windows on multiple operating systems, with as little as 1 line of code, is practical for creating many sorts of applications. "RebGUI" is a third party GUI toolkit built on REBOL/View which replicates many of the basic components in VID, and upgrades/adds to the concept with many desirable features:

1. Modern look and feel.
2. Many powerful and useful new widgets and built-in functions: resizable tables (data grids) with automatic column sorting, trees, menus, tab and scroll panels, group boxes, tool-bars, spreadsheet, pie-chart and chat widgets, new requestors, native undo/redo, spellcheck, and translate functions (with many provided language dictionaries) for text widgets, etc.
3. Simple and elegant syntax (similar to VID).
4. Full documentation and demo code for all widgets.
5. Super simple notation to handle *automatic alignment and layout of widgets in resized windows*.
6. Config file to easily manage user settings for global UI sizes, colors, behaviors, and effects of all widgets. A built-in native requestor is also provided to adjust all these settings.
7. Automatic handling of window close events.
8. User assignable function key actions.
9. Easy, automatic handling of multiple user languages.
10. Well designed object structure to access every widget, function, and feature (and containing all necessary help information, built in).
11. The entire system compresses to just over 30k.

VID is great for building quick scripts, and many of the features found in RebGUI have been created elsewhere as VID add-ons. The menu system and listview widget described earlier in this text, for example, are more powerful than those found in RebGUI. Close events and spell checking can also be handled in other ways described earlier in this text. But for most types of applications, RebGUI provides a single, simple, integrated way to build applications with all the most commonly needed user interface features. It uses a simple, consistent language structure, and provides a clean, modern looking visual design.

RebGUI is available at <http://www.dobeash.com/download.html>, and several tutorials are available at <http://www.dobeash.com/rebgui.html>. A mirror of the required files in version 117 is available at http://musiclessonz.com/rebol_tutorial/rebgui.zip. You can also download RebGUI directly within REBOL, using the built in Viewtop. To open the Viewtop, type "desktop" into the REBOL interpreter, then click REBOL -> Demos -> RebGUI. That will download the main "rebgui.r" include file, along with the "RebDoc.r" help program, the "tour.r" demo program, and some supporting graphic images. The downloaded package will automatically run tour.r, which demonstrates many of RebGUI's features. Be sure to click the "RebDOC" button to view all the documentation necessary to use RebGUI.

All you need to use RebGUI is %rebgui.r. Copy it to an accessible folder and include the line "do %rebgui.r" (with its path, if necessary), and then you can use all the built in widgets and functions in RebGUI.

A quick and dirty way to do this in Windows is to run the "request-file" function in REBOL, then click Public -> www.Dobeash.com -> RebGUI, right click rebgui.r and paste it into a folder of your choice. You can also use the following script to copy it to any folder:

```
write to-file request-file/file/title/save %rebgui.r "Save As:" {
  } read view-root/public/www.dobeash.com/RebGUI/rebgui.r
```

If you're going to use RebGUI regularly, it's a good idea to copy it directly into your main REBOL install directory (the default folder is c:\program files\rebol\view).

To build your first RebGUI interface, after running the RebGUI demo, try the following code:

```
do view-root/public/www.dobeash.com/RebGUI/rebgui.r
display "Test" [button "Click Me" [alert "Clicked"]]
do-events
```

Notice that "view layout" has been replaced with "display". This function always requires some title text. Notice also that "do-events" must be included after your RebGUI code to activate the GUI.

Once you've included %rebgui.r, you can try any of the built-in widgets and functions:

```
display "" [area] do-events ; the "area" widget
```

Notice that the area widget above has built-in undo/redo features using [CTRL]-Z and [CTRL]-Y (REBOL's native "view layout [area]" does *not* have any undo/redo capability). A built-in *spellchecker* can also be activated using [CTRL]-S! To use the spellchecker, you need to download a dictionary from <http://www.dobeash.com/RebGUI/dictionary>, and unzip it into %view-root/public/www.dobeash.com/RebGUI/dictionary/ (or in the /dictionary subdirectory of wherever rebgui.r is located).

Take a look at a few of the other great widgets built into RebGUI:

```
do %rebgui.r ; be sure to include the path, if necessary

display "Pie Chart" [pie-chart data ["VID" yellow 19 "RebGUI" red 81]]
do-events

display "Spreadsheet" [
  sheet options [size 7x7] data [a1 "very " a2 "cool" a3 "=join a1 a2"]
]
do-events

display "Chat" [
  chat data ["Nick" blue "I like RebGUI" yellow 20-sep-2009/1:00]]
do-events

display/maximize "Menu" [
  menu data [
    "File" [
      "Open" [request-file]
      "Save" [request-file]
    ]
    "About" ["Info" [alert "RebGUI is great!"]]
  ]
]
do-events
```

You can run the RebDoc.r program to see the syntax required to use any of the other RebGUI widgets, requestors and functions.

The `/close` refinement of the `display` function lets you set any action(s) you want to run when a GUI window is shut down. This can help avoid data loss from accidental window closure, and provides a way to automatically process data or run other applications when a window is closed:

```
display/close "" [area] [question "Really Close?"] do-events
```

Be sure to try the `request-ui` requestor function. It lets you easily adjust the global settings for the overall look and feel of layouts created with RebGUI on your machine. Settings are saved in the file `%ui.dat`, in the current working directory.

```
request-ui
```

RebGUI includes a variety of "span directives" to easily automate resizing of widgets:

These directives automatically set the initial size of a widget:

```
#L - align the right hand edge of the widget with the adjacent edge
#V - align the base edge of the widget with the adjacent edge
#O - align the left hand edge of the widget with the adjacent edge
```

("adjacent edge" is the edge of the adjacent widget, or the edge of the GUI, if there is no adjacent widget.)

These directives automatically adjust the size and position of a widget when the GUI is resized:

```
#H - stretch or shrink the widget to fit the window height
#W - stretch or shrink the widget to fit the window width
#X x - move the widget x number of pixels to the right
#Y y - move the widget y number of pixels downward
```

Here's an example of an area widget that stretches and shrinks to fit a resized GUI window:

```
display "" [area #HW] do-events
```

Here's a fully functional, resizable text editor application, with built-in undo/redo, spell checking, and close event handling:

```
do %rebgui.r
display/maximize/close "Text Editor" [
  menu #LHW data [
    "File" [
      "Open" [x/text: read to-file request-file show x]
      "Save" [write to-file request-file/save x/text]
    ]
  ] return
  x: area #LHW
] [question "Really Close?"] do-events
```

Now that's a lot of program for just a little code!

Here's a useful spreadsheet application, with save, load, print and data view features:

```
do %rebgui.r
display "Spreadsheet" [
  x: sheet options [size 3x3 widths [8 8 10]] data [
    A1 32 A2 12 A3 "=a1 + a2" A4 "=1.06 * to-integer a3"
```

```

]
return
button "Save" [
  x/save-data
  save to-file request-file x/data
]
button "Load" [
  x/load-data load to-file request-file
]
button "View" [
  x/save-data
  alert form x/data
]
button "Print" [
  save/png %sheet.png to image! x
  browse %sheet.png ; or call %sheet.png
]
]
do-events

```

This example demonstrates how to use tab panels and a variety of useful techniques:

```

display "Tab Panel" [
  main-screen: tab-panel data [
    "Spreadsheet" [
      x: sheet data [
        A1 32 A2 12 A3 "=a1 + a2" A4 "=1.06 * to decimal! a3"
      ]
      a: area
      reverse
      button -1 " Show Data " [x/save-data set-text a x/data]
      button -1 " Quit! " [quit]
    ]
    "VID style" [
      style -1 data [text bold "Back to Spreadsheet" [
        main-screen/select-tab 1
      ]]
    ]
    action [wait .2 face/color: 230.230.230] "Text" [
      text "Tabs are a great way to maximize screen real estate."
    ]
    action [wait .2 set-focus z] "Fields" [
      y: field
      z: field "Edit me"
    ]
  ]
]
do-events

```

To really get to know RebGUI, explore its main object "ctx-rebgui":

```
? ctx-rebgui
```

The "ctx-rebgui" object is set up much like REBOL's built-in "system/view/vid" object. You can explore it using path notation. Notice that built-in help is included in the "tip" path of each widget:

```
? ctx-rebgui/widgets/tree/tip
```

Here's a quick and dirty way to view help for all the RebGUI widgets:

```
foreach i (find first ctx-rebgui/widgets 'anim) [
```



```
do compose/deep [print rejoin[i" - "(ctx-rebgui/widgets/(i)/tip)"^/"]]
]
```

Be sure to read the main RebGUI user guide at <http://www.dobeash.com/RebGUI/user-guide.html>, and the cookbook at <http://www.dobeash.com/RebGUI/cookbook.html>. Then read through all the info in RebDoc.r, examine the code in tour.r, and get to know your way around ctx-rebgui. You'll likely find that RebGUI is the best choice for GUI layout in many situations.

Here is a point of sale system (sales checkout, receipt printer, and data storage system) written using RebGUI. It should provide a number of practical insights into how to use RebGUI. Note that the username and password info in the posp.db file should be created and read using a separate method, and encrypted. The example posp.db file is created here as a demonstration. Note also that the first field in the layout is designed to accept input from a keyboard wedge bar code scanner, with data in the format: item (space) booth (space) price (inserted [ENTER] key character). Using this format, and the automatic refocus upon entry, the user can continually scan multiple items into the system:

```
REBOL [title: "POINT OF SALE SYSTEM"]

write %posp.db [{"username" "password"} [{"username2" "password2"}] ; etc.
make-dir %./receipts/
write/append %./receipts/deleted.txt "" ; create file if not exists

unless exists? %scheme_has_changed [
  write %ui.dat decompress #{
    789C9552CB92A3300CBCE72BBCDCA18084995A7E652A078115F08EB129592C33
    7FBFC24E32CC2387A5EC2A49ED6EB56C267845E5BB3FD8F32FF57250F2CD3060
    ABEEA629E23E95B1CAF8C6AD7A3A1571A5D28813E6D60CA32055752AAAE67751
    97CF3B5003BDB6EA5817CF821E9B8804067E484BE04F34BFB035EE4EACCB5371
    DD9FE044AD8E4FC5751FCE6AFA3E648FD6B62A51516F035731BE78B7B9AAEF49
    3EE2D5693A3CC02CCD63B8F5DB8CC464021A8CBB49066B3492901EB4879E8D77
    B92C74BC1D7CD1E467992DB0D8319CA28B41ABE53D42583D691566E31C521438
    7F9161E844241276780F84BCC117DF2F410E480E7BFCBDB7A697FA407E99F3CE
    BF493787568511919588E631DF5146131F602FFA1F8645B1437D35A2BA85D93B
    F5317A8C9810BF5DC240E6A1F0CF374CE4D790B31F507E45B9E10BD8801122D0
    6633DEEC5E3CFB8BA4C14176AF6D936540066CA6B2DE2F649094C35532361386
    EC0B270D18660B61CC355A78BFFD53ECBD6533DF8A655BCA4AD08A9D366E905E
    4C4B72B71AA7FDDA2AE71D1ECEFF004BE40F38A0030000
  }
]

do http://re-bol.com/rebgui.r

do login: [
  userpass: request-password
  if (length? userpass) < 2 [quit]
  posp-database: to-block read %posp.db
  logged-in: false
  foreach user posp-database [
    if (userpass/1 = user/1) and (userpass/2 = user/2) [
      logged-in: true
    ]
  ]
  either logged-in = true [] [
    alert "Incorrect Username/Password"
    do login
  ]
]

calculate-totals: does [
  tax: .06
  subtotal: 0
  foreach [item booth price] pos-table/data [
    subtotal: subtotal + to decimal! price
  ]
  set-text subtotal-f subtotal
  set-text tax-f (round/to (subtotal * tax) .01)
  set-text total-f (round/to (subtotal + (subtotal * tax)) .01)
  set-focus barcode
]

add-new-item: does [
```

```

if ("" = copy f1/text) or ("" = copy f2/text) or (error? try [
  to-decimal copy f3/text
]) [
  alert trim/lines {You must enter a proper Item Description,
    Booth Number, and Price.}
  return
]
pos-table/add-row/position reduce [
  copy f1/text copy f2/text copy f3/text
] 1
calculate-totals
]
print-receipt: does [
  if empty? pos-table/data [
    alert "There's nothing to print." return
  ]
  html: copy rejoin [
    {<html><head><title>Receipt</title></head><body>
    <table width=40% border=0 cellpadding=0><tr><td>
    <h1>Business Name</h1>
    123 Road St.<br>
    City, State 98765<br>
    123-456-7890
    </td></tr></table><br><br>
    <center><table width=80% border=1 cellpadding=5>
    <tr>
    <td width=60%><strong>Item</strong></td>
    <td width=20%><strong>Booth</strong></td>
    <td width=20%><strong>Price</strong></td></tr>}
  ]
  foreach [item booth price] pos-table/data [
    append html rejoin [
      {<tr><td width=60%> } item
      {</td><td width=20%> } booth
      {</td><td width=20%> } price {</td></tr>}
    ]
  ]
  append html rejoin [
    {<tr><td width=60%></td><td width=20%><strong>SUBTOTAL:
    </strong></td><td width=20%><strong>
    </strong></td></tr>
    copy subtotal-f/text
    {</strong></td></tr>}
  ]
  append html rejoin [
    {<tr><td width=60%></td><td width=20%><strong>TAX:
    </strong></td><td width=20%><strong>
    </strong></td></tr>
    copy tax-f/text
    {</strong></td></tr>}
  ]
  append html rejoin [
    {<tr><td width=60%></td><td width=20%><strong>TOTAL:
    </strong></td><td width=20%><strong>
    </strong></td></tr>
    copy total-f/text
    {</strong></td></tr>}
  ]
  append html rejoin [
    {</table><br>Date: <strong> } now/date
    {</strong>, Time: <strong> } now/time
    {</strong>, Salesperson: } userpass/1
    {</center></body></html>}
  ]
  write/append to-file saved-receipt: rejoin [
    %./receipts/
    now/date "_"
    replace/all copy form now/time ":" "-"
    "+" userpass/1
    ".html"
  ] html
  browse saved-receipt
]
save-receipt: does [
  if empty? pos-table/data [

```

```

    alert "There's nothing to save." return
  ]
  if allow-save = false [
    unless true = resaving: question trim/lines {
      This receipt has already been saved.  Save again?
    } [
      if true = question "Print another copy of the receipt?" [
        print-receipt
      ]
      return
    ]
  ]
  if resaving = true [
    resave-file-to-delete: copy ""
    display/dialog "Delete" compose [
      text 150 (trim/lines {
        IMPORTANT - DO NOT MAKE A MISTAKE HERE!
        Since you've made changes to an existing receipt,
        you MUST DELETE the original receipt.  The original
        receipt will be REPLACED by the new receipt (The
        original data will be saved in an audit history file,
        but will not appear in any future seaches or totals.)
        Please CAREFULLY choose the original receipt to DELETE:
      })
      return
      t11: text-list 150 data [
        "I'm making changes to a NEW receipt that I JUST SAVED"
        "I'm making changes to an OLD receipt that I've RELOADED"
      ] [
        resave-file-to-delete: t11/selected
        hide-popup
      ]
      return
      button -1 "Cancel" [
        resave-file-to-delete: copy ""
        hide-popup
      ]
    ]
    if resave-file-to-delete = "" [
      resaving: false
      return
    ]
    if resave-file-to-delete = trim/lines {
      I'm making changes to a NEW receipt that I JUST SAVED
    } [
      the-file-to-delete: saved-file
    ]
    if resave-file-to-delete = trim/lines {
      I'm making changes to an OLD receipt that I've RELOADED
    } [
      the-file-to-delete: loaded-receipt
    ]
    if not question to-string the-file-to-delete [return]
    write %./receipts/deleted--backup.txt read %./receipts/deleted.txt
    write/append %./receipts/deleted.txt rejoin [
      newline newline newline
      to-string the-file-to-delete
      newline newline
      read the-file-to-delete
    ]
    delete the-file-to-delete
    alert "Original receipt has been deleted, and new receipt saved."
    resaving: false
  ]
  if true = question "Print receipt?" [print-receipt]
  saved-data: mold copy pos-table/data
  write/append to-file saved-file: copy rejoin [
    %./receipts/
    now/date "-"
    replace/all copy form now/time ":" "-"
    "+" userpass/1
    ".txt"
  ]

```

```

] saved-data
splash compose [
  size: 300x100
  color: sky
  text: (rejoin [{^/      *** SAVED ****^/      } saved-file {^/}])
  font: ctx-rebgui/widgets/default-font
]
wait 1
unview
allow-save: false
if true = question "Clear and begin new receipt?" [clear-new]
]
load-receipt: does [
  if error? try [
    loaded-receipt: to-file request-file/file/filter %./receipts/
      ".txt" "*.txt"
  ] [
    alert "Error selecting file"
    return
  ]
  if find form loaded-receipt "deleted" [
    alert "Improper file selection"
    return
  ]
  if error? try [loaded-receipt-data: load loaded-receipt] [
    alert "Error loading data"
    return
  ]
  insert clear pos-table/data loaded-receipt-data
  pos-table/redraw
  calculate-totals
  allow-save: false
]
search-receipts: does [
  search-word: copy request-value/title "Search word:" "Search"
  ; if search-word = none [return]
  found-files: copy []
  foreach file read %./receipts/ [
    if find (read join %./receipts/ file) search-word [
      if (%.txt = suffix? file) and (file <> %deleted.txt) [
        append found-files file
      ]
    ]
  ]
  if empty? found-files [alert "None found" return]
  found-file: request-list "Pick a file to open" found-files
  if found-file = none [return]
  insert clear pos-table/data (
    load loaded-receipt: copy to-file join %./receipts/ found-file
  )
  pos-table/redraw
  calculate-totals
  allow-save: false
]
clear-new: does [
  if allow-save = true [
    unless (true = question "Erase without saving?") [return]
  ]
  foreach item [barcode f1 f2 f3 subtotal-f tax-f total-f] [
    do rejoin [{clear } item {/text show } item]
  ]
  clear head pos-table/data
  pos-table/redraw
  allow-save: true
]
change-appearance: does [
  request-ui
  if true = question "Restart now with new scheme?" [
    if allow-save = true [
      if false = question "Quit without saving?" [return]
    ]
    write %scheme_has_changed ""
  ]
]

```

```

        launch %pos.r ; EDIT
        quit
    ]
]
title-text: "Point of Sale System"
if system/version/4 = 3 [
    user32.dll: load/library %user32.dll
    get-tb-focus: make routine! [return: [int]] user32.dll "GetFocus"
    set-caption: make routine! [
        hwnd [int]
        a [string!]
        return: [int]
    ] user32.dll "SetWindowTextA"
    show-old: :show
    show: func [face] [
        show-old [face]
        hwnd: get-tb-focus
        set-caption hwnd title-text
    ]
]

allow-save: true
resaving: false
saved-file: ""
loaded-receipt: ""

screen-size: system/view/screen-face/size
cell-width: to-integer (screen-size/1) / (ctx-rebgui/sizes/cell)
cell-height: to-integer (screen-size/2) / (ctx-rebgui/sizes/cell)
table-size: as-pair cell-width (to-integer cell-height / 2.5)
current-margin: ctx-rebgui/sizes/margin
top-left: as-pair negate current-margin negate current-margin

display/maximize/close "POS" [
    at top-left #L main-menu: menu data [
        "File" [
            "    Print      " [print-receipt]
            "    Save      " [save-receipt]
            "    Load      " [load-receipt]
            "    Search     " [search-receipts]
        ]
        "Options" [
            "    Appearance  " [change-appearance]
        ]
        "About" [
            "    Info      " [
                alert trim/lines {
                    Point of Sale System.
                    Copyright © 2010 Nick Antonaccio.
                    All rights reserved.
                }
            ]
        ]
    ]
]
return
barcode: field #LW tip "Bar Code" [
    parts: parse/all copy barcode/text " "
    set-text f1 parts/1
    set-text f2 parts/2
    set-text f3 parts/3
    clear barcode/text
    add-new-item
]
return
f1: field tip "Item"
f2: field tip "Booth"
f3: field tip "Price (do NOT include '$' sign)" [
    add-new-item
    set-focus add-button
]
add-button: button -1 "Add Item" [
    add-new-item

```

```

        set-focus add-button
    ]
    button -1 #OX "Delete Selected Item" [
        remove/part find pos-table/data pos-table/selected 3
        pos-table/redraw
        calculate-totals
    ]
    return
    pos-table: table (table-size) #LWH options [
        "Description" center .6
        "Booth" center .2
        "Price" center .2
    ] data []
    reverse
    panel sky #XY data [
        after 2
        text 20 "Subtotal:" subtotal-f: field
        text 20 "      Tax:" tax-f: field
        text 20 "      TOTAL:" total-f: field
    ]
    reverse
    button -1 #XY "Lock" [do login]
    button -1 #XY "New" [clear-new]
    button -1 #XY "SAVE and PRINT" [save-receipt]
    do [set-focus barcode]
    ] [question "Really Close?"]

do-events

```

9.16 Creating PDF files using pdf-maker.r

PDF is a standard file format used to display and print document content in exactly the same way on different computer platforms. In Windows and other operating systems, the PDF reader by Adobe is often installed by default. Other free PDF readers such as [Foxit](#), [Sumatra](#), and [PDF-Xchange](#) allow you to view and print PDF documents. [Openoffice](#) can be used to create, convert, and save various document formats (i.e. MS Word and other word processor formats) to PDF, so that they are viewable/printable in the exact same visual layout, on any computer.

Gabriele Santilli has created a REBOL [pdf-maker](#) script that generates universally readable and printable PDF files directly from REBOL code. The official documentation is available at <http://www.colellachiara.com/soft/Misc/pdf-maker-doc.pdf> (the REBOL source used to create that PDF document is available at <http://www.colellachiara.com/soft/Misc/pdf-maker-doc.r>). Pdf-maker.r is a complete, self contained multi-platform solution for creating PDFs. No other software is required to create PDFs with REBOL.

The basic functionality of pdf-maker.r is very simple. Import pdf-maker.r with the "do" function (or simply include it directly in your code). Next, run the "layout-pdf" function, which takes one block as a parameter, and write its output to a .pdf file using the "write/binary" function. Inside the block passed to the "layout-pdf" function, a variety of formatting functions can be included to layout text, images, and manually generated graphics. Here's a basic example of the format, with one simple text layout function:

```

do http://www.colellachiara.com/soft/Misc/pdf-maker.r
write/binary %example.pdf layout-pdf [[textbox ["Hello PDF world!"]]]

; To open the created document in your default PDF viewer:

call %example.pdf

```

Here's a more complex example that creates a multi-page PDF file and demonstrates many of the basic capabilities of pdf-maker.r. Separate page content is contained in separate sub-blocks. All coordinates are written in MILLIMETER format:

```

REBOL [title: "pdf-maker example"]

do http://www.colellachiara.com/soft/Misc/pdf-maker.r

```

```

write/binary %example.pdf layout-pdf compose/deep [
  [
    page size 215.9 279.4 ; American Letter Size!!!
    textbox ["Here is page 1. It just contains this text."]
  ]
  [
    textbox 55 55 90 100 [
      {Here's page 2. This text box contains a starting
      XxY position and an XxY size. Coordinates are in
      millimeters and extend from the BOTTOM LEFT of the
      page (this box extends from starting point 55x55
      and is 90 mm wide, 100 mm tall).

      *** NOTE ABOUT PAGE SIZES - IMPORTANT!!! ***

      All the following page sizes are the default ISO A4,
      or 211x297 mm. That is SLIGHTLY SMALLER than the
      standard American Letter page size. If you are
      printing on American Letter sized paper, be sure to
      manually set your paper size, as is done on the first
      page of this example.}
    ]
  ]
  [
    textbox 0 200 200 50 [
      center font Helvetica 10.5
      {This is page 3. The text inside this box is centered
      and formatted using Helvetica font, with a character
      size of 10.5 mm.}
    ]
  ]
  [
    apply rotation 20 translation 35 150 [
      textbox 4 4 200 20 [
        {This is page 4. The textbox is rotated 20 degrees
        and translated (moved over) 35x150 mm. Graphics
        and images can also be rotated and translated.}
      ]
    ]
  ]
  [
    textbox 5 200 200 40 [
      {Here's page 5. It contains this textbox and several
      images. The first image is placed at starting point
      50x150 and is 10mm wide by 2.4mm tall. The second
      image is 2x bigger and rotated 90 degrees. The last
      image is placed at starting point 100x150 and is
      stretched to 10x its size. Notice that this ENTIRE
      layout block has been evaluated with compose/deep to
      evaluate the images in the following parentheses.}
    ]
    image 50 150 10 2.4 (system/view/vid/image-stock/logo)
    image 50 100 20 4.8 rotated 90
      (system/view/vid/image-stock/logo)
    image 100 150 100 24 (system/view/vid/image-stock/logo)
  ]
  [
    textbox [
      {This page contains this textbox and several generated
      graphics: a line, a colored and filled box with a
      colored edge, and a circle.}
    ]
    line width 3 20 20 100 50 ; starting and ending XxY positions
    solid box edge width 0.2 edge 44.235.77 150.0.136 100 67 26 16
    circle 75 50 40 ; starting point 75x50, radius 40mm
  ]
]

call %example.pdf

```

The compose/deep evaluation is very important when using computed values in PDF layouts. Take a look at the following example that uses computed coordinates and image values:

```
do http://www.colellachiara.com/soft/Misc/pdf-maker.r
xpos: 50 ypos: 200 offset: 5
size: 5 width: (10 * size) height: (2.4 * size)
page1: compose/deep [[
    image
        (xpos + offset) (ypos + offset)
        (width) (height)
        (system/view/vid/image-stock/logo)
]]
write/binary %example.pdf layout-pdf page1
call %example.pdf
```

Here is a program that I wrote for guitar students. It prints out fretboard note diagrams that can be cut out, wrapped around, and taped directly to guitar fretboards of specific varied sizes. The pdf-maker script is included in compressed, embedded format:

```
REBOL [title: "Guitar Fretboard Note Overlay Printer"]

chosen-scale: none
view center-face layout [
    hl "Fretboard length:"
    text-list "25.5" "27.67" "30" [
        chosen-scale: join "scale" value
        unview
        alert rejoin [
            "Now printing "
            value
            " inch scale fretboard overlay to 'notes.pdf'"
        ]
    ]
]

notes: [
    [{F}{C}{ }{ }{ }{ }{F}]
    [{ }{ }{A}{E}{B}{ }{ }]
    [{G}{D}{ }{F}{C}{G}]
    [{ }{ }{B}{ }{ }{ }{ }]
    [{A}{E}{C}{G}{D}{A}]
    [{ }{F}{ }{ }{ }{ }{ }]
    [{B}{ }{D}{A}{E}{B}]
    [{C}{G}{ }{ }{F}{C}]
    [{ }{ }{E}{B}{ }{ }{ }]
    [{D}{A}{F}{C}{G}{D}]
    [{ }{ }{ }{ }{ }{ }{ }]
    [{E}{B}{G}{D}{A}{E}]
]

scale25.5: [
    36.35 70.66 103.05 133.62 162.47 189.71 215.41 239.67 262.58 284.19
    304.59 323.85 342.03 359.18 375.38 390.66 405.09 418.70 431.56 443.69
    455.14 465.95 476.15 485.77
]

scale27.67: [
    39.45 76.68 111.82 144.99 176.30 205.85 233.74 260.07 284.92 308.38
    330.51 351.41 371.13 389.75 407.32 423.91 439.56 454.34 468.28 481.45
    493.87 505.60 516.67 527.11
]

scale30: [
    42.77 83.14 121.24 157.20 191.15 223.18 253.43 281.97 308.91 334.34
    358.34 381.00 402.38 422.57 441.62 459.60 476.57 492.59 507.71 521.99
    535.46 548.17 560.17 571.50
]
```



```

x: 40 line-width: 30 text-width: 4 height: 5

make-overlay: does [
  page1: copy [
    textbox 40 0 4 6 [center font Helvetica 5 "E"]
    textbox 45 0 4 6 [center font Helvetica 5 "B"]
    textbox 50 0 4 6 [center font Helvetica 5 "G"]
    textbox 55 0 4 6 [center font Helvetica 5 "E"]
    textbox 60 0 4 6 [center font Helvetica 5 "A"]
    textbox 65 0 4 6 [center font Helvetica 5 "E"]
  ]
  output: copy []
  for i 1 10 1 [
    y: do compose [pick (to-word chosen-scale) i]
    notes-at-fret: pick notes i
    append page1 compose/deep [
      line width 4 (x) (y) (x + line-width) (y)
      textbox (x) (y - 10) (text-width) (height + 1) [
        center font Helvetica (height) (notes-at-fret/1)
      ]
      textbox (x + 5) (y - 10) (text-width) (height + 1) [
        center font Helvetica (height) (notes-at-fret/2)
      ]
      textbox (x + 10) (y - 10) (text-width) (height + 1) [
        center font Helvetica (height) (notes-at-fret/3)
      ]
      textbox (x + 15) (y - 10) (text-width) (height + 1) [
        center font Helvetica (height) (notes-at-fret/4)
      ]
      textbox (x + 20) (y - 10) (text-width) (height + 1) [
        center font Helvetica (height) (notes-at-fret/5)
      ]
      textbox (x + 25) (y - 10) (text-width) (height + 1) [
        center font Helvetica (height) (notes-at-fret/6)
      ]
    ]
  ]
  append/only output page1
  write/binary %notes.pdf layout-pdf output
  alert "Done"
]

do to-string load to-binary decompress 64#{
eJztvWmzosyWKPy9I/o/eOrEjao6Rh0GJ6jo0ydABRRUBESxum4EM8goo3r7/vc3
Qd3isHfVc3q4/eH1edxqkrly5col5lDCmFwxrR8//mf/vmf9CjMzEPW+vHP/9QC
r8DMElDpV7f8SDVahqlHQZyYadrqd//8f85Vqpc5PWWHEjISl0fcGiwwsu46HK7
eC+tlB126ASqyUz7h5M0XJiuM5rLSCbNfWJpzCTsSKs3SF3F21iHDYERa8wx4XKs
HpyhfrYjCjeHlfmsZ2KRvKiZ3prQ/QEue1Ya5/d9nonfVd0wxsK3IjCfQ9qG5sQ
SjdQbFlsmChAZrcvU6YT7HDMCx1E5znIRLENfihwPONQTyJXR9819vsbPHC627tM
ziQZ1rVV77Q5FT1Gi7Keh9BFuIYGITgyujmOQINQ6nQ6AxwVoN4UfEMHUHug3SAN
+lJRFPwChf1DxCeFBB6LQxNrI/hmdoHEZj7Ng4GA8BsqtEpeUzJdMgaYAW2zqQsd
2jdIcddYF/5BG+wSt4tz2BCQ47adJVCU20w2JsRYSFKs+HyRz/P9gELCG8RtBfEG
CVrn2Qzqd3ornvG77WxAtVUH7XZFih04ctLJJoPM32+3XLcvhWm84srTSELzvi8t
90nagW6QertBjq5dqQ/N4O0s5/eDgYgHVCB2OUIrtkW8iadWxPdQvBeh+xDLZ4gd
2tRA2wz0Tm7mN0gelOqn/XQC7zTmqEjbaOee1G04FMfaaQvZWyo4HT0aCop5EEI7
JE/bgYLhx00Xk4zyoNI3SPlytFMCbKyMZJtzeytF7aGsGrT9w6qnzGIHctxC2hpC
NlT4lDM3Qy2FyKJwecbjrKk/uUEau9quNlSmWLF0EteUvczdtYlwwg8nEMttR3rh
9wYzI0/FXi4x815Kerird+ksilcQOYtukKglT3rswRnRZbA9OLOuJy5KYbcNlsdZ
ik6lWafc0ZqUr5OVu1spkN0RO/Fu3tbMsTUCdBpz16961hpyIWaypK3pensakJzN
oEQhBZMRb3dJfE+MjmiE9x2pra17WMEQJMecjE+d42yhsjdIO4HLvaXHj/wOLEFc
m2wTXpeQ7MWCiMvQJk2i1yX93YmUNA8ds7alcoJeyXypJhLhaXe8QRq2ybAcm+0N
JdswoW09sCB2XbIgrRhr2HNS2LEtjBzY3DJPJwRAR5vOhEtJfp5hudbdYzdIrMUG
xyIbDgpeFHFuWqLnEzxxni8VmIujktiQ2hKkt/fJQTlCWUCTxJqM2sSh3j/Nj2xbK
gyQGihSMHJUER7A5EXRHmk2tCT1tY5MoDKP530gCYFudREpqqQ4xTQinTVSAKkyhd
rVWpwQUTb7Vmtcmkjax3Vjc2N+WWJgliE6NluPGHQ4dZjrzh0aGWu4g8ktPqoyR7
SzsSYKJ3g0SkkhCa9AndFvc9tLAX+zx008meLqKJ2FGGOYF3R4w9MQlSIY1y3CE0
ndiXI99mLA+bWQ1IBkZYNomRkL3G+P5wTjPQdG5AxLg71PhUESHwNlPp+l4ZY5GN
YxFOxKgIdP8GKenxnY0yLPIFLCoAXHHY6soA3WyoVd/u2/LBSNmQnfr3ZgTvs0Uk
7Wd33xv8dC3lUkramdhwtuBnfdkpu1gJEbsR4CSM1QDziK5gkxOBndLk2B1HnjI9
Kvvd5gaJDNEKcjEst2nasJaSaZUUBph7gg2ZDr/C94UnYESnGn/HpgFnIRbsZ1a1
kmEH3EdXN0htVbTHXdyChpHT5wJ72+XWJNeZlt3BJDJOijfZWGpLS2tfF86QEr/Dx
aLnFj4zVHs+97JDDIC02Pgdze3u7ogckh5DzfVs42HDPQMKLsaI2pAwDjsJfZk9C

```

J21CK4k2MShHFpH1ChRhmRukoDekmU3sEETy15CK5IrkT9t2u79b5YyisjjVddOp
he9Rd+AIWxy0B4Khx3uvJxjKPrhBWhlEI8pNWObmqBr1lnqXVccDUY8WyzEjmtFi
zIzEZcpaKbQRunNSkKmCa08zmcrj/WAlaNhg3JjmbUBRRrofdPZLxFokTl+IjXmy
VMeL3UiB0fnlu9HpkB2D8qHEGBm5KkUG3QabvYs1Vprz7Z9lvQ0VvB08DbA2wRv
C7xtyrQXPTki5WnGtVvZODXBezmLpmJTZ07XyMQ2unaJWx5MIKRfygbVEWSYlEmx
y85gn8t8WiPnXci5hhZAFEYQY5KMr4AUz7Z0L6lWLvcwNM+1d87gOUP8IkbFeR4
ghf+KBZ0a3XI5+1se9jjdJsy6B3ZH/CZt8I2W/Z0aMzdBhdVYJaVdnfKerTvTbeE
KmGHBSYicdzl9ZksbpdHyJdmvWA5pNYUOoGVjbKZ7Ka07Og3SO6M7q0tWliF0o5a
nLbldC7GCafR8T28pMctO+znJl0RIaFukYtn1LYU623i9F/z+urlapSszhg9HaYJG
9HSFCSOm8OKS/dlb7BMtRGDjnj2mo96nczZdxsUxwOv6PD9HnrCT+3TusMPTKWL
ndi22z7hBUotoBEAgC2osj+ATCO3MNVhpqEGtTUuX5u+SpIVlm6lcoZDFIH3ytHA
pbC0RnD2Iif63WfID9fibq3TFG5Ay8AzFh7ahjECL2meWGKNuRuVoPI0J9AugdnM
hpjtr6KHp7t50dQhK7K1fgeb7lI3AzSjUjDjsHKRxuPNUiYtvGGvZuD0nAjwHCK
T+dHE2cW260RIN6mR+GCpciobNTfevRaa3jC5hvZyriVfFrCKHwGhRXtqs0iNee
Ly+VQOcm1FgnziOW8sRgJtGUN3TneJ0Nh0ds0Hu+39XWUB9jDplwBssszRY3SfNk
YzNc0tIusbMphHwCUl/zQ8Y6ddSsz8Dz/vGw6KzGrLEoBzRQjUJMtTEQ/9nlkOu3N
FwlpizHZIvbbWRZi0iLiU02zjv0oFxB0EeRyTea3+6mLo2sPP8pOmMWedVqAXvzx
HAeOZGpUfVm93+krEoTIC9UEYit08Q6CsF48nQ8WUG+D7/V53wvi6X6peuw+23v9
csvsbNbSiZtr2mCemAHD2iV39mhBgDEWtqjwrEzBbCUCumRoJ3LiCDF51EIW5WxB
nLoMQ0wrcU4a+gkoUl4HNpHseEMBMFvZkQfDl/CIgDBCQnCC6pDFcUJtdXjIWse+S
iU3mxLE7SuwGF+QEW2azzOm0XT3HwrAoT5nT5mYndSocxsBMyuJ0kZDOjGbU9e64
ONAYcdHtGHUpzgD+3Q3STPR0p+9OId4Jygz4zydrSaIjPzJi8cW6N1oOypJxJ4XG
HcUFZGq9kze2EJ8cMXNcLqSGvSNp39qOvOUun1FYUKLMxJzlsavp5rjLzQZwxhxx
mo+7LiusF70+zWuJ0e+cmJijBPB73ODMET8Fhd20yZzmOyI25wZUSoSydN3uJLJF
Z1G+IRewLE0tjre32JoT27gw2ChHBxb9ScMT26jDvgweLZ3lghLP+YBrj0fcEu0v
M3myg33Yn0+4fm+S9LSfAkI2azxcr3MyQmPJYqN1QlomlnogY8eNjNoFkXaHXUM
GHBu3eMKyrbcUSAkftyX0ymy5iWLMlna8FZ8Ea+0pClCjWjDPKJUOTn0JilEhuPT
xB9S3tEhjtulu5lFwoxesCfOqCHxxdTzk6iBysmcwI2Jj2RQCn5Q1qSycZWPRU4
lRNjssZEJ0Tzk2bjZY/moh20mh+Z7g5e9fpMd5TKCDvkvewgVCfrkqSkodfwxKLt
qpwsLE1NyOUxtkViNWM3uOadMXbhFpG9H53stDtFkzkxQjVqOVkf24jiKvv1lOu6
yg2SPQRepH2YzLxhQe3EmUsyiW8PFXqRo5Vf3le4REG6RGgvTMJQiHFxAMgsijE/
UULv3NDjwZJiy3E+o/WlslLK7WHRcGxwvMgp5UpuGPj0dMGA6krxunEvXrq4rRiD
uTHpu5xZNLyhhU+5ONkMTfKKL0SaZShhNm02pGw5Ee5ypo+0oPQTqySBTJlB082nu
OmVtXAx33A2SQVLHcksGyWKhwr2CKKOe00oP5Si/Bw7ngFWrCm1Mzm2sq/DMZq
Hx/ODDohC97eGXHDzzzGyGrMcpUKUd94KjocsR6W2m2jfbRdtfvTon2gl3yozwY
OXo3leWhsycc6rhmTVPDdg0r1bG8gdLHotPxYRBsNX5vWkBsxx2hQfMnpu8aFL9j
Bq6aklx4iqVoARxJ21fHwGT1fKbB4w65iVx1NLCDLme6u8hWSXlpzBjHkgXHEyfb
o71bHrztMXWWQqQcZ7EIPsrXVlxGE3i8bfhPejxZjdXhZJUUA6+SHD3bwwlRQDk5
7KkbJuBTlMKp4366RycBQqHRPhksNkcXlwsCMhs8biX6aTNVRpk5GKCQPS5m9EJs
m6sJRfT4OmEoStPhKtagZN7ombp9QPSqr2od/ZRldGjWiKjVYpXGduDkvb46j2MZ
4cxksVf26WAwB6BNqVOXMimvwmZEEJ5zXZQDBkWTBgo2CE7hqOFnrvThhucwckY
os8oolERIUKuchbDQ3ogQGt9KW0iypvPtzRJe4gdSWuTjzucMcBSlW5EZQVjarha
ROm4VJ2cnCESoyFG+mDdF+HM2EtZeASB3NexhiUuhhNaPJXsYjLNTwcmH6/oX31
9dAXsFfc470lW5DvlvNffhA1cwfQ4gR32DBuD8awF3pelwtXdt/TD8SU1/ux2elh
e77B46utudvUQtWPA/Wo5WMkXujySh3QOjTE4+Jwmg1+3uULfKkOnfl+ceh4+xNE
J4E+mNDWcr1BwlKxnRc6kndkOxsFnV0a9zimBhGVfMjN63jnJ9bKTAdqIDCJZNoR
rhLkA4IfsQ8ulzsfCDVK/15ktghhnZ8hyOkOXilnaVxOYYrRlG7TqLIIEXxKWBCR
DPhrbarVO+qpo3ZsnhipGUuB0g7oboHGUnBHLSTLLqGEowifzAuO2e/59TavmBnu
JHzG7xJofvQ6c8pZ9Ch4kvsNKwVHvpe5bIwcs+zU062N0u8zow0Ha9pMHpvZAAUu
cHdC0XobW821sKcNRA4zswvOfAOnTweuObCi6f0s6nCmeCJGaoHqsBl1CBImw7BQ
0slBjv39DtELhNmj7QlZCqnlvI+PBbPBT+ZCRstD7v1Wseqld/lCItv4ocnJi6Ek
dGekleIapMZWF2esxAr5zRbr5jlniM1lOcIbMQKD0YlxlIphgeCi38ePR0elMTMx
Ovj80M/5ABrttc3UWUX4ZoCAn+sOWjDRJh/RgtyGGrG5IhwLK5hmOnfqR+bCUlG/
vW6TvQRAOKjyTmizG4JPifJwIkChiwX6it4NJNjNzyjBADNo3SFItcgency9fTc7
jk77eV+BGMEakCeEmub00lRwOg8JknIXwA/i4t3YcZQd6emFrVWmjTydMS35THCn
c8YW+B3CrFmNCPb0Zou6Lq3EkeOyaqQAozuf0Fsd07X3ILb1lx3BLkjsZhqje8yb
mMP5Udp2ZITycGOJZLbomcPyJcgO6ZACTZ5wvb0kbWSZms/nhtzgzBUMI4gsSBsF
2jFwMwCp/oDwYTEDinqTxxvfnFv4Zpge2u01G/ussSonhaovQhpDIqiyGTQm+ldbf
5wifzKqf9slhstxZkiXhHBePo/GSFiPRFohovyfDJKPCEUJBcoPHV5CHCRZwZ4c8
QQKfG56LEEiwe0jJOAbzPVSzWzQgbsokrZl427faBzy5zogUsiST0GrpAIHry2mSG
c3k7XFIceE+HSx18yuDTnw6R4R5C3X0KtTmPwzGJHSuUvAxdYqUEJDNUUPyk5iLu
y10in3uOvBEPpBo5yyExdw+IkEGFZFTZiAh4h20biIRD6G9oQ23LQ6I9JXq7RrTB
oFlr0/VGHg2dpOHDW+redOGBD4WlvYOyqgb9YoeENGFI+W6euqysxdDRjU7uMNUJ
aiPaIIFPDIP5zqIVEDDTJwYw3J0q+wa8ygID4zfDDIQnRemYuYDhsylDdA6dubFb
ezmAn8A3Sfp35Wko7bGSaamMvNuZ40KCIR/qAdnldtGvApjTtUVhjE5zczazCERI
caBLE0i1Z5tGjnVFS8d83j/ZgjqkSo5l6Zl1b7mJy0r9TsDNjnljXpCl6iEcxeYn
me4d5+oC52BcbaczZtmIOVEN7zKxstqPEzdkSQ1LqEL0QAi11ZFpYTBIEQnqwPd1
Y9uGBiDwc/ComuyuZUDhonODxLeXYnt2yiwQlZtoD0LansLnURZtQy6xbndJ5DBK
dzrhlyBi1qu4mOriIV60WXYvZ0bDwyh491CnFQLCSiljRLp+JMMTrhGbpz485XB3
vVjCvsVSqINPJHG8iiB2jja0Cs5IirzyoCm06jjDKlu8CqcRCnc2WxkVrPq7X4fT
Mdu2lqvjbblCDXqHOuWnZkOC55OA7XvosUL5uFNIttvsdsNBtjhQeOZAfrjndIZY
6UTcPvm8pfdwZUypY9UvUHreUb2GTydoA7rYRKmjUyU6Wi6uTjyt4+Lc9+A08Dws

SLfUfHK5Db7xt8jCjI/I8MCgpyoLHzT0ONzZiykW/MTqnbaoRA7p/2izR0PBtWG
RqrRZvGj6M7CI8RHbbMnerGQKIHQZgXFGOVQGEZ67FMzkVJCSeiNlyRpJzg8N4m
Zhh5KkGcSi+IWxe4s4cLgivHQdHzyElN511NYtoFTmUj5jQJp0tQNmURg+5oZOsY
4ZS0SRTltE3g5ahDbHRClnIngC9YwPlO9kgS14rJFqC6sQNEjpZLa18M7FS4NLS
OUF3RzUD7LtEQozZAcOr81MSaBY/4GAqnpwiPQmPmJXJ7X4wyRpxCzNHOqkwVZfe
Nj20+b21bA8X5MKYnzq6wmvt3mGJoq5oxBSet61xOhin0WHmKMx0x1d1tJHrGUzQ
KZgchRnigXMA5mCnC9BYTjIBv/R2IJZmJ5GXINBmMXAmB2Psd5wDbakmzy4cA+s2
/IJDwoRp3970qG2IA3fcj9b8SrclWBkXOexZ8XEH7VE3GZxQm44OI9628nnmGcfI
AWHftKKhptHgSUX1Vnw4ThnFXyvSER4ltC6lATeV5zOvbUsO68xTN+G1/guv5DOYP
yZjSxcoB0qDnzjHDvuyOdK1kmnH1Co6bU+71Q/pZMoeXG+kdpXOFvIKXtiFLLT3
RBAi27NI75RKbzguGrpA7fd7w5HNVtmPKkBDR4s9esilBOF1Yx61rYXkMEWnXxC
0L3VLBdZeJmda+p6PcsmccOaH5Z9hb4jiZAtVFGTgVgKQKSQUGW4LwetAh2JA4vIk
8H1BRgaIEJ+wpR71lmdvqTkOr3NZ5RGtZxFreYTj0YGn0Up6o0URcrSasw3L+ONi5
Qxq82M1EAa/I dhzfFhsUbx+Xgh4snRWTUyE5TfejzW5ciOrgaOa+Dhyco9BfLoH7
hJQ7ZjuauXE4J8ZH9DDdCyzW0HRAF90LtgJdzvciLag6OS79gkXhFFHaBduJm1Zb
UvFRDEJEtQaddTKslhwYfAYPRgklvUEq+a66ACpJYDeYj7fHRY6PFN1ALGP7hPTI
tGscGDrm5nDe07E1WhgCVVLAndLJXj1KRo3svxlE3GbXp1la8sYSdxzSGy+Sx2Jn
TU0815o67nIrO9IWXggcX0IjuzdylvquLKcazm6njWwIsamC8K1CDE7TDdCNSBoM
M8NJRnNqB2ftwv7AGSaUPe+bafe4L51Aasgdt+pnRE8hc2yn0F0y6TDrkXrsnXpV
6iwnWORYkoWrQ3zJtgnrvLLBmSS+HGbwMG5mHhAlf9KskW/DaNSZcC6yLDML4hEg
8RY3kuCCyYm8SwxsckNoidBbtfsQcJjXESOTxy7byNPBLDcLlCU8y4KluBYVYbKd
bhfeZSPCV1UPNHetkUPvCPwTshb3kLgN8S6BwOnFw0PAzrxsJfH8p2udo9ThAWO
9s4OhqLuge+3J8s2v6d5qb3bcYJj7FvkqImE3dngM/wASZBuNDwMqEP5Ae/RC+1E
74VrbhEQqEv4NttZzdk+e/A3Qj6MVBne7PaBo8dbI2aKziYd9hujs2NB1mdrbmBn
fW7hOhFhDmV7PU8CSGwPNbavB8N1h9PyPekvBVkWLzK3ktcscKZXvso2dipQ1NrF
D/dyJLR1ThWPjiyi3ixarZJ/yPrFRGf8IF1ZKL9drVl+bBHSKO9mCoVwLkEHZoML
CooVVixFubMdKx3MDiH3RyC0GVGe5rLlqEGMKJlUt+Vy6erDk2z2tdWhPMYAYaY6
48m4AQlfcf5souJ3No3c9nHLLocFOzCGI6h0GB84Lbb5i0CFjEyZwVUYftZiVy3LM
QuUsOujrhqarFkD7XdK35+JxcwqOns7nyCd6uuWgNOnkp13aXk6TWCdGiIaK+HFO
TaL1IFTW9pzpIKNRI5ZCdGsYhGbMrKWD11HnQajG9Fpy9og1D5ggmKDRbLhIz71d
AIRJSHYhpXSLIpm54wweNyyC6oho/8iFWZSlmKH38nbaz09pz9hw+95cmu63vMTP
81iI9C7extQ8t4rewijs42124DqNmNOM2dMxsDvpdm+5xnqZdqj9mqG6I8nbTDGy
zYgOtNusu9kGSSGaLtlhZKAgRE5BlmsVw4YuYJCOn3FTSHN2pBOOKpnCZd3CTNEd
vluGhEo68j4+DlCTa9t36OGkDNS5sWB6ZlQc1jDbyNnjJ80iNYIr3EzuLWfHvuth
p32vNEqrW06XIE0p/SVvj1778+ZiUXGI/jEexFn7YiVvg/sCLa5nWdwd7Ifu/Tc
tENMoUco29EzyNrR4cmOSXLjLcGdwWYmk+hdq63Bql664Gn2ZNCjxug02Dr1zNnc
Qw9dPxTsE6Sss2654Icamg3YPD0ebS3SjVrnCjrrRK5mQmG55H5e4XRw0/Ew0DV11
mQZM1luZkqmsqKxkRiPZs+1jiPeIeCan7WDOyozOJlt/qMJbDc+WgWwDLpXnTU2H
TZBV2+kusn4xWBP3melwn9rb6MZz1H6CDhJb4yayRuVaW6UPRHEK4Kg1eLxe7xvz
1XpfB9uFb+sce216bOuqHE5GOnnx6411sFKO6iVl1GeP9rDLNThzeIrCPbNL5pPJ
gaHGzssNf8JkPdMTCXcXf2Q4fKOxm+wf2C2ncvE49jI7t531MsV8zC8bed/TcZMX
RDkYQIa61vu4bVJZPhUompGMOHTNaNsCqvaLLiLJr8i5yVQn2iU1IA7lcDD1Tg39
tIDGKqYFHbs0fW0yVh3AdxAGkyAMU0FwvRJjSmTlyV5Y7X2R9VbsduUmRsi4UyVd
mbOGX6AA28y1yV05xr0EOKiko5nXm46YLCVWpsRuNDONy3FadIilxpdUd/i2h8Ue
yZNdY3S4t600reBMBX/tBWOfl1VREVdbOeBIsui7e2U37LqlGIXkSA6cURQOR+pI
2Hgrz55EzSwkOzyI7tgGpdREhAl1cZhaFHXMoLzTJfrpAdtqA7Gv9xKpXW75PruL
cmleCgYVCgZMYQ2dKZfLbLiOnaEiYWKWnibqWcDmMvwnd3n1GYyljarCF47vaK3
o5V21ANoy0K1Tm4bTiOl4dNtFJmTge6QNQemxJ7hrLJN12DlPpvSIBCed8y+G8i+
nJZ+jqPLftIpRs5OIITleD/0yUbuEAxrKJOiHe0JglQ7XZneLizTWzc6XM9HGhA
EFa1R115r2yVvsuPDy6/TVHgq/usI3ANrwcjbMhpcjN4S/QZmQ2X7RgWSW1YCrRa
iSawGWUUEkyd0sCIKTIsiylU8mYpTg+jRE39hs6MS0Y9Og6fh502XAxo483YwAc4
roIYfELy7XfhsEcrs0mgSKm15f5bMezp+FG29j9yaQhd1Cy3LjHilnOZWwexiWC
JLwCXLCwp5CTV6aTCb9Avt1juF72jxtR7IvSSXcFKYIWqtK2GpoOh44GxB8yb7Ja
Q2w0H6N2OMZhON6ZftxzBG2/YEGmVpMBV0ZWNy+07NSJMVFBYcdu2zs69HiwFus
9bGKL/ZDOBIgYBlWXXG2XqqaeflnA5KVJA1rGOMI1IcXkWqjePOnOkKDGmuJfW7
tmEegfWgO5DS1/Gj0B2SyyDseEcm3A2ncRsVR6ZuHCyXWX1LY+ET6/HSDrYeje8o
+0Q15K5bumocLU1B47ztIILm+TbMiynb3vu7La3Fa0YNNqO2GpoBvDWCbWp5Gvho
Ry65PYSic4007e1H1EYNRL72bcPs7nSN1xpPNO43gRazN31KKBD0yvQdlZMG8UO
nQa1PtS3KQvNRgBkc7/KdILPgM/WNY29gXRP0RS3ixhZirZLiiq3CEYBd7/hgwFE
dIMGuDX3EwLRkRqZ0YMR2YeFxbhHMTVQqMk6sBUi68dZGmlJszCq32vABah0G6
0+IRTvJjrDc99VFiuX005M4yJITtB+rYWEzdRTA+DbkxREtHmBF8ufBKE4PG2yPe
ns6m0CR329HMBc5Q3J/QjuzRciPaoMPLYveAGozjz8hLtEvKNsMRc1Rc9QvdtBvh
emwDIR0vhwxBxLbsjJv5J3PFhCS5ElbeVMB6Xbd7qDUiCBE2RB/ZEBLbntLHYX88
pyl32BsQv9odHiJDXdieyZ4auqBgNkMHYMoOaIls5yP5f4EG7Nj6shiKRvwEHh
vTQN/KvyjIjVRCXGQ0zk10s66kM28iGzLOUGIvLcJx8fk9puDc77IUDG2crYje8
wfUeuKwcxTYtk5nUPjb4qZmzAEQguvgK3hym2/S0XvTsbY6x/nTTU9CVGTiHeUfs
R8xmLJRtJmF0XrBrWClMOM0VS9uI7W2khF0VwxdkIGnYfKGGMwk3YHexL1bLhMHZ
0yyM3uzKaXJE2kLRWCsz13hJdYbMtt81jD0/30bSgp7Mu31FWhxipjs+9Y1M8/ab
tax1CCpt15vNSaOzbm+717150+sxZjKtbtG9Zu4D1U86EykwjrmMxCSG9kc9Rpr5
HKLZ1ARZHC1iNRrA+HbXgSkBOjozqMFPqJTRFqrxdjTjkmRjyaZSMpgEQiWfKrTl
dGhaUj7Yiz5JIDE6EeQmcyRe5DTc20f9eUM/bZ1TGEWLEdXrOCeKIfyTAOItfeHP
MvxAlgc16iozYLaD4Zw+keNdL7KF05oj4L6MZwuiKdXuklub0YjZghgpUyHs+yt+

QKzQNjPiMCDwKikBHsLkWoI8WOPgMBgZCyyMNgajLob4eNnwerZ9mxZKCuvlVorl
+dGT0aUxUYEXMogP8RGVcN7o7vHTadLrnBi10uOSqKqSNDs3/nHR0Cp03Nl0uNZP
2w2PfbTRrn46YybZ7kaMukmiAi2jd7Sj6gIF5ByVHKIZjfwTTrmItT5hiogzkxOM
lVlDi/dh+9BOqYrFrhe5+o3KlJ6aUIKP7di6RPhOgaJyMvELq8o1VXI9fHCPqhMKo
aZy7lYqFft9ezRj/MJblPCFm+2lwhJT+dGluxkrHlRh3w+8yRCV9gW/jjf0q2iEU
VuJB3/VXe3Ls8i658zG7nEmueZBnqDza6oKzGveKySkip/390ewszb3iS/iGkybr
xiqJ6ix7B2qGKXKR28d0XsoLIyOSaD46yamaTw4ZnQn3ydaacIc9C8/DfYRAui9v
NwxnslGD4gTOzohlSC8osU27zA4eqWtd3QvcIYfVaa+HRuzUORkyxmDHI+8BP3ha
Eu7o4O9XXFHSGLaKTPiEyGEPi60tavkIy88TotMloXoFZuhMqfy8QqUoFvy+qmqzN
YE9vtrnr05t4i5E9ozl3mS8gx42J7lfdZE9CMDUTAwXW9FLmGHRfNSe7HHbDo5hH
mzBzVi4icDanS0smj+1Rg05e2smHVyp3xBN0TgJ7sHu/x3d9wtfxdmfRx3A/jzTr
xDBsLu8W6yUEXJzuDZIL9KrUjgZEGhf7EusRToQXndLfch1005k0WZcPe2tGG3Xt
cJmD4UAw2qATPDhEJLlN9AxGpgGKq0oOBsmWEWNfjFvjxHGj8ZaOTWGGcncvGE+Y6
NlXrUj6k4tswVo39v16bYcNYh6I5Nk+Ajdvlq53KlAy5XBb35LlJ4fSdslyzh87I
q1Gy6LkUstMTRtEURbEbFHCyx3FJlF4lgZYeZEGfSMPxodrHSoxJBbfZvrpdoYdD
f9RnGHtmHhOPsX2FoJemFOPwC190pXxnJcmDOIRcd/7coW2e5rLjWlT2W4eQxyeb
FVVJnUTzzhGZmLi0dtqmBHxzeAh3GzFCGHAHQ8IwfnCYaLMzy7DMZDje0AZn5Tk
uOSH2U1UWKUR3R0td2lms7ulsqIpIV6p1LBhparSrTBSu5EVJiqNE6Nys+ikwFFA
lmBYwBYWCxa1sJGI9RI4YWUS7K1cZx9QuMrz48Z+X98i0GjRBfVkilizwDM8IMGK
B3Gh5XfQXbFTNSKAQ51QwmywZqcnrgwnw5myM0bb+NSI8gvLnPY6aT7L+gRwMjGb
NuDuqECNjtn19FmUyou578LwUCJNZbcJlUmHpIMZ4gSJ6SX75nrwaEpQqUcbulj6
K2HCR5Q8QQQECvVklkGpiWcnOUq1lubC/sAe05tc33Eh9iYHDctZScTqiE9ZE2sv
g3K3H02G3HBB8LNJOSEIogxhnVe0PheIUVvlJLkiCtyKKNu5Pw+bepxSMjj3LSI2
KE615mKQHFUE2/bLVRYPCPZiaFORjc6UVbCs2iWCgcTw7Q2vp5rp0UkNvynkXuC
XQ6JA1ZXDwZ22KzJA+Zv0hVSyIOVwKi+5SapYLhaKp6QfKqepEBvQ5tB3IE8Xrth
zUcat0T8vR7AbTtCndKAZtr79qxHt+F9AKEHV+wDRVAiuHaIE5gYdn03wcrOgNts
D5oFNXaZDtrRj7NatNa0KOBQUPQifd6OJSHcRTGruVupnBxtKVeOK+2/ibYdgaL
zQxvr7ATDlHdhg0+DsRZmu5FL6GOandAKyKUOXiH7cY8Mx53dsNidnKnuTLOPEQc
LTpZAGR+Z/TmbcsVebOhVSQio2YT2JdkIZBJIxZ7/eNx3k8iFm1JVNxjUhZDT+Tg
qBU9OoyXHXuGIrgzwKA5HbpqY0fsSt+2PT7Yaks+Q6Adj42YXTGbTaNUCNaOTy3W
861B7bbyCGNNP1DXy8ApvZNP05472y4aKxL+aqcniDu2FNLZbyNt2Bs17BJmaSHC
A1/MTjnvvgDDWzAa0MDdzYr5lQE/Blku4EMomE5DWopYPtSnRyH5HQIrxhWE44z
eH0yUnYZILY5owVu6WvhUpqdlEwrCS2zMQRoQ729ocONaOM0aEsoOwAxvNlu87zG
dnXesmJ4shB0Y072417onlbKeo+yVmArIdbNRHS/cEusOma7ZYML3KMCn0yDXRSd
HQuw0aBtb4rucsnidupW7GwJl7wfACCje1h5bsLJBt1QFAa7pU8cNDGjn27111g
JwUESFDIqFmG4SyMLg4nsZmpuDYRqRI5hDEGD7r2fG7PJubpVKxHc/CXO5y23Ubm
2TsgSCe2w3g/g3fafNo5HQdh2/TDjqWqVq/T6Yty3BvzZoBs4fYU0+aJdxqJVqBn
UtdJGrG5NRku1stJpXy4To5uKJ4KCy7K315EOVax4v58YQ7TDJgdBYPmDnNYZx64
WIEYGG3W2BUNTyydIytlp0sYSqADHuqpFLVbcTNKWysdmEZPg9gabUY4CuJDzRkm
69NA6c+nxTR0QrJH76cN2wLjBdoRuJ0AbzeWcIq6AUwbjC84+Pggd7fhQtDURIf9
PiLoZLRcSDtD4Hd2PvlDo8b+QIF7klKVzik5no426ZIEB64cV/XiO4RnmvmzHRbv
14ckUXqnkD2N4WCLUo4kKSPRWIM4zxv6KUegzv5kbKydCYcWOxh0T4VH6hvo0J56
q6n19mCSIP72t3OL/3v+ia3rW5oB8n5vffpf/Ij6hvy187+ht7eHZmhUj/7XeEfd
Sq0cCb4Zpu6CQOR7y8pD/XpctHqFedD6Af5oZvKnn40Eix/pqt9Ks6SVunbYsvxI
zVpu3LIuuzl/NoG4VutkJthfz9ASM8utsKVH8bh1Cf7UgFqB+t4y3cwXk1Zo2mrm
Fuall3kWBa3qLVVLqy/3Tz59+3QrAFh8uusgs763AtUzq29uaP+phcJ3Y/1ek6MW
5H7mxv6xUFuclQAWBz9iY53F+b2XRNzfMTBs88yP7W/Uc4AhKL3S8R8uNAVhgs7L7
YgsU10RIPUC4CkBDf7thaiYZZOTx/fAu5TGY4vsHt4fP5R8B/N3293XeZv7jypep
PHPHv7RgMB3wXz89zsrj68+AK95/+glpftTdfGegLwZovSh7xi1TXR9UBejVhQ8Y
PmNlBvqt5ZuhnTl/v+sFsLzq+xdIrX/9G4B/7elW/ecjWl+Ie/mo8akI/edPf/10
5hIrfhz6PXdfhK+pDCo+/laovmtU7BbEvhmYYdbSHTVJzaz16cvXf2voh4r9r1rg
klAfJc+idfAknloArm62oCgEcNGR/8RMgaS0AuBEVH/QuwGdHz7KW69/RyQNAPL+
3vp+Bv5IDqt1BnF2/Pul73vV8ePnIxOB+jV2Py4EvKD36cdjRTBKU9WdlNkhxsve
35mQC9Arsc70uAL686fWA5M89HzhuJoAYa5C22xpqu7dwf70s5KRxAyi4vnpa8AL
Sc7PXRiFoEo12e8R+QLAMVWjdU+3xDRy/SVZ/vzpywsJvUqUGxpPvHcl8adqZH/+
9G/goy55Bfvr+yS8H9a5g3e5554JHJGOK/6HKiF9d/bTKHhZXR0qnv9+rvE01koU
vre+/ErR1lr8buLfBO1106+viv/9ikqlH37Z5ytWrqaJbGIhv93vzw+5/EUnT7P6
W4x7sae3Kb60ajot5/m7b+emaW6+bPVU04h841LxTnseEtP6Xt+jUf2qb9IIs/R7
68//5/9WV2tUhdXEL1FipN9bDzdtVK9I2z37UzV+Xv1vQ80ad2a8ZxRqYlZ11Vo8
ArxrmGbc+vHFNb6Cv8AstKfVwzz8/Vz1ivHXnx9MzrXSB7IO+PkTsF5gNMCRFFN7
NdKtT/8bAg71+dHvyCyQELMN/mdS5c0W1SP7Uf39fj/c/0Q6Pj9+6+kyjvf0zp//
5V9aEFe7EK0vV1eiwu5r68//+q+/FNTqBWbtPBEvEbmne6MNM01rsz806UBGbFP3
51x9LHADG1jzCsCfHgZy9UBsDThasfPfySggz+8VZhd48oB/hcn52QNSj3j8NzOM
dIyB67ZZadtT/8DBh8Rcy+qqk4rmH1Rcu0bFGnVIU/dkQoeXtulSmTFd28katY8f
1R5GfPSIsQqAo3MwtVNgSY/qE+6WcqbYbAiQ1g5YdgHlSeA7EkC+VUwlyWv/I+3
quJMTb3WF7ViD7glfFDzURwBX7wzwP8cEX3iu0uTPySh1etXkqH+F9sW9f/n8SuP
0416/H/A5CNTjwxAV6QFfxCRP3F4rd3+S3n8hf68NppH7NDPq8tW5aG+xaphmMbV
JBVVvubOaBR1JuziLN6KmyHSLZ1yH9+GdZ4AfNzSAsXZRB1zLqs2384epqOmR+A
uWsB/Nzy1TSzEtM8Z4zqb3qe3KEHKn+/F7GGhxUBRopQoJbnRiBRgweOqm+qyZtb
W73eOvr+1vn3ViMt1pixWSX3Wrf7jURr2N/QR3G8BIAAXXCogJBYz8413fdD63P4
/Ab085uyAEAgpPU5fAw0XoF6CzyvFKvSLT8a43JBsxo89P06RAipip9h3Ujg/jbo
dT7iB9yy3o+Kmv7QmYQKX+TGt9VUP83BAPVWCneKx+d+/pUeeENLm6MGqla9Hu9

Tq9lTe6Eojnbl9SHm5nBBEQH7tL7SFavJhoVPDBhNQ5w9QKfdRkKvvyup/hbPX/K
ElDBTJ6A/o6lqC2FCPRz68sTbd/RZ5AQRrmYiZc+wJOye2CBWsmBMP88pQ8IN+1q
Nd7QLH03NJ9duc/mo0nWfa80BRnpRXmLsgr915PKnn3fCcRb0qt/HsmetcSH8m8V+
Woa4VTGillY1Yduo03fAW+7Y+A1Fv9PGm2hrdVvLR1J73/sf1XeJBU8fAOKe3AdXP
TQPMbh2CX8uqn98SM43yRG/WrdeHeN5KDNNScz/7FtehyItgvTLZoDqKIC0UHzQm
MbIsQPfvlXg3LWQSZWRmRuGdprwlCX7cz9y1+6pXLtQ8xECrH/wAAoQMWggO8Oh3
7uQWjDVUA4D1Z8b0CznZdfXh8XkQ3b+iJeW2Sp/VdAOWQ+A6tKo/zfSHeri0awyk
4kJL1bMIKHLkr8j9A6f2dL7XgB768Z2nYtMCVZNzC/ih+pw2jXIrN4HtrWgBdWob
alUZ9rr9rVKZqHfSjLXa5ZrFbn/7t6Z0hdG3qtLfK3Saba4YIFefSgPgAAGi7vI0
c62GD1ZxN2AjVQeGHeD41949GbTcauSHq1c1o/cleuXmVW3Bfw9jvzy6pxYweglg
oG/Hb7WNh+9hf7tSvlFejedbZe+/txr4ZVGLIr4DoTXTRY34gXLCpxd9qacC+Xr5
gr7QkecnnWuV7legtlvr1oulIVJ6ggcU4LWVZLS+VMP82hpLz22X90UvXbzq4ypq
1cs9FnVgPsK08o0fqZ/qqv9UWAv6clXPLJ8m70n6694uU1G7eZcM/nMKvrFSctbl
9ws1les+nf35Ya5c6zauDxYymhnZq3WtLBtQOrf2UPM72vqsB7/I9l0XKv3Bj1+b
Wz1KgXRdITA+v65+WZhttrmHUA0ODOGXicnzoGp++INjqtAZ5Kev6NXDH7dH2Cq
PzX3WbWEBOLBgjH08BNTIb/X+dUpjOrY+WaZfw+ZcyvozOkf9vPkAlY5efkrchat
1lbzY6F7rf8evZ8HLYtTda/hs+Spc40UMweYgp9vy4uX9d16fa5+cm6h5dmlgQr+
D4/fqnTDn362tOYvAOB7NaMcR/EEV8AGIfA2L8ueZ+A/AMTaaFx+Py0M1sXXVEzt
fxmRngCv9YpH7Uvdb8loutoXd+mRUMBeAQP9ypk+pl2Gaqb6kflaRiEZGGvgLLUg
5K/dd6os8qyyqmKlFt/ZBVHVOFpf6uG8k5R75ZA/D+spdh0YzhWbd/AYRjmQMfgf
7b3zqvcfED+iQp8Vg59TU8NfhpoXj7AyRoXqI/Vf9HsrA27m91YtMzcbBX5+MwP3
jSnqJY2HbToV74F69ywOWEnVqEGWghugmgCaXknjAMPocdE4G2F4dKokgjxX07
01A3jCtsvlXz0Cx85bxxG3d0p/YlyyppB9SBZybaOY8Tszh7icCprB228vJRBwVy
w8vGiJtHeW/TawwKMznWUfaVchW8JyN+AXzVzOcOGCI6Z4ZqHB7ms0a7Tqqckb5g
WwWFjQ1GVcP7dJVS5zF9r79HVfrjiTneqj7hfl088Z4GcQ4Q66E89Hl0sXjXxA6k
q0An1MhXlK5Rr1F9uY5eDdR7Ln+xFJ13fTXqXusVFR+E4t0OX4jnc0+/0cGLSQN/
wCT9N0xd/fj3pu4/PkPnUf13ztMdxGqn038h+R9J25yFNwm/1Yn8c/BX5xXg2o2q
7S8QF7Mfnv587QESgtSe//N8XXeIlfPy8axVu4pe83mNatT5/vbt9QRenqJv9VAQ
VHsfE/pcEXlRuhEXEvnnvvnael0XjbrnlXyyxmQJudbklfh2I/zRNxqvfxlberq
KgApTf/a+verIm8+/Onv3+qnjagXrT8PeCr6n8Nu9m6ygdcmT4P6Ee9DagJvQUc
vdsGAIJ1jbeCB1PhcXbX+vnPj4oFLhjW5Pta93AprOI/YPGHKpPR+lvrs5p+cWHP
3Wr/vFuoeXxTnUT5fst3m0LTmuhap/7+oo6mXx3YJ4j194p3Gt1q6V31K8DGj4cG
Se0fBGpiu+Frt/5KgZpj9C//evlxyzL9Sv3U9WvH4mrBb+C+PUMDQZVkvFg+eKz4
/YbVr5y561WneN/cnrPq8EFcZqWv9Md50i8JvPOixzNGl71PdUTx7T69/NB5Pdkg
2Kk564z2W7rvoa+/tN6en/OEz9FsvFeFbUS9FGRG8j5il+unHOAFgAMLdnL6G+MJ0
3ayVNPkscR921IQPeN15QOM12M/SXx60W+lmIJS+CeQLRC+5xvdSIEluf13jSSbP
UvbtUUNfXxfnoCG+rx99zS5vo7WagH9R+X3yfJzrab7qNlX698pczfxc7rD/bNU
/hogcpXb00B/aXQENYf4WdI/hvnB+vg7j17a7Ovr/yGB/8vH/Vz8oqh06r+HONB4
DdVZ+XVX7F/X/5g4ANofUeLV61mRAYC/NS7drLZf/PGBGw15Z9/v/6DB1Uj/Q2rr
BbCLn/KfA02DbUg3gr2ZrOfw9m0SLnPztgD15AQ8LEW9NX65jla9ziH1B33/TjRS
vX4dkVsvOw+tasbGXD0itwbX53zGdXa7WU7WLV3/7M0fTSadXuM7mKgq8fxocd2
8REaTsffWMMvlefvew2/Z64/QB9MRWU6XmP/FoheDcplARaIMQLD8HtzV0VLzV+/
1/5iv29Eui5wXmLh04j/8reGUmlo+r+9Q9Lq2MytPVP5Wu8aoxcuVqNt9x7Q+ZzO
i81dL3RBY0NVdbXod9+BrmOdRskLV+eZ+d+iWZD8LMrarwD5tm7eg2kfvZxbFGL
1WUKL8mJv58zKADMO4R+kYOrKfeLibnR7pzeOnfyuklYCCr7/bwT2jR0ZM1e32oG
/HbHgL+R+HkLcd7NVTxlB94Gar2g4SX5ehvRuxz22xR6msCPyPU+bd6pezMX99L/
C57+bbZ9jzVf6PjKte35hd151fX123QX3jmF6jvSfDdnJjNxcGLiwdXrI+ckaJm8
OEL5dmbwvEpgHtznI3OxD9Coz37VlS77r16c3nuYK/DtIRD+aPbqrMMLe1Yn8+oc
1s+WbVYK9Pqv8TzAVNt73slqXHfxVMr5LkHx1vABlZdi19xElYfVityt5B2wvxCK
165DFn1LTauUlociP8QTWORXwno/6ioN+RGZXRAP5as1/kK6LY15y3fcP71gpgP
Db43qv8jNHuto3XUaMAFqu6hAH0s6LQ+Jy+WYT/216/uRZWPbiw/3yMKXD/gQtSa
8+7BS0476+PbjuF7UN8eAp1fLg78hzzUh5+XhULzoPu5YV423bgZKPzTJcsM9MpV
Pm4Lg+dUwJVZ/Lbx7Hlv69ui4rWHuLPXF/j/Wajwm6r2drTlcaX0+qpzyq857j+c
ax4N9suzGX1/OL8+cFpToz6e+5aWvyBd/a6WBK5K/cstDnnE7d0FdaAVL3smz0an
1ltPwVVeIhw404v3Wuf762bDrquer8FP2/bRYJqX8FzHw/bAp/LgC96bvVQ8G7X
4JvxapS+gPU+iNa/NoLj7t1YzNCIn+OkK7dc910+LVnWXqD6yOWNqLbu/rbH8b5a
JYmh0Yjt3naqWk0v15XJ+/bVHsOfRcW/vXG0J+PQ6wrgeC7kp7Pvd8/PseA0z5X
xTbQDM5PwG2AE1c+qlyXmwJpDP5zVdr6chfJVX1/PQvmZ6B4Kj1Rbel40lny5U4B
3ba+VpVUzA2WmaLwc/ZOF0cz/Xo3qluOJb0OrATG4A7Zov3x+VzrhtflUphLF+d9
vjUuDVTOk5fNL1sDm60/dlA7kLye8ewhvLjumW36umMI9C7dtjo+O33JSf37xeN
9fPxoHw1a688v3prcNXb7WFDN9WK8cnnu9Kz+eDfLxNb0/ZzpaKAobqmpGuqn5dR
3qPR/V7kOzJXlVPLH8xf3fNaraSM+rT759rHfEOi6vZP15/oDaerfjzXqp41Wd43
VaOCVavfJiNd1Mh7LNTYW/7ISB9T53FX+uPi1Ifmddk93csztKuAVayKZ+rZeZPw
9D0cGqCanZ0/jEQtL7ubfjwL9oPGvSmjYzPUuvhor8zvPQueN4LdXW+B1MeGnlze
hqt3lqgXtM4zAqsgvQqVr9tHL8HUIXsXXD2Q92P/px6rP3/EmQW28wnjy+MrhwJ/
uXHyDzQw3MI1ziv29VLA+GcL7fUaXHJx728z1+XAn7tO/OVpUw0X150fP85CD5y5
6rCG//PKwa9Z6GLy6gdPtU3q8r7dRFVXqzL8107fjOmzHX7FOu8sQTbU3ufnResn
tAA+kg68Nq181Vh4nuQm+KcDF89bmp6B3Nvky3ma510Zr25uuaq5e738ueEnXnr7
el/jPjv3ZVdn4L70qlKeSyuVeF/6phKeKz+FkP9+50m87vPBQfpZoxGdE2CKe31k
W4e02hz/we01Wp5VJ01aCXARjWprVbrP1QRQURG6AeDV7js4pZ1FZXRQ1508zc7n
OinyQgyuW1RrQQTsXf5sGgEdODQN619hWNv6CsPqyxndJ9t+A3pJvNyP/iJJzaCz
2ekuanouPz7XY7rth78P9jr7plez70AC1pb+DWDZnd0MtT0aXvE5zsq90fdWv74

```

WSORGj+/PvHTuTM3zKLLzqbr/X8vPIEHTOqH90DvJbbm7StHnNVjXfSz9aRdb6Cr
FMFZ9rTevqK3r503HZjqb3u73vppAvos0G91rV/VTey3ui91TB211hh3b/R4jwku
6F9QP6N9/ugCVjKf2eBSUukjQKZr77WRuhOsasrOI/L5Q/axxdkV+0W79FVD07Cf
G55LL83Bb+sek04muv9C7G8E6/yaYM9W/0LC9h31ALe9SLG/rFottcF/7fXQa/mL
1fbXFd/m7Qrw3R4f6gGd9Vz12xn2X651/nAn3/6xYT02RF9i91j1HWxfdkPKrcX37
TeJ9+4h4/9E+2n98XO/xnQ4Cmncd0Xsprs7rfMuiKiiqj+7UMUUNWT88rSW0/un
QCpjNXOu4vQZ/H6ten5f2VzVWhPu2WNqdlab3FqUmxJd6Q1Hjc171fFWcifw1UAu
Q2+g/K71uKH8Ofj59aUPV0G8kOsPQvQfDd0/jNiD/6iZJ7fabP4Gpv9Hp6T+6J0/
+oDm73Xx+Q7bPz7zxbuArSQK/kOgj0+gdb9KxTXtqFORV3A+IfTMQi9SLJ8vXn8N
/BLwv3tc6XwS6u680rX5j8c0c+2OvKTC5aLOt9TKxVG5JV2uSuW9fMvT3hQwlc3g
5YF4wNH3j68uc6xOI1YDfH7ycNjrverd3iFOFG7ujzTk+/fGA7tdX03Ceiss54Wqp
5KUgVf01D1zlf5XUAa75ep/DC160gXA9hv9e8OmlbHzt5D4XL0e5321cnb99v7F3P
1z20/XmeyDvurZt8r4503qbKUTZqLd/07N5bj/ldIvk5eJRKv/VZfGTyn69VwB02
t26x9xy16vWRs1a9HtH7oNY7urD+GJw/sNriis9AHpnlcYBAXBue7Zsvf6ebxCf9
dY6X6tbpL5uTz+rvbDibLZtG9Lf6vsBIfwFIMwZp1kTePQY1t97s+8dIWK7vt74U
9Xnsz9ZFBVj6LQYozPBbZBi3On/5+vPMYo/3U1V9WCKs109Aizc45Pvq5o9EIy9x
JP/ywOQ/QPbJrrnx1UN7A7u+Ltw8dbiuiPJxF9U1V4+91Fde/k8yAPWI1ewfVfJ1
83q7x2+p6HcZ4GwIjH/UTPyjar6RADpfRLqxmevXn/UayVP6pya7VT+8Jterv9/r
ztT/Vt1f7aqa6H19P1KNdxs8b8as9/PUONYpJsCCdQLr0ySwP73ddvVQ6UVG/8ah
91t5zvw6il4g82z23tXL985fdZr/2fH7cndDQY3qM7dW5YBZX1ras0DWNV45kTUz
PrHRC4Kr5ox6A6f+agq8bvNQNZ17MZadikz/rS6OeuAy0vuzb/02crhv3P8SquTHk
zkt5mIAKNS8XZt1uFbu/crCqcr776xIpXnSafR8IXuPd6g6Kyz6z+gybe3/RwPdW
4xqI8wb5+7u8bk+va0v1cmNjt9oHl9bdg3pnU1oNz61SoMIHG8ffrsa4vxj1mfur
ax2+uF9/44JSKgp/63b8qvY7G3friqSamhWs1pfngX109eg41COjP1K1dkMiTN1r
wTuY/8Ztno8E/A4Ie3dYuHk5xB2j1Ero1RVuDRV1K6zZ61p451t3xZ13D0Cfeem8
n6eu9vNOGX7AVA9A3+GqM+D/NK66uAGAr77UFK0+q6KpfPo3+qO/Qf8gQO03XU5B
8PO2hyaotJz8GaDVqaTeX7tfmlMQ383A25UErpG2AtNw1dpprq9obcWucTddVaVX
15DG1Ya5L1U+7mqkLpe8tJv3cF4nsNbq8a+mrEboOk8vJ+WK7ffg+ip8JkoN/nyT
L/JUgJ4elr/ca/88rkecLmR5I/OXM2jka7357fbrS6PLs6qHXpeiX1tPtzs9XOdU
V//dO50uCP7+nuU7/xeqS//iOZl6tdq61vsS/vqV7Vk02WSV+v1zn/b3NinV94Xx/
WH3b0Jvp/vhS5wuJr8L6MT7Cmy4Bw32/3nmYSaSLwA/ofAyzen25rPzfNnY8GEPg
LP14Y77aFtXE/nJfrf63BF5uw/ygp0cNed/V5V7uc28PVX/d3Usr9O6Dn4+XLlWv
C2NF5+YdzvtzyrvbH/8WTD3XuHxWRD8TjQTTeu6GKrXTfjy+VCnyPyS+3WH25V7gv
evzgitvmIG8m/7Z3pvXZV49RnjVurL21uLu791Z8MSexfRnbCwsf34/8XHhzDl8+
OZv4J0iX6Hwdc9T9PDATr837F/TG2k4vLf6zYvYqsb3p/Pf7vG9x6BJujgxASH0
t4T1I/3Ouyhe/Ot8Lwj7tKn4vaT4/Vsf9xFebtV6MDJ14vuMw3sXtf58IOsZs9eJ
7+qSuy+vToF+rRc4EQzBrqelHzcwN8NN0CX4//8Dw8SJGQWraAAA=
}

make-overlay

```

Several articles about pdf-maker are available at rebolfrance.info: [first translated by Google](#), [second translated by Google](#).

9.17 Creating .swf Files with REBOL/Flash

Flash is a ubiquitous multimedia format used to deliver graphics, sound, video, games, and entire web sites on the Internet. Flash is already installed on over 90% of all computers connected to the Internet. It is available as a small free plugin for every major web browser, at <http://get.adobe.com/flashplayer>. There are a variety of other flash players available which can display Flash formatted ".swf" files on mobile devices, on desktop operating systems, and on the web. Flash's ubiquity, power, and comprehensive multimedia features makes it a popular platform for rich media development, especially online.

Flash was originally created by the Macromedia company, and is now owned by Adobe. Adobe's Flash CS4 development package is an expensive and heavy development environment with a significant learning curve, and it requires proficiency in the "Actionscript" language. There are many other commercial and open source offerings that can be used to create flash .swf files, but many of those are oriented to creating simple animations with moving text effects, graphic sweeps, pans, fades, etc.

CS4 is a fantastically powerful tool (the industry standard), but for many Flash development needs, you'll be happy to learn that you don't need to venture outside the REBOL world. REBOLers have their own Flash creation tool available, which is freely downloadable and which *does not require any additional languages or development tools* to create rich multimedia .swf files. Just do the REBOL/flash script at http://box.lebeda.ws/~hmm/rswf/rswf_latest.r, and you've got a powerful Flash development system at your fingertips.

Using REBOL/flash is simple. The following 3 lines demonstrate the basic process of installing the dialect (DOing the REBOL/flash script file), compiling a downloaded REBOL/flash *source code* file, and then viewing the *compiled* .swf file in your browser:

```
do http://box.lebeda.ws/~hmm/rswf/rswf_latest.r ; install REBOL/flash
make-swf/save/html http://tinyurl.com/yhex2cf ; compile the source
browse %starfield1.html ; view the created .swf
```

To begin working with REBOL/flash in earnest, you'll want to save a copy of the REBOL/flash dialect to your hard drive:

```
write %rswf.r read http://box.lebeda.ws/~hmm/rswf/rswf_latest.r
```

The file above is a native REBOL program, created by David 'Oldes' Oliva, which takes input in the REBOL/flash dialect (a REBOL mini-language created by Oldes), and which directly outputs Flash .swf files. No other tools (besides the REBOL interpreter) are required to build very powerful Flash applications that you can use on your web site, in desktop presentations, etc.

Here are a few demo examples to download:

```
examples: [
  http://box.lebeda.ws/~hmm/rswf/examples/swf5/swf5-eyeball.rswf
  http://box.lebeda.ws/~hmm/rswf/examples/swf5/swf5-snow.rswf
  http://box.lebeda.ws/~hmm/rswf/examples/swf5/swf5-starfield2.rswf
]
foreach file examples [write (to-file last split-path file) (read file)]
```

Those are just several of the **175 code examples** at <http://box.lebeda.ws/~hmm/rswf/>. That large collection of code examples represents the full existing documentation for the REBOL/flash dialect. Reading and experimenting with them will help you become familiar with the REBOL/flash API, and will demonstrate how to use the essential building blocks required to accomplish many necessary REBOL/flash development tasks. Note that Oldes' previous REBOL/flash web site is still available at <http://oldes.multimedia.cz/swf/>. That site has a downloadable zip file of all the code examples and some additional older tools such as a swf-to-exe compiler (that site is no longer updated).

After downloading/doing the script at http://box.lebeda.ws/~hmm/rswf/rswf_latest.r, you can compile REBOL/flash source code files into working .swf files using the "make-swf" function. The /save and /html refinements of that function are most typically used, as they generate the HTML needed to insert the Flash object in your own web pages. The make-swf/save/html function creates a fully functional .swf Flash file and the necessary container HTML file in the same folder as rswf.r. Here's a simple script I use to compile REBOL/flash source files, and then view the compiled results in the browser:

```
REBOL [title: "Compile and View Flash Files"]

my-rswf-folder: %./
; my-rswf-folder: %/C/12-2-09/My_Docs/WORK/rswf/ ; choose your own
change-dir my-rswf-folder
do %rswf.r ; assuming you've already saved it to your hard drive
make-swf/save/html to-file request-file/filter "*.rswf"
browse to-file request-file/filter "*.html"
```

Go ahead and try it now - use the above script to compile the source files downloaded earlier. The compile-run process is unbelievably simple! This next script is a build tool that helps to automate the process of creating, editing, and compiling REBOL/flash source files, viewing the results, and then re-doing the entire process repeatedly to debug and complete projects quickly:

```
REBOL [title: "REBOL/flash Build Tool"]

; The following folder should be set to where you keep your REBOL/flash
; project files:

my-rswf-folder: %./
; my-rswf-folder: %/C/12-2-09/My_Docs/WORK/rswf/
change-dir my-rswf-folder
```



```

do %rswf.r
current-source: to-file request-file/filter/file "*.rswf" %test.rswf
unset 'output-html

do edit-compile-run: [
  editor current-source
  if error? err: try [make-swf/save/html current-source] [
    err: disarm :err
    alert reform [
      "The following compile error occurred: "
      err/id err/where err/arg1
    ]
    either true = request "Edit/Compile/Run Again?" [
      do edit-compile-run quit
    ] [
      quit
    ]
  ]
  unless value? 'output-html [
    output-html: to-file request-file/filter "*.html"
  ]
  browse output-html
  if true = request "Edit/Compile/Run Again?" [do edit-compile-run]
]

```

Reading and adjusting the 175 online code examples is an essential part of learning to write your own REBOL/flash scripts. Try this example, derived from <http://box.lebeda.ws/~hmm/rswf/examples/swf5/swf5-soundstream.rswf>:

```

write %mp3.rswf {
  REBOL [
    type: 'swf5
    file: %mp3.swf
    background: 200.200.200
    rate: 12
    size: 1x1
  ]
  mp3Stream http://re-bol.com/example.mp3
  finish stream
  end
}

```

Notice that I've adjusted the original file name, changed the .mp3 file to a URL link, changed the graphic size and background color, and trimmed off some of the header. I compiled this script with make-swf/save/html, added some text to the generated HTML file, and uploaded both files to <http://re-bol.com/examples/mp3.html>, all with the script below:

```

REBOL [title: "Generate from source and upload SWF and HTML to web site"]

; You can edit these file names and FTP info for your own use:

source-file: %mp3.rswf
output-html: %mp3.html
output-swf: %mp3.swf
inserted-html: {<center><h1>MP3 Example!</h1></center>}
insert-at: {<BODY bgcolor="#C8C8C8">}
my-ftp-info: ftp://username:password@site.com/public_html/folder/
destination-url: http://re-bol.com/examples/mp3.html
do http://box.lebeda.ws/~hmm/rswf/rswf_latest.r ; do %rswf.r
make-swf/save/html source-file
content: read output-html
insert (skip find content insert-at length? insert-at) inserted-html
write output-html content
write (join my-ftp-info form output-html) (read output-html)
write/binary (join my-ftp-info output-swf) (read/binary output-swf)

```



```
browse destination-url
```

That's a fully REBOL-based Flash development and deployment system in just a few lines of code, and it requires only a few hundred kilobytes of simple to use, stand-alone development tools. Incredible! Think for a moment about the possibility of automatically creating and deploying custom .swf files right on your web server, in real time, using scripts as simple as this...

Now take a look at <http://box.lebeda.ws/~hmm/rswf/example/swf5-3dtext>. Notice that the source code for this example (<http://box.lebeda.ws/~hmm/rswf/examples/swf5/swf5-3dtext.rswf>) imports some assets from a separate included file, stored on the web server (at %includes/fnt_euromode_b.swf). Files such as images and other binary resources are often included in REBOL/flash code, so they can be compiled into the final .swf file. If you want to compile this source code on your local machine, you must download the included files, as well as the source code (TRY THIS EXAMPLE!):

```
; Notice the folder which contains the included resource. By
; saving downloaded resources to the same folder structure, you
; don't need to alter the original code at all:

make-dir %./includes/
web-resource: http://box.lebeda.ws/~hmm/rswf/includes/fnt_euromode_b.swf
local-resource: %./includes/fnt_euromode_b.swf
write/binary local-resource read/binary web-resource

source: http://box.lebeda.ws/~hmm/rswf/examples/swf5/swf5-3dtext.rswf
do %rswf.r
make-swf/save/html source

; Notice the output file name in the header of the source code file:

browse %3dtext.html
```

The code example above is complex, but you should notice that much of it is in standard REBOL format (colons are used to create variables, code is contained in square bracketed blocks, functions and structures such as the "for" loop are formatted in standard REBOL syntax, etc.). You'll see many words and phrases in this example that are used in other examples: ImportAssets, EditText, sprite, place, at, "show 2 frames", doAction, "goto 1 and play", showFrame, end, etc. To understand how to use the dialect, start with simpler examples and look for the common words, study their syntax, and experiment with adjusting their parameters. Below are a few examples which demonstrate the basics of using text, images, graphics, sounds, and animation techniques in REBOL/flash. First, a rectangle:

```
REBOL [
  type: 'swf
  file: %shape.swf
  background: 230.230.230
  rate: 40
  size: 320x240
]
a-rectangle: Shape [
  Bounds 0x0 110x50
  fill-style [color 255.0.0]
  box 0x0 110x50
]
place [a-rectangle] at 105x100
showFrame
end
```

Here's some text:

```
REBOL [
  type: 'swf
  file: %text.swf
  background: 255.255.255
  rate: 40
  size: 320x240
```

```

]
fnt_Arial: defineFont2 [name "Arial"]
some-text: EditText 'the-text 110x18 [
    Color 0.0.0
    ReadOnly
    NoSelect
    Font [fnt_Arial 12]
    Layout [align: 'center]
]
place [some-text] at 105x100
doAction [the-text: "Hello world!"]
showFrame
end

```

Try altering all the above examples (copy/paste and edit them directly with the "REBOL/flash Build Tool" provided earlier). They should provide enough basic understanding to begin reading through the API examples at <http://box.lebeda.ws/~hmm/rswf/>.

To see just how powerful REBOL/flash is, take a look at <http://machinarium.net/>. Machinarium is an absolutely beautifully designed, commercially successful game (see the reviews), created using REBOL/flash. A number of complete, complex Flash web sites have also been created with REBOL/flash. See the links at <http://oldes.multimedia.cz/swf> and <http://miss3.cz/> for a few examples.

9.18 Rebcode

REBOL provides speedy performance for most common scripting tasks. For situations where higher performance computations are required (for image processing, large looping mathematical evaluations, etc.), REBOL's "rebcode" VM acts as a sort of native cross-platform assembly language which can dramatically improve the processing speed of CPU intensive tasks that benefit from low level optimization. Rebcode uses a syntax similar to typical REBOL block/function code, and allows you to access variables used outside the Rebcode context, but it is not intended for beginner programmers. Rebcode is structured similarly to assembly language, with some additional benefits such as the ability to use built-in math functions, loops and conditional evaluations, embedded documentation, and the ability to run identically on all processors. Low level Rebcode typically improves performance speed by 10x-30x. Using Rebcode is beyond the scope of this tutorial. For more information, see <http://www.rebol.com/docs/rebcode.html> and <http://www.rebol.net/rebcode/>, and search the mailing list at rebol.org. Be sure to see the the examples at <http://www.rebol.net/rebcode/docs/rebcode-demos.html>:

To use rebcode, you must use a version of REBOL downloaded from <http://www.rebol.net/builds/>, in the section marked "Download Directories" (others don't contain the rebcode VM). Get the most recently dated version available (for Windows, at least rebview1361031.exe). Once you've downloaded a rebcode enabled interpreter, try this example:

```
do http://www.rebol.net/rebcode/demos/dot-flowers.r
```

9.19 Useful REBOL Tools

Here are some web links containing free code modules and various programs that can help you accomplish useful programmatic tasks in REBOL:

<http://www.hmkdesign.dk/rebol/list-view/list-view.r> - a powerful listview widget to display and manipulate formatted data in GUI applications. Perhaps the single most useful addition to REBOL's built in "VID" GUI language.

<http://www.dobeash.com/rebdb.html> - a database module written entirely in native REBOL code that lets you easily store and organize data. This is the same web site where you'll find the REBOL sqlite module and RebGUI (covered earlier): <http://www.dobeash.com/rebgui.html>

<http://www.rebol.org/cgi-bin/cgiwrap/rebol/view-script.r?script=rebzip.r> - a module to compress/decompress zip formatted files.

<http://www.colellachiara.com/soft/Misc/pdf-maker.r> - a dialect to create pdf files directly in REBOL (covered earlier).

<http://softinnov.org/rebol/mysql.shtml> - a module to directly manipulate mysql databases within REBOL

(covered earlier). A module for postgres databases is also freely available at the same site.

<http://www.rebol.org/cgi-bin/cgiwrap/rebol/view-script.r?script=menu-system.r> - a dialect to create all types of useful GUI menus in REBOL (covered earlier).

<http://softinnov.org/rebol/uniserve.shtml> - a framework to help build client-server network applications.

<http://softinnov.org/cheyenne.shtml> - a full featured web server written entirely in native REBOL. It enables inline, PHP-like server scripting.

<http://www.rebol.net/demos/BF02D682713522AA/i-rebol.r>
<http://www.rebol.net/demos/BF02D682713522AA/objective.r> and
<http://www.rebol.net/demos/BF02D682713522AA/histogram.r> - these examples contain a 3D engine module written entirely in native REBOL draw dialect. The module lets you easily add and manipulate 3D graphics objects in your REBOL apps (covered earlier).

<http://web.archive.org/web/20030411094732/www3.sympatico.ca/gavin.mckenzie/> - a REBOL XML parser library.

<http://earl.strain.at/space/rebXR> - a full client/server XML-RPC implementation for REBOL (contains the parser library above). Tutorials (translated from French by Google) are available [here](#) and [here](#).

<http://box.lebeda.ws/~hmm/rswf/> - a dialect to create flash (SWF) files directly from REBOL scripts (covered earlier).

[libwmp3.dll](#) - the easiest way to control full featured mp3 playback in REBOL. <http://www.rebol.org/view-script.r?script=mp3-player-libwmp.r> demonstrates how to use it in REBOL.

<http://www.rebolforces.com/articles/tui-dialect/> - a dialect to position characters on the screen in command line versions of REBOL.

<http://www.rebol.net/docs/makedoc.html> - converts text files into nicely formatted HTML files. *This tutorial page is written and maintained entirely with makedoc* (you can see the makedoc source at <http://rebol.com/rebol.txt>).

<http://www.rebol.org/cgi-bin/cgiwrap/rebol/view-script.r?script=layout-1.8.r> - a simple visual layout designer for REBOL GUI code. Not stable enough for commercial use, but helpful for quickly laying out simple GUI designs.

<http://www.crimsoneditor.com/> - a source code editor for Windows, with color highlighting especially for REBOL syntax. Quick start instructions are available at <http://www.rebol.net/article/0187.html>.

<http://www.rebol.org/> - the official REBOL library - full of many additional modules and useful code fragments. The first place to look when searching for REBOL source code.

9.20 6 REBOL Flavors

This tutorial covers a version of the REBOL language interpreter called REBOL/View. REBOL/View is actually only one of several available REBOL releases. Here's a quick description of the different versions:

1. View - free to download and use, it includes language constructs used to create and manipulate graphic elements. View comes with the built-in dialect called "VID", which is a shorthand mini-language used to display common GUI widgets. View and VID dialect concepts have been integrated throughout this document. The "layout" word in a typical "view layout" GUI design actually signifies the use of VID dialect code in the enclosed block. The VID dialect is used internally by the REBOL interpreter to parse and convert simple VID code to lower level View commands, which are composed from scratch by the rudimentary display engine in REBOL. VID makes GUI creation simple, without the need to deal with graphics at a rudimentary level. But for fine control of all graphic operations, the full View language is exposed in REBOL/View, and can be mixed with VID code. View also has a built-in "draw" dialect that's used to compose and alter images on screen. Aside from graphic effects, View has built in sound, and access to the "call" function for executing command line applications. As of version 2.76, REBOL/View contains many capabilities that were previously only available in commercial versions (dll, database, encryption, SSL, and more - see below). The newest official releases of View can be download from <http://rebol.com/view-platforms.html>. The newest test versions are at <http://www.rebol.net/builds/>. Older versions are at <http://rebol.com/platforms-view.html>.
2. Core - a text-only version of the language that provides basic functionality. It's smaller than View (about 1/3 to 1/2 the file size), without the GUI extensions, but still fully network enabled and able to run all non-graphic REBOL code constructs. It's intended for console and server applications, such

as CGI scripting, in which the GUI facilities are not needed. Core is also free and can be downloaded from <http://rebol.com/platforms.html>. Newest versions are at <http://www.rebol.net/builds/>. Older versions are at <http://rebol.com/platforms-core.html>.

3. View/Pro - created for professional developers, it adds encryption features, DLL access and more. Pro licenses are not free. See <http://www.rebol.com/purchase.html>. NOTE: STARTING IN VERSION 2.76, THESE FEATURES ARE AVAILABLE IN THE FREELY DOWNLOADABLE VERSIONS OF REBOL!
4. SDK - also intended for professionals, it adds the ability create stand-alone executables from REBOL scripts, as well as Windows registry access and more to View/Pro. SDK licenses are not free.
5. Command - another commercial solution, it adds native access to common database systems, SSL, FastCGI and other features to View/Pro. NOTE: STARTING IN VERSION 2.76, THESE FEATURES ARE AVAILABLE IN THE FREELY DOWNLOADABLE VERSIONS OF REBOL!
6. Command/SDK - combines features of SDK and Command.

Some of the functionalities provided by SDK and Command versions of REBOL have been enabled by modules, patches, and applications created by the REBOL user community. For example, mysql and postgres database access, dll access, and stand-alone executable packaging can be managed by free third party creations (search rebol.org for options). Because those solutions don't conform to official REBOL standards, and because no support for them is offered by REBOL Technologies, commercial solutions by RT are recommended for critical work.

9.21 Bindology, Dialects, Metaprogramming and Other Advanced Topics

On the surface, REBOL presents itself as a simple, practical, and useful tool. Many developers tend to dismiss it because of its simple appearance, small file size, and atypical language syntax. Those who stick with REBOL, however, eventually discover that it has some truly deep and powerful language features, not immediately apparent. Several great articles have been written which cover those topics well. Be sure to read <http://blog.revolucent.net/search/label/REBOL>. The bindology article at <http://www.rebol.net/wiki/Bindology>, and other pages at <http://www.fm.vslib.cz/~ladislav/rebol/> provide more understanding. Be sure to also see all the additional links in the last section of this tutorial. If your interests run deeper than simple scripting and user application development, REBOL offers unique food for thought.

9.21.1 Metaprogramming

Metaprogramming has been defined as "the writing of computer programs that write or manipulate other programs (or themselves) as their data, or that do part of the work at compile time that would otherwise be done at runtime. In many cases, this allows programmers to get more done in the same amount of time as they would take to write all the code manually, or it gives programs greater flexibility to efficiently handle new situations without recompilation".

Many REBOLers tend to use metaprogramming techniques intuitively as a result of the design of the language. A primary concept in REBOL is that data is code, and code is data. You can easily create blocks and strings that can be executed simply with the "do" function:

```
REBOL []

function: ask "'print' or 'editor': "
text: ask "Enter some text: "
do compose [(to-word function) (text)]
halt
```

The task above could also be completed by "DO"ing a concatenated string:

```
do rejoin [function { " } text { "}]
```

Understanding "reduce", "compose", and related functions are key to the above concept, along with understanding how to build and manipulate strings and blocks which can be executed (series functions really are the *bedrock* of the language). Search this tutorial for examples that contain "compose", "reduce", and "rejoin" functions, and you'll see many simple but useful "do compose [some (generated) code]" and "do rejoin [{some } generated { } code]" examples. Also, look at the "Voice Alarms" and "VOIP" scripts, as well as the final webcam program in the "multitasking" section. Those examples run separate .r scripts using the "launch" function, which have been created dynamically by a main script. Similarly, it's common to use the "browse" function to view dynamically created HTML, as in the "Guitar Chord Diagram Maker", "Point of Sale System", "Guitar Chords", and other examples in this text. This technique is often used to

create printable documents in REBOL.

Another common technique is to write code which is capable of building dynamically changeable GUI layout blocks. Here's a simple example:

```
view center-face layout [
  text "Select a button width, in pixels:"
  d: drop-down data [250 400 550]
  text "Enter any number of button labels (text separated by spaces):"
  f: field 475
  btn "Generate GUI" [
    created-buttons: copy compose [
      style new-btn btn (to-integer d/text) [
        alert join "This button's label is: " face/text
      ]
    ]
    foreach item to-block f/text [
      append created-buttons compose [
        new-btn (form item)
      ]
    ]
    view/new center-face layout created-buttons
  ]
]
```

The entire VID "layout" function is actually a metaprogramming tool. To use VID, you compose blocks, which are evaluated by the layout function, and the *generated* native REBOL/view code is then run by REBOL's lower level compositing engine. RebGUI works the same way. In this manner, many REBOL dialects are metaprogramming tools. Dialects ("DSL"s) tend to rely heavily on the use of the "parse" function to (re)organize the meaning of input given in a specified syntax. There's a short introductory article which might be helpful in relation to this topic at http://computer-programming-languages.suite101.com/article.cfm/how_to_create_a_rebol_dialect. REBOL/flash and pdf-maker.r are powerful examples of REBOL metaprogramming tools that are productive outside the realm of REBOL coding. Both those tools use dialects as input, and they actually output interpreted formats (REBOL/flash creates SWF files, and pdf-maker creates PDF files). That could be considered "multi-level" metaprogramming. If you want to know more about metaprogramming with dialects, study parse, contexts, and bind, and examine the various dialect tools created by the REBOL community. To get an idea of just how powerful this concept can be, take a look at the beautifully designed game "Machinarium", which was created using the REBOL/flash dialect.

10. REAL WORLD CASE STUDIES - Learning To Think In Code

At this point, you've seen most essential bits of REBOL language syntax, but you're probably still saying to yourself "that's great ... but, how do I write a complete program that does _____". To materialize any working software from an imagined design, it's obviously essential to know which language constructs are available to build pieces of a program, but "thinking in code" is just as much about organizing those bits into larger structures, knowing where to begin, and being able to break down the process into a manageable, repeatable routine. This section is intended to provide some general understanding about how to convert human design concepts into REBOL code, and how to organize your work process to approach any unique situation. A number of case studies are presented to provide insight as to how specific real life situations were satisfied.

10 A Generalized Approach Using Outlines and Pseudo Code

Software virtually never springs to life in any sort of initially finalized form. It typically *evolves* through multiple revisions, and often develops in directions originally unanticipated. There's no perfect process to achieve final designs from scratch, but certain approaches typically do prove helpful. Having a plan of attack is what gets you started writing line 1 of your code, and it's what eventually delivers a working piece of software to your user's machines. Here's a generalized routine to consider:

1. Start with a *detailed definition of what the application should do*, in human terms. You won't get anywhere in the design process until you can *describe* some form of imagined final program. *Write down* your explanation and flesh out the details of the imaginary program as much as possible. Include as much detail as possible: what should the program look like, how will the user interact with it, what sort of data will it take in, process, and return, etc.
2. Determine a list of general code and data structures related to each of the 'human-described' program goals above. Take stock of any general code patterns which relate to the operation of each imagined program component. Think about how the user will get data into and out of the program.

Will the user work with a desktop GUI window, web forms that connect to a CGI script, or directly via command line interactions in the interpreter console? Consider how the *data* used in the program can be represented in code, organized, and manipulated. What types of data will be involved (text types such as strings, time values, or URLs, binary types such as images and sounds, etc.). Could the program code potentially make use of variables, block/series structures and functions, or object structures? Will the data be stored in local files, in a remote database, or just in temporary memory? Think of how the program will flow from one operation to another. How will pieces of data need to be sorted, grouped and related to one another, what types of conditional and looping operations need to be performed, what types of repeated functions need to be isolated and codified? Consider everything which is intended to *happen* in the imagined piece of software, and start thinking, "*_this_* is how I could potentially accomplish *_that_*, in code..."

3. *Begin writing a code **outline**.* It's often easiest to do this by outlining a user interface, but a flow chart of operations can be helpful too. The idea here is to begin writing a generalized code container for your working program. At this point, the outline can be filled with simple natural language PSEUDO CODE that *describes* how actual code can be organized. Starting with a user interface outline is especially helpful because it provides a starting point to actually write large code structures, and it forces you to deal with how the program will handle the input, manipulation, and output of data. Simple structures such as "view layout [button [which does this when clicked...]]", "block: [with labels and sub-blocks organized like this...]", "function: (which loops through this block and saves these elements to another variable...)" can be fleshed out later with complete code.
4. Finally, move on to replacing pseudo code with actual working code. This isn't nearly as hard once you've completed the previous steps. A language dictionary/guide with cross referenced functions is very helpful at this stage. And once you're really familiar with all the available constructs in the language, all you'll likely need is an occasional syntax reminder from REBOL's built-in help. Eventually, you'll pass through the other design stages much more intuitively, and get to/through this stage very quickly.
5. As a last step, debug your working code and add/change functionality as you test and use the program.

The basic plan of attack is to always explain to yourself what the intended program should do, in human terms, and then think through how all required code structures must be organized to accomplish that goal. As an imagined program takes shape, organize your work flow using a top down approach: imagined concept -> general outline -> pseudo code description / thought process -> working code -> finished code.

The majority of code you write will flow from one user input, data definition or internal function to the next. Begin mapping out all the things that need to "happen" in the program, and the info that needs to be manipulated along the way, in order for those things to happen, from beginning to end. The process of writing an outline can be helped by thinking of how the program must begin, and what must be done before the user starts to interact with the application. Think of any data or actions that need to be defined before the program starts. Then think of what must happen to accommodate each possible interaction the user might choose. In some cases, for example, all possible actions may occur as a result of the user clicking various GUI widgets. That should elicit the thought of certain bits of GUI code structure, and you can begin writing an outline to design a GUI interface. If you imagine an online CGI application, the user will likely work with forms on a web page. You can begin to design HTML forms, which will inevitably lead to specifying the variables that are passed to the CGI app. If your program will run as a simple command line app, the user may respond to text questions. Again, some code from the example applications in this tutorial should come to mind, and you can begin to form a coding structure that enables the general user interface and work flow.

Sometimes it's simpler to begin thinking through a development process using console interactions. It tends to be easier to develop a CGI application if you've got working console versions of various parts of the program. Whatever your conceived interface, think of all the choices the user can make at any given time, and provide a user interface component to allow for those choices. Then think of all the operations the computer must perform to react to each user choice, and describe what must happen in the code.

As you tackle each line of code, use natural language pseudo code to organize your thoughts. For example, if you imagine a button in a GUI interface doing something for your user, you don't need to immediately write the REBOL code that the button runs. Initially, just write a *description* of what you want the button to do. The same is true for functions and other chunks of code. As you flesh out your outline, ***describe the language elements and coding thought you conceive to perform various actions or to represent various data structures.*** The point of writing pseudo code is to keep clearly focused on the overall design of the program, at every stage of the development process. Doing that helps you to avoid getting lost in the nitty gritty syntax details of actual code. It's easy to lose sight of the big picture whenever you get involved in writing each line of code.

As you convert you pseudo code thoughts to language syntax, remember that most actions in a program occur as a result of conditional evaluations (if this happens, do this...), loops, or linear flow from one action to the next. If you're going to perform certain actions multiple times or cycle through lists of data, you'll likely need to run through some loops. If you need to work with changeable data, you'll need to define some variable words, and you'll probably need to pass them to functions to process the data. Think in those general terms first. Create a list of data and functions that are required, and put them into an order that makes the program structure build and flow from one definition, condition, loop, GUI element, action, etc.,

to the next.

What follows are a number of case studies that describe how I've approached various programming tasks in a productive way. Each example traces my train of thought from the organizational process through the completed code.

10.1 Case 1 - Scheduling Teachers

In my music lesson business, teachers were familiar with hand written paper schedules that looked like this:

Monday:

```
3      student1, 555-1234, parent's names, payment history, notes
3:30   student2, 555-1234, parent's names, payment history, notes
4      (gone 3-17) student3, 555-1234, payment history, notes
4:30   student4, 555-1234, parent's names, payment history, notes
5      student5, 555-1234, parent's names, payment history, notes
```

Tuesday:

```
3      ----
3:30   ----
4      (john doe 3-18) ----
4:30   ----
5      student1, 555-1234, parent's names, payment history, notes
5:30   student2, 555-1234, parent's names, payment history, notes
6      student3, 555-1234, parent's names, payment history, notes
6:30   ----
7      student4, 555-1234, parent's names, payment history, notes
7:30   ----
8      student5, 555-1234, parent's names, payment history, notes
.
.
.
```

To run my business, I wanted to create the above schedule format on a web page, and frame it in an HTML document that had some permanent info which teachers wouldn't alter. I wanted each teacher to be able to make adjustments to their schedule without having to mess with ftp or anything having to do with the web site. I just wanted them to be able to click a desktop icon, type changes into their schedule, and have it appear on a web page. I imagined a simple application that would do those things, and came up with this basic outline of how it could work:

1. Download a teacher's current schedule text file.
2. Backup a copy of the existing schedule, just in case.
3. Edit the schedule.
4. Upload the altered schedule data back to the website.
5. Include the new schedule text in an HTML template, retaining the proper line format.
6. Confirm that the changes were made correctly and that they displayed correctly on the web page.
7. Keep the teacher interface simple and intuitive, like writing on a piece of paper.

After looking at the above outline, I just did each step above in the most direct way possible in REBOL code:

```
; first set I some initial required variables:

url: http://website.com/teacher
ftp-url: ftp://user:pass@website.com/public_html/teacher

; ... and gave the teacher some instructions:

alert {Edit your schedule, then click save and quit.
      The website will be automatically updated.}

; 1) download the file containing the schedule text:

write %schedule.txt read rejoin [url %/schedule.txt"]
```

```

; 2) create a timestamped backup on the web server:

write rejoin [ftp-url "/" now/date "_" now/time ".txt"] read %schedule.txt

; 3 and 7) edit the text:

editor %schedule.txt

; 4) save the edited text back to the web site:

write rejoin [ftp-url "/schedule.txt"] read %schedule.txt

; 6) confirm that the changes are displayed correctly:

browse url

```

To satisfy step 5 in the outline, I created a downloadable executable (".exe" file) of the above program (using XpuckerX), and uploaded it to the web site. In the <http://website.com/teacher> folder on the web site, I created an index.cgi script containing the following code:

```

#!/home/path/public_html/rebol/rebol -cs
REBOL []
print "content-type: text/html^/"

print {<a href="./scheduler.exe" target=_blank>Download Scheduler</a><br>}
print rejoin ["<pre>" read %schedule.txt "</pre>"]

```

The first HTML line creates a download link, so that the teacher can download and run his scheduler program at any remote location. The second line includes the preformatted schedule text on the web page. I can put any other HTML I want on this page, which the teacher never touches (their contact information, lesson rates, information about vacation dates, types of students they want to teach, etc.).

What could have been a very long and involved database programming task was accomplished in minutes, and was used every day for many months in the business. The free form format enabled by using a simple text file provided the opportunity to incorporate various notes, changes, and info that would otherwise be awkward to include or difficult to emphasize in a database type scheduling app. In this case, writing the pseudo code outline provided an immediate solution, and it worked out to be the best way to satisfy our needs. You'll see later how I built this basic idea into a much more complex application which runs a busy business of 25+ instructors.

10.2 Case 2 - A Simple Image Gallery CGI Program

When putting together the web site for my music lesson business, I wanted to regularly add photos of students performing at various events. At first, I just uploaded the photos individually, and added a link to the folder that contained them. As the collection grew, I wanted users to see the images more easily, without having to click on each individual file name. So, I put together a simple flash presentation that showed the images one by one. But updating that presentation required too much maintenance. What I wanted was to simply upload photos, and have them all display in a nice format on a single web page, without any required maintenance. This type of small CGI application was perfectly suited to REBOL. It only took a few minutes to write, and it now gets used every day.

For this program, here's the outline and pseudo code I worked through in my head:

1. Start by creating a simple command line script on my home computer that reads a directory listing and uses a foreach loop to run through the files and perform necessary actions.
2. Within the foreach loop, check for specified image types (extensions in each file name), and only work with those files. Add a counter to display the total number of images. To do that, use a counter variable and increment it each time through the loop.
3. In the foreach loop, wrap each image in the list in the HTML tags required to display them on a web page. Add necessary headers to create a CGI script that runs on the web site. The script should print the HTML to the visitor's browser so they see a web page containing all the images.

Here's the code for step 1:


```

REBOL []

folder: read %.
foreach file folder [
    print file
    ; this is just a dummy action to be sure the loop is working properly
]
halt

```

For step 2, I added the counter variable, and checked for specified image types using an "if any" conditional expression:

```

REBOL []

folder: read %.
count: 0
foreach file folder [
    if any [
        find file ".jpg"
        find file ".gif"
        find file ".png"
        find file ".bmp"
    ] [
        print file
        count: count + 1
    ]
]
print rejoin [newline "Total Images: " count]
halt

```

I shortened that script a bit by using an alternate version which relies on nested foreach loops. The alternate code makes the list of potential image types easier to extend in the future:

```

REBOL []

folder: read %.
count: 0
foreach file folder [
    foreach ext [".jpg" ".gif" ".png" ".bmp"] [
        if find file ext [
            print file
            count: count + 1
        ]
    ]
]
print rejoin [newline "Total Images: " count]
halt

```

For the last step, I borrowed a line from the earlier "guitar chord diagram maker" example. It builds the HTML required to display each image on a web page. I replaced the dummy print function above with this code:

```

print rejoin [{}]

```

Finally, I added the typical CGI headers and page formatting code required to make REBOL CGI scripts perform correctly (see the previous CGI examples in this tutorial for similar patterns):

```

#! /home/path/public_html/rebol/rebol -cs
REBOL [title: "Photo Viewer"]
print "content-type: text/html^/"

```

```

print [<HTML><HEAD><TITLE>"Jam Session Photos"</TITLE></HEAD><BODY>]
print read %pageheader.html

folder: read %.
count: 0
foreach file folder [
  foreach ext [".jpg" ".gif" ".png" ".bmp"] [
    if find file ext [
      print [<BR> <CENTER>]
      print rejoin [{]
      count: count + 1
    ]
  ]
]
print [<BR>]
print rejoin ["Total Images: " count]
print read %pagefooter.html

```

I uploaded that script to the folder containing images on our web server, and updated the link to the photos on our web site. Now, we just upload new images directly to the server, and when web site visitors click the "Photos" link on our site, they instantly see a dynamically created web page full of all images currently contained in that folder.

10.3 Case 3 - Days Between Two Dates Calculator

In my business, teachers often need to figure the number of days that are between any two given dates. I can do that easily with the REBOL interpreter - just subtract any one date from another. For the unfortunate souls who don't know REBOL, I wanted to create a little GUI app that would quickly figure the calculation with some simple pointing and clicking.

This application ended up being built in stages. I started with this very simple pseudo-code idea for a script:

1. Use the "request-date" function to get a start date from the user. Assign the response to a variable.
2. Run the request-date function again to get an end date from the user. Assign that response to another variable.
3. Subtract the end-date variable from the start-date variable. Assign the result to a third variable.
4. Alert the user with the result.

That's all very straight forward. Here's the working code:

```

sd: request-date    ; get the START-DATE
ed: request-date    ; get the END-DATE
db: ed - sd         ; calculate the DAYS-BETWEEN
alert rejoin ["Days between " sd " and " ed ": " db] ; display the result

```

That was too easy. So I decided to create a bit more of a GUI interface. Here's the pseudo-code thought process I went through:

1. Create a "view layout" window and have a separate button run each of the request-date functions (start-date and end-date).
2. Run the days-between calculation after the end-date is selected, and display the result in a text field. In order for this to happen, the numeric days-between result needs to be converted to a text string (because fields can only display text string values). Don't forget to update the displayed results with the "show" function.

Here's the code:

```

REBOL [title: "Days Between"]

view layout [
  btn "Select Start Date" [sd: request-date]
  btn "Select End Date" [
    ed: request-date
    db/text: to-string (ed - sd)
  ]
]

```

```

        show db
    ]
    h1 "Days Between:"
    db: field
]

```

It works, but I'd like the user to be able to see the chosen dates in text fields. Here's my pseudo-code thought process for that feature addition:

1. I'll add two more text fields to the GUI layout.
2. Whenever the user selects a new start/end date, I'll update the appropriate text field to display the selected date. In order for that to work properly, again, I'll need to use the "to-string" function to convert the chosen date to a text value.

Here's the code I came up with to make those changes:

```

REBOL [title: "Days Between"]

view layout [

    btn "Select Start Date" [
        sd: request-date

        ; Update the start-date text field:

        sdt/text: to-string sd
        show sdt

    ]

    ; Here's the field to display the selected start-date:
    sdt: field

    btn "Select End Date" [

        ed: request-date

        ; Update the end-date text field:

        edt/text: to-string ed
        show edt

        db/text: to-string (ed - sd)
        show db

    ]

    ; Here's the field to display the chosen end-date:
    edt: field

    h1 "Days Between:"
    db: field

]

```

As it stands now, the program will crash if I select the end date before setting the start-date (because the days-between calculation tries to run without any value set for the start-date variable). In order to fix that, here's the pseudo-code thought process I went through:

1. I'll start the program by setting the "st" and "ed" variables (start-date and end-date) to an initial value of today's date ("now/date").
2. I'll display the initial start and end dates in the GUI text fields. In order for that to work properly, again I'll need to use the "to-string" function to convert the date into a text value.

Here's how the program looks when I make those changes:

```

REBOL [title: "Days Between"]

```

```

; set the initial values for start/end date:
sd: ed: now/date

view layout [
    btn "Select Start Date" [
        sd: request-date
        sdt/text: to-string sd
        show sdt
    ]

    ; show the initial start date in this field:
    sdt: field to-string sd

    btn "Select End Date" [
        ed: request-date
        edt/text: to-string ed
        show edt
        db/text: to-string (ed - sd)
        show db
    ]

    ; show the initial end date in this field:
    edt: field to-string ed

    h1 "Days Between:"
    db: field
]

```

Great, it works, but the days-between calculation still only runs when I change the end date. I'll add the days-between calculation code to the "Select Start Date" button:

```

REBOL [title: "Days Between"]

sd: ed: now/date
view layout [
    btn "Select Start Date" [
        sd: request-date
        sdt/text: to-string sd
        show sdt

        ; Run the days-between calculation, and update the display:

        db/text: to-string (ed - sd)
        show db
    ]

    sdt: field to-string sd
    btn "Select End Date" [
        ed: request-date
        edt/text: to-string ed
        show edt
        db/text: to-string (ed - sd)
        show db
    ]

    edt: field to-string ed
    h1 "Days Between:"
    db: field
]

```

As I played with the program a bit, I realized that it would be great if the user could manually enter/edit the chosen dates. Here's my thought process:

1. I'll run the days-between calculation whenever the user makes a change to the text field.
2. I'll need to stop using the "sd" and "ed" variables to perform the calculation, and instead use the *text contained in the GUI fields*, in order to be sure I'm working with any potentially edited text values.
3. Again, I'll need to pay attention to converting dates back and forth between text and date data types. Data displayed in the GUI text fields needs to be converted to a text string, using the "to-text"

function, and data used to perform the days-between calculation must be converted to a date value, using the "to-date" function. REBOL automatically knows how to subtract and add dates, but it doesn't know how to perform those types of calculations on text strings. Just use the "to-date" function to perform appropriate calculations, and it works like magic.

```
REBOL [title: "Days Between"]

sd: ed: now/date
view layout [
    btn "Select Start Date" [
        sd: request-date
        sdt/text: to-string sd
        show sdt

        ; Perform the days-between calculation using the value
        ; contained in the end-date text field (first convert
        ; that text value to a date value):

        db/text: to-string ((to-date edt/text) - sd)

        show db
    ]
    sdt: field to-string sd [

        ; Perform the days-between calculation using the values
        ; contained in the start-date and end-date text fields
        ; (first convert those text values to date values):

        db/text: to-string ((to-date edt/text) - (to-date sdt/text))

        show db
    ]
    btn "Select End Date" [
        ed: request-date
        edt/text: to-string ed
        show edt

        ; Perform the days-between calculation using the value
        ; contained in the start-date text field (first convert
        ; that text value to a date value):

        db/text: to-string (ed - (to-date sdt/text))

        show db
    ]
    edt: field to-string ed [

        ; Perform the days-between calculation using the values
        ; contained in the start-date and end-date text fields
        ; (first convert those text values to date values):

        db/text: to-string ((to-date edt/text) - (to-date sdt/text))

        show db
    ]
    h1 "Days Between:"
    db: field
]
```

Next, I realized that I wanted an additional feature. The program should also be able to figure an end date based upon a given start date and a given number of days-between. Here's the pseudo-code thought process I went through to add that feature:

1. Display an initial value of "0" days in the "db" text field (that's the number of days between the initial start and end dates (today - today)).
2. If the user manually enters a number of days, add the given number of days to the start date, and update the end-date text field with the result (again, be sure to convert between text and date values, as in each previous example).

Simple. Here's the updated code:

```
REBOL [title: "Days Between"]

sd: ed: now/date
view layout [

    btn "Select Start Date" [
        sd: request-date
        sdt/text: to-string sd
        show sdt
        db/text: to-string ((to-date edt/text) - sd)
        show db
    ]
    sdt: field to-string sd [
        db/text: to-string ((to-date edt/text) - (to-date sdt/text))
        show db
    ]
    btn "Select End Date" [
        ed: request-date
        edt/text: to-string ed
        show edt
        db/text: to-string (ed - (to-date sdt/text))
        show db
    ]
    edt: field to-string ed [
        db/text: to-string ((to-date edt/text) - (to-date sdt/text))
        show db
    ]
    h1 "Days Between:"
    db: field "0" [

        ; Add the manually entered number of days to the start date,
        ; and update the display:

        edt/text: to-string ((to-date sdt/text) + (to-integer db/text))
        show edt

    ]
]
```

As I tested the above code, one bug became apparent. If a date is manually entered incorrectly (for example, I tried "267-Aug-2009"), the program would come to a crashing halt with an error message. To fix that, I wrapped each date calculation that involved manual text entry in an "either error? try" routine, and alerted the user with a nice message if they entered anything other than a proper date:

```
sdt: field to-string sd [
    either error? try [to-date sdt/text] [
        alert "Improper date format."
    ] [
        db/text: to-string ((to-date edt/text) - (to-date sdt/text))
        show db
    ]
]

edt: field to-string ed [
    either error? try [to-date edt/text] [
        alert "Improper date format."
    ] [
        db/text: to-string ((to-date edt/text) - (to-date sdt/text))
        show db
    ]
]
```

I also added an error check routine to the "db" text field, in case the user entered something other than a valid number of days:

```

db: field "0" [
  either error? try [to-integer db/text] [
    alert "Please enter a number."
  ] [
    edt/text: to-string (
      (to-date sdt/text) + (to-integer db/text)
    )
  ]
  show edt
]

```

At this point, every feature I can think of has been added, and all obvious bugs squashed. The evolution of this application is typical of many software case studies. Many large applications start with a basic working idea, then gradually evolve as the code is tested, user interface adjusted, features added, bugs found and eliminated, etc. That process is creative, and it can be really fun and satisfying. When writing your own applications, you have complete control to make them perform however you like :)

Here's the final code:

```

REBOL [title: "Days Between"]

sd: ed: now/date
view layout [
  btn "Select Start Date" [
    sd: request-date
    sdt/text: to-string sd
    show sdt
    db/text: to-string ((to-date edt/text) - sd)
    show db
  ]
  sdt: field to-string sd [
    either error? try [to-date sdt/text] [
      alert "Improper date format."
    ] [
      db/text: to-string ((to-date edt/text) - (to-date sdt/text))
      show db
    ]
  ]
  btn "Select End Date" [
    ed: request-date
    edt/text: to-string ed
    show edt
    db/text: to-string (ed - (to-date sdt/text))
    show db
  ]
  edt: field to-string ed [
    either error? try [to-date edt/text] [
      alert "Improper date format."
    ] [
      db/text: to-string ((to-date edt/text) - (to-date sdt/text))
      show db
    ]
  ]
  h1 "Days Between:"
  db: field "0" [
    either error? try [to-integer db/text] [
      alert "Please enter a number."
    ] [
      edt/text: to-string (
        (to-date sdt/text) + (to-integer db/text)
      )
    ]
    show edt
  ]
]

```

I packaged that script as an executable program, using XpackerX, and distributed it to all the teachers. We use it every day. (... Of course, I still just use the REBOL command line to perform my date calculations :)

10.4 Case 4 - Simple Search

It happens fairly often that I need to search for text within files on my various web site servers and on computers at my office and home. Every operating system has programs to accomplish such searches, but I'm often unhappy with the way those programs work, so I decided to create my own customized tool that operates the way I want, on every machine. This was a simple problem for which REBOL allowed me to devise a quick solution.

I started the process by thinking through the algorithm in terms of normal human activity. If I was to manually search through every file in a given folder and all its subfolders, here's the pseudo-code that describes what I'd do:

1. Obtain a directory listing of all items in a given start folder.
2. For each item in the list, if the item is a file, read/scan it to see if it contains the given search text.
3. For each item in the list, if the item is a folder, switch into that folder and repeat steps 1-3 (I must include step 3 in step 3 itself if I want to do the same thing to every subfolder - otherwise the process would stop with 1 subfolder - very important!). When done, switch back up to the parent folder.

Step 1 is easy in REBOL code:

```
; define a starting folder:
current-folder: %.\
; read the directory listing:
read current-folder
```

Step 2 isn't much more complicated:

```
; define the search text:
phrase: "the"

; for every item in the directory listing:
foreach item (read current-folder) [
  ; if the item is a file:
  if not dir? item [
    ; read/scan the file for the given phrase:
    if find (read to-file item) phrase [
      ; display the path/filename in which
      ; the search text is found:
      print rejoin [{" } phrase {" found in:  } what-dir item]
    ]
  ]
]
```

Step 3 is recursive - the actions in step 3 include executing the actions in step 3. Such recursion operations typically require creating a function that contains the actions desired, which include calling the function itself, in which those actions are contained. Here's the new code needed for step 3 - notice that the function is named "recurse" and that that "recurse" function is called within the body of that recurse function:

```
; create the function name:
recurse: func [current-folder] [
  ; for every item in the directory listing:
  foreach item (read current-folder) [
    ; if the item is a folder:
    if dir? item [
      ; change into that folder:
      change-dir item
      ; and do all the steps in the function again:
      recurse %.\
      ; go back up to the parent directory when
      ; there are no more sub-folders:
      change-dir %..\
    ]
  ]
]
```



```

    ]
  ]
]

```

I put all of the code for steps 1 and 2 into that recurse function, and now it's fully operational:

```

recurse: func [current-folder] [
  foreach item (read current-folder) [
    if not dir? item [
      if find (read to-file item) phrase [
        print rejoin [{" } phrase {" found in:  } what-dir item]
      ]
    ]
  ]
  foreach item (read current-folder) [
    if dir? item [
      change-dir item
      recurse %.\
      change-dir %..\
    ]
  ]
]

```

While testing the function, I found that some of the system files could not be read. That produced a read error. I squashed that bug by adding a bit of "if error? try []" code:

```

foreach item (read current-folder) [
  if not dir? item [ if error? try [
    if find (read to-file item) phrase [
      print rejoin [{" } phrase {" found in:  } what-dir item]
    ]] [print rejoin ["error reading " item]]
  ]
]

```

To complete the program, I added a few variables to request the search text and the starting folder. I created a string variable to hold a complete text list of all files in which the search phrase was found, and I printed a little header to show that the search process had begun. When complete, the text list of files is displayed in the REBOL text editor. Here's the final version:

```

REBOL [title: "Simple Search"]

phrase: request-text/title/default "Text to Find:" "the"
start-folder: request-dir/title "Folder to Start In:"
change-dir start-folder
found-list: ""

recurse: func [current-folder] [
  foreach item (read current-folder) [
    if not dir? item [ if error? try [
      if find (read to-file item) phrase [
        print rejoin [{" } phrase {" found in:  } what-dir item]
        found-list: rejoin [found-list newline what-dir item]
      ]] [print rejoin ["error reading " item]]
    ]
  ]
  foreach item (read current-folder) [
    if dir? item [
      change-dir item
      recurse %.\
      change-dir %..\
    ]
  ]
]

```

```

print rejoin [{SEARCHING for "} phrase {" in } start-folder "...^/" ]
recurse %.\
print "^/DONE^/"
editor found-list
halt

```

Next I wanted a CGI version to run on my web sites. I'll need to input my search text and starting folder using an HTML form:

```

print [<CENTER><TABLE><TR><TD>]
print [<FORM ACTION="./search.cgi">]
print ["Text to search for:" <BR>
      <INPUT TYPE="TEXT" NAME="phrase"><BR><BR>]
print ["Folder to search in:" <BR>
      <INPUT TYPE="TEXT" NAME="folder" VALUE="../yourfolder/" ><BR><BR>]
print [<INPUT TYPE="SUBMIT" NAME="Submit" VALUE="Submit">]
print [</FORM>]
print [</TD></TR></TABLE></CENTER>]

```

To make this work on the web site, I'll need to include all the standard CGI headers, and decode the submitted data (this standard code format is copied from the earlier CGI examples in this tutorial):

```

#! /home/yourpath/public_html/rebol/rebol -cs
REBOL []
print "content-type: text/html^/"
print [<HTML><HEAD><TITLE>"Search"</TITLE></HEAD><BODY>]
; print read %template_header.html

submitted: decode-cgi system/options/cgi/query-string

```

Here's the final CGI version:

```

#! /home/yourpath/public_html/rebol/rebol -cs
REBOL []
print "content-type: text/html^/"
print [<HTML><HEAD><TITLE>"Search"</TITLE></HEAD><BODY>]
; print read %template_header.html

submitted: decode-cgi system/options/cgi/query-string

if not empty? submitted [
  phrase: submitted/2
  start-folder: to-file submitted/4
  change-dir start-folder
  found-list: ""

  recurse: func [current-folder] [
    foreach item (read current-folder) [
      if not dir? item [ if error? try [
        if find (read to-file item) phrase [
          print rejoin [{" } phrase {" found in: }
            what-dir item {<BR>}]
          found-list: rejoin [found-list newline
            what-dir item]
        ]] [print rejoin ["error reading " item]]
      ]
    ]
    foreach item (read current-folder) [
      if dir? item [
        change-dir item
        recurse %.\
        change-dir %..\
      ]
    ]
  ]
]

```

```

]

print rejoin [{SEARCHING for "} phrase {" in }
             start-folder {<BR><BR>}]
recurse %.\
print "<BR>DONE <BR>"
; save %found.txt found-list
; print read %template_footer.html
quit

]

print [<CENTER><TABLE><TR><TD>]
print [<FORM ACTION="./search.cgi">]
print ["Text to search for:" <BR>
      <INPUT TYPE="TEXT" NAME="phrase"><BR><BR>]
print ["Folder to search in:" <BR>
      <INPUT TYPE="TEXT" NAME="folder" VALUE="../yourfolder/" ><BR><BR>]
print [<INPUT TYPE="SUBMIT" NAME="Submit" VALUE="Submit">]
print [</FORM>]
print [</TD></TR></TABLE></CENTER>]
; print read %template_footer.html

```

I use this search program constantly. It took only a few minutes to write using the most basic principles and syntax patterns seen over and over again in this tutorial, and it runs on every computing device I own, including all my home and work computers, my web sites, my phone, etc.

10.5 Case 5 - A Simple Calculator Application

Next is a quick case study about how to build a small calculator application in REBOL (this is not so much a real life case study - it just seems that building a GUI calculator app is an obligatory cliché among computer programming tutorials).

I started with a pseudo-code outline of how I wanted the program's user interface to look when complete:

1. There needs to be a display area to show numerical digits as they are input, as well as the results of calculations. A simple GUI text field will work fine for that display.
2. There need to be GUI buttons to enter numerical digits and a decimal point, as well as buttons for mathematical operators, and a button to execute calculations (an "=" sign). Each of those three categories of buttons will do generally the same types of actions, so I'll create them as separate GUI styles, each with shared action blocks.

That was enough of an outline to begin writing some actual REBOL GUI code. I toyed with various window, button, and font sizes/colors until the layout looked acceptable. Here's what I came up with using the pseudo-code above:

```

view center-face layout/tight [
  size 300x350 space 0x0 across ; basic window sizing/spacing
  display: field 300x50 font-size 28 "0" return ; the display
  style btnn button 100x50 [
    ; add the action code here for number buttons
  ]
  style evaln button 100x50 brown font-size 13 [
    ; add the action code here for operator buttons
  ]
  btnn "1" btnn "2" btnn "3" return ; arrange those buttons
  btnn "4" btnn "5" btnn "6" return ; in the window
  btnn "7" btnn "8" btnn "9" return
  btnn "0" btnn "." evaln "+" return
  evaln "-" evaln "*" evaln "/" return
  button 300x50 gray font-size 16 "=" [
    ; add the action code here for "=" sign button
  ]
]

```

To turn the above display into a functioning calculator, next I needed to think about what must happen when the number buttons are clicked. Here's some pseudo-code to outline that thought process:

1. The user must be able to enter numbers that are longer than a single digit, so every time a number button is clicked, that numerical digit should be appended to the digits in the display. I'll use "rejoin" to build the display number, and then I'll set a variable to store that number, each time a new digit is clicked.
2. In the GUI code above, I started with a "0" in the display field. That'll need to be erased before any other numbers are displayed.

That's all easy enough to do in REBOL code:

```
if display/text = "0" [display/text: ""] ; erase the displayed "0"
display/text: rejoin [display/text value] ; build the displayed #
show display
cur-val: display/text ; use a variable to save the displayed #
```

Now I need to think about what should happen when the operator buttons are clicked:

1. I need to assign a variable to save the number currently entered in the GUI display (that number is already saved temporarily in the "cur-val" variable above).
2. Erase the display to prepare for a new number to be entered.
3. Assign a variable to save the operator selected.

That's all very simple - in fact, it's simpler in real REBOL code than it is in pseudo-code:

```
prev-val: cur-val ; save the displayed # in a variable
display/text: "" show display ; erase the display
cur-eval: value ; save the selected operator in a variable
```

Finally, I need to think about what happens when the "=" button is clicked:

1. A computation must be evaluated, using the first number entered (the "prev-val" variable above), the operator entered (the "cur-eval" variable), and the second number entered ("cur-val").
2. The display area needs to be updated to show the value of that computation.

The easiest way I could think to build the computation was to use the "rejoin" function to build a string representing the first number entered, the operator entered, and the second number entered. I could then evaluate that computation by simply using the "do" function on the built string:

```
cur-val: do rejoin [prev-val " " cur-eval " " cur-val]
display/text: cur-val
show display
```

That was all very easy. Here's the code we've got so far:

```
view center-face layout/tight [
  size 300x350 space 0x0 across
  display: field 300x50 font-size 28 "0" return
  style butn button 100x50 [
    if display/text = "0" [display/text: ""] ; erase the "0"
    display/text: rejoin [display/text value] ; build the #
    show display
    cur-val: display/text ; use a variable to save the displayed #
  ]
  style eval button 100x50 brown font-size 13 [
    prev-val: cur-val
    display/text: "" show display
    cur-eval: value
  ]
  butn "1" butn "2" butn "3" return
  butn "4" butn "5" butn "6" return
  butn "7" butn "8" butn "9" return
  butn "0" butn "." eval "+" return
```

```

eval "-" eval "*" eval "/" return
button 300x50 gray font-size 16 "=" [
  cur-val: do rejoin [prev-val " " cur-eval " " cur-val]
  display/text: cur-val
  show display
]
]

```

After testing the code a bit, I found a bug. Whenever the first computation is completed, any additional digits entered are appended to the total displayed from the first calculation. That happens in this line of code in the number buttons definition (the "butn" style):

```
display/text: rejoin [display/text value]
```

That problem is easily solved by setting a flag variable when the "=" button is clicked:

```
display-flag: true
```

... and then checking for that flag every time a number button is clicked - if the flag is set (meaning that a total is being displayed), erase the display so that a new number can be entered, and reset the flag variable:

```
if display-flag = true [display/text: "" display-flag: false]
```

That fixes the first bug. Testing the program a little more, I found another small bug. The calculator would crash with an error if the "=" sign or any of the operator buttons were clicked before numerical digits were properly entered. That was easy to fix by simply setting some default variables in the beginning of the program - that's a fundamentally good practice in any sort of programming:

```
prev-val: cur-val: 0 cur-eval: "+" display-flag: false
```

After using the program a bit more, I found another bug. If the equal sign was clicked repeatedly, it would perform calculations that weren't intended. The following line was the culprit:

```
cur-val: do rejoin [prev-val " " cur-eval " " cur-val]
```

The "cur-val" variable was updated every time the "=" button was clicked, whether or not a new number or operator was entered. To squash that bug, I just used the "display-flag" variable that was created earlier to check if a total was being displayed. I wrapped all of the action code performed when the "=" sign was clicked, into an "if" conditional, and only performed those actions if the flag had been reset (only if a total was not being displayed):

```
if display-flag <> true [ ... ]
```

Finally, there was a bug I'd had in mind from the beginning: if the user tried to divide by 0, the program would crash. To handle this situation, I added the following conditional check inside the code above:

```

if ((cur-eval = "/") and (cur-val = "0")) [
  alert "Division by 0 is not allowed." break
]

```

At this point, the program appeared to be reasonably bug free, so I decided to add an additional feature that

seemed useful while testing the code. I wanted a running printout of all calculations performed, similar to paper tape on traditional printing calculators. Adding that feature was as simple as could be. At the beginning of the program I added a "print 0" line, and then added the following line changes to the "=" button:

```
prin rejoin [prev-val " " cur-eval " " cur-val " = "]
print display/text: cur-val: do rejoin [
  prev-val " " cur-eval " " cur-val
]
```

Here's the final calculator program:

```
REBOL [title: "Calculator"]

prev-val: cur-val: 0 cur-eval: "+" display-flag: false
print "0"
view center-face layout/tight [
  size 300x350 space 0x0 across
  display: field 300x50 font-size 28 "0" return
  style butn button 100x50 [
    if display-flag = true [display/text: "" display-flag: false]
    if display/text = "0" [display/text: ""]
    display/text: rejoin [display/text value]
    show display
    cur-val: display/text
  ]
  style eval button 100x50 brown font-size 13 [
    prev-val: cur-val
    display/text: "" show display
    cur-eval: value
  ]
  butn "1" butn "2" butn "3" return
  butn "4" butn "5" butn "6" return
  butn "7" butn "8" butn "9" return
  butn "0" butn "." eval "+" return
  eval "-" eval "*" eval "/" return
  button 300x50 gray font-size 16 "=" [
    if display-flag <> true [
      if ((cur-eval = "/") and (cur-val = "0")) [
        alert "Division by 0 is not allowed." break
      ]
      prin rejoin [prev-val " " cur-eval " " cur-val " = "]
      print display/text: cur-val: do rejoin [
        prev-val " " cur-eval " " cur-val
      ]
      show display
      display-flag: true
    ]
  ]
]
```

10.6 Case 6 - A Backup Music Generator (Chord Accompaniment Player)

In my music lesson business, one of the things we teach is improvisation ("jam session") skills. In order for beginning students to practice, I created a simple program they could use to hear and play along with any given chord progression, at any given tempo. Building such a program with REBOL was easy. Designing an application to play pre-recorded chords from a given text list took less than a half hour.

Here's the basic outline I came up with to get started (a very basic knowledge of chord notation is required for this case study):

1. Record wave files of major, minor, dominant 7th, half diminished, diminished 7th, minor 7th, and major 7th chords on all 12 root notes (A, A#, B, C, C#, D, D#, E, F, F#, G, and G#), along with a few other commonly used chord voicings. The recordings all needed to be of short block chords, of the exact same duration and volume.
2. Compress and embed the wave files using the binary resource embedder from earlier in this text.

3. Load each sound into memory and give each one a variable label.
4. Create a GUI with text fields for the chords to play, and the tempo. Add "play" and "stop" buttons to control the action.
5. When the "play" button is clicked, play the wave data for each chord in the given progression, using the given timing gap. There will need to be some multitasking code to enable the looping chord progressions to be stopped.
6. Add some buttons to save and load the chord progressions, along with a button to provide some help/instructions.

The first step was mechanical - no programming required. I recorded the sounds of all twelve major, minor, and dominant 7th chords using my favorite recording software and my guitar. I saved each sound as a separate wave file in 1 directory on my hard drive (I later recorded a much larger collection of chords, but this was enough to get started).

For step 2 in the outline, I used a variation of the binary resource embedder program from earlier in this text to loop through the files in the directory:

```
REBOL []

system/options/binary-base: 64
sounds: copy []
foreach file load %./ [
    print file
    uncompressed: read/binary file
    compressed: compress to-string uncompressed
    if ((length? uncompressed) > 5000) [
        append sounds compressed
    ]
]
editor sounds
```

It provided one huge block of data containing every one of those sounds in embedded format. The output of that chord data can be seen at http://musiclessonz.com/rebol_tutorial/backup.r:

```
64#{
eJxEEd2VUW833ddyIE8fdHYoVCi1S2mJ1F+ruTvvU3d3dC1RpC7S4ExwSJfGSSEhC
EmIQIvf19//yrr32mTMz58vcNXfP2XOTEhIQx0CgRbEL4zds32dPBIFA4EnEZYFA...
```

For step 3, I placed the "load to-binary decompress" code (found earlier in this text) in front of each embedded sound file data chunk (to decompress the data and load the sound into memory for quick use). I gave each chord it's appropriate chord label (A major, Bb major, C minor, G7, etc.). In doing so, I decided to use all flat symbols for any root notes that had accidentals (i.e., F# = Gb, C# = Db, etc. (no sharps)). Here's how the code for the A major and Bb minor chords looked:

```
a: load to-binary decompress 64#{
eJxEEd2VUW833ddyIE8fdHYoVCi1S2mJ1F+ruTvvU3d3dC1RpC7S4ExwSJfGSSEhC
EmIQIvf19//yrr32mTMz58vcNXfP2XOTEhIQx0C ...

bbm: load to-binary decompress 64#{
eJwstwVcU9//P757d9eMbQwYMWB0d4cgraCogIgdKHY381b0rZjYXW8VOxGbDukc
3TVqCWPdv32+///j9Tj3nnvuOa9+Pc85iQtjYkr ...
```

Here's the full list of chord labels I created (the underscore symbol was a label that I gave to a silent sound that I recorded, to be used for a beat of rest). I manually labeled each of the chord data with the following labels (using my text editor's search, copy, and paste facilities, that took about ten minutes):

```
a bb b c db d eb e f gb g ab
am bbm bm cm dbm dm ebm em fm gbm gm abm
a7 bb7 b7 c7 db7 d7 eb7 e7 f7 gb7 g7 ab7
adim7 bdim7 bdim7 cdim7 dbdim7 ddim7
ebdim7 edim7 fdim7 gbdim7 gdim7 abdim7
am7b5 bbm7b5 bm7b5 cm7b5 dbm7b5 dm7b5
```

```

ebm7b5 em7b5 fm7b5 gbm7b5 gm7b5 abm7b5
am7 bbm7 bm7 cm7 dbm7 dm7 ebm7 em7 fm7 gbm7 gm7 abm7
amaj7 bbmaj7 bmaj7 cmaj7 dbmaj7 dmaj7
ebmaj7 emaj7 fmaj7 gbmaj7 gmaj7 abmaj7
-

```

Step 4 in the outline just required building the following simple GUI. It consists of a few labels, a text area to hold the user-entered chords, a text field for the tempo, and a couple buttons to stop and start the music action. I also decided to add the buttons from step 6 - I even put all that code in here - all that was required was to save and load the contents of the text area. Simple:

```

view center-face layout [
  across
  h2 "Chords:"
  tab
  chords: area 392x300 trim {}
  return
  h2 "Delay:"
  tab
  tempo: field 50 "0.35" text "(seconds)"
  tabs 40 tab
  btn "PLAY" []
  btn "STOP" []
  btn "Save" [save to-file request-file/save chords/text]
  btn "Load" [chords/text: load read to-file request-file show chords]
  btn "HELP" [
    alert {}
  ]
]

```

Now all that's left is step 5. I started by loading the user entered list of chords into a block:

```
sounds: to-block chords/text
```

I also gave a label to the tempo, and made sure it was treated as a decimal value:

```
the-tempo: to-decimal tempo/text
```

I took the play-sound function that you've seen earlier, and used its code inside a foreach loop that played each of the sounds in the user provided list (now in the "sounds" block). Because those chord labels now refer to actual pieces of sound data that can be inserted and played directly by the sound port, this was simple:

```

wait 0
sound-port: open sound://
foreach sound sounds [
  do rejoin ["insert sound-port " reduce [sound]]
  wait sound-port
  wait the-tempo
]

```

I wrapped the above foreach loop in a forever loop, because I wanted the chord progression to repeat continuously. To stop the music, I first thought that I'd need some multitasking code, but it turns out that it was simpler than expected. All I did was create a flag variable (the word "play"), which was set to false when the GUI stop button was clicked. Inside the above foreach loop, I checked to see if the play variable had been set to false, and if so, broke out of the loop. The stop button then simply closed the sound port after setting the variable flag to false. Below is the full code for the PLAY and STOP buttons in the GUI. Simple :)


```

btn "PLAY" [
  play: true
  the-tempo: to-decimal tempo/text
  sounds: to-block chords/text
  wait 0
  sound-port: open sound://
  forever [
    foreach sound sounds [
      if play = false [break]
      do rejoin ["insert sound-port " reduce [sound]]
      wait sound-port
      wait the-tempo
    ]
    if play = false [break]
  ]
]
btn "STOP" [
  play: false
  close sound-port
]

```

To finish up the program, I added some instruction text to the alert which pops up when the help button is clicked, and I put in an example chord progression that appears in the text area by default (the chords to "Hotel California"). In testing the program, I realized that if the GUI was closed before the music was stopped, play would continue without any way to stop it. The operating system's task manager was the only way to end the music at that point. To fix that bug, I added some code to trap the close button and stop the music (set the play flag to false and close the sound port), along with a request to "really close the program?". You've seen that sort of code in several previous examples.

Here's the final program (a shortened version, WITHOUT the chord data required to play the example):

```

REBOL [title: "Chord Accompaniment Player"]

play: false
insert-event-func [
  either event/type = 'close [
    if play = true [play: false close sound-port]
    really: request "Really close the program?"
    if really = true [quit]
  ][
    event
  ]
]

{
  .
  .
  .

  all the chord data goes here

  bm: load to-binary decompress 64#{
    eJw8dgdUU0/w7k0vJNTQe++9SpUqCogIiiKgIIq9YAdU7L397NgVRAQEpEnvvfca
    CCUhQEhCIJUK9/E/7/3f2bN7z92d...
  }

  .
  .
  .
}

view center-face layout [
  across
  h2 "Chords:"
  tab
  chords: area 392x300 trim {
    bm bm bm bm
  }
]

```

```

    gb7 gb7 gb7 gb7
    a a a a
    e e e e
    g g g g
    d d d d
    em em em em
    gb7 gb7 gb7 gb7
    g g g g
    d d d d
    gb7 gb7 gb7 gb7
    bm bm bm bm
    g g g g
    d d d d
    em em em em
    gb7 gb7 gb7 gb7
  }
  return
  h2 "Delay:"
  tab
  tempo: field 50 "0.35" text "(seconds)"
  tabs 40 tab
  btn "PLAY" [
    play: true
    the-tempo: to-decimal tempo/text
    sounds: to-block chords/text
    wait 0
    sound-port: open sound://
    forever [
      foreach sound sounds [
        if play = false [break]
        do rejoin ["insert sound-port " reduce [sound]]
        wait sound-port
        wait the-tempo
      ]
      if play = false [break]
    ]
  ]
  btn "STOP" [
    play: false
    close sound-port
  ]
  btn "Save" [save to-file request-file/save chords/text]
  btn "Load" [chords/text: load read to-file request-file show chords]
  btn "HELP" [
    alert {
      This program plays chord progressions. Simply type in
      the names of the chords that you'd like played, with a
      space between each chord. For silence, use the
      underscore ("_") character. Set the tempo by entering a
      delay time (in fractions of second) to be paused between
      each chord. Click the start button to play from the
      beginning, and the stop button to end. Pressing start
      again always begins at the first chord in the
      progression. The save and load buttons allow you to
      store to the hard drive any songs you've created.
      Chord types allowed are major triad (no chord symbol -
      just a root note), minor triad ("m"), dominant 7th
      ("7"), major 7th ("maj7"), minor 7th ("m7"), diminished
      7th ("dim7"), and half diminished 7th ("m7b5").
      *** ALL ROOT NOTES ARE LABELED WITH FLATS (NO SHARPS)
      F# = Gb, C# = Db, etc...
    }
  ]
]
1

```

A full, playable version, with the complete data set of embedded chords, can be found at http://musiclessonz.com/rebol_tutorial/backup.r.

Here are a few chord examples to load. All the chords:

```

a bb b c db d eb e f gb g ab
am bbm bm cm dbm dm ebm em fm gbm gm abm
a7 bb7 b7 c7 db7 d7 eb7 e7 f7 gb7 g7 ab7
adim7 bbdim7 bdim7 cdim7 dbdim7 ddim7
ebdim7 edim7 fdim7 gbdim7 gdim7 abdim7
am7b5 bbm7b5 bm7b5 cm7b5 dbm7b5 dm7b5
ebm7b5 em7b5 fm7b5 gbm7b5 gm7b5 abm7b5
am7 bbm7 bm7 cm7 dbm7 dm7 ebm7 em7 fm7 gbm7 gm7 abm7
amaj7 bbmaj7 bmaj7 cmaj7 dbmaj7 dmaj7
ebmaj7 emaj7 fmaj7 gbmaj7 gmaj7 abmaj7
-- -- --

```

Brown Eyed Girl:

```

g g c c g g d d7
g g c c g g d d7
g g c c g g d d7
g g c c g g d d7
g g c c g g d d7
g g c c g g d d7
g g c c g g d d7
c c d d g g em em c c d d

```

10.7 Case 7 - FTP Tool

I often use REBOL's built in text editor to edit files on my web server:

```
editor ftp://user:pass@site.com/path/public_html/file.ext
```

This entire case study evolved from my use of that function. I decided to create a small script to speed up the above process. By hard coding all my FTP info directly into a GUI text field, all I have to do to edit a file on my server is run the script and change the specific file name:

```

view layout [
  p: field "ftp://user:pass@site.com/path/public_html/file.ext"
  btn "Edit" [
    editor to-url p/text
  ]
]

```

While using that script, I'd often forget the exact names of files I needed, so I decided to add a folder browsing feature to the code. Here's the thought process I went through:

1. Add a text list to the script. Instead of entering the URL of a file name in the text field, enter a folder. When I submit the URL now, the script will read the contents of that folder and display each item in the text list.
2. When I click an item in the text list, the script will join the selected file name with the given folder, and open the editor at that URL.

Here's the code - as always with REBOL, it's extremely simple:

```

view layout [
  p: field "ftp://user:pass@site.com/path/public_html/" [
    f/data: read to-url value
    show f
  ]
  f: text-list [
    editor to-url (join p/text value)
  ]
]

```

```
]
```

This worked well, but after using it a few times, I decided that I still wanted the option to type in a specific file name, to have it open immediately. Here's my thought process:

1. Add an "either" condition.
2. If the entered URL is a folder, do as in the previous script (I can use the `dir?` function to perform this check).
3. Otherwise edit the entered URL directly.

Here's the code:

```
view layout [
  p: field "ftp://user:pass@site.com/path/public_html/file.ext" [
    either dir? to-url value [
      f/data: read to-url value
      show f
    ][
      editor to-url value
    ]
  ]
  f: text-list [
    editor to-url join p/text value
  ]
]
```

I ran into some occasional problems with the `dir?` function, so I changed that line to read:

```
either (to-string last value) = "/" [
```

As it stands, the above script is a useful FTP editor. To create a new file, all I have to do is type its path and file name into the text field. REBOL's built in text editor automatically creates the file if it doesn't already exist. As I used this script more, I wanted to be able to navigate folders automatically (without having to type in the names of paths/files at all). Here are my thoughts:

1. If the user clicks on a folder, append the folder name to the current folder displayed in the text field, then re-read and display the contents of the new folder in the text list. This effectively changes directories.
2. To go *up* a folder (back to the previous folder), add `"../"` to the directory contents read from the folder currently displayed in the text field, and show that data in the text list. Also, sort the data, so `"../"` appears at the top of the list.
3. When the user clicks the `"../"`, remove the last portion of the currently entered path (everything back to the prior slash symbol), update the text field, and read/display the files in that folder in the text list. For example, if the currently displayed path is `"ftp://user:pass@site.com/path/public_html/folder/"`, remove the `"folder/"` portion, update the text field to `"ftp://user:pass@site.com/path/public_html/"`, and read/display the contents of that folder.

Step 1 is easy. Just rejoin the currently displayed folder in the text field, with the value selected from the text list:

```
p/text: rejoin [p/text value]
show p
```

Step 2 is just as easy. Append `"../"` to the line of code that reads and displays the files in the current folder (`"f/data: read to-url value"`), and sort it:

```
f/data: sort append (read to-url p/text) "../"
show f
```

For step 3, we need to search for the 2nd to last "/" symbol in the currently displayed path, and remove everything after it. To do that, we'll start searching backward from the 2nd to last character (to eliminate the final "/" character in the folder, because we want the *2nd to last* "/" character). That's easy - start searching backwards from ((length? p/text) - 1). I decided to use a "for" loop starting at that index position, and decrementing by 1. Each time through the loop, pick the character at the current index position, and if it is "/", erase all characters after that index position (use the "clear" function to delete everything at (current index + 1)). Then, update the text field with the new path, read the directory contents, and display in the text list, as in steps 1 and 2 above:

```
for i ((length? p/text) - 1) 1 -1 [
  if (to-string (pick p/text i)) = "/" [
    clear at p/text (i + 1)
    show p
    f/data: sort append read to-url p/text "../"
    show f
    break ; quit the loop once the 2nd to last "/" is found
  ]
]
```

As I looked at that code, I realized that a simpler way to do the same thing would be to use the following code. First clear the "/" at the end of the text, then clear everything after the next "/" character ("find/last" searches backward from the end):

```
clear at p/text (index? find/last p/text "/")
clear at p/text ((index? find/last p/text "/") + 1)
show p
f/data: sort append read to-url p/text "../"
show f
```

I added those changes to the current script:

```
view layout [
  p: field "ftp://user:pass@site.com/path/" [
    either dir? to-url value [
      f/data: sort append (read to-url p/text) "../"
      show f
    ] [
      editor to-url value
    ]
  ]
  f: text-list [
    ; if the user selects "../", run the code from step 3:
    either (to-string value) = "../" [
      for i ((length? p/text) - 1) 1 -1 [
        if (to-string (pick p/text i)) = "/" [
          clear at p/text (i + 1) show p
          f/data: sort append read to-url p/text "../" show f
          break
        ]
      ]
    ] [
      ; if the user selects a folder, run code from steps 1 and 2:
      either (to-string last value) = "/" [
        p/text: rejoin [p/text value] show p
        f/data: sort append read to-url p/text "../" show f
      ] [
        editor to-url rejoin [p/text value]
      ]
    ]
  ]
]
```

Now that's a useful FTP editor! We can browse through any folder and edit/save any file, just by clicking items with the mouse. I could certainly stop there, but as I used the program, more desired features kept

popping up. Next, I decided to add an image viewing feature. The thought process is simple: if a selected file is an image (jpg, png, gif, or bmp), open a new GUI window, and load/display the image. Otherwise, open the file with the text editor, as before. That's easy:

```
either find [%.jpg %.png %.gif %.bmp] suffix? value [
  view/new layout [image load to-url rejoin [p/text value]]
][
  editor to-url rejoin [p/text value]
]
```

I would occasionally click a file accidentally while browsing, so I added the following line to check whether the code above should actually be run:

```
if ((request "Edit/view this file?") = true) [(do the code above)]
```

I actually have several sites that I update regularly. It would be easy to simply copy this script several times, and change the hard coded FTP information for each web site, but I wanted a more elegant solution. I decided to add a mechanism to save and load FTP info for any website, in a config file. First I created a button in the GUI to save FTP info for a site. Here's the thought process of what should happen when the button is clicked:

1. Use a text requester to ask the user for the FTP info. I'll save it in URL format, as one line, exactly the way it's typed into the GUI text field. Use the current FTP URL typed into the text field as the default text in the requester.
2. To avoid an error, stop there if the user cancels out of the requester (i.e., doesn't enter anything).
3. Use a file requester to ask the user for a text file to save the info to (default to "%ftp.cfg").
4. Add another error check to make sure the user has actually selected a file.
5. If the file doesn't exist, create it by writing the FTP URL line to a new file.
6. If the file does exist, append the FTP URL line to the existing file.
7. Alert the user that the operation is complete.

As always with REBOL, each of those steps is extremely simple:

```
btn "Save URL" [
  url: request-text/title/default "URL to save:" p/text
  if url = none [break]
  config-file: to-file request-file/file/save %/c/ftp.cfg
  if (url <> none) and (config-file <> %none) [
    if not exists? config-file [
      write/lines config-file ftp://user:pass@website.com/
    ]
    write/append/lines config-file to-url url
    alert "Saved"
  ]
]
```

Now I need a button to load saved URLs. Here's the thought process:

1. Use a file requester to have the user select a config file (default to "%ftp.cfg")
2. Use an "either" condition to check if the file exists.
3. If the file doesn't exist, notify the user that they need to first save some URLs to a config file.
4. If the file does exist, have the user select the desired FTP information from the file (one URL line from the file). An easy way to do this is with the "request-list" function. I'll load each line in the config file into a block (use a foreach loop to read and append each line in the file to a new block), and then display that list with the request-list function. When the user selects a line from the list, I'll copy the selected line of text to the GUI text list (the original text field in this program, containing the FTP information).

Again, that's all very easy to do:

```
btn "Load URL" [
  config: to-file request-file/file %/c/ftp.cfg
```

```

either exists? config [
  if (config <> %none) [
    my-urls: copy []
    foreach item read/lines config [append my-urls item]
    if error? try [
      p/text: copy request-list "Select a URL:" my-urls
    ] [break]
  ]
][
  alert "First, save some URLs to that file..."
]
show p
focus p
]

```

I added a "focus" function to the end of the above button code, so that the user can just hit their [ENTER] key to connect to the server after selecting a URL from the config file. It makes sense that some users would expect to have "Load URL", "Save URL", and "Connect" buttons, so I also decided to add a separate "Connect" button to the GUI. Since clicking on the text field and clicking on the button both do the same thing, I created a "connect" function, so that code wouldn't need to be duplicated in the action block of each of those GUI widgets. In that function I added an error check, so that the program doesn't crash if the user types in incorrect FTP information:

```

connect: does [
  either (to-string last p/text) = "/" [
    if error? try [
      f/data: sort append read to-url p/text "../" show f
    ] [
      alert "Not a valid FTP address, or the connection failed."
    ]
  ] [
    editor to-url p/text
  ]
]

```

As I tested the code, I realized that it would be much better to increase the size of the text list and the text field, so that I could view the entire FTP URL and the listed file/folder names. 600x350 pixels works well (fits on screens with low resolution, but is big enough to see full file paths). This is how the program looks now:

```

REBOL [title: "FTP Tool"]

connect: does [
  either (to-string last p/text) = "/" [
    if error? try [
      f/data: sort append read to-url p/text "../" show f
    ] [
      alert "Not a valid FTP address, or the connection failed."
    ]
  ] [
    editor to-url p/text
  ]
]

view center-face layout [
  p: field 600 "ftp://user:pass@website.com/" [connect]
  across
  btn "Connect" [connect]
  btn "Load URL" [
    config: to-file request-file/file %/c/ftp.cfg
    either exists? config [
      if (config <> %none) [
        my-urls: copy []
        foreach item read/lines config [append my-urls item]
        if error? try [
          p/text: copy request-list "Select a URL:" my-urls
        ] [break]
      ]
    ]
  ]
]

```

As I used the program more, I recognized several additional essential features that were required. I needed to be able to: upload/download binary files, create new folders, delete, copy, rename, change permissions, and get info about existing files. I just added buttons to the existing GUI to implement each of those features. Here's my thought process and the code which does each of those things:

```
btn "Get Info" [
  p-file: to-url rejoin [p/text f/picked]
  alert rejoin ["Size: " size? p-file " Date: " modified? p-file]
]
```

```
btn "Delete" [
  p-file: to-url request-text/title/default "File to delete:"
  join p/text f/picked
```



```

    if ((confirm: request "Are you sure?") = true) [delete p-file]
    f/data: sort append read to-url p/text "../" show f
    if confirm = true [alert "File deleted"]
]

```

Renaming a file is just as easy, using the "rename" function. Again, I just added a confirmation request and notification when complete:

```

btn "Rename" [
  new-name: to-file request-text/title/default "New File Name:"
    to-string f/picked
  if ((confirm: request "Are you sure?") = true) [
    rename (to-url join p/text f/picked) new-name
  ]
  f/data: sort append read to-url p/text "../" show f
  if confirm = true [alert "File renamed"]
]

```

Copying files on an FTP server is just as easy as copying files on your local hard drive - just read and write:

```

btn "Copy" [
  new-name: to-url request-text/title/default "New Path:"
    (join p/text f/picked)
  if ((confirm: request "Are you sure?") = true) [
    write/binary new-name read/binary to-url join p/text f/picked
  ]
  f/data: sort append read to-url p/text "../" show f
  if confirm = true [alert "File copied"]
]

```

Creating a new file is as simple as writing a file with an empty string (""):

```

btn "New File" [
  p-file: to-url request-text/title/default "New File Name:"
    join p/text "ENTER-A-FILENAME.EXT"
  if ((confirm: request "Are you sure?") = true) [
    write p-file ""
  ]
  f/data: sort append read to-url p/text "../" show f
  if confirm = true [alert "Empty file created - click to edit."]
]

```

Creating a new folder on the FTP server is also done the same way as creating a folder on your hard drive. Just use the "make-dir" function:

```

btn "New Dir" [
  make-dir x: to-url request-text/title/default "New folder:" p/text
  alert "Folder created"
  p/text: x show p
  f/data: sort append read to-url p/text "../" show f
]

```

Downloading binary files is done using the "read/binary" and "write/binary" functions. I just added some code here to find the file name (separate it from the full path of the selected file), and used a requester to present that as the suggested save-to file name:

```

btn "Download" [
  file: request-text/title/default "File:" (join p/text f/picked)

```

```

l-file: next to-string (find/last (to-string file) "/")
save-as: request-text/title/default "Save as..." to-string l-file
write/binary (to-file save-as) (read/binary to-url file)
alert "Download Complete"
]

```

Uploading is also accomplished using the "read/binary" and "write/binary" functions:

```

btn "Upload" [
  file: to-file request-file
  r-file: request-text/title/default "Save as..."
    join p/text (to-string to-relative-file file)
  write/binary (to-url r-file) (read/binary file)
  f/data: sort append read to-url p/text "../" show f
  alert "Upload Complete"
]

```

Changing file permissions (i.e., read, write, and execute on Unix/Linux servers), is done using "write/binary/allow":

```

btn "Chmod" [
  p-file: to-url request-text/default rejoin [p/text f/picked]
  chmod: to-block request-text/title/default "Permissions:"
    "read write execute"
  write/binary/allow p-file (read/binary p-file) chmod
  alert "Permissions changed"
]

```

I also created a help button to display some text held in an "instructions" variable:

```

btn-help [inform layout [backcolor white text bold as-is instructions]]

```

Here's the final code for my full featured FTP application. It's a far cry from "editor ftp://..." :) I use this program regularly (a downloadable Windows .exe is available at http://musiclessonz.com/rebol_tutorial/FTP_tool.exe):

```

REBOL [title: "FTP Tool"]

Instructions: {

  Enter your username, password, and FTP URL in the text field, and
  hit [ENTER].

  BE SURE TO END YOUR FTP URL PATH WITH "/".

  URLs can be saved and loaded in multiple config files for future use.

  CONFIG FILES ARE STORED AS PLAIN TEXT, SO KEEP THEM SECURE.

  Click folders to browse through any dir on your web server. Click
  text files to open, edit and save changes back to the server.
  Click images to view. Also upload/download any type of file,
  create new files and folders, change file names, copy and delete
  files, change permissions, etc.

}

connect: does [
  either (to-string last p/text) = "/" [
    if error? try [
      f/data: sort append read to-url p/text "../" show f
    ]
  ]
]

```

```

        alert "Not a valid FTP address, or the connection failed."
    ]
    ][
        editor to-url p/text
    ]
]
view center-face layout [
    p: field 600 "ftp://user:pass@website.com/" [connect]
    across
    btn "Connect" [connect]
    btn "Load URL" [
        config: to-file request-file/file %/c/ftp.cfg
        either exists? config [
            if (config <> %none) [
                my-urls: copy []
                foreach item read/lines config [append my-urls item]
                if error? try [
                    p/text: copy request-list "Select a URL:" my-urls
                ] [break]
            ]
        ]
        ][
            alert "First, save some URLs to that file..."
        ]
        show p focus p
    ]
    btn "Save URL" [
        url: request-text/title/default "URL to save:" p/text
        if url = none [break]
        config-file: to-file request-file/file/save %/c/ftp.cfg
        if (url <> none) and (config-file <> %none) [
            if not exists? config-file [
                write/lines config-file ftp://user:pass@website.com/
            ]
            write/append/lines config-file to-url url
            alert "Saved"
        ]
    ]
]
below
f: text-list 600x350 [
    either (to-string value) = "../" [
        for i ((length? p/text) - 1) 1 -1 [
            if (to-string (pick p/text i)) = "/" [
                clear at p/text (i + 1) show p
                f/data: sort append read to-url p/text "../" show f
                break
            ]
        ]
    ]
    ][
        either (to-string last value) = "/" [
            p/text: rejoin [p/text value] show p
            f/data: sort append read to-url p/text "../" show f
        ]
        ][
            if ((request "Edit/view this file?") = true) [
                either find [%.jpg %.png %.gif %.bmp] suffix? value [
                    view/new layout [
                        image load to-url join p/text value
                    ]
                ]
                ][
                    editor to-url rejoin [p/text value]
                ]
            ]
        ]
    ]
]
]
across
btn "Get Info" [
    p-file: to-url rejoin [p/text f/picked]
    alert rejoin ["Size: " size? p-file " Date: " modified? p-file]
]
btn "Delete" [
    p-file: to-url request-text/title/default "File to delete:"
    join p/text f/picked
]

```

```

        if ((confirm: request "Are you sure?") = true) [delete p-file]
        f/data: sort append read to-url p/text "../" show f
        if confirm = true [alert "File deleted"]
    ]
    btn "Rename" [
        new-name: to-file request-text/title/default "New File Name:"
            to-string f/picked
        if ((confirm: request "Are you sure?") = true) [
            rename (to-url join p/text f/picked) new-name
        ]
        f/data: sort append read to-url p/text "../" show f
        if confirm = true [alert "File renamed"]
    ]
    btn "Copy" [
        new-name: to-url request-text/title/default "New Path:"
            (join p/text f/picked)
        if ((confirm: request "Are you sure?") = true) [
            write/binary new-name read/binary to-url join p/text f/picked
        ]
        f/data: sort append read to-url p/text "../" show f
        if confirm = true [alert "File copied"]
    ]
    btn "New File" [
        p-file: to-url request-text/title/default "New File Name:"
            join p/text "ENTER-A-FILENAME.EXT"
        if ((confirm: request "Are you sure?") = true) [
            write p-file ""
            ; editor p-file
        ]
        f/data: sort append read to-url p/text "../" show f
        if confirm = true [alert "Empty file created - click to edit."]
    ]
    btn "New Dir" [
        make-dir x: to-url request-text/title/default "New folder:" p/text
        alert "Folder created"
        p/text: x show p
        f/data: sort append read to-url p/text "../" show f
    ]
    btn "Download" [
        file: request-text/title/default "File:" (join p/text f/picked)
        l-file: next to-string (find/last (to-string file) "/")
        save-as: request-text/title/default "Save as..." to-string l-file
        write/binary (to-file save-as) (read/binary to-url file)
        alert "Download Complete"
    ]
    btn "Upload" [
        file: to-file request-file
        r-file: request-text/title/default "Save as..."
            join p/text (to-string to-relative-file file)
        write/binary (to-url r-file) (read/binary file)
        f/data: sort append read to-url p/text "../" show f
        alert "Upload Complete"
    ]
    btn "Chmod" [
        p-file: to-url request-text/default rejoin [p/text f/picked]
        chmod: to-block request-text/title/default "Permissions:"
            "read write execute"
        write/binary/allow p-file (read/binary p-file) chmod
        alert "Permissions changed"
    ]
    btn-help [inform layout[backcolor white text bold as-is instructions]]
    do [focus p]
]

```

10.8 Case 8 - Jeopardy

My fiancé wanted to create a program to help train employees at work. She hoped to create a game similar to the Jeopardy TV show, which could be played with a group of employees, in order to quiz, instruct, and interact with them in an enjoyable way. Together, we devised these specifications about how the program should work:

1. Employees are organized into 2-4 teams of players who compete against each other for prizes.
2. The program displays 5 columns of boxes, each under a separate category header. The columns of boxes are divided into rows of 5, with each row displaying incremental values of \$100, \$200, \$300, \$400, and \$500.
3. The host of the game operates the program and manages game play. To start off, one team chooses a category and a dollar amount to wager, and the host clicks the chosen box. When the box is clicked, an *answer* is displayed. The first player to respond gets a chance to determine the correct *question* for the given answer (i.e., "What is ____?"). The program then displays the proper question, along with some educational information related to the topic (the point of the program is to both test and teach the employees). The program then asks the host which player got the question correct or incorrect. The wagered amount is either subtracted or added to the player's score, based on correct or incorrect response, and a running total score is displayed in an area on the bottom of the screen.
4. After each question is completed, the chosen boxes are displayed as empty, and made unresponsive.
5. Winning teams continue to choose answers, and game play continues until all boxes are completed.
6. The program needs a way for the host to prepare and save the categories, answers, and questions required to play the game.

Most of the code required to create this program will revolve around the game screen design, so I started outlining the program with a GUI layout. I looked online for some images of the Jeopardy TV show, and with a little trial and error I came up with a design of buttons and boxes that satisfied the general required description:

```
REBOL [title: "Jeopardy"]

view center-face layout [
  backdrop effect [gradient 1x1 tan brown]
  style button button effect [
    gradient blue blue/2] 100x65 font [size: 30]
  style box box brown 100x35
  space 40x10
  across
  box 660x10 effect [gradient 1x0 brown black] ; separator line
  return
  box "Category 1"
  box "Category 2"
  box "Category 3"
  box "Category 4"
  box "Category 5"
  return
  box 660x10 effect [gradient 1x0 brown black]
  return
  button "$100" []
  button "$100" []
  button "$100" []
  button "$100" []
  button "$100" []
  return
  button "$200" []
  button "$200" []
  button "$200" []
  button "$200" []
  button "$200" []
  return
  button "$300" []
  button "$300" []
  button "$300" []
  button "$300" []
  button "$300" []
  return
  button "$400" []
  button "$400" []
  button "$400" []
  button "$400" []
  button "$400" []
  return
  button "$500" []
  button "$500" []
  button "$500" []
]
```

```

button "$500" []
button "$500" []
return
box 660x10 effect [gradient 1x0 brown black]
return tab
box "Player 1:" effect [gradient 1x1 tan brown]
player1: box white "$0" font [color: black]
box "Player 2:" effect [gradient 1x1 tan brown]
player2: box white "$0" font [color: black]
return tab
box "Player 3:" effect [gradient 1x1 tan brown]
player3: box white "$0" font [color: black]
box "Player 4:" effect [gradient 1x1 tan brown]
player4: box white "$0" font [color: black]
]

```

That looks like a lot of code, but it's all just simple VID GUI layout widgets. Next I began devising the data and logic required to make the GUI operational. First, I thought about the data required to play the game, and decided to organize all the potential questions and answers into 2 separate blocks of strings:

```

answers: [
"$100 Answer, Category 1"
"$100 Answer, Category 2"
"$100 Answer, Category 3"
"$100 Answer, Category 4"
"$100 Answer, Category 5"
"$200 Answer, Category 1"
"$200 Answer, Category 2"
"$200 Answer, Category 3"
"$200 Answer, Category 4"
"$200 Answer, Category 5"
"$300 Answer, Category 1"
"$300 Answer, Category 2"
"$300 Answer, Category 3"
"$300 Answer, Category 4"
"$300 Answer, Category 5"
"$400 Answer, Category 1"
"$400 Answer, Category 2"
"$400 Answer, Category 3"
"$400 Answer, Category 4"
"$400 Answer, Category 5"
"$500 Answer, Category 1"
"$500 Answer, Category 2"
"$500 Answer, Category 3"
"$500 Answer, Category 4"
"$500 Answer, Category 5"
]
questions: [
"$100 Question, Category 1"
"$100 Question, Category 2"
"$100 Question, Category 3"
"$100 Question, Category 4"
"$100 Question, Category 5"
"$200 Question, Category 1"
"$200 Question, Category 2"
"$200 Question, Category 3"
"$200 Question, Category 4"
"$200 Question, Category 5"
"$300 Question, Category 1"
"$300 Question, Category 2"
"$300 Question, Category 3"
"$300 Question, Category 4"
"$300 Question, Category 5"
"$400 Question, Category 1"
"$400 Question, Category 2"
"$400 Question, Category 3"
"$400 Question, Category 4"
"$400 Question, Category 5"
"$500 Question, Category 1"

```

```

    "$500 Question, Category 2"
    "$500 Question, Category 3"
    "$500 Question, Category 4"
    "$500 Question, Category 5"
]

```

I also needed variable labels for the category headers (so that they could be edited later by the host, without having to edit any program code):

```

Category-1: "Category 1"
Category-2: "Category 2"
Category-3: "Category 3"
Category-4: "Category 4"
Category-5: "Category 5"

```

To manage game play, I realized that every button would do basically the same thing when clicked, so I created a function which would run in the action block of each button. If each button sent a unique number ID to the function, it would be easy to map each question/answer in the blocks above to individual buttons:

```

do-button: func [num] [
    ; "num" refers to the unique number parameter sent by each
    ; individual button, every time this function is executed:
    alert pick answers num
    alert pick questions num
]

```

The questions/answers in the data blocks above are arranged so that every 5 items are incremented by \$100. I added the following code to assign a dollar amount to the chosen question, based on which "num" value was passed by the button (questions 1-5 = \$100, 6-10 = \$200, etc.):

```

if find [1 2 3 4 5] num [val: $100]
if find [6 7 8 9 10] num [val: $200]
if find [11 12 13 14 15] num [val: $300]
if find [16 17 18 19 20] num [val: $400]
if find [21 22 23 24 25] num [val: $500]

```

Now I just need to ask the host which player responded correctly or incorrectly to the alerted answer above, and assign a variable to the response ("correct"):

```

correct: request-list "Select:" [
    "Player 1 answered correctly" "Player 1 answered incorrectly"
    "Player 2 answered correctly" "Player 2 answered incorrectly"
    "Player 3 answered correctly" "Player 3 answered incorrectly"
    "Player 4 answered correctly" "Player 4 answered incorrectly"
]

```

... and then update the score display boxes based on the response above:

```

switch correct [
    "Player 1 answered correctly" [
        player1/text: to-string ((to-money player1/text) + val)
        show player1
    ]
    "Player 1 answered incorrectly" [
        player1/text: to-string ((to-money player1/text) - val)
        show player1
    ]
    "Player 2 answered correctly" [

```

```

        player2/text: to-string ((to-money player2/text) + val)
        show player2
    ]
    "Player 2 answered incorrectly"[
        player2/text: to-string ((to-money player2/text) - val)
        show player2
    ]
    "Player 3 answered correctly" [
        player3/text: to-string ((to-money player3/text) + val)
        show player3
    ]
    "Player 3 answered incorrectly" [
        player3/text: to-string ((to-money player3/text) - val)
        show player3
    ]
    "Player 4 answered incorrectly"[
        player4/text: to-string ((to-money player4/text) - val)
        show player4
    ]
    "Player 4 answered correctly" [
        player4/text: to-string ((to-money player4/text) + val)
        show player4
    ]
]

```

I added that function (with a unique incremented number argument) to the action block of every button. I also added the code to erase the face and disable each button after it's been used:

```

button "$100" [face/feel: none face/text: "" do-button 1]
button "$100" [face/feel: none face/text: "" do-button 2]
button "$100" [face/feel: none face/text: "" do-button 3]
.
.
.

```

I now have a working game according to the specified outline:

```

REBOL [title: "Jeopardy"]

answers: [
    "$100 Answer, Category 1"
    "$100 Answer, Category 2"
    "$100 Answer, Category 3"
    "$100 Answer, Category 4"
    "$100 Answer, Category 5"
    "$200 Answer, Category 1"
    "$200 Answer, Category 2"
    "$200 Answer, Category 3"
    "$200 Answer, Category 4"
    "$200 Answer, Category 5"
    "$300 Answer, Category 1"
    "$300 Answer, Category 2"
    "$300 Answer, Category 3"
    "$300 Answer, Category 4"
    "$300 Answer, Category 5"
    "$400 Answer, Category 1"
    "$400 Answer, Category 2"
    "$400 Answer, Category 3"
    "$400 Answer, Category 4"
    "$400 Answer, Category 5"
    "$500 Answer, Category 1"
    "$500 Answer, Category 2"
    "$500 Answer, Category 3"
    "$500 Answer, Category 4"
    "$500 Answer, Category 5"
]

```



```

questions: [
  "$100 Question, Category 1"
  "$100 Question, Category 2"
  "$100 Question, Category 3"
  "$100 Question, Category 4"
  "$100 Question, Category 5"
  "$200 Question, Category 1"
  "$200 Question, Category 2"
  "$200 Question, Category 3"
  "$200 Question, Category 4"
  "$200 Question, Category 5"
  "$300 Question, Category 1"
  "$300 Question, Category 2"
  "$300 Question, Category 3"
  "$300 Question, Category 4"
  "$300 Question, Category 5"
  "$400 Question, Category 1"
  "$400 Question, Category 2"
  "$400 Question, Category 3"
  "$400 Question, Category 4"
  "$400 Question, Category 5"
  "$500 Question, Category 1"
  "$500 Question, Category 2"
  "$500 Question, Category 3"
  "$500 Question, Category 4"
  "$500 Question, Category 5"
]

do-button: func [num] [
  alert pick answers num
  alert pick questions num
  if find [1 2 3 4 5] num [val: $100]
  if find [6 7 8 9 10] num [val: $200]
  if find [11 12 13 14 15] num [val: $300]
  if find [16 17 18 19 20] num [val: $400]
  if find [21 22 23 24 25] num [val: $500]
  correct: request-list "Select:" ["Player 1 answered correctly"
    "Player 1 answered incorrectly" "Player 2 answered correctly"
    "Player 2 answered incorrectly" "Player 3 answered correctly"
    "Player 3 answered incorrectly" "Player 4 answered correctly"
    "Player 4 answered incorrectly"
  ]
  switch correct [
    "Player 1 answered correctly" [
      player1/text: to-string ((to-money player1/text) + val)
      show player1
    ]
    "Player 1 answered incorrectly" [
      player1/text: to-string ((to-money player1/text) - val)
      show player1
    ]
    "Player 2 answered correctly" [
      player2/text: to-string ((to-money player2/text) + val)
      show player2
    ]
    "Player 2 answered incorrectly"[
      player2/text: to-string ((to-money player2/text) - val)
      show player2
    ]
    "Player 3 answered correctly" [
      player3/text: to-string ((to-money player3/text) + val)
      show player3
    ]
    "Player 3 answered incorrectly" [
      player3/text: to-string ((to-money player3/text) - val)
      show player3
    ]
    "Player 4 answered incorrectly"[
      player4/text: to-string ((to-money player4/text) - val)
      show player4
    ]
    "Player 4 answered correctly" [

```

```

        player4/text: to-string ((to-money player4/text) + val)
        show player4
    ]
]

view center-face layout [
    backdrop effect [gradient 1x1 tan brown]
    style button button effect [
        gradient blue blue/2] 100x65 font [size: 30]
    style box box brown 100x35
    space 40x10
    across
    box 660x10 effect [gradient 1x0 brown black] ; separator line
    return
    box "Category 1"
    box "Category 2"
    box "Category 3"
    box "Category 4"
    box "Category 5"
    return
    box 660x10 effect [gradient 1x0 brown black]
    return
    button "$100" [face/feel: none face/text: "" do-button 1]
    button "$100" [face/feel: none face/text: "" do-button 2]
    button "$100" [face/feel: none face/text: "" do-button 3]
    button "$100" [face/feel: none face/text: "" do-button 4]
    button "$100" [face/feel: none face/text: "" do-button 5]
    return
    button "$200" [face/feel: none face/text: "" do-button 6]
    button "$200" [face/feel: none face/text: "" do-button 7]
    button "$200" [face/feel: none face/text: "" do-button 8]
    button "$200" [face/feel: none face/text: "" do-button 9]
    button "$200" [face/feel: none face/text: "" do-button 10]
    return
    button "$300" [face/feel: none face/text: "" do-button 11]
    button "$300" [face/feel: none face/text: "" do-button 12]
    button "$300" [face/feel: none face/text: "" do-button 13]
    button "$300" [face/feel: none face/text: "" do-button 14]
    button "$300" [face/feel: none face/text: "" do-button 15]
    return
    button "$400" [face/feel: none face/text: "" do-button 16]
    button "$400" [face/feel: none face/text: "" do-button 17]
    button "$400" [face/feel: none face/text: "" do-button 18]
    button "$400" [face/feel: none face/text: "" do-button 19]
    button "$400" [face/feel: none face/text: "" do-button 20]
    return
    button "$500" [face/feel: none face/text: "" do-button 21]
    button "$500" [face/feel: none face/text: "" do-button 22]
    button "$500" [face/feel: none face/text: "" do-button 23]
    button "$500" [face/feel: none face/text: "" do-button 24]
    button "$500" [face/feel: none face/text: "" do-button 25]
    return
    box 660x10 effect [gradient 1x0 brown black]
    return tab
    box "Player 1:" effect [gradient 1x1 tan brown]
    player1: box white "$0" font [color: black]
    box "Player 2:" effect [gradient 1x1 tan brown]
    player2: box white "$0" font [color: black]
    return tab
    box "Player 3:" effect [gradient 1x1 tan brown]
    player3: box white "$0" font [color: black]
    box "Player 4:" effect [gradient 1x1 tan brown]
    player4: box white "$0" font [color: black]
]

```

After playing the game a bit, there were no bugs, but I realized that it could use a few additional features. First, I used the binary resource embedder from earlier in this tutorial to create an image header of a photo I found online from the Jeopardy TV show:

```

header: load to-binary decompress 64#{
eJyVj3s804v/xz/bzGyFucRGohgmlziuuU7CNGxWuTaxbBpyLVJUpItLcyfXNIZI
jkuJboqFJJsNodG9uuXryya18ncfj93t8//4+3/+9X6/H6/1+bY1ufQKQzg5ODgAI
BAIo2wNsJQE4QFQEKgoVERWFisJgomIiJAIBhyNkJSR3IuVlUsh5Wtk5BSWmsOKi
6m45ORVtFVV1DawWFq2so6+jqY/RxGr+GwKCwWAIMYQMAigjqScNoPk/s/UMkBiD
dAEmBLQPAEuBIFKgrZeAigBAQP8C/D/bT4qIbs+3xUNIAASGgiFQsNhOKPrfEQSG
Ant1pKT3wmQMxGT32br7X5JHHTAKiGCW75JTNbQjkk6GZzYOqG163Hl++UrSA952
jAIIAEH/e2AbMACCbMdsA5pSABgMgkBEwJD/c4DAAERKRNpAZq8tdJ+7PzHc71L5
gy0BSHPbAJaCSAHwWnfKVxP98V4tOkWdfD7FEjacdjSkarU//C/n4IDH8tIsGPlr
F8jSOHVpqlEgNs++1taBHGuEkzY4eM/ojEII4R/1Q+ZIEH2QWTpkVWn+ntRBthgZ
kympJr8jt/eRTxvTS1RNGD3meRMcm4kAZ2CAnTULVlJf1feI8BVvJWeJaNZitC7j
HSzwe21RvYdfbQEZcgNoufW05RxBPLziaGaLDnMiIu5cgjXhKavuH/3ewXQVtg6Q
BLgRCGfHVNfMn6LPf/fJDI1/TejRG5NB2X8vi01llhEm3Fb/XnK+KeG/sKxkl6Py
E3ZteGrG4qppYSazc72YsFrY6n0ht0oo2EEs4dhdJjJvOThxbRVx3ruRD921c4ct
XXp89nPCl1Ikh1ZwlkpVLRz53sKF8WfDpRW0V7dePB2671umDPyzp0PJxcKwXbHc
pTnsOjTC54hLNXHdWIVdxd19pDKhqNWOrCdNu3LPTh8e6tlxg9pQZw/KFHWY2OGM
Z33g/Y140axOK5pkwP2FSiCj0RhPPofjhXBtt52xdJjhjMZC9IMH+GNXzhlmhiJ6
fGjvfqN11IHPvdV686aDXaIb6tn6gH1kYnlbpyM5Fi6c6cIsFn391XJXLYbMmRTv
soo4Nv7eqf/Byy2ANn2FByPx1Xt8KZQEjhr08GMzINfiQIfbVT7HI4YKYlv/MRP
bv94klJMSbsZATZ0lnwEa64bdZBL/dz6iEm1v1FwwpnNoCoplqla0drmb70Sd/H1
sz9ijEDcfSc3TrdMbtAs3ZOg0+s96CofOOEnUod2Xqo2Ty1A/5xW1LtJzLNtp8vs
1UwD/YqprdJffrIwcdFhwvmr+CKmQDfT+P2R2AvoJAzZ4RitnkWq00z74hIujcx1
Mzh420ioCCKVxeU3Ze4LhSjNyZyt72K7Xrxlyf0plTZX2MX1rulNBYG1Uc2umsfJ
9fPvBnVHGUeACRImNyxX74XvEyg79i/XIB/bfXsPlDChf7003rV/mvFg3u344qJ6
8IDbp3PMP47rJyasP1i1lwgX3yT4Zzh8dPzt1lElr3yH+6TqFHKa0UL1S3gtZBPE
oj41Dr4sEL91rb7w12Lg5jL3+g8+L+V5QmpvPdnGOED5HQNZnxvqubX52yVriGraQ
t06Jrj6r7imhjdzFQqA3yqLzMDmjNeevW4rluGeg03qjg5oeh8z8EE0fVZ7+TelY
e3W27vblk7f1nIP9tWUx+PCf150zdzXALUJViesptLVw1les2qRi0C0KawvonDkS
0zL7bfgZvd+C5RxyaI+NmlSmpC36BtZYZsVXrEgGDPrIzSG/uVbdKpq2Dcr1Pyi
N42GS+7PFLRyYffvkrYAZeOf6SN31IrlRJfPpgUQok531brErr+803Wn81LXOyzc
bNkDgxT0n0PxnGhFDEeBBES3nirrFOlQfMk1ZaTK+10ZkzuhnKYwWElxeMtoRuA
m1188t34vrAtIIR9quLENPsJkebltLCELN50PXG+jtoA74lKjV7Wr30c3Az4bqHH
fC+6atqPZVOY5d5DeF5My+8XnELv+nu97Rt08WoK2HySEbXy6rSNWuimAyaJS7A6
SX0ou0A3F0RV4b2KuCabPbAT8W5z54Vty8Izbu7qnrLNNLxwflHB5liKIqWUNJ90
UfHge9e0PKqdz/zrQxifKoPGRGGVylrq3QXxlbRaHMTv11ezce038aWZYhJPuMJH
ejSw/FUCKXptlhuR899Au2Lnd/fl/tDL75bbTwxWxWELbRTCUw+KEEO4+xf+yK7
3NIwRBDsOyJweXaOzW5N2+4XZNvQ8G1lt3u37tUzZQKfQtWQdgLrxKIsAlpsf6tD
o/ZAtHwp++FX7lndP1t88Jk0P6Rhaytfj1lr5fos47hqjFXgyu3S1PEfY9U/P058
QWn5uLJ7wslYbYFUsvopb0qbc/Nnm7CRPWdKT7sQuDHzpfn5uRG+T86/YcEu3Hrt
qNEbH/QR/R0a0GSdJJ31FmDdk2+Vrw2R/IrOT3wZ3zliXC5Qzz5s5/XnCsqu3Ryv
RyQmaybczOGgx6KGS0+DCivDV/LMjJpNtDiBbQ1wOFQtCMMkZZ2lr+++T2P02ZpG
riura80pOBz1xXNgZhgo0q4p3T6ePqo/9ojap3RR5kcx41Jp9ustIK5ctU1T/Zsb
SqOttfW3g+LDtANDVTJz3ZW78YyWXH4z+5MatFYdaTpNZtaOeCzr0gsqN9pkqlnB
aJE5SAux9MS4hQRy8gt+7QTuz+hSoPD+StBsxmHcpWWzji2A+PlddStmXqvT1d7D
It5HXH6KH6UkVzP4LFPesul65Bzn7PU8M+Eeca0dcPOOR8hk2tBMbjm1GnG6Th4P
bTaewuxw9UHqx6WXDQZ1QgV1Wfvt0esmCRs35Onlp7W1RHe+rRTwm3ees/YJwTX1
7seY44NCcNbGVr4UV7kQr2W7n+w+J+LEqePRR6qbW9KcsOJ31RuuNGmaedb2fnia
6r+SRnLzuwMnTD0nWOqHS+iGR0zPl9NCc3fVwrTvo/6EMAQHowN3/SQZuBn+85z0
A5Qn0pwjxFWWaw5bnzpbTHGiBzh3eZu03bPe4ffgx8rpjoET1/GxCwpXrQ0rUNZI
/GzFqw/+umAS0bYUePotMSieKOYANUqvjVot/dJ12R8VWFsLYeUcT6hG/LbnCQaWu
nYh71cfoGmh0uLEmJHaJoedAYNc79Jq4fcZ13veLs3UOnW8efhb3IANW1UaGEXz6
SOqrnr5OXQ91GobK/1kkW0UBoaYmWLUk0i5ssklkr21+Yb53rXgFBIOdMpsShr70h
l/ejIBs3xoZzsiML7GchNCTryNM5U3ulWxKJdfcCM+MSQKBzCHP5127zTafCJwTB
ODP3kch3oNnHd6pC/nY/mV99Rv1tdJ6ClirctOvPIGHoxqMuuK+OWNgib6At5uzn
hDUjZBUH45SPH50uEPDDVJsQc3AvvfEGL+magCbq2xieplZX3ayThenXi9+g4dfh
7315xFvLRDRuVMFD1vLgr+e/bK6GIV6m/XJ7pBB8iLQo/iu63OmYtppIog038vOe
M0QcNEPH7Ds4A1rpyAGrL/tc0y41DdT3jHISLyblw0K38rcmQRJwaRHRX9ZPT6Y/
kzCWO9z6mFnaBuOHBH/rVhqrMcQXkE0JBz7nD3ziZVdpWE35yFO9Tq4Fz8T51Wjk
U1qQiR0I1OBDbpzMP1jyzuVxCgmbtOHcvf1M3HK51PbPNYf1oj2/U72/z1+UOsEj
SsbQVq/tcZMeKOMHTdJIXKZ3KaxBN7veuhaPRHBWpofxGGz2ksnNHPP1fguPGHfj
r/NsDNaRd5VnDHF8s5byWoA6TG5atr7hkLEfVbyTuc6X6PR6eHpj4CyLau5BBRl2
d1WP2QJSHD7ouDj3hiskzdk2zN5mlIep3NXEgk5zuwNas4+s5hvwI9ck90b4FtBD
iSSWDqbmQ2IS6F1sEbJ9RxI+Y4V7c3HQSmqh414Vmhb0GTMMnrRjD8cyUiouJjHT
kyuWUSMHnnAXTzE3nkbF6X/2ezD1aHCjwNdZ691/ABEeZGXyCwAA
}

```

Adding it to the top of the GUI was this easy. I didn't edit the image to fit, but instead just used REBOL's built in ability to simply resize the image:

```
image header 660x40
```

Next, I decided to add an option to resize the entire GUI, so that the program could run on computers with varied screen resolutions. I looked through all the GUI code and realized that all the widget sizes were divisible by a factor of 5, I stored that as a variable word "sizer":

```
sizer: 5
```

Then, anywhere in the GUI where there was a sizing pair, I added a little math calculation to dynamically specify the size. The image size above (660x40), for example, was written as follows:

```
image header (to-pair rejoin [(132 * sizer) "x" (8 * sizer)])
```

Tabs and pad sizes were set like this:

```
tabs (sizer * 20)
pad (sizer * 2)
```

With those sizing calculations added to every widget, all the host needed to do was change the one sizer variable, and the whole pixel size of the game would be adjusted.

Next, I realized that the host could potentially make mistakes in game play (I did while testing the program), so I wanted a way to manually adjust game scores. I added the following code to the action block of the score boxes, which allows the host to click on the box, and enter a new value to be shown on the box's face:

```
player1: box white "$0" font [color: black size: (sizer * 4)] [
  face/text: request-text/title/default "Enter Score:" face/text
]
```

According to the last item in our specification outline, all I need now is a way for the host to edit and save game data. I started by assigning a variable to all the code that contained variables which the host should be able to edit. I wanted this code to be writable to the hard drive, and "do"able, so I stored it as a text string and included a REBOL header:

```
config: {
  REBOL [ ]
  ;_____

  sizer: 5

  Category-1: "Category 1"
  Category-2: "Category 2"
  Category-3: "Category 3"
  Category-4: "Category 4"
  Category-5: "Category 5"

  answers: [
    "$100 Answer, Category 1"
    "$100 Answer, Category 2"
    "$100 Answer, Category 3"
    "$100 Answer, Category 4"
    "$100 Answer, Category 5"
    "$200 Answer, Category 1"
```

```

"$200 Answer, Category 2"
"$200 Answer, Category 3"
"$200 Answer, Category 4"
"$200 Answer, Category 5"
"$300 Answer, Category 1"
"$300 Answer, Category 2"
"$300 Answer, Category 3"
"$300 Answer, Category 4"
"$300 Answer, Category 5"
"$400 Answer, Category 1"
"$400 Answer, Category 2"
"$400 Answer, Category 3"
"$400 Answer, Category 4"
"$400 Answer, Category 5"
"$500 Answer, Category 1"
"$500 Answer, Category 2"
"$500 Answer, Category 3"
"$500 Answer, Category 4"
"$500 Answer, Category 5"
]
questions: [
"$100 Question, Category 1"
"$100 Question, Category 2"
"$100 Question, Category 3"
"$100 Question, Category 4"
"$100 Question, Category 5"
"$200 Question, Category 1"
"$200 Question, Category 2"
"$200 Question, Category 3"
"$200 Question, Category 4"
"$200 Question, Category 5"
"$300 Question, Category 1"
"$300 Question, Category 2"
"$300 Question, Category 3"
"$300 Question, Category 4"
"$300 Question, Category 5"
"$400 Question, Category 1"
"$400 Question, Category 2"
"$400 Question, Category 3"
"$400 Question, Category 4"
"$400 Question, Category 5"
"$500 Question, Category 1"
"$500 Question, Category 2"
"$500 Question, Category 3"
"$500 Question, Category 4"
"$500 Question, Category 5"
]
; _____
}

```

To use that code in normal game play, I just executed the code contained in the "config" variable:

```
do config
```

Next, I outlined some pseudo code describing each step the host might go through to edit the config data:

1. Warn the host that these steps will erase the current data and end the current game. A simple requester and if condition will serve this purpose. Break out of the current block of code if they choose to continue the game.
2. Before going through the process of editing/saving, request if the user would simply like to load a previously edited configuration file. If so, just run ("do") the chosen config file, close the current GUI, and rerun the GUI using the new config data.
3. If the user hasn't chosen either of the previous options, give them some directions about how to edit the file, save the default config code to a file, and open it in the built in editor. After the editor has been closed, request a config file to load, then close the current GUI and rerun it using the newly chosen config data.

Here's the code I created to satisfy each of the above steps:

```
; step 1

contin: request/confirm {
    This will end the current game.  Continue?}
if contin = false [break]

; step 2

loadoredit: request/confirm "Load previously edited config file?"
if loadoredit = true [
    do to-file request-file/title/file {
        Choose config file to use:} "File" %default_config.txt
    unview
    view center-face layout gui
    break ; needed so that step 3 doesn't run
]

; step 3

alert {Edit carefully, maintaining all quotation marks.
    You can open a previously saved file if needed.
    When done, click SAVE-AS and then QUIT.
    Be sure choose a filename/folder
    location that you'll be able to find later.
}
write %default_config.txt config
unview
editor %default_config.txt
alert {Now choose a config file to use (most likely the file
    you just edited).}
do to-file request-file/title/file {
    Choose config file to use:} "File" %default_config.txt
view center-face layout gui
```

I added that code to the action block of the header image. Now the host can click the header to edit and save all the data for category, answer, question, and GUI size required to store complete Jeopardy sessions. I packaged this final program using XpackerX and gave it to my fiance. It suits her needs perfectly:

```
REBOL [title: "Jeopardy"]

config: {

    REBOL []

    ;_____

    sizer: 4

    Category-1: "Category 1"
    Category-2: "Category 2"
    Category-3: "Category 3"
    Category-4: "Category 4"
    Category-5: "Category 5"

    answers: [
        "$100 Answer, Category 1"
        "$100 Answer, Category 2"
        "$100 Answer, Category 3"
        "$100 Answer, Category 4"
        "$100 Answer, Category 5"
        "$200 Answer, Category 1"
        "$200 Answer, Category 2"
        "$200 Answer, Category 3"
        "$200 Answer, Category 4"
        "$200 Answer, Category 5"
```

```

"$300 Answer, Category 1"
"$300 Answer, Category 2"
"$300 Answer, Category 3"
"$300 Answer, Category 4"
"$300 Answer, Category 5"
"$400 Answer, Category 1"
"$400 Answer, Category 2"
"$400 Answer, Category 3"
"$400 Answer, Category 4"
"$400 Answer, Category 5"
"$500 Answer, Category 1"
"$500 Answer, Category 2"
"$500 Answer, Category 3"
"$500 Answer, Category 4"
"$500 Answer, Category 5"
]
questions: [
"$100 Question, Category 1"
"$100 Question, Category 2"
"$100 Question, Category 3"
"$100 Question, Category 4"
"$100 Question, Category 5"
"$200 Question, Category 1"
"$200 Question, Category 2"
"$200 Question, Category 3"
"$200 Question, Category 4"
"$200 Question, Category 5"
"$300 Question, Category 1"
"$300 Question, Category 2"
"$300 Question, Category 3"
"$300 Question, Category 4"
"$300 Question, Category 5"
"$400 Question, Category 1"
"$400 Question, Category 2"
"$400 Question, Category 3"
"$400 Question, Category 4"
"$400 Question, Category 5"
"$500 Question, Category 1"
"$500 Question, Category 2"
"$500 Question, Category 3"
"$500 Question, Category 4"
"$500 Question, Category 5"
]

;_____

}

do config

header: load to-binary decompress 64#{
eJyVj3s804v/xz/bzGyFucRGohgmlziuuU7CNGxWuTaxbBpyLVJUpItLcyfXNIZI
jkuJboqFJsNodG9uuXRYya18ncfj93t8//4+3/+9X6/H6/1+bYlufQKQzg5ODgAI
BAIo2wNsJQE4QFQEKgoVERWFisJgomIIJAIBhyNkJSR3IuVlUSh5Wtk5BSWMsoKi
6m45ORVtFVV1DawWFq2so6+jqY/RxGr+GwKCwWAIMYQMAiGjqSCnoPk/s/UMkBiD
dAEmBLQPAEuBIFKgrZeAIgBAQP8C/D/bT4qIbs+3xUNIAASGgiFQsNhOKPRfEQSG
ANtlpKT3wmQMxGT32br7X5JHHTAKiGCW75JTNbQjkk6GZzyOqGL63Hl++Ursa952
jAIIAEH/e2AbMACCbMdsas5pSABgMgkBEWJD/c4DAAERKRNpAZq8tdJ+7PzHc7lL5
gy0BsHPbAJaCSAHWwNFKVxP98V4tOkWdFD7FEjacdjSkarU//C/n4IDH8tIsGPlr
F8jSOHVpqLEgNs++ltaBHGuekzY4eM/ojEII4R/lQ+ZIEH2QWtpkVWn+ntRBthgZ
kypmJr8jt/eRtxvTS1RNGD3meRMcm4kAZ2CANTULVlJf1feI8BVvJWeJanZitC7j
HSzwe2lRvYdfbQEZcgNoufW05RxBPLziaGaLDnMiIu5cgjXhKavuH/3ewXQVtg6Q
BLgRCGFHVnFm6LPP/fJDI1/TejRG5nB2X8vi0llhhEm3Fb/XnK+KeG/sKxkl6Py
E3ZteGrG4qqpYSazc72YsFrY6n0ht0oo2EEs4dhdJjJvOThxbRVx3ruRD921c4ct
XXp89nPCLlIkhlZwlkpVLRz53sKF8WfDpRW0V7dePB267lumDPyzp0PJxckwXbHc
pTnSOjTC54hLNXHdWIVdxdI9pDKHqNWOrCdNu3LPTTh8e6tLxg9pQZw/KFHWY20GM
Z33g/Y140axOK5pkwP2FSiCj0RhPPofjhxBtt52xdJjhjMZC9IMH+GNXzhlmhiJ6
fGjVfqN1lIHPvdV686aDXaIb6tn6gHlkYn1bpyM5Fi6c6cIsFn39lXJXlybMmRTv
soo4Nv7eqf/Byy2ANn2FByPxt1Xt8KZQejhR08GMzINfiQifBVT7HI4YKYlv/MRP
bv94klJMSbsZATZOlNwEa64bdZBL/dZ6iEmlv1FwwpnNoCoplqla0drmb70sd/H1
sZ9ijEDcfSc3TrdMbtAs3ZOg0+s96CofOOEnUod2Xqo2Tyla/5xw1LtJzLntp8vS
1UwD/YqprdJffrIwcdFhwvmr+CKMQDfT+P2R2AvoJAzZ4RItknwq00z74hIuJcx1

```

```

Mzh420ioCCKVxeU3Ze4LhSJNyZYt72K7Xrxlyf0p1TZX2MXlru1NBYgLUC2umsfJ
9fPvBnVHGUEaCRImNyxX74XvEyg79i/XIB/bfxsP1DCbf7003rV/mvFg3u344qJ6
8IDbp3PMP47rJyasP1iilwgX3yT4Zzh8Dpzt1lElr3yH+6TqFHKa0ULlS3gtzBPE
oJ4lDr4sEL9lrb7w2lG5jL3+g8+L+V5QmpvPdnGOED5HQNZNxxvqubX52yVriGraQ
tO6Jrj6r7imhjdZfQqA3yqLzMDmjNeevW4r1uGeg03qjg5oeH8z8EE0fVZ7+Tely
e3W27vblK7f1nIP9tWUx+PCf150zdzXALUUVIesptLVwlles2qRi0C0KawvonDkS
0zL7bfgZvd+C5RxyaI+NmlSmpC36BtZYzsvXrEgGDPrlzSG/uVbdKpq2DcrlPyi
N42GS+7PFLRyYffvkrYAZe0f6SN3lIr1RJfPpgUQok53lbrErr+803Wn8lLXOyzc
bNkDgxT0n0PxnGhFDEeBBES3nirrFOlQfMk1ZaTK+1OZkzuhnKYwwElxeMtoRUa
m1188t34vrAtIIR9quLENPsjKebLtLCe1N50PXG+ jtoA74lKjV7Wr3Oc3Az4bqHH
fc+6atqPZVOY5d5DeF5My+8XnELv+nu97Rt08WoK2HySEbXy6rSNWuimAyaJS7A6
SX0ou0A3F0RV4b2KuCabPbAT8W5z54Vty8Izbu7qnrLNNLxwflLHB5liKIqWUNJ90
UfHge9e0PKQdZ/zrQxifKoPGRGGVylrq3QXxlbRaHMTv1lezcce038aWZYhJPuMJH
ejSw/FUCKXptlhuR899Au2Lnd/fltDL75bbTwXWELbRTCUw+KEEO4+x4f+yK7
3NIWrbDSoyJweXaOzW5N2+4XZNVQ8GIlt3u37tUzZQKfQtWQdgLrxKIsAlpsf6tD
o/ZAtHwp++FX7lndPlt88Jk0P6Rhaytfjllr5fos47hqjFXgyu3S1PEfY9U/P058
QWn5uLJ7wsllybFYUsvopb0qbc/Nnm7CRPWdKT7sQuDHZpfn5uRG+T86/YcEu3Hrt
qNEBH/QR/R0a0GSdJJ3lFmDdk2+Vrw2R/IrOT3wZ3zliXC5Qzz5s5/XnCsqU3Ryv
RyQmaybczOGgx6kGS0+DCivDV/LMjJpNtDiBbQlwoFQtCMMkZZ2lR+++T2P02ZPG
riura80pOBzlxXNgZhgo0q4p3T6ePqo/9ojap3RR5kcx41Jp9ustIK5ctU1t/Zsb
SqOttfW3g+LDtANDVTJz3ZW78YyWXH4z+5MatFYdaTpNZtaOeCzr0gsqN9pkqlnB
aJE5SAUx9MS4hQRY8gt+7QTuz+hsOPD+StBsxmHcpWWzji2A+PlddStmXqvTld7D
It5HXH6KH6UkVzP4LFPesul65Bzn7PU8M+Eeca0dcPOOR8hk2tBMbjMlGnG6Th4P
bTaewuxw9UHqx6WXDQZlQgVlWfvt0esmCRS35Onlp7WlRHe+rRTwm3ees/YJwTX1
7seY44NCcNbGvR4UV7kQr2W7n+w+J+LEqePRR6qbW9KcsOJ3lRuuNGmaedb2fnia
6r+SRNLzuwMnTD0nWOQHs+iGR0zPl9NCc3fvwrTvo/6EMAQHowN3/SQZuBn+85z0
A5Qn0pwjxFWWaw5bnzpBTHGiBzh3eZu03bPe4ffgx8rpjoETl/GxCwpXrQ0rUNzI
/GzFqW/+umASObYoPoTMSieKOYANUqVjVot/dJl2R8VWFsLYeUcT6hG/LbnCQaWu
nYh7lcf0GmhOulEmjHajoedAYNc79Jq4fcZl3veLs3U0nW8efhb3IANWlUaGEXz6
SOqrnr5OXQ9lGobK/1kkW0UBoayMwLUK0i5ssklkr2l+Yb53rXgFBIODmpShr70h
l/ejIBs3xoZsziML7GcHNCtryNM5U3ulWxKJdFcCM+MSQKBzcHP5l27zTafCJWtB
ODP3kcH3oNnHd6pC/nY/mV99Rv1tdJ6ClirctOvPIghOXqMuuK+OWNgib6At5uzn
hDUjZBUH45SPH50uEPDDVJsQc3AvvfEGL+magCbq2xieplZX3ayTbenXi9+g4dfh
73l5xFLRDRUvMFD1vLgr+e/bK6GIV6m/XJ7pBB8iLQo/iu63OmYtppIog038vOe
M0qCnEPH7Ds4AirpYAGrL/tc0y4lDdt3jHisLyblwOK38rcmQRJwaRHrX9ZPT6Y/
kzCWO9z6mFnaBuOHBH/rVhqrMcQXkE0JBz7nD3ziZVdpWE35yFO9Tq4Fz8T5lWjk
U1qQiR0I1OBDbpzMpLjyzuVxCgmbtOHcvf1M3HK5lPbPNYf1oj2/U72/zl+UOsEj
SsbQVq/tcZMeKOMHTdJIxKZ3KaxBN7veuhaPRHBWpofxGGz2ksnNHPP1fguPGhfj
r/NSdNard5VnDHF8s5byWOa6TG5atr7hkLEfVbyTuc6X6PR6eHpj4CyLau5BBRl2
dlwP2QJSHD7ouDj3hiskzdk2zN5mlIep3NXEgk5zuwNas4+s5hvwI9ck90b4FtBD
iSSWqbmQSD7IS6FISeBj9Rxi+Y4V7c3HQSmqh4l4Vmbb0GTMNnrRjD8cyUiouJjHT
kyuWUSMHnnAXTzE3nkbF6X/2ezDlaHCjwNdz691/ABEEZGXyCwAA
}

do-button: func [num] [
    alert pick answers num
    alert pick questions num
    if find [1 2 3 4 5] num [val: $100]
    if find [6 7 8 9 10] num [val: $200]
    if find [11 12 13 14 15] num [val: $300]
    if find [16 17 18 19 20] num [val: $400]
    if find [21 22 23 24 25] num [val: $500]
    correct: request-list "Select:" ["Player 1 answered correctly"
    "Player 1 answered incorrectly" "Player 2 answered correctly"
    "Player 2 answered incorrectly" "Player 3 answered correctly"
    "Player 3 answered incorrectly" "Player 4 answered correctly"
    "Player 4 answered incorrectly"
    ]
    switch correct [
        "Player 1 answered correctly" [
            player1/text: to-string ((to-money player1/text) + val)
            show player1
        ]
        "Player 1 answered incorrectly" [
            player1/text: to-string ((to-money player1/text) - val)
            show player1
        ]
        "Player 2 answered correctly" [
            player2/text: to-string ((to-money player2/text) + val)
            show player2
        ]
        "Player 2 answered incorrectly"[

```



```

        player2/text: to-string ((to-money player2/text) - val)
        show player2
    ]
    "Player 3 answered correctly" [
        player3/text: to-string ((to-money player3/text) + val)
        show player3
    ]
    "Player 3 answered incorrectly" [
        player3/text: to-string ((to-money player3/text) - val)
        show player3
    ]
    "Player 4 answered incorrectly"[
        player4/text: to-string ((to-money player4/text) - val)
        show player4
    ]
    "Player 4 answered correctly" [
        player4/text: to-string ((to-money player4/text) + val)
        show player4
    ]
]

view center-face layout gui: [
    tabs (sizer * 20)
    backdrop effect [gradient 1x1 tan brown]
    style button button effect [gradient blue blue/2] (
        to-pair rejoin [(20 * sizer) "x" (13 * sizer)]
    ) font [size: (sizer * 6)]
    style box box brown (to-pair rejoin [(20 * sizer) "x" (7 * sizer)
    ]) font [size: (sizer * 3)]
    image header (to-pair rejoin [(132 * sizer) "x" (8 * sizer)]) [
        contin: request/confirm {
            This will end the current game. Continue?}
        if contin = false [break]
        loadoredit: request/confirm "Load previously edited config file?"
        if loadoredit = true [
            do to-file request-file/title/file {
                Choose config file to use:} "File" %default_config.txt
            unview
            view center-face layout gui
            break
        ]
        alert {Edit carefully, maintaining all quotation marks.
            You can open a previously saved file if needed.
            When done, click SAVE-AS and then QUIT.
            Be sure choose a filename/folder
            location that you'll be able to find later.
        }
        write %default_config.txt config
        unview
        editor %default_config.txt
        alert {Now choose a config file to use (most likely the file
            you just edited).}
        do to-file request-file/title/file {
            Choose config file to use:} "File" %default_config.txt
        view center-face layout gui
    ]
    space (to-pair rejoin [(8 * sizer) "x" (2 * sizer)])
    pad (sizer * 2)
    across
    box (to-pair rejoin [(132 * sizer) "x" (2 * sizer)])
        ) effect [gradient 1x0 brown black]
    return
    box Category-1
    box Category-2
    box Category-3
    box Category-4
    box Category-5
    return
    box (to-pair rejoin [(132 * sizer) "x" (2 * sizer)])
        ) effect [gradient 1x0 brown black]
    return

```

```

button "$100" [face/feel: none face/text: "" do-button 1]
button "$100" [face/feel: none face/text: "" do-button 2]
button "$100" [face/feel: none face/text: "" do-button 3]
button "$100" [face/feel: none face/text: "" do-button 4]
button "$100" [face/feel: none face/text: "" do-button 5]
return
button "$200" [face/feel: none face/text: "" do-button 6]
button "$200" [face/feel: none face/text: "" do-button 7]
button "$200" [face/feel: none face/text: "" do-button 8]
button "$200" [face/feel: none face/text: "" do-button 9]
button "$200" [face/feel: none face/text: "" do-button 10]
return
button "$300" [face/feel: none face/text: "" do-button 11]
button "$300" [face/feel: none face/text: "" do-button 12]
button "$300" [face/feel: none face/text: "" do-button 13]
button "$300" [face/feel: none face/text: "" do-button 14]
button "$300" [face/feel: none face/text: "" do-button 15]
return
button "$400" [face/feel: none face/text: "" do-button 16]
button "$400" [face/feel: none face/text: "" do-button 17]
button "$400" [face/feel: none face/text: "" do-button 18]
button "$400" [face/feel: none face/text: "" do-button 19]
button "$400" [face/feel: none face/text: "" do-button 20]
return
button "$500" [face/feel: none face/text: "" do-button 21]
button "$500" [face/feel: none face/text: "" do-button 22]
button "$500" [face/feel: none face/text: "" do-button 23]
button "$500" [face/feel: none face/text: "" do-button 24]
button "$500" [face/feel: none face/text: "" do-button 25]
return
box (to-pair rejoin [(132 * sizer) "x" (2 * sizer)])
    ) effect [gradient 1x0 brown black]
return tab
box "Player 1:" effect [gradient 1x1 tan brown]
player1: box white "$0" font [color: black size: (sizer * 4)] [
    face/text: request-text/title/default "Enter Score:" face/text
]
box "Player 2:" effect [gradient 1x1 tan brown]
player2: box white "$0" font [color: black size: (sizer * 4)] [
    face/text: request-text/title/default "Enter Score:" face/text
]
return tab
box "Player 3:" effect [gradient 1x1 tan brown]
player3: box white "$0" font [color: black size: (sizer * 4)] [
    face/text: request-text/title/default "Enter Score:" face/text
]
box "Player 4:" effect [gradient 1x1 tan brown]
player4: box white "$0" font [color: black size: (sizer * 4)] [
    face/text: request-text/title/default "Enter Score:" face/text
]
]
1

```

10.9 Case 9 - Creating a Tetris Game Clone

One of my favorite games to play is Tetris. I particularly like the "Rebtris" clone, written in REBOL by Frank Sievertsen. While playing Rebtris recently, it struck me that writing a Tetris clone of my own would be a helpful exercise for this tutorial. In conceiving how to make it a bit different from all the other endless variations of Tetris, I thought "why not try a text version?". Creating it may be easier than a GUI version, and it would run on machines where GUI versions of REBOL aren't available. Writing a text version of Tetris would also force me to organize a set of display techniques that could be useful in laying out other text-based applications. Sounds like a fun project with some useful side effects.

NOTE: I've never considered how to build a Tetris clone, and I'm writing this section as I design, experiment, and write code for the program. So as you read this, you'll follow my exact train of thought in putting the program together, and I'll make no attempt to artificially clean up the process. The point of this tutorial is to demonstrate exactly how to go about creating all types of programs on your own. I hope that following my footsteps exactly - imperfections and all - should be a helpful experience. Let's see what happens...

Instead of starting this entire thing from scratch, I remembered briefly skimming a tutorial about how to

create a text positioning dialect called "TUI". I found it again at <http://www.rebolforces.com/articles/tui-dialect/> and looked for some reusable code...

Here's the TUI dialect, created by Ingo Hohmann (I renamed his "cursor2" function to "tui"):

```
tui: func [
  {Cursor positioning dialect (iho)}
  [catch]
  commands [block!]
  /local screen-size string arg cnt cmd c err
]
  screen-size: (
    c: open/binary/no-wait [scheme: 'console]
    prin "^(1B)[7n"
    arg: next next to-string copy c
    close c
    arg: parse/all arg ";R"
    forall arg [change arg to-integer first arg]
    arg: to-pair head arg
  )
  string: copy ""
  cmd: func [s][join "^(1B)[" s]
  if error? set/any 'err try [
    commands: compose bind commands 'screen-size ][
    throw err
  ]
  arg: parse commands [
    any [
      'direct set arg string! (append string arg) |
      'home (append string cmd "H") |
      'kill (append string cmd "K") |
      'clear (append string cmd "J") |
      'up set arg integer! (append string cmd [
        arg "A"]) |
      'down set arg integer! (append string cmd [
        arg "B"]) |
      'right set arg integer! (append string cmd [
        arg "C"]) |
      'left set arg integer! (append string cmd [
        arg "D"]) |
      'at set arg pair! (append string cmd [
        arg/x ";" arg/y "H" ]) |
      'del set arg integer! (append string cmd [
        arg "P"]) |
      'space set arg integer! (append string cmd [
        arg "@"]) |
      'move set arg pair! (append string cmd [
        arg/x ";" arg/y "H" ]) |
      set cnt integer! set arg string! (
        append string head insert/dup copy "" arg cnt
      ) |
      set arg string! (append string arg)
    ]
  ]
  end
]
  if not arg [throw make error! "Unable to parse block"]
  string
]
```

I read the tutorial and played with the code a bit. In addition to being a great tutorial, the end product is a useful tool for formatting output in console applications. The function "tui" gets passed a block of parameters including text to be printed, directional keywords to move the cursor around the screen ("home", "up", "down", "left", "right", and "at" a specific location) and several other commands to get the screen size, clear the screen, delete text, repeat text, and insert spaces.

I tried a few commands to get familiar with the syntax:

```

prin tui [ clear ]
print tui [ 50 "-" ]
prin tui [ right 10 down 7 50 "x" ]
prin tui [ clear right 10 down 10 50 "x" ]
print tui [ clear home "message1"]
print tui [ home space 20 "message2"]
print tui [ at 20x20 "message3" kill "message4"]
print tui [ at 20x20 del 10]
print tui [ move 10x10]
prin tui [ clear (screen-size/y * screen-size/x - 4) "x" ]

```

I had more fun playing with the TUI dialect than I did playing Tetris :) Basically, TUI wraps up some of the native print control codes built into REBOL, in a nice clean format that eliminates all the odd characters used in native codes. It contains everything required to move game pieces around the screen, so I'll start to come up with some requirements to build the game. Here's an outline that covers the main design goals I'm conceiving at this point:

1. Draw a static playing field (the unchanging graphic backdrop design that's on screen the whole time the game is being played). This will represent the left, right, and lower vertical bounds which the game coordinates may not exceed.
2. There are 7 block shapes used in the game. Create text versions of each graphic shape, in each of the 4 possible rotated positions. Come up with code to print and delete each of the graphic shapes. The TUI dialect will let me print and delete characters anywhere on the screen. I'll use directional statements to print the required characters, starting from any given coordinate. Put all these shape routines into a block for easy naming and reuse.
3. Write a continuous loop to put one shape on the screen, make it fall at a given speed, and allow the user to spin it around and move it left-right.
4. If a shape touches the bottom of the playing field, make it lock into the grid of other shapes that have already fallen. If the bottom row is complete, remove it, and make all the rows above it fall down a row to take its place. If the shape touches the ceiling, end the game.

The first part of the outline is easy. I'll use the "print a-line" code created in the "loops and conditions - a simple data storage app" example earlier in this tutorial. Here's a simple little backdrop that's printed to the screen:

```

a-line: copy [] loop 28 [append a-line " "]
a-line: rejoin [" |" to-string a-line "|"]
loop 30 [print a-line] prin " " loop 30 [prin "+"] print ""

```

For the second part, I need to create some code to print the 7 block shapes. They look like this:

```

; 1  #####  2  ###  3  ###  4  ###
;                #      #      #
;
; 5  ##      6  ##  7  ##
;      ##      ##      ##

```

Here are all the possible variations when the above shapes are rotated clockwise:

```

;
; 1  #####  2  #
;                #
;                #
;                #
;
; 3  ###  4  #  5  #  6  #
;      #      ##  ###  ##
;                #      #
;
; 7  ###  8  ##  9  #  10 #
;      #      #      ###  #
;                #      ##
;
;

```

```

; 11 ### 12 # 13 # 14 ##
;      #      #      ###      #
;      #      ##      #
;
; 15 ## 16 #
;      ##      ##
;      #
;
; 17 ## 18 #
;      ##      ##
;      #
;
; 19 ##
;      ##

```

To print any piece, I can start at the top left coordinate in the shape and move the appropriate number of spaces right, left, and/or down to print the other characters in each piece. Starting at the first character in shape 2, for example, I would move as follows: "#", down 1 left 1, "#", down 1 left 1, "#", down 1 left 1, "#". Shape 3 would move as follows: "###", down 1 left 2, "#". Here's a block called "shape", made up of individual blocks that can be passed to tui to print all the above shapes:

```

shape: [
  ["####"]
  ["#" down 1 left 1 "#" down 1 left 1 "#" down 1 left 1 "#"]
  ["####" down 1 left 2 "#"]
  [right 1 "#" down 1 left 2 "###" down 1 left 1 "#"]
  [right 1 "#" down 1 left 2 "####"]
  ["#" down 1 left 1 "###" down 1 left 2 "#"]
  ["####" down 1 left 3 "#"]
  ["###" down 1 left 1 "#" down 1 left 1 "#"]
  [right 2 "#" down 1 left 3 "####"]
  ["#" down 1 left 1 "#" down 1 left 1 "###"]
  ["####" down 1 left 1 "#"]
  [right 1 "#" down 1 left 1 "#" down 1 left 2 "###"]
  ["#" down 1 left 1 "####"]
  ["###" down 1 left 2 "#" down 1 left 1 "#"]
  ["###" down 1 left 1 "###"]
  [right 1 "#" down 1 left 2 "###" down 1 left 2 "#"]
  [right 1 "###" down 1 left 3 "###"]
  ["#" down 1 left 1 "###" down 1 left 1 "#"]
  ["###" down 1 left 2 "###"]
]

```

Now I can use the format "prin tui shape/number" to print any shape. For example:

```
prin tui shape/3
```

is the same as writing:

```
prin tui [right 1 "#" down 1 left 2 "###" down 1 left 1 "#"]
```

I came up with the following code to print out each shape, to check for errors, and to get used to using the above format. Notice the use of the "compose" function:

```

for i 1 19 1 [
  print tui [clear]
  print rejoin ["shape " i ":"]
  do compose [print tui shape/(i)]
  ask ""
]

```

To erase the shapes, I decided to extend the block using duplicates of each shape to print spaces instead of "#".s. Now all I have to do is add 19 to any shape's index number, and I can print out a shape made of spaces that erases the original shape made of "#".s. Here's the final shape block:

```
shape: [
  ["#####"]
  ["#" down 1 left 1 "#" down 1 left 1 "#" down 1 left 1 "#"]
  ["####" down 1 left 2 "#"]
  [right 1 "#" down 1 left 2 "##" down 1 left 1 "#"]
  [right 1 "#" down 1 left 2 "###"]
  ["#" down 1 left 1 "##" down 1 left 2 "#"]
  ["####" down 1 left 3 "#"]
  ["###" down 1 left 1 "#" down 1 left 1 "#"]
  [right 2 "#" down 1 left 3 "###"]
  ["#" down 1 left 1 "#" down 1 left 1 "##"]
  ["####" down 1 left 1 "#"]
  [right 1 "#" down 1 left 1 "#" down 1 left 2 "##"]
  ["#" down 1 left 1 "####"]
  ["###" down 1 left 2 "#" down 1 left 1 "#"]
  ["###" down 1 left 1 "###"]
  [right 1 "#" down 1 left 2 "##" down 1 left 2 "#"]
  [right 1 "##" down 1 left 3 "###"]
  ["#" down 1 left 1 "##" down 1 left 1 "#"]
  ["###" down 1 left 2 "###"]

  ; Here are the same shapes, with spaces instead of "#".s:

  ["   "]
  [" " down 1 left 1 " " down 1 left 1 " " down 1 left 1 " "]
  ["  " down 1 left 2 " "]
  [right 1 " " down 1 left 2 " " down 1 left 1 " "]
  [right 1 " " down 1 left 2 " "]
  [" " down 1 left 1 " " down 1 left 2 " "]
  ["  " down 1 left 3 " "]
  [" " down 1 left 1 " " down 1 left 1 " "]
  [right 2 " " down 1 left 3 " "]
  [" " down 1 left 1 " " down 1 left 1 " "]
  ["  " down 1 left 1 " "]
  [right 1 " " down 1 left 1 " " down 1 left 2 " "]
  [" " down 1 left 1 " "]
  [" " down 1 left 2 " " down 1 left 1 " "]
  [" " down 1 left 1 " "]
  [right 1 " " down 1 left 2 " " down 1 left 2 " "]
  [right 1 " " down 1 left 3 " "]
  [" " down 1 left 1 " " down 1 left 1 " "]
  ["  " down 1 left 2 " "]
]
```

I wrote another quick script to test it. Notice the "i + 19" used to erase the exiting shape:

```
for i 1 19 1 [
  print tui [clear]
  print rejoin ["shape " i ":"]
  do compose [prin tui [move 10x10] print tui shape/(i)]
  ask ""
  do compose [prin tui [move 10x10] print tui shape/(i + 19)]
  print rejoin ["shape " i " has been erased."]
  ask ""
]
```

Beautiful. Steps 1 and 2 are complete. Now I can work on the last part of the outline (the things related to how the game actually plays, moving pieces and responding to user input). First, I'll get the shapes to fall down the screen. That'll be done by printing, erasing and then redrawing the piece one row lower, in a continuous loop. Here's an outline to organize that thought process:

1. Start by clearing the screen.

2. Pieces appear in a random order, so come up with a random number to represent some random shape's index number.
3. Use a for loop to increment the vertical position of the piece: for each row, print the random piece number at the current horizontal position (initially set to 15), and at the vertical position represented by the current "for" variable.
4. Wait a moment, then erase the piece (using the shape number + 19). Then increment the row number and start again.
5. When the piece reaches the last row, print it there without erasing.
6. Wrap that whole thing in a forever loop to keep it going indefinitely.

Let's get that much going:

```
prin tui [clear]

forever [
  random/seed now
  r: random 19      ; the number of a random shape
  xpos: 18          ; the initial horizontal position
  for i 1 25 1 [
    pos: to-pair rejoin [i "x" xpos]
    ; print the shape represented by "r" at the "pos"
    ; coordinate:
    do compose/deep [prin tui [at (pos)] print tui shape/(r)]
    ; The wait time could be a user controlled variable, or
    ; it could be sped up as the difficulty level increases:
    wait :00:00.30
    ; erase the shape, then continue the loop:
    do compose/deep [
      prin tui [at (pos)] print tui shape/(r + 19)]
    ]
    ; reprint the shape at its final resting place:
    do compose/deep [prin tui [move (pos)] print tui shape/(r)]
  ]
]
```

NOTE: It struck me in writing the above code that the TUI function actually takes all its coordinates in an unusual order. Typically, in coordinates with the form XxY, "X" is the horizontal position and "Y" is the vertical position. TUI uses the format YxX, where Y is the vertical position measured in rows from the top of the screen. X is the horizontal position, measured in columns from the left side of the screen. Keep in mind that the order of X and Y coordinates is opposite the normal expectation.

Now I need to come up with a way for the user to control the horizontal position of the shape. Here's some pseudo code to help me think about how to do that:

1. Be on the lookout for keystroke input from the user.
2. If the user presses the "l" key, add 1 to the current horizontal position of the shape (held in the variable "xpos"). If the user presses the "k" key, subtract 1 from xpos.

First, I need a way to get keystroke input without blocking the program flow (i.e., I need to wait for keystroke input to be acknowledged when it occurs, but I can't just stop the normal program flow to wait for key presses. For game play to continue, the "for" and "forever" loops can't be interrupted. So I searched Google for "REBOL key stroke" and got pointed to the following code at <http://www.rebol.org/cgi-bin/cgiwrap/rebol/ml-display-thread.r?m=rmlSCRQ> (in the REBOL mailing list archive):

```
c: open/binary/no-wait [scheme: 'console]
; set following to whatever you wish
; intentionally slow at 2 secs so you can "see" the effect
wait-duration: :0:2
d: 0
forever [
  if not none? wait/all [c wait-duration] [
    print to-char to-integer copy c
  ]
  d: d + 1 ;let's do other stuff
  print d
]
```

That little bit of code does exactly what I need. The parts required for my needs are:

```
c: open/binary/no-wait [scheme: 'console]
forever [
  if not none? wait/all [c wait-duration] [
    print to-char to-integer copy c
  ]
]
```

I adjusted the variable names, checked for "k" or "l" key presses, and used the code below to test that it worked the way I wanted:

```
keys: open/binary/no-wait [scheme: 'console]
forever [
  if not none? wait/all [keys :00:00.01] [
    switch to-string to-char to-integer copy keys [
      "k" [print "you pressed k"]
      "l" [print "you pressed l"]
    ]
  ]
]
; print "nothing pressed" ; make sure it's working
```

Next, I integrated the above code into the loop created earlier to drop the shape down the screen. Notice that I added a conditional "if", to be executed when either "k" or "l" keystrokes are encountered. It checks that the horizontal bounds don't go outside the 5-30 positions. That keeps the shapes within the horizontal boundaries of the playing field. Also, notice that the variable "old-xpos" is used to hold the position of the shape that needs to be erased:

```
keys: open/binary/no-wait [scheme: 'console]
forever [
  random/seed now
  r: random 19
  xpos: 18
  for i 1 25 1 [
    pos: to-pair rejoin [i "x" xpos]
    do compose/deep [prin tui [at (pos)] print tui shape/(r)]
    old-xpos: xpos
    if not none? wait/all [keys :00:00.30] [
      switch to-string to-char to-integer copy keys [
        "k" [if (xpos > 5) [xpos: xpos - 1]]
        "l" [if (xpos < 30) [xpos: xpos + 1]]
      ]
    ]
    pos: to-pair rejoin [i "x" old-xpos]
    do compose/deep [
      prin tui [at (pos)] print tui shape/(r + 19)]
  ]
  do compose/deep [prin tui [move (pos)] print tui shape/(r)]
]
```

It's coming along well :) Now I need to be able to spin the shapes around. Here's some pseudo code to organize my thoughts:

1. Watch for the "O" key to be pressed. That will be the keycode to run the shape spinning code.
2. Create a set of conditionals to cycle through the list of rotated shapes related to the current shape. For example, if the current shape (variable "r") is number 12, then the rotated versions of that shape are numbers 11-14. With each press of the "O" key, replace the variable r with the next shape in that list. That logic must "wrap around" (i.e., the next shape after 14 should be 11). Instead of using a block list of shapes to do this, I decide to use a switch structure to individually map each shape to the one it should rotate to (something like "if shape r is now #14, turn shape r into #11" - do that explicitly for each shape).

I already have some code to watch for keystrokes, so I'll try the last part of the above outline first:

```
switch to-string r [
  "1" [r: 2]
  "2" [r: 1]
  "3" [r: 4]
  "4" [r: 5]
  "5" [r: 6]
  "6" [r: 3]
  "7" [r: 8]
  "8" [r: 9]
  "9" [r: 10]
  "10" [r: 7]
  "11" [r: 12]
  "12" [r: 13]
  "13" [r: 14]
  "14" [r: 11]
  "15" [r: 16]
  "16" [r: 15]
  "17" [r: 18]
  "18" [r: 17]
  "19" [r: 19]
]
```

Wait a sec - that makes the shapes rotate clockwise (from #11 go to #12, #14 to #11, etc.) I prefer for them to rotate counterclockwise (#11 to #14, #14 to #13, etc). Here's the revised code:

```
switch to-string r [
  "1" [r: 2]
  "2" [r: 1]
  "3" [r: 6]
  "4" [r: 3]
  "5" [r: 4]
  "6" [r: 5]
  "7" [r: 10]
  "8" [r: 7]
  "9" [r: 8]
  "10" [r: 9]
  "11" [r: 14]
  "12" [r: 11]
  "13" [r: 12]
  "14" [r: 13]
  "15" [r: 16]
  "16" [r: 15]
  "17" [r: 18]
  "18" [r: 17]
  "19" [r: 19]
]
```

Now add the letter "O" to the list of keys to be watched, and run the above code when it's pressed. Also create an "old-r" variable to retain the number of the shape that needs to be erased. (Since the user changes shapes after the current one has been printed, we need to keep track of which one to erase):

```
keys: open/binary/no-wait [scheme: 'console]
forever [
  random/seed now
  r: random 19
  xpos: 18
  for i 1 25 1 [
    pos: to-pair rejoin [i "x" xpos]
    do compose/deep [prin tui [at (pos)] print tui shape/(r)]
    old-xpos: xpos
    old-r: r
    if not none? wait/all [keys :00:00.30] [
      keystroke: to-string to-char to-integer copy keys
```

```

        switch keystroke [
            "k" [if (xpos > 5) [xpos: xpos - 1]]
            "l" [if (xpos < 30) [xpos: xpos + 1]]
            "o" [switch to-string r [
                "1" [r: 2]
                "2" [r: 1]
                "3" [r: 6]
                "4" [r: 3]
                "5" [r: 4]
                "6" [r: 5]
                "7" [r: 10]
                "8" [r: 7]
                "9" [r: 8]
                "10" [r: 9]
                "11" [r: 14]
                "12" [r: 11]
                "13" [r: 12]
                "14" [r: 13]
                "15" [r: 16]
                "16" [r: 15]
                "17" [r: 18]
                "18" [r: 17]
                "19" [r: 19]
            ]]
        ]
    ]
    do compose/deep [
        prin tui [at (pos)] print tui shape/(old-r + 19)
    ]
]
do compose/deep [prin tui [at (pos)] print tui shape/(r)]
]

```

The shapes are moving correctly now, but there's still a lot of work to be done. The first line of the last section of the overall game outline reads: "If the shape touches the bottom of the playing field, make it lock into the grid of other shapes that have already fallen". Right now the pieces all just fall to different stopping points in the playing field (depending on their height), and they don't stack on top of each other. Here's some pseudo code to fix that:

1. I need to be aware of the highest coordinate in each column on the playing field. When the game starts, the highest coordinate in every column of the playing field is row 30 (the flat bottom line that makes up the playing field). I'll store each of these coordinates in a block called "floor".
2. I also need to be aware of the lowest coordinate in each column of the currently falling shape. I'll make a block called "edge" to hold those coordinates (referring to the lower edges of the shape). Those coordinates will define the position of each of the lowest points in the currently falling shape, in relation to its top left point (the "pos" coordinate).
3. Every time the shape falls one position down the screen, add each of the edge coordinates to the pos coordinate. If any of those coordinates is one position higher than the floor coordinate in the same column, then stop moving that shape (break out of the "for" loop that makes the shape fall). Use a foreach loop to cycle through the current coordinates in the relevant columns of each block, performing a comparison check on the floor and edge coordinates in each column.
4. When a shape finishes its drop down the screen, calculate the new highest position in the columns it occupies (the coordinates of the top character in each column), and make those changes to the block that holds the high point information. To do that, I'll need to make a "top" block to hold the relative positions of the highest coordinates in the shape, and add them to the height of the current coordinates in the appropriate columns.

I'll start out simply, just getting each shape to lay flat on the floor of the playing field (row 30). For the moment, all I need to do is create a block of floor coordinates that represents that bottom line:

```

floor:      [30x1 30x2 30x3 30x4 30x5 30x6 30x7 30x8 30x9 30x10 30x11
             30x12 30x13 30x14 30x15 30x16 30x17 30x18 30x19 30x20 30x21
             30x22 30x23 30x24 30x25 30x26 30x27 30x28 30x29 30x30 30x31
             30x32 30x33 30x34 30x35]

```

Next, I'll define a set of lower coordinates for each shape, and store them in a nested block structure similar to the earlier "shape" block. "0x0" refers to the same coordinate as "pos" (0 positions to the right, and 0 positions down from "pos"). "0x10" is one position to the right, and "1x0" is one position down. I look at the

visual representations of the shapes again to come up with the list:

```

;
; 1  #####  2  #
;      #
;      #
;      #
;
; 3  ###    4  #    5  #    6  #
;      #    ##    ###    ##
;      #    #
;
; 7  ###    8  ##    9  #    10 #
;      #    #    ###    #
;      #    #    #
;
; 11 ###    12 #    13 #    14 ##
;      #    #    ###    #
;      #    ##    #
;
; 15 ##    16 #
;      ##    ##
;      #
;
; 17 ##    18 #
;      ##    ##
;      #
;
; 19 ##
;      ##

```

Here's the complete set of low point definitions for each shape:

```

edge: [ [0x0 0x1 0x2 0x3] [3x0] [0x0 1x1 0x2] [1x0 2x1]
        [1x0 1x1 1x2] [2x0 1x1] [1x0 0x1 0x2] [0x0 2x1] [1x0 1x1 1x2]
        [2x0 2x1] [0x0 0x1 1x2] [2x0 2x1] [1x0 1x1 1x2] [2x0 0x1]
        [0x0 1x1 1x2] [2x0 1x1] [1x0 1x1 0x2] [1x0 2x1] [1x0 1x1] ]

```

So, the relative coordinates of the low points in shape 3, for example, are referred to as edge/3. Here's some sample code to demonstrate how I can now refer to the bottom points in any shape using a foreach loop. The code "pos + position" refers to the low edge in each column:

```

pos: 5x5
r: 6
foreach position compose edge/(r) [print pos + position]

```

To check if any of those edges are touching the floor, use a foreach loop to cycle through the current coordinates in the relevant columns of each block, performing a comparison check on the floor and edge coordinates in each column. Here's some sample code to flesh out and test that idea:

```

pos: 30x10
for r 1 19 1 [
  print tui [clear]
  prin "Piece: " print r
  foreach po compose edge/(r) [
    print pos + po
    foreach coord floor [
      floor-y: to-integer first coord
      floor-x: to-integer second coord
      edge-y: to-integer first pos + to-integer first po
      edge-x: to-integer second pos + to-integer second po
      print rejoin [
        "edge: " edge-y "x" edge-x " "

```

```

        "floor: "floor-y "x" floor-x
    ]
    if (edge-y >= floor-y) and (floor-x = edge-x) [
        print rejoin [
            "You're touching or beyond the floor at: "
            pos + po
        ]
    ]
]
]
ask ""
]

```

Now let's integrate this technique into the existing code. We'll use a new variable "stop" to break out of the loop that drops the shape, when the current shape touches the floor:

```

keys: open/binary/no-wait [scheme: 'console]
forever [
    random/seed now
    r: random 19
    xpos: 18
    for i 1 32 1 [
        pos: to-pair rejoin [i "x" xpos]
        do compose/deep [prin tui [at (pos)] print tui shape/(r)]
        old-r: r
        old-xpos: xpos
        if not none? wait/all [keys :00:00.30] [
            keystroke: to-string to-char to-integer copy keys
            switch keystroke [
                "k" [if (xpos > 5) [xpos: xpos - 1]]
                "l" [if (xpos < 30) [xpos: xpos + 1]]
                "o" [switch to-string r [
                    "1" [r: 2]
                    "2" [r: 1]
                    "3" [r: 6]
                    "4" [r: 3]
                    "5" [r: 4]
                    "6" [r: 5]
                    "7" [r: 10]
                    "8" [r: 7]
                    "9" [r: 8]
                    "10" [r: 9]
                    "11" [r: 14]
                    "12" [r: 11]
                    "13" [r: 12]
                    "14" [r: 13]
                    "15" [r: 16]
                    "16" [r: 15]
                    "17" [r: 18]
                    "18" [r: 17]
                    "19" [r: 19]
                ]]
            ]
        ]
        do compose/deep [
            prin tui [at (pos)] print tui shape/(old-r + 19)
        ]
        stop: false
        foreach po compose edge/(r) [
            foreach coord floor [
                floor-y: to-integer first coord
                floor-x: to-integer second coord
                edge-y: i + to-integer first po
                edge-x: xpos + to-integer second po
                if (edge-y >= floor-y) and (floor-x = edge-x) [
                    stop: true
                    break
                ]
            ]
        ]
    ]
]

```

```

    ]
    if stop = true [break]
  ]
  do compose/deep [prin tui [at (pos)] print tui shape/(old-r)]
]

```

This works, but there's a bug. If the piece has been spun around (using the "O" key), the new foreach loop fails to stop the piece from falling. That's because the foreach loop only cycles through the coordinates of the "edge/r" block. If the user flips the shape around, the "r" value gets changed before this code is run. The easiest way to fix this problem is to simply repeat the foreach loop using the "edge/old-r" block. This is an inefficient quick hack, but I'm writing this late at night - and there's some value to pointing out bad coding practice - so I choose to use that solution. I make a promise to myself to come up with a more elegant solution later... (Note to self: once a coding solution has been implemented, changes are harder to make, and bad code typically remains permanent ... I need to be careful about using quick hacks). Here's the current code:

```

keys: open/binary/no-wait [scheme: 'console]
forever [
  random/seed now
  r: random 19
  xpos: 18
  for i 1 32 1 [
    pos: to-pair rejoin [i "x" xpos]
    do compose/deep [prin tui [at (pos)] print tui shape/(r)]
    old-r: r
    old-xpos: xpos
    if not none? wait/all [keys :00:00.30] [
      keystroke: to-string to-char to-integer copy keys
      switch keystroke [
        "k" [if (xpos > 5) [xpos: xpos - 1]]
        "l" [if (xpos < 30) [xpos: xpos + 1]]
        "o" [switch to-string r [
          "1" [r: 2]
          "2" [r: 1]
          "3" [r: 6]
          "4" [r: 3]
          "5" [r: 4]
          "6" [r: 5]
          "7" [r: 10]
          "8" [r: 7]
          "9" [r: 8]
          "10" [r: 9]
          "11" [r: 14]
          "12" [r: 11]
          "13" [r: 12]
          "14" [r: 13]
          "15" [r: 16]
          "16" [r: 15]
          "17" [r: 18]
          "18" [r: 17]
          "19" [r: 19]
        ]]
      ]
    ]
    do compose/deep [
      prin tui [at (pos)] print tui shape/(old-r + 19)
    ]
    stop: false
    foreach po compose edge/(r) [
      foreach coord floor [
        floor-y: to-integer first coord
        floor-x: to-integer second coord
        edge-y: i + to-integer first po
        edge-x: xpos + to-integer second po
        if (edge-y = floor-y) and (floor-x = edge-x) [
          stop: true
          break
        ]
      ]
    ]
  ]
]

```

```

    ]
    foreach po compose edge/(old-r) [
        foreach coord floor [
            floor-y: to-integer first coord
            floor-x: to-integer second coord
            edge-y: i + to-integer first po
            edge-x: old-xpos + to-integer second po
            if (edge-y = floor-y) and (floor-x = edge-x) [
                stop: true
                break
            ]
        ]
    ]
    if stop = true [break]
]
do compose/deep [prin tui [at (pos)] print tui shape/(old-r)]
]

```

Next, I decide to test the existing program for other bugs. I've been keeping separate text files containing all the code changes I make as I go along. Every time I make, test, and change a chunk of code, I save the new trial version with a new filename and version number. I save each version, just so that I don't permanently erase old code with each change - it may be potentially useful. My current working version is now #19.

I noticed during this debugging session that shape 1 still breaks through the right side of the wall. I could change that by adjusting the "(xpos < 30)" conditional expression that occurs when the "L" key gets pressed. But that solution will keep the other shapes from laying snugly against the wall. In fact, that additional problem is occurring now with shapes that are only 2 characters wide - I didn't notice until now. To deal with these problems, I create a block of values called "width", listing the widths of all 19 shapes, which can be used in the existing conditional expression:

```
width: [4 1 3 2 3 2 3 2 3 2 3 2 3 2 3 2 3 2 2]
```

Now I can check if the shape is at the right boundary, using the revised code below:

```

[if (xpos < (33 - compose width/(r))) [
    xpos: xpos + 1]
]

```

That check also needs to be performed every time the "O" key is pressed (we don't want the shape breaking out of the wall when it spins). I make the above changes to my current version of the program, and the problems are fixed.

The game is really starting to take shape! Now we need to make the shapes stack on top of each other. Earlier, I wrote these outline thoughts: "when a shape finishes its drop down the screen, calculate the new highest position in the columns it occupies (the coordinates of the top character in each column), and make those changes to the block that holds the high point information. To do that, I'll need to make a "top" block to hold the relative positions of the highest coordinates in the shape, and add them to the height of the current coordinates in the appropriate columns". Sounds like I'll need to loop through some columns to make the changes to the floor.

To create the "top" block I look at the visual representations of each shape once again, and come up with a coordinate list representing the high points in the shape, relative to the top left coordinate. It's similar to the "edge" block:

```

top: [ [0x0 0x1 0x2 0x3] [0x0] [0x0 0x1 0x2] [1x0 0x1]
      [1x0 0x1 1x2] [0x0 1x1] [0x0 0x1 0x2] [0x0 0x1] [1x0 1x1 0x2]
      [0x0 2x1] [0x0 0x1 0x2] [2x0 0x1] [0x0 1x1 1x2] [0x0 0x1]
      [0x0 0x1 1x2] [1x0 0x1] [1x0 0x1 0x2] [0x0 1x1] [0x0 0x1] ]

```

The shape finishes its drop down the screen during the previous foreach loops we created, so to calculate the new highest positions in the columns occupied by the shape, I first need to determine which shape was

the last one on the screen ("r" or "old-r"). The quick hack I made earlier is now coming back to bite me a bit - I now need to make duplicates of any changes that occur in both foreach loops:

```
stop-shape-num: r
; (or stop-shape-num: old-r, depending on the foreach loop)
stop: true
break
```

Now to make the changes to the "floor" block, I loop through the columns occupied by the piece, setting each of the top characters in the shape to be the high coordinates in the respective columns of the floor. The "poke" function lets me replace the original coordinates in the floor block with the new coordinates. Those changes are made just before breaking out of the loop that drops the shape:

```
if stop = true [
  ; get the left-most column the last shape occupies:
  left-col: second pos
  ; get the number of columns the shape occupies:
  width-of-shape: length? compose top/(stop-shape-num)
  ; get the right most column the shape occupies:
  right-col: left-col + width-of-shape - 1
  ; Loop through each column occupied by the shape,
  ; replacing each coordinate in the current column
  ; of the floor with the new high coordinate:
  counter: 1
  for current-column left-col right-col 1 [
    add-coord: compose top/(stop-shape-num)/(counter)
    new-floor-coord: (pos + add-coord + -1x0)
    poke floor current-column new-floor-coord
    counter: counter + 1
  ]
  break
]
```

The new stacking code works, but there's a design flaw. If I maneuver a shape into an unoccupied space directly underneath any high point in the floor, without first touching the high point in that column, the piece doesn't stop. Furthermore, if that happens, it changes the new high point to the bottom of the column which the current shape occupies. I realize here that what I need to mark are not only the high points in the floor, but also every additional coordinate on the screen that contains a character. This is just as easy to accomplish. Instead of *changing* the current coordinates in the floor block (using the "poke" function):

```
poke floor current-column new-floor-coord
```

just *add* the new coordinates to the list (using "append"). That will keep track of all points at which a character is printed on the screen:

```
append floor new-floor-coord
```

That fixes the problem above, but I've also realized that if I move a shape sideways into an open position in the floor, the characters sometimes still overlap inappropriately. That's because the "top" and "edge" blocks only mark the highest and lowest points in each shape. It strikes me now that I could just combine those two blocks into one, marking all the coordinates occupied by a shape. Here's the new block - I call it "oc", short for "occupied":

```
oc: [
  [0x0 0x1 0x2 0x3] [0x0 1x0 2x0 3x0] [0x0 0x1 0x2 1x1]
  [0x1 1x0 1x1 2x1] [0x1 1x0 1x1 1x2] [0x0 1x0 1x1 2x0]
  [0x0 0x1 0x2 1x0] [0x0 0x1 1x1 2x1] [0x2 1x0 1x1 1x2]
  [0x0 1x0 2x0 2x1] [0x0 0x1 0x2 1x2] [0x1 1x1 2x0 2x1]
  [0x0 1x0 1x1 1x2] [0x0 0x1 1x0 2x0] [0x0 0x1 1x1 1x2]
  [0x1 1x0 1x1 2x0] [0x1 0x2 1x0 1x1] [0x0 1x0 1x1 2x1]
```

```
[0x0 0x1 1x0 1x1]
]
```

I remove the "top" and "edge" blocks, and replace all code references to them with "oc".

Now there's another bug I need to fix. Sometimes when I press a key, the following error occurs:

```
** Script Error: Invalid argument: [45
** Where: to-integer
** Near: forall arg [change arg to-integer first arg]
arg: to-pair
```

The code referenced is not part of any code I've written. It seems to be related to keystroke input because it only happens when I press one of the game control keys. Since I'm not sure what's creating the error (maybe it's related to the timing of keystrokes, or perhaps it has to do with a key release), I make an educated guess and figure that the following line, which waits for keystrokes, is where it's occurring:

```
if not none? wait/all [keys :00:00.30] [...]
```

I wrap that whole thing in an error check:

```
if not error? try [if not none? wait/all [keys :00:00.30] [...]]
```

And, hmmm ... that doesn't work. So instead of guessing, I work methodically to check each of the other main sections of the program. Every section gets wrapped in an "error? try" routine, and I also put in an "if" conditional structure to print out a numbered error message whenever an error occurs. I find that the error is first occurring here:

```
do compose/deep [prin tui [at (pos)] print tui shape/(r)]
```

Wrapped in the error test, that section looks like this:

```
if error? try [
  do compose/deep [
    prin tui [at (pos)] print tui shape/(r)
  ]
] [print "er1"]
```

I'm curious about what's causing the error, so I dig a little deeper. This time I have the error check print out the variables contained in the code:

```
if error? try [
  do compose/deep [
    prin tui [at (pos)] print tui shape/(r)
  ]
] [print rejoin [pos " " r]]
```

Nothing seems to be amiss. Every time the error occurs, the variables show a correct coordinate and shape number. So, for now I'll simply leave the error check in place, removing the printout. This will keep the game moving along whenever the ghostly error occurs. I'll need to post a message to the REBOL mailing list to see if anyone knows why the error is occurring. For the time being, the following error handler fixes the issue:


```

if error? try [
  do compose/deep [
    prin tui [at (pos)] print tui shape/(r)
  ]
] []

```

It turns out that I need to do the same thing for all the other similar occurrences of code that print a shape to the screen:

```

if error? try [
  do compose/deep [
    prin tui [at (pos)] print tui shape/(old-r + 19)
  ]
] []

if error? try [
  do compose/deep [
    prin tui [at (pos)] print tui shape/(old-r)
  ]
] []

```

With all the known bugs controlled, I can move on to implementing the last parts of the game design. We need to check if the top row of the playing area is reached. If any shape stops moving at this ceiling row, end the game. This needs to be done any time a piece reaches it's final resting place, so I put it immediately after the main "for" loop in the program outline (so that it's evaluated immediately after the stopping code is executed):

```

if (first pos) < 2 [
  prin tui [at 35x0]
  print "Game Over"
  halt
]

```

Finally, to erase the bottom line of shapes every time a row is filled in horizontally, we're going to have to redraw the playing field entirely. The "floor" block contains all the information needed to rebuild the current state of the playing field (all the positions at which a character is currently printed). Here's an outline and some pseudo code to think through what needs to be done:

1. Every time a shape stops moving, check to see if any row of the floor is full (i.e., there's one character printed in every column). I can use a for loop and a find function to perform that check on the floor block. (I'll start things off by just checking the bottom row).
2. If any row is full (for now, just the bottom row), remove that row of characters from the floor block. Use a remove-each loop to remove any coordinates that have y positions in the relevant row from the floor block.
3. Move all of the other characters above the relevant row down one row. Add one y position to all the other coordinates in the floor block which are above the relevant row. Use a foreach loop to go through each coordinate in the block and add 1x0. To replace the old floor block with the new one, first create a temporary block made up of the new floor block coordinates, then copy it back to the floor block once it's complete.
4. Erase the current screen, print the static background, and then reprint a new playing field using the refreshed block of floor coordinates. We can accomplish this easily using a foreach loop and TUI to print the characters at each coordinate in the list.

```

; #1:

line-is-full: true
for column 5 32 1 [
  each-coord: to-pair rejoin [29 "x" column]
  if not find floor each-coord [
    line-is-full: false
    break
  ]
]

```

```

; #2:

if line-is-full = true [
    remove-each cor floor [(first cor) = 29]

; #3:

    new-floor: copy []
    foreach cords floor [
        append new-floor (cords + 1x0)
    ]
    floor: copy new-floor

; #4:

    prin tui [clear]
    a-line: copy [] loop 28 [append a-line " "]
    a-line: rejoin ["  " to-string a-line "|"]
    loop 30 [print a-line]
    prin "    loop 30 [prin "+"] print ""
    foreach was-here floor [
        if not ((first was-here) = 30) [
            prin tui compose [at (was-here)]
            prin "#"
        ]
    ]
]

```

At this point, I realize that I've made some logic errors in how the floor block and the stopping routine are structured. As it stands, when the screen is refreshed, the bottom row of the block (row 30) needs to be erased so that all the characters in row 29 can fall down one position. But if row 30 is erased, then the bottom of the floor disappears. As it turns out, row 31 should actually be treated as the bottom row, and all the characters should stop at 1x0 position higher than any character in the floor.

I make the required changes to the coordinates in the floor block (change all the y positions from 30 to 31). I also change the "new-floor-coord" variable in the stopping routine, and adjust the code above so that characters below line 30 are not printed. Additionally, the entire section above gets wrapped in a "for" loop to check if each row 1-30 is full. In the code above, I only checked if the bottom line was full - the number 29 referred to the row. I replace that number with the "row" variable created in the for loop. And with that, the last requirements of my original game outline are satisfied and an initial version of "Tetris" is in working order. Here's the code:

```

REBOL [Title: "Tetris"]

tui: func [
    {Cursor positioning dialect (iho)}
    [catch]
    commands [block!]
    /local screen-size string arg cnt cmd c err
][
    screen-size: (
        c: open/binary/no-wait [scheme: 'console]
        prin "^(1B)[7n"
        arg: next next to-string copy c
        close c
        arg: parse/all arg ";R"
        forall arg [change arg to-integer first arg]
        arg: to-pair head arg
    )
    string: copy ""
    cmd: func [s][join "^(1B)[" s]
    if error? set/any 'err try [
        commands: compose bind commands 'screen-size []
        throw err
    ]
    arg: parse commands [
        any [
            'direct set arg string! (append string arg) |

```

```

'home (append string cmd "H") |
'kill (append string cmd "K") |
'clear (append string cmd "J") |
'up set arg integer! (append string cmd [
  arg "A"]) |
'down set arg integer! (append string cmd [
  arg "B"]) |
'right set arg integer! (append string cmd [
  arg "C"]) |
'left set arg integer! (append string cmd [
  arg "D"]) |
'at set arg pair! (append string cmd [
  arg/x ";" arg/y "H" ]) |
'del set arg integer! (append string cmd [
  arg "P"]) |
'space set arg integer! (append string cmd [
  arg "@"]) |
'move set arg pair! (append string cmd [
  arg/x ";" arg/y "H" ]) |
set cnt integer! set arg string! (
  append string head insert/dup copy "" arg cnt
) |
set arg string! (append string arg)
]
end
]
if not arg [throw make error! "Unable to parse block"]
string
]

shape: [
["#####"]
["#" down 1 left 1 "#" down 1 left 1 "#" down 1 left 1 "#"]
["####" down 1 left 2 "#"]
[right 1 "#" down 1 left 2 "##" down 1 left 1 "#"]
[right 1 "#" down 1 left 2 "###"]
["#" down 1 left 1 "###" down 1 left 2 "#"]
["####" down 1 left 3 "#"]
["###" down 1 left 1 "#" down 1 left 1 "#"]
[right 2 "#" down 1 left 3 "###"]
["#" down 1 left 1 "#" down 1 left 1 "###"]
["####" down 1 left 1 "#"]
[right 1 "#" down 1 left 1 "#" down 1 left 2 "##"]
["#" down 1 left 1 "####"]
["###" down 1 left 2 "#" down 1 left 1 "#"]
["###" down 1 left 1 "###"]
[right 1 "##" down 1 left 2 "###" down 1 left 2 "#"]
[right 1 "###" down 1 left 3 "###"]
["#" down 1 left 1 "###" down 1 left 1 "#"]
["###" down 1 left 2 "###"]
;
[" "]
[" " down 1 left 1 " " down 1 left 1 " " down 1 left 1 " "]
[" " down 1 left 2 " "]
[right 1 " " down 1 left 2 " " down 1 left 1 " "]
[right 1 " " down 1 left 2 " "]
[" " down 1 left 1 " " down 1 left 2 " "]
[" " down 1 left 3 " "]
[" " down 1 left 1 " " down 1 left 1 " "]
[right 2 " " down 1 left 3 " "]
[" " down 1 left 1 " " down 1 left 1 " "]
[" " down 1 left 1 " "]
[right 1 " " down 1 left 1 " " down 1 left 2 " "]
[" " down 1 left 1 " "]
[" " down 1 left 2 " " down 1 left 1 " "]
[" " down 1 left 1 " "]
[right 1 " " down 1 left 2 " " down 1 left 2 " "]
[right 1 " " down 1 left 3 " "]
[" " down 1 left 1 " " down 1 left 1 " "]
[" " down 1 left 2 " "]
]

```

```

floor: [
  31x5 31x6 31x7 31x8 31x9 31x10 31x11 31x12 31x13 31x14 31x15
  31x16 31x17 31x18 31x19 31x20 31x21 31x22 31x23 31x24 31x25
  31x26 31x27 31x28 31x29 31x30 31x31 31x32
]

oc: [
  [0x0 0x1 0x2 0x3] [0x0 1x0 2x0 3x0] [0x0 0x1 0x2 1x1]
  [0x1 1x0 1x1 2x1] [0x1 1x0 1x1 1x2] [0x0 1x0 1x1 2x0]
  [0x0 0x1 0x2 1x0] [0x0 0x1 1x1 2x1] [0x2 1x0 1x1 1x2]
  [0x0 1x0 2x0 2x1] [0x0 0x1 0x2 1x2] [0x1 1x1 2x0 2x1]
  [0x0 1x0 1x1 1x2] [0x0 0x1 1x0 2x0] [0x0 0x1 1x1 1x2]
  [0x1 1x0 1x1 2x0] [0x1 0x2 1x0 1x1] [0x0 1x0 1x1 2x1]
  [0x0 0x1 1x0 1x1]
]

width: [4 1 3 2 3 2 3 2 3 2 3 2 3 2 3 2 2]

a-line: copy [] loop 28 [append a-line " "]
a-line: rejoin [" |" to-string a-line "|"]
loop 30 [print a-line] prin " " loop 30 [prin "+" ] print ""

keys: open/binary/no-wait [scheme: 'console]
forever [
  random/seed now
  r: random 19
  xpos: 18
  for i 1 30 1 [
    pos: to-pair rejoin [i "x" xpos]
    if error? try [
      do compose/deep [
        prin tui [at (pos)] print tui shape/(r)
      ]
    ] []
    old-r: r
    old-xpos: xpos
    if not none? wait/all [keys :00:00.30] [
      keystroke: to-string to-char to-integer copy keys
      switch/default keystroke [
        "k" [if (xpos > 5) [
          xpos: xpos - 1
        ]]
        "l" [if (xpos < (33 - compose width/(r))) [
          xpos: xpos + 1
        ]]
        "o" [if (xpos < (33 - compose width/(r))) [
          switch to-string r [
            "1" [r: 2]
            "2" [r: 1]
            "3" [r: 6]
            "4" [r: 3]
            "5" [r: 4]
            "6" [r: 5]
            "7" [r: 10]
            "8" [r: 7]
            "9" [r: 8]
            "10" [r: 9]
            "11" [r: 14]
            "12" [r: 11]
            "13" [r: 12]
            "14" [r: 13]
            "15" [r: 16]
            "16" [r: 15]
            "17" [r: 18]
            "18" [r: 17]
            "19" [r: 19]
          ]
        ]]
      ]
    ]
  ]
]
if error? try [

```

```

        do compose/deep [
            prin tui [at (pos)] print tui shape/(old-r + 19)
        ]
    ] []
    stop: false
    foreach po compose oc/(r) [
        foreach coord floor [
            floor-y: to-integer first coord
            floor-x: to-integer second coord
            oc-y: i + to-integer first po
            oc-x: xpos + to-integer second po
            if (oc-y = (floor-y - 1)) and (floor-x = oc-x) [
                stop-shape-num: r
                stop: true
                break
            ]
        ]
    ]
    foreach po compose oc/(old-r) [
        foreach coord floor [
            floor-y: to-integer first coord
            floor-x: to-integer second coord
            oc-y: i + to-integer first po
            oc-x: old-xpos + to-integer second po
            if (oc-y = (floor-y - 1)) and (floor-x = oc-x) [
                stop-shape-num: old-r
                stop: true
                break
            ]
        ]
    ]
    if stop = true [
        left-col: second pos
        width-of-shape: length? compose oc/(stop-shape-num)
        right-col: left-col + width-of-shape - 1
        counter: 1
        for current-column left-col right-col 1 [
            add-coord: compose oc/(stop-shape-num)/(counter)
            new-floor-coord: (pos + add-coord)
            append floor new-floor-coord
            counter: counter + 1
        ]
        break
    ]
]
if (first pos) < 2 [
    prin tui [at 33x0]
    print "GAME OVER!!!"
    halt
]
if error? try [
    do compose/deep [
        prin tui [at (pos)] print tui shape/(old-r)
    ]
] []
for row 1 30 1 [
    line-is-full: true
    for column 5 32 1 [
        each-coord: to-pair rejoin [row "x" column]
        if not find floor each-coord [
            line-is-full: false
            break
        ]
    ]
    if line-is-full = true [
        remove-each cor floor [(first cor) = row]
        new-floor: copy [
            31x5 31x6 31x7 31x8 31x9 31x10 31x11 31x12 31x13
            31x14 31x15 31x16 31x17 31x18 31x19 31x20 31x21
            31x22 31x23 31x24 31x25 31x26 31x27 31x28 31x29
            31x30 31x31 31x32
        ]
    ]
]

```

```

        foreach cords floor [
            either ((first cords) < row) [
                append new-floor (cords + 1x0)
            ] [
                append new-floor cords
            ]
        ]
        floor: copy unique new-floor
        prin tui [clear]
        a-line: copy [] loop 28 [append a-line " "]
        a-line: rejoin ["  |" to-string a-line "|"]
        loop 30 [print a-line]
        prin "    " loop 30 [prin "+"] print ""
        foreach was-here floor [
            if not ((first was-here) = 31) [
                prin tui compose [at (was-here)]
                prin "#"
            ]
        ]
    ]
]
]

```

Now that the program is working to my original specs, I want to make it look a bit spiffier. First of all, the playing area looks too wide and tall. I check Rebris, and it's only 10 columns wide by 20 rows tall. I like that look and feel, so I adjust the floor block, the code that draws the static backdrop, and all computations related to the right boundaries of the playing field and the number of rows, to reflect that change.

I also want to print out a "Tetris" title header, some keyboard instructions, and a score header. Tui allows me to print this text to the right of the playing field where I want it:

```

print tui [
    at 4x21 "TETRIS" at 5x21 "-----"
    at 7x20 "'K' = left" at 8x20 "'L' = right"
    at 9x20 "'O' = spin" at 11x21 "Score:"
]

```

Keeping track of the score is simple. When the program starts, a "score" variable is created and set to 0 ("score: 0"). Every time a piece stops falling, 10 points are added to the score. That number is printed beneath the score header (notice that the score number must first be converted to a string, in order to be printed by tui):

```

score: score + 10
print tui compose [at 13x21 (to-string score)]

```

Every time a row is filled in, 1000 points are added to the score. When the screen is redrawn to reflect the newly erased row, the tui code that prints the backdrop also prints out the updated score:

```

print tui compose [
    at 4x21 "TETRIS" at 5x21 "-----"
    at 7x20 "'K' = left" at 8x20 "'L' = right"
    at 9x20 "'O' = spin" at 11x21 "Score:"
    at 13x21 (to-string score)
]

```

Next, I want to add a pause key. This will fit in the switch structure that watches for keystrokes. Whenever the "P" key is pressed, print a message indicating that the game has been paused. Use an "ask" action to wait for input, and then print two blank lines to erase the pause message and any errant characters that the user may type in before hitting the [Enter] key:

```

"P" [

```

```

    print tui [
      at 23x0 "Press [Enter] to continue"
    ]
    ask ""
    print tui [
      at 24x0 "
      at 23x0 "
    ]
  ]
]

```

After posting some of this code to the REBOL mail list, another bug has become obvious. If the insert key or the arrow keys are pressed during game play, the game crashes. The following code produces a "*** Math Error: Math or number overflow" when those keys are evaluated:

```

keystroke: to-string to-char to-integer copy keys

```

To fix that, I create my own error check. The keys codes for the arrow keys are #{1B5B41}, #{1B5B42}, #{1B5B43}, #{1B5B44}, and #{1B5B327E}. I check to see if they've been pressed first. If not, run the code above:

```

now-key: copy keys
if not (
  find [
    #{1B5B41} #{1B5B42} #{1B5B43}
    #{1B5B44} #{1B5B327E}
  ] (now-key)
) [keystroke: to-string to-char to-integer now-key]

```

That works, but a message to the list by Gabrielle Santilli creates a simpler solution. It turns out that I should have looked at the console port format a bit more carefully. All that's needed to get the keystroke is:

```

keystroke: to-string copy keys

```

And that does not produce errors for any entered keys.

I added all the above code to the program, and then tested everything. In doing so, I made an interesting discovery - it turns out that the code which produced the ghostly key input error in the shape printing routines is in a section of the TUI dialect that enables one to check for screen size. I think the error has something to do with the fact that I'm "compose"ing the results - not sure, but it doesn't matter. Since I'm not using that function, I simply remove it from the code. While I'm at it, I remove all the other parts of the TUI dialect that I'm not using. It turns out that all I need is:

```

tui: func [commands [block!]] [
  string: copy ""
  cmd: func [s][join "^(1B)[" s]
  arg: parse commands [
    any [
      'clear (append string cmd "J") |
      'up set arg integer! (append string cmd [
        arg "A"]) |
      'down set arg integer! (append string cmd [
        arg "B"]) |
      'right set arg integer! (append string cmd [
        arg "C"]) |
      'left set arg integer! (append string cmd [
        arg "D"]) |
      'at set arg pair! (append string cmd [
        arg/x ";" arg/y "H" ]) |
      set arg string! (append string arg)
    ]
  ]
  end

```

```

    ]
    string
]

```

With that error gone, I can remove all the error checking routines in the program (they were causing some additional problems). Now Tetris feels like a reasonably complete program. Here's the final code:

```

REBOL [Title: "Tetris"]

tui: func [commands [block!]] [
    string: copy ""
    cmd: func [s][join "^(1B)[" s]
    arg: parse commands [
        any [
            'clear (append string cmd "J") |
            'up set arg integer! (append string cmd [
                arg "A"]) |
            'down set arg integer! (append string cmd [
                arg "B"]) |
            'right set arg integer! (append string cmd [
                arg "C"]) |
            'left set arg integer! (append string cmd [
                arg "D"]) |
            'at set arg pair! (append string cmd [
                arg/x ";" arg/y "H" ]) |
            set arg string! (append string arg)
        ]
    ]
    end
]
string
]

shape: [
["#####"]
["#" down 1 left 1 "#" down 1 left 1 "#" down 1 left 1 "#"]
["#### down 1 left 2 "#"]
[right 1 "#" down 1 left 2 "##" down 1 left 1 "#"]
[right 1 "#" down 1 left 2 "###"]
["#" down 1 left 1 "##" down 1 left 2 "#"]
["#### down 1 left 3 "#"]
["### down 1 left 1 #" down 1 left 1 "#"]
[right 2 "#" down 1 left 3 "###"]
["#" down 1 left 1 #" down 1 left 1 "##"]
["#### down 1 left 1 "#"]
[right 1 #" down 1 left 1 #" down 1 left 2 "##"]
["#" down 1 left 1 "####"]
["### down 1 left 2 #" down 1 left 1 "#"]
["### down 1 left 1 "##"]
[right 1 #" down 1 left 2 "##" down 1 left 2 "#"]
[right 1 "##" down 1 left 3 "###"]
["#" down 1 left 1 "##" down 1 left 1 "#"]
["### down 1 left 2 "##"]
;
[" "]
[" " down 1 left 1 " " down 1 left 1 " " down 1 left 1 " "]
[" " down 1 left 2 " "]
[right 1 " " down 1 left 2 " " down 1 left 1 " "]
[right 1 " " down 1 left 2 " "]
[" " down 1 left 1 " " down 1 left 2 " "]
[" " down 1 left 3 " "]
[" " down 1 left 1 " " down 1 left 1 " "]
[right 2 " " down 1 left 3 " "]
[" " down 1 left 1 " " down 1 left 1 " "]
[" " down 1 left 1 " "]
[right 1 " " down 1 left 1 " " down 1 left 2 " "]
[" " down 1 left 1 " "]
[" " down 1 left 2 " " down 1 left 1 " "]
[" " down 1 left 1 " "]
[right 1 " " down 1 left 2 " " down 1 left 2 " "]

```



```

    [right 1 " " down 1 left 3 " "]
    [" " down 1 left 1 " " down 1 left 1 " "]
    [" " down 1 left 2 " "]
]
floor: [
    21x5 21x6 21x7 21x8 21x9 21x10 21x11 21x12 21x13 21x14 21x15
]
oc: [
    [0x0 0x1 0x2 0x3] [0x0 1x0 2x0 3x0] [0x0 0x1 0x2 1x1]
    [0x1 1x0 1x1 2x1] [0x1 1x0 1x1 1x2] [0x0 1x0 1x1 2x0]
    [0x0 0x1 0x2 1x0] [0x0 0x1 1x1 2x1] [0x2 1x0 1x1 1x2]
    [0x0 1x0 2x0 2x1] [0x0 0x1 0x2 1x2] [0x1 1x1 2x0 2x1]
    [0x0 1x0 1x1 1x2] [0x0 0x1 1x0 2x0] [0x0 0x1 1x1 1x2]
    [0x1 1x0 1x1 2x0] [0x1 0x2 1x0 1x1] [0x0 1x0 1x1 2x1]
    [0x0 0x1 1x0 1x1]
]
width: [4 1 3 2 3 2 3 2 3 2 3 2 3 2 3 2 2]
score: 0

prin tui [clear]
a-line: copy [] loop 11 [append a-line " "]
a-line: rejoin [" |" to-string a-line "|"]
loop 20 [print a-line] prin " " loop 13 [prin "+"] print ""
print tui compose [
    at 4x21 "TETRIS" at 5x21 "-----"
    at 7x20 "Use arrow keys" at 8x20 "to move/spin."
    at 10x20 "'P' = pause"
    at 13x20 "SCORE: " (to-string score)
]

keys: open/binary/no-wait [scheme: 'console]
forever [
    random/seed now
    r: random 19
    xpos: 9
    for i 1 20 1 [
        pos: to-pair rejoin [i "x" xpos]
        do compose/deep [prin tui [at (pos)] print tui shape/(r)]
        old-r: r
        old-xpos: xpos
        if not none? wait/all [keys :00:00.30] [
            switch/default to-string copy keys [
                "p" [
                    print tui [
                        at 23x0 "Press [Enter] to continue"
                    ]
                    ask ""
                    print tui [
                        at 24x0 "
                        at 23x0 "
                    ]
                ]
            ]
            "^[[D" [if (xpos > 5) [
                xpos: xpos - 1
            ]]
            "^[[C" [if (xpos < (16 - compose width/(r))) [
                xpos: xpos + 1
            ]]
            "^[[A" [if (xpos < (16 - compose width/(r))) [
                switch to-string r [
                    "1" [r: 2]
                    "2" [r: 1]
                    "3" [r: 6]
                    "4" [r: 3]
                    "5" [r: 4]
                    "6" [r: 5]
                    "7" [r: 10]
                    "8" [r: 7]
                    "9" [r: 8]
                    "10" [r: 9]
                    "11" [r: 14]
                    "12" [r: 11]
                ]
            ]
        ]
    ]
]

```

```

        "13" [r: 12]
        "14" [r: 13]
        "15" [r: 16]
        "16" [r: 15]
        "17" [r: 18]
        "18" [r: 17]
        "19" [r: 19]
    ]
]
]
] []
]
do compose/deep [
    prin tui [at (pos)] print tui shape/(old-r + 19)
]
stop: false
foreach po compose oc/(r) [
    foreach coord floor [
        floor-y: to-integer first coord
        floor-x: to-integer second coord
        oc-y: i + to-integer first po
        oc-x: xpos + to-integer second po
        if (oc-y = (floor-y - 1)) and (floor-x = oc-x) [
            stop-shape-num: r
            stop: true
            break
        ]
    ]
]
foreach po compose oc/(old-r) [
    foreach coord floor [
        floor-y: to-integer first coord
        floor-x: to-integer second coord
        oc-y: i + to-integer first po
        oc-x: old-xpos + to-integer second po
        if (oc-y = (floor-y - 1)) and (floor-x = oc-x) [
            stop-shape-num: old-r
            stop: true
            break
        ]
    ]
]
if stop = true [
    left-col: second pos
    width-of-shape: length? compose oc/(stop-shape-num)
    right-col: left-col + width-of-shape - 1
    counter: 1
    for current-column left-col right-col 1 [
        add-coord: compose oc/(stop-shape-num)/(counter)
        new-floor-coord: (pos + add-coord)
        append floor new-floor-coord
        counter: counter + 1
    ]
    break
]
]
do compose/deep [prin tui [at (pos)] print tui shape/(old-r)]
if (first pos) < 2 [
    prin tui [at 23x0]
    print "    GAME OVER!!!^/^^/"
    halt
]
score: score + 10
print tui compose [at 13x28 (to-string score)]
for row 1 20 1 [
    line-is-full: true
    for column 5 15 1 [
        each-coord: to-pair rejoin [row "x" column]
        if not find floor each-coord [
            line-is-full: false
            break
        ]
    ]
]

```


1. Save high scores to disk.
2. Add a way to incrementally increase the speed at which shapes drop. Do this every time a certain number of rows is cleared.
3. Add a "next piece" preview.
4. Look for a way to remove the cursor from the printout, so that it's not visible along the left side of the wall as the shapes fall.
5. Add sound. Play tones for each event that occurs, and play a background tune while the game is running.
6. Rewrite the entire program using GUI techniques, instead of console text characters and TUI.

Looking at my coding process in retrospect, I should note some criticisms. One element that annoyed me was a set of badly chosen variable names. I initially used "r", for example, to represent the current shape number because it was first used to represent a random number. "R" is not so descriptive, and it was hard to remember what "r" represented while I was coding. The same was true of "i", which became more important as the loop that dropped the shapes grew in complexity. I left those variables as they were in this case study so that the lines of code fit neatly onto this web page, but in my own coding I choose to use more descriptive variables. Doing that in general makes code more readable and easier to think through.

The Moral of the Story:

Whether or not you're interested in game programming, and despite the fact that the final product of this case study is a bland implementation of Tetris, some general understanding about coding can be gained from the thought process covered in this section. It's typical of any general coding project you'll encounter: start with a design concept, outline the main structure of the program you imagine, use pseudo code to guide you from the "what am I trying to do?" through the "how do I code it" stages, and refine the detail of your outline by testing and experimenting with small code chunks along the way.

In general, if you can't think through the process of "what am I trying to accomplish" in a structured way, then you won't be able to write the code to accomplish it. Once you've got a basic grasp of language concepts and syntax, you'll see that writing code just takes lots of creative organization and experimentation. Keep a language reference close at hand, and you can work out the syntax of virtually any code you need to write. That's only a matter of knowing which functions and constructs are available to solve your problems, and looking up the format for those you're not familiar with. The difficult part in any coding situation is mapping each small thought process to a data construct, conditional expression, looping routine, function definition, existing code module, word label, etc. For large projects, you'll typically need an outline because it's so easy to get lost in the minute coding details along the way. Start with a top down approach, conceive and design a flow chart/outline, and then flesh out the details of each section until you've got code written to solve each design concept. Once you become familiar with that process, experience will show that you can code solutions for virtually any problem you encounter.

You'll find that in many cases REBOL allows you to think directly in code more easily than you can with pseudo code. That's because REBOL's high level design is meant to be human readable and human "thinkable". Although many coding concepts in all computer languages are generally the same, most other languages are more overtly designed and constrained by legacy concepts derived from requirements about how computers operate. Some languages tend to require much more low level coding or coersing of disparate modules to fit together in order to make the conceptual design take shape in final code form. Other languages get you bogged down in thinking about higher level OOP constructs. A lack of universal data structures such as REBOL's block/series structure, a lack of built in native data types such as time, tuples, pairs, money, etc., and a less natural way of structuring functions, variables and module definitions (not using words and dialects in a natural language way), require unique and contrived constructs to be designed to manipulate data in each individual program. In the most popular languages, program authors typically have to be more concerned about managing the rudimentary memory and cpu actions of the computer for everything that occurs in a program. That enables a greater measure of control over how a computer uses it's hardware resources, but it's very far from the way humans naturally think about solving real life situations. REBOL allows things to be done in a way of thinking that's closer to the outline stage. When you get used to writing REBOL code, you'll find that it saves a tremendous amount of time compared to other languages. Remember along the way that no matter what computer language(s) you learn, understanding how to think through the "what I am I trying to accomplish" outline is essential to writing code that accomplishes your task.

10.10 Case 10 - Scheduling Teachers, Part Two

After several months of using the teacher scheduling application described in the first case study, my business expanded, and the teaching staff grew. With the way things worked in my short initial program, I would have to create a new folder on the web site and compile a unique version of the program for each new teacher. This would require recompiling and uploading a new version, for each teacher, every time I alter the program. I wanted to make a multi-user version of the application to simplify setup and to save maintenance time. I also wanted to add some error checking and a simple password scheme to the existing program. To create a new version of the application, here's my concept in outline/pseudo code form:

1. Maintain the existing folder and file structure on the web site (<http://website.com/teacher/name>,

- schedule.txt, and index.php).
2. Add a file to the web site containing a list of current teachers and associated passwords. Put it outside the public_html folder, so that people can't download it without a password.
 3. In the application, start by downloading that file from the website (using ftp).
 4. Display a text list of teacher names from the downloaded file.
 5. When a teacher name is selected, request a password from the user and check that it matches the associated password for the given teacher.
 6. Append the teacher name to the http and ftp URLs, and run the program as before.
 7. Add some error checking and backup routines every time the data is read or written locally, or on the web server. That way, no data is ever lost.
 8. Compile the program and upload it to the web site. Point all links on the index.php pages to that single file. Now, any time I want to add a new teacher, all I need to do is add the new teacher name and password to the downloadable text file and copy a blank index.php and schedule.txt to a new folder on the web server. If I ever make additional changes to the program, I only need to recompile and upload that single program file.

To start things off, I created a text file called "teacherlist.txt" and stored it outside the public_html folder on the web server. It's formatted like this:

```
[ "mark" "markspassword" ] [ "ryan" "ryanspassword" ]
[ "nick" "nickspassword" ] [ "peter" "peterspassword" ]
[ "rudi" "rudispassword" ] [ "tom" "tomspassword" ]
```

The first thing I do in the program is read the data:

```
teacherlist: load ftp://user:pass@website.com/teacherlist.txt
```

Next, display a list of the teachers. The first item in each block of teacherlist.txt is the teacher name. A foreach loop reads each of those names into a new block, and that block is displayed using a GUI text-list widget:

```
teachers: copy []
foreach teacher teacherlist [append teachers first teacher]
view center-face layout [
    text-list data teachers [folder: value unview]
]
```

Next, get the password from the user and use a foreach loop to look through the list, checking for a match in teacher names and passwords entered by the user (the first and second elements, respectively, in each block):

```
pass: request-pass/only
correct: false
foreach teacher teacherlist [
    if ((first teacher) = folder) and (pass = (second teacher)) [
        correct: true
    ]
]
if correct = false [alert "Incorrect password." quit]
```

I add the following line to the script, which keeps REBOL from terminating the script when the [Esc] key is pressed. That behavior is the default in the REBOL interpreter, and makes it easy for someone to just stop the script and view the teacherlist. (I'm not so concerned about security here, but I don't want passwords to be blatantly available):

```
system/console/break: false
```

Finally, I come up with an error message to be executed any time an Internet connection isn't available. It

allows the user to read any of the recently backed up schedule.txt files so that the program is useful even if an Internet connection isn't available:

```
error-message: does [
  ans: request {Internet connection is not available.
    Would you like to see one of the recent local backups?}
  either ans = true [
    editor to-file request-file quit
  ][
    quit
  ]
]
```

I wrap all attempts to connect to the Internet in "error? try" routines, and duplicate the original backup routine from the initial program so that no data is ever lost. Here's the final code:

```
REBOL [title: "Lesson Scheduler"]

system/console/break: false
error-message: does [
  ans: request {Internet connection is not available.
    Would you like to see one of the recent local backups?}
  either ans = true [
    editor to-file request-file quit
  ][
    quit
  ]
]

if error? try [
  teacherlist: load ftp://user:pass@website.com/teacherlist.txt
][
  error-message
]
teachers: copy []
foreach teacher teacherlist [append teachers first teacher]
view center-face layout [
  text-list data teachers [folder: value unview]
]

pass: request-pass/only
correct: false
foreach teacher teacherlist [
  if ((first teacher) = folder) and (pass = (second teacher)) [
    correct: true
  ]
]
if correct = false [alert "Incorrect password." quit]

url: rejoin [http://website.com/teacher/ folder]
ftp-url: rejoin [
  ftp://user:pass@website.com/public_html/teacher/ folder
]

if error? try [
  write %schedule.txt read rejoin [url "/schedule.txt"]
][
  error-message
]

; backup (before changes are made):
cur-time: to-string replace/all to-string now/time ":" "-"
; local:
write to-file rejoin [
  folder "-schedule_" now/date "_" cur-time ".txt"
] read %schedule.txt
; online:
if error? try [
```

```

        write rejoin [
            ftp-url "/" now/date "_" cur-time
        ] read %schedule.txt
    ][
        error-message
    ]

    editor %schedule.txt

    ; backup again (after changes are made):
    cur-time: to-string replace/all to-string now/time ":" "-"
    write to-file rejoin [
        folder "-schedule_" now/date "_" cur-time ".txt"
    ] read %schedule.txt
    if error? try [
        write rejoin [
            ftp-url "/" now/date "_" cur-time
        ] read %schedule.txt
    ][
        alert "Internet connection not available while backing up."
    ]

    ; save to web site:
    if error? try [
        write rejoin [ftp-url "/schedule.txt"] read %schedule.txt
    ][
        alert {Internet connection not available while updating web
        site. Your schedule has NOT been saved online.}
        quit
    ]
    browse url

```

With the new application complete, I wanted to create an additional cgi application for the web site to collectively display all available times in each of the teachers' schedules. This would help with scheduling because both students and management could instantly see a bird's eye view of all open appointment times, on a single web page. In order for that display to be viewable by the general public, I want the cgi app to strip out all personal data contained in the schedules. To create the cgi, I need to search each line of schedule text for "----". If a line contains the characters "----", that time is available. Here's a pseudo code outline that I thought through as I organized the process:

1. Make a list of all the teacher pages. Store the links in a block.
2. Use a foreach loop to cycle through each page in the list. Read in the data on each page in line format, using another foreach loop.
3. For each line, use a find function to check whether the line contains the name of a day of the week, or the characters "----". If so, print the line, adding some additional formatting to separate days as headers. Also print each page link as a header separating each teacher's schedule in the printout.

First, I created the block of links:

```

page-list: [
    http://website.com/teacher/ryan
    http://website.com/teacher/mark
    http://website.com/teacher/nick
    http://website.com/teacher/peter
    http://website.com/teacher/tom
    http://website.com/teacher/rudi
]

```

For step 2, I created the foreach loop to read each page:

```

foreach page page-list [
    data: read/lines page
]

```

Inside that loop, I added the code to print out the teacher name and day headers, and the available times:

```

foreach page page-list [
  print newline
  print to-string page
  print ""
  data: read/lines page
  week: ["MONDAY" "TUESDAY" "WEDNESDAY" "THURSDAY" "FRIDAY"
        "SATURDAY" "SUNDAY"]
  foreach line data [
    foreach day week [
      if find line day [print "" print line print ""]
    ]
    if find line "----" [print line]
  ]
]

```

Now I've got a little command line application that does what I need:

```

REBOL []
page-list: [
  http://website.com/teacher/ryan
  http://website.com/teacher/mark
  http://website.com/teacher/nick
  http://website.com/teacher/peter
  http://website.com/teacher/tom
  http://website.com/teacher/rudi
]
foreach page page-list [
  print newline
  print to-string page
  print ""
  data: read/lines page
  week: ["MONDAY" "TUESDAY" "WEDNESDAY" "THURSDAY" "FRIDAY"
        "SATURDAY" "SUNDAY"]
  foreach line data [
    foreach day week [
      if find line day [print "" print line print ""]
    ]
    if find line "----" [print line]
  ]
]

```

Next, to the basic CGI framework provided earlier in this tutorial, I simply added the code above. The only real changes I needed to make were some added "< B R >"s (HTML line ends) to make the text display properly in the browser:

```

#!/home/path/public_html/rebol/rebol -cs
REBOL []
print "content-type: text/html^/"
print [<HTML><HEAD><TITLE>"Available Appointment Times"</TITLE>]
print [</HEAD><BODY>]
page-list: [
  http://website.com/teacher/ryan
  http://website.com/teacher/mark
  http://website.com/teacher/nick
  http://website.com/teacher/peter
  http://website.com/teacher/tom
  http://website.com/teacher/rudi
]
foreach page page-list [
  print [<BR><BR>]
  print to-string page
  print [<BR>]
  data: read/lines page
  week: ["MONDAY" "TUESDAY" "WEDNESDAY" "THURSDAY" "FRIDAY"
        "SATURDAY" "SUNDAY"]

```



```

    foreach line data [
        foreach day week [
            if find line day [print [<BR>] print line print [<BR><BR>]]
        ]
        if find line "----" [print line print [<BR>]]
    ]
]
print [</BODY></HTML>]

```

As more teachers were added to the scheduling system, it became apparent that a CGI version of the editor would be helpful (for use on mobile phones, at work, and in other environments where installing an executable was problematic). For that, I simply used the password protected online text editor, found earlier in this tutorial:

```

#!/home/path/public_html/rebol/rebol -cs
REBOL []
print "content-type: text/html^/"
print [<HTML><HEAD><TITLE>"Edit Schedule"</TITLE></HEAD><BODY>]

; submitted: decode-cgi system/options/cgi/query-string

; We can't use the above normal line to decode, because
; we're using the post method to submit data (because data
; from the textarea may get too big for the get method).
; Use the following function to process data from a post
; method instead:

read-cgi: func [/local data buffer][
    switch system/options/cgi/request-method [
        "POST" [
            data: make string! 1020
            buffer: make string! 16380
            while [positive? read-io system/ports/input buffer 16380][
                append data buffer
                clear buffer
            ]
        ]
        "GET" [data: system/options/cgi/query-string]
    ]
    data
]

submitted: decode-cgi read-cgi

; if schedule.txt has been edited and submitted:

if ((submitted/2 = "save") or (submitted/2 = "save")) [
    ; save newly edited schedule:
    write to-file rejoin ["/" submitted/6 "/schedule.txt"] submitted/4
    print ["Schedule Saved."]
    print rejoin [
        {<META HTTP-EQUIV="REFRESH" CONTENT="0;
        URL=http://website.com/folder/"
        submitted/6 {">}
    ]
    quit
]

; if user is just opening page (i.e., no data has been submitted
; yet), request user/pass:

if ((submitted/2 = none) or (submitted/4 = none)) [
    print [<strong>"W A R N I N G - "]
    print ["Private Server, Login Required:"</strong><BR><BR>]
    print [<FORM ACTION="./edit.cgi">]
    print [" Username: " <input type=text size="50" name="name"><BR><BR>]
    print [" Password: " <input type=text size="50" name="pass"><BR><BR>]
    print [<INPUT TYPE="SUBMIT" NAME="Submit" VALUE="Submit">]
    print [</FORM>]
]

```

```

quit
]

; check user/pass against those in teacherlist.txt,
; end if incorrect:

teacherlist: load %teacherlist.txt
folder: submitted/2
password: submitted/4
response: false
foreach teacher teacherlist [
    if ((first teacher) = folder) and (password = (second teacher)) [
        response: true
    ]
]
if response = false [print "Incorrect Username/Password." quit]

; if user/pass is ok, go on:

; backup (before changes are made):

cur-time: to-string replace/all to-string now/time ":" "-"
schedule_text: read to-file rejoin ["/" folder "/schedule.txt"]
write to-file rejoin [
    "/" folder "/" now/date "_" cur-time ".txt"] schedule_text

print [<strong>"Be sure to SUBMIT when done:"</strong><BR><BR>]
print [<FORM method="post" ACTION="./edit.cgi">]
print [<INPUT TYPE=hidden NAME=submit_confirm VALUE="save">]
print [<textarea cols="100" rows="15" name="contents">]
print [schedule_text]
print [</textarea><BR><BR>]
print rejoin [{<INPUT TYPE=hidden NAME=folder VALUE="} folder {">}]
print [<INPUT TYPE="SUBMIT" NAME="Submit" VALUE="Submit">]
print [</FORM>]
print [</BODY></HTML>]

```

Now there's a way for all the teachers to edit their schedules. I can add a new teacher to the system in about 5 seconds (just create a new directory on the server and copy blank schedule.txt and index.php files). Anyone involved in scheduling can make changes online, regardless of location or computer type, and everyone stays synchronized. In addition, anyone can get an instant bird's eye view of all available appointment times - this helps tremendously when scheduling new students and maintaining daily activities.

10.11 Case 11 - An Online Member Page CGI Program

One of my friends wanted to create an online member database for a local club. He wanted members to be able to sign up and add their contact information, upload photos, and add info about themselves. He was tired of manually making changes to the members' pages, and wanted users to be able to add, edit, and delete their own information. He wanted basic password enabled access so that users could only edit their own information, and he wanted a back end utility that allowed him to make changes as administrator, and which automatically saved each successive change to the database, so that no data could ever be lost. He also wanted users automatically emailed their password, in case they forgot.

Here was my basic thought process and plan of attack:

1. This will be an online system (a web site), so the user interface will be a set of HTML pages that display each user's information, as well as a set of HTML forms for users to enter information. We decided to have the page display the following fields: Name, Address, Phone, Email, Age, Language, Height, Date the user was added, and an uploaded photo.
2. The data will be stored in some sort of online database. Since this is a small group with only a few users, I decided to create a simple flat file database - just a text file filled with blocks of REBOL data, one block per user, stored on the web server.
3. The page that pulls the info from the database and displays it in the above HTML will basically be a REBOL CGI application that runs a "foreach" loop to print each of the entries in the above HTML format. The pages where the users enter their information will be forms that submit the information to a REBOL CGI that appends it to the database text file. The pages where the users edit their information will be forms that display the information currently in the selected entry, without the password. When the user submits the new password and updated info, the CGI checks that the submitted password matches the existing password for that entry, and then replaces the old block with the new one, in the database text file. The code for emailing the user a forgotten password and

- for automatically backing up data will also be put here.
4. An image upload/update page also needs to be created. This will be an HTML form that accepts a local image file on the user's computer, submits that file to the CGI, which in turn writes that binary data to a directory on the web server, creates an HTML image link to it, and adds that link to the appropriate user entry in the database text file.
 5. The back end will simply be the password protected text editor explored in case study #8, with links to all the backup text files, for easy recovery (copy/paste) of lost data.

Here was the basic HTML layout I came up with for step 1. Each entry in the database will be displayed using this template:

```
<HR><BR> Date/Time: 23-Mar-2008/13:11:42-7:00

<A HREF="./index.cgi?function=">edit | </A>
<A HREF="./index.cgi?function=">delete</A>

<TABLE background="" border=0 cellPadding=2 cellSpacing=2
  width="100%"><TR>

<TD width = "600">
<BR>
<FONT FACE="Courier New, Courier, monospace">Name:           </FONT>
<STRONG>The User Name Goes Here</STRONG>
<BR>
<FONT FACE="Courier New, Courier, monospace">Address:           </FONT>
<STRONG>The Address Goes Here</STRONG>
<BR>
<FONT FACE="Courier New, Courier, monospace">Phone:           </FONT>
<STRONG>The Phone</STRONG>
<BR>
<FONT FACE="Courier New, Courier, monospace">Email:           </FONT>
<STRONG>The Email</STRONG>
<BR>
<FONT FACE="Courier New, Courier, monospace">Age:           </FONT>
<STRONG>The Age</STRONG>
<BR>
<FONT FACE="Courier New, Courier, monospace">Language:       </FONT>
<STRONG>The Language</STRONG>
<BR>
<FONT FACE="Courier New, Courier, monospace">Height:        </FONT>
<STRONG>The Height</STRONG>
<BR><BR>
</TD>

<TD width="170" valign="center">
<A HREF="./default.jpg" target=_blank><IMG align=baseline alt=""
  border=0 hspace=0 src="./default.jpg" width="160" height="120">
</A>
</TD>

</TR></TABLE>

Some Additional Notes Go Here...

<BR><BR>
```

The database design for step 2 was even simpler to create. Here's an example of what each block looks like. Notice that each entry in the database is just a text string separated by spaces, for each field of info we want displayed on the member page. In the block, I added a link to a default image, in case the user didn't upload their own photo. This file was saved as %bb.db:

```
[ "Username" "19-Feb-2008/4:55:59-8:00" "1 Address St."
  "123-456-7890" "name@website.com" "40"
  {REBOL, C, C++, Python, PHP, Basic, AutoIt, others...}
  "6'" {I'm a nobody - just a test account.} "password"
  [
    {<a href = "./default.jpg" target=_blank>
      <IMG align=baseline alt="" border=0 hspace=0
```

```

        src="./default.jpg" width="160" height="120"></a>}
    ]
]

["Tester McUser" "22-Feb-2008/13:14:44-8:00" "1 Way Lane"
 "234-567-8910" "tester@website.com" "35" "REBOL"
 {5' 11"} "I'm just another test account." "password"
 [
    {<a href = "./files/photo.jpg" target=_blank>
    <IMG align=baseline alt="" border=0 hspace=0
    src="./files/photo.jpg" width="160" height="120"></a>}
  ]
]
]

```

At this point I could begin the work of step 3, creating a CGI program that prints the HTML page in step 1, with the above data. Here's a simple CGI script that simply prints the HTML design together with the entries from the database inserted:

```

#! /home/path/public_html/rebol/rebol -cs
REBOL []
print "content-type: text/html^/"
print read %header.html

bbs: load %bb.db ; load the database info

print [<center><table border=1 cellpadding=10 width=90%><tr><td>]
print {<TABLE background="" border=0 cellpadding=0 cellspacing=0
  height="100%" width="100%"><tr><td width = "600">}
print [<hr>]
reverse bbs
foreach bb bbs [
  print [<BR>]
  print rejoin ["Date/Time: " bb/2]
  print " "
  print rejoin [{<a href="./index.cgi?function=">edit | </a>}]
  print rejoin [{<a href="./index.cgi?function=">delete</a>}]
  print " "
  print {<TABLE background="" border=0 cellpadding=2
    cellspacing=2 height="100%" width="100%"><tr>
    <td width = "600"><BR>}
  print rejoin [{<FONT FACE="Courier New, Courier, monospace">
    "Name: </FONT><strong>" bb/1 "</strong>"}]
  print [<BR>]
  print rejoin [{<FONT FACE="Courier New, Courier, monospace">
    "Address: </FONT><strong>" bb/3 "</strong>"}]
  print [<BR>]
  print rejoin [{<FONT FACE="Courier New, Courier, monospace">
    "Phone: </FONT><strong>" bb/4 "</strong>"}]
  print [<BR>]
  print rejoin [{<FONT FACE="Courier New, Courier, monospace">
    "Email: </FONT><strong>" bb/5 "</strong>"}]
  print [<BR>]
  print rejoin [{<FONT FACE="Courier New, Courier, monospace">
    "Age: </FONT><strong>" bb/6 "</strong>"}]
  print [<BR>]
  print rejoin [{<FONT FACE="Courier New, Courier, monospace">
    "Language: </FONT><strong>" bb/7 "</strong>"}]
  print [<BR>]
  print rejoin [{<FONT FACE="Courier New, Courier, monospace">
    "Height: </FONT><strong>" bb/8 "</strong>"}]
  print [<BR><BR>]
  print </td>
  print {<td width = "170" valign = "center">}
  print bb/11 ; image link
  print {</td></tr></table>}
  print bb/9 ; "other information " text
  print [<BR><BR><HR>]
]
print [</td></tr></td></tr></td></tr></table>]

```

```
print [</td></tr></table></center>]
print read %footer.html
```

To that code, there were a number of features that I realized I should add. First, I wanted to munge email addresses so that they were less likely to get collected by spam bots. This line of code does the job well enough for my needs. It turns "name@address.com" into "name at address dot com":

```
(replace/all (replace bb/5 "@" " at ") "." " dot ")
```

I also wanted any http:// links in the "other information" section to be automatically linked. To do that, I used parse to search for "http://" and the ending space character, then wrapped that link in the required < A H R E F = ...> tags. Here's the code:

```
bb_temp: copy bb/9
bb_temp2: copy bb_temp
parse/all bb_temp [any [
  thru "http://" copy link to " " (replace bb_temp2
    (rejoin [{http://} link]) (rejoin [
      { <a href="} {http://} link
      {" target=_blank>http://} link {</a> }]))
    ]
  to end
]
```

Furthermore, I wanted to have line endings in the "other information" section automatically converted to HTML "< b r >"s, so that they display correctly on the web page. That's easy:

```
replace/all bb_temp newline " <br> "
```

My friend wanted a count displayed of the total number of members. That's also easy, with "length? bbs":

```
print rejoin [{<font size=5> Members: (} length? bbs {)</font></td>}]
```

I also added a "join now" link to the CGI page where users would be able to add themselves to the database (that page hasn't been created yet):

```
print {<td><a href="./add.cgi">Join Now</a></td></tr></table><BR>}
```

In order for users to edit/delete their info later, I needed to tag each displayed entry with a unique number to automatically select the appropriate block from the database. To do this, I added a counter variable to the foreach loop, and incremented it each time through the loop (counter: counter + 1). Then I replaced the generic edit and delete links in the code above ...

```
print rejoin [{<a href="./index.cgi?function=">edit | </a>}]
print rejoin [{<a href="./index.cgi?function=">delete</a>}]
```

... with links that contain the counter, and which can be deciphered by a CGI program as "get" data:

```
print rejoin [
  {<a href="./index.cgi?function=edititemnumber&messagenumber=}
  counter {&Submit=Post+Message">edit | </a>}
]
print rejoin [
```

```

    {<a href="./index.cgi?function=deleteitemnumber&messagenumber=}
    counter {&Submit=Post+Message">delete</a>}
]

```

Here's the script, as it stands so far:

```

#! /home/path/public_html/rebol/rebol -cs
REBOL []
print "content-type: text/html^/"
print read %header.html

bbs: load %bb.db

print [<center><table border=1 cellpadding=10 width=90%><tr><td>]

print-all: does [
  print {<TABLE background="" border=0 cellpadding=0 cellspacing=0
    height="100%" width="100%"><tr><td width = "600">}
  print rejoin [{<font size=5> Members: (} length? bbs {)</font></td>}]
  print {<td><a href="./add.cgi">Join Now</a></td></tr></table><BR>}
  print [<hr>]
  counter: 1
  reverse bbs
  foreach bb bbs [
    print [<BR>]
    if bb/1 <> "file uploaded" [
      print rejoin ["Date/Time: " bb/2]
      print " "
      print rejoin trim [
        {<a href=
          "./index.cgi?function=edititemnumber&messagenumber=}
          counter
          {&Submit=Post+Message">edit | </a>}
      ]
      print rejoin trim [
        {<a href=
          "./index.cgi?function=deleteitemnumber&messagenumber=}
          counter
          {&Submit=Post+Message">delete</a>}
      ]
      print " "
      print {
        <TABLE background="" border=0 cellpadding=2
        cellspacing=2 height="100%" width="100%"><tr>
        <td width = "600"><BR>
      }
      print rejoin [{<FONT FACE="Courier New, Courier, monospace">}
        "Name: </FONT><strong>" bb/1 "</strong>"]
      print [<BR>]
      print rejoin [{<FONT FACE="Courier New, Courier, monospace">}
        "Address: </FONT><strong>" bb/3 "</strong>"]
      print [<BR>]
      print rejoin [{<FONT FACE="Courier New, Courier, monospace">}
        "Phone: </FONT><strong>" bb/4 "</strong>"]
      print [<BR>]
      print rejoin [{<FONT FACE="Courier New, Courier, monospace">}
        "Email: </FONT><strong>"
        (replace/all (replace bb/5 "@" " at ") "." " dot ")
        "</strong>"
      ]
      print [<BR>]
      print rejoin [{<FONT FACE="Courier New, Courier, monospace">}
        "Age: </FONT><strong>" bb/6 "</strong>"]
      print [<BR>]
      print rejoin [{<FONT FACE="Courier New, Courier, monospace">}
        "Language: </FONT><strong>" bb/7 "</strong>"]
      print [<BR>]
      print rejoin [{<FONT FACE="Courier New, Courier, monospace">}
        "Height: </FONT><strong>" bb/8 "</strong>"]
    ]
  ]
]

```

```

        print [<BR><BR>]
    ]
    ; automatically convert line endings to HTML " <br>"
    bb_temp: copy bb/9
    replace/all bb_temp newline " <br> "
    bb_temp2: copy bb_temp
    ; automatically link any urls starting with http://
    append bb_temp " "
    parse/all bb_temp [any [
        thru "http://" copy link to " " (replace bb_temp2
            (rejoin [{http://} link]) (rejoin [
                { <a href="} {http://} link
                {" target=_blank>http://} link {</a> }]))
            ]
        to end
    ]
    print </td>
    print {<td width = "170" valign = "center">}
    print bb/11 ; image link
    print {</td></tr></table>}
    print bb_temp2
    print [<BR><BR><HR>]
    counter: counter + 1
]
print [</td></tr></td></tr></td></tr></table>]
]
print-all
print [</td></tr></table></center>]
print read %footer.html

```

The page above was saved as index.cgi, and serves as the main display page for the site. In order to ensure that a fresh copy of that page is always viewed by visitors, I also created the following index.html page that simply refreshes the index.cgi page. By using that index.html page as the primary link (and by making that HTML file the default page for the web site), visitors always automatically see a refreshed view of the member page, with any changes/updates that have been made:

```

<html>
<head>
<title></title>
<META HTTP-EQUIV="REFRESH" CONTENT="0; URL=./index.cgi">
</head>
<body bgcolor="#FFFFFF">
</body>
</html>

```

Next, I needed to create a form for users to enter their member information. This was saved as add.cgi. The form posts any submitted information back to index.cgi.

```

#! /home/path/public_html/rebol/rebol -cs
REBOL []
print "content-type: text/html^/"
print read %header.html

print [<center><table border=1 cellpadding=10 width=90%><tr><td>]
print [<font size=5>" Add New Member Information:"</font>]
print " "
print " "
print " "
print [<hr>]
print [<FORM method="post" ACTION="./index.cgi">]
print [<br>" Your Name: " <br><input type=text size="60"
    name="username"><BR>]
print [<br>" Password (required to edit member info later): " <br>
    <input type=text size="60" name="password"><BR>]
print [<br>" Address: " <br><input type=text size="60" name="address">
    <BR>]

```

```

print [<br>" Phone: " <br><input type=text size="60" name="phone"><br>]
print [<br>" Email: " <br><input type=text size="60" name="email"><br>]
print [<br>" Age: " <br><input type=text size="60" name="age"><br>]
print [<br>" Language: " <br><input type=text size="60" name="language">
<br>]
print [<br>" Height: " <br><input type=text size="60" name="height"><br>
<br>]
print [" Other Information/Notes: " <br>]
print [<textarea name=otherinfo rows=5 cols=50></textarea><br><br>]
print [<INPUT TYPE="SUBMIT" NAME="Submit" VALUE="Post New Member Info">]
print [</FORM>]

print [</td></tr></table></center>]
print read %footer.html

```

I integrated the following code into index.cgi, to read and add the info from the above form to the database:

```

; here's the default code used to read any data from an HTML form:

read-cgi: func [/local data buffer][
  switch system/options/cgi/request-method [
    "POST" [
      data: make string! 1020
      buffer: make string! 16380
      while [positive? read-io system/ports/input buffer 16380][
        append data buffer
        clear buffer
      ]
    ]
    "GET" [data: system/options/cgi/query-string]
  ]
  data
]
submitted: decode-cgi read-cgi

; make sure at least a user name and password was entered:

if submitted/2 <> none [
  if (submitted/2 = "") or (submitted/4 = "") [
    print {
      <strong>You must include at least
      a name and password.</strong>
      <br><br>Press the [BACK] button
      in your browser to try again.
    }
    print [</td></tr></table></center>]
    print read %footer.html
    halt
  ]
]

; now create a new entry block to add to the database:

entry: copy []
append entry submitted/2      ; name
; the time on the server is 3 hours different then our local time:
append entry to-string (now + 3:00)
append entry submitted/6      ; address
append entry submitted/8      ; phone
append entry submitted/10     ; email
append entry submitted/12     ; age
append entry submitted/14     ; language
append entry submitted/16     ; height
append entry submitted/18     ; other info
append entry submitted/4      ; password
append only entry [
  {<a href = "../default.jpg" target=_blank>
  <IMG align=baseline alt="" border=0 hspace=0 src="../default.jpg"
  width="160" height="120"></a>}
]

```



```

; append the new entry to the database, and notify the user:

append/only tail bbs entry
save %bb.db bbs
print {<strong>New Member Added.</strong>
      Click "Edit" to upload a photo.}
print [</td></tr></table></center>]
print read %footer.html

; now display the member page with the new info refreshed:

wait :00:04
refresh-me: {
  <head><title></title>
  <META HTTP-EQUIV="REFRESH" CONTENT="0; URL=./index.html"></head>
}
print refresh-me
quit

```

Now we can finish up the rest of the work in step 3 of our outline. The pseudo code in my outline reads "The pages where the users edit their information will be forms that display the information currently in the selected entry, without the password. When the user submits the new password and updated info, the CGI checks that the submitted password matches the existing password for that entry, and then replaces the old block with the new one, in the database text file". I've already created links in index.html to reference the "edititemnumber" (created earlier using a counter variable in the foreach loop of index.cgi). And we've already created the basic data entry form to add new users. So we can check for the edititemnumber, and fill the form with appropriate items from the database. In order to find and replace the original entry in the database, once the user has made changes, the original values also need to be submitted as additional hidden form fields, along with the user-editable values in the form's text fields. Here's what I came up with:

```

if submitted/2 = "edititemnumber" [
  ; pick the correct entry from the database, using the submitted
  ; counter variable from the "edit" link in index.cgi:
  selected-block: pick bbs (
    (length? bbs) - (to-integer submitted/4) + 1
  )
  print [<font size=5>" Edit Your Existing Member Information:</font>"]
  print "      "
  ; here's a link we'll need for the section of the outline that
  ; enables image uploading:
  print rejoin [
    {<a href="./upload.cgi?name="} first selected-block
    {">Upload Image (Add or Change)</a><hr>}
  ]
  print "      "
  print "<br><br>"
  print {<strong><i>PASSWORD REQUIRED TO EDIT! </i></strong>
        (Enter it in the field below.)}
  print "<br><br>"
  print [<FORM method="post" ACTION="./edit.cgi">]
  print rejoin [
    {<br> Your Name: <br>
      <input type="text" size="60" name="username" value="}
      first selected-block {"><BR>}
  ]
  print [<br> <strong> " Member Password " </strong> "(same
        as when you created the original account): " <br>
        <input type="text" size="60"      name="password"><BR>
  ]
  print rejoin [
    {<br> Address: <br><input type="text" size="60"
      name="address" value="}
    pick selected-block 3 {"><BR>}
  ]
  print rejoin [
    {<br> Phone: <br><input type="text" size="60"
      name="phone" value="}
    pick selected-block 4 {"><BR>}
  ]

```

```

]
print rejoin [
  {<br> Email: <br><input type=text size="60"
    name="email" value="}
  pick selected-block 5 {"><BR>}
]
print rejoin [
  {<br> Age: <br><input type=text size="60"
    name="age" value="}
  pick selected-block 6 {"><BR>}
]
print rejoin [
  {<br> Language: <br><input type=text size="60"
    name="language" value="}
  pick selected-block 7 {"><BR>}
]
print rejoin [
  {<br> Height: <br><input type=text size="60"
    name="height" value="}
  pick selected-block 8 {"><BR><BR>}
]
print [" Other Information/Notes: " <br>]
print [<textarea name=otherinfo rows=5 cols=50>]
print [pick selected-block 9]
print [</textarea><BR><BR>]
print rejoin [
  {<input type="hidden" name="original_username" value="}
  pick selected-block 1 {">}
]
print rejoin [
  {<input type="hidden" name="original_date" value="}
  pick selected-block 2 {">}
]
print rejoin [
  {<input type="hidden" name="original_address" value="}
  pick selected-block 3 {">}
]
print rejoin [
  {<input type="hidden" name="original_phone" value="}
  pick selected-block 4 {">}
]
print rejoin [
  {<input type="hidden" name="original_email" value="}
  pick selected-block 5 {">}
]
print rejoin [
  {<input type="hidden" name="original_age" value="}
  pick selected-block 6 {">}
]
print rejoin [
  {<input type="hidden" name="original_language" value="}
  pick selected-block 7 {">}
]
print rejoin [
  {<input type="hidden" name="original_height" value="}
  pick selected-block 8 {">}
]
print rejoin [
  {<input type="hidden" name="original_otherinfo" value="}
  pick selected-block 9 {">}
]
print [<INPUT TYPE="SUBMIT" NAME="Submit"
  VALUE="Update Member Information">]
print [</FORM>]
print [</td></tr></table></center>]
print read %footer.html
quit
]

```

I added the above code to index.cgi. Notice that the above form points to edit.cgi, which actually does the

work of checking the password and processing the changes in the database. It has all the standard header and read-cgi code, and then it uses a foreach loop to look for a database entry that has all the same data as that submitted by the hidden items in the form above, and checks the original password in that entry. In comparing the original password with that entered by the user, I also enabled an administrator password "blahblah". I also added the code to email users their password, in case they've forgotten it (just send the stored password to the email address contained in the database, for that entry):

```

#! /home/path/public_html/rebol/rebol -cs
REBOL []
print "content-type: text/html^/"
print read %header.html

bbs: load %bb.db

read-cgi: func [/local data buffer][
  switch system/options/cgi/request-method [
    "POST" [
      data: make string! 1020
      buffer: make string! 16380
      while [positive? read-io system/ports/input buffer 16380][
        append data buffer
        clear buffer
      ]
    ]
    "GET" [data: system/options/cgi/query-string]
  ]
  data
]
submitted: construct decode-cgi read-cgi

; get password from the entry submitted:

foreach message bbs [
  if all [
    find message submitted/original_username
    find message submitted/original_date
    find message submitted/original_address
    find message submitted/original_phone
    find message submitted/original_email
    find message submitted/original_age
    find message submitted/original_language
    find message submitted/original_height
    find message submitted/original_otherinfo
  ] [read-pass: message/10]
]

; save the old block:

old-message: to-block reduce [
  submitted/original_username
  submitted/original_date
  submitted/original_address
  submitted/original_phone
  submitted/original_email
  submitted/original_age
  submitted/original_language
  submitted/original_height
  submitted/original_otherinfo
  read-pass
]

; so that the original pass is not replaced by "blahblah":

either submitted/password = "blahblah" [
  entered-pass: read-pass
] [
  entered-pass: submitted/password
]

; create the new entry for the database:

```

```

new-message: to-block reduce [
  submitted/username
  submitted/original_date
  submitted/address
  submitted/phone
  submitted/email
  submitted/age
  submitted/language
  submitted/height
  submitted/otherinfo
  entered-pass
]

; check the password, and replace:

if submitted/password <> "" [
  either (
    read-pass = submitted/password
  ) or (
    submitted/password = "blahblah"
  ) [
    foreach message bbs [replace message old-message new-message]
  ] [
    print {
      <strong>Forgot your member password?</strong> <br><br>
      It's being emailed to the address for this entry, right now...
      Wait for this page to refresh, then <strong>check your email!
      </strong>
    }
    print read %footer.html
    wait 3
    set-net [user@website.com smtp.website.com]
    send (to-email submitted/original_email) (to-string rejoin [
      "Forgot your member password?" newline newline
      trim {Someone was editing an entry with this email address,
        but the incorrect password was used. Here is the correct
        password, in case you've forgotten:}
      newline newline read-pass
    ])
  ]
]
save %bb.db bbs

; display the edited results on the main user page:

refresh-me: {
  <head><title></title>
  <META HTTP-EQUIV="REFRESH" CONTENT="0; URL=./index.cgi"></head>
}
print refresh-me
print read %footer.html

```

Here, I decided to add the backup code. What I did was create a folder for all previous versions of the database text file to be saved as backups. Then I created a text file that contained the number of the current backup file (to start out, that text file just contained the number 1). Then, I incremented that number and saved it back to that number file. And finally, I saved a copy of the current database to a text file with the current backup number appended to the filename. This code went right before bb.db was saved in the CGI above:

```

backup-num: load %backup-num.txt
backup-num: backup-num + 1
write %backup-num.txt backup-num
filename: to-file rejoin ["/backup/bb-" (to-string backup-num) ".txt"]
save filename bbs

```

The following code is basically a simpler version of the editing code above, which allows users to delete an entry. All that's needed in this case is the username and password. All the other info is passed along to

delete.cgi as hidden fields. This code gets added to index.cgi:

```

if submitted/2 = "deleteitemnumber" [
  selected-block: pick bbs (
    (length? bbs) - (to-integer submitted/4) + 1
  )
  print [<font size=5>" Delete An Existing Member Account:"</font><hr>]
  print [<FORM method="post" ACTION="./delete.cgi">]
  print rejoin [
    {<br> Your Name: <br>
      <input type=text size="60" name="username" value="}
      first selected-block {"><BR>}
  ]
  print [<br>" Member Password (
    same as when you created the original account): "
    <br><input type=text size="60" name="password"><BR><BR>
  ]
  print rejoin [
    {<input type="hidden" name="original_username" value="}
    pick selected-block 1 {">}
  ]
  print rejoin [
    {<input type="hidden" name="original_date" value="}
    pick selected-block 2 {">}
  ]
  print rejoin [
    {<input type="hidden" name="original_address" value="}
    pick selected-block 3 {">}
  ]
  print rejoin [
    {<input type="hidden" name="original_phone" value="}
    pick selected-block 4 {">}
  ]
  print rejoin [
    {<input type="hidden" name="original_email" value="}
    pick selected-block 5 {">}
  ]
  print rejoin [
    {<input type="hidden" name="original_age" value="}
    pick selected-block 6 {">}
  ]
  print rejoin [
    {<input type="hidden" name="original_language" value="}
    pick selected-block 7 {">}
  ]
  print rejoin [
    {<input type="hidden" name="original_height" value="}
    pick selected-block 8 {">}
  ]
  print rejoin [
    {<input type="hidden" name="original_otherinfo" value="}
    pick selected-block 9 {">}
  ]
  print [<INPUT TYPE="SUBMIT" NAME="Submit" VALUE="Delete Member Info">]
  print [</FORM>]
  print [</td></tr></table></center>]
  print read %footer.html
  quit
]

```

Here's the code for delete.cgi, which the above form points to, and which does the actual work of deleting the selected block from the database (it's basically a variation of the edit.cgi script above):

```

#! /home/path/public_html/rebol/rebol -cs
REBOL []
print "content-type: text/html^/"
print read %header.html

```

```

bbs: load %bb.db

read-cgi: func [/local data buffer][
  switch system/options/cgi/request-method [
    "POST" [
      data: make string! 1020
      buffer: make string! 16380
      while [positive? read-io system/ports/input buffer 16380][
        append data buffer
        clear buffer
      ]
    ]
    "GET" [data: system/options/cgi/query-string]
  ]
  data
]
submitted: construct decode-cgi read-cgi

foreach message bbs [
  if all [
    find message submitted/original_username
    find message submitted/original_date
    find message submitted/original_address
    find message submitted/original_phone
    find message submitted/original_email
    find message submitted/original_age
    find message submitted/original_language
    find message submitted/original_height
    find message submitted/original_otherinfo
  ] [read-pass: message/10]
]

old-message: to-block reduce [
  submitted/original_username
  submitted/original_date
  submitted/original_address
  submitted/original_phone
  submitted/original_email
  submitted/original_age
  submitted/original_language
  submitted/original_height
  submitted/original_otherinfo
  read-pass
]

if submitted/password <> "" [
  if (
    read-pass = submitted/password
  ) or (
    submitted/password = "blahblah"
  ) [
    backup-num: load %backup-num.txt
    backup-num: backup-num + 1
    write %backup-num.txt backup-num
    filename: to-file rejoin [
      "./backup/bb-" (to-string backup-num) ".txt"
    ]
    save filename bbs

    foreach message bbs [replace message old-message ""]
  ]
]

remove-each message bbs [
  any [
    message = [""]
    (all [
      message/1 = "" message/2 = "" message/3 = "" message/4 = ""
      message/5 = "" message/6 = "" message/7 = "" message/8 = ""
      message/9 = ""
    ])
  ]
]

```

```

    ]
  ]

  save %bb.db bbs

  refresh-me: {
    <head><title></title>
    <META HTTP-EQUIV="REFRESH" CONTENT="0; URL=./index.cgi"></head>
  }
  print refresh-me
  print read %footer.html

```

Creating the image upload page for step #4 in our outline was a bit of a challenge. That's because REBOL has no built-in way to accept binary data from HTML forms (images, in this case), called "form-multipart" data. I searched the mailing list and quickly found a solution at <http://www.rebol.org/cgi-bin/cgiwrap/rebol/ml-display-thread.r?m=rmlKVSQ>. Andreas Bolka's "decode-multipart-form-data" did exactly what I needed. That function converts the data entered by a user, as well as the files they choose and upload from their hard drive, into a friendly and easy to use REBOL object.

```

#! /home/path/public_html/rebol/rebol -cs
REBOL [Title: "HTTP File Upload"]
print "content-type: text/html^/"
print read %header.html

read-cgi: func [/local data buffer][
  switch system/options/cgi/request-method [
    "POST" [
      data: make string! 1020
      buffer: make string! 16380
      while [positive? read-io system/ports/input buffer 16380][
        append data buffer
        clear buffer
      ]
    ]
    "GET" [data: system/options/cgi/query-string]
  ]
  data
]

; here's Andreas's magic function to read form/multipart data:

decode-multipart-form-data: func [
  p-content-type
  p-post-data
  /local list ct bd delim-beg delim-end non-cr non-lf non-crlf mime-part
] [
  list: copy []
  if not found? find p-content-type "multipart/form-data" [return list]

  ct: copy p-content-type
  bd: join "--" copy find/tail ct "boundary="
  delim-beg: join bd crlf
  delim-end: join crlf bd

  non-cr: complement charset reduce [ cr ]
  non-lf: complement charset reduce [ newline ]
  non-crlf: [ non-cr | cr non-lf ]
  mime-part: [
    ( ct-dispo: content: none ct-type: "text/plain" )
    delim-beg ; mime-part start delimiter
    "content-disposition: " copy ct-dispo any non-crlf crlf
    opt [ "content-type: " copy ct-type any non-crlf crlf ]
    crlf ; content delimiter
    copy content
    to delim-end crlf ; mime-part end delimiter
    ( handle-mime-part ct-dispo ct-type content )
  ]
]

handle-mime-part: func [

```

```

    p-ct-dispo
    p-ct-type
    p-content
    /local tmp name value val-p
  ] [
    p-ct-dispo: parse p-ct-dispo {;=}

    name: to-set-word (select p-ct-dispo "name")
    either (none? tmp: select p-ct-dispo "filename")
      and (found? find p-ct-type "text/plain") [
        value: content
      ] [
        value: make object! [
          filename: copy tmp
          type: copy p-ct-type
          content: either none? p-content [none] [copy p-content]
        ]
      ]

    either val-p: find list name
      [change/only next val-p compose [(first next val-p) (value)]]
      [ append list compose [ (to-set-word name) (value) ] ]

    ]

    use [ ct-dispo ct-type content ] [
      parse/all p-post-data [ some mime-part "--" crlf ]
    ]

    list
  ]

; now we can put the uploaded binary, and all the text entered by the
; user via the HTML form, into a REBOL object. we can refer to the
; uploaded photo using the syntax:  cgi-object/photo/content

post-data: read-cgi
cgi-object: construct decode-multipart-form-data (
  system/options/cgi/content-type copy post-data
)

; I created a "./files" subdirectory to hold these images. Now
; write the file to the web server using the original filename,
; but without any Windows path characters, and notify the user:

adjusted-filename: copy cgi-object/photo/filename
adjusted-filename: replace/all adjusted-filename "/" "-"
adjusted-filename: replace/all adjusted-filename "\" "-"
adjusted-filename: replace/all adjusted-filename " " "_"
adjusted-filename: replace/all adjusted-filename ":" "_"
adjusted-filename: to-file rejoin ["/files/" adjusted-filename]
write/binary adjusted-filename cgi-object/photo/content
print [<strong>]
print {Upload Complete.  }
print [</strong>]
print [<br><br>]

; now add an HTML link to this file, to the database:

bbs: load %bb.db
entry: copy []
link-added: rejoin [
  {<a href = "} to-string adjusted-filename {" target=_blank>}
  {<IMG align=baseline alt="" border=0 hspace=0 src="}
  to-string adjusted-filename
  {" width="160" height="120">} </a>
] ; display image inline
append entry link-added
foreach message bbs [
  if (all [
    cgi-object/username = message/1
    cgi-object/password = message/10
  ]) [

```



```

        if ((length? message) < 11) [append message ""]
        message/11: entry
    ]
save %bb.db bbs

; show additions by refreshing the index.cgi page:

refresh-me: {
    <head><title></title>
    <META HTTP-EQUIV="REFRESH" CONTENT="0; URL=./index.cgi"></head>
}
print refresh-me
print read %footer.html

```

The last step in the outline was easy. I just used the code from the previous case study (the password protected CGI text editor), and pointed it to the database text file. I also looped through the backup directory and printed links to each of the files in that directory, so that any of the previous backup files could be easily copied and pasted into the editor, to revert the database to a previous state.

```

#! /home/path/public_html/rebol/rebol -cs
REBOL []
print "content-type: text/html^/"
print [<HTML><HEAD><TITLE>"Edit Database!!!"</TITLE></HEAD><BODY>]

read-cgi: func [/local data buffer][
    switch system/options/cgi/request-method [
        "POST" [
            data: make string! 1020
            buffer: make string! 16380
            while [positive? read-io system/ports/input buffer 16380][
                append data buffer
                clear buffer
            ]
        ]
        "GET" [data: system/options/cgi/query-string]
    ]
    data
]

submitted: decode-cgi read-cgi

; if schedule.txt has been edited and submitted:

if ((submitted/2 = "save") or (submitted/2 = "save")) [
    ; save newly edited schedule:
    write %/bb.db submitted/4
    print ["Database Saved."]
    ; print {<META HTTP-EQUIV="REFRESH" CONTENT="0; URL=./bb.db">}
    quit
]

; if user is just opening page (i.e., no data has been submitted
; yet), request user/pass:

if ((submitted/2 = none) or (submitted/4 = none)) [
    print [<strong>"W A R N I N G - Private Server, Login Required:"
        </strong><BR><BR>]
    print [<FORM ACTION="./editor.cgi">]
    print [" Username: " <input type=text size="50" name="name"><BR><BR>]
    print [" Password: " <input type=text size="50" name="pass"><BR><BR>]
    print [<INPUT TYPE="SUBMIT" NAME="Submit" VALUE="Submit">]
    print [</FORM>]
    quit
]

; check user/pass, end if incorrect:

response: false

```



```

#! /home/path/public_html/rebol/rebol -cs
REBOL []
print "content-type: text/html^/"
print {<HTML><HEAD><TITLE>Event Calendar</TITLE></HEAD><BODY>}

; print month + year header:

date: now/date
html: copy rejoin [
  {<CENTER><TABLE border=1 valign=middle width=99% height=99%>
    <TR><TD colspan=7 align=center height=8%><FONT size=5>
      pick system/locale/months date/month { } date/year
    </FONT></TD></TR><TR>}
]

; print days header:

days: ["Sun" "Mon" "Tue" "Wed" "Thu" "Fri" "Sat"]
foreach day days [
  append html rejoin [
    {<TD bgcolor="#206080" align=center width=10% height=5%>
      <FONT face="courier new,courier" color="FFFFFF" size="+1">
        day
      </FONT></TD>}
  ]
]
append html {</TR><TR>}

; print non-month days at the beginning of month in gray:

sdate: date sdate/day: 0
loop sdate/weekday // 7 + 1 [append html {<TD bgcolor=gray></TD>}]

; print every other day, with the current day in a unique color:

while [sdate/day: sdate/day + 1 sdate/month = date/month][
  append html rejoin [
    {<TD bgcolor=#}
    ; I ADDED THIS CODE TO VISUALLY HIGHLIGHT THE CURRENT DAY:
    either date/day = sdate/day ["AA9060"] ["FFFFFF"]
    {" height=14% valign=top>} sdate/day
    </TD>}
  ]
  if sdate/weekday = 6 [append HTML {</TR><TR>}]
]

; print non-month days at the end of month in gray:

loop 7 - sdate/weekday [append html rejoin [{<TD bgcolor=gray></TD>}]]

; finish and print:

append html {</TR></TABLE></CENTER></BODY></HTML>}
print html

```

With step 1 in my outline done, I completed the second and last step by adding the code below. It was really simple. First, I created a variable called "event-labels" which would hold any events in the database that occurred on a given day. I put this inside Bohdan's while loop, which ran through each day of the month and printed the calendar table cells for each separate day). I used a foreach loop to compare each date found in the database to the current date being added to the calendar. If there's a match, "event-labels" is rejoined with the first item in the event entry (the description of the event), and linked to the event display. The string of text in event-labels is then later printed into the table, within the current day's cell.

```

while [sdate/day: sdate/day + 1 sdate/month = date/month][
  event-labels: {}
  foreach entry bbs [
    date-in-entry: 1-Jan-1001
    attempt [date-in-entry: (to-date entry/3)]

```

```

        if (date-in-entry = sdate) [
            event-labels: rejoin [
                {<font size=1>}
                event-labels
                "<strong><br><br>"
                {<a href="http://website.com/path/calendar">}
                entry/1
                {</a>}
                "</strong>"
                {</font>}
            ]
        ]
    ]
]

```

That's it! Here's the whole script:

```

#! /home/path/public_html/rebol/rebol -cs
REBOL []
print "content-type: text/html^/"
print {<HTML><HEAD><TITLE>Event Calendar</TITLE></HEAD><BODY>}

bbs: load %bb.db
date: now/date
html: copy rejoin [
    {<CENTER><TABLE border=1 valign=middle width=99% height=99%>
      <TR><TD colspan=7 align=center height=8%><FONT size=5>
        pick system/locale/months date/month { } date/year
      {</FONT></TD></TR><TR>}
    ]

    days: ["Sun" "Mon" "Tue" "Wed" "Thu" "Fri" "Sat"]
    foreach day days [
        append html rejoin [
            {<TD bgcolor="#206080" align=center width=10% height=5%>
              <FONT face="courier new,courier" color="FFFFFF" size="+1">}
              day
              {</FONT></TD>}
            ]
        ]
    ]
    append html {</TR><TR>}

    sdate: date sdate/day: 0
    loop sdate/weekday // 7 + 1 [append html {<TD bgcolor=gray></TD>}]

    while [sdate/day: sdate/day + 1 sdate/month = date/month][
        event-labels: {}
        foreach entry bbs [
            date-in-entry: 1-Jan-1001
            attempt [date-in-entry: (to-date entry/3)]
            if (date-in-entry = sdate) [
                event-labels: rejoin [
                    {<font size=1>}
                    event-labels
                    "<strong><br><br>"
                    {<a href="http://website.com/path/calendar">}
                    entry/1
                    {</a>}
                    "</strong>"
                    {</font>}
                ]
            ]
        ]
        ]
    ]
    append html rejoin [
        {<TD bgcolor=#}
        either date/day = sdate/day ["AA9060"] ["FFFFFF"]
        ; HERE, THE EVENTS ARE PRINTED IN THE APPROPRIATE DAY:
        {" height=14% valign=top>} sdate/day event-labels
        {</TD>}
    ]
]

```

```

    if sdate/weekday = 6 [append html {</TR><TR>}]
  ]

  loop 7 - sdate/weekday [append html rejoin [{<TD bgcolor=gray></TD>}]]

  append html {</TR></TABLE></CENTER></BODY></HTML>}
  print html

```

10.13 Case 13 - Ski Game, Snake Game, and Space Invaders Shootup

The Tetris project was entertaining and educational, so I'm motivated to create another simple game. For this case study, I wanted to create a game that demonstrated more graphic techniques, instead of using text. I found a nice game tutorial at <http://gm2d.com/2009/02/simple-flash-game-in-haxe>. That game was written in another programming language, but does provide a nice example to emulate in REBOL.

In the Ski Game, the player is represented by a graphic that can be moved side to side across the top of the screen. Randomly placed tree images scroll up the screen, into the path of the skier. The goal is to avoid hitting trees for as long as possible. The longer the skier stays alive, the higher the score.

I began thinking through a plan of attack with this outline:

1. First, I'll need some images to use in the game. The tutorial link above contains open source graphics. I'll use the binary resource embedder provided earlier in this tutorial to import and use those graphics in the code of this game.
2. I'll need to build a screen full of scrolling trees. To do that, here's some pseudo code, and a description of my imagined code outline: I'll create a graphical playing area using a 'draw' block on a 'view layout' window. To create a set of trees at various locations, I'll use a 'for' loop and the 'random' function to build up a block of the necessary enumerated coordinate positions, image data, etc. To move the trees, I'll use 'feel engage' on the draw block. Whenever a given amount of time has passed (some milliseconds, tested with a 'time' action in the engage loop), I'll increment the coordinate position of every tree, and increment the score. The majority of the program will run in this timer loop, so that the trees continuously move up the screen. If any of the trees reach the top of the screen, I'll remove them from the draw block, and replace them with new ones at random horizontal positions at the bottom of the screen. That will give the appearance of an endless hill of scrolling trees, and a continually counted score.
3. I'll need a player graphic. Side to side movement of that graphic needs to be controlled by the player, either via key strokes or mouse movements. I can either check for 'key actions' in the engage loop above, or continuously check mouse position using the 'all-over' view feel option. If a movement left is detected, display a left facing skier graphic and update his position 1 pixel to the left (current-position - 1x0). If a movement right is detected, display a right facing graphic and update his right position 1 pixel to the right.
4. I'll need to check for collisions and end the game if the skier hits a tree. That'll involve comparing the positions of the skier graphic with those of *all* the tree graphics, in every iteration of the timer loop above.

For step one, I used Windows Paint to modify the right and left facing skier images that I found at the web site above. I created my own tree graphic by editing a simple line drawing found with Google. Using the binary resource embedder from earlier in this tutorial, I converted those images to the following REBOL code:

```

tree: load to-binary decompress 64#{
eJzt18sNwjAQBFDtBSVw5EQBnLjQE1XRngmBQEj8Wa/3M4oYOZKBKHkaWwTO1/sh
jDkNx3N6HI7LcOzCfnz/9v5cMnEai7l1j4mokT9C7XczUsrhvGSku6RkgDIbHAEP0
2EiIMBdMDuaOWZCSL9lBQvCsSY4MHE9umXz7ydVi3xglTtYvEKboexzVSlpTa614d
NonpUauIv176dX0ZTRgJlVgzN125A3gkGwld1bkrNFqqedQfEI02AU9PjDeMpac/
ShKeTXylROqCImLXRFd9zkQoh4tp+GpqlSTnLnum4HTEzK/gjpmTpDxSAS1HFqYU
EE/8nddG9n+9LIm8t9OeIEra2JZWDRSG4VEioa0UFCZFqv/aMQh2Rf790EnGgcJU
SVAer0Bhpc7/epVJvkHkBHjPpz+XSe6BwryC5gmQno3mAY3tpba2KAAA
}
skier-left: load to-binary decompress 64#{
eJyN0U8og2EcB/DvNrZ+E5fJZSmRf9Ej76h3Ne1AIsPyMQflpJDFU/KO1cQmSnGa
A3PYkvInB3kvuyzlgJolh+fCRUq5iBvP8+5lTvKrX33ep+/zp9/b2Tthh16zvGt5
W3nX8TYhs1//MOGnsjNEa/AUxd0UVQ3raL9IYbBvA2OB19Q0DqB6fAuJl08Yi97D
Hr3F5EQYSSs2OrrWEFo5xB+VO5Vx/skvnxmQbDCFvxcjMJ/b0s6LAZXGA300ZtTt
pW3WbJmDeMC8algE9o3bTBFI9YvGhrOKSueyEQpu9ri60vQFXFqPMx1K+sNWrDoh
73Y/uMr85fKdcIrJ0z6vxSfsYV5KCU2JEPN1LD9dFZ65AfXwD+HsKdAZi1Ldqtvt
Hh65E5ZklTGmDvWLgxxKkjAivwt7XxhJEvIsrCY8ikLs0Tj3yGeCKaQtdsX9fv3G
N1jCJdyv841HJkNriim7Li29O1DV0jcU8kuIHaiPLEDEsG9DQYxiQTi0A8sBpEvh

```

```

OT65GmBYH9Jx5nf8TFFUFF5ZX2hFdGluAgAA
}
skier-right: load to-binary decompress 64#{
eJxz8s1jYgCDMiDWAGIJINYCYkYGFrd4D0YGOBBAMBn4++Yz6HjVMSgY1oP5gWdu
M/gHTmCwNutlKJ26l6F03VUGp3XnGGo+/mGILVnMoFkwhaHm7GcGz4m7GbABFwST
eQWSNXMQbM+3DAwlULbmEgaWXih75QUGzvkJstMBwbPRRA2L1D5yS8QNudioNQF
qNYPDExAZRCtDg78c6Fa7wZK3Ycq94003L1fAcLWigpctUsZzHTSj5Jd+17NAKS6
3HnXk6jHSiBF7sUmxi7G19VAZrqVOxsZuTirg8TTS0qAQs5FIPF0BhYXFkgog/zg
7gJlq5SXpaWVF4091ZKuXl6eVl4AZLIfKS82LzYuB2nlOFxWXl5ubA6ytm1KWU65
cXExkMl091NNR3q5eTFQPYfHE7YT6cXlJgcYGI7cPMAOMtKhgcH9wE8FBuPycgOG
BoYKtl8ODL4gjjccY2HSAfr4BVMvgAwyzwxsXSA7ORgY2BQYeH+Cw+sAKPo5wEHj
kQAO/GZWIIHDgc0AaxQSBAAF0XD7bgIAAA==
}

```

For all the rest of the steps in my initial outline, I organized my pseudo code thoughts into a general code outline. Since this program is all about a visual interface and event handling, I could use a very basic graphic and event handling code structure to begin filling out. Here's a simple skeleton:

```

; (Include the above graphic code here)

; Define some variables to start with (i.e., initial score = 0, etc).
; Create a "board" block to hold image information for all graphics
; to be display on screen. Skier image should be first, then the trees.
; Use a "for" loop to create the data:

for i 1 20 1 [
    ; Add tree image data to the block described above. Use the "random"
    ; function to come up with 20 random coordinate locations.
]

; Here's a basic screen layout structure with draw block, timer and
; key action detection, and the outline ideas above written into the
; appropriate areas of code:

view layout [
    scrn: box effect [draw board] rate 0 feel [
        engage: func [f a e] [
            if a = 'key [
                ; Move skier graphic left-right
            ]
            if a = 'time [
                ; Scroll the tree graphics upward.
                ; Remove any trees that go past the top of the screen.
                ; Replace removed trees with new trees at the bottom
                ; of the screen.
                ; Check for collisions and end the game if skier hits
                ; a tree.
                ; Update the score.
            ]
        ]
    ]
    ; Display a score in the GUI using some sort of text widget
]

```

Next, I fleshed out the code structure above with more detailed thoughts about how to accomplish everything in the initial descriptive outline. No actual code yet - just thoughts about how to accomplish each of the outline ideas, in the appropriate areas of the code structure. Here are my thoughts:

```

; (Include the above graphic code here)

; Define some variables to start with:

; I need to generate some random position coordinates. Prepare (seed)
; the 'random function.

; All the items on the screen will be kept in a block (I'll call it

```

```

; "board"). Start with the code needed to display the skier image
; in a draw block. The block should contain the following info for
; each image:

[
  the draw function 'image',
  the coordinate position of the graphic,
  the actual binary image data,
  the transparency color (black), so the edges of the images
  don't appear square (i.e., so the black outer frame corners of
  the image file disappear by blending into the background).
]

; Now add twenty trees to the above block, to appear at random places
; on the screen:

for i 1 20 1 [

  ; Assign a random coordinate to the variable 'pos', within the
  ; bounds of the playing screen.

  ; Shift every image position down 300 pixels, so the user
  ; has a moment to see them coming, and to get situated at the
  ; beginning of the game.

  ; Put each image into the "board" block described above.

]

; We now have a block of images that can be displayed on screen
; using 'draw' (see the '2D Drawing, Graphics, and Animation'
; section earlier in this tutorial).

; Center the GUI window, and get rid of the standard 20 pixel
; gray padding around the edges ('layout/tight'):

view center-face layout/tight [

  ; Set the color of the screen white like snow, and set the
  ; size of the playing area:

  scrn: box white 600x440 effect [draw board] rate 0 feel [
    engage: func [f a e] [
      if a = 'key [
        if e/key = 'right [

          ; The second item in the block created above will
          ; be the position coordinate of the skier graphic.
          ; If the right arrow key has been pressed, add 5
          ; to the horizontal portion of that position
          ; coordinate.

          ; The third item in the graphic block is the
          ; actual graphic data used to display the skier.
          ; If the right arrow key has been pressed, that
          ; data should be replaced with the right facing
          ; skier graphic.

        ]
        if e/key = 'left [

          ; Same as the section above, but for the left key.

        ]

        ; Now that the data block has been updated with position
        ; and graphics alterations, show them on screen:

        show scrn
      ]
      if a = 'time [

```

```

; Everything in this block happens each time a timer
; action is detected in the feel block of the draw
; function above (currently, the rate is set to 0
; seconds, so all this code just keeps looping).

; First, move the trees up 5 pixels each.
; I'm going to need to deal with every item in the
; graphic block, sometimes removing and adding items.
; To make the whole process easier, I'm going to
; build a new copy of the changed block from scratch.

; I'll loop through each item in the existing block
; and check for the pair items (remember, there are 4
; items for each image ('image, coordinate pos, graphic
; data, and transparency color)). Remember also that
; the first graphic in the block is the skier character.
; When working with tree graphics, we want to be sure to
; skip over the first four items in the block:

foreach item board [

    ; Looping through the existing graphic block,
    ; subtract 0x5 from each tree's position (move each
    ; one up 5 pixels). Append those new coordinate
    ; positions, along with every other item, in order,
    ; into the new block:

    either all [

        ; If the item is a coordinate,
        ; and we're not dealing with the first 4 items:

    ] [

        ; Add the new coordinate position
        ; (old position + 5) to the new block.

    ] [

        ; Otherwise, add all other items to the new block,
        ; as is (i.e., we're not changing the image or
        ; transparency data).

    ]

    ; If the newly added coordinate is higher than the
    ; top of the screen, remove all 4 of its items from
    ; the new block (i.e., remove the tree graphic from
    ; the game).

]

; Now copy the new block back to the "board" variable.

; If any tree graphics have been removed from the top
; of the screen, replace them with new graphic
; data in the block. We can check for removals by
; looking at the length of the data block. It should
; be 84 items long (1 skier + 20 trees = 21*4, or 84
; items long). Coordinates of the new trees should be
; at random horizontal locations along the bottom of
; the screen (i.e., somewhere along (random)x440 pixels).
; Append the new graphic data to the "board" block.

; Collision Detection:
;
; Check to see if skier position is within range of ANY
; tree position. Use a foreach loop to make
; comparisons. To ensure we're not detecting the
; skier colliding with himself, use a copy of the board
; without the first 4 items. To check if images are
; touching, we need to consider the sizes and shapes of

```



```

; both the tree and skier graphics. I came up with the
; following measurements: If the top left corner of the
; skier image is within -40 and +15 horizontal pixels and
; 5 to 30 vertical pixel, they will be touching.
; This is an imperfect estimate that I came up with after
; some trial and error eyeballing the images, which
; considers the fact that we're starting calculations
; from the top left corner of each differently sized
; square image file.
; The calculation should check to see if horizontal
; skier_position - horizontal tree_position is within
; that range of pixels.

; I'll build a new block of data to perform the
; comparison, which has the skier items removed:

collision-board: remove/part (copy board) 4
foreach item collision-board [
  if (type? item) = pair! [
    if all [

      ; "item/1" and "item/2" refer respectively to
      ; horizontal and vertical components of the
      ; tree coordinate being checked (the x and y
      ; values in the coordinate). "board/2/1" and
      ; "board/2/2" refer to the position of the
      ; skier graphic (remember, the skier's
      ; current position is always the second item
      ; in the block). The calculations in this
      ; section will check the ranges described
      ; above.

    ] [
      ; If the above calculations evaluate to true,
      ; alert the user and end the game.
    ]
  ]
]

; Every time through the loop, increase and update the
; score display.

]

]

; Put the text label "Score:" at the top left corner of the screen.

; The game score updated in the code above can just be contained in
; another text widget. Assign that widget the word label "score".

; To make 'key actions work in the engage code above, the following
; stock line needs to be added to the layout:

do [focus scrn]
]

```

Finally, I filled in the pseudo code outline above with actual working code that completed each pseudo code thought:

```

; (Include the above graphic code here)

; Define some variables to start with:

the-score: 0

; I need to generate some random position coordinates. The following
; line is stock REBOL code to ensure that numbers are actually random:

```

```

random/seed now

; All the items on the screen will be kept in a block.
; Start with the code needed to display the skier image
; in a draw block (black is the transparent color):

board: reduce ['image 300x20 skier-right black]

; Now add twenty trees to the above block, to appear at random places
; on the screen:

for i 1 20 1 [

    ; Assign a random coordinate to the variable 'pos', within the
    ; bounds of the playing screen:

    pos: random 600x540

    ; Shift every image position down 300 pixels, so the user
    ; has a second to see them coming, and to get situated at the
    ; beginning of the game:

    pos: pos + 0x300

    ; Put each image into the block above:

    append board reduce ['image pos tree black]
]

; We now have a block of images that can be displayed on screen
; using 'draw' (see the '2D Drawing, Graphics, and Animation'
; section earlier in this tutorial).

; Center the GUI window, and get rid of the standard 20 pixel
; gray padding around the edges ('layout/tight'):

view center-face layout/tight [

    ; Set the color of the screen white like snow, and set the
    ; size of the playing area:

    scrn: box white 600x440 effect [draw board] rate 0 feel [
        engage: func [f a e] [
            if a = 'key [
                if e/key = 'right [

                    ; The second item in the block created above is
                    ; the position coordinate of the skier graphic.
                    ; If the right arrow key has been pressed, add 5
                    ; to the horizontal portion of that position
                    ; coordinate:

                    board/2: board/2 + 5x0

                    ; The second item in the graphic block is the
                    ; actual graphic data used to display the skier.
                    ; If the right arrow key has been pressed, that
                    ; data should be replaced with th right facing
                    ; skier graphic:

                    board/3: skier-right
                ]
                if e/key = 'left [

                    ; Same as the section above, but for the left key:

                    board/2: board/2 - 5x0
                    board/3: skier-left
                ]

                ; Now that the data block has been updated with position
                ; and graphics alterations, show them on screen:
            ]
        ]
    ]
]

```

```

    show scrn
  ]
  if a = 'time [

    ; Everything in this block happens each time a timer
    ; action is detected in the feel block of the draw
    ; function (currently, the rate is set to 0 seconds,
    ; so this code all just keeps looping).

    ; First, move the trees up 5 pixels each.
    ; I'm going to need to deal with every item in the
    ; graphic block, sometimes removing and adding items.
    ; To make the whole process easier, I'm going to
    ; build a new copy of the changed block from scratch:

    new-board: copy []

    ; Now I'll loop through each item in the existing block
    ; and check for the pair items (remember, there are 4
    ; items for each image ('image, coordinate pos, graphic
    ; data, and transparency color)). Remember also that
    ; the first graphic in the block is the skier character.
    ; When working with tree graphics, we want to be sure to
    ; skip over the first four items in the block:

    foreach item board [

      ; Looping through the existing graphic block,
      ; subtract 0x5 from each tree's position (move each
      ; one up 5 pixels). Append those new coordinate
      ; positions, along with every item, in order, into
      ; the new block:

      either all [

        ; If the item is a coordinate:

        ((type? item) = pair!)

        ; and we're not dealing with the first 4 items:
        ; (after we're done with this loop, 4 items will
        ; have been added to the new block):

        ((length? new-board) > 4)
      ] [

        ; Add the moved up position to the new block:

        append new-board (item - 0x5)
      ] [

        ; Add all other items to the new block:

        append new-board item
      ]

      ; If the newly added coordinate is higher than the
      ; top of the screen, remove all 4 of its items from
      ; the new block (i.e., remove the tree graphic from
      ; the game):

      coord: first back back (tail new-board)
      if ((type? coord) = pair!) [
        if ((second coord) < -60) [
          remove back tail new-board
          remove back tail new-board
          remove back tail new-board
          remove back tail new-board
        ]
      ]
    ]
  ]

```

```

; Now copy the new block back to the "board" variable:

board: copy new-board

; If any tree graphics have been removed from the top
; of the screen, replace them in the with new graphic
; data in the block. We can check for removals by
; looking at the length of the data block. It should
; be 84 items long (1 skier + 20 trees = 21*4, or 84
; items long). Coordinates of the new trees should be
; at random horizontal locations along the bottom of
; the screen (i.e., somewhere along (random)*440 pixels):
; Append the new graphic to the screen:

if (length? new-board) < 84 [
    column: random 600
    pos: to-pair rejoin [column "x" 440]
    append board reduce ['image pos tree black]
]

; Collision Detection:
;
; Check to see if skier position is within range of ANY
; tree position. Use a foreach loop to make
; comparisons. To make ensure you're not detecting the
; skier colliding with himself, use a copy of the board
; without the first 4 items. To check if images are
; touching, we need to consider the sizes and shapes of
; both the tree and skier graphics. I came up with the
; following measurements: If the top left corner of the
; skier image is within -40 and +15 horizontal pixels and
; 5 to 30 vertical pixel, they will be touching.
; This is an imperfect estimate that I came up with some
; trial and error eyeballing of the images, and which
; considers the fact that we're starting the calculations
; from the top left corner of each differently sized
; image.
; The calculation should check to see if horizontal
; skier_position - horizontal tree_position is within
; that range of pixels.

collision-board: remove/part (copy board) 4
foreach item collision-board [
    if (type? item) = pair! [
        if all [

            ; "item/1" and "item/2" refer respectively to
            ; horizontal and vertical components of the
            ; tree coordinate being checked (the x and y
            ; values in the coordinate). "board/2/1" and
            ; "board/2/2" refer to the position of the
            ; skier graphic (remember, the skier's
            ; current position is always the second item
            ; in the block). The calculations below
            ; check the ranges described above:

            ((item/1 - board/2/1) < 15)
            ((item/1 - board/2/1) > -40)
            ((board/2/2 - item/2) < 30)
            ((board/2/2 - item/2) > 5)

        ] [

            ; Alert the user and end the game:

            alert "Ouch - you hit a tree!"
            alert rejoin ["Final Score: " the-score]
            quit

        ]
    ]
]

```

```

        ; Every time through the loop, increase and update the
        ; score display:

        the-score: the-score + 1
        score/text: to-string the-score
        show scrn
    ]
]

; Put the word "Score:" at the top left corner of the screen:

origin across h2 "Score:"

; Here's the game score text which is updated in the code above,
; It's just a text header widget, assign the word label "score":

score: h2 bold "000000"

; To make 'key actions work in the engage code above, the following
; stock line needs to be added to the layout:

do [focus scrn]
]

```

Here's the final game, with comments removed:

```

REBOL [title: "Ski Game"]

tree: load to-binary decompress 64#{
eJzt18sNwjAQBFDTBSVw5EQBnLjQE1XRngmBQEj8Wa/3M4oYOZKBKHkaWwTO1/sh
jDkNx3N6HI7LcOzCfnz/9v5cMnEai7l1j4mokT9C7XczUsrhvGSku6RkgDIbHAEP0
2EiIMBdMDuaOWZCSL91bQvCsSY4MHE9umXz7ydVi3xgltYvEKboexzVS1pTa614d
NonpUauIv176dX0ZTRgJlVgzN125A3gkGwld1bkrNFqqedQfEI02AU9PjDeMpac/
ShKeTXylROqCIm1XRFD9zkQoh4tp+GpqlSTnLnum4HTEzK/gjpmTpDxSAS1HFqYU
EE/8nddG9n+9LIm8t9OeIEra2JZWDRSG4VEioa0UFCZFqv/aMQh2Rf790EnGgcJU
SVAer0Bhpc7/epVJvkHkBHjPfz+XSe6BwryC5gmQno3mAY3tpba2KAAA
}

skier-left: load to-binary decompress 64#{
eJyN0U8og2EcB/DvNrZ+E5fJZSmRf9Ej76h3NelAIsPyMQflpJDFU/KO1cQmSnGa
A3PYkvInB3kvuyzlgJolh+fCRUq5iBvP8+5lTvKrX33ep+/zp9/b2Tthhl6zvGt5
W3nX8TYhS1//MOGnsjNEa/AUxd0UVQ3raL9IYbBvA20BI9Q0DqB6fAuJl08Yi97D
Hr3F5EQYSSs2OrrWEFo5xB+VO5Vx/skvnxmQbDCFvxcjMJ/b0s6LAZXGA300ZtTt
pW3WbJmDeMC8alge9o3bTBFI9YvGhrOKSueyEQpu9ri60vQFXFqPMx1K+sNWrDoh
73Y/uMr85fKdcIrJ0z6vxSfsYV5KCU2JEPN1LD9dFZ65AfXwD+HsKdAZiiLdgtvt
Hh65E5ZklTGmDvWLgxxKkjAivwt7XxhJEvIsrCY8ikLs0Tj3yGeCKaQtdsX9fv3G
N1jCJdyv84lHJkNriiM7Li29OIDV0jCU8kuIHaiPLEDEsG9DQYxiQti0A8sBpEvh
OT65GmBYH9Jx5nf8TFFUFf5ZX2hFdGluAgAA
}

skier-right: load to-binary decompress 64#{
eJxz8s1jYgCDMiDWAGIjJINyCYkYGFrD4D0YGOBBAMbn4++Yz6HjVMSgY1oP5gWdu
M/gHTmCwNutmKJ26l6F03VUGp3XnGGo+/mGILVnMoFkwhaHm7GcGz4m7GbABFwST
eQWSNXMQbm+3DAwLULbmEgaWXih75QUGzvKQJstMBwbPRRA2L1D5ys8QNudioNQF
qNYPDExAZRCtDg78c6Fa7wZK3Ycq94003L1fAcLWigpctUsZzHTSj5Jd+17NAKS6
3HnXk6jHSiBF7sUmxi7G19VAZrqVOxsZuTirg8TTS0qAQs5FIPF0BhYXfkgog/zg
7gJlq5SXpaWVF4091ZKuXl6eVl4AZLIfKS82LzYuB2nlOFxWXl5uba6ytm1KWU65
cXExkMl09lNNR3q5eTFQPYfHE7YT6cXlJgcYGI7cPMAOMtKhgcH9wE8FBuPycgOG
BoYKt18ODL4gjccY2HSAfr4BVMvgAwyazwWSXSA7OrgY2BQYeH+Cw+sAKPo5wEHj
kQAO/GZWIIHDgc0AaxQSBAAFoxD7bgIAAA==
}

random/seed now
the-score: 0
board: reduce ['image 300x20 skier-right black]
for i 1 20 1 [
    pos: random 600x540
    pos: pos + 0x300
    append board reduce ['image pos tree black]
]

```

```

view center-face layout/tight [
  scrn: box white 600x440 effect [draw board] rate 0 feel [
    engage: func [f a e] [
      if a = 'key [
        if e/key = 'right [
          board/2: board/2 + 5x0
          board/3: skier-right
        ]
        if e/key = 'left [
          board/2: board/2 - 5x0
          board/3: skier-left
        ]
        show scrn
      ]
      if a = 'time [
        new-board: copy []
        foreach item board [
          either all [
            ((type? item) = pair!)
            ((length? new-board) > 4)
          ] [
            append new-board (item - 0x5)
          ] [
            append new-board item
          ]
          coord: first back back (tail new-board)
          if ((type? coord) = pair!) [
            if ((second coord) < -60) [
              remove back tail new-board
              remove back tail new-board
              remove back tail new-board
              remove back tail new-board
            ]
          ]
        ]
        board: copy new-board
        if (length? new-board) < 84 [
          column: random 600
          pos: to-pair rejoin [column "x" 440]
          append board reduce ['image pos tree black]
        ]
        collision-board: remove/part (copy board) 4
        foreach item collision-board [
          if (type? item) = pair! [
            if all [
              ((item/1 - board/2/1) < 15)
              ((item/1 - board/2/1) > -40)
              ((board/2/2 - item/2) < 30)
              ((board/2/2 - item/2) > 5)
            ] [
              alert "Ouch - you hit a tree!"
              alert rejoin ["Final Score: " the-score]
              quit
            ]
          ]
        ]
        the-score: the-score + 1
        score/text: to-string the-score
        show scrn
      ]
    ]
  ]
  origin across h2 "Score:"
  score: h2 bold "000000"
  do [focus scrn]
]

```

10.13.1 Addendum

It should be noted that I did lots of trial and error coding along the way, while writing and testing this

program. One thing that I tried initially was to have the skier move left-right by following left-right mouse gestures. I scrapped that idea because my code performed too slowly for this application, but the resulting code may still be useful in other projects. It's included here for completeness.

I defined this starting variable at the beginning of the program:

```
mouse-pos: 0x0
```

and added this code to the "feel" block, directly beneath the "engage" function:

```
over: func [f a p] [
  if not mouse-pos = p [ ; i.e., if mouse has moved
    either p/1 > mouse-pos/1 [ ; true = mouse has moved right
      ; update the skier image data in the "board" block:
      board/3: skier-right
    ] [
      board/3: skier-left
    ]
    ; set skier's position based on the column position of the
    ; mouse:
    board/2: to-pair rejoin compose [(p/1 - 35) "x" 20]
    mouse-pos: p
    show scrn
  ]
]
```

In order for the REBOL to continuously check for mouse events, the following "all-over" option must be added to the 'view layout' code:

```
view/options layout [...] [all-over]
```

Remove the key action code in the engage function, and replace it with the above changes. The skier will move left-right based upon left-right movements of the mouse.

Another way to accomplish the same goal, without using the "all-over" option, is to use the feel "detect" function:

```
detect: func [f e] [
  if e/type = 'move [
    p: e/offset
    if not mouse-pos = p [
      either p/1 > mouse-pos/1 [
        board/3: skier-right
      ] [
        board/3: skier-left
      ]
      board/2: to-pair rejoin compose [(p/1 - 35) "x" 20]
      mouse-pos: p
      show scrn
    ]
  ]
  e
]
```

That type of mouse control wasn't the best solution here, but could certainly be useful in other programs.

10.13.2 Snake Game

Below is the code for the classic "Snake" game. The point of the snake game is to move a snake image around the screen, devouring a food pellet that appears at random locations. Every time you eat a pellet,

your snake body grows by one unit. Avoid hitting the edge of the playing field, and avoid hitting your own body for as long as possible.

Notice that the code outline for this program is nearly identical to that of the ski game:

1. Embed the images needed to display snake sections and food pellets (for this example, I used simple green and red button images created using the "to-image" and "layout" functions, but that can be easily changed).
2. Set some initial variables (starting score, random starting coordinates, initial values for flags used throughout the program, etc.).
3. Create a board block to hold the image data and coordinates of the snake sections and food images.
4. Display the playing board in a "view layout" draw block, and move game play along by continuously checking for "feel engage" time and key events.
5. Change the direction the snake moves every time a key is pressed. Adjust snake coordinates (move the snake section images), and adjust the score, every time a timer event occurs (15 times per second). As in the ski game, create a temporary block to copy and adjust all the new snake coordinates (move the head of the snake to a new adjacent location, then move each consecutive section of the snake to the previous location of its adjoining section).
6. Check for collisions by comparing coordinate positions of the snake sections with other items on the board. End the game if the snake collides with a wall, or itself. Whenever the snake collides with a food image, move the food image to a new random coordinate, and add a new snake section image to the board (append an image to the board block, to increase the length of the snake).

```
REBOL [Title: "Snake Game"]

snake: to-image layout/tight [button red 10x10]
food: to-image layout/tight [button green 10x10]
the-score: 0 direction: 0x10 newsection: false random/seed now
rand-pair: func [s] [
  to-pair rejoin [(round/to random s 10) "x" (round/to random s 10)]
]
b: reduce [
  'image food ((rand-pair 190) + 50x50)
  'image snake ((rand-pair 190) + 50x50)
]
view center-face layout/tight gui: [
  scrn: box white 300x300 effect [draw b] rate 15 feel [
    engage: func [f a e] [
      if a = 'key [
        if e/key = 'up [direction: 0x-10]
        if e/key = 'down [direction: 0x10]
        if e/key = 'left [direction: -10x0]
        if e/key = 'right [direction: 10x0]
      ]
      if a = 'time [
        if any [b/6/1 < 0 b/6/2 < 0 b/6/1 > 290 b/6/2 > 290] [
          alert "You hit the wall!" quit
        ]
        if find (at b 7) b/6 [alert "You hit yourself!" quit]
        if within? b/6 b/3 10x10 [
          append b reduce ['image snake (last b)]
          newsection: true
          b/3: (rand-pair 290)
        ]
        newb: copy/part head b 5 append newb (b/6 + direction)
        for item 7 (length? head b) 1 [
          either (type? (pick b item) = pair!) [
            append newb pick b (item - 3)
          ] [
            append newb pick b item
          ]
        ]
        if newsection = true [
          clear (back tail newb)
          append newb (last b)
          newsection: false
        ]
        b: copy newb
        show scrn
        the-score: the-score + 1
      ]
    ]
  ]
]
```



```

        score/text: to-string the-score
    ]
]
]
origin across h2 "Score:"
score: h2 bold "000000"
do [focus scrn]
]

```

10.13.3 Obfuscation

Just for fun, I created an obfuscated (unreadable) version of the snake program. REBOL is such a malleable language that it's possible to create unbelievably compact code. I was able to squash the above 2030 bytes of nicely formatted code into the following 771 bytes of pure REBOL fury:

```

do[p: :append u: :reduce k: :pick r: :random y: :layout q: 'image z: :if
g: :to-image v: :length? x: does[alert join{SCORE: }[v b]quit]s: g y/tight
[btn red 10x10]o: g y/tight[btn tan 10x10]d: 0x10 w: 0 r/seed now b: u[q
o(((r 19x19)* 10)+ 50x50)q s(((r 19x19)* 10)+ 50x50)]view center-face
y/tight[c: area 305x305 effect[draw b]rate 15 feel[engage: func[f a e][z a
= 'key[d: select u['up 0x-10 'down 0x10 'left -10x0 'right 10x0]e/key]z a
= 'time[z any[b/6/1 < 0 b/6/2 < 0 b/6/1 > 290 b/6/2 > 290][x]z find(at b
7)b/6[x]z within? b/6 b/3 10x10[p b u[q s(last b)]w: 1 b/3:((r 29x29)*
10)]n: copy/part b 5 p n(b/6 + d)for i 7(v b)1 [either(type?(k b i)=
pair!)[p n k b(i - 3)][p n k b i]]z w = 1[clear(back tail n)p n(last b)w:
0]b: copy n show c]]do[focus c]]]

```

The above code is a fully functional snake program (go ahead, paste it into the interpreter...). I created it by renaming functions using single-letter labels (r: :random, p: :append, etc.). Any function that was used several times in the program got renamed. I also removed any spaces which surrounded parentheses or brackets. Line breaks are included only so that the code fits inside this web page - otherwise, they're not necessary. There's not much practical purpose to obfuscating code in this way, but it can be used to impress all your friends who don't know REBOL :)

10.13.4 Space Invaders Shootup

Below is an extremely simple variation of the classic Space Invaders game idea. Compare the code outline of this program with that of the previous games, and notice again the similar structure: embedded image definitions, game board block creation, view layout draw display, "feel engage" key and time event loops, coordinate calculations to move game images and to detect collisions, etc. Notice also the "system/view/caret: none" and "system/view/caret: head f/text" code before and after each "show scrn". This erases the text caret (small vertical line) that appears in a face whenever the "focus" function is called:

```

REBOL [title: "Space Invaders Shootup"]

alien1: load to-binary decompress 64#{
eJx9UzFLQzEQjiJUOognHTIVhCd0cXJ1kLe3g7SbFKcsWQoWZ7MFhNKxg0PpH3Cx
WbKUqpPoUncOPimlQ+kPkCJekvf0NTx7cL17d8l33+XywwL+FrFyhVpCPUY9QN0g
LnG7ScjJrtM98iedToem3kbW7/f71k4/p6R+USE9Xo/UqjUbi94jMhgMrL/8XpLm
ZZP4spPyzxVT35MM2Zir4vFYu4dM7GP2M483Fa8f8w0O/Vy24yzo8RXipfJmdb8
kJxwrdJ7K4gxiSs7/09czYpdW6vcsI+AtrEKQ7ScDPlLHO/aNQ8huzaVeSDaHrNi
3i1BjDI6mqVswvIA0E5ZJ20t1UIuAKHmqoS5kHOT9UPMP0sm3TU5PHdHQVIZMs3v
qZTPmrMAQAj6ZXOSutkwPKRwloKQNlexCDovR4fpc1Gq76KNzC2mQPig68li5gAw
ZusVJEAh5JoJbzrEGQYC2dncuh7+y83d7ASVAu8MpaQqkT9+3Gg3Q+whI2AZSAFm
1+99FzMqkz11VUxeTFUrc4vC4Q4VV4w1LyaerjD1XPe+tLxK8SNbqTrJOIf/Bd4X
V+VU7AfjSm0ZEgQAAA==
}

ship1: load to-binary decompress 64#{
eJx1Us9L3EAU/rTbMdHE9V1YukSQFhUpvXjQXrfizR8XkYAnt0oQVsTLGlgEFdSL
l3jqpxgre6sEJAgDsidiPIul/sHjopeIfILj0JdnV3ez0y7zJzLx533vvY2YXhzOI
scs2yfaF7QNbdXLHjzfAu4HEhpKryAgDfccC4rfAws0IjF/96HsWyH7XMNXIon9Z
QJvWsNQw8XZP4NPLKD73Whi/HcZO4z207fv7jyo8/jk4r1TdFQXcSrV+flEtq3x2
5amuB44lyU+BpHRKHq4dKXnZCbLkx19kOF5BarPVDfWYBAWCEAVFsjrHENGmhyPK
UXe+XNHf9HqZw9GgyzUUoloqXcXE1wv6iSTHohSkQ8yJQ512RCiSvPIGbaVktFuu
Ge5/erfdurb+wM3ETZHPyjaX5NzNHPATOHmsn894sMZJWX4uH78OYSvTrUU+paI2
q8nQl5JHMFaSOZLBbHPnoR2ndHUa5NtPwubfFKziT1YqRDdY2VV3Jckt3X2Zi1wW

```

```

KQjmUxGhGQ0Ecm50lhBvUsSi/NpXmjLRoFx4YWuL0789fN24m+jsK2x+wGE+JjLR
DePiqdbKZqZojf1qLZ2ptd03ZrxXwjCODzuThK3Af4EF8jYSBAAA
}
alien-fire: load to-binary decompress 64#{
eJxz8oljZACDMiDWAGI+IJYFYkYGFrd4CyAW5oZgAYhSBhZmFoaWphaG48eOMwQF
BDFOaGgWPH36lGHZsmUM4uLiDFk5WQyzZsliuHHzBsOfv38Ydu7cyWBhZsFQXlrO
EBEVATTBaW1o1AoDA/vp3bt37wHyZwPpTUCaedqpUBWGS6HLMj8AedpA0ZlQGqTK
KXrNtCdGf/BLtrCD6GywOAPDabA6BobCTAMwXTfzFMh8uM7ZUBpi/p3QZdMMwLp2
796GbH7omrR2sH6Omc+h5m4C09pQuiKzHWp+OlR+DlQeQjstPQINIwag+wBUhlwj
XgEAAA==
}
ship-fire: load to-binary decompress 64#{
eJxz8t3FAAF1QKwBxOxALAJeJawsYHEXIBbmhmABqFo2FhYG9l4eBvajbAwKSTIM
/H8FGFjUOBg4tnEyGP1VYWAXZWOWadNg4KHiYdA5JMLAacbJIHNLhUFnkgiDIpMg
2IyDd2UYVMqdGNLLyxOz7RpCJ5p2pDi4sYAwlFpSz+AcEoJkF8O5KstZWWhUkvig
4uLEoAIUO7f7zQcA8m8lvboAAAA=
}
bottom: 270 end: sidewall: false random/seed now
b: ['image 300x400 ship1 'line -10x270 610x270]
for row 60 220 40 [
  for column 20 380 60 [
    pos: to-pair rejoin [column "x" row]
    append b reduce ['image pos alien1]
  ]
]
view center-face layout/tight [
  scrn: box black 600x440 effect [draw b] rate 1000 feel [
    engage: func [f a e] [
      if a = 'key [
        if e/key = 'right [b/2: b/2 + 5x0]
        if e/key = 'left [b/2: b/2 - 5x0]
        if e/key = 'up [
          if not find b ship-fire [
            fire-pos: b/2 + 25x-20
            append b reduce ['image fire-pos ship-fire]
          ]
        ]
        system/view/caret: none
        show scrn
        system/view/caret: head f/text
      ]
      if a = 'time [
        if (random 1000) > 900 [
          f-pos: to-pair rejoin [random 600 "x" bottom]
          append b reduce ['image f-pos alien-fire]
        ]
        for i 1 (length? b) 1 [
          removed: false
          if ((pick b i) = ship-fire) [
            for c 8 (length? head b) 3 [
              if (within? (pick b c) (
                (pick b (i - 1)) + -40x0) 50x35)
                and ((pick b (c + 1)) <> ship-fire) [
                  removed: true
                  d: c
                  e: i - 1
                ]
            ]
            either ((second (pick b (i - 1))) < -10) [
              remove/part at b (i - 2) 3
            ] [
              do compose [b/(i - 1): b/(i - 1) - 0x9]
            ]
          ]
          if ((pick b i) = alien1) [
            either ((second (pick b (i - 1))) > 385) [
              end: true
            ] [
              if ((first (pick b (i - 1))) > 550) [
                sidewall: true
                for item 4 (length? b) 1 [
                  if (pick b item) = alien1 [

```

```

do compose [
  b/(item - 1): b/(item - 1) + 0x2
]
]
]
bottom: bottom + 2
b/5: to-pair rejoin [-10 "x" bottom]
b/6: to-pair rejoin [610 "x" bottom]
]
if ((first (pick b (i - 1))) < 0) [
  sidewall: false
  for item 4 (length? b) 1 [
    if (pick b item) = alien1 [
      do compose [
        b/(item - 1): b/(item - 1) + 0x2
      ]
    ]
  ]
  bottom: bottom + 2
  b/5: to-pair rejoin [-10 "x" bottom]
  b/6: to-pair rejoin [610 "x" bottom]
]
if sidewall = true [
  do compose [b/(i - 1): b/(i - 1) - 2x0]
]
if sidewall = false [
  do compose [b/(i - 1): b/(i - 1) + 2x0]
]
]
]
if ((pick b i) = alien-fire) [
  if within? ((pick b (i - 1)) + 0x14) (
    (pick b 2) + -10x0) 65x35 [
    alert "You've been killed by alien fire!" quit
  ]
  either ((second (pick b (i - 1))) > 400) [
    remove/part at b (i - 2) 3
  ] [
    do compose [b/(i - 1): b/(i - 1) + 0x3]
  ]
]
if removed = true [
  remove/part (at b (d - 1)) 3
  remove/part (at b (e - 1)) 3
]
]
system/view/caret: none
show scrn
system/view/caret: head f/text
if not (find b alien1) [
  alert "You killed all the aliens. You win!" quit
]
if end = true [alert "The aliens landed! Game over." quit]
]
]
do [focus scrn]
]

```

I created a version of this game for my fiancé using an image of my face for ship1, and an image of her face as alien1. An XpackerX executable version of it is available at http://musiclessonz.com/rebol_tutorial/corina_invaders.exe.

Now take a break from coding, and play a few games :)

10.14 Case 14 - Media Player (Wave/Mp3 Jukebox)

This case study started when a reader of this tutorial sent me an email question. He was having trouble creating a simple script that would load the file names from a directory on his hard drive into a GUI text list. He wanted to be able to click on .wav files in the list in order to play the sounds. I generally don't have time

to answer questions like that, but this one was a quicky. The following code switches to the Windows media folder, reads the directory listing, and displays the file names in a GUI text list:

```
change-dir %/c/Windows/media
view layout [text-list data read %.]
```

I just added the contents of the "play-sound" function found earlier in this tutorial, to the action block of the text list. This loads the contents of the value selected in the text list (the file name), and plays the sound:

```
change-dir %/c/Windows/media
view layout [
  vh2 "Click a File to Play:"
  text-list data read %. [
    wait 0
    sound-port: open sound://
    insert sound-port (load value)
    wait sound-port
    close sound-port
  ]
]
```

That was simple.

A few days later the reader emailed me for some additional help. As it stands, the script crashes if the user selects anything other than a .wav file, or if another file is selected while a .wav is currently playing. I wrote back with some code to get the text list to show only .wav files and to make the program wait to play another file. I also wrote some additional code to let users select a different starting directory. Here it is:

```
; Here's how to use the "request-dir" function to let the user
; select a folder to switch into:

start-dir: request-dir/dir %/c/Windows/media
change-dir start-dir

; To display only files with a ".wav" extension in your text list,
; create a new empty block. Use a "foreach" loop to go through the
; directory listing, and append to the new block only file names
; which have ".wav" as the suffix:

waves: []
foreach file read %. [
  if %wav = (suffix? file) [append waves file]
]

; Now you can display the "waves" block of data in the GUI text list.

; To wait for sounds to finish playing before another file can
; be selected, add a "wait-flag" variable to the play-sound
; function. When a sound starts playing, set the wait-flag
; variable to true. When it's finished playing, set the wait-flag
; to false. Also be sure to set it initially to "false" at
; the beginning of your program:

play-sound: func [sound-file] [
  wait 0
  wait-flag: true
  ring: load sound-file
  sound-port: open sound://
  insert sound-port ring
  wait sound-port
  close sound-port
  wait-flag: false
]
wait-flag: false
```

```

; When a file is selected from the text list, only run the
; "play-sound" function if the "wait-flag" variable is not
; set to true (i.e., if no sounds are playing):

view layout [
    vh2 "Click a File to Play:"
    text-list data waves [
        if wait-flag <> true [
            play-sound value
        ]
    ]
]

```

As I tested the above code, I realized that a few various .wav files in the Windows media folder wouldn't play properly, and the script crashed. I added the following code to handle errors:

```

if error? try [play-sound value] [
    alert "malformed wave"      ; Alert the user with a message,
    close sound-port           ; close the port opened by the broken
    wait-flag: false           ; play-sound function, and set the flag
]                               ; back to false (so other waves can play).

```

I also decided to add a button to the GUI to allow users to change the directory at will, instead of just at the beginning of the script:

```

btn "Change Folder" [
    change-dir request-dir
    waves: copy []
    foreach file read % [
        if %.wav = suffix? file [append waves file]
    ]
    file-list/data: waves
    show file-list
]

```

At this point, we've got a nice little .wav playing application:

```

REBOL []

play-sound: func [sound-file] [
    wait 0
    wait-flag: true
    ring: load sound-file
    sound-port: open sound://
    insert sound-port ring
    wait sound-port
    close sound-port
    wait-flag: false
]

wait-flag: false
change-dir %/c/Windows/media
waves: []
foreach file read % [
    if %.wav = suffix? file [append waves file]
]

view layout [
    vh2 "Click a File to Play:"
    file-list: text-list data waves [
        if wait-flag <> true [
            if error? try [play-sound value] [
                alert "malformed wave"
                close sound-port
                wait-flag: false
            ]
        ]
    ]
]

```

```

    ]
  ]
  btn "Change Folder" [
    change-dir request-dir
    waves: copy []
    foreach file read % [
      if %.wav = suffix? file [append waves file]
    ]
    file-list/data: waves
    show file-list
  ]
]

```

This was posted online, and within a few days several readers asked the same question: "How do I get it to play .mp3 files?". REBOL cannot natively play mp3s, so we need to use an external tool to make that happen. Earlier in the tutorial, I included a .dll example that plays mp3 files, but I wanted a slightly more industrial strength solution. I decided to give the well known "LAME" mp3 encoder/decoder a try. I downloaded the compiled Windows version of LAME from <http://www.rarewares.org/mp3-lame-bundle.php>, and compressed the .exe version of it using the binary resource embedder found earlier in this tutorial. For the sake of saving space in this tutorial, I uploaded the compressed, embedded code to http://musiclessonz.com/rebol_tutorial/lame_embedded.r. The following line writes the lame.exe program to the current directory of your hard drive:

```
do http://musiclessonz.com/rebol_tutorial/lame.r ; ~250k download
```

To use our media player program without having to download anything, simply put the above lame.r code directly in your script. Once you've got lame.exe on your hard drive, you can use it to convert .mp3 files to .wav files using the format:

```
call/wait {lame.exe --decode your-input.mp3 your-output.wav}
```

I added the line above to my existing program, and changed the "waves" block-building foreach routine to include .mp3 files:

```

waves: []
foreach file read % [
  if ((%.wav = suffix? file) or
    (%.mp3 = suffix? file)) [append waves file]
]

```

I also changed the wave playing routine (the action block of the GUI text list), so that if an mp3 file is selected, lame is run and the file is converted to a temporary wav file, and then that wav file is played:

```

file-list: text-list data waves [
  either %.mp3 = suffix? value [
    call/wait rejoin ["lame.exe --decode "
      (to-local-file value) " temp.wav"]
    if wait-flag <> true [
      if error? try [play-sound %temp.wav] [
        alert "malformed wave"
        close sound-port
        wait-flag: false
      ]
    ]
  ]
] [
  if wait-flag <> true [
    if error? try [play-sound value] [
      alert "malformed wave"
      close sound-port
      wait-flag: false
    ]
  ]
]

```

```

    ]
  ]
]

```

With those changes, the code now looks like this:

```

REBOL []

do http://musiclessonz.com/rebol_tutorial/lame.r
play-sound: func [sound-file] [
  wait 0
  wait-flag: true
  ring: load sound-file
  sound-port: open sound://
  insert sound-port ring
  wait sound-port
  close sound-port
  wait-flag: false
]
wait-flag: false
change-dir %/c/Windows/media
waves: []
foreach file read % [
  if ((%.wav = suffix? file) or
      (%.mp3 = suffix? file)) [append waves file]
]
view center-face layout [
  vh2 "Click a File to Play:"
  file-list: text-list data waves [
    either %.mp3 = suffix? value [
      message/text: "Decoding mp3..." show message
      call/wait rejoin ["lame.exe --decode "
        (to-local-file value) " temp.wav"]
      message/text: "" show message
      if wait-flag <> true [
        if error? try [play-sound %temp.wav] [
          alert "malformed wave"
          close sound-port
          wait-flag: false
        ]
      ]
    ] [
      if wait-flag <> true [
        if error? try [play-sound value] [
          alert "malformed wave"
          close sound-port
          wait-flag: false
        ]
      ]
    ]
  ]
  btn "Change Folder" [
    change-dir request-dir
    waves: copy []
    foreach file read % [
      if ((%.wav = suffix? file) or
          (%.mp3 = suffix? file)) [append waves file]
    ]
    file-list/data: waves
    show file-list
  ]
  message: h2 " "
]

```

That's a cute solution, but the performance is not acceptable for any legitimate use. Large mp3 files take a long time to convert before being played.

Another potential mp3 playing option I considered was a small command line mp3 player called "madplay.exe", available from <http://www.rarewares.org/mp3-others.php>. Madplay doesn't have any GUI interface - you simply run it on the command line and control playback using keystrokes. Madplay can play many types of media, and keystrokes can be sent to it programatically using the Windows API or the [Autoit DLL](#). I did create a working app using madplay.exe and autoit.dll, but I won't document that code here because it felt like another cobbled together solution.

To find a real solution, I googled "play mp3 dll". The first thing that came up was "libwmp3.dll" from <http://www.inet.hr/~zcindori/libwmp3/index.html>. Bingo - that did exactly what I wanted. The dll shipped with example usage code written in Visual Basic, C, C++, and Delphi. From these examples, I was able to decipher the required function names, input parameters, and return values, and came up with the following code to access the .dll in REBOL:

```
lib: load/library %libwmp3.dll

Mp3_Initialize: make routine! [
    return: [integer!]
] lib "Mp3_Initialize"

Mp3_OpenFile: make routine! [
    return: [integer!]
    class [integer!]
    filename [string!]
    nWaveBufferLengthMs [integer!]
    nSeekFromStart [integer!]
    nFileSize [integer!]
] lib "Mp3_OpenFile"

Mp3_Play: make routine! [
    return: [integer!]
    initialized [integer!]
] lib "Mp3_Play"

; The following function and structure aren't required
; to play mp3s, but we'll use them to determine if a
; file is currently being played:

Mp3_GetStatus: make routine! [
    return: [integer!]
    initialized [integer!]
    status [struct! []]
] lib "Mp3_GetStatus"

status: make struct! [
    fPlay [integer!]
    fPause [integer!]
    fStop [integer!]
    fEcho [integer!]
    nSfxMode [integer!]
    fExternalEQ [integer!]
    fInternalEQ [integer!]
    fVocalCut [integer!]
    fChannelMix [integer!]
    fFadeIn [integer!]
    fFadeOut [integer!]
    fInternalVolume [integer!]
    fLoop [integer!]
    fReverse [integer!]
] none

; The following functions stop play and release memory when done:

Mp3_Stop: make routine! [
    return: [integer!]
    initialized [integer!]
] lib "Mp3_Stop"

Mp3_Destroy: make routine! [
    return: [integer!]
```



```

    initialized [integer!]
] lib "Mp3_Destroy"

```

Now those functions can be used in REBOL to play any .mp3. It's very easy, using 3 functions:

```

initialized: Mp3_Initialize
Mp3_OpenFile initialized "test.mp3" 1000 0 0
Mp3_Play initialized

; Just change the "test.mp3" file to any .mp3 you want to play.
; Be sure that the file name is sent as a string, and that it's
; written in Windows file format (use the "to-local-file" and
; "what-dir" functions if necessary, to convert from REBOL file
; format).

```

That's all the code required to play an mp3. To check if an mp3 file is currently playing:

```

Mp3_GetStatus initialized status
if ( status/fPlay > 0 ) [print "playing"]

```

To stop an mp3 from playing:

```

Mp3_Stop initialized

```

To clean up afterward:

```

Mp3_Destroy initialized
free lib

```

I added some code to download the libwmp3.dll to the hard drive (of course, the .dll file could also be embedded directly in your code, using the binary resource embedder from earlier in this tutorial):

```

if not exists? %libwmp3.dll [
    write/binary %libwmp3.dll
    read/binary http://musiclessonz.com/rebol_tutorial/libwmp3.dll
]

```

Now we can add real mp3 playing ability to our little app. Here's the final code:

```

REBOL [title: "Jukebox - Wav/Mp3 Player"]

if not exists? %libwmp3.dll [
    write/binary %libwmp3.dll
    read/binary http://musiclessonz.com/rebol_tutorial/libwmp3.dll
]

lib: load/library %libwmp3.dll

Mp3_Initialize: make routine! [
    return: [integer!]
] lib "Mp3_Initialize"

Mp3_OpenFile: make routine! [
    return: [integer!]
    class [integer!]
    filename [string!]

```

```

        nWaveBufferLengthMs [integer!]
        nSeekFromStart [integer!]
        nFileSize [integer!]
    ] lib "Mp3_OpenFile"

Mp3_Play: make routine! [
    return: [integer!]
    initialized [integer!]
] lib "Mp3_Play"

Mp3_Stop: make routine! [
    return: [integer!]
    initialized [integer!]
] lib "Mp3_Stop"

Mp3_Destroy: make routine! [
    return: [integer!]
    initialized [integer!]
] lib "Mp3_Destroy"

Mp3_GetStatus: make routine! [
    return: [integer!]
    initialized [integer!]
    status [struct! []]
] lib "Mp3_GetStatus"

status: make struct! [
    fPlay [integer!]
    fPause [integer!]
    fStop [integer!]
    fEcho [integer!]
    nSfxMode [integer!]
    fExternalEQ [integer!]
    fInternalEQ [integer!]
    fVocalCut [integer!]
    fChannelMix [integer!]
    fFadeIn [integer!]
    fFadeOut [integer!]
    fInternalVolume [integer!]
    fLoop [integer!]
    fReverse [integer!]
] none

play-sound: func [sound-file] [
    wait 0
    wait-flag: true
    ring: load sound-file
    sound-port: open sound://
    insert sound-port ring
    wait sound-port
    close sound-port
    wait-flag: false
]

wait-flag: false
change-dir %/c/Windows/media
waves: []
foreach file read % [
    if ((%.wav = suffix? file) or
        (%.mp3 = suffix? file)) [append waves file]
]

initialized: Mp3_Initialize

view center-face layout [
    vh2 "Click a File to Play:"
    file-list: text-list data waves [
        Mp3_GetStatus initialized status
        either %.mp3 = suffix? value [
            if (wait-flag <> true) and (status/fPlay = 0) [
                file: rejoin [to-local-file what-dir "\"" value]
                Mp3_OpenFile initialized file 1000 0 0
            ]
        ]
    ]
]

```



```

        initialized [integer!]
    ] lib "Mp3_Destroy"
Mp3_GetStatus: make routine! [
    return: [integer!]
    initialized [integer!]
    status [struct! []]
] lib "Mp3_GetStatus"
status: make struct! [
    fPlay [integer!]
    fPause [integer!]
    fStop [integer!]
    fEcho [integer!]
    nSfxMode [integer!]
    fExternalEQ [integer!]
    fInternalEQ [integer!]
    fVocalCut [integer!]
    fChannelMix [integer!]
    fFadeIn [integer!]
    fFadeOut [integer!]
    fInternalVolume [integer!]
    fLoop [integer!]
    fReverse [integer!]
] none
Mp3_Time: make struct! [
    ms [integer!]
    sec [integer!]
    bytes [integer!]
    frames [integer!]
    hms_hour [integer!]
    hms_minute [integer!]
    hms_second [integer!]
    hms_millisecond [integer!]
] none
TIME_FORMAT_SEC: 2
SONG_BEGIN: 1
SONG_CURRENT_FORWARD: 4
Mp3_Seek: make routine! [
    return: [integer!]
    initialized [integer!]
    fFormat [integer!]
    pTime [struct! []]
    nMoveMethod [integer!]
] lib "Mp3_Seek"
Mp3_PlayLoop: make routine! [
    return: [integer!]
    initialized [integer!]
    fFormatStartTime [integer!]
    pStartTime [struct! []]
    fFormatEndTime [integer!]
    pEndTime [struct! []]
    nNumOfRepeat [integer!]
] lib "Mp3_PlayLoop"
Mp3_GetSongLength: make routine! [
    return: [integer!]
    initialized [integer!]
    pLength [struct! []]
] lib "Mp3_GetSongLength"
Mp3_GetPosition: make routine! [
    return: [integer!]
    initialized [integer!]
    pTime [struct! []]
] lib "Mp3_GetPosition"
Mp3_SetVolume: make routine! [
    return: [integer!]
    initialized [integer!]
    nLeftVolume [integer!]
    nRightVolume [integer!]
] lib "Mp3_SetVolume"
Mp3_GetVolume: [
    initialized [integer!]
    pnLeftVolume [integer!]
    pnRightVolume [integer!]

```

```

    return: [integer!]
] lib "Mp3_GetVolume"
Mp3_VocalCut: make routine! [
    return: [integer!]
    initialized [integer!]
    fEnable [integer!]
] lib "Mp3_VocalCut"
Mp3_ReverseMode: make routine! [
    return: [integer!]
    initialized [integer!]
    fEnable [integer!]
] lib "Mp3_ReverseMode"
Mp3_Close: make routine! [
    return: [integer!]
    initialized [integer!]
] lib "Mp3_Close"
waves: []
foreach file read % [
    if (%.mp3 = suffix? file) [append waves file]
]
append waves "(CHANGE FOLDER...)"
initialized: Mp3_Initialize
view center-face layout [
    vh2 "Click a File to Play:"
    file-list: text-list data waves [
        if value = "(CHANGE FOLDER...)" [
            new-dir: request-dir
            if new-dir = none [break]
            change-dir new-dir
            waves: copy []
            foreach file read % [
                if (%.mp3 = suffix? file) [append waves file]
            ]
            append waves "(CHANGE FOLDER...)"
            file-list/data: waves
            show file-list
            break
        ]
    ]
    Mp3_GetStatus initialized status
    if (status/fPlay = 0) [
        file: rejoin [to-local-file what-dir "\" value]
        Mp3_OpenFile initialized file 1000 0 0
        Mp3_Play initialized
    ]
]
across
tabs 40
text "Seek: "
tab slider 140x15 [
    plength: make struct! Mp3_Time compose [0 0 0 0 0 0 0 0]
    Mp3_GetSongLength initialized plength
    location: to-integer (value * plength/sec)
    ptime: make struct! Mp3_Time compose [0 (location) 0 0 0 0 0 0]
    Mp3_Seek initialized TIME_FORMAT_SEC ptime SONG_BEGIN
    Mp3_Play initialized
]
return
text "Volume: "
tab slider 140x15 [
    volume: to-integer value * 100
    Mp3_SetVolume initialized volume volume
]
return
btn "Reverse" [
    Mp3_GetStatus initialized status
    either (status/fReverse > 0) [
        Mp3_ReverseMode initialized 0
    ] [
        Mp3_ReverseMode initialized 1
    ]
]
btn "Vocal-Cut" [

```

```

    Mp3_GetStatus initialized status
    either (status/fVocalCut > 0) [
        Mp3_VocalCut initialized 0
    ] [
        Mp3_VocalCut initialized 1
    ]
]
return
tabs 50
text "Loop Start:"
tab start-slider: slider 120x15 []
return
text "Loop End:  "
tab end-slider: slider 120x15 []
return
btn "Play Loop" [
    plength: make struct! Mp3_Time compose [0 0 0 0 0 0 0 0]
    Mp3_GetSongLength initialized plength
    s-loc: to-integer (start-slider/data * plength/sec)
    pStartTime: make struct! Mp3_Time compose [0 (s-loc) 0 0 0 0 0 0]
    end-loc: to-integer (end-slider/data * plength/sec)
    pEndTime: make struct! Mp3_Time compose [0 (end-loc) 0 0 0 0 0 0]
    ; TIME_FORMAT_SEC: 2
    Mp3_PlayLoop initialized 2 pStartTime 2 pEndTime 1000 ; 1000x
]
btn 58 "Stop" [
    Mp3_GetStatus initialized status
    if (status/fPlay > 0) [Mp3_Stop initialized]
]
]
Mp3_Destroy initialized
free lib

```

Libwmp3.dll is a very powerful and easy solution for playing mp3 files in any Windows programming language. If you're interested in playing mp3s in REBOL, it's a must-have.

10.15 Case 15 - Creating the REBOL "Demo"

At the beginning of this tutorial, a short application was provided to demonstrate how potent REBOL code can be. The 10 programs included in that demo are all shortened versions of other pieces of code found throughout this tutorial:

The "paint" program was covered in the section of the tutorial about the draw dialect:

```

view center-face layout [
    s: area black 650x350 feel [
        engage: func [f a e] [
            if a = 'over [
                append s/effect/draw e/offset
                show s
            ]
            if a = 'up [append s/effect/draw 'line]
        ]
    ] effect [draw [line]]
    b: btn "Save" [
        save/png %a.png to-image s
        alert "Saved 'a.png'"
    ]
    btn "Clear" [
        s/effect/draw: copy [line]
        show s
    ]
]

```

The "game" is the obfuscated snake program covered earlier:

```

do[p: append u: :reduce k: :pick r: :random y: :layout q: 'image z: :if
g: :to-image v: :length? x: does[alert join{SCORE: }[v b]quit]s: g y/tight
[btn red 10x10]o: g y/tight[btn tan 10x10]d: 0x10 w: 0 r/seed now b: u[q
o(((r 19x19)* 10)+ 50x50)q s(((r 19x19)* 10)+ 50x50)]view center-face
y/tight[c: area 305x305 effect[draw b]rate 15 feel[engage: func[f a e][z a
= 'key[d: select u['up 0x-10 'down 0x10 'left -10x0 'right 10x0]e/key]z a
= 'time[z any[b/6/1 < 0 b/6/2 < 0 b/6/1 > 290 b/6/2 > 290][x]z find(at b
7)b/6[x]z within? b/6 b/3 10x10[p b u[q s(last b)]w: 1 b/3:((r 29x29)*
10)]n: copy/part b 5 p n(b/6 + d)for i 7(v b)1 [either(type?(k b i)=
pair!)[p n k b(i - 3)][p n k b i]]z w = 1[clear(back tail n)p n(last b)w:
0]b: copy n show c]]do[focus c]]]

```

The "puzzle" is the tile program explained in the first section of the tutorial about GUIs:

```

alert {Arrange tiles alphabetically:}
view center-face layout [
  origin 0x0 space 0x0 across
  style p button 60x60 [
    if not find [0x60 60x0 0x-60 -60x0] face/offset - x/offset [exit]
    temp: face/offset face/offset: x/offset x/offset: temp
  ]
  p "O" p "N" p "M" p "L" return
  p "K" p "J" p "I" p "H" return
  p "G" p "F" p "E" p "D" return
  p "C" p "B" p "A" x: p white edge [size: 0]
]

```

The "calendar" is a simple application in which the user selects a day using the date requester function. Events for the day are typed into an area widget and then appended to a text file. The text file is searched every time a date is chosen. If the chosen date is found, the events for that day are shown in the area widget, which can be edited and saved back to the text file:

```

do the-calendar: [
  if not (exists? %s) [write %s ""]
  the-date: request-date
  view center-face layout [
    h5 to-string the-date
    aa: area to-string select to-block (
      find/last (to-block read %s) the-date
    ) the-date
    btn "Save" [
      write/append %s rejoin [the-date " {" aa/text " } " ]
      unview
      do the-calendar
    ]
  ]
]

```

The "video" program was covered in the section of the tutorial about multitasking. All it does is continually load and display images from a web cam server. The image refresh is handled using a feel-engage loop, which checks for a timer event:

```

video-address: to-url request-text/title/default "URL:" trim {
  http://tinyurl.com/m54ltm}
view center-face layout [
  image load video-address 640x480 rate 0 feel [
    engage: func [f a e] [
      if a = 'time [
        f/image: load video-address
        show f
      ]
    ]
  ]
]

```

```
]

```

The "IP" program was covered in the section about the REBOL parse dialect. This program reads a web page which displays the remote WAN IP address of the user's computer in the title tag, then parses out all the extra text and displays the IP address, along with the user's local IP address (the local address is gotten by using REBOL's built in dns:// protocol:

```
parse read to-url "http://guitarz.org/ip.cgi" [
  thru <title> copy my to </title>
]
i: last parse my none
alert to-string rejoin [
  "WAN: " i " -- LAN: " read join dns:// read dns://
]
```

The "email" program is extremely simple. The user enters email account information into a GUI text field, and then the mail from that account is read using REBOL's native POP protocol. The contents of the mailbox are displayed in REBOL's built-in text editor, each separated by 6 newlines:

```
view center-face layout [
  email-login: field "pop://user:pass@site.com"
  btn "Read" [
    my-mail: copy []
    foreach i (read to-url email-login/text) [
      append my-mail join i "^/^/^/^/^/^/"
      editor my-mail
    ]
  ]
]
```

The "days between" program was covered in an earlier case study. Here's a simple version of the program (an example given in the first part of the case study):

```
view center-face layout [
  btn "Start" [sd: request-date]
  btn "End" [
    ed: request-date
    db/text: to-string (ed - sd)
    show db
  ]
  text "Days Between:"
  db: field
]
```

The "sounds" program was also covered earlier:

```
play-sound: func [sound-file] [
  wait 0 ring: load sound-file
  wait-flag: 1
  sound-port: open sound://
  insert sound-port ring
  wait sound-port
  close sound-port
  wait-flag: 0
]
wait-flag: 0
change-dir %/c/Windows/media
do get-waves: [
  waves-list: copy []
  foreach i read %. [
    if %.wav = suffix? i [
```



```

        append waves-list i
    ]
]
view center-face layout [
    waves-gui-list: text-list data waves-list [
        if wait-flag <> 1 [
            if error? try [play-sound value] [
                alert "Error"
                close sound-port
                wait-flag: 0
            ]
        ]
    ]
    btn "Dir" [
        change-dir request-dir
        do get-waves
        waves-gui-list/data: waves-list
        show waves-gui-list
    ]
]

```

The "FTP" program is a stripped down version of the "FTP Tool" explained earlier:

```

view center-face layout [
    px: field "ftp://user:pass@site.com/folder/" [
        either dir? to-url value [
            f/data: sort read to-url value
            show f
        ][
            editor to-url value
        ]
    ]
    f: text-list [
        editor to-url join px/text value
    ]
    btn "?" [
        alert {
            Type a URL path to browse (nonexistent files are created).
            Click files to edit.
        }
    ]
]

```

I enclosed all of those examples in a simple GUI, with buttons to run each program:

```

REBOL [title: "Demo"]

view layout [
    style h btn 150
    h "Paint" [
        ; code for the paint program goes here
    ]
    h "Game" [
        ; code for the game program goes here
    ]
    h "Puzzle" [
        ; code for the puzzle program goes here
    ]
    h "Calendar" [
        ; code for the calendar program goes here
    ]
    h "Video" [
        ; code for the video program goes here
    ]
    h "IPs" [

```

```

        ; code for the IP program goes here
    ]
    h "Email" [
        ; code for the email program goes here
    ]
    h "Days" [
        ; code for the days-between program goes here
    ]
    h "Sounds" [
        ; code for the sound program goes here
    ]
    h "FTP" [
        ; code for the FTP program goes here
    ]
]

```

To make the demo as compact as possible, I used the same techniques as in the obfuscated snake program (from earlier in the tutorial). Here are the global functions that I renamed with shorter word labels:

```

p: :append kk: :pick r: :random y: :layout q: 'image z: :if gg: :to-image
v: :length? g: :view k: :center-face ts: :to-string tu: :to-url sh: :show
al: :alert rr: :request-date co: :copy

```

I also renamed other functions within their local contexts. In the following code, the value "s/effect/draw" is assigned the variable "pk". That saves having to write "s/effect/draw" again. That value does not exist in the global context, so that variable must be assigned locally. This type of shortened local variable assignment occurs several times throughout the demo code:

```

view layout [
    s: area black 650x350 feel [
        engage: func [f a e] [
            if a = 'over [
                append pk: s/effect/draw e/offset
                show s
            ]
            if a = 'up [append pk 'line]
        ]
    ] effect [
        draw [line]
    ]
]

```

To finish the application, I simply removed any spaces which surrounded parentheses or brackets. The final code is found in the first section of this tutorial. Here's a screen shot - it's less than 1/2 a page of printed code:

```

REBOL[title:"Demo"]p: append kk: pick r: random y: layout q: "image z: if gg: to-image v: :length? g:
view k: center-face ts: to-string tu: to-uri sh: show al: alert rr: request-date co: copy g y/style h btn 150
h"Paint"]g/new k y/s: area black 650x350 feel[engage: func[t a e][z a = "over[ppk: s/effect/draw e/offset sh
s]z a = "up[ppk 'line]] effect[draw[line]b: btn'Save'save/png %s.png gg s al'Saved 's.png"]btn'Clear"
s/effect/draw: co[line]ah s]]h"Game"tu: reduce x: does[al join[SCORE: [v b]unview]s: gg y/tight[btn red
10x10]p: gg y/tight[btn tan 10x10]d: 0x10 w: 0 r/seed now b: u[q o(((r 19x19)* 10)+ 50x50]q s(((r 19x19)*
10)+ 50x50)]g/new k y/tight[c: area 305x305 effect[draw b]rate 15 feel[engage: func[t a e][z a = "key(d:
select u/up 0x10 'down 0x10 'left -10x0 'right 10x0]e/key]z a = "time(z any[b/6/1 < 0 b/6/2 < 0 b/6/1 > 290
b/6/2 > 290][x]z find(at b 7)b/6[x]z within? b/6 b/3 10x10]p b u[q s (last b)]w: 1 b/3: ((r 29x29)* 10)]n: col/part
b 5 p n(b/6 + d)for i 7(v b)]either(type?(kk b i)=pair!)[p n kk b(i - 3)][p n kk b i]]z w = 1[clear(back tail n)p
n(last b)w: 0]b: do n sh c]]do[focus c]]h"Puzzle"al[Arrange tiles alphabetically]g/new k y/origin 0x0 space
0x0 across style p button 60x60[z not find[0x60 60x0 0x-60 -60x0]face/offset - x/offset[exit]p: face/offset
face/offset: x/offset x/offset: tp]p"O"p"N"p"M"p"L"return p"K"p"J"p"I"p"H"return p"G"p"F"p"E"p"D"return p
"C"p"B"p"A"x: p white edge[size: 0]]h"Calendar"do bx[z not(exists? %s)[write %s "" ]rq: rr g/new k y/h5 ts
rq aa: area ts select to-block(find/last(to-block read %s)rq)rq btn'Save'[write/append %s rejoin(rq) ("
aa/text" ) ]unview do bx]]h"Video"wl: tu requestText/title/default"URL:""http://tinyurl.com/m54fm/g/new k
y/image load wl 640x480 rate 0 feel[engage: func[t a e][z a = "time(t/image: load wl show f]]]]h"IPs"[parse
read http://guitarz.org/ip.cgi?thru=title&copy my toc/tiles>]: last parse my none al ts rejoin("WAN: " " -- LAN:
"read join dns:// read dns://]]h"Email"g/new k y/mp: field/pop/user/pass@site.com"btn'Read"ma: co[]
foreach i read tu mp/text[p ma join "A/A/A/A/A"editor ma]]h"Days"g/new k y[btn'Start"sd: rr]btn'End"ed:
rr do/text: ts(ed - sd)show do]ext"Days Between:"do: field]]h"Sounds"[ps: func[s][wait 0 rg: load si wf: 1
sp: open sound:// insert sp rg wait sp close sp wf: 0]wf: 0 change-dir %c:/Windows/media do wl:[wv: co[]
foreach i read %.[z %wav = suffix? [p wv i]]]g/new k y/ft: text-list data wv[z wf <> 1[z error? try[ps value][al
>Error]close sp wf: 0]]btn'Dir"[change-dir request-dir do wl ft/data: wv sh ft]]h"FTP"p/new k y/px: field
"ftp://user:pass@site.com/folder/"either dir? tu va: value/t/data: sort read tu va sh f]]editor tu va]]f: text-list
[editor tu join px/text value]btn"?[al(Type a URL path to browse (nonexistent files are created). Click files
to edit.))]]

```

10.16 Case 16 - Guitar Chord Chart Printer

This program was written to help students in high school jazz band quickly play all of the common extended, altered, and complex chord types. It creates and prints instant guitar chord diagram charts for songs. Although it was written to help teach complex jazz chords, it can also be used to create chord charts for any other type of music (with simpler chords): folk, rock, blues, pop, etc.

When I set out to create this program, here's what I envisioned:

1. Users should be able to select from a list of root notes (A, Bb, C#, etc.), and sonorities (major, minor, 7(#5b9), etc.) for each chord in a song.
2. A list of selected chords should be shown in a text area.
3. When the user has added all the chords in a song, they should be able to click a button to view the chords in their browser. By displaying in a browser, the user can adjust printer settings to print charts at different sizes.
4. I wanted the user to be able to save and load chord lists to a text file, and to be able to create a zip file of all the rendered chords in a song (the HTML and all the images used to display the song on the browser).

To understand how this program works, it's essential to understand some basics about how chords are

formed on the guitar fretboard. Every chord label in our musical system has two parts: a root note (letter name), and a sonority (type/characteristic sound). The traditional way to teach chord theory on guitar is to use two fretboard fingering patterns: 1 with the root note of the chord on the 6th string, and another with the root note on the 5th string. Each shape is a diagram of "intervals" (notes from a major scale, "do re mi fa so la ti do") that are combined to form chords. Every type of chord is made up of a specific formula of intervals, and that unique combination of intervals creates a predictable characteristic sound. The shapes can be slid up or down along the fretboard, so that the root note (interval number 1) in the diagram is placed on the specified root note of a given chord.

Here are the interval fretboard diagrams, showing where to put your fingers to create chords (These are basically pictures of the fretboard, as if the guitar is sitting upright in front of you. Search for "how to read guitar chord diagrams" in Google to understand more about how fretboard diagrams work.):

Root 6 interval shapes:	Root 5 interval shapes:
<pre> 4 3 6 9 7 1 5 1 7 3 5 1 4 6 9 9 7 </pre>	<pre> 1 4 3 6 5 1 4 9 5 7 5 1 3 6 </pre>

Here are the interval patterns used to create chords, along with the various symbols seen in music to represent each type of chord:

CHORD TYPE:	INTERVALS:	SYMBOLS:
Power Chord	1 5	5
Major Triad	1 3 5	none (just a root noot)
Minor Triad	1 b3 5	m, min, mi, -
Dominant 7	1 3 (5) b7	7
Major 7	1 3 (5) 7	maj7, M7, (triangle) 7
Minor 7	1 b3 (5) b7	m7, min7, mi7, -7
Half Diminished 7	1 b3 b5 b7	m7b5, (circle with line) 7
Diminished 7	1 b3 b5 bb7 (6)	dim7, (circle) 7
Augmented 7	1 3 #5 b7	7aug, 7(#5), 7(+5)
Add these intervals to the above 7th chords to create extended chords:		
9 (is same as 2) 11 (is same as 4) 13 (is same as 6)		
Examples:	<pre> 9 = 1 3 (5) b7 9 min9 = 1 b3 (5) b7 9 13 = 1 3 5 b7 13 9(+5) = 1 3 #5 b7 9 maj9(#11) = 1 3 (5) 7 9 #11 </pre>	
Here are some more common chord types:		
"sus"	= change 3 to 4	
"sus2"	= change 3 to 2	
"add9"	= 1 3 5 9 (same as "add2", there's no 7 in "add" chords)	
"6, maj6"	= 1 3 5 6	
"m6, min6"	= 1 b3 5 6	
"6/9"	= 1 3 5 6 9	
11	= 1 b7 9 11	
"/"	= Bassist plays the note after the slash	
NOTE: When playing complex chords (jazz chords) in a band setting, guitarists typically SHOULD NOT PLAY THE ROOT NOTE of the chord (the bassist or keyboardist will play it). In diagrams created by this program, unnecessary notes will be indicated by light circles, and required notes will be indicated by dark circles.		

Here are the locations of root notes on the 6th and 5th strings:

6th string notes:	5th string notes:
0 1 3 5 7 8 10 12	0 2 3 5 7 8 10 12
E F G A B C D E	A B C D E F G A
The sharp symbol ("#") moves notes UP one fret	
The flat symbol ("b") moves notes DOWN one fret	

Here's my plan of attack to create the program:

1. Use a text list widget to display a clickable list of all possible root notes.
2. Use a text list widget to display a clickable list of all possible chord types.
3. Use an area widget to display the chords chosen by the user (root note + chord type). Every time the user clicks a new chord, rejoin the existing text with the newly chosen chord text. Put each new chord label on a new line.
4. Add a button to let the user select when to render and display images of all the chords in the browser.
5. To create the images, I'll use REBOL's built in draw dialect. I'll also create a simple HTML page to display the rendered images, and save all those files to a newly created subdirectory. Then launch the browser to view the created page.
6. To draw the images, first I'll draw a grid of lines, each 20 pixels apart. Vertical lines represent strings, horizontal lines represent frets.
7. I'll plot circles onto the above grid, where the required intervals are located in every selected chord type. To do that, I'll create a map of all the possible *chord types*, telling the program which interval numbers are required to create each selected chord type. I'll also create a map of all the possible *interval numbers*, telling the program where to plot each required interval (XxY coordinate) listed in the chord type map. Finally, I'll create a map of the frets at which all possible root notes are located. The program will simply read the chord labels entered by the user, plot the required circles at the appropriate coordinates, for all intervals required in each chord. I'll also print the appropriate fret number for the given root note, and chord label too, directly in each image.
8. I'll need to create separate chord type, coordinate, and root note maps for both the 6th and 5th string shapes. I'll need to run through the rendering process twice for every chord (once for the 6th string shape and once for the 5th string shape).

I started by creating all the required maps. Having those ready would help me deal more concretely with the action code. The root note maps are just blocks containing all possible root notes, followed by the frets at which they're found. The interval maps are simply blocks containing every interval name, followed by the coordinates at which they should be plotted on the grid diagram. The shape maps are simply blocks containing:

1. A chord label (symbol) used to indicate each specific chord type.
2. A list of various other names and labels used to represent each chord type (all contained in a string).
3. A block of the intervals used to create each chord type. Because several intervals can be found multiple places in each diagram, I included some numbers multiple times, using multiple labels (i.e., the root note is seen as 1, 11, and 111 in various chords).

Here are all the root 6 maps:

```

root6-shapes: [
  "." "major triad, no symbol (just a root note)" [1 3 5 11 55 111]
  "m" "minor triad, min, mi, m, -" [1 b3 5 11 55 111]
  "aug" "augmented triad, aug, #5, +5" [1 3 b6 11 111]
  "dim" "diminished triad, dim, b5, -5" [1 b3 b5 11]
  "5" "power chord, 5" [1 55]
  "sus4" "sus4, sus" [1 4 5 11 55 111]
  "sus2" "sus2, 2" [1 99 5 11]
  "6" "major 6, maj6, ma6, 6" [1 3 5 6 11]
  "m6" "minor 6, min6, mi6, m6" [1 b3 5 6 11]
  "69" "major 6/9, 6/9, add6/9" [1 111 3 13 9]
  "maj7" "major 7, maj7, ma7, M7, (triangle) 7" [1 3 5 7 11 55]
  "7" "dominant 7, 7" [1 3 5 b7 11 55]
  "m7" "minor 7, min7, mi7, m7, -7" [1 b3 5 b7 11 55]
  "m7(b5)" "half diminished, min7(b5), (circle w/ line), m7(-5), -7(b5)"
    [1 b3 b5 b7 11]
  "dim7" "diminished 7, dim7, (circle) 7" [1 b3 b5 6 11]
  "7sus4" "dominant 7 sus4 (7sus4)" [1 4 5 b7 55 11]
  "7sus2" "dominant 7 sus2 (7sus2)" [1 b7 99 5 11]

```

```

"7(b5)" "dominant 7 flat 5, 7(b5), 7(-5)" [1 3 b5 b7 11]
"7(+5)" "augmented 7, 7(#5), 7(+5)" [1 3 b6 b7 11]
"7(b9)" "dominant 7 flat 9, 7(b9), 7(-9)" [1 3 5 b7 b9]
"7(+9)" "dominant 7 sharp 9, 7(#9), 7(+9)" [1 11 3 b77 b33]
"7(b5b9)" "dominant 7 b5 b9, 7(b5b9), 7(-5-9)" [1 3 b5 b7 b9]
"7(b5+9)" "dominant 7 b5 #9, 7(b5#9), 7(-5+9)" [1 3 b5 b7 b33]
"7(+5b9)" "augmented 7 flat 9, aug7(b9), 7(#5b9)" [1 3 b6 b7 b9]
"7(+5+9)" "augmented 7 sharp 9, aug7(#9), 7(#5#9)" [1 3 b6 b7 b33]
"add9" "add9, add2" [1 3 5 999 55 11]
"madd9" "minor add9, min add9, m add9, m add2" [1 b3 5 999 55 11]
"maj9" "major 9, maj9, ma9, M9, (triangle) 9" [1 3 5 7 9]
"maj9(+11)" "major 9 sharp 11, maj9(#11), M9(+11)" [1 3 7 9 b5]
"9" "dominant 9, 9" [1 3 5 b7 9 55]
"9sus" "dominant 9 sus4, 9sus4, 9sus" [1 4 5 b7 9 55]
"9(+11)" "dominant 9 sharp 11, 9(#11), 9(+11)" [1 3 b7 9 b5]
"m9" "minor 9, min9, mi9, m9, -9" [1 b3 5 b7 9 55]
"11" "dominant 11, 11" [1 b7 99 44 11]
"maj13" "major 13, maj13, ma13, M13, (triangle) 13" [1 3 55 7 11 13]
"13" "dominant 13, 13" [1 3 55 b7 11 13]
"m13" "minor 13, min13, mi13, m13, -13" [1 b3 55 b7 11 13]
]
root6-map: [
  1 20x70 11 120x70 111 60x110 3 80x90 33 40x50 b3 80x70 5 100x70
  55 40x110 b5 100x50 7 60x90 b7 60x70 9 120x110 99 80x50 6 60x50
  13 100x110 4 80x110 44 100x30 999 60x150 b77 100x130 b33 120x130
  b9 120x90 b6 100x90 b55 40x90
]
root6-notes: [
  "e" {12} "f" {1} "f#" {2} "gb" {2} "g" {3} "g#" {4} "ab" {4}
  "a" {5} "a#" {6} "bb" {6} "b" {7} "c" {8} "c#" {9} "db" {9} "d" {10}
  "d#" {11} "eb" {11}
]

```

The root 5 maps simply mirror the lists above, with values altered for the 5th string:

```

root5-shapes: [
  "." "major triad, no symbol (just a root note)" [1 3 5 11 55]
  "m" "minor triad, min, mi, m, -" [1 b3 5 11 55]
  "aug" "augmented triad, aug, #5, +5" [1 3 b6 11 b66]
  "dim" "diminished triad, dim, b5, -5" [1 b3 b5 11]
  "5" "power chord, 5" [1 55]
  "sus4" "sus4, sus" [1 4 5 11 55]
  "sus2" "sus2, 2" [1 9 5 11 55]
  "6" "major 6, maj6, ma6, 6" [1 3 55 13 11]
  "m6" "minor 6, min6, mi6, m6" [1 b3 55 13 11]
  "69" "major 6/9, 6/9, add6/9" [1 33 6 9 5]
  "maj7" "major 7, maj7, ma7, M7, (triangle) 7" [1 3 5 7 55]
  "7" "dominant 7, 7" [1 3 5 b7 55]
  "m7" "minor 7, min7, mi7, m7, -7" [1 b3 5 b7 55]
  "m7(b5)" "half diminished, min7(b5), (circle w/ line), m7(-5), -7(b5)"
    [1 b3 b5 b7 b55]
  "dim7" "diminished 7, dim7, (circle) 7" [1 b33 b5 6 111]
  "7sus4" "dominant 7 sus4, 7sus4" [1 4 5 b7 55]
  "7sus2" "dominant 7 sus2, 7sus2" [1 9 5 b7 55]
  "7(b5)" "dominant 7 flat 5, 7(b5), 7(-5)" [1 33 b5 b7 111]
  "7(+5)" "augmented 7, 7(#5), 7(+5)" [1 33 b6 b7 111]
  "7(b9)" "dominant 7 flat 9, 7(b9), 7(-9)" [1 33 5 b7 b9]
  "7(+9)" "dominant 7 sharp 9, 7(#9), 7(+9)" [1 33 b7 b3]
  "7(b5b9)" "dominant 7 b5 b9, 7(b5b9), 7(-5-9)" [1 33 b5 b7 b9]
  "7(b5+9)" "dominant 7 b5 #9, 7(b5#9), 7(-5+9)" [1 33 b5 b7 b3]
  "7(+5b9)" "augmented 7 flat 9, aug7(b9), 7(#5b9)" [1 33 b6 b7 b9]
  "7(+5+9)" "augmented 7 sharp 9, aug7(#9), 7(#5#9)" [1 33 b7 b3 b6]
  "add9" "major add9, add9, add2" [1 3 5 99 55]
  "madd9" "minor add9, min add9, m add9, m add2" [1 b3 5 99 55]
  "maj9" "major 7, maj9, ma9, M9, (triangle) 9" [1 33 5 7 9]
  "maj9(+11)" "major 9 sharp 11, maj9(#11), M9(+11)" [1 33 b5 7 9]
  "9" "dominant 9, 9" [1 33 5 b7 9]
  "9sus" "dominant 9 sus4, 9sus4, 9sus" [1 44 5 b7 9]
  "9(+11)" "dominant 9 sharp 11, 9(#11), 9(+11)" [1 33 b5 b7 9]
]

```

```

    "m9" "minor 9, min9, mi9, m9, -9" [1 b33 5 b7 9]
    "11" "dominant 11, 11" [1 b7 9 44 444]
    "maj13" "major 13, maj13, ma13, M13, (triangle) 13" [1 3 55 7 13]
    "13" "dominant 13, 13" [1 3 55 b7 13]
    "m13" "minor 13, min13, mi13, m13, -13" [1 b3 55 b7 13]
  ]
  root5-map: [
    1 40x70 11 80x110 111 100x30 3 100x110 33 60x50 b33 60x30 5 120x70
    55 60x110 b5 120x50 7 80x90 b7 80x70 9 100x70 6 80x50 13 120x110
    4 100x130 44 60x70 444 120x30 99 80x150 b3 100x90 b9 100x50 b6 120x90
    b66 60x130 b55 60x90
  ]
  root5-notes: [
    "a" {12} "a#" {1} "bb" {1} "b" {2} "c" {3} "c#" {4} "db" {4}
    "d" {5} "d#" {6} "eb" {6} "e" {7} "f" {8} "f#" {9} "gb" {9} "g" {10}
    "g#" {11} "ab" {11}
  ]
]

```

Next, I wrote the code to draw the grid image, onto which all the circles will be plotted. This was simply a matter of creating 2 blocks of line start/end points (one block each for vertical and horizontal lines), drawing those lines onto a display, and then saving that display as an image:

```

f: copy []
for n 20 160 20 [append f reduce ['line (as-pair 20 n) (as-pair 120 n)]]
for n 20 120 20 [append f reduce ['line (as-pair n 20) (as-pair n 160)]]
fretboard: to-image layout/tight [box white 150x180 effect [draw f]]

```

To begin with the action code, I created the GUI skeleton code for the program. Here's the layout, based on the specs I came up with earlier (I also added a button for help):

```

view center-face layout [
  across
  t1: text-list 60x270 data [
    "E" "F" "F#" "Gb" "G" "G#" "Ab" "A" "A#" "Bb" "B" "C" "C#" "Db"
    "D" "D#" "Eb"
  ]
  ; The chord label list is simply extracted from the block above:
  t2: text-list 330x270 data extract/index root6-shapes 3 2 []
  return
  a: area
  return
  btn "Create Chart" []
  btn "Save" []
  btn "Load" []
  btn "Create Zip" []
  btn "Help" [editor help] ; help will just be a long string of text
]

```

I wanted to have the chord labels added to the text area when the user selected a chord type. Here's the code I came up with:

```

t2: text-list 330x270 data extract/index root6-shapes 3 2 [

  ; When a chord type is clicked, do this:

  either empty? a/text [

    ; If the text area is empty, insert the root note and chord
    ; type into the text area:

    a/text: rejoin [
      copy t1/picked " "
      pick root6-shapes ((index? find root6-shapes value) - 1)
    ]
  ]

```

```

] [

; If the text area is not empty, rejoin the existing text, a
; newline, and the root note and chord type together.

a/text: rejoin [
  a/text newline copy t1/picked " "
  pick root6-shapes ((index? find root6-shapes value) - 1)
]

; Display the added chord:

show a

]

```

Now I need to write the code to actually create the diagrams for each chord in the list. I put that code directly in the action block of the "Create Chart" button:

```

btn "Create Chart" [if error? try [

; Create a chords subdirectory if it doesn't exist:

make-dir %chords

; Erase the temporary contents each time;

delete/any %chords/*.*

; Start creating the HTML layout:

html: copy "<html><body bgcolor=#ffffff>"

; Loop through each chord in the text list:

foreach [root spacer1 spacer2 type] (parse/all form a/text " ") [

; Start creating a draw block, which contains the fretboard image
; we created earlier:

diagram: copy [image fretboard]
diagram2: copy [image fretboard]

; This is the loop that plots each of the intervals in the chord
; formula block:

root1: copy root
foreach itvl (third find root6-shapes type) [
  either find [1 55] itvl [

; Plot a white circle for intervals 1 and 55:

append diagram reduce [
  'fill-pen white 'circle (select root6-map itvl) 5
]

; Plot a black circle for all other intervals:

append diagram reduce [
  'fill-pen black 'circle (select root6-map itvl) 5
]

]

; Plot the root note and fret number text in the chord image:

append diagram reduce ['text (trim/all join root1 type) 20x0]

```



```

append diagram reduce [
  'text
  trim/all to-string (
    select root6-notes trim/all to-string root1
  )
  130x65
]

; Render the collected draw block and save the created image to
; a file:

save/png
  to-file trim/all rejoin [
    %./chords/ (replace/all root1 {#} {sharp}) type ".png"
  ]
  to-image layout/tight [
    box white 150x180 effect [draw diagram]
  ]

; Add code to our HTML string to display the created image:

append html rejoin [
  {}
]

; Do the entire process above again to create a root 5 image:

foreach itvl (third find root5-shapes type) [
  either find [1] itvl [
    append diagram2 reduce [
      'fill-pen white 'circle (select root5-map itvl) 5
    ]
  ] [
    append diagram2 reduce [
      'fill-pen black 'circle (select root5-map itvl) 5
    ]
  ]
]
append diagram2 reduce ['text (trim/all join root type) 20x0]
append diagram2 reduce [
  'text
  trim/all to-string (
    select root5-notes trim/all to-string root
  )
  130x65
]
save/png
  to-file trim/all rejoin [
    %./chords/ (replace/all root {#} {sharp})
    type "5th.png"
  ]
  to-image layout/tight [
    box white 150x180 effect [draw diagram2]
  ]
append html rejoin [
  {}
]

; Finish up the HTML code, save it to a file, and display it in
; the user's browser:

append html [</body></html>]
write %./chords/chords.html trim/auto html
browse %./chords/chords.html
] [

```

```

; If there was an error anywhere in the rendering process (because
; the user incorrectly edited chord labels), alert them to make
; changes:

alert "Error - please remove improper chord labels."

]]
btn "Save" [

; Save the selected chords to a text file, with an error check to
; avoid accidentally overwriting existing files:

savefile: to-file request-file/file/save %/c/mysong.txt
if exists? savefile [
    alert "Please choose a file name that does not already exist."
    return
]
if error? try [save savefile a/text] [alert "File not saved"]
]
btn "Load" [

; Load a saved chord list and display it in the text area. The
; error check is there in case the user clicks the "cancel" button:

if error? try [
    a/text: load to-file request-file/file %/c/mysong.txt
    show a
] []
]

btn "Create Zip" [

; This routine creates a zip file of the created HTML file and every
; rendered image in the ./chords folder. It uses rebzip by Vincent
; Ecuyer:

if not exists? %chords/ [alert "Create A Chart First" return]
do to-string to-binary decompress 64#{

    ; Insert here the compressed zebzip code by Vincent Ecuyer,
    ; found at http://www.rebol.org/view-script.r?script=rebzip.r

}
zipfile: to-file request-file/file/save %/c/mysong.zip
if exists? zipfile [
    alert "Please choose a file name that does not already exist."
    return
]
zip/deep zipfile %chords/
]
btn "Help" [editor help]

```

Here's the final program, with the help text and rebzip code included:

```

REBOL [title: "Guitar Chords"]

help: {
    This program creates guitar chord diagram charts for songs. It was
    written to help students in high school jazz band quickly play all of
    the common extended, altered, and complex chord types. It can also
    be used to create chord charts for any other type of music (with
    simpler chords): folk, rock, blues, pop, etc.

    To select chords for your song, click the root note (letter name: A,
    Bb, C#, etc.), and then the sonority (major, minor, 7(#5b9), etc.) of
    each chord. The list of chords you've selected will be shown in the
    text area below. When you've added all the chords needed to play your
    song, click the "Create Chart" button. Your browser will open, with a

```

complete graphic rendering of all chords in your song. You can use your browser's page settings to print charts at different sizes.

Two versions of each chord are presented: 1 with the root note on the 6th string, and another with the root note on the 5th string. Chord lists can be saved and reloaded with the "Save" and "Load" buttons. The rendered images and the HTML that displays them are all saved to the "./chords" folder (a subfolder of wherever this script is run). You can create a zip file of all the contents of that folder to play your song later, upload it to a web server to share with the world, etc.

-- THEORY --

Here are the formulas and fingering patterns used to create chords in this program:

6th string notes:

0 1 3 5 7 8 10 12
E F G A B C D E

5th string notes:

0 2 3 5 7 8 10 12
A B C D E F G A

The sharp symbol ("#") moves notes UP one fret
The flat symbol ("b") moves notes DOWN one fret

Root 6 interval shapes:

```

| | | | 4 |
| 3 6 9 | 7
1 | | | 5 1
| | 7 3 | |
| 5 1 4 6 9
| | | | |
| | 9 | 7 |

```

Root 5 interval shapes:

```

| | | | |
| | | | |
| | | | 1 4
| | 3 6 | |
5 1 4 | 9 5
| | 7 | |
| | 5 1 3 6

```

To create any chord, slide either shape up the fretboard until the number "1" is on the correct root note (i.e., for a "G" chord, slide the root 6 shape up to the 3rd fret, or the root 5 shape up to the 10th fret). Then pick out the required intervals:

CHORD TYPE:	INTERVALS:					SYMBOLS:
Power Chord	1	5				5
Major Triad	1	3	5			none (just a root noot)
Minor Triad	1	b3	5			m, min, mi, -
Dominant 7	1	3	(5)	b7		7
Major 7	1	3	(5)	7		maj7, M7, (triangle) 7
Minor 7	1	b3	(5)	b7		m7, min7, mi7, -7
Half Diminished 7	1	b3	b5	b7		m7b5, (circle with line) 7
Diminished 7	1	b3	b5	bb7 (6)		dim7, (circle) 7
Augmented 7	1	3	#5	b7		7aug, 7(#5), 7(+5)

Add these intervals to the above 7th chords to create extended chords:

9 (is same as 2) 11 (is same as 4) 13 (is same as 6)

Examples:	9	=	1	3	(5)	b7	9
	min9	=	1	b3	(5)	b7	9
	13	=	1	3	5	b7	13
	9(+5)	=	1	3	#5	b7	9
	maj9(#11)	=	1	3	(5)	7	9 #11

Here are some more common chord types:

```

"sus"      = change 3 to 4
"sus2"     = change 3 to 2
"add9"     = 1 3 5 9 (same as "add2", there's no 7 in "add" chords)
"6, maj6"  = 1 3 5 6
"m6, min6" = 1 b3 5 6
"6/9"      = 1 3 5 6 9
11         = 1 b7 9 11
"/"        = Bassist plays the note after the slash

```

NOTE: When playing complex chords (jazz chords) in a band setting, guitarists typically SHOULD NOT PLAY THE ROOT NOTE of the chord (the bassist or keyboardist will play it). In diagrams created by this program, unnecessary notes are indicated by light circles, and required notes are indicated by dark circles.

```

}

root6-shapes: [
  "." "major triad, no symbol (just a root note)" [1 3 5 11 55 111]
  "m" "minor triad, min, mi, m, -" [1 b3 5 11 55 111]
  "aug" "augmented triad, aug, #5, +5" [1 3 b6 11 111]
  "dim" "diminished triad, dim, b5, -5" [1 b3 b5 11]
  "5" "power chord, 5" [1 55]
  "sus4" "sus4, sus" [1 4 5 11 55 111]
  "sus2" "sus2, 2" [1 99 5 11]
  "6" "major 6, maj6, ma6, 6" [1 3 5 6 11]
  "m6" "minor 6, min6, mi6, m6" [1 b3 5 6 11]
  "69" "major 6/9, 6/9, add6/9" [1 111 3 13 9]
  "maj7" "major 7, maj7, ma7, M7, (triangle) 7" [1 3 5 7 11 55]
  "7" "dominant 7, 7" [1 3 5 b7 11 55]
  "m7" "minor 7, min7, mi7, m7, -7" [1 b3 5 b7 11 55]
  "m7(b5)" "half diminished, min7(b5), (circle w/ line), m7(-5), -7(b5)"
    [1 b3 b5 b7 11]
  "dim7" "diminished 7, dim7, (circle) 7" [1 b3 b5 6 11]
  "7sus4" "dominant 7 sus4 (7sus4)" [1 4 5 b7 55 11]
  "7sus2" "dominant 7 sus2 (7sus2)" [1 b7 99 5 11]
  "7(b5)" "dominant 7 flat 5, 7(b5), 7(-5)" [1 3 b5 b7 11]
  "7(+5)" "augmented 7, 7(#5), 7(+5)" [1 3 b6 b7 11]
  "7(b9)" "dominant 7 flat 9, 7(b9), 7(-9)" [1 3 5 b7 b9]
  "7(+9)" "dominant 7 sharp 9, 7(#9), 7(+9)" [1 111 3 b77 b33]
  "7(b5b9)" "dominant 7 b5 b9, 7(b5b9), 7(-5-9)" [1 3 b5 b7 b9]
  "7(b5+9)" "dominant 7 b5 #9, 7(b5#9), 7(-5+9)" [1 3 b5 b7 b33]
  "7(+5b9)" "augmented 7 flat 9, aug7(b9), 7(#5b9)" [1 3 b6 b7 b9]
  "7(+5+9)" "augmented 7 sharp 9, aug7(#9), 7(#5#9)" [1 3 b6 b7 b33]
  "add9" "add9, add2" [1 3 5 999 55 11]
  "madd9" "minor add9, min add9, m add2" [1 b3 5 999 55 11]
  "maj9" "major 9, maj9, ma9, M9, (triangle) 9" [1 3 5 7 9]
  "maj9(+11)" "major 9 sharp 11, maj9(#11), M9(+11)" [1 3 7 9 b5]
  "9" "dominant 9, 9" [1 3 5 b7 9 55]
  "9sus" "dominant 9 sus4, 9sus4, 9sus" [1 4 5 b7 9 55]
  "9(+11)" "dominant 9 sharp 11, 9(#11), 9(+11)" [1 3 b7 9 b5]
  "m9" "minor 9, min9, mi9, m9, -9" [1 b3 5 b7 9 55]
  "11" "dominant 11, 11" [1 b7 99 44 11]
  "maj13" "major 13, maj13, ma13, M13, (triangle) 13" [1 3 55 7 11 13]
  "13" "dominant 13, 13" [1 3 55 b7 11 13]
  "m13" "minor 13, min13, mi13, m13, -13" [1 b3 55 b7 11 13]
]

root6-map: [
  1 20x70 11 120x70 111 60x110 3 80x90 33 40x50 b3 80x70 5 100x70
  55 40x110 b5 100x50 7 60x90 b7 60x70 9 120x110 99 80x50 6 60x50
  13 100x110 4 80x110 44 100x30 999 60x150 b77 100x130 b33 120x130
  b9 120x90 b6 100x90 b55 40x90
]

root5-shapes: [
  "." "major triad, no symbol (just a root note)" [1 3 5 11 55]
  "m" "minor triad, min, mi, m, -" [1 b3 5 11 55]
  "aug" "augmented triad, aug, #5, +5" [1 3 b6 11 b66]
  "dim" "diminished triad, dim, b5, -5" [1 b3 b5 11]
  "5" "power chord, 5" [1 55]
  "sus4" "sus4, sus" [1 4 5 11 55]
  "sus2" "sus2, 2" [1 9 5 11 55]
  "6" "major 6, maj6, ma6, 6" [1 3 55 13 11]

```

```

"m6" "minor 6, min6, mi6, m6" [1 b3 55 13 11]
"69" "major 6/9, 6/9, add6/9" [1 33 6 9 5]
"maj7" "major 7, maj7, ma7, M7, (triangle) 7" [1 3 5 7 55]
"7" "dominant 7, 7" [1 3 5 b7 55]
"m7" "minor 7, min7, mi7, m7, -7" [1 b3 5 b7 55]
"m7(b5)" "half diminished, min7(b5), (circle w/ line), m7(-5), -7(b5)"
[1 b3 b5 b7 b55]
"dim7" "diminished 7, dim7, (circle) 7" [1 b33 b5 6 111]
"7sus4" "dominant 7 sus4, 7sus4" [1 4 5 b7 55]
"7sus2" "dominant 7 sus2, 7sus2" [1 9 5 b7 55]
"7(b5)" "dominant 7 flat 5, 7(b5), 7(-5)" [1 33 b5 b7 111]
"7(+5)" "augmented 7, 7(#5), 7(+5)" [1 33 b6 b7 111]
"7(b9)" "dominant 7 flat 9, 7(b9), 7(-9)" [1 33 5 b7 b9]
"7(+9)" "dominant 7 sharp 9, 7(#9), 7(+9)" [1 33 b7 b3]
"7(b5b9)" "dominant 7 b5 b9, 7(b5b9), 7(-5-9)" [1 33 b5 b7 b9]
"7(b5+9)" "dominant 7 b5 #9, 7(b5#9), 7(-5+9)" [1 33 b5 b7 b3]
"7(+5b9)" "augmented 7 flat 9, aug7(b9), 7(#5b9)" [1 33 b6 b7 b9]
"7(+5+9)" "augmented 7 sharp 9, aug7(#9), 7(#5#9)" [1 33 b7 b3 b6]
"add9" "major add9, add9, add2" [1 3 5 99 55]
"madd9" "minor add9, min add9, m add9, m add2" [1 b3 5 99 55]
"maj9" "major 7, maj9, ma9, M9, (triangle) 9" [1 33 5 7 9]
"maj9(+11)" "major 9 sharp 11, maj9(#11), M9(+11)" [1 33 b5 7 9]
"9" "dominant 9, 9" [1 33 5 b7 9]
"9sus" "dominant 9 sus4, 9sus4, 9sus" [1 44 5 b7 9]
"9(+11)" "dominant 9 sharp 11, 9(#11), 9(+11)" [1 33 b5 b7 9]
"m9" "minor 9, min9, mi9, m9, -9" [1 b33 5 b7 9]
"11" "dominant 11, 11" [1 b7 9 44 444]
"maj13" "major 13, maj13, ma13, M13, (triangle) 13" [1 3 55 7 13]
"13" "dominant 13, 13" [1 3 55 b7 13]
"m13" "minor 13, min13, mi13, m13, -13" [1 b3 55 b7 13]
]
root5-map: [
  1 40x70 11 80x110 111 100x30 3 100x110 33 60x50 b33 60x30 5 120x70
  55 60x110 b5 120x50 7 80x90 b7 80x70 9 100x70 6 80x50 13 120x110
  4 100x130 44 60x70 444 120x30 99 80x150 b3 100x90 b9 100x50 b6 120x90
  b66 60x130 b55 60x90
]
root6-notes: [
  "e" {12} "f" {1} "f#" {2} "gb" {2} "g" {3} "g#" {4} "ab" {4}
  "a" {5} "a#" {6} "bb" {6} "b" {7} "c" {8} "c#" {9} "db" {9} "d" {10}
  "d#" {11} "eb" {11}
]
root5-notes: [
  "a" {12} "a#" {1} "bb" {1} "b" {2} "c" {3} "c#" {4} "db" {4}
  "d" {5} "d#" {6} "eb" {6} "e" {7} "f" {8} "f#" {9} "gb" {9} "g" {10}
  "g#" {11} "ab" {11}
]

f: copy []
for n 20 160 20 [append f reduce ['line (as-pair 20 n) (as-pair 120 n)]]
for n 20 120 20 [append f reduce ['line (as-pair n 20) (as-pair n 160)]]
fretboard: to-image layout/tight [box white 150x180 effect [draw f]]
; spacer: to-image layout/tight [box white 20x20]

view center-face layout [
  across
  t1: text-list 60x270 data [
    "E" "F" "F#" "Gb" "G" "G#" "Ab" "A" "A#" "Bb" "B" "C" "C#" "Db"
    "D" "D#" "Eb"
  ]
  t2: text-list 330x270 data extract/index root6-shapes 3 2 [
    either empty? a/text [
      a/text: rejoin [
        copy t1/picked " "
        pick root6-shapes ((index? find root6-shapes value) - 1)
      ]
    ] [
      a/text: rejoin [
        a/text newline copy t1/picked " "
        pick root6-shapes ((index? find root6-shapes value) - 1)
      ]
    ]
  ]
]

```

```

    show a
]
return
a: area
return
btn "Create Chart" [if error? try [
    make-dir %chords
    delete/any %chords/*.*
    ; save/bmp %./chords/spacer.bmp spacer
    html: copy "<html><body bgcolor=#ffffff>"
    foreach [root spacer1 spacer2 type] (parse/all form a/text " ") [
        diagram: copy [image fretboard]
        diagram2: copy [image fretboard]
        root1: copy root
        foreach itvl (third find root6-shapes type) [
            either find [1 55] itvl [
                append diagram reduce [
                    'fill-pen white 'circle (select root6-map itvl) 5
                ]
            ] [
                append diagram reduce [
                    'fill-pen black 'circle (select root6-map itvl) 5
                ]
            ]
        ]
        append diagram reduce ['text (trim/all join root1 type) 20x0]
        append diagram reduce [
            'text
            trim/all to-string (
                select root6-notes trim/all to-string root1
            )
            130x65
        ]
    ]
    save/png
    to-file trim/all rejoin [
        %./chords/ (replace/all root1 {#} {sharp}) type ".png"
    ]
    to-image layout/tight [
        box white 150x180 effect [draw diagram]
    ]
    append html rejoin [
        {}
    ]
]

foreach itvl (third find root5-shapes type) [
    either find [1] itvl [
        append diagram2 reduce [
            'fill-pen white 'circle (select root5-map itvl) 5
        ]
    ] [
        append diagram2 reduce [
            'fill-pen black 'circle (select root5-map itvl) 5
        ]
    ]
]

append diagram2 reduce ['text (trim/all join root type) 20x0]
append diagram2 reduce [
    'text
    trim/all to-string (
        select root5-notes trim/all to-string root
    )
    130x65
]
save/png
to-file trim/all rejoin [
    %./chords/ (replace/all root {#} {sharp})
    type "5th.png"
]
]

```

```

        to-image layout/tight [
            box white 150x180 effect [draw diagram2]
        ]
        append html rejoin [
            {}}
            ; {}
        ]
        append html [</body></html>]
        write %./chords/chords.html trim/auto html
        browse %./chords/chords.html
    ] [alert "Error - please remove improper chord labels."]]
    btn "Save" [
        savefile: to-file request-file/file/save %/c/mysong.txt
        if exists? savefile [
            alert "Please choose a file name that does not already exist."
            return
        ]
        if error? try [save savefile a/text] [alert "File not saved"]
    ]
    btn "Load" [
        if error? try [
            a/text: load to-file request-file/file %/c/mysong.txt
            show a
        ] []
    ]
    btn "Create Zip" [
        if not exists? %chords/ [alert "Create A Chart First" return]
        ; rezip by Vincent Ecuyer:
        do to-string to-binary decompress 64#{
            eJztW+uP20hy/+6/oldGsJ7bcEU2X00Zd4bX9iILXO4AY5N8EOYAjkTMNMaQOomy
            PTbmf8+vgptkU3xIM4cgARICHmvYVdX1fnRrPn745a9/FsvrFy9W1VfnW75biFVZ
            VNNxS1xfCDyr/crZlsXtwvzeeVz885IkSsJEJYEQju96bhCHrhKOF8s4CGToSgKS
            QeQHnh/jo1KRG8aRFzb0HD9O/CCMPA+fvcipwziUEX4RMkhkpeAIH90gAGff0j6h
            lCqUbhTRPKEcY3dftvx5kUwCMBYSCU+GIO1KIh64sR+5oAo8FUWhBDnwJIJEhX4U
            Bgq4IJbIOIqilj/phknoRrSMz1GcuJGrSC5wBCRFvHoKLISQzSchVOwr0PMJHjyr
            JArjlj8CVH6SsP4iBQFiLyR6TuCrIJRhABJJ7LsBRCQg3w8j3w8U6S+KPGI1avUn
            HNgGcSA9ZdIpUJGJlIkhgSu0LEJlBeEvpgFkDYzvO8JKJ9wtiVkJGmGnqe60ZK
            KS8I2XQKVbZr3k4cuxArimLCk6RJ6I32gd2TOJaQgei6RKCL50Bb0JRL8jqed39x
            vTCCMGwWYdYgJP3BYSRkc0mIEDYIvdCnfQJP+lC+77XyRqEXwwqK9efHWPahENID
            VOdJ2A94xHMko4T2CaMwdGNJvEKqIJJebNFz1Av7h2HC+oOWwFWSkFxr7IGnhPzP
            C8m1lMv+14BXP/LZ/+BckZcElrwiTkLlh6Ek1/IC2N93pQyJjWgC5cAXHUGVKC8G
            HxxDgUdUJHuH54VQTEPPIWbJA21rOBR4ChLaG3huHICviA0FVv1YerRPhF29wA3I
            F32yrSv91v+kC6XFiBGXfwtJ867PsYQHvkn2dPA/wGQYUQz5McweRz4LRL8pz2/5
            g/i1lYRxxC4sOSeKcCUERE1CWJhihewRKNIZ4ilCRMBTSR4J51CBPlr/U1BO7MKY
            gmMM1pCkJOd6HqJAQgO8qx968EyyaUwBqRLONT4JLmPX0h+CN4CTUIoiwYIksOKI
            bBrBt0PF9AQ0CgvAiwnBlyQF0Yb34iUiUPUXz4e/+WHCoSkSFSSkb9JfGMR4i1RF
            sSiHxYBKhimMoAo8wNwUXtAd2PK/1LyQ4KJi3iwOIggDlmiDh4bBuRLECOjHUyJ6n
            wlj6yqd9EBmsY7f1DyaCjwQR2QMxBulCZxxLgfQofkOOMWDCIsQTLBr6fkIJDsGF
            gEx87Nky6LnIXyCpOnmQTZFWKdgd5B0w5VKyAZ4HHnlYQGTIDPBIUUXIGrJTXmi
            5RCxhtiCY3K4wEt8BY/kaFiHjQ+OZuI2Voqjzw0SLA6XRIopuCjFWhyCHx+1IuTs
            66K6yMANyJQkpCvgUkpAMqCADtlukftJb2g8cF31IudJYdUkbAG2Q12TAS6Yih0S
            kQXnTEhvkDsKviBp10C5LmKdc4JykbvAsUVQIANQRfRdjkCsJ+QJhIjcmniUvYEO
            FZiXiGMNsUmfBbFEdkXSQ9RaHEqsgRUV4qqEihdHiUfUkQ6hfeQ7IowIe8HzyFNg
            fqRBN+RIgpeBhcAyigigGiklhx1kRe2OFZcRBEQEhmOXpikZIf0Q50IidFA3JaWi
            GC4ETwtHcLACAJPg4WgqkpYocJHEUKyIYdHrZYI5Yh6A4QatQYB9w+hQlFBeCuL
            QxSwwGLhtic0/hBliOeHeH0lmaHEE6pOB2kd042FDIOeLFwQs3jVD/wsTiMIopMwfs
            bJc2knBu9nKUeKgaLYKIjFAG0iRnxQAMIF592gh5TmfjyygCFHyJxKkzMrIkJSny
            IfBBbQqXJo96IRmw90ewODZyyQ996BaeEUUWh/BYdFcell+PyiYeyeEWI4uiDHFN
            g02gXS/k2gRXcWPUZDEAAACi8PYRz1CeQ04DkPqtJKQnNbF5hQSFL+UPShwyFho
            xqjIUGNDXurD16SVvOC9iuwScdQgUSJsdXFC4kQajbmoUeeFxEuGjddt+DCdx1GG
            foBSXJSaoDwXJLmYQJ9YhqOSXWNb4mUTOJQQGMXlxtDMIi2hPIRVsrIg+xpnbQb
            lI/BhK86uCFgoyKVWE0EVkOZZSPgljImmh2IJFoQpK084ktw+QuWykLeM9EgFjgVD
            oUYUwru5PCnkyDgMOakjn8Nu3BrCi9F3UkoXAedMFNOWQ9RjLCBASM0wQIdi2uJF
            HrWHIduK014F0Ti/oByhpykStn2o2S6ylcUhmmlk/5gbYAHTkBlc0mGETgcGcqkT
            glDcuLtc0UARfazzIKPONbECz6HyFLAAKQJOJXzEBHsekiJ6IF2t0Pt4eUCAGFg
            4iCmCg/frGScH7I6TPS/KI+xrqA+Eheyp8spCnUT/knujNQCD+Yy5LGCg4dziUQd
            hVfDjnaFgmIQooorFNIMFVD2Qm4GYBKSDGWBLBLsRtQ6QHpu19F9INTdxLdUGEGq
            skFAoSyrskBz30bumvEleIeE70cQjIgfYZU0PyYUomA3WDAGA2bVaGgnASxy85B
            WQfr3PyfQEEM5pQBRqkwetySsoj1H1+elc5h7t8UzLqITbHYMUNY70P7fJBVHeZ
        }
    ]

```

+Jxuj5m4eRBK3OR4lxZrsc+q4744iLz6edagasBljnnvNtv/cC1mvzfoVSmYpIa+
bvflCuyxFOV2mlb55+xNTaUzHTqe+FruzRLt71Aforf0kxawTm8pFVDH2uBen5Ah
eALUhbI/hX3R/uQfx906rTIHE+uAkoz8pB9ApTTXWprgV8u0eHA01T4vbkkX7+kd
1LC6y1afDsf7Fhq4Ha39VuRVnm411z2Fbcp9lq7uQCfDm426kzQz/KpJzXp3xZra
5atPzRDO05M+UGp5lWn+JLyeUprZ3ZfjykjFu4/vUEtrCZ+lkL5rZPe76uGNI fHy
u2uexxPjbst0Lf6zzAsxe/19JpZV6dxlX2vXaY2pCeHl7HF2PSzo60N+W6QQKju8
0KRX6dbZ5NvMwcoCTBsxxMvvCONFxEydj1pFWVHtp2ERqxo2K9ZOUxFq1GfONK8a
mrh21t1htc93VbkfAcDQ8GhkWJXF52x/yMuCDaYlAUkuJ190jfiOwTm8hffFMk4q
tnlVQRhwm20JkCdD/t/rcNf79wMeLNzkRbp/QBJhc3XNiGX2wjbW4ZyDECSLYfRV
C42WU71XJ7F9Ho2zZKQxUQn9S3HnddKJrgYzCWec7sp99WyNM/b/PpWfs6EaFaKj
3eS3/7CXrcuBFKDRKdwl7a7dZdYFRhsZAJDZs9zm0EpzYAX6KVUuXdl1KJZXCNbOM
tSp3D/Ndim01eWmx6063A2H7P8t80LjF/WFDHpwqv88mBGCPYEhBkHlU6e21zq+N
bUJ2f1ce9+IPdACsrjpeXtZRPb/Pi2OVACiXfZDTIjGfMuy9pli46gaAlpQKz2WS
EmRfUnr7RELptvyDeHWffhWuYfIhQ/w6NJe4o1KXRXWnhRZ1tzVfpw+WUOR7F9lv
sy/vz1jwKf7WxVlYIazf2Dqg3eCQ6+PqtI3E0ICGvtMAwgk6IjIdui2ifQ8g6DTQ
WoUTDea+Vktbn/R0rD1/7u0RLuNaCmkQ2lBb+ROP7HrdAAD5V6qqvEu+lu+c6gD
emjU9P1deb9D63XIKI9RJ9UZOSxmuS/TEJSFMupdVzXymhdaYNNnafBlvs9WaKMe
BO+toa4fG+gihQ8tCZT0/Rf6rdwwaqentaLzX8t1vslXGGLQCpHSEMj4E2zY1tBz
lqwzINxn1V25tsRzmBxUlr455N8ycfL7qWu8RgHYlEIziaKb0TzRIIF5e9dFN7vr
AYARG6geA4umyRTbrLit7nTr/mKyre84jhz1IX48wEkw63ShXotv2/xGQJVZet9Z
OdHRonnR5dXoY2MLD+VKG5gxhlv8s+D92xkvLw4V1NEHYIR5ZYt6Jf7Uvjjh5mrg
3rNmOhTM3j09h0/5rmd8OQ5apfM2B++oHkKj63W22cJrOwDXfV5HbN0oofkl5mTf
Lk0rFYw5Zbqpsv2wTz7R1wYT3Gs7cVjxbx5uIF9+fxYVHCQ7C3r4fQRG5jJawIC
2r499NaNO5lg/6NR89BdeYdYaz9slQE7Gnxlgj/kBUyh96bTyHHCm9OncTjOiQy3
HtqBchw9r02W6QMM5DX76SWiIVZMNaydhdp8a3YE/qjft1gt+4oassmz7XoMLumw
HDxVQd1rkkK0KA7mBaOstqhnBJSBNecJKHHP8PDTA4zzPi406KdXfSn7gOiQ/z8g
/s8FhGvHUAVL93Cx88Dr/PCpON7fwPiHaqqqtqA0je0LJPS0Q19lg8mt70fWuaHm
+okYpr8sN5td1uflSUE/EfEtKnhTaNOnUP/k/aihp2zfjJ70/f/y3D3Rw3HbTx705
Xz78PLNHjeph3bWNI14oZvg+lQeWObjtdkcLrRLqztmoLf/92bQAEIP1OZyR23a
+fvyMzp8UiwdYM7ms7b9NgxpamK9ZOjJdb89fIOAxZfYAhG9yfeH+lBiaQYl6r1E
Qd9S08J1UPXgMTjHNLwukChW5TpzGr0265xs/2k202GoPosAL+CrS8Rq1+ukWzGb
XY+tIzIw5HUGOr4BZxU/YsRqZqtfjv12TXMVvUz3q7v8c1aPoewccBJMBWh0PtUD
zOfNtbt2JhOVWKVakcOGENCQ+rml4Rfk7Y4NhT4Z+kG0089/MAXsekNsibxqFaGr
ShefuCK0X4krQsuL1fa4ziwGwGLzdzbt6DKFQQ5aFII8HG/q8Q/MWwjqwpsSY87s
z/mhghG+3JFWml60uB2c0DgBcL3maiuKG6dWjiZTIOvDP9o0Y5VpM4kyoJ7hymM1
mqJguTje10GmHbWuJ00OqNXecZglJhdeJfK7cfGTWrhkoIWYRLFjrrelIVDusmKu
pZtry8+/7HOUPF63mv9W7oWlt4Vwx3VlIhYtZIsTh9HDHllx+Uq/ubq2XJJSuSzk
iuejNwbnRANKy4VZmnvdJWPFhY5BTofa9Plef+pgKotmgHvJPTluxbJBNNvid3IA
frOn2ZuJLrtkTlu+/KARUKGi8WddnnC8GzP9d4UIA3GG83t9QCnr0W6gzXX+ru8
RVNcrFFoAwWsfqSkqEaOUbaNnqMu/HYakKfMOaL7iHOoAIGujnbj6xYtK8Z260cf
0RX11xcDcpNmQsyUhQlU00JtZddpDDItyEpltrNmISRqg0X42FypBK1KEzVqYo
FFqHteuP4LE2N2zX210n9N5qgA8tGZq3+fHeOtByBjvU+un3wvVDljfBL0a7oj76
iGS6ctdxbin1gu5cR5fdrQwzBM3VZWC5Q5mqBqKantekr9PDRvjX4MGi9ZijzubU
s6kCWx+y0/vopKlrm3efVrXrzwR3aXGb6SMgppj+XIpDtKumbawd2Ose7HaP98mW2
G6Db15LupnugVPY0mX6Y2lXCqpQ/NaPLEOjpomsfQcvUeT3lUC0B4m1kbu7poptx
e9f8neXuxEPNldRyfyiNrTpg7SRnZTvIe9P0aIT+NJQedOecbVrocw7XisXNqWmx
piZDevrrQwy0J3ZM07chqS8fsmo4aqBW5ly0fC7tffp+t7NsIu2vml7wV/9vG2fTL
fy22D+JLuf+EJhK5vHPMrM8XDvVxBglE9Qms1ULTo6Xo9MFUQupe2Oqhlw2rnUaa
Bes3091rriLetTC2ZLo2p9rjFovHuFSRJj9vq6oTA3485zSrvy+LHiluHCSKDXTYf
EQ3chHAmGD/uoBTraLfS6badwOvXXNubg5sGs00TYaxY4dmMnZEP7P9vtwftJt2
/dZuZgl4pImnpkwriaq30fdpfl6gFxnV3qlmma9AzJ7VtPSG9CReCIG408Xi7vEr
mdK8OeHnPV2UUYrQwxhDnGOn9tU6Lds9hOnXB8KYNNy83qX7QzYnhmtiJ8lp6iD/
UA42qtXd/nju/P/VeNt51QOWukP3xVwn6ddXsMO5sRXptf7lu3LNXp8br4NKZbm
6GKTbuFHFZRZ4BxNOU1vUlz7WfbJ+NUKSA8nI90p/UaD7xQGGGEHmXqhGHuTH6le7
B6mj0HPNXOB5bEuR6Tg0Csy/Ich6kH2Gg9qGo0e0u4deogomNN2732q+7HNKZKR7
/fvgqe0GLm/bDXuLi1va6XXKiyy4jitZ70d26OfraqXL60J3deqsTUnVEm3DIzrgY
nyvo4TixuNrnoS/yoMDD++3a5IOgw6wf0Jqs7uamYtfJYHxedM/Mkr2KuZgEp6f9
ppj+JvWzSwv7YY30/uYI50+i/IsaQd3U9d9OzlPtZ3xWVeen5Ha419m2H2zTJGpp
+eBqCmhitzK+fM9/pHhtelfl014sfgviRmvD37lvvrFuWgvHmO88X0jGXI+8J97d/
ef9xqne/fWaEMAMiXtcsxsbBoQfzcl5GNPyxo3xx11Pqx3wt9YLLsaGnkdrTd0L0
HXuw4qGbHagXIxQU4d7kcPdsd6G+aN9HnqS3GDNIadjl8p8+HNCPXM76ozWmt1PI
k9CR4Sr7PrYYKpRTBIps39dt04FzmzHE9h6uaP9e4EJ/eYJb1s5B33aLoT8lu9xF
Zr+9f/t769qDhZpDz8vvsUrePdZfa3pSSlHsiNo2dM8Hvyie4pOuoD+OFL9++PVX
AUVfhPYP5G175+fbtov9pPTz4S/vWxtlxeUx8Dxux6uOXp1crr8vR5PkG0Fnhktd
i/gvXujjBeXCrpSbFG3Kms7/+cBhsl42TJg5Vv8/eJB++vRbgfPZ4gJjntFh0EOT
aHMD+fTsv892WVqJ/Fklnx778LQnwkUU6Kn/EIP/jIt/6G8mXmCOaR/ULHa7qUv9
Y5zy8MrUxQWxsDzxU1NsZnXVmRFH45s+wVWf4qLDG1r3r3wkn3wBaz9D96ut3xgZ
QrBPjCZtc3p9NJlp9D3g5e55rU+jlJ2MJxv+tQ7Q9jg15b+oQClr7z/GLT52VTY9
PGz6x1fzXQWI9AwcbGnc50bk9JZ0Mr1sDhyvXWG3zSu+yzpV1WE5GfeZchLuM+U0
DPUPVs+zwo5QnwReqvH6eXrKPTT3oU/zDhp6d6eL8fMp+znXJzxtpf+2e87QXa/K
TiNknc6anHxSBfS3cObvc+TYy2EuRdYLPgnr5LOP1V6o0ARS5+pZna07CC0Pet62
j9hfoGv6L0cgfYluTAA


```

    }
    zipfile: to-file request-file/file/save %/c/mysong.zip
    if exists? zipfile [
        alert "Please choose a file name that does not already exist."
        return
    ]
    zip/deep zipfile %chords/
    ]
    btn "Help" [editor help]
]

```

10.17 Case 17 - Web Site Content Management System (CMS), Sitebuilder.cgi

For many years I used a simple CGI web site manager called Chico WebTool. Together with a javascript WYSIWYG HTML editor, the WebTool script enabled an extremely simple way for users to add, edit, and manage page content on web sites, without installing any software on a client PC (i.e., no Dreamweaver, Frontpage, etc., needed). New pages could be added directly in a browser, from any computer, and they were automatically linked in a sub-page tree structure on the web site. Users selected from a list of HTML templates (which were very simple for designers to create), to give the entire site a consistent look and feel. By adding the third party javascript editor, page content could be edited easily by users, even without any knowledge of HTML. WebTool ran in web servers on any operating system, as long as they had CGI and PERL installed. WebTool created static HTML pages, and didn't require any SQL database. It was a versatile setup that worked absolutely intuitively for novice and experienced users alike, long before any of the modern CMS packages became popular.

One problem with WebTool was that it took a long time to install and configure on each web server. There were also a number of features that I wanted to add to it, and some significant changes that I wanted to make to the workflow. The web site where Web Tool was distributed is no longer hosted by its author. So I decided to create a similar system in REBOL, more exactly suited to my needs. Here were my thoughts to get it going:

1. Start with a simple HTML textarea editor to create and edit pages. The password protected editor presented earlier in this tutorial is a good start.
2. Create an interface to add new pages, and to select existing pages to edit and delete. All that's needed is a text field to enter new page names, and a list of links to existing pages. The contents of any existing page would be read and sent to the textarea editor, and the edited text would be saved back to the same file after being submitted by the user. If a new file name is entered, the new file should simply be created with an empty string, then sent to the editor.
3. Integrate the code for a javascript WYSIWYG editor, to automatically enable visual creation/editing of pages in the above editor. I decided to use the openwysiwyg editor from <http://openwebware.com/> because it is stable, small, runs in just about every browser, and enables many essential features. The openwysiwyg installation is composed of numerous files in several folders, so I decided to compress it with Carl Sassenrath's [zip](#) archiver. This would allow me to embed and extract the whole package on any operating system, directly from the web editor script.
4. Create an interface to upload images and other files used on the web site. Andreas Bolka's decode-multipart-form-data function, explained earlier, will work great to handle file uploads.
5. Add an interface to run OS and REBOL console commands, to manage files and folders, to create backups, to download files from other FTP servers, etc. An entire script that does all this was already presented earlier in this text.
6. Create a template system to wrap all user created content pages in a consistent overall page design. User created content will simply be inserted into a table area in any template's HTML layout. This gives the entire site a uniform look and feel, without any work or general design by users. All users have to do is type some text, add some images and/or other basic content, submit it, and the page generated by this script will look complete. To link pages together and create a navigation structure on the site, the template system should create several menu areas on each page, with automatically generated links to other pages on the site. I wanted users to be able to add new pages as *sub-pages* of any other existing page on the site. The home page should be able to have links to as many sub-pages as desired, and each of those pages should be able to have as many sub-pages as desired, and so on, for as many levels deep as desired, to create a simple tree structure, with the home page as a starting point. The system should automatically choose between 2 basic template designs - 1 with a link menu area (for pages that have sub-pages), and another without any link menu area (for pages without sub-pages). I also wanted each page to contain a separate menu area with links back up through the currently traversed sub-page tree structure, on every page. This would make the entire site easily navigable both down through sub-pages, and all the way back up to the home page. This organizes every area of the site into clearly divided sub-sections, and enables visitors to instantly know where they are, and how to move up and down through the tree structure. The site map and menu links should be built automatically by the script, but should be manually editable, directly within the script, using a simple syntax. Template layout pages should be easily editable by a web designer, or even by users who know basic HTML, to change the entire look of the site, and to easily alter static elements found on every page (logo graphics, color layouts, copyright info, etc.).

Steps 1, 4, and 5 were already covered in scripts described earlier in this tutorial. I would just need to incorporate them into a new script with steps 2, 3 and 6 above. I started out with this large amount of code that I've already written for other situations, and covered earlier in this text:

```
#!/rebol276 -cs
REBOL []
print "content-type: text/html^/"
print [<HTML><HEAD><TITLE>"Sitebuilder"</TITLE></HEAD><BODY>]

; Read the submitted GET or POST data (standard code covered earlier):

read-cgi: func [/local data buffer][
    switch system/options/cgi/request-method [
        "POST" [
            data: make string! 1020
            buffer: make string! 16380
            while [positive? read-io system/ports/input buffer 16380][
                append data buffer
                clear buffer
            ]
        ]
        "GET" [data: system/options/cgi/query-string]
    ]
    data
]

submitted: decode-cgi submitted-bin: read-cgi

; If no data has been submitted, request user/pass (as demonstrated in
; several earlier scripts):

if ((submitted/2 = none) or (submitted/4 = none)) [
    print [<strong>"W A R N I N G - "]
    print ["Private Server, Login Required:"</strong><BR><BR>]
    print [<FORM METHOD="post" ACTION="./sitebuilder.cgi">]
    print [" Username: " <input type=text size="50" name="name"><BR><BR>]
    print [" Password: " <input type=text size="50" name="pass"><BR><BR>]
    print [<INPUT TYPE="SUBMIT" NAME="Submit" VALUE="submit">]
    print [</FORM>]
    print [</BODY></HTML>} quit
]

; Check user/pass, end program if incorrect:

username: submitted/2 password: submitted/4
either ((username = "username") and (password = "password")) [
    ; if user/pass is ok, go on
][
    print "Incorrect Username/Password."
    print [</BODY></HTML>} quit
]

; Here is Andreas Bolka's decode-multipart-form-data function,
; wrapped in some standard CGI code (all covered earlier in this
; text). It's given here in compressed form, and written to the
; server to avoid some of the issues that can occur when
; deciphering different types of post data. Uploaded binary data
; is simply sent to a totally separate script (created below), and
; then returned afterwards to this script:

if not exists? %upload.cgi [
    write/binary/allow %upload.cgi to-binary decompress 64#{
eJyFV21v2zYQ/m7A/+GqoYUDTFHaAV2h2A7aNVsHpEixZhGwxsoibbZSsqJKUs2M
LP99d3yRZNnFBFGv5N3xubvnjvR3T84TxTNZvvjxJcS5nk5+u35zewOr9XTSKFEb
eMh1bXhtYrNveAqG/2OSnanKv5LHILKav7t7f7Ocv7t+/XY5v/v17uZ6GX0Uhmet
KAuuonniBueJE3lz+/bPJ4wnSjOi j j f i h Q 2 b Z 3 D K i l l z k o o m G G Q t Z s N V + v V d A J 4
6Xth8h3ovTa8SmRjhKx1gqQI/0vLtYkrbnayAC9PV/Th9uNdNByhi4ynULHPHLRB
B7ZP4PnFi4tDIbf4WOz1D69Gcvc7UXJYNVILi77yK7AeCRmANLIznYi6aY236ays
R6DoYk3D62Lo/LFMXnKmTs6u+8/Ba/TLNUXA+XwieBg6tY+dg17NP0hlOrFZKngu
Cx5XbWlEw5SJNlJVsbPp8uZUmnhIljCGsTGxs0YDPsWl0AZyDAo6zEtRxRnf+jcK
    }
```

```

Qi3rOff2UW78F75UouIxQUBkYVWylEIum72lLQ0JUjGwkWldXMFGoMFDdbBB1ziSd
MxgnTJ9pVe3QWd9t0IP9Uw5mRQqfPkgHuiPIidGCiWGiJAejjFAwtV9EPrDBXa+H
ESDfhpMYAT9pvc6KgMQFInVUkFVT8grRQL5jSnOD6Is2RzqiWkiji+D/a9T8vhQ1
H6rR2qS4Ctn4F/qUeLkuISg4oPQMPY8LoRtJkbMhS0mT07jrJJftJU3JRB3Bwa/a
s+Gyt44lSHc7h41lQP0oZMSuRlUoazTuEhFAAKv3PYn6aNOF1YAeRodtrte3bDls
H5aY/b4Mbp7C6Gy5+X7UyAHfvZHeYdsJjk3NYMfqosRi7CQ7JwPagOSSq2f3MtY8
LF5fwN7YaKyn+0Gd900+qk3VQM0qDl9Z2dp73HgUp9dJoSEIdkbq4XIRPQbMloto
EHceGSNh43upCphpXnKsrYFWRFLRgEdcmB122xmx7oqAYf871tpg+x5r+gujBbNR
CwndY8Dds/H+Yl1Pj/O9/oag3WJk9gmhPRmL0BUg+h6EnhzLONaGHjXOV7i6SvSx
caHpsukKnRPQUbsb0t26crDXHMXcpj11QbOd1OafWlhRB6q3PJFlibWF4XRatkDJ
TRlpthGKdLu5M5jzKJ0hwvXYnN883bbs2xiyhlCcsNF50FqVb5bTIY0JtQkry+EG
h9paIvn72nr7wqBhdIsRUL+9dvophPPQdIK32JHCUGl36Dan5vKtnfjU5n6w47mM
9nvxdHIJjZIZznRLYQci30u212B9wyU0yAlgWkG3GTYjwwvolve0JVN/KGxUlqvU
2DRXX5EIrcZjhVWWSmxFjr0isPl7Wl+4S4vN3kpg9FVKsPAJjJqkUSobJRDjCYDTN
jlqAXcDl0w510uykkUmwPJ3cE5Ykw/WUte21xgpdhfgT7jzHL66WcwY7xTeL6DzR
/Sn2HPWvyP6CkNLLs4ZpvaAb0euZi8/CPaLlG5Z/plAMdsLzhC3nmVo+9ksaliG0
elGY3eLVxVPI0BJXi+cHmgjJFF7o+cXFU2sko00FHbHmSBVZb5e/f7i5ff0Wfrp9
/+Hm+u56nvhxq4u/Q+mfMUIa8lYptIoViUcPsxMajlAEPD2hj6v6SSS9Mpa68PSc
RvEVj+o26E6kOyC6/wuK27PN6mEQ6Ucn/xAB7vRbbhZ/ZyWrPy/9eBRiF63XtmxC
cAhPYgq62TeKJz7tXwz8v0F/TBDpllaY/wDPpuhm7AwAAA==
} [read write execute read write execute read write execute]

; I added a little error check to be sure permissions are set
; correctly for the upload script:

if error? try [call {chmod 755 ./upload.cgi}] [
    print {
        <center><table border="1" width=80% cellpadding="10"><tr><td>
        <strong>./upload.cgi</strong> has been created, but there was
        apparently a problem setting permissions for it. Please be
        sure that upload.cgi is chmod to 755.<br><br><center>
        <a href="./sitebuilder.cgi?name=username&pass=password&submit
        =submit">Continue</a></center></td></tr></table></center>
        </BODY></HTML>
    } quit
]
]

; If a username and password have been submitted to the script, but no
; other data, print the main start page:

if submitted/6 = "submit" [

    ; Print the current working path (by default, where this script is
    ; installed) - just to let the user know what folder they are working
    ; in on the web server:

    print rejoin [
        "<center>Path: " what-dir
        {<br><table border="1" width=80% cellpadding="10"><tr><td>}
    ]

    ; Here's the form to upload data to the upload.cgi script:

    print rejoin [
        {<br>
        <FORM ACTION="./upload.cgi" METHOD="post"
        ENCTYPE="multipart/form-data">
        Upload File: <INPUT TYPE="file" size="50" NAME="photo">
        <INPUT TYPE="submit" NAME="Submit" VALUE="Upload">

        ; I added some new code here so that users could click a
        ; link to see the existing files on the server. This link
        ; sends some GET data back to the script. IMPORTANT:
        ; *** The data after the question mark in the URL appears
        ; just as if it was submitted by an HTML form ***. When the
        ; script sees this submitted data, it runs the appropriate
        ; code in the "listfiles" section below (see the section with
        ; "if submitted/6 = listfiles"). This technique is used
        ; throughout this script to run "subroutines" in the CGI code,
        ; to perform various actions. This allows us to use 1 single
        ; CGI script, instead of many separate files (similar to the

```

```

; webserver management script described earlier in this text).

<a href="./sitebuilder.cgi?name=username&pass=password&
subroutine=listfiles">Files</a>
</FORM>

; Here's the form that sends data alerting the script to create
; a new file name. When submitted, the script will run the
; "edit" subroutine using the file name entered below:

<FORM method="post" ACTION="./sitebuilder.cgi">
<INPUT TYPE=hidden NAME=username VALUE="" submitted/2 {">
<INPUT TYPE=hidden NAME=password VALUE="" submitted/4 {">
<INPUT TYPE=hidden NAME=subroutine VALUE="edit">
Create New Page:
<INPUT TYPE=text size="50" name="file" value="">
<INPUT TYPE="SUBMIT" NAME="Submit" VALUE="Submit">
</FORM>}
]

; This link runs the "console" subroutine:

print {<a href="./sitebuilder.cgi?name=username&pass=password&
subroutine=console">Console</a>          }

]

; If a constructed edit link has been submitted, run this edit
; subroutine. This code was presented earlier in the tutorial:

if submitted/6 = "edit" [

; Create new file if it doesn't exist:

write/append to-file rejoin [what-dir submitted/8] ""

; Backup (before changes are made):

cur-time: to-string replace/all to-string now/time ":" "-"
document_text: read to-file rejoin [what-dir submitted/8]
make-dir %edit_history
write to-file rejoin [
  what-dir "edit_history/"
  to-string (second split-path to-file submitted/8)
  "--" now/date "_" cur-time ".txt"
] document_text

; Print the HTML textarea, in which the text can be edited by the
; user. This data is submitted back to this script, and when the
; script sees the "save" value (submitted/6), it runs the "save"
; subroutine using the submitted text data. Closing textarea
; tags are replaced in the editable text, so that they don't break
; the actual textarea in which they are being displayed:

prin rejoin [
  {<center><strong>Be sure to SUBMIT when done:</strong><BR><BR>
  <FORM method="post" ACTION="./sitebuilder.cgi">
  <INPUT TYPE=hidden NAME=username VALUE="" submitted/2 {">
  <INPUT TYPE=hidden NAME=password VALUE="" submitted/4 {">
  <INPUT TYPE=hidden NAME=subroutine VALUE="save">
  <INPUT TYPE=hidden NAME=path VALUE="" submitted/8 {">
  <textarea id="textareal" name="test1" cols="100" rows="15"
    name="contents">}
  replace/all document_text "</textarea>" "<\/textarea>"
  {</textarea>
  <a href="./sitebuilder.cgi?name=username&pass=password&
    subroutine=listfiles-popup" target=_blank>
  <FONT size=1>Files</FONT></a><BR><BR>
  <INPUT TYPE="SUBMIT" NAME="Submit" VALUE="Submit">
  </FORM></center></BODY></HTML>}
]
print {</BODY></HTML>} quit

```

```

]

; The following subroutine saves the edited file text that has been
; submitted by the edit routine above:

if submitted/6 = "save" [

    ; Save newly edited document (textarea tags replaced during the edit
    ; process are returned back to normal here and saved as they should
    ; be):

    write (to-file rejoin [what-dir submitted/8])
        (replace/all submitted/10 "<\</textare>" "</textare>")
    print {</BODY></HTML>} quit
]

; Run REBOL console (for file and OS operations). This whole script was
; presented earlier in the tutorial:

if submitted/6 = "console" [
    if not exists? %rebol276 [
        print "<center>REBOL version 276 required!</center><br>"
    ]
    print {<center><a href="./sitebuilder.cgi?name=username&
        pass=password&submit=submit">Back to Sitebuilder</a></center>}
    entry-form: [
        print {
            <CENTER><FORM METHOD="post" ACTION="./sitebuilder.cgi">
            <INPUT TYPE=hidden NAME=username VALUE="username">
            <INPUT TYPE=hidden NAME=password VALUE="password">
            <INPUT TYPE=hidden NAME=subroutine VALUE="console">
            <INPUT TYPE=hidden NAME=submit_confirm
                VALUE="command-submitted">
            <TEXTAREA COLS="100" ROWS="10" NAME="contents"></TEXTAREA>
            <BR><BR>
            <INPUT TYPE="SUBMIT" NAME="Submit" VALUE="Submit">
            </FORM></CENTER></BODY></HTML>
        }
    ]
    if submitted/8 = "command-submitted" [
        write %commands.txt join "REBOL[ ]^/" submitted/10
        ; The "call" function requires REBOL version 2.76:
        call/output/error
            "./rebol276 -qs commands.txt"
            %conso.txt %conse.txt
        do entry-form
        print rejoin [
            {<CENTER>Output: <BR><BR>}
            {<TABLE WIDTH=80% BORDER="1" CELLPADDING="10"><TR><TD><PRE>}
            read %conso.txt
            {</PRE></TD></TR></TABLE><BR><BR>}
            {Errors: <BR><BR>}
            read %conse.txt
            {</CENTER>}
        ]
        quit
    ]
    do entry-form
]

; List existing files:

if submitted/6 = "listfiles" [

    ; Print a link to get back to the sitebuilder home page:

    print {<center><a href="./sitebuilder.cgi?name=username&
        pass=password&submit=submit">Back to Sitebuilder</a><br>}
    print {<table width=60% border=1 cellpadding="10">}
    print {<tr><td width=100%><br>}

    ; Get a list of all files in the current folder, and print

```

```

; a link which runs the edit subroutine on any selected file
; name:

folder: sort read %.
foreach file folder [
  print [rejoin [
    { <a href="./sitebuilder.cgi?name=username&
      pass=password&subroutine=cleanedit&file=}
    file {>(edit)</a> }
  ]]
  print [rejoin [
    {<a href="./} file {" target=_blank>} file {</a><br>}
  ]]
]
print {<br></td></tr></table></center></BODY></HTML>}
quit
]

```

That's it for steps 1, 4, and 5 in the outline. Step 2 is very simple. The new file creator routine was already taken care of in the code above. To create a list of existing pages that can be edited, I simply constructed links to each of the files, with a call to the "edit" subroutine in the submitted data (submitted/6 = "edit"). I only want content page files to appear in this list, so I removed all other file types from the list:

```

pages: sort read %.
dont-show-suffixs: [
  %.html %.jpg %.gif %.png %.bmp %.rip %.exe %.pdf %.cgi %.php
  %.zip %.txt %.tpl %.r %.tgz
]

; Remove file types listed above from the display:

remove-each page pages [find dont-show-suffixs (suffix? page)]

; Don't show directories either:

remove-each page pages [find to-string page "/"]

; And a few other odd files:

dont-show-files: [%rebol276 %sitemap %ftpquota]
remove-each page pages [find dont-show-files page]

print "<hr><br>Edit Existing Pages:<br><br>"
foreach page pages [
  print rejoin [
    {<a href="./sitebuilder.cgi?name=username&pass=password&
      subroutine=edit&file=}
    to-string page {">} to-string page {</a>
    } ; <br>}
  ]
]
print {<br><br><hr>}

```

Step 3 is also very easy. I used [rip.r](http://rebol.org/rip.r) from rebol.org to package the openwysiwyg editor - it just took a few seconds. The results are at <http://re-bol.com/openwysiwyg.rip>. Just "do" that file, using REBOL on any platform, and all the contents are unpacked. Here's the code that unpacks and runs it, along with a nice notice to the user:

```

if not exists? %./openwysiwyg/scripts/wysiwyg.js [
  write/binary %./openwysiwyg.rip to-binary decompress 64#{

    (compressed/embedded rip file data)

  }
  print {
    <center><table border="1" width=80% cellpadding="10"><tr><td>

```

```

        <center><strong>INITIAL SETUP: PLEASE RELOAD THIS PAGE AFTER
        FILES HAVE BEEN UNPACKED...</strong>
    </center></td></tr></table></center></BODY></HTML>
    }
    do %openwysiwyg.rip
    print {
        <center><table border="1" width=80% cellpadding="10"><tr><td>
        <center><strong>FILES HAVE BEEN UNPACKED: PLEASE RELOAD
        THIS PAGE NOW</strong>
        </center></td></tr></table></center></BODY></HTML>
    }
}
]

```

Here's the javascript code that integrates the WYSIWYG editor into our existing textarea editor. I just printed this on the same page as the textarea editor script:

```

{<script type="text/javascript"
src="openwysiwyg/scripts/wysiwyg.js"></script>
<script type="text/javascript">
    var full = new WYSIWYG.Settings();
    full.ImagesDir = "openwysiwyg/images/";
    full.PopupsDir = "openwysiwyg/popups/";
    full.CSSFile = "openwysiwyg/styles/wysiwyg.css";
    full.Width = "85%";
    full.Height = "250px";
    WYSIWYG.attach('all', full);
</script>}

```

I decided that I wanted to include a separate editor that did not include any WYSIWYG code. This would be useful for editing templates, code files, and any other text that doesn't need visual HTML editing. I simply included our original text editor code in a separate "subroutine" that can be called by setting the third GET value (submitted/6) to "cleanedit":

```

; non-wysiwyg edit:
if submitted/6 = "cleanedit" [
    write/append to-file rejoin [what-dir submitted/8] ""
    ; backup (before changes are made):
    cur-time: to-string replace/all to-string now/time ":" "-"
    document_text: read to-file rejoin [what-dir submitted/8]
    make-dir %edit_history
    write to-file rejoin [
        what-dir "edit_history/"
        to-string (second split-path to-file submitted/8)
        "--" now/date "_" cur-time ".txt"
    ] document_text

    prin rejoin [
        {<center><strong>Be sure to SUBMIT when done:</strong><BR><BR>
        <FORM method="post" ACTION="./sitebuilder.cgi">
        <INPUT TYPE=hidden NAME=username VALUE="" submitted/2 {>
        <INPUT TYPE=hidden NAME=password VALUE="" submitted/4 {>
        <INPUT TYPE=hidden NAME=subroutine VALUE="save">
        <INPUT TYPE=hidden NAME=path VALUE="" submitted/8 {>
        <textarea id="textareal2" name="test2" cols="100" rows="15"
            name="contents">}
        replace/all document_text "</textarea>" "<\</textarea>"
        {</textarea><br>
        <a href="./sitebuilder.cgi?name=username&pass=password&
            subroutine=listfiles-popup" target=_blank>
        <FONT size=1>Files</FONT></a><BR><BR>
        <INPUT TYPE="SUBMIT" NAME="Submit" VALUE="Submit">
        </FORM></center></BODY></HTML>}
    ]
    print {</BODY></HTML>} quit
}
]

```

Step 5 is the main work of this project. The first thing I did was make a link on the main page that would run a "buildsite" subroutine:

```
print {<a href="./sitebuilder.cgi?name=username&pass=password&
subroutine=buildsite">Build Site</a> }
```

To start building the template system, I created some basic HTML templates, compressed them, and had the script write them to files on the server:

```
; Build site:

if submitted/6 = "buildsite" [
  if not exists? %menu.tpl [
    write %menu.tpl decompress #{
      789CB556DB4EDB40107DE72B0623A456AA63C7691E00AFA5247649A484A46129
      E2A9F265B15D8C9DAE9D00ADFA41FDCBCEAEED90847015355292DD999D3D73E6
      CC1873D71EF7E8C5C4813E1D0D6172D61D0E7AA0A89A76DEEA699A4DEDD2F0B9
      A103E56E9AC7459CA56EA269CE8962ED98C268997DA7635B261DD0A163EDE063
      EEAA2AA02BF3E6711230FEBD888B8481AA5A20CD5AE96A8E1CDA81A828662AFB
      398F17A497A5054B0B95DECD18F8E5822805BB2DB4A8B84E8EC08F5C9EB382DC
      C46990DDE46AD3681B02860CD4A774A23A5FCF06DF88327143A63A18802BD01B
      9F50E7841265CA16CC4D641A1FC09E7357E4428C4FF78991A6F151C43BA51743
      07042FD5F57E9EE3BE7B18650BC6E137824B327E085E326747203CD480F95919
      F110E629269DC429DA3CD7BF0A79863B87B0F7E5C0B11D1BFE2003F206BC4993
      DCED98DDB17D015ED81371C99E2E1FDCA69D2E027193384C89CF443E2B1189A2
      809771BC8BE8E0B32499B84110A72131E4EA74E6FAE52A62711821934D5DDF57
      E0260E8A882807ED7D912A15378BEFA9F8B037C35788121120E4EC0E161D09A6
      C8664B78EF85482EDE00A93A6EB4CAD3DB3055676E2214658DB0B986B0A9BF1C
      220868880C6F9BAC15072D5F506DA53C48374110D807BF1869A1E5944EC727C7
      F8C38588B34BA2A088D96D43285BB1FAD9353335D712CAA8DC341147C4F7017
      2FC30F418826132CB79EA0C79397574934756B13A96CC41A49435BC5620E46C7
      95B3E7E64C0819974885D0AA3385C1A873ECAC143ACA9134863F72EE8B581173
      D1D0F8310B3116E654F6FC7A16756D9F97D35A3EFF5B5CD551437F58DAD5CA96
      3A929535ACBAB02396CE97E5ABAAB72D6DC1C6EB1AED0194AE909F24ABCC0E7B
      D9326BE3E6F0C5FA5DE562F89A5AEDB2D45085AE1ECB5321B792A1DA074C8F57
      4E0F51BFB87A7B97F7279DFFA9945F02C8BF7055DF273CF4211BCB81ACB38CBF1
      29E0949AA83AFCD102CCDC22DAE0FF125F6E2B00DE21918DBE5A0F87AA457A53
      D25AE7F63513BCD97E6B976D657855DD9B7C556FFE923231E56A716E6AF3BEB3
      1EB73CF71AD90B5AE2AF4EA7BD6DA6D76DF25498F295FD449847E647D3EA65B3
      3B2E4EC15F3074FD006814E770CE3C3845AF06749204A43D07CE72C6172C686C
      1D2F2FA747125A954893FFC3EDFC039C3D1A760A0A0000
    }
  ]
  if not exists? %nomenu.tpl [
    write %nomenu.tpl decompress #{
      789CAD556D6FDA3010FECEAFB8A6AAB4490B09B47C288D235192162468197557
      F5D3E4246E92CD4B9863A0DDB41FB47FB973121874636DA7FA83E397E3B9E79E
      3B1FCE9E77D9A7B7131F06743C82C9F5E968D807C3B4AC9BC3BE6579D4AB2E8E
      9A3650C9B22255699E316159FE85E1361C7DE93A03BFE7B90E1DD291EF420387
      B3679A80B63C98A722E2F2A34A95E0609AF5B555D9369CB14F7B90283533F9D7
      79BA20FD3C533C53267D987108AB0D3114BF5756A2BE88130813260BAEC832CD
      A27C5998AD76A76DAC8006944E4CFFFD5F00331262CE6A68F00D280FEE505F5
      2F2831A67CC19928037903DE5C321D0D69BFFB1D1A691DBDD57857F476E48356
      A6761F16059EB36E922FB884EF484EE4B20B8198F313D01666C4C3BC42ECC23C
      C3A8459AE15DC0C2CFB1CCF1A40BFB67C7BEE77BF00325283DA027AB54AE19C
      5E7AB710C47D8D4BF6ED72E031ED9D221126D2382321D7F16C2012C3802097E8
      8BD8107221262C8AD22C26ED7277356361B54B781A27A864CBB60F0C58A6914A
      8871DC39D0A152ED597FA77AF21EC3D78C840688257F8045AF24A3F2D99ADE6B
      312A37DB9476330A041EAF705AB6EB4CB66472CB4A6390487E478CA68505C3EF
      9BBA8A0CD7198ECF6BE380155C270AB7C846E7C29FC270DC3BF73702490AE4CD
      7151CB9018096778DCFC348B11C96295236B826BEAE969BA53CCA7A55BE5FFAE
      1CAF2B253C2BBD355A1B05AD8574ACF5424565B42F016AD9EB7AD38CD6A08F5B
      C48CA94477880D6F28E74BBDEDA6FDCFC4E06B463D3372B82DE64B0ABCD5F9CF
      B4FC3DC28D52F943AABA31566AD52295E1E154E2E257D3DEA8C8DD374F3DFCBA
      15ADC2E9A0EDA387E69C617FAD1A225926C813C97EE3A4E5F6F3D983D4BF829F
      D0B6ED63A0495AC00D0FE00AAD9A003D21A0342840F282CB058F9A8EA5E1DCED
      07F5FCC050885A5AABFC736AFC02A1651F4AE3060000
    }
  ]
}
```



```

    ]
]

```

The documents above are just simple generic HTML pages, with 4 codes inserted:

```

sitebuilder_title      ; Page title in head tag
                        ; ** By default same as the source file name **
sitebuilder_links      ; Link menu(s) generated by this script
                        ; (as defined in the site map that we'll create)
sitebuilder_path       ; Links back up through the hierarchy of sub-pages,
                        ; to the home page, which we'll also create
sitebuilder_content     ; All of the data contained in the source file
                        ; of each content page

```

Wherever those codes are found, the script will replace them with appropriate data, and then save the newly constructed files as web pages to be viewed on the site.

I'll keep the list of links that should appear on each page, along with the site's entire sub-page tree structure in a file named `sitemap.r`. When the script first starts up, it will create the `sitemap.r` file, and a blank home page content file:

```

if not exists? %sitemap.r [
    write %sitemap.r {%Home []}
    write %Home {}
]

```

Starting with the home page, every entry in the site map will simply consist of a block containing 2 items: a source file name, and a block of sub-page links. The site map must have one and only one "home" page. It can be any file name, but by default, we'll use "Home" (notice the `%Home` file name created above - that can be replaced by the user in the site map, but it's a recommended default). We'll also automatically create an `index.html` page that forwards to the home page, if no `index.html` exists. Here's an example of how the site map would look with only one page on the web site, labeled "Home.html":

```

%Home []

```

The file name (`%Home` above) contains the name of a source file to be processed (a content file that the user can upload or create with the built-in editor). The block following it (empty above) contains the names of any sub-pages that will be processed and automatically linked to it (none in the case above).

Below is an example of how the site map would look for a site made up of a home page and two sub-pages. `Home.html`, `Page_One.html` and `Page_Two.html` would all be created from the source files listed, and a menu bar would be automatically generated and placed on `Home.html`, linking to the 2 other pages. Neither `Page_One.html` nor `Page_Two.html` would contain any menu bars with links, because they don't contain any sub-pages:

```

%Home [                ; your home page (index.html forwards to it)
    [%Page_One []]     ; Page_One.html appears in the menu bar of Home.html
    [%Page_Two []]     ; Page_Two.html appears in the menu bar of Home.html
]

```

The next example site map below contains a home page with 5 sub pages, the 3rd of which contains 2 sub pages, and the 2nd of that contains 3 sub pages. In the generated `.html` pages, link menus are only placed on pages which have sub-pages (i.e., only `Home.html`, `Page_Three.html` and `Page_Three_B.html` below would contain link menus):

```

%Home [                ; your home page
    [%Page_1 []]       ; Page_1.html appears in menu of Home.html
    [%Page_2 []]       ; Page_2.html appears in menu of Home.html

```

```

[%Page_3 [                                ; Page_3.html appears in menu of Home.html
  [%Page_3_A []                          ; Page_3_A.html is in menu of Page_3_A.html
    [%Page_3_B [                          ; Page_3_B.html is in menu of Page_3_B.html
      [%Page_3_B_1 []                    ; Page_3_B_1.html is in menu of Page_3_B.html
        [%Page_3_B_2 []                ; Page_3_B_2.html is in menu of Page_3_B.html
          [%Page_3_B_3 []              ; Page_3_B_3.html is in menu of Page_3_B.html
        ]
      ]
    ]
  ]
[%Page_4 []                          ; Page_4.html appears in menu of Home.html
[%Page_5 []                          ; Page_5.html appears in menu of Home.html
]

```

The key to understanding the site map idea is that any source file names followed by a link block will contain an auto-generated menu of links to those sub-pages in the .html files generated by this script. Pages without link blocks will not contain any sub-page links. They are simply wrapped in a template. Of course, users can manually link to any page they've created, if they don't want any auto-generated link menus or template design to appear on the site. They can use this script to simply upload content, or to create/edit HTML/script files. If that's the case, they don't need to create a site map at all.

To process the pages and build the site, my thought process is to create a function that reads each item in the site map and does the following:

1. If the item does not contain any sub-pages, use the nomenu.tpl template. If it does contain sub-pages, use the menu.tpl template.
2. Read the contents of the file listed, and replace the sitebuilder_content code in the template with the contents of the file.
3. Replace the sitebuilder_title code in the template with the name of the file given.
4. If the current item *is a sub-page of another page*, replace the sitebuilder_path code in the template with links to the containing pages, to create a path up through the tree structure, all the way back to the home page.
5. If the item contains sub-pages, replace the sitebuilder_links code in the template with links to each of the sub-pages listed.
6. Save the file using the file name given, plus ".html".
7. Call this function recursively for every sub-page that is contained in the current item. This will work through the entire site map.

Here's the code I came up with:

```

; First, load the sitemap and get the name of the homepage:

homepage: to-string first load %sitemap.r
current-path: rejoin [
  {<a href="."} homepage {<.html">} homepage {</a>}
]

; Set up a flag variable to help determine if I'm on the home page
; during the recursion process:

begin-recurse: true

; Here's the main function. It takes the name of a page to read
; from the site map, and a current-path variable, to keep track
; of where we currently are in the site-map tree:

recurse: func [page current-path][

  ; Set the current path (where we are in the site map):

  either begin-recurse = true [
    print-path: (to-string page/1)
  ] [
    print-path: rejoin [current-path { : } (to-string page/1)]
  ]
  begin-recurse: false

  ; STEP 1

  ; Choose whether to use the menu.tpl or nomenu.tpl template
  ; (page/2 refers to the block of links in the current page - if

```

```

; it's empty, use the template without menus):

either (page/2 = []) [

    ; STEP 2 (for pages with no menu):

    constructed: replace (
        read %nomenu.tpl
    ) {<!-- sitebuilder_content -->} (read to-file page/1)

    ; STEP 3 (for pages with no menu):

    constructed: replace constructed {<!-- sitebuilder_title -->}
        (to-string page/1)

    ; STEP 4 (for pages with no menu):

    constructed: replace constructed {<!-- sitebuilder_path -->}
        print-path

] [

    ; STEP 2 (for pages with a menu):

    constructed: replace (read %menu.tpl)
        {<!-- sitebuilder_content -->}(read to-file page/1)

    ; STEP 5 (for pages with a menu). This code creates an HTML link
    ; with a nice color changing rollover effect, for each sub-page
    ; listed on the current page (the page/2 block):

    link-list: copy {}
    foreach item page/2 [
        link-list: rejoin [
            link-list
            {<TR><TD style="border: solid" }
            {onmouseover="this.bgColor='#FFFFFF'"; }
            {onmouseout="this.bgColor='#D3D3D3'";> }
            {<CENTER><FONT face="Arial, Verdana,
                MS Sans Serif" size=1>}
            {<A HREF="."/} (to-string item/1) {.html">}
            (to-string item/1) {</A>}
            {</FONT></CENTER></TD></TR>}
            newline
        ]
    ]

    ; Now add it to the menu area in the template:

    constructed: replace constructed {<!-- sitebuilder_links -->}
        link-list

    ; STEP 3 (for pages with a menu):

    constructed: replace constructed {<!-- sitebuilder_title -->}
        (to-string page/1)

    ; STEP 4 (for pages with a menu):

    constructed: replace constructed {<!-- sitebuilder_path -->}
        print-path

]

; Step 6:

write (to-file join page/1 ".html") constructed
print page/1 print { ... DONE<br>}

; Step 7:

; This code builds the sitebuilder path and calls the recurse

```

```

; function on every page in the link list:

if not (page/2 = []) [
  if (to-string page/1) <> homepage [
    current-path: rejoin [
      current-path
      { : <a href="." (to-string page/1) {.html">}
      (to-string page/1) {</a>}
    ]
    foreach block page/2 [recurse block current-path]
  ]
]
print {<center><table border="1" width=80% cellpadding="10"><tr><td>}

; Start the whole build process by calling the recurse function on
; the sitemap. This will start with the home page and work down through
; the tree structure:

recurse mymap: load %sitemap.r current-path
print {</td></tr></table><br><a href="./sitebuilder.cgi?name=username&
pass=password&submit=submit">Back to Sitebuilder</a></center>}

; Write an index.html file that forwards to the home page:

if not exists? %index.html [
  write %index.html rejoin [{
    <html>
    <head>
    <title></title>
    <META HTTP-EQUIV="REFRESH" CONTENT="0; URL=.">
    (to-string mymap/1) {.html">
    </head>
    <body bgcolor="#FFFFFF"><div id="divId">
    </div>
    </body>
    </html>
  }]
]

```

I added the following link to the sitebuilder home page to allow me to manually edit the sitemap.r file using the editor subroutine (the one without WYSIWYG):

```

print {<a href="./sitebuilder.cgi?name=username&pass=password&
subroutine=cleanedit&file=sitemap.r">Edit Site Map</a> }

```

At this point, I can create and edit my own sitemap.r file and actually build the site. Now I need to write the code that builds the site map *automatically*. I added the following code to the "save" subroutine created earlier, to keep users from ever having to understand the site map format, or from ever having to manually create/edit the sitemap.r file:

```

either (submitted/8 <> "sitemap.r") and (
  submitted/8 <> (to-string first load %sitemap.r)
) [
  print {<center><strong>Document Saved</strong><br><br>}

  ; This code recurses through the existing site map, and lists all
  ; the existing pages:

  recurse-sitemap: func [page] [
    append sitemap-pages page/1
    if not (page/2 = []) [
      foreach block page/2 [recurse-sitemap block]
    ]
  ]
  sitemap-pages: copy []

```

```

recurse-sitemap load %sitemap.r
prin {<table border="1" width=80% cellpadding="10"><tr><td>
  <center>Now ADD this page as a SUB-PAGE of another in
  your site map:<br><br>}

; For each page currently in the site map, print a link back to the
; sitebuilder script, which will run the subroutine that actually
; adds the new page to the selected location in the site tree:

foreach page sitemap-pages [
  prin rejoin [
    {<a href="./sitebuilder.cgi?name=username&pass=password&
      subroutine=addsitemap&newpage=}
      submitted/8 {&existingpage=} page {">} page {</a>      }
  ]
]

; Give the user the option to not add the current page to the
; site map:

print {
  <br><br>If you've ALREADY added this page to your site map,
  or if you do not want it in your site map
  <a href="./sitebuilder.cgi?name=username&pass=password&
    submit=submit"><strong>click here</strong></a>
  </center><br></td></tr></table></center>
}
] [
  print {<html><head><META HTTP-EQUIV="REFRESH" CONTENT="0;
    URL=./sitebuilder.cgi?name=username&pass=password&
    submit=submit"></head>}
]

```

This is the subroutine called when the code above is run and submitted. It recurses through the existing site tree, finds the page that the user has selected and adds the new sub-page info, then saves the data to the sitemap.r file:

```

if submitted/6 = "addsitemap" [
  recurse-add-sitemap: func [page] [
    if page/1 = (to-file submitted/10) [
      new-block: copy []
      append new-block (to-file submitted/8)
      append/only new-block []
      insert/only page/2 new-block
    ]
    if not (page/2 = []) [foreach block page/2 [
      recurse-add-sitemap block
    ]]
  ]
  recurse-add-sitemap new-site-map: load %sitemap.r
  save %sitemap.r new-site-map
  print {
    <html><head><META HTTP-EQUIV="REFRESH" CONTENT="0;
    URL=./sitebuilder.cgi?name=username&pass=password&
    submit=submit"></head>
  }
]

```

At this point, the script is fully functional. I added one more subroutine to display help text:

```

; Print instructions:
if submitted/6 = "instructions" [
  print {<pre>}
  print instructions: {

; ... HELP TEXT GOES HERE ...

```

```

    }

    print {<pre>}
    quit
}

```

To finish up, I added the following links to the main page, to display help, and to view the generated web site pages:

```

print rejoin [
    {<a href="."} (to-string first load %sitemap.r)
    {<.html" target=_blank>View Home Page</a>}
]
print {<a href="./sitebuilder.cgi?nameword&
    subroutine=instructions">Instructions</a>}
print {<br></td></tr></table></center></BODY></HTML>} quit
]

```

The following code is the complete web building CGI script. It's the longest program in this tutorial, so has been compressed to fit on this web page neatly. Unpack it and upload the sitebuilder.cgi script to your web server, along with a copy of REBOL version 2.76+, and you can use it to visually build WYSIWYG web sites, directly in your browser. Upload and edit files of any type, automatically create navigation link menus, wrap pages in design templates (2 included to get you started), run console scripts, and everything else required to create and manage complete sites. It takes just a few seconds to install and it's easy enough for absolute beginners to use immediately.

```

write %sitebuilder.cgi to-binary decompress 64#{
    eJy0vOmyPBiWJvjfn+K2t1RNldCZGdtURWQJYBgGBgbGDik5I+z7YuyQku8yjjzpc
    99iIzBqp6e65IdcuBqpHVY+e5fu04vHf/9sfwt402gom8I8/hMMXjWMU6ePPf/nS
    9XkzfzfnwN22aMm/EP49bF//YxxusIZmNd/Z/g159a/PmHuyFLf/rhztHXP/lGCIbE
    /emrno9xMOVVFPdfwC/3/wB/N6EUa7un/7ypY/96A9hmv/bRzI14cefwaon/eoj
    8kf/I5iSJO7/8ucvH8fPsORjmHOM2zDGNdh2Y942A3j0PCb+nuJh/EMdj1kbfxv
    /vnzVVV04+tvbnz+fEr+t4/aL+OPYTymnv63D+gCX05tvG/8+1Y4Qp6bLVlexR9/
    7toH/M5/o+Pb4vJ258n2bX9OIB5003jTyK/C/nLeUafP37XxU3022X/XZOWiv3+
    Hz38y5e/v/rKc58r/77Yf6CzQ2P99cfvS/ve6/vnZ4cvf/nyZZiCOh/HOPq3jygo
    2yj+3KOPX+7+Icibf/v4ee++fPn3jzz5aNrv88/84SOI4+bX5v/j46c9+piGuAc7
    fxj+7cuXo8u//MsvbUD448dDRBP/60fbf/zmPvrz/X/9aSD/Nrhj9m2T/umr/UF/
    aB/PD+H45T8+/nCs/i+/bfhV7fPZH+MPPe7nuP8fH1Kb5s2Hdkwp748VHqb5k6gf
    GO3b76n7DzdFkz9kzrgrlx+/Hps9fv2gWUNQnj9+/SM4/GrifzxU8fXc9+uHeSy4
    8evDab5+/PDdFD596MdPF/oY8j3+8st2+frx2eThR5+fX//xLL5+qIfWlraP/kuS
    PlX8n0j6QXiQpvFhuCr341fdZGThsJQnLX9++6b0rx8WLZnH1+978Ls1/QB+6uN0
    768/gN+8+XdtzxjwT49DseOnFf37R5jFYfnrrn/ExwZsH2Nex8c+fVp817dp79ef
    9pM3Ydv3cTgetjH9orbfgKj3iwp+ax5f4nzMDt/613/5uddhMV9/vv76rx/+Mc6/
    /Nz389nP11//9bux/UuSH01+O9Jf2Z8C3jUfvvt3exh80vblHz5t/N//9q8fP/zp
    J3P9bpXfXODXhebDRlv+j4+0/WibL3/5reF+FX5e5y/GAf68t3/8+vFf0es3Zxs/
    4jUfxuE/Pv7p0whrv/tj/9Nclv648dvbf/2ne3uo5c9/+dvHbxt8u/nXv/0jkVNX
    tX70adK/lQkefu/3G+hXVbucGo3tH74/+xYv6q6PDyXg6H//65dY3G4WDM3w7r7A
    mqBBgH+3rnk1bneftuAMpgn/aQ33jstXL0v5ZR3aPag8/S0+zagWv0gqRUXIpnnP
    5sbc0hl7IusUzE0xa4hBosZqPL15L1Yx1LGmxIAJwfZ4UXrKMfTHjQu+xHJWBU42
    uv1zjUK3D8KK3vjNY8akuyA9/JkYiYRQwuMvADouNoMzREwezjsXMzuyypcHPU1t
    0+TMFIscUu0AGKiiJy6NXih5USR59oIDD7k+8gray7atef41esPTAmYrokX0C+6M
    GZkh7Wz4pF5rRfZYofT9FSDLLi1u2QeNv9EspVqgkVHTM3oyW5ajW2NKd/UuacwX
    hvBUVGlu0TpehSBBbWWvrjJfH3NImI7oPi1BEghiexB0zGo1/awEr3Fz3HdhBPe3
    I6Hj19YtkSsOSy0o3WSnedTGgE8ACTI+aEhP06EBZ81jJsVHF4hsSiHiql6xS+pv3
    aNLpC7tiTmBX3ILp4hMSrSFQO3LyzLrJhKpg+cHg1+HiXtXBri60t13pft+5UVu1
    JgK8PH11S09cktg0ybIG4GZ7SSsL5MpXcveK6KfYagKupNdFNat+KW0ocuQb38q3
    a8Aw0J7rORD5TRtdpDorR152RI0XQaXMBau11zvpHmMT6qQRzyb23wu0nFR3Oh1
    tChO7a+M4wP3L5x+TbJ0dmmD6uYQf6Ty6yY01lneLINMe+01YYXeKfDcGGBtf+d2
    mRc5cAV9yiDn7AV9ueO9Br911B0b9Aa+zVgqJ0FP0VZ9yapLSq02imUgZ/qlNi5E
    0YvibRRNRNQYhLF90P8yAPw2omil30MiQ6HqpV5aT9YnrTJbfzcmLrvR9GNGVLFb
    /adyglw61tpo7McYCa6V/uWO+S4YoHLQESzObxjgEOZG35PZu8duNiHfiTxDOxm3
    g5YT7IsQF9VPFX14wwkiJy75RbphyfIkXP+xNcCFj6iLArxLxHrJl/el0jw46gjk
    npodFYmtzuXXMKhRR9DUVyBX7dh+4e5hzOvPDEWmju2y7jCkoXdvtnaTtJSLwpqB
    YHitv6J9025CEtDYpcCK9UA6FUzw1L6wSxO55DUawDvgVpBagAoFtn6K2GJJPXWm
    arV0YcwUyHCuyXZJefr8vXAUi8hxfdbXL6F/74apfDTHpMxgCC4jjif91bnLTtgV
}

```

EPQKlKhS6MSuMo3B34gq3qA8sG+oo/1jGYlfDA3qxox/RNKEyVjhleIlW2bHbZ4k
iQSDbQ/511VsODxv2OX2tgISMARXEcdX2W8Ax3/JqM4X5oaAG41Y3kwWCYNmSgAV
zW2XqeorEh4iLN5ZM60Q/Oo32PwYm6QwsQZfUKKwv1DNvEZ3QSw8wsbTXJfYY5V
JhiCGWrZzmtGQ6ld8ghvumWyzG0lxxfReoIPfjWr92x+ga+a42Cc0IdekWm2rdrfr
rdAu+aBWhA0BqI7OT6TsUupmPQaVLSR3aeptIGrXgnWvxnLUBlpJ7xC1wWDLtNW
lma9qCIScphbLqBtjjEMrWkXZcnbIir9LuG4HS4usRqxhF937QuoN/BdtedNxdny
KUKd6nWzTweXePjYEmRVX6p4zAO7ipavg7RnLNLUVgtQ5eBXOX/5EkO8i8sstVqq
cGFEJwfCu5wW4u1GtEDo3Ex4KFvlcrsH91pnLC/AYjAhcixJLnbsd9QXELjXwITh
zZytb3QCX0CdyKbgk5XbjUjr5WaoDqvsFxDNqVc4K+IZ13WdkjsfJ1U9/KLNNFUA
LYxzeK1sLA4u0wMm1Cdecy/cDBtwpRli1oIg80Bvs3t1A6mY0f1bjjhjvbjfQjpt
3fsNw0b8EHdidJadnC830GCuXQUdnrplW7KjqS30DT9449f/vbx50/Q/FP+jdc4
nI6//6Vb3wHXkabjvm/7//gYj1T754MqVR9/DbP64D0Ehn38Efw1Jf/tL79hpj8B
ihNv+CE8AE7c/+mH0Q8OHhMc+CPuf/wKfflY8mjMfiQv//QRxlXV+VF00ITjyewa
lONnh+hPZ0k/4effDv8LqP6VD4THqr6xgeATux6QLf5YjmcH9/H7YyrV9uF/4sFj
MvVJ/BCP4zGBjy7u63wYPknMJxt7yMc/fnyoBy0ajtkfRG06BI6zf7CMX3HJgcO+
q2dsPzX0xx+CY/7H7z/WxEFe+jj5B7j+P77B6p8x5T9/QRwff0aR//wdOP74M1z+
hI55M8U/gP7vhgF/Hgc8NHh8fLv6VP6ffvPot5Dvl+4/Yb/vRO0vPxGutj1U9ivk
/EXP3yR96vn7rtf+wXaG0e/HA0Cn8cd36vUr2sU/IffPk/8FzH6Hez/R0t8gya9f
P59+J8af+s5/xoy/wa19XLTHkL8h4j8rWPXH7JO/LMcU/SHK+49fmvz128b8z1ji
335DX/+T8f962vHvh05XCvertXz9Hc3jnux3mlRP1ZgfVjqCv1CAR78KNL8J+Lj1
1cFXTvQqOW59/Q05+06zuuxIpL/pf+ry80b8Q0b2faTPrv/3t/+ucttm+nw0rj
H6tj8z6nedDFzwUMn1b78eu+/ET3fge876WW/wLb/viHi8zyKDRs9NsSf+FsPy3x
b2ce9p+o6bcSfmF2/OAC+l+S8Ks6fpYRR5+e/EtH9lvk+njGy0HD02OX/6Hif8je
v5vA7Fft8eU/2/T/Vxr+09c//X5PToZ/zGo4aHHbj99zxz/98Xs954hfxfiydvnD
MCVJvh5t/vxPf/ws3R0tii49PtMjGPzTH7vm8zqou+Ozzz8/j7zzeT/6fPoZSY/r
7PP+/u3peCz1+Ow+5fSfv+n+fSZ9XLdz/IfYD7Pv4ebb1D7+/Ili/910Pgs9nxf/
8a3Zv/4XRBxE83vZ6vujr+DXv3xGpEPy/3Eo/xD9ccSVg1y3fR4Pv9PBNzv/1MAV
tc6fI9uxgmTs3lM7+t/EfZYm/I/k20/2W22hjaKpb70//r8s8nuPz2e/DU9ff8i+
5yDuMLIP7jN6fi5H/baFP+enr986HNHm78b4XU7/u2D3Ped9L8eFTw/4588F/Pi3
k+jf6f9wr7/93blvMeSfm2Do/v2nPycRfzsU/LnGXwX/5e9i+F9/VsSnsV52evC/
vLTPSmrz6/p+SW5fv+/IZ9X6Q/a7b6v4Hmf/N0/gW5fPv1//xHxfhvYpXnu5/39
7bB+/iXX1We5P0wfnzLQL/m6X/9+Os3L//6ceT9NB5//L+Cym/KPln5YdLfYj6f
5vbbIf/yvlnHB0hrj8j3iYY+L/7/U2beHIqYwm+17a9/En7z7XPMv/2dtf1Xsddv
y5HiPxc0DfJcftXaTsFvd6U/6DW/Q/R1bd0ciqk/Yssjm38tMFfdvKXYPsRAPIV
P4Gu7/D5oz128LNaOh6BJh4+o943APyzPThV8f4Itscwyzbky5aCQ3hE9nEAF/r+
x+K30es39b3fdfyWEP7zAt9vXTsWdxmArbAKZ4RZduOuCbqZDWVnBBGX9rrACpna
b3gIqbroCfqlvTwu4yVfDdMTgld6EnalJJ1CrUV9BpiKgUliABilzG5M+UNTWL3V
7M5+t7pW40kCe6C1IAy6ohIUOalD2pgnYYhAJ9rdscChoBHx6i109WYp/lpXqZ+G
miyxPLznjGbvUMet4ZWTYLLihetTu8kchFOWm4KU6GwYo+ImHppfAWswlPUElOS
xlvcNqT56zKv18pg0ayN+O3ZM5dIcvfQecFuz0FnePgjlRtkOKx0pa5bdwINfc0
PHhifHgEvZ5fmxH2beiiC11CIP08pIk/JzHRUC3leJ4M8jPiCl5kXsGedS3AUo0q
Bor3DJ8KENib0746zBIyNks2Cs6vHfOymF2GGL75rJrQ15MwFnIJ1aYvD3bmoCFV
KDGsBY2NigAW6eTVuPGOvrt2wpToi4XHnV694k3bQuENksY/85Mw2u2c2gzdviBfp
9HhzbagJbBdCufiN3gkg3ScXBMyyqKGRoVQQiwyYk0pDNWTwgchv+yRsDQuOkw2e
TXCjraEqNp0StfCbz2u9ZwNdD0ONm+JDRTomnBbcOssYsJB9CCJzIO3hsdhMGJS8
9vNMzq+BEGFwJPh9SagdkMHEqFAlwcYRjWLKdhpQakYNIueET4znTimP052FQule
ABrJRzkB31ft+oCma4MZzd7LDeaG26SS1hYdNqH2hLCHDbEBTxAxahQ8j1L5sidh
yespvSUfs+07pYwFhdyBAVSKxiAeY+7dlwQUARHEIzGk6Nu7G6/3nOmDWuyiMmFn
gDofVy7HSG+jxXfCFpvuFVNDvzsSMEOAWM6klwrzXlZqlLsh+wNxp6InjQRLReBG
ErJ7Y0/Cdg65EA/MZGecAtx4A3HbhceRMV5bNCYmvWuFC46gmVAZBqhEG6oImHfg
OJMFqM/r/SSSWIEAlJKp2RNCwncwmL1EVklqQEGdee7ctc5hyIixZlBsL4OYZkoE
3sLeW8SDwnRQPglrVioBwztgLMev4HOvy9Ie4Mnt1RuObvPYWl+HKklBXXZYgFpo
VQg/Nhq6kQAY7JhNnhLazdr/AY0EtoOKT7ZlIgQaiGcpU7uWn1GHdK0COouJA74gNv
maAIkqX1CbCzgbhS4XxepkGSmacWheJKjyPEBDoz2Rw7YQu7gx6C93AxqIhJq0qG
WywRIlgHyvcrqWBktCo3/yTMjvZw3g2AU4gmymkWL3kG9wFnX0oerBHYXdeFAaJS
XRRB7a5Ef1GnBLuDV/OG7jyCnGe2N2QWzZOIzikglz1Bb/SF1hmnTZpmkZbrIhE3
1+nFpb9wb9V19HhpsJ+Fu7fLm+zzJCzV1tpT1/ugbjdgkIlk1UxnDt+XBG3QV2gQ
F/LyknvQnUCG05ov5RXO/EIXcJ0mCokzkBgSbJSs4Cl0cbeADqUkNYM9sCwI+Z7
LTAhs/ceyBD7jItHeIISP2JpY4fjCwG+kgw7CVOjSGB8sWd0baXlzaUvfeMLAORo
k4C9PFro85xEmB3Mrz2stbSpCniEbM3QK3sIXs7ZCcTuaZ8H6WwZew/BQA6mKqBJ
qyM+wdprdrM4RRyIi5IVc/rObEaQwja7yyFr6tI6N+cQtBUDn7mbg5jL+FJZtDZd
EEPIJNAkOUsQB8tA+Hp9pd5M7QvuEPE6oPlkRihy+NW9PQmDo5LxX0/yqifQEwgu
O02X+0DcVnKQmvk+FfVcQTRpLcwPXCCmKdxRaAvUi6WzEdg4kkYkcQJRG2vB1Ko
10WEXx51UcsRODbJRMjcXkt0SngB3t/bl7I87YdscCBD5izf3xIZOs/Mr62c9R/5
zaJviWtv7fRogPwU9uNSZt4nsfCs8ElheY0rjnOt9QEaLWudde5NSfKp2+AjkEm
8eBrFaAvKQOkQMro4DANQc10kwtNM95tNffPZDCquMsaCkQ8N3hM8OFFr8p5ZoN7
HzGndULlouszSax3sq1EBwTwDXzP9tuMh3tPeTMKZNeWYVOHvr26xUqTgeGdVDyn
OkFFvFdDtdjtwtTtIBgTCI+It9gLyMYJvB60XIbAG1YlCQRakbupO9vpFNmy6YO/b
tsInYb2Vvn01rmIjs4qFyZn01uljoEGp9hboLb/MXcXxVwZZGhB+imoJwZMTT4nj
s7gJLL/DGjIJ4geiLgdE30aBN17zOG3I2u51pbW07Tr1ldTNkLQD3erX7uJuHSrY
OKvsUyGw4pOwSyEij0e0qZXBGbjmD310n0axywAcffGBpUE+Ukz0S8THEVlyfs+d
JLsJue1hgzfJr7POTGLab3mMKi0MbiJLdjSGbfs63d+1D5r2Xcbu5kVUx9Kdd64z

4pvppLr2pG5oH/jv8iQsD9Y+vMSUJW8x0EN56f16ACvt5kUHFCWiMj4CXROFPZGJ
oallAdeq7KIWFZ8hLHvpTsIq2b4jAtuOhjY40BpqXHTvcdwXWs5wxufuiUq1Ek/wN
ZYF4ftBbIWI72fVPE8Vc0AbxczyDODuaHAX80IF11U3JnRC4G+sbnngYSv0Qih2uv
Oh6otHkUQ13vftreG+f2DPNeva3nwwguE0rzvuloaCLyfQJKTaxRIGRTu8Mid4vQ
Fmfk1+Oq0AlwQOT9va2F+kKCG53mWyFsJ2HyHMC0mrzQmFqfzpbmGtfnrfSkXO3W
GaCTURu3Mx2QSqYmv1703Nfe9Ii859bXgyYaJ2FuFJcvu8DzbmjzHkNMAZx9Z5xr
EQYi+C5oEdi4bLUpR3ZP13a0dbjxiLuYr4bVKd0ZuOBIM3OIQuKggoDOE5HhDE8gH
Mw1E9aat0OMWvdp4QZ0nt1BZMmlXADWTgKml6yBUYaidhGnG40oagmm8EfxA3eab
Ye2RTJ8z1rDBBLJMOBkxRsRPRHOCodvMN2qTphzt3IKMD/v8BphmF2Ve0ktZBxcU
frp99K7jrsJXmK8QmcZ8Hm+1RPcMbzfV7OjEy201L6ZXMfUCHe30LZXM6R12oLob
mFbee/boTt6RS2JiQvBYwK0ModzsWdUikJeXNLT7buldLktXhB0uHJ3za27rbgJo
pbteKj5iMfM6sxJv0TsA3tiwFoSk+TDH7ZiHjVpTONLmStZz4Al6ny+Iu4HnHBDU
azEQMDER4mo61Ew/jhCl6wwjeFya19yy1spz6bnrJlH1tS+6g1ltEnQkhYeGxTt7
AOnrAikUiZisU4IoWKw8u2nn/ULCvC7tMzL+q4Nlns5jyqBaTgAaNemqWYZRcu2
zu6U3PBOoSfDokIZkQmpjxxdDLu2k44oEW47GOLPy2eWiNAAdWUHJiWNuMYMpnS
ykKSSzs5s0MaoHO2wBrFMGCOS5T4DtFN4p1lsCnR4/fkFcyUTik6Pd53BJhWreB
Ie6urp+FSUpKIutjuai4no6R3+2wWQhG4DwgYaTmgIvgRcTc52V6BXzW46Da7IvM
0AFmZQ4EnoXdnIqO7z3r8s+iowgOFV7q7eY53JawIuo/SsGvOAFZXXLWA4QUnNwc
4vmIy3ZWXtbxDN1vpfBsMw5+SDItoYizELDdZtdRi8glDtoICMOelbjgCaNkIsLh
Qy1oZpTgon6KxIM4bwAnNLb5sEOL0LSqy1zHM8cUJDOYWiTnsWAPz7u7xH7D77gn
dWk1B/XtSHdmLCScdL+j51THb6+8OGAPUQjd4z1xtvfcx+eS++82kPADN7e9Hbml
GOK3QlsXyYDDA+V0iDtm/EIQ6c3S4cbWlDEC4KharniNrO6CJLmDXHvH71HxLmTBL
EC+idQdRcZOTIqu/zCOIG4Z/v25nnUGX1cUrxexEfYaz0p3U0svx7jrGczKDFMkz
0maWjxlTMFjAmobQ5cCBLZGFECOG2bojyx7lVmhCwi/jcM+TLfQb5mG9fT3qU7GS
DCSKm5h3OM2/XB8XqfL4h+C79WNfLjh8IMxxzeU5JFurHobf075OvdL3YiCUiGCA
/bgpc/vKtyrDunICrS7y7jvM0WjNiBjKl9dgvJ8z0jrsuZUX12TNS2fFmi9NcIGY
ves4m3ciZhs0eMXoANLM7urdOpaZq/gA6OXlyQ/e4JyJWmdCLi9WDNazydy9CJL+q
0ytrN80TFM40/exQNKUZoSuy53IVBCKFTjdYgRyiz143852FtXk4smKJKNbeUVX
EesyC/JMdESQeHPxgAdvSrGlCnblYiCiOdRpQVQRlrfCX1VSPGNaw5nmi6LwB74L
b9g08NyC9eARkeeFk0fjvmKNCJcgBVqyOsQc/iDmMjnlDnkHc9a8z0b79OQclQrM
i1loA+51B/fE6JbbsKa25ODFXOq8tLYHnZuqznzc7/ebywSN10rvEt1f6xmuIdtR
4x2bpxYmFD1eMDAAtV5cjhCCTe0uWJO91SC3513KCFhd0utmukPva1ghd7ZDPnUsR
KPWgCuEWob4UZ/5gGfRm5rQoZvpSmhwY8XmY3HJGYyrs9lzHoFSruVilii2X3NrP
+CzPKW0DMol23hhcRXlwqV50ls+07N4xsagy72WipSA70L3lNbdaYl4r+ulWJnce
1t3KFCORZQceMwVil1VwDyuan2CLhloDb/tjZhrfU/1uTcScaIramQH4OXDpndJG
fa4PtzhjWi4vs+e22b7aJlqLOxy7P/csDC+sAvl3yJ/Yw7jFpaBfamc6Uj2U5SSk
jHSs9ptlnsFeREclZUjEOM0HdVsrbtFtQj6SO0k9aX2E5RcZ2wskJfkbJhzEhmpW
yy4RPZLZ+Izdszsp8LXGarZoJUvOW6MG9CeOmEzccfK7R407xhqNtb+LnPTURwsF
jTI97vKSA921DrL07OgphwNux9MamTEMkeJ3ArX5tFMN/zIs69wjDa1EYenn7vae
rIECyNuJazwDm8ZHRMvn7oQtjocC8Q5hFK5h22N/RUUVzLd4i3cXZ8docYKm6YqB
TQ7ireUN7Sfu+HpguYeMsLwGcE4p9oz5TYCBK/1rc13aEdzNT146n3D6FwZ4Wfffd
iwFPljtPiS67lyhVzWyvL5uiVM5FEknL12tUueGtO/B10EM4mMwNHFSdZ9vb0Ers
Mgg0y+GvSb6NhX17eOEjXdbRHX1ZbUieGUqZqmh2QbI+i6LOJAvbN2BrqK/RcKwZ
Hlmlk1HRJYpyIKPl7wLRK7j7VbhZbL/b897m0a1Ogerjks0r0TCfUhDdtcQcni1My
M15k0AA/t1ct29SjWC6hc73RC3m77CAkr2V5s/VzqvNwMDN9s6wIBsula0sug9a4
qSiM3bYAwWkuHUmR+JLaOot7uj4FT+rq8y/g6dlwffYA4dLjKhG9dYmjspWPZOuq
wq4WqfCQ6ubJo/I+A7GYpNLf2qSRmIpPC78fb4Sga/o5wImKYUe40Yu710v4i5t
3jvGN70dZ3YMGct79qyyHSQhToHHFXVViO5R9PIeZU3S1SoMpjPhyZ41uq5efjp
/cZVJmElRfK+VE0X1Ap6N1X17inKcsl2jUbOpes5wx5Ap7j6d71BzxzdcxBT1zmf
l3ADTnj0+RnDQ2Ruxk2MIAjpUDtmApF/jTJaJlyMPqlDmyWiYto7HPTn8wDgshQa
clksMXSspIamwGzi9vdoCZjVCKDeGqfviOxSLN6d+BO46acAT9Q7vKQRwjIWeuRPs
z4ad4LkPFKIfj6kOPkPIh8LKjj3S5tB96UemTZ01szSMtffa76Eo83Gxc/rZZS5V
9/5SBwbLyJacuRYSPhCaEX2eNxCRe5jWyHDPCLAM5H113QOmKLp7jVkl9PPf1Ysb
vZ6xBnaE9msrWLFNek8phVQB+c71A5DtHH9Z6KHxrm+rQrSpbyibjfbLgI/TjKmZ
4JUNLp2rB0HUxxazTjlrgrDv0JWK8YAdR9X3r7rKu3jzliUEKVTvXqAEumGyMkC
5xovVYGsgvxJmNnocECwVx6AC+OuXavNyQxQV3A4ssMuaXGZUZarCj4Pg4Z77L7K
E5k43sYqRh1Pvzv2Ame2JWWkoJ6zstbaLXV8CgCb7mKxNd3aCwA0B7mVRe6KMTLe
uLwIr/Ubg9R9iPfqVp2EMYFALCojFerbIIg2SsqRi1Vwd+QCghG/u07Sa6Kw1d87
td2EhOeron0vRDabG/DGzxmw9Wq5rNYBjzIK96Xuk8AafIwBjMYi5/IXeOVHr71e3
fk+b/SJLbntDNXJsQZG8avKwn0urN1ogk17RHNXGXPXCMThd7T3Z368souQbvovZA
WyksXKDakdpMcdL28t1F5cYmq4JQ0dmdZLtaojLBKDBIL4+s00zrZluVc11I9bmH
iLiF9wOiaGh8P1Lckc4xgJG8u3U006zmXFqlzFU27q8LrV0x9pUKpMo5FRYfv66c
ugAAZjON7vImjzjZ+v6BhOw6qKtj9Cs4T+DvstMlfdgnoBQtrhyDYpN8TVjQw6PJ
VckYi4BSTu+jxDC+LzostTeDydveQ+w7Suef9b1OW9+8MbuHKLPGA8DM5NaWBv+q
okYJ31W2b+Xbh2+WNEiQZ90Ne7UKulwioYbe5kw8r9Yzn70RRpxonTbQoJJrZagW
BcYewTon0Cv9XiF29sDCIBvAAM6orKXdHofe2asFr7Rs+uccAAflc5i1+B6JWNkG
Qejb73RutcsWxvRLOnhsOYAK7wqmKKmJfal84tFXZHUBgef16jHnmfU59Rr8kQNe
2ZUYYaUr7zaduVtYF1fVGjqEeQTK4/HY2jUtdeKmYak6sLqEk0+ie5yLJJfL7nix
dKfca2Pg23SXoyVVPfgZ2Qmy1jtT3bb5jek37s45aspW5H3NZVc97NF7OP25eqAO
9dp4Mv5605gvQz4N0G8Js9qhkVJpgpcn+JBdStC6HomFUK6NfDwCfx4Vdxr09p04
Z6ddITrDixltw0q1RMzwPhT6bpUkiPod6rH7lakMqiew8vHklwt7hVLU4tebaldd
J53DNolZ1yZiyaVsNtXx6Rln+VqSaG4E1zBwX2GvJufnttrrSFilEoEp0Fvdu1HkY

53PMdMYaUW5Grsmz1ZgudOeuhDbBNonH5TbBz1cskgVPKJXrDMulKhZLGOWW2CKK
jlmUXrvsf06U0XCioh7MgI/CYLG1hlxyc4eaROJ4FFd4k8wX/djErI9ehVtzmALd
cGQ22j6LF714I0eQbtlu06FufwitNa71lRbzHK4IVH0+LEqAXvGGTUoOoE9S8mXA
vGP9a5hfPrsSLa2ew7YsyG27gUPaN/3sTJ6IxxQvs6MnMuDNruE9weISGhGsv03Ou
jYxtx2r+caR6804G8XquBRXzAbU1WIOqYFWZA7gHDSrs1NYsoYdIkvcNIR4R32f
7leLrzftsQAxr0Qykc/dsfEnYe+rHe26q98BmczQPGzUPUiXGjAzj3wysDLPe9UP
y64coe15MN3oWiNdrO4zs7CQDjw3IDxCz82vPXt3ZxJQOHlusFFPpFoZkTAParFP
nxLrEULlKDRHJBInqcyFgSbG70/59D6fIk79AEIaxeikQRGLJm2kU+miV13gXo28
hxmCfR/f384zy2Dfqmb+Wdm7CY2F5TwSyD0Jc6QNGt1B2kBQKw+6PKrCkX6FWHsA
JFF4crUf0NJAu5RtJpyGWPqpXsd3aELuG6vc97mu4V29ifRhPMjffZDDXD0V5k8r9
8p5z29tthRHNXTFaJFmnuwKFWwstg3QkPagFd/pJPc9V98ZFehm8HQFFXQO2BrTV
eHEKYy4cUHKXP18EsFoE/KEBOD0RU4Hg0aIEStDY6AKb4718I7CO6O34E+CZMO8j
ZycZD7vfZ1IKMqEAq8OUT98Z9WuotZN8+MYt6Ka3zXUaHBMng+XESVnYZcBMv14hl
wh3QC+/W5NJFg8J5Fw8S1MM01pd5QTCM1Yu0s3LDg3dW3el4ckm48Ry2ixH1s2R8
m8FVcJ9p7gn01YIQ8jUPWsoYsdcUMg9oFHiJy38i/Eqb09m8bK4dvPCncY60ofx8
vIWLkF2UCPhPdOqg5ELwNBwlio18HBCTesq8hGIfpvqzkFV7hMeqt2t6iJkqpxw
bRX0141lgigctNEA7tCV5hywWfGOy7CI7RDLzUOQFQKKKvnlweiRsclXxrx+sKMAe
Z0cHW8W5mFvebdKdVRCpX0xTORieqT9l6xi7cCgo8grO/AAbIZaJq4Hk31LAJ4Q
bP5xrrjU7x6wXG+BSnW/XZG7bwdjXR5OnToEbWFW/DLCWi6Uipph4NKuZv9kuWFr
sw2o0N+fB3AXkDWeJiJRMua3wGLUEHobzBdYFndXGirbRkZevlahcGUsOLwpfZu4
wiRqAZZvHHO20rlPZFG76unpsaIjq5tPHrya40MF35mFyAuWcjdCK2G5Yun110+
dDiJzbbi4++3Vp5LXj3fJBQbgdi8LMSI4Gn7GHVEY7W7FuGBSKVac6evZXE5LL65
cu/7k7A6lgCOVL01R8j6HaR6kLiNTfNoZVgmTasK4X5QcB0vGhyaOKRnWDRkrwU9
8u2kwkhAyWQPjJpofXg4nj3g+o4mbb3g1+vD7p0tyZSkjTmPv5pvEaTCftNvMdCj
ekUii5TFTOXnovpC7skxVvZUziEobjWEI6IUfY9t4wAJxggx3ZXJ9oz814zeSpbc
nkWzREhZGqh6D9+9TjWqY2O10lfp+Xxz1r3EYr1MMISDnx4okmVmOq/ngXjuHpw0
aKjc2/cjf/Eul1219yItOpk6ARbyJi3dz29FPIQ5z8qlccsVxd3aHF+Hz2I17K/
+qg1NTYgK4C3OEDM2HoT9BtXQrrRUB20PTWoOC+TLflrJOfqbNHRsV/oTPFFnxa9
lHequVagY18m70WYO68oshmZg3y7v6jxdtxaR8s+J+ExKp+P3lrFO+owsHu9wZjz
YF8XqvYQKjAXBKjehCF7+/Oq4HZ5iwxnFZHyxjwMTjOEs9HKb7q83XClZTiCDynN
yeVhLD2wYXf0EUKX8eAcnkMrjivdH+0McGV+nR0zWI4Ez9zSM0eHH8TOQIi+35dX
wmRkzbhu/SDvtXWEvX26HywO9seOUktjtsTF11+wN+RAG3CEEqDr2c6kPWg56aqS
zhLX8Ph62Epo12k4x25c1m4IvTmD032dfwdkovSxv9rabaVxkJ0kWzOwTFdBTEm
+lcmig8/ml5DptD6+0W+yiuX4TztvkSYnbzNyAoOrWrcvMOGpxyWxyQddCfOorNo
7nXpUeQJoJcyaS8UE3szz4mvl5EIo1jpJkO7hJyNzqaArJ/LmgNqftTS1mfW+btjZ
aPkA0opXPafgBDEylHMDFXSa09tFx7XrUF5uE+fxWnvlc3QSU1R7vBiFz133likC
S56BC5eatajwBwe7sgeCNVacWZmewZHB5wQz4g5Mw6Tbk30J8t6SBC1ykrTlyq8N
9jCj17PR0mgsVNDaoZuCd4sda3toXYgP0tcXXtfH7DohyzozyEj00UrxBge0pAs
1zd84TglPr+Wwpchre/tPAPwAFUwZBST1Hh3AGYM42a5+2YK07VklbjjBSfDMt3W
jagkUxwq1iJqNXdzi+IhfapYmLraUKDd08N6chwjoqe4Cq3IqPUp0lphfUe4u+Bv
erLDzhosZFfYU0B6eN+BZuMiTShyToEg58A+Lf0FPw0Q03gonVfQyRTaoD225Ny79
Yxuu9CIb3CpTiRmBB+M91xwDmLpnuB424mZa8lWqNuCatil7IvhlCDhGvDA3LXTTo
hWMY2EA/2XGEJBdFBmN4xC9nWn33+IQxxXi5LRaPTQeMYCnlybt0SVZXXLR5Tu25
cNlQ9+v8kmDShQa4jiaAaciLRz9NzLQh74Y9EFEjIUSKwbXWhE5Jr0jYp2WrvnXvl
kvNSX68rH5R5HcM5AWx1W7+Ia7rXYNKfyesoK7By5zeJokbV8Lr8BRmZ4RUCMTX
dSNPTKdM4f1EAgkIr6ZxbHomizNyUW41xBfnukbjyuK7vAFgWYJvlu5Sv0+WSVE
0Dwtq4mOvReFjwvMSO6oNKK2Pn3YZRXqKpi8y07nKpXiW9Y4rkb21IUZXoePCXuF
yShue770yS/0PvSTBoYaT/LAJ6fV9rKsaS4bdqByl+18IDMDxNY9D2IvzxrabC9m
hW8xhki6LaNk5tsXXK6Mvu06HS4VvtmJi7cR3gYnWi83sPzKxY3MpWconfIN7AR
DnAk/7vkAbf9wgyRryIX9PFw7mCHR8QARKyJB8Tux1fQD9ALQVzKMwrcVCWDLUGO
qi0inJyMGSYrFh/ULIqzRlr3Lw+PjMLO2+fr/I5DKkwdGLldIwnp9WQ568xYvQcO
0hs1R6VfKGWC5fFdbL07BrulSlxM26o9vtvCOlP6zXVJKaldUdBwV9Dyut5f5gN1/
kd3bHkjrDpSUPUma6VC57z+6t1jXUUA/KHu5Pe21lnNzYwprUNnDDYoWFWrUXl/n
M5TnJRMecjaVGX3gf0UvJ9koQ0rveVLrc7DYfTBLrOZqQxtaBy00X21kCtJl1B/+
0nPng78CzZnceckRbKZXkFzLOz4B004wtZSztC44RLWWsojQO3/hmRyxkTdDvoUm
julniDvnKlXpX4hLXzEXZdYfGSHLXjBR2TsQeRQ/bC7rySN6eHSUU4cWZVrAlbSE
Df8G10qUpCs5SjXn1f19b7msHEUoeGyRdDPq9H2L9sJ9QjBSXbRZVnxzssKw0iPp
3V0rdYtSDXpvt3Is8V6nmU4NPcbB3cPGkA3POKTu7gq19QHoyvPRF5cD504eKBz71
RG/TVat02RJvt+wNC7JlPvjreoo0y9rQLsKY3y5cpQlT3N48DN4IH5lWxEyktn1f
GU2PVUcJqKshjtgdfBTbDBfbmVRQkDvtaDJPRcuAus/4t2s/3ydyXt0rJl6KAj6P
b8PhB0mUKvicJisEgU4QPGQVVcfze0EEBSnSqDoS5XTbxAQR97A1nlfdjSVAS0PB
ZhCkmF2ulY6AVVaCHBEMLFsdESjr9+v8JsuvB9QQIM17BEVFTiFTklF7AubItr2
3o1TP9B5f4ctJiEdlyNUPddBKdkd4fA0UAHn14wEjQq1ldd3aL0Ln0cCO9yV7A2I
rwy9hs5tStm3Ho9kUna+DY29rxtCJUw199Dp9nfulCAGmNG6f10GVy0Yx6elC1jh
h2EpWVCZH9t7e4+whUU+4LHwsD2gVEKqtqWC6KIV2PkvVWKEQS3mb3xDw9IBm2YXZ
v7oPPUEOH1fjQJ4UGB7Xjb/460m1NtwJMH4PoJvTz78d3cueYVv+cmtkBEEBR9D
FNkGzdPknTrkI2gmWqKpa3k+Ig5fOa+5C/CiUNURkY9UoJwAqDvnADGeHwHA3LIq
bb8LqsC1ML45i4S91pVL0D0idu9v9o3FXg2K19TbFMBgIw5XGZyQeTu/BA7XBdLO
IkcbDx6p9XcdTow2iWjwSLYQkDEPjQwjlRoqgaZeZT8KxxOssxsqCmncPjn52dPvV
lQLPvRCDI4WACPJakjwlwoyLo8WK6OVbTJYRONjlicxIo5VuRskgeGNXTdZy6Axc
6LRcWTUaMZtREVLV7PKIYvN8LlHhKLFAKoANY/dXDDhgjoxT/8Trg7eucbNuCW+m
Z3ym2iUAR9AZFLXYSAZTVrEX55Ggkxl8iYPGC9B5bOXaZ2ppDFdfGjN3pXdt1Mde

FzZ15uhtLggv6IUQRSIAWEHPLRtgHvxUAAaId+29PmKh0SKVNig6gPO7EfH8PYfn
716MOMuedZ6wLWQ6jq788F61OuP6wPtBFOo2TfTnENpVHSFvyXrNNdQDFzPBB9MR
V6iQ7XdoO9X5SJBKINOX142eFsthte2hCnl/hzvAz8GDMvx052bOIwG6D7mCxlf
x827EJyYccqrhME5odrUHOXKksWqLCo4TEkvhaFRt/dx2Wd77xIy7xLE9u51m947
Pip40tdRfXmiBXRJt+CchJlQtGiA39HMSercAI7fxqBmHpN7WNiMV7YlUxiTmLG1
Slx0T3TQXybuoqx4Dc3r45wDnOAShM6K2heir6+VtDsT8QQiUTzQcQUPmd2PY0DB
6E1OmQGoF61tPjM2dJB+KSISn+tn64oq/IKBD1MEiNqUekyKkikSiQgKn3aoZGhv
iyuVcDRWePhiJfqbElLc+AxstTKRS7DnDrnK7KjkbhZtW3mZNNtTtDBDEW67Gs0
2Z3qWGOxc773ISbzhr2y2DrvzIx/578rxunN21U5Bp4UCoZcFMSJ7hJrJdJG8hts8
DsgQYnyWyEuzK/d4iBvMvx/onGfRvEAD4H6eWSy6IxoGlpRXRqP6pQunPRYr2GxA
qup71PVSPQB3NuEWJk2YdqyVkiQaSOoElqhnnEMQ2pUNSSedVT5aRviktQ+fadfl
kmhcvBXbBmoOiidANaccU+KIxhj+SAX1tPW8AUPi+bWU7fk0DIeTYlHeRjK51eV9
xfA2ZF8W0gt6Z7fWs7LwCzhLU708YGDAA/JlaV5LLgv+u/+JoPKCGiOOERCmR/zs
gzWl44st7zaJNYhSRrcEQlNyfrZj4YRNeuA077WEHqEm2GZKzrmCjgKmjWxjYyKj
GTzMzKgfcWQ//LuQ3EwQjyT5zXoXNSOGmbwUqIXYbbMRHgluijCayTkeAYdWM3Bs
HpYpOBan394EGC88GLU1Pd0TPlgbOQybarGfd+pRp36w5hUVSfoguGRBnCoTviYA
RxfyYeBcT3dgb7Sk2LSolPJU0RK5bydG4/t8VWlo8iJU7dh+UNh6nIzzoAb07htf
rTic36Wqr1vcqu6zQpn6DQjzPjzSqaQlJlVn2SmD7XnX1smvMZINNVJk4/InktX5
LXxSGBcHT3i95EuJePO9QJCALEM5Rm5VHHWVA97eEb8VLvxu8r1+0BkEoFlhCskX
7vEZbbOKipQJ2Fu9SuKVv+f+MwxJCIXnVzuqGPBC+nL1pYFSVNH3hvsAXrtgG4yy
LEhwdc+mwSty87Ih4ABMQP1+YwagoqsfEskDLY6AyyMv0xTRCQGIiUZZv9CCfASE
gJ6OFVgWxv14ztNqIWR3JXB4s6ER3Ts1Ivwc2D99XpnXAI56aE2+DkoTAPiHeFc
HAvR7B4i484M4vMBc/HSLScU6R3A80zL6FD4Fn2VVA86oOE5ke/NGr5mjTa0uwqp
5DAhdWeJtb6BfZd230/+hYxDWpSXjE8cFBti+Z5j6DW8ciCwqGxQN5NQjCdhYPTb
7JA8CUCQagBpVw80ucR0QJx3M7pNURj48s0xp51H6FB1kZwNwGFGQA/hkyS2Aimn
nIg3FXiL8ID1SvmMNXuEl3cPpe8RFHpOYje5gj2b7wO6xdrOciS9gABNUqQxbOg
BCTq6W71f6o2MssgUGIaFrdsYwlpzkYrAtRVUjboncePoiAgYKU1jHw8Ro+mQHLe
XOCfYopX514Wp9AZRGKpUMR0Tww6t1p57qGfimUV7U5ffuo3yollknVrpZM3XSA
vMuArlxB/I7aB/iXYt4DRAqx/RJs6Tcy2W6ZncGeV1SWGWv1KmZaU/VYXboMj8vq
bVkeitlMUJwvoptvKxRCUXGRb+YuejEnocA9Ww7eeH5fw6KSAM5angkdhtJC1bhQ
bNo+5F3eb8zLflGXWmIXeWF9Gng/67XH37UO310OR2EFP0P37V1KrVD1zw28a3gX
PpT5ZhgnBgQXyNxBO538QH2HusTwscbKYak/mGhhQ8qQZfDRnf/1mqmUpN0ZadZu
TDbF6JWDPhzwUtZeuIuj14EjQbeseFgwHVZ88yB3nmT59dDFC3Iv0JmhxHFORSSX
tTZjigd/FelluIqZwN8FOTLS8n6gAZvVbvorKpWrfAPongOUQbjdbwOtU2dIZYgm
YF+125XVXFha0a2LRiJ8a5NkwwcVhmghd1E3hyYxXV67e4WV/IE0DCPSDMP3rmw
FMIOIRHN3R22xSIWxgFdVXk66yqAJQfTk9TvlGVUnGYrqCND6atzBLEHjsxeNiFp
cTbalcP5ynqW79BSDXg8IB4Sxos4ZaBphms3L5VmZECpyaFeibb/ZlSrOmSOSiWw
vGHN+djjVQaXleMY3C3g2qN8rJ9j6WD2L+71sIppZZDmx1I3zTVbWzYRXdVftKY
20uwrS19/+69IO91CzHa0boDFm4d/obLKDCrIMJF4thQ+KWO7JT4KFrUxVuwXoYh
zoIrNXYZs7hyOeKS7S17zwKZxFULG5fozsZVEOem+RzeuJLTnTDdff2iV6R/BL
z33BVVelleA7YhbK5/ec7AlviCklyTcmv0A5Kt3dTWLLOthvkkmjxlri7WKAi5/N
lgCyIU5T1UGnqwf9/3B1FVuuAkH0glhgwZbB3X2HBrfgX//ylsx+pg80XVeqqisu
b7Z/7gdU9LFp6aYaAaGXNQbDQhx8KDgYy5Cqa7XWT0isiFEqL65eD3yZxdwWbmg
jGXWge/zya4jKu2RkY05HstngNjaYYqC4fFRrDDzLXugDyS4ieJxP6y126ZKzTNW
5P4Q5rh/NPSMAJdGhcpiHTB7SdohnZb+Q4NPQ0CRZwgYitwHL/5Y/pUzbf0Q9Oca
AC99aZ0jB/U6PpHWLvsPHeutTpZYJ6aTmh0rwhfnq3ADln+dPEZwr3v8cn4bm1yN
Z74kCHx1zMrddvnlvA7tcFYVFM54vT/dNjAl10CTysYj0dPcSRO8+mUawZxpXBEz
0e5k4U0QRcU79s9FCYnKP2t1oZEIRvjTOBULK596+4TxAc1S3p4KWBvtTNkE5c
HTF6KEaH8klYHa59IEyycEyfrYnHrjNQ/MY9idG9aIzMPfoo8L1LEFGjNYuCFuKw
16WFH/I+pv/CfSiWQIGF2Yegynw+WWxsxejJvitXLN6z+8gyry0dEX6eFhRHlGQL
z3syfnuWnXZEvRjNY8BgwegduRaEetpq4gx5zhU+25otaU5OWkj8z85z4FYv4YKk
HM+7POsCU4cdc86gWfVKBKfXX9Ec3E55FrGmrTMGyJdOPpQm8lrWEWtnlk/VqUaW
vuogN+5yrrqQd0M6811cuZfRjzmRB/gzz2U1PGsqm7wpLEMYDlFjzPhZijgwRTrY
oF2ealXgEdS+hO9VSPYeb8ea9gxGS/pPrEpCfD4hSHO3WRh5gyfCClCq6zJwnf+J
jk+0/QSYQISOULhglrtvZ6cyfORfzhwwy0tvtb19BU+/OSFlv6blZO1t1qU1BslY
0vSu+EKK3o+/TjhIwea/8bP98Y0VJodUAYf5psEmSJIEPosLZy5PWLwgk3PYOakv
s1Wi6a4pgQ6P1JUTX8K0eqMkXqgmUuJRQIX+HXK9kCcKsZr4mQsKeuBHAv1NHF5G
wJ3fHfgGap6WwzqbflUG5KcWsew0LCqm4Ku5c2Z3SB2uWhJPpbnOWT/Av3nB03f
5ksFEoFRnQeMtbXelKIm6kuMWhw4msAo5JqOhj5RmYNgatlc5LJYFT21xuf4gHyX
JUNfTa/XupPknzbjz07y1PQSu9avZDuIh3oaX5w3eJBhzFA8fe4V+Ch6zfzpl+iU
yvJGPjXzrbIr67wEayLk6i5I0y4OTCzqaH3X5B3OYaOygcMe92JR2765dDkCz2yo
xobf6eNz1XjDYB2LYfce9Rx+/TDegV8N8BamZJgXLtJr6dL7KdkTKZjtc2sPckk
ni2wnhd8rAnYvt1XSiaGyV4Y/+69FiRyEs4yzcdBifxwzPssEfqN8gklCF53d77W
omiz7AmOMRSUqaKirKzWrBciCMBPDsYbhlPt6TBifrl6Gb6OplovhyfdXyG4+Rzj
7Oni7rp6yoME3KKa+YTUH+sEnGRvKxJtiekgQGWo5Ii4/wNKBJSO0HVJgP/kev+
Ev97LLXSHO4nnhEAuONGNSZCPS7K8VWZk6QALE/6aU6F8xvwtUTThZWbKSDY017pE
iP4O6t9i//+ifi6mMO2kofJ9fPefQEzYTyCAGFRHM3GK1K7HWaoasN+d+UJgygwy
TEo5NK9p+2oRbi69nxyQo3SOzWimjoQU0LHUWK2rQt+iGWK+A30tCQJbDTrTfY+g
7Q9VLR+k8TMkqFiSN7Y+PwAX4oQmer7+IqShBEWDBXwSaZorXmak87i4hl0swlN
QXI2YzNRLaWw2ETbW0C/zlMgM7DPRJevnzehntD6tttkObr5ONSNSKNZvHTec0PA
XVWk+RA9UZ0/gjKFVbsJjklNZ6BvOwlo92mDYtqSYZVw5+zagLyogK/RLc93X6Pf
qpHhqsTMgnPbPR9/g2nAZYJQEvNTIM+CbpvSIYCg80ZmfPjm7V3ttgXZi8hd+dgM

45DAiGKKrTkAJaPjPnYkEBDnStfd4rMiRuR53yiYp1PUYNCEadbXEtVr46E7U+Xe
dK7ke09nmq6i5hP0iAzdq7utRhFzbuN6zxsyZ8FmmwcJ/IDR22GY/4fuGsANv+0I
08NNNDZvvQIntGfcqsMHZD2Am1CFN3b3lX4iGz3MmROruUN/LhGVmfB24J88vGLTH
TBEXamaLn0Ztg5fK15PSimzUkuP6iG8T5qnM1MPU/pkKKZ/Y6KB4IMK1hKEa0Xk5o
BwxREGZyQthHERFJpdewOCA0Cd1Nmf7EcdaLg0tYaJ9ZqrvMAPsEdvHk6W/bhHxO
3KQe64a/KJe95YSEBiPjohxE4AoZt8ytNSZ7RwYXwa0fsI29Crfig7bVZanEcb3
P2ARMkzTTYu7KrCzx3MSNh/L1z1FqGHonI0aXuNmgfrXYbDk2U/bQGGYG5nf4Kg5
Ube5Q1VbGPNpQTXRvY7CGMWMu6tYgwydkGIEvYaL+fYIGVvuuvTPlyTHAmb8nDPe
oxm0AW1DH2JXXxBg4zxZqjskGU0/2DP0ky+xkohVWHPTaC4oihiFwKbP+qbZALzm
Hxgn9K5J0decphpohr5NzDSzlq5IEvR8a+mSFOnRfjiUPnb3AyY/ADLx4+kDdvde
mEtu/azzhfMTKZiEmVfZa7obwlfZfVHE7Zo0xCWDROXCI4Gfuv3MSrCgBOJst4di
vxKKDP7XkPr1J6ITP413D9ZpnXXKHrwtXWmNDHav5ksZIguR6qZgtzau5g0R5g0/
O5ZC/uBK6eJOTJHq/xcm7rglJchT6nE2Ppz7UtlYK3MHvwb3sAAZl1tcy9LpaB+Q
33vP7AFRPOffTfUrMYcf1d0bj0dG0Qnz752wEdvF5Mdn8PJHGEZywdarDWPBi+Xu
Yv7uJpJZewDBCjk3LzZvRtn7mD+/HG/1ccgy737fAHbxU0BwjRvteeT8nhYVANyD
LECG4CuGv+ATz+gRjNRI06puJ+e+rufVpoqSg5voQE3ER7whhiYk85n4gnNOKBwx
+KnQT+EDyIwlwBO2g3Qisf5zQ8xpASviFp8c50uai/KlP2tYE5iLde1u3BPjzILX
louKMhbVzfo1furUk4TFF1smhf7MghMh2vlpSWIT97KCWmOadpcZ1WO/QfzrqIbo
i7TZh/uQt5talh+9R+dnBrmCQfCcfrAHPq7w0xZKvr3NdOW4Ad174TLkW0955eS
HGTNflvW2+7YRTNxEbCTpXzumQ91NautsmtDjBwouC74Nol8lV0WOU4IztKB+UtX
XlkEwGNObrvpyYW1ihHdOfVPVQ145A4H8w49Iu5mjlvSjtrCzsQtXlRjYaSmVv
nhxd9LeipNDt5gw/RtxllVXeBDg+WyzotV+qPqajfnsBvRnKF5YGBWxhK6qXjrsH
16H7X3UrNkpriLaqQLCWKCZW131Dw0yPP8hp8xwYnz7qBzaXCd0AAHpHazon+k/9e
c3yriyLDmFqGshJh5lUdusZeuw+Q3YXHZPbs2yacw0VwQFeZy4c0p7dYcu795XV
MdZklktQisZ05vuVdOSiTaddotBssHL2wkc/OZ/spLJToEaRAsFiHiPTNWb8DiY/
12QXQIEzof5FgsD1dkPCOZc9IMOqLTGIuM+tMMLfYJjRtRltaQDrdQr+0JgNss5
qTAzgu3EUjZDsk179lW8donkVdox3YqQ3lvcVEH/Y0P9qYlMAiw3IuM5CiAl2zj8
lDngHovmMmq7hIHxobJC6XS4IyUP+HZy3UUC3bbMDMW3tETNVZuln+eOdYL2yWW
eW1OH7ZXFZaPDVNVhx/p36FhuZMqXTQ5NGPVWSDbVrcpzM3bqCcJf8JI2Ufofne1
d2rO2wLp5L7j10f035WcdZnk/L725+s00/7IOR+K2iSycQw3feEqzLNNL/HxWiIt
zOXiGMW70gTJdfI7j1CgOa10A3Ey4x6yoOSGkFQPFu3HilYWXG4wWbvwZziVCuPL
BuZC9NjJBTmpuzoPG9kMOCs2eJOePGUzdyZxztgHiXcDn68IOcrwMYZgZrhnQSZN
0FnOrPIks7F1lnq1jrkI1e9iOkKuRAi0DcrWbbjg73hwngi6DHigj1pluRwF2U8n
/FoJZqmdemTfh6xXsNmNa0200i8vAVLw9DulSpvBYdy7hJQEEDXlK/ExLmK/T7T
/YzNCCat/qMvaStCJfBzX+GxfSTGzPqxRQJBk9p2dyxg3DJ0MJxR3goGFRCO7e6M
v5T7mcDMzToD50tKRv92Uly61Ez7HR9wpsN5FecqogDfdbA0sRba/uaXmK9Gb3/N
YuukcPg+Z5IAMyrXL4tpYvCzD6+pSaXvcgdZFPgG/OmCuTihOVj3YAsnxzTY9xdV
iNyaOwwNJOF6JjCvWAsod/r+IqmMKgUKDuvIOmOrYBRrbY/XAMJ39y3tJRsdK7Mh
DpAWMwPMR5y0vezIOM5dgUYCV9n74hVhlLaUwa358aw+TTiV/vlkUnrRxc3y+L1
oRgALFY/C9mBFs1V+ZPZ+x7nRfaKpupmOyz0ZCFX1ZaifVZ/3OpC7Et1c+9emuk
j319ATgMWiEGXalGfaBjflarHQBbRn+f3Mx/LLCaUVht3E7SimitTSp6ESpJdcscy
o7+JaaEHl1fQYOlQSKEu/sqAZ0Fm3RLaeAULZtRoEX5eCt9U9pUxbYZKsHgsV3yO
vW35cPGJs6tGezR/5z/vJxfC6w7/FGQq9fbm2CSBUQbwa3YJ2cf8bIkNdVARjZHB
NW1WF2niJMbTr/iLoqjFQXDtyeiH1z+j8X7M1twYVBCWJfSbYwInXCQn+gaFb7bi
iUr9zrPVVq+3nuPrAuKC9rGTNSCbHjd+B/fp0T9frCx98ZznBQHKAxv9cMgRiHwb
/qe0cnr9/eCMHZN+RnLRyggjemlq5flwOfB2Sj5L36ASFCK4KweHzkL4lRgVIXQV
sHkmgj02iVd1UlmzeS40uBDYKbmtCjZQoz9qPOA/kwsWYGD3UziZqHvT4uw/Vy
nnJ6m/nv9b17afzxprTbc2X3bkr7JyAdT5f7iTiJGP8ptGduG97HPnvf+Hc+9Y9g
J5Pp0EMuXr99avbPfmMfryAhna9E0NeGGiaHvqcHB18Qlkizp0AG63s3ITG8ryhQ
1EZGi8VckZVplfImpheAo8guDHa0wBhZ8CmZOCsO+q3+f0AXMrrP9M1WRci1o+JI
BGdVmmj/Mc41HVcy7gElkkJbXwsxi6j+i3kZ93N+FYn9NA6hWgcpX8vzug2xklb9
QVMt11cs5g35uhlLLqgJftfb9h4BY+XkMyTOQdam91TwMt+vO5FH5vp3qg8LPYmkV
2Vmtb2b/ab9GERMhywnQ7jmpR79LqcOLwvp+hgZOhGODymARg7p1DtsILxf1fh/j
2X0j6QCzYClKXM20tHImy8Ritpbrfa556ayy8HvsTFu9TrLPd6+rsQDUhSNy4bVN
LvMcolCupylqGdSk44RzmzNJOCYIIRiwnKK5+JnznNzhnXwpjOYwpy2W5Cr5oCG6
UXBC4jOFLx+7V4aB1VbhSkNvrzGf1zfczHKgpEEZ048hvZ2a5KJ304szcn0byWNW
jxv7Sn3Tr2cDIpt5XXzffnsYSxW5fX947EjX66B3VsCPbB/wenpndM7drPF1JEpm
rJavosCBVLXSpOeFM9ti3mSCrkrGBuroVpKdmkjzTSwdmUjTKHBwxINFMKbs0vl
x8AqkJfG5H+sQ+Jm8lzM9SYThfrQwz5KMG7StJFozpvsScarSivmYhBr4NkL26+4n
CWTwdJeuPpkoWBGsYftzuZ04w0z0vqo3IQbkq/VS2lOH0eM9z871gbWLamW1QfWb
/7kdcsaBy22s1L/yBM+K8c/R4JaNklwH4kgjB4TYiHolvYrsQ2blbGu49OpJzYD5
et9jsODVilDzEaF2BdV2SbeXJ9ULE0C/cknYgT5pYB30qfgoJNRvGdmeUaZ3yqv4
+VchJqRJ+XHW4R9nHxieko819baeflOax/oO5UnNtiJlZ5e13r7XgmNwpxffdnI0
8208N+9gfQ+2FEM72nBzO4DdB7xw9vMUyLXp3znXianj1wa44FW684x+izE6bDQF
dt263dlFEwIntbobotK2d5UocnIc34JAYP6mO3HyG/NIF7NyAmVBvkzpQoizcn8+i
9Fa2fzi5e/12NN9TNZdMmsL7EEJLg8pP8IrA583S1zkYGpRzZ84mvFiMR6zRABz0
4n6lsOaI810UnirLopmc0iDdnfJlRxAvm1h9Vz5h02bk3QJbTKgh4uYESBEomfB
Bn2LwJyYFIwgJfvZe9l9ItYLRhZFMPlrCtinoPtRCD7Vth8wX7XtkmZoywQhubG1
GafjVH5U8NQZTek7dj6LNxUiNoww5s3j3/DnasQpz2HEU7Fmt5vKz1n7PAGn4lnrt
wRqglBCAYyrV0PcARozNANRHSXXyUs5UBPLmpA+58tE8TFln+D45Uvb5YLza7py
gJGU/NJaLdN6AotPCGF1jFVT/D0uRN6iC2ZPlOu3OmQWyjLvFb/FOUp2u/WNO10
LamwuZBR1EICzv8/sQA2D2qUZ+TD8Hp3UVkUy4cGI/2qMelHaFn4szwFCgruxVW9

RZosO6q8e1809uUCQiRqsNv83m9xba+6zMckD2d0Q3aCRK7fIsbJ+J/8/Ux5ecCu
vs11YoVqyWgGli0V0EoW/wQzEE8hH5udtnsFbX8C9WvS/PcmkQ//fRdv7d0mzNOI
vU0vqv70/cv0Vd1dHlteXexFBlfeRMh1hr/IGAfuArvADCC1LcyqaUINtZHZEXp
z+hikp083MDO/F2GnSmsgtJu5vf7as0y7I0yXwFjQsDjixFOWx4tTFRLX2ZQORNEK
9gHyp6Z982fwm9HGB9YgVmQDYzTXos0+IsqYSHntDV8nxJXQmva6E2Ro0qCZMrDm
YpEMrvXnYrcGch6Ha/7nHqJIVrYcFQ2DMWkFjaokqSULylcGxtMMnhrmG6TUnNvy
ymFrIt61/Ewsav78YcakznAajCaW2azoJ9fsLUjZer3f0oe9SY7uz5AJfxwze/Xc
TQiqr+X4aVUjfl6e0gdNrW0jupirtaPvpCnkVzZaP8Urf1NeupyXBVpR5pEtKCPv
OVqBy3y36f+hnyU+PQVYvvceul/jbECVnO9ZQXPfhexAC4ldcwe/fYEGweddMlbK
QEGFHR4vNjNjEazawT336hkK4cNIv0zZ7PL91oYy7j7MMJSn3M0k3XRg7ZxpFRu2/z
ximTV+LcULYPD/IYolGS+g6fga4vhhof9JvcayQjBMvzA0t1U31Q6fW7JlWjjd4X
FmVk2emvA2ObC/5MAG6NREhtifY8ZwRFw10HgVfHOBzWBZxtuBCPZJDWod6+d9a9
E4dVi3stqB0SKulWgzUr1Cx6CkhW+FlgNhfgG9N0foiEPAONK0Xn7V3FtFBGxscu
3k0xPHPgqWUUAVPd72Y2LPjBwHLEQ8zjnrkgK2CU0X7rR3Fi3e5aHdn7SX/2H0w3
XSxznymCBW/BgdTAjciCR1UIBDR0WNhA31//mSh/BV4Elnc9QzUktD0iJUPuhUX7
aq3PNQa5qVAXX5Juf5bzGuV4gX7BENx1XAY9FX54TpgJFzBIUNwo0g+c9SgzokdN
HPibjctM0qaFTZROt6yDftFqxaKG+zJk1lFiWPzFof550oaKsD+VTZFuIa7B0c34
lPRyPb5fuWkLHhIE8IkzdJXh4cKxH7DcWcVTHGtKDMvpMeMZTmzGuD9A9N8JU08i
Suh12I1vFjpWZlcrBTx4tiDZc02caq/Y+yQ/1L9/6g/nrQ57K08jJtAmcIbvtH6h
zrQMYCGanpWXpOnCuSssyo/lBTIRK1Rbbe4U+O9RoBs4rElctH7+5ypct/yMy60M
kC3VRmKdQaDKCWB3KH9hOzV1Z95rTincAKcnNw2G8RsrfaOdInlk7bH06EIVbld
nO1PGkrge2EvtbGgyDsfiYkAgCotUKxNefVdNK4nlLicDwGpxWS8j125OH5ZE0U
C+WYHJehfudPQPk8kxh6rys5A5R8fpgkjdmAu3NMQRuXhXvtCj6j+LdHtHe11Me
UKYlKyhFvWUr6wBbbsil0sY9GeveoUvIConHnS/pxDDVi73fpyhiCFsFFhNKC0io
pzygl3JpyUDntuzGUjjevv/eAUUuNDGuekQ5+IUY+9phfQvhkEHmutipCnAaDG7X2
C6qncrQoBM++a823m6vUzRxx2FaG988/+2uW2u8a0abuG8Yh9BJU5drdT0Tmb81j
vYhZfjv4tIg0n3BpHSJVa0MamfHVBzdFnk4L4ZhSCH0Rm/RGQZiFsu4Wvvb+WmJ
rVf3EzeeAz+z71EBN0iav26/hkdAVUHVCoWtJAZ4gcCUOMlhLATtu5YS078KtLar
ZXylb6nbzLk48Wdf0BYX0sX4FSEqvvsN5mz6HKP+0fuzvckkD2ay4X7miz0lw2vi
y3Zeh11ClIUAnRQtXTOBqUtcXkCckuEsDRXDJJKr5CzogpR3t3mceoRmMBCBHoUs
JrJvDRUAyDosWIDMTXeLp3cK0IJHJUWwHmJ2Kt3FXVtjIpPebDS80jXDTfZGO+8Hc
15T+v0th4z/O/MF2wR5vOPWjy6c+Q2d7NfZwBz9wmdNV6QoqdBsQgqDiyysOvizO
A0RzXHZI64a9W0D8ydyt94R9bbd7pgnNYfou1l7z1M+gT4dXfE96rqe0JVUuUJUI
VEQhs1Q2zAvJktitc6Yf1G2TMnbUlKLPiQy6IViYYdic13kwKm07ceKZc+1Qbsj+
yfulfQk0ui3N5rWebGdQoicUkI6tUVxf9s/RiFUP66KD9Kexy2BSuEkwQ1pjHs03
aZyEKGPMOaMpdJJ2M3rQTvVXq9mzgtXIGaXl8lrXNev5GYDBqil2ppfU1XdIfnrO
GG4ly5u0q3T8dA1AzbhF6ANG2bzjGFxLSmlM8Kfezb+vrYvb9EcaItoANQd4V/w
mJNEOMBzs4NoWkcnqgcLhI3jGdVa7nshfi78gEFFgT1Tq9uUjPxp6nzGikLeYHni
qVt6UutVGUWJomBMy4YpR/jY3dlry5bmO+nFTN+8a+XL9/lk4d1EhUjjxTBjMvpd
EmJX/el7i32jyH70szftSL7NMAUcellBCSGAN4Xu4PwtYkPInxc07FBhAeunN0dX
T2ZPbaZ5ZITMRWRwN653M4NiQFTN1iHVkq3Nw3BzBHs1eBfzZf65/3NMDfKhefK
GH3PuVMa1B7c6YYjrp5PLEY4hj0GSNRiNZRZJipNBVK3Yzl/jqUrdG14Up3Hi/nd
KMP35XWKrm948vsv+IAqDK+sUSC8CB1B4OLK/Js0YP/KrHyyYOPHMTuptvGzY8m/
QHlm+73AERGAznf8Vmmgc+L0ysUS7u5zYew4fh0w01RXVtmKh5SbkWjydm5vv31W
KmDqxDv/VMqEIPAoidyT1Wa9D0tVWDcN/fkf+cd1vg1CITtkmiirgz2QcTDdmFbU
n2fpo+4EktgjpbA7/Kt4bv+29em89gKqJ3258axm74rxHZHDYUeCys09A+9b8t43
RitkeYKjyOM90xt5Hwt8nNm0f5RRLZVeP/OoiUCab44D41OJqjSnsX8WHSgUZXscI2
ZvW1lDufRSyY8Fjh9qDTEicXoLEMCFJwBSMkrYQRQ/MCLEoG4Js9gB4dQL0Kbh1H
xOuXFa4k6vPM7OE7BzSBW24NG5jjAXziCHIT2VBk+GYB9DaKcJcg/Gch3K1pzju9
4E5d3iXv1kAwX8+i/A3CHrAmrtZD/c/PtGk2wQdHwumlc+pEUTHtnr67yYeRDX5B
CYyB1GwzmhTg+5Q5PWPzFzBqtttdwGsfkRBN2PC2kNTuits86sGhahGxaHu81pNBi
D1E3CwFC5VmCXat5jOnPGzIJ4bhQvuhDDO9LU1D+dJbFVa37nw5wnDFLHLQRNQpa
V9dg5bVCehMTKydiheSEONTHTxeXZMAjwULZV+louU3G8gXLE1IILto9RqWYtMe
YF3Ghshlfs9huZTNYqsgCTsr6Eko/KReFCULVqjq7VlyVuIisASjyzbFVrEngf71
8RpCq9ZNQfk1lnxiNXMKq4RIaip/wvZwW0iFLvbyEyJx9OpjrwhjfbUYBboXu2Zg
vTDSd+7DL2xMQ9QOB71RByuqx5ggtu25mPCZ2FTNFnf/QOk0/wBjUt14tdr8nME4
jDHQGPAGMmWg6ulP6Fkvm5Q6JOjz9PZ+h10kyPvqvqtIh31ro1BDZ4YXucuIG+0
jle/rX4o5KhHXk3V4vZ90uLwjMaCHOXcBnbLn0HUSU9cEcJLEDDjULrCLxdicr9
n011En0W0j+3+cbGOGCrmtxe00W4Rn2HtBo4sOU9F7NfmadAhekB9YA1QY9HwFYV
o0PJFn7jw1Gq1Ucam/b1sgGoVgaw8yFDPxywc65F1J4CeXGo5miduIZUBQCHDSu2
461Z81th09RDw7NovfAb8Rx7s71/vQEn23pxScuBggf39VSOWWlxqW9ecKCCyLfA
yfxLaKgpZpnPbm6Gkr2cECqrVLZ7x8z0pd5xTf8LbMJOr/BZ8sYQjbd6Zhefgau
Rt+TNft23pfET1uBS2DTExi239/ZcEu/MyeBiFXAIPma9ayULDT+6YS/ORIb1IUA
P/pikWEXFFpuBUT110VT1w1J/RxGivlK83389mi69shyESmLDXu/T93zNeMvHvfH
ChL1Zyeko3Thvtd6jWkN7tNbeLIMxjbqq2ynkMjtaVMAKbFvLDJziEL2P81sx+BR
6bGuk4HPKxh7Vb3pYukVBtBXWVhs2asSDHUp/ePlpelpBHYEt/NsQF8wNUjyxqRyV
BTvD3sHdZSer1T6Mza2hjsbQ+/qidBzWfQz7+Rbv9r7EzoqCMvGtx7IpOhdkQuSZ
2Zv5H1zk4AwYxe5mQ5zkS56vYIXMgIyC6AmYnk3B5YyWkNqW5LCVr55zQBkGnJ2P
wadARs+g7GJ+0w8U6FfwHryaPDdnko+PSbc9S1Jrf5eHrfYZLM4535KhZJd64c/U
pXDI06OLyKaOMNFaeUSfAM/gsfdb+fcFpgXQQMqmtjnPeuULiIQs9Jufu33NUCvR
hBtRT8afXqqE9SkI10pHJ4rQ0MHwutn3+DPATTfSPqHZAHHFjtbd7fas3pIZPlj
bBFWFrZJpmc4VX4ykC6W9IwdjHwCUNjnc/MbjBNRfdrcuzlxW+PZ78wsAZ29TqRkH

nnnwsdz0bEDpz5ownGRISCbki43dZZNPSf1u/m+kCUa4Onkmc/VbI2di/PHzOfV
+hzvRvPFSPP53HICn2r7HTplrIRwDlsJromLbFEoAh4Kyge5SRHbDrONQI6m3h+c
pslSTK2HjZWT/hXiNimfEPRCy2n5sEVvoju6eolgQhC4+7dobaoOn+MqAh7Xt530
gTjni8JdSrApY0EgP3ZD6z4LMS3AUmC2FmJY5yAmm+ZOIGT4VkaCv6ryt1Pv1Fku
qOM6BWQbTxTz75vZj3Wz11panedrMpKdUEcu2qAH5QXM5zcmM6+KMF6UbwrXvU/1
oAQf00I/G73HIpAP2WrJbVGhLCLCzwQmekMlBcameIN0INGo9nUhP1AoIuum1YTD
zi/YH0VJCFvowWCE20p5kPNWmikq0N6qu0XQUqv9x2D71s2OfxngRtdW16WIEpD
01bR2r/2Bq9bjp5f1d2W8LCBWTAI3Q4mvqg8uyLGyp1BeU02CQcTg5+FmONmHa/3
ldhG1VRhGxAF/1vKrJVRLfRx3/4RphM5KcNyBtGzB/kKGBECMuzFU36WMB8rBUe6
SkGRsomZ1256k5OwxZsJRiqDYt4GM1RVUEz5TRXDMT0rYhYn6u/UwaFQBLac8agf
5Wog5rogZtYfWaCkQh8+jKTnielxLotgwvQ9RHDiuPy5+asNifd++5FM1RF+Pv
EiAWWNG2LvJ6hWzVjNpOtejvSTNGS42g+UH8dlCW6U3Z2P32nsJlPs6u4bFIu49
BH1whpAVEhuAOGj2wFJ/a0/9UKQIeeGxIwuDHuHhz8mT4Xd9USD4BzW8URUPAWiR
ZFH9KALbMpayuJRTVLbAnkPvxA+p1DhHY7gNv4FvafHLTD3wDf038vmazYssibQU
IBhk6117sSormGD0udBGBq+9I0vETdJAN/UY+SEPAGuGXOP2Bbs1svTms2cPS1qH
J/IrpUKi/5Rejmi190PK1Q07J1i/pLTFbx/OUBMsjpJyJRuPvblD52A4aHR8jhOc
vaMfEuId3nj8VQuUPy2Pp6NabzwYK8phJZSLqzibs98WR6szimNv3RwWz69aVgWe
hGL81IHimpw7pdSFxlopRFxjOSVmvdv/f0/037FtpLZ4ezVBfeOWp6GZYJBXGX46
9P1sZFAqgaZFU14ZckwVyzvjt3z9KIRf0fcBd7FB719U64UTSrljWt7kYU5W/WYR
hX3L+OuZ225t2nHHXgppqv+HmIww28CyxHIF/hnFMXMD5yZ0kjHVNNGNZPZtI4eCRE
5SAJiXYy+ackGVKh04cbe/2+1cf89kQ+E7BXdr5Rm5f/TmkmMSdzarbyf9Oz1bGw
iUGoy/ZehYrn8WeiKYQDjfanODT+pMc7ktho46TU5FJQtQVaUvaMjy/9CGxjHODy
/2arGcRbMcgkALLoM4N8uMA7ykUw6K6fi+crzkdzEgYUHG2iEhWWpERL3m53M4bo
CXHWHdfU95a9KzVhr6/wbGbrPYnhFpkZ87CJqyQpC/G9vxjy+lxjiHl8X05idvWC
0Q+oUKK+c/BTW2LDjjONWxn8jACHdIJRmsfzJOW4ypvxDw0YyQToXk9Y60yCIRD5
u/gu0+JGF61LUDZFMbwhT2qRS+jpNycYogGTYGyWdYe7i0jl7uMXE+igCUHx6mON
ZHSguXzslqQ4KxAR8+0GQV+u0Ned5aekSuqW8haAhNOUwtWkdTLRA4aCP2wfnAt0
his5+Mw4huE9VX9pj/CY/3P7DwY0gHyinkhLwMx5k4hs6U06FSv0K/P/J08aA
ppBi5yPVNJ7Fui7/fAMj7101cNtBgZ26agP7WZJcUB5TLvBSDuqaFINwdiCN6B2g
1zg7kc96pF8gnCfqs3LAGbbgL9hiSnYqaNs9D9mfVEfB83Da40+ogzpr53Ewa+dh
7ocw5CDF9fSpKYfgnfG9S005kxcUzZo/oWn1Uj36Ap7ZA4tHQglIwpDiSV71/L5f
3+n3+6arobfwcolI5DTyBHvWHBga3adCgZmuqNz03waT5DODNm+nbHkiS4Lp9dW1
MI88QMkpx4CVLOqyPogrZya1RP8M0FI5ZM2/13v8yJJCgAZ/+vNjURSDxIJWIO1R
WY0ESdEx+E55z5FH7C8vutkr3M8ND11i0hY0Sik//mltbwjxgiHls6Nk16xVmwi
0OPf10foA7Vuw6g73fPejFopN84wIYNog3uR014Py6WfjXk1Pnn/ivf7ibQvKXZP
TI0UsQdAha/7m8X3PtI6VNYgaJvcs8Xin1NxoHaxVgDghyJuxsWine7T2Omz7kr/
oBCv712REnHx1jbiLF0rVoLDxXc7Lj39039FkECc60c/wd1Hx1XagiWPru2w+f7U
Gh9vCjFmUhhRvG3faF5ET37e/3/ArtjFr8CP8aJkFfdibv5gd7HW3ZHD2NW1sbRu
heRpxJRI08dpHFnaVek3Q1GCIytzl/zOCW7fSPT6Cd01j1+DemjukALM5nOUBBKJ
Y38kY/gzGay8Ee3jN5r8QWeFw0L8ws01vZbc5U4Z8Vx+tEKJfEt9VCQecMP9rAHH
m8g+9HC51wd1Jwz9m1PMo+wm9oTbnQeYK2iaV/xy3lJTsG3oyDQB7rTVcJafQdxs
NSPk0ylQQPA2PPscaVL5YNX6kt6qCaqa6mJVjLDhgzLQr9z18Ek32/vVhPLMIY
rPBKu5eq0Awa80M5P1NePTc1NF85Mf5TiUrD/IxIBdevLPKHtvCn8AW/xuQFXwft
hHM71iWdvYuyvUYTXBNjzyBqnO66TxXqkaPBH6jA8bKzZcBUCYSzVugEeeAnEQOT
ArlwndLSVNL/LQG+4Rss5nPunykWah1PuO9fHuTdHpfgyFWUjtsEXhpwEvRRT2TX
4G+Qi/IiRjta5bBn8ZuBcg0jy/0TH11PXI+Jtuy4KfAbzTkfRazYE4WLPgnR01Ym
fGL9WKZpRD3WRWqXqzuI9oWgH9jW7z9XLglkDM0mXdxjp6qTG+dRS/62sJvdT2JT7
EZ/6bQ4qvVy0FoALfxiiHwx1yh90ffCPpUjy+/RRel3b0Z1+Xq8N1LozaQOtR2W
yEEwK2uCiHTmV2mV3xPIOVamRZhCVf7Gs3J5BvpWrQS6udk73Lgvp3bty400ovnZ
fDber5XzGml153ZmzH3P6p0xuoUJeCE7BoCwtP25mDD41JltkwjNIXKMLv7MsLS
muKOGx9rZshUH/H/LGTPpydTbMDWDai56KvZuCF1+zRiJ0RTzXcaq4Eq6y6gw5mX
1RJc0fEqvPR+QelUwebMFT7NDUjArdJXy7nDbhNau7P+eanlHno+UK511Ly10Az0
wsZx82WKgb+k5u7U17DxNxpBMsJ2tmJfXXIzZi1TbcOv/wN3n1n3vXPTVeXOeDiY
ohWi29T9MjOUbmhyf6FIEHJ5egs5SSSTRa9S+STBGKSZUGOOe6fC87XHncUb49Bag
aziTm0z0gO+faFZfBj00ZZbwXGBDP6R+ideX2/HFT8CLt8k6xDD29J9pwiYoJ6/x
NK/vECxPozDDQrd+4/3jpKIth2q1H9CHCSKICMD9NO6+HJR9tsAPOKg8mc9AAjO
DuMO9FJQR7AreFcjN8QdG8h3tJds6sca0QdL7chw5s9h78cHh/cMvY13r/IW9FzM
MhpmAPplCJ0u3zwICm/CzKEpMVCLiwxbvdi7hN/iphL3hBk9QomlCb77FDREpm3/
3ef/sbm87Gu9slbjveOxpv0hCYWwQ4353kYml8xd30Xc6C+OKU2rSiycmJym5Rwb
fj95s5LRMWUSJuECf/EgM5LZpV3Gbp2XisJmHK37Uu2pEdvCYymneIedkF6FpWI8
2pnipwy11VKUGvSYBgw+0M3RMWDo4JbMnEU9mCQ0nDcirIFwq+h8ONqBSmdH8mIV
cTOp5H9m4TMHTlbsMbhu1gLVvZbsqxVntJIq53XKqb4aWedanGo4/BsmVJgxIaY/
40wMxv0U0iehrOvlvOiqVzKFu10FQ66a5j6fz+2I2vf9ddKx+k6+JEXbRgE2nMZj
/x2AA+NeiwiIn6fffBv6uCffVvKGN01Yo9Lk6euHLQs5DAPUsv18mNc2S4xWqOm8
Rz6gBE5iZiksMr2cPCTiil0Jp2cZ1/sthUJE+aFfM5L8yf7/bpEs8sRpyY7ZwICw
VyfcNSixlIN/Yccaa5XgPmEbwoMX71ImCuPCUCklb80xRG6sspHEaRdhSTIpXmY/
/brUTKrTQP4R9LAqWskAJp4PB4SaIUQoRi/48IVEFYYSKWUF+NKJV7YvYVB64Zr5
rhFoSHVTVN5zUmMkFIXNba9D4jMZZ0k9V40AtB4/20oAvXj8rTWfGCnqQrNaDnZ
asolyn3wbzSMylKr5BDNQtx1qcw1/wzrgFFx3P2BNTPosxbf0WxXtO/rheR+qohN
BLLYcENVXpVxfl+RciqHZDLwLDc/Yyx10+A/Sft8qDV53gv1lonXRePGys2yyb9MU
mKOC4f7g8HXMLLgvdFeNw0QcAKQLbmCH+vDJTts+wOVXQjjub4Ddj3/x053P30yQ
cbrDRWLQ89MIHrMyNpBW0zCtImYEhb0SSPk64GcZd6ouWdgXzCwjneaBksdgoIBH

YoGVswgBUg13b/1ZxVwEyDBM2jVRcgL3KRm5ioIxnq6O+xETJoaJoK/KjzAycr+1
iPN0m9prhDvBe+de+U+vjlPBNnWO3IuaokZMjuHBCpDzzB7QlmgQylADHS8h4Wk6
A7Awniw3MyWO0PGjOuPUdhr21Ss2Md2dJewswC8XfhryC7NPTVvQ9ilvUddwx3Lc
uYpoX1aUxgq+IKX+eLMim2G09knfmkdjKHyrW+b2VylQdn9g2P18zYnGlPrnxRdO
H2HpQxZKUS9bV4i7ccgE4ZAp1jL8oJhz07HT783TEakdYnXBebpi6hmb90qcaK3y
HK8xVmi056siQpljQkjp3lpY4JHLNALK6AIfURmWsmXHC5iIYk5qJzX12dkfu8Gm
L8jOf2c69IWPRLxIJ6ah6YzOjKY6vwDY2s6AOc3R5dvY56dk9J0JYdLvaOLPrAgt
WqaPqEclWymAB7X6TR7Fmn3VkiH3j6ze7sgEw+sEDO7si7Opv84o+OpofiX3UPzn
no3QcnCzL6zKBfMyjtKI/64ynRaV6H1i8TdlRBtfmtx0DxUjJssqrYlaBGYjwkJt
q2c7pwZAYzv6EsjowAC6knYQG2FhFK3S+Ye0w3bxCWZArTfzU2/fgVpzvJFRvJxp
kiqD4511vy49xY7vTovIVQbsyI/83sUUmE3QO94Jn6QWSff41cm02lmoXOKpD+aj
ne77ffJxf+4Jr3zRKVkyFVPTu+1XV870tkgplz8/PyGFMiXW40s3AiJoxZTbp2gd
hs5rUMbWdcd+ZqnOVho6HW6uQh5QKTMxklTpMAyOe2QORkWG0WxccISqk6uAqYXN
t7peb7eC/cVH39afX+2VhRmwqobgbUqbze4qOr8nxelLB2FDVLta61KaJqKd08tB
6NunCBsvuKbz/anb0n3eXFDf+YeHfIlunCAqyMjKHwiwbMhJaxaodK5RjnkfrUW7
0MClg4oEuDwkuSmWmG/EuZ+v6bzek2H41OHUwW4pr/tj8Yj9qili7jxuzbuIGmbX
1L8JZwv8EwDQ2K5n5JWNk9NS7DMCVkwqJ+iVwZ/UY33LPvRC7RliCbyt5tvvgMuaT
QZm43kjm/xy1IAyEcdM5D+CMiV/NZ6fvz9e7mjWklTExohhRtCZJPYsolUUAaVtJ
qiNiA75zQxpx7GUyEDYStaFKTL+/tEF4Vvh/7OMWM2Ku5cDVWG73N73oC1J12cy+
min4OeUv09i9068/zfeDEY6Y+MSuvVMt3un36YSjYhq/82TjYhke/pDFsVIX4dGl
cD+MLvsag7GqUoEL7ioLqqWoIDG7vpO+OLA+vvfna3pu0c00WwY/S0rfuC807i1f
KwSzBPKqQk7ODps3F740eJobHHfpBarc9lHbBN34Gs+Mi+8U1OBpl07HawTQE6xh
Pjm7owZKUyfu0Rp+VTb/aFbz/nQKH2S6ns/D+rGr3wa9r6cKatNzBpYlWBhuC86x
B71hID7Y+J0xePP5Lsw7VOMWhzs2ZTkmkzzK5RnFEd9+SPH858mbns7q7coqcNsp
XFQhfV3Yt3WLRrp1FxQgxvj1QOUOEcuZ6PeRzXVKjgesSnWN6PL9dMJGQ3/d3rz0
cjvY0QhiGVUEVFDWovb1BeqxrlqTTmjzrwkab65NJKMiRshJVu6gX4asWxyG/XW
fixp/LjruOjWenlzQ3VkeY5YstGlyME4cKoJv8mLRwyXGxvBrfvfSvm0yzPpew4l
TS88f/CmtM2RwufQg5KZMVUPB0xluSa/WBUA00N0YSP5vGoEhgm9zJj3XE6952sy
ewJU56k2lcug7ZiklJV50VKYb8bWJDzA9HvjhrWeXXz1uN76xgnZ+dfAUAUcc+Yz
56iWjIrVvkq7615HAIicN+9cgo9xHsN7NvnJTzlvqShYbZ8ZcaleL65qr8S2iKmR
wGfWfbZkBVfNLzKnw+5Lhs1eOBKtFd7/4+q8tVtndij8QCyyU8mcg0Qxdsw5Zz79
r3NvJReuvCxTwwGwPwCD8du60lfvXHZr9H3KPVW3cDW/+jDjEq51T/U8cf+ae0dD
5qutPLWecfXaYjQ7bt12Ci9Py/AmPZSN7/FM2lNDWQcCsLWecI8HvnG9XP3G+20Z
q4twauxnG8fzS6K7X5h6TzfsfQzyl7nbl/eu+Tkc1ZFlbxFMat+B1NoLbI79
CwyiuOkOPzbBxe4CTEaMz8ciXP4lgr4mcwqXd8NQZKNyme8+s7bs7N0rGNgde+ZW
Xc6/hw2Ap1lwURZCv9W3FL9kzRTGwWmPkbkjlOg5CRcPPSYoZD3ZcgNE6gQ9ZN6Tp
USc98M81VrDGY2WxatAzfF1E7/chOm21lpL32zHAY27oEECptvGmuXjFwugfQskB
TbHhSJvYju/5AOiDniPMakynCLyJGqqUAdvYwzoTAib4eqXWlnJmRlYIELRuaqK6
c9zUQfa4UBSZ+ZuKkft2TQTmHqKIQLRVztsv2AdVF3UKmt4+kUugTamXHGC6WadV
xxn3d/hFBGswRtUDfru8XHVkpavdraerJaIfR8kRKbBxzRCKY2wVxwUetXyQh8OJ
kzxvUkDoJGXd7IePBP7rdXNcfffCLuovrEX6zp89M2OES8eRlPwSYQOBA9q/tWC
uU0+OfbaxjOGmcJkRrp81hn77fKCeRu+B5S7DQXLwhbMkOAEbtZDU7cRfyj8eMd8
G+rJBrbKHDx1E/gQ8IdYbj2r9PYviI2zVMOSM/W+JVCvoh8+svlRvgBsolkMcyv2
6mw6xO4NV12rBh4XfLgSeLXPWnch5P7WA3C+yJ0Xzm2kUSJSKswJVFCoe5IF61Je
imoQ17hYvKRaicydYw6YKFOPnmz7oUCH/LtpdxX6hw6TtmLw3LCf2BWpGzvfFrIp
z9vZ8TrPR66Mjift7Htoudf7OdrGvM0ZxYPktwEwHEWFWSegoiA+vd/eNrM1OI8X
aUi70r11tTyYu3TG8nyofGnG+8TBRWzNC7Lmr7R/LaBPS87OP92bmfIfQCAfMG3b
ps8VrM/wQ/HBwOcIsvIYhqWlt2zQ9uhWF5x30Rnc7f6q7WqLTEo+WGPmkQg/wPSV
nLyRaiGKie27WnZBDliv9uGSwRzEuOvnYZgOOjYpqpQp++2KuPQ4ArZBlxtMTzn
dvX2Pr7BBB02GopV7milBEjlF2nJO/t5izOO5hR6aXf3Cv/atX6hailKpqbWf354
0tBEG11Sn8d9A2rAfTnH8MsDAhO0Ob4eJ6CVk7i1DNECzQiVne7E32MQqUJ6fRcR
Mw19aFFBexx6aw+mdLm6yG1FECIOqctBWVvyXGUSKKXU8OVCqG7z8g719yBQNulv
MdxrtvGNkUxLVBPLjVjVoeSZd9Xmp3/RXffYrEP5IO+tJhJmeyAR0vXYwXGQDQWxf0
OTJXfpsqJzCeczyfLJ8PRQp7mPz0GEWswVXbDIhq+w2YnXRkHqQY91KbImZLdd/+
Zg/mKQeFkjI4xt52koSBaVuaAQaklxS11YDc43R9eX3uSgvp8zmbPYHeVNSRLCn
P/af+zePUWlArKlnNtnNQUK2Jn+iF25ICVINvQTlpKYeaYSqvgB0tgY7X3JAPwc5
RN8VbX9dkHgR4zzKusqx72itY/etf/Fh/3TDUoWylDv9vWAZdky2wDn3c60a/FbQ
oh7Ex8z78rdW58T3Lq6EjEmBg+QlvRtSpQb30jf9+2Uhl3L33107dsx+4HT0jUqc
Ncc5wepT40Bc/xuEwXz17Iu8TarSez+3KcNYC0tULlSAiJqVQKrLQhWETxyHdEBG
lh4IBMo0t0ezZWD4pTp9Iuee4TpCDyJBtRSrcFNCUwLjVrqlghl0nQ0Tx/QQWVgrE
bKnG+hGlwnXjf3LeXPi7ZiE5x0hSbaofKvrMq8c5ueVXeIth9RqHYqg9wrlpDPNV
3t1PB/v62snHwkZ1XD16M78cAAf15gEAtgHEUMg5kpDj6VoeRfkyT/w7xSNFeOdQ
GDC982By/x2JWirVN8fv0/+bPPKbinBUGEZWOdND+CuseYYRekzCnP1IvyJy9r+x
/Uly/KgTg7Vu2Ny+K0k56SJJKNmYf+Yg92TN0bUmdP0J/KsAJ9r0MEHUR+nluqjx
ctbMWPeqDctKdoNM6IC8UjUnCK5SFZP5N+vOrpi5AVWzS9MAZo+777DQ1Btesec
6djsiRlTnrj8bNVKbeSQB+QQvvnvdh6JVy/BzQWMREQSTx4MSX3e0Y2Kff9T6Kz
Tn0ZZLeeSjA6z40ViBk3+WQHxaeWAqahX1Yhs/nvowM5CnSKcVjci+RLET9ibvNp
2n4gstW8DQXi9INMjPuogQVJyNzdolt+xezcNLoSddvBvnyYa40ghcEO6M9+oBS
9e7S9Sw/c4Rci9nkt2fPLU3goEBB+GLRwnNKkeTMktuUQb8RPaqN068peItthyps
Of3GTWkKbhmvhfUJ/ESzdW7o4RM8JpEHENIPOUoz/dHO8V02fmXoCBEV8NqXnfSa
H31DuKFUAPX1DQnCPBFe6p9ilt2hbVsPuAWmi67PYRFk9qoei00OXxAbBg9U1iY4
53z0mXR2kbcCtDZ7BU9ai+wOskSmUQppGF/30j8ZkGdFUjZJAJuJszfzrHfBlpY

SaFeG0eoyHagGEXyoYsoPlWuGCv5xiygt/a+hs/ECeN3qTg/b5TqY6/fh/zNBXWH
tWjFS/vGDTzigrooebvBoSmxW7jb0YN+ce8WFzMXhljuM86aqZVQ7NgJuPL7Yv7u
s5xodRDRaouogcB5j4RQ+X1b6P4Vj4tJuPjz0aD3jHnh2i/EYtbdV0479NZN7Sbg
4p+SpMqUGwNNSHZjnzMBfnd/UnGoBvX1Kms1cs5bFOFWBuIK3t5gzEROi1zb/FJS
Jmf03zKubfGOBxB1doVlh6v++ynruH+HugUi+KsRWj15kGr0pM4+mMmoTypyAhWU
Up5HOED71VRBM15iCpUOTWWtca2uSBaSX2sh5ZSPgiGdIeVB/DZfSmzmAVAxBjq3
pwmvGzcVbvT7NW3ZNVp8cfK2vkOWWMES31TRczNBjNcyUaSuR3A2cFSygr0mxHfX
VLw9Brylnkwl+IVXiOWjOk4Juk2i1+Ew9UK4U46F7yY26DVNKHufalzuBGhPFiLC
HgMM+ZGcwQmJT5H87aU6LOvLSHZJtF5E6w93cs0ZErUyxRxQru7KqMGkvBOF9Gdn
OnlwOrtOybrMZxcFSSU/V0s46xBeQ2ZzOT5zSNYxzIVnjG8dGTAW73mQRODRwB1k
fbBrcCORgOZOzxcIzU1Gq18XFAgeP5zv6sSWC4wUHO6nfWkjf5OrWrt+sGvVyj21
WHgPQhr+0HCUTKpQQ8CXT7Lib18QXIXGq3iv5i692XJ1ZbyKIKQgT2o6rcUic1XD
nEv2BUblVgQ2uj1jHqFXO/ukrUX9uiDbkEYp4K/7k6eRu117oWR5BLd0Jp+3j1At
0lvVPp+r7D6KhtQivHxFXgryVJo4z58Bwrt7BAeCZrTq9dtsFwWravbwmdjOCs9M
skCf3F6Lspe+ToFQszSzXp06ed99nUzKnxbyHZgC+Lsi+MixHEuCdSnKcxrT1jOF
rLiG94cn4G3hPiZESnnOObHbRBUiO9dc19/BtBJMOww/Her2/dLW/KcNz9yoyzx
ttcf07QxBVfcymkJWiPnJVWgYK1j/r4d+1yX178tU2Bu5dL/DfAjuU8vyqASjH+r
HCe7ygmKLwF20NXwjtKuiXYIy22Ph+H3GHKpb76LcB/PS0EuJeb9Q/YVB9+P3NO
bLnYC62XgmknFPWc/kv2K4eUYkQBs4LhTtPNSvHcbAaCBPKrabUMhwaT/CBPRZsr
1UcYTVgyfsfmY1AAvw19VjxaGn88kKzfsLixJ90uxKIRw0RnAfxnn6my4yM+hTLE
GMMFde+Lu907pd6Xxs17h4CBOXUQB62Ii85Xb1j181Xx2Y1gvDb/pqML4YteEtD8
49J7iFOOM7G4sFfrtB+fL/g3mPfM2CmfWueiqITU9yu+oPiJEt2T2wDefAxrzJGUc
9qWhm85Y25jOuMtelrvIQ7X3I4DMCAOCsm5+SWiQtFzuHM8pCKfFkAJuJ+OvbWbT
+/nQZQeILtt6ZfnvahvHP2IJJw4Yut6Lc2cSH2o4iBBS14X1/RJHx1liboeter/a7
z3xlbQnygv41XVRVS8gy+izRhyJez1dJ+daHjTkbFe35AVvMVZUXoTaPxea7WL2e
Pvito8NbeKWhy+tfMWRsXyh04j6T4skdUJKoKpFjs6KyUJEydcTJgaS58Jd25ErD
jAlWW7+NDFtU9peRdnTuZ11Z+Kx8fs57DzMOIj9vvWmbzI9aiPTa8+h5XfjvQDjC
CHB3UciC379agxL4jq6yPV5HWN6erxjWFEvrVXmVkuQrzuVrt0+3Ctub0LNV9pKD
4b4h6gMPSYu/nV9N+9V1HxGeA2woICQlwxV4dBfZtIis6qzxHbRTiZ4MviaeOgbT
c+TDDCs98D3z0Qzj/DPewWHFW/FDiLQQjxEgu3P2J/7qVwp4aDOg7Tnp3h/8yV1e
xgrVeXhHY8aXKDijybTJbxGL8UAEOwLVETWW91bfagLTThFULKYU7NFCZ9S1QWNKY
v/NzNjz35pybc0x4hqY04mi/WXf68kdVfHPI6xnfcP+UnvBVGjI5T6SWRQiu0EE3
NVQDmZgSn1WtL+kyyLkLHG7i9X9C3WIDOX41HVYz8YXjrlPyWaLqyidUW0870jM
Xg55JgV6OLQ0S4JCmp2y2Yn7tP828i8HSNVxflb3Njvd8T4nQHZOG3KfZ6puhJvf
9QkhfTuMDEIWH4bcTx7mkWjs4kk7exz5pbrXYzf19P7QubHuOLmka2iNg1Dy4sxi
qohTVL2ajs6AR8gXBUIxRxQ8H1mb2aEOq+V3zagCevEhnwptTzV8u9IG9KU/ov/q
xoupM4KEqTHxr81HkiGwPd3sOyIOlUfZAZB4hb+GzvrsdcYfjacXszsreGJMleK9
joB54c04iKtnCOxj9KBOblVPalqRtZi0tW11Onh/flMRyHvS1VmfCCEDGNEMas55
NI31sW8wFvAbMd8CHwUM0pHfF9g3oX8ptV9FulBNlqLEv/ssHnW58fwkUDC28TYx
h14pw0FMTCIfyUjRWLg9xp8B2kBYgFNG5niTL2d8VGKAgr8Td/MEAJUJtImL9pL
XnWT3XZz+JdTEZg9TSqurucdMww9y+DVM5Lr2OYgFz0iSbS8++ufZrYoP+19fFpC
A5sLmp8ijhpEaQVIMmVVeKkhi7CWH7Fa89mCqQnnXInkZXW2Xhd7Ldu9GqzigA6
hmhmKCKClgrNsA2Y0I9IPKVxQwwn0vAYGt60XGZF0bc9kVh1J7Ku+mLA330mkn4L
YzP2jmsi+zp+OuuvPaBg2ZbWnO/zEb+Q5eocYVxaYC5xdwjScGTmnEeE6XX95jUm
izGd4d+gXYy3d2nWG/UGzUIb4nNln7qzk7Jzkd4n30HAEPxEb21JfzraLYp4COVv
pUJx6HYwiKALqRtGRk2v27jgPFz5xJXOKpwZdPcX5oZqrcbXNB7hQTakyA206E2
EH5TEbiAT3VThx+i4mzs4PF+dSyf9bzn2tn7MiLE5Q8qu+0L1BfiAyQEVTfspDl0
3wmC+qsce31XDJNruDEN+GIYAmwlnQ2HnjIzTu/05dGFknIPTSuVE6CIdOp182bv
wnvtX1jzwm29V/e1GdPjG/33X4ekAaY4Asa5RCC9ISjhY/SfwrO/719tOCO9NhL8
RLAgHb0nofn0m8J/5QjnAs3Xma3ACQDzAh3WeIxx8DnVlqA9JFh4JKimkLvORCOa
5UWAwGA03b+ja3bxu2bvYdyx9ewMNLXHu+TJ8P0OXRGkLdXiX5zvKU3sukS20Sb4
luDG5Udlri8NEF+kVKK/7EQdL4KNAvgjSng6LzuvuNuy4rjc4df0JQ13V3jwZgZ5
3yiXmWNiWoJDo06+ZTheL38jen4H3hNg/qsozjCpi6rq5MWEbXthSehWZSwiW6Qb
MwVhQPPp+r0V3U3F7bpLY4IQ/srQhJyfoeKA8YVpnGAKuf06K6TpVPZ9DmVJQYN2
6Y0wHuz+biHWGjRbm0byi1Ec4+k/MrQt6yF4Y43T0ZPQtJmbjKHDVh9ieAa7rmjc
lpa6HrzGebJkHXHjvZj0BxZPWRgmufhVQa8mWXFp4AcUBrttDrEbaJbilHDK/Ko2
JqMLZQ4oUCE63Ln8JodAIptvhigSahWSP4klfoSvpCKU1d0/fgpJEZTivDNGoHmM
ZCUN4IOUDIvmfbCpKNAC65N50sC3mVa7Ezw2zTJixkEMTD/xkwlXz1xNJPJoIOo
tHQqGMGLdlaq9MoOPjpI7PIEVZqUjLH5pBvWsd6/BeaoPNHczM8Zzc76SpDMJ615
RA6uKUZKXHRmrHxRDgyKRnr57V+fn2vsaC09ODO/1gfmbl1gXhFAM56PzcjQxbjQ7
10rs3W5Fhk8hULmOpRLNmo0nDcZ11ZQmXw/oO4QTrzcI3n/mhnIUeqU05K61nL1D
uhm/NHbn3D11MEWYJLAzUd94EEKv7SN8deDbLGiwcMF3yQgR+g1148yPc4Yu91Bf
Sx7Iz/oKWS7j1Rejt5+6WZBUyqlIh1Dpqpba8eGvHEXcWd2r11X8qSJS12WQY8ky
8BnVrcNUeoKee9m/t84KuUF6i0H5M1Wm6htJFz/wWLEJFYzDiDtZTr9/A4ooWwG6
SyCcy5MIC5pz4N0svHGZEtS4g3ZZZALAlDAe+EYxVcIjLq93+mDM6ko/0+3+kVrt
jbXcevM3qgBzY63NfX3D+nu1TPuWz5y5BtEU6mmhUm2h8urTbNSnk8nOWz4Zw7y
SjBIOJuAgr9VrYmHkKaM/OvKdMCscqEC9Ao6dI+CDsMEMiWfN0ZawGIQVI91T3T+
M2t17fQZYpGpCxrFLSVS2AZXda2to0v5zK2NkwasqpfN4yEAH86OnSZWn3DQJjbp
Ava3zQ7qUWnJi+ppG+yliovtfhy59Rd/fTwyp7i1WKcNaJscMyGku6oisq8lqqpU
MOv6Nf9OT7/zNDnLm1x1LB8bnB26Q2ttbDaOqTQjq4jMzUAu45HI/LSOWXAFZ771
14iJx/vgxD8NM13Smo4TUaOx0yN81P28T4nZMHMT2Z/K1Tx9jLEXjibioEozbqxX
edZQJS93uKrmr9eYrDeGM2JxutjwDjyeY9+zSefw3FWXhVnhCp58qhO9iYpGvWPW

MjDpNyIqcki/9ST/jZvYnmKJJE/XtrDPCE8viglSmhewlCwsCj+ueEPvVhavEj98
FiFbmhgFKKb889OHwv3raS+ckvJwL99w7ulP0IadjsmAgrcHeHeruBcF+qqEeneE
HKi8tnxNPFReXlNlyHd357/VauJ5sm8QkuzRjOzRGh/uiUM9Vzg35aFB7e00IKVE
Mdw+uLO9yLskl1Texb8ns7uGI+EVEx8cQSM8Fssp5tLRj8Fo4MdRa3/2gd72hq1Fk
KZ1T44d6VpxdQfbluvpGhbIdw+3hl9NqXl6J3lewGhlJR+T6bt6NV/OGazJiXG84
sZyZ8RKpz/sgOtuwFO/NhBELgFZGwa/rt8Dce3DXcGzujx+bDNR3xM8mIk2fv8t+
ffygvlvtqzJkiYlMiktHzFR3CI+aJNxs6GK37cZzPpWghMLCxZuBs0HuZ5g05zr
JDILB7IcPektcem8o8BlCJOgQrOBwCB212DkA8W/ayZlCEJf19KeycbvFCeFgNgC
0ZctHdUKY9Wasmj+Ku8QK6xtmZHDIE+xaUhxzbOfKn4JRdUA99JLeqm/mjPnxhtC
7OnOsTd9yX3l1IfYhxIqbfvjqlcSEKrxFDXAZTKKR6Pr69cFhWTr8tgIo6P0BTzC
ELuMaAYertfEXLRerym7aYqCTOJxjWdLWxQj8gB6WASya+a/19mK04CD3vFlie8X
GM499Pbf6imvgJ/RZT9yK6aqX6267mki+QGN6xKS5IoJmhdLUtZv+U0UL4MkGfw1
tzU9IT7kBGgCySjBUD5JT3j+WlAdGC5h+Niaig+lzcIKH53ibbCL5/g9OoIGJ0Kc
28HXHZE56fo1Q4TuvpuLafYv1465drCcoa2y+qHlBc2f0Xi6xqC8rworwz8T54d3
tZJ9j4SEMjPjwblSHj/pk0MbGE+0ZmdMkLLEwAUWkNsWlvinwZY7uuRqvvc+d9W
69AS6SXrPCZoSwlBM9cC211SyauXMxVY+p0lmmguDcB+iMt5z80o+SoKiIu/bVwX
/1b4G66hi1XBNDT8+iyi/ehH+DVlJoRoZfXChZSCnCDkMuFvNTynlRRP6KmtZ8/h
rgCB3zMVeUGnQIKCL5ivsbiubem23/nMsY+Rw0iN+pGmkuLasPgQNxMxVO/ngs3P
VmeD+GTLl+4w8CbPkBP6Mc4DN3SI3uGezzK5wgGpUCAfe/+NIHveaUonAVA3F+XE
UAR5gflXc7W/atuT7Xgndagi87dwJumSxBE594+Wyx05YLymeYTax55nRA8WXh7
p4W7iLEPyuiPhL8uKIWMGRxEcoqMLU6jL7I/1Zfq53cQyHMsDLRmeLyKTm82NTbF
rtMtNoT6FT3wC20d49c2i5yeA77SGxiuCDsJ2/cZbVymTh/tWkra3/bLiHkviSqm
cxHr0bbEL/fc2Ufl+DOTv/vM4ktYX28K+oppNHYGtq70cqdoY5reBkyun0rP0CCs
p4/RR5BZBEjx/a7jLrdm4V/db+m7DUmdqxLpRuXlk+PF3TNGQbHVcNTUM0mG1A9
2RKZT0TWqD51WgOhIMK+/+8iqCX7BbHIGdHDF1TUz/0E6Qqe6zq1/ARRfQfQaxNV
9/2Vs0A76G+rJ+0P+t6THetSgySNR/yD1alza+/WJSTRktPnw+4falHoFkC1OMP5
rd6kpzJlfiEC74WEbD5RPTGLEZR9wU/w69AfvJDeA8TPvksdQciAvIXKLrIwxU
73+Xf9iyWRlX6oUpg61P7/GdaNlLUUmGMSGI+jlAWlDc9TJtTKvAKMK3yoIro3BH
ynlPF8iGksTvwCnKCAVLveseH4fiwCKSWx25hlqXfrPuDI6XBz6V0kIhO9rNwe3t
uTXYWJECA0DLC3+j4udORMVJX+ykR5R30R6MVuRQmdDg/fEa6V5oNPbeL2hFPJ9G
cZ4dULUDVHamI8HCpgYIDdSHIpoEYgyk1XxhkJUKa8XlUt/Mnk2Pqr6zblsUT9qh
zs983Lv/ilYrOxiJjQ+dMkK+8Brw4kCdShq6RGkjfespuG3o/msBsUi8rkGLkFwQ
Tjbrj/euMC4g2O5MZVMXL0bpryYeJmTxd1/kx+Kb14F8sedATD7+M4a3/QC+sFVP
tzn22FFRWTSa5tzPgUm7uGJExxR4QlYgTy2cNe5LOyQ1Tw369nnqipt/04Q5B10h
JRby6jcz+gAFpp8Ic4E9Ddj0C7gxHlSg74scjy80ZqktQrwUzZoYTjVN2PuvQDZ4
7Tr0lSKNAKYNeayjb/StAOXEZZzadkvQBBYIGUj2GluleYlKosai+RuvDfVA5N8C
MzV1YOhrgPK2YMO+5hsiCNIDQp3Tj5dLkV6OuqAn9WGOzy+Kdlt3GUP34FQmqEFq
+d0aBZp09Ex87QRYNWQmhYaqu4zePuoCCn/H3Z7C0zpr6T+6EsJLV9qd39uuLDeP
qCT2bxAmz/Jm6RL0RE40X0VZHRtZngUtOhJcdHdUkm9Jsnfz4XfKfn15PmTRQsht
yursqvpdOTMvFzQkV4bvdvbwBg96td18DZ4Rbipgs8RxCdTqiUI5huAoTA8pJpb
Vxrs1Y9IER/FhePC07otdbrotQX0QDAS/125SCc2onQDKarOXvgWgpq4wl+eYHxJ
npNBRL1sMKu34zduUglcHAX5BcPCQMqF7sEs/n7D9JTrYuvRp5aBL3jBEGyxymIK
H+DhMbD9GAfJg6+385unBV85k7P09SR6X5SB9sTNxybyenLjhLfowJxHaSiwzykD
MIiGBrKDEIgf6Hs+AVSifzdtUefzcWBkeRAXBoJq3qYs+HUUoGDngQgAh9IadFF9
9bb1BHZ2VP2ia8iQUMTuYSnwi9XT+ALHIB3sI9bnbl7fLw618eEpsKVwvgsjuPmq
324Logf3XQsI8SMcG4eraPW06MHfuCnr+10oBLlJtLICZvkBfg7MWitwdV19DdhR
zJurs1Bw+SyIM9C+iltnMK91ZosImH6dI3K5QcfeAaw+BNS/vdWSHMzkaJfbM0ZY
0XQJvO8DChXAKsEbvOBpq+isugGZLVdb/W3ntB5Pzke3NFWctPYATANKoR8z7fZ6
+CjcVyny6EK+FFvtajinQjIik8qppCKPoX2SftvTRAqitFZ7NspxuC4Tgvt0LKxb
EF4YtTBz/zUmvwQhEiS1GP2eWvkAlz4Tk3BKycr87zQ7bBseCsBuGUTHfHm6PHmD
JydfMhziwJIH0D/OowW03HYn7N1Tc9rj+KugDzIjlbjFxFg/2/1piykNVnigYlYX
/CUPchfVOqQZY+o6yBFsRpvY+SVLHMk2jehrtk2EOhSXGfyf0XgoXYvIV+xrrGC3
0HQ+cpF2KxRS0dk/mdo0nShE0HhJPQ6YI05DGHsNUA7kyqGs029xwd09Nv0oH4wk
5Ff6MSl10p/KubJm+sjsCN+8P2MbwSbixzekI4PsmV5QrxKr8SnH5HdRJBnJJfxz
sKQ9bTaWVcaMWK/xamefmrYXvoLdY4BRfNkWBtXXnD2vzfzuOeSTKpRT/t5C3sRL
1EpNt91+1F3ijqWLaK0RaRodbptzB0dhH7J4KbMUhILvWds2yttL11PBZE2k32p1
F2vwBabbTGd6PpRz2H7IB6rqVVLlgn0DlUVq9nUIFqgtPfMj1sH7EjKkftGbsGLc
b6f08ydUzdMK61kGebQgbj/hoc8RuyZY7vQ+wPJFou03BKKLLaJFUo1u/HzQDkg
mvfnQOp87sqa51rCxp3JhVmu2UaRG8naRjvBcWaKqm8h5SRvG3IjkuAlj7LXs94
4oBz1f4ennLnAXyzNfPWHedk9ocxQHed4QM8qjZ3OeyyesHMG30HIgXvBcJ4vtfv
8/XISwwiXtD+fJjx6P2VabQ7hN6F8EfhOJEy2xX1sALPQaaUBPwet1eR8hhhKne1
nDZQhdIu+QK13xS+Ep7atKhVK4qcwrXOc4FUVgOvs1bHwW8foll3GbeO1qx0Fk/f
YrMC3tdSuEgHb9b9cz+6iv/EnpyMkcADR849dX09diWvRQY9wSAdtPpuK4+jn3B1
+2Mq9aw/5RVHQ7H8qulfQ38fZBQDKa/JCIKWZYAppq1OSmaJmmWc97sZxU2XkWte
joktNUL7icgWT7yCi5Rmdn9uBpXPfV43+2GsqT5mHtOTkMgivil5pXXqcw9MMHapa
B7Igk0nYtwufy++a/fKbE6j2HxfEJ/BXOXOJgrQv7loZ0jNQiWtfvjbvnn5cPd17
oGsg7Ea+oYPAWbu1TbBPVYWXHpf6pTqi62kyKPy81GdBkdU0/i49Jz1bkmpdo+Xo
mEuDYW2c8CGYJP0X5ryUULYocCWKF7NkZ7bLPkUVJIm94jHKUKnL8Lf772xj2kd
I5XxvqFBDi6jYmsK61DcfigViw/bfMHery283oSBQ7tetQJgp5S80QQNWTg9xYP25
s/DEHnC0+b5DvpHN81KISMNPaT2kbjT3Y+mW7bf3AGvJ6nCrqkTjhwXivcr6i0gi
XONAYLj9QZoFxpO+2h201NB6trQoCRSXj5zB2ztft5Mk8IlfuVXEZE7ouuOOOf/G
Yz8+pJ3RHODP1MNXSuvLXu0KC/MXqg6p8URviP3ki67K79dEy21Sn0tWnYtN2qWX

Wje2G7VV1cn+7J5G5VHkCx02w5vls0cxJb4ITPW67tEWX+gv7vizEPXt/IWwwYCF
c58hEc9PU3UcMzDxD0n056aMndetd/gEypxEEOudv1Upr0b5e5+woZoKs8Zn9N2k
2T9XLwOCLKUKbHGdFD2fDBH0AoQQ3w34EclqfwGbOKrRRtekKbV+/Zn41RRsim5t
9amBXb/Xtr1dGVA7DmauMQIAHALF24yYvFPNRE9zd1oxEUSix1LHS/gfmbJkTe1CK/
4NV1LQR7WLGOGym/MCoG5GrRoJGOVHKLF++yFRC/2gKMj7VI5anah2CfPRv68gFZf
z+37lxGNnc/AyhnGjI1HZzfv1IVC1pRTvzrTTQjGit2XxNaB3E/8h5Qm863uv4x+
fFC46r9qM0kPXIsVSuYGb3aHNXcHymJp1BN8UAWMpecBn0iAYSVRKEWzG+G11dF/
oYKQLEZuy6GdzUJRXKKukzGSgsrXv5Q0FiKgq56onqy34DDT2Qn2wXCDMjYSVDhV
NH5BzAtf8v4pkL2JERDDNbV2ZLf92tB03AKo1BveYNJtGDZm2bqnyyOF2KrgclRB
ULvk/Bb+nM1OZCEf8EFLbHaeqQ3vm5L9Bh6NEGOJ1HkfnMFVvyFOtcKrFT/uCIHV
CKdNxht/ZsYJWY8aXCB3kAARs/nhEJar1sgYRIYyviQ1Z/vbzHPMB1kp41oR0s6+
ld9eAdtBUMO/ifKXr/TPVcjUlfYggVzkMcKcsDnPKjQ9a+I7MkDozPBhQ3uYjY5+
VZP4Evr2A6jdxfyqbWxfj0NczGkb2emuHwrs9ARfh3iJoblrMCFAnTBen01Cy1Ni
wnkYQkZC2MNwmpn4M1I2NucqDFbBcgrasZWJbRXVTKwLhq7RUPx0DbSvCBTJE9IV
UrapAcMz0Diyl8gTmRP/Sd+gPZd69T6FN3qitTkRF3G89RVCgtv1a+zJAXPlaPge
GEAsGg/+6Cd+Q+eXwFQzSH+pDoGKZp1ZDovet5W3Wv1BHTjbp7qiP491fxUu861J
LFbLbJF3N7W3x0thyqAaL8e269cCYmjaJfU0pYgyp/rzZiWtYvq+PVzgM10xvFra
IoSLHcpnR9+v9+EI/YXyU9SM/0zwd2sofrK+HEifvMIyifoNdTHHHdU694YlkaLd
9K9jOjWH44qc2CFaLjEx2y/Py9Qr+zqp39z2Yio9BO6p3eaOK/QgeNHOGNQ0/RX0
Z4d+VzDip5UAIGWC05AdvKqcf221HtPJKu63wt8N0wb7rPEw5JW2rfRd6Qxq57rC
dgu43qRGpdWdh5eopqNSHQrWAqhPvrYYv3S7gv+02eVgeV4MDweT8wLUW/h6kHfB
HPLplvuZAlmAafdeA7cUCML6gV+mwEL6XT1VbTK38Qv8FAPcnMLL/uJJa9GNTkpU
u3x94y0Di9ZNChW7zcW4vzb6Dui4HW/Yg3aJ8dGB9C7uN0ksfN/8oJA5s5kCRqR6
gXJdfGQvVw4P8d38IPyCEwDMr+irSI2vUJDG9aXrZPhhe5+qftesWbuNhZfExpuH
GwfqzTXWNlrZJw6KVGByZ5vtA/34qr7pRvAe0b514pCupQ43Uv9nxA/MfBE+aLUv
8/PLAWqxjs+RoRKRcGZCEi91BDfs0tYmyllkzDHP40SPq7jew4fd9me+RsVr2znv
vCRA78QE4PFLatMoHep+dxIIN++9JFu/Z1+p9Ubadg4k0wwD82DwfAte9i/VqfaC
qS35X67q85DDv1MEOR8vKd5gNoif+GttOhjs/LHpbI+UNb9QUZfB5uBXzMYlv93R
92ss3I9dde26GPCqikd6te88e0Jdf0gPzh5nSsz3nNNqX9135dGMc+EbqVLv+Xbz6
Z2uEcDQOb8DX5YOYwBE5JqDeis+9vlyjRoYoJrZgggyNcfFizhpcfje6d3kc9WVN
c2R+XRDWACNiXPZDlGzGgOwW159uSiR6PIK6xwK7KirriE9ZpMHzaEl1LM9jXD/4
W9ks4895dNn42Dq1b3jaBOYTXO1CfqaJmYIPGgOHaiCt9hFO5W0htYWUjOFm57J9
LV6LmkeMtF9ExE/NS4KV929ZUFChbt4BjZpmykYmTa8L1h5QpH+3/ZJJYAUApVhV
BZ/WJY0mNudUf7bGGwITH4uuVjrIDJnm3DWAw6KVfZ5P5DYdU5/KADbWZnuPLQe8
VZE7BB6grPtICui39L0s3uxNz4I9gwo+qa7A7T4SC4ERUeNF1/tOUeuTDH0HsbIf
+p3zgCSR9y9dfDrcq36jU1J/+Jdnj4H7hZRqiHieXCBxh6zimZycGQCz9eCwceAW
WJVDjmY1ONWFLbltSu/S+c0gX3z5b0jlchuvdKdS2TDuj/wav2pymSSI4Plil65t
sw5+t/UQRQctDODxG772XVW/+un3a95zPGc3bsXyQ9L6g/LOofLnbUKfEG5CnJy5
gafaMP+k1hzy41IcQW69AmaumH+3Nfw2Mih4CNAzdQ5Ckx15rZhdM3oP6tiXWHx6
fn30UvQ1/jSueiGwes93VlbflXKr3rPEv5rWfJUEFoafzLo/e8bak09dnioxFAB
kn80Itt3QftohK6qsZQhgfkCaJfVYwp8xf52zBDRDODCOAd2fVCMvEEG6VBZq3
YuVhklvzcfKdCIt3A05pg7j95Y23+xkoFbjQwi9/b7ns7a0v9o9NCLcKZ02cNqYY
ThYapcz79S4r9wsG0FBT3Jgjr0jXJvzTL++HmqGJys3tFxBKqLK8iQGZRI+gmCO
+kZpXmQB9dPPfF6/OKmAOOy1M3z7MSjhaK61/XgNEt1bK/9pZlvh3k7FL9ntpNhk
Y7F7RBJ8bWcBj2STWsbFw5Fhquj1ACNk90OpXcYmCvVztXuwGr9FeZ/vB0a/8ved
7yi4Q1DARfyIgdueEqAiH+QVntI9Q4t+hDCZpcED5wr95PIDwV7K/3atai54KiW9
QT1SSKTZuqEMnf4NCke+wQjReAlct77MP/OKY993bo/kHr51mTdIZuf/JENE36XU
xO28thxInNp6GYz1LaGlQE4g+M4qy/iB6ciYdtWIzcfCCubzcuCEqHfpBrnfmrAA
xdx5d6g/Vs04eqCEVC5IENSYSxKukTTVbwr8DkSbGAqyJvNm6aSLSFFcX5EBSh/1
Qa4OWT2nFyAm+JeKpGHiaXopCxrBw4cmZoaSuEhXh+eU23KvmndoEMUmXjFffOV
95skmeA2jXr+ZQ4ZLm0rAlh00Sxt/2mPHH+fJ7/CYEG3j01D/BtLhtbJaNnmNHe0
P5t1/rGAC0E+FRQapfJ18HoNEdl7B6Py/NgK95gqMCUNQwz51zmpjHoYOYUoY4h2
HmtuTB1+4+ay+tEqSpwuijKj1IxQjd7VZlerF4jAPEWcCB47x0DjQesme/fGNLc7
I7UK9p1FhL/n0Tsl1tPxc3DjFduSPQk5eu/AEDv6i3FPt7uBUpgLSaJhLYi8uvir
W57Fob7KdamBqfv9sAjpyiD18lW2jdsY++NNfj4Jb0Rf//AeBwuONJ6Uek+qbZKm
Vc/ABnisdb+2VY3d+T/jns1Py5INqo41/9QdfroT2bvrUZRFuXRxElk3VjfMeV9C
oVTecKfQJFBtj9XWiPjHl/DfamLVRnKmwXLR5Zno7h7FqIa3siBRkndTo3zeTCO
4czZQornzIvldRvV1DaP875/SXiyhXALdvk9HUFdzu3gmgyWXzgsBzNmGwLwkpBW
zp6EZcm0s1sbWfvrKzexT+NGoPLbNEksvH2VJ+98A0nZKtGmXpD0m3xFEV1+Ronb
D7qmRcUU3ZGgcolioItUeLMub8o3hp7us7NhpTEtj3BN2bo9P72JmNdtAL0FOx53
ZaXlGQtdzMQffwmbnMqnLp4gVgUrEcry/AUxaiVNLmKc/f6Q7zU38Yc1IZSOW1RB
q3xfHJ9jIIdbdrRiPnnk6GGWDTOwVEpHJK/ml4TvcJn05nSdcZUZDLjPzonqs7df
7VcQoQk/5Xuga/AjzHFtnFgYp/tuVCOOQexkXNuv2GNOHKvk1+s9tafKNxk22jJf
OuA+TYaylhPz2gHRTZE38Qr3MurngHKH4+Hru4WMFv/9MHSZxBPeekGS0grCv+7s
0BE7tgbVE/prGR6L/04uHr/ACoG0mYxBo4mlduiRHeDHPx+GAwGyjdM2Wnb1IPc
4USpyq+b7VL+WZr3Cm27odOG1ROmcGsGcyPjEmC1aqlxMdO/bSkK51fjFFJqWPWC
2kezcMZ74bypD059cet2ky0gtg8dti8CP9jTvZKXeLwU+StQES77zbrPZnfzbp0W
3kXtZpody+dx59bCN+U/la6yasb2q7IZTMv+QpFijBEXNXw3j1B/fpzAy2nVHDW
eYe6VjuPczjEGPWQtELC2Xeq9eGr1VrykUfL1sQSUXoJ1In7rZ120mbRiv22Job3
HtzdsVP2gKqT3H/K4SiOMM58M3Gftbdr9c78FWRA5zHBSnmFI2rhVHfVfHN81+I3
45Kfs6w16KD3X8Qdc4jLliJEgEFJ2zIKLIURcm96ZQoLMKflouQaMgGt8GK0mnsV
/77N9gz3F3wIaJe5n3Mkxsi+DcyrkDJSRMGKQDYOEmsyhp14kvGwVNWx9YOBqCo

j5z9a+ivCnmXVOhnJn98omh7aU3ZnyXhYO0VyPws63zmmTlTyHNKQ0JgYUjKtCe+
eNpuk/7v19xt5gzU6B1Uzde+K8fiVv8xwcmXgzvUGWdd+u9GxC+Yp9AyZWK5fRyW
q7ta0CP75Tu/AcXXYle3xciYcFYz1BzS1fzE7vpG3gJGSD62mJgly4QfHexq8OHh
ASXvAKLOYMbpqpf6yU5q/vTL7N16rRtDDdFhg01/K8RisG7+LjtVmFZNCCKJiNgyn
sutL6t3v6LU4tj3Z6J+z1exkYcBmxrTmvIPDLbgXzqN7SLv1C1oUVrAJxmyo4S50
pSZix+TzOOLwRW/8mL3+1DdBjrfaykqyqs6m2FaKg5qeMnkjwhCWKa68VancZDSM
bSyc6G7CWIZTeyZVxotggOa38mr2JmgqwoS6LvoVnbd6HVpz+srsKUtW1Wu6t7I
ZYV3gr412ZW7ckLuUPYmwt3L159zkwIuwCkLbD7+AV4mMp8FSSE59tFFYgC/v9n
/P6EYFGRzfPhYl6QQOgtYlUTwX/qAfPFLoxy9nyIdkn6DxzW9hcnlSaKHKcxMy4
8wiH3NL3BVX1gKHNP/Nbx4JzDnet31xQS1PHZXQDX++F1VwU3vBPn9pmdGLkgMJB
GKtZeD7hwnDmytOaJ/c3T1k+4PI2kGC/kmrkjSGOcIwuvzrTfxPI24R8NBxeyDLG
05W5JNHQ6ayynYqmLsgSfms09r0SIDRnqvyb1/jahYst8ONu6/0MeUn73AxvLhzv
wnwvMrtLq7ZYDva6djQLdh9eRglscOFLgaOI1z+TP05dDw0bb8/blzEii5IyJgef
WV/CnkW+fss2hjeBhWOW282WEBzb818JprfAZDf23w9LNHhXsZDLZsrAQHFkKzjs
Osh6TxE+LcfqvlDBrZpkZV690PczCDZeEVwhwHv0lxZ+ulb3+UNdYDqdn0RMw16
LjZv+if0362nfvnChPLAmkaL8IuHpfik2DKY8JokWpyBJfbf6QKOEr32jPoS3yJO
CyU8e39g/eimSL+FsZxAKte5WWjU/U43RnwOatthwvqN+zdEvedf22yHZ0e9Qt9A
rSERqrqXDYUdQg8qyp+0DMMa7t+FFRT3hbwwmFnd8OixpRtAvq7r+NNNYC05zwJt
OOZkzn7e8gZ13vcBk51HYVm7psDESjWUul6Jx3ZzQrtn90E9mmYaZD5Z0LzitXD
Pull0btYdXWYqGFMYcRYK4MWPWyp+Oy+qATg541KSfg7jxwv+qp6DKtTymD9tqx4
gwUu+lbIS1UCgwQWlgacaY840RrvFZ7DmzUQeRmKV53C+eCvd/1lEHZSr8L1cO33
yZylHSCGCUVpAJtaxZ1rPGueqbsScaAosx836MCCcRhs1toS+IT7flxdt5bbQAz8
IBbMqSTFJOacOuYk5syvt1zqnvhv73Zksd4HBDDBat19C6iTwJrCm3P6pQa4hw8rQ
GjNcGMMijizImJX1JPRD4Jvk/zVVjbsWPge2/Yw55MrDkdncxCbzRsLwL0EecGWu
I3Nq7bi9ldUn6hu0lpVHN8Y/Nl+eSpWl+VSNXnWYhCalHBBMV3FQFEwf2M+vo//
xRNgAwIovLn13R75TCOryc7D5PPmRUqDwhlhASvOwLSNjHMrDxXwsQaI2OE5/31N
p4Mhfx3TvZtdXOTfU2/48tYfsIZeChqgmVKNR6Qgh3P4/YaxqknfT1HoQL3zaEbu
3x6xlGvgbJk5wVyeF0md0E+g/iidwZ5sdQJuunp603fjtdJxwKq8sQd0COG+Jox
CZP2604WYda+ODipin4+MC2GGk4HEQFXuLCoqzXg8S5wYc8rf4yd0Idi9+3hj50E
psNZxZ8WckQDrx6eZ5hOqXsGQ/h4vkie467ZLHQXJycYKvV3e46CTpanmRaGfBEJ
SyTWvinrn0btxxkmgBRK+fEQX8mUCd8UhVa6g71BfzuXjMigWfKHYIacznJd8UYZ
Xn4cwUg8ZTV/K8OniXrZSZFDjJW471J5cx1VBYoRfr2Ybgf/CHb6milmyiTIHtez
VpZWUiliv4T1w12/6ZsQ5A15CjxTSRans9rYZ71NfWSq2KGAQvqnKSxBGV0I0mGx
dnyjg43Lu940Dr3xjvklLsRqV8bUyUlaUvPWHF/Yy8B8KS5DSsq914X+/YaxCmdd
YcxRhg6//M+xcdQ2RE8b/uRpo20Uzg9f1Fw0+K8v6xsOv6u6ZF4SL0r+ByA4mtXV
/6CytWdQboVU00ezkXC7rrD+DNTMhVDR2KA8vdHj0suc9klpPwC8wsA2g6Qsmx8/
Iuc55uykMd7cTir+R7ldj0BhTSV+iYsx0suVOE4pvbaPdU9CWt5KZYq4WcNQk5Aq
pZrvV9ed63cDqvWqes/KqG1+qWW4p+MvCVFu4U3pOyNb4NjLNdK6yNLlib/AtJzcc
5A/Thg63KC3wcqZUh+8prUNJqbxvJF2u+Pw12q91LfcQd0j+3nLAXZ0qsA1EpQZd
6d5zdosn3CxL86zvQIGD5IW3vvhGH9G3X5nbLL9H31etFdXX/YZWwHiaMXxjUIp
0q1+onkOwdjz+p37cBe+DB+0ybdwJnnMVSrtFK8SYX6714ZJmvGy9blezfBjpfU+
rMzjdGoqakfVZS5/XIbaMtLbs087UJOSnqhjh7ZJ+1Y8W9eo3yWm0uiQNjegSZK
Ys2pC8GyboTiXiggiWV7cAMH8uvqp0KP6bhZLjyxSdUby4V+LUzkozEoVCyftF7
2PN1ySOSOXpjthgnyGE6CEW6bYGGeeERBENug35AbMwYqImWMB+hVgijfVFE/ig
vB39Jbod5uaJeuFp+X7CI7ahrHUWjDpLhuUkHMHdDd3U/DtebXYM3f1rZ/pASE9z
DydoYeK8PAq/YQVSUZZ8Rbczh++B81AJfIG+QeN3L21LTxi8HtaQRR188guOfDfj
ems9If/14Kt9dkvGLLByQFaQRSPtKfHTfc60uJCAPosscVYONmf+ThQbMHP2z8y4
s+kfoVRVyw1GUC7Rm7sTMBAJkrEIY8PFuvDIoyaYLo1J1uM71Xt1z94WwmUkyf1r
Guzsfy17EwrcR3IFVDk7wnP6ntilx9EmMjfb9W6zhYIR9YehLOOMn/RSjzV72eU9
//UAXRI3uqNuVDcWfaouJmldQpVKXDq2qW3ssuIIs3X9rh4PpGHuOyAOJ7BcdRtH
5kp8mZYSnJtN5GwovziSuuZjcIxNz6q4EJPft4vIINaZzCv/IDoZVliSh7EUZb3
kSDg4U8uCGHTG4h6tt5OP6uoTIDPE9HsLZCKiplxQqQOe67PIAKh6gBRuTKecD3i
fQXSLGq831QEevbDosDR5xueloKYCv0FW8qCUImhyu2Z75whRv7Gq1/Z+oUogv3k
krvdLg81PQavv5RqUT4u4FhKxPLC+emAqpaRMm/YOag+Y11IECRSGcoxNrZSrxRW
2R2AEBQffC6KSbn9RY3RZdFSyOa6fn6TpJ48BX/CpRAHb0Xa/HKRUP+2CMJQby5
tc100k+/yBDvLZRto/7LadHuYUJxsMbJk3BSVGK5J18YJ6KCuyVjPAHj0FOxhk1T
yJNF8Qt03JeBUP774Rv5Tfrnuy7fk2aRe/urHGLQOE041lmjsspiVMA/0a502W5
kfZGplai9X7zYcn2A+qdYtWRvWAXn0ysAiASkkGLDMI7xjRruBA6C/NDNP+IUs2
p9ecd08x5ntWdtfXbK+U3A/ZMtbP19tu8DjKvXz/n1BskPSSnuBFNdAEN78joEt
F3EOOUSNBMTZ/iysRsd4rhDDvPQ1v652eDaFQU/zI47DuRe/NL5jLJ/D+6afiwy
p/vtHV3EzM/NBGxjckSgStfpnDRnpc5ONP6WpSjdsYGTid8K8WLHEBVngMiVAN6Y
WHgC13fWlyavVApHIBFQGUJzXzt6cQgqifxr8349oMcPMcvKD+BXJApYNjCjHBYL
pZI0y2wDzzrT6wKUDab50v7pltr94jxJrNL2MXgL+dMpj6VHEL/5TUH0PugWc/Mo
CLs91bZKIjdZu3kIOefynOJF+N309mg9HiS4rz/APXP8gmNAubHxmqq2hyfz3tz
Fcg3BTqq2YVoE0i4e/Yw/yol0DZ3zSw5ykzYbK8z5CvJ/D85R6RjfxKXnkVY7P/TM
Mb4fxwe1auQ5ht1E8vBcAf0TnTCW2wp9RF1RYp+CkJ/aask/SUuz9B8LpvZS8Uq
UM1VegiyvWAEkKxMS9520Hyle0zxTaWhfbbZakXXpVrvnyK3LioX6T9kkul9nNb
axff4AkG0TPbGt+KFKMv1m8sqV021ulR0FGod2nLGKCMqfTaXb+BY+DPPrdHBXT6
11MqdfvJryEpjNOWMuaDRIs9zDXFuIZXR3gGH4YNH0SX7Z+J00+cPxn1MY7fIEzn
zAxoX0qJKe3wvI10ER4tIVkVcO4YNVw7yhwg0KUNeyTMR4p4wH0KGWtKsd+RmP+u
WehsgU9XMDaX8yNCWhu8103NCPvcfQpS6CvQco3MbZDuMr4wyqhCOoZsRuTnKIjQ
+YsaKYUxkYGHpiskByd8iQLdoO8KsqH6hv/N1Jereosa4DeykFNkAzYfhagz+NXf

oF2Ov311vcE3sIddJq9Ia9Ig6Xl06kkiNGL1EMHGo6+fIZNXFZW7I+dyKc1eobCd
Ya8ItPv+LX+yzGPtX4XRbL9Zn3uyU4Eqsg+T+t5MR9GNlRALRbxjrbVGn7bDgrwG
tWl0IEWJUn/ /uanlYPcD3jXl0Ez1ucQGryhphJBA4ayYooZCexb3Vb7vBD9nbdUJ
d9kIcW8ZBVHxY7P3rTtTlLpmUj3zr7wWJkFtEtamWWl9KNIsEUUVVe3hs6xj6bXPMw
qhd5c64RECDIeiFO+7ubzRF9I9CKk3lg5G08yPxtk5ivH0v8Nin81njmtKpFzZo8
jyI9DeVOe6PUvLHkEny836z71LlBlId4x3JlWuGdV6lPFFrgevOVTXl6N26zCJKA
R09ZpcUthIe7iLutiJyouq6/xbkz8ZEQURGuZxmCn36tZHIiCnB4bhupJFBWdfmc
6m9IfQtR/zJFUw6YguM0MSaWU+Z+hRjHY2Dwik7QqUgQq5mOah007HWDKb6syXKU
kf96D+rJGkyPQjbIFOUvQCyqrwMjLva3c8H4lC8OZ/VqWm8AKeXszbhhiRmdCoUZ
lXjq1xhGzeS4eGUIasNMvWWjymokjQ+C1+sXz3SKwWOkK4dPP1FIqS+Suw90JsEz
N5pH/RiXruFLVbI8bml6M+4oYrC5ivikDvMu9luvMTf3R8fhOxHek7YJ7wsYqvtQ
k+/ni5VOLWuDjMQL8QRCZuVRmjZakfQFwOAZa18t+tvCPpSbBSISIZD+oVmwW6aZf
vZ68d4sja8xjPPoqXvHqgCdEz7e8rv4x9rUOMcD7noovbfpNR2sm+ZU1Q4MIDCtc
gFZML9Z3zvAKGROWnJ5xNIhOOezLUlWecb5waUn4G1b0jdxF4JdsbVbnnq9R4AWw
warVWdUD7KCDrZicbdGRISW+5sxn6UcosqWhbtbk1UgBCKPcLcQTx78PcqfYvSqp7
ODtK+H4Tb5/1Tio818xCdD380gUfGy+BMnuGxQrQ1MHU6GcAAHKbAtHfhrMRSFdm
fGfGQY7YATs1nDHBwwSwSDNfmspeJWtQgMsVyIFKNWPK26o2iy9eQmH0GPPr6C+j
gigsfZ3fJYCsGarHJq6webRvs8vOxbUO+nLNOJivvWRDhdleGHjUp75mzSvZzd/y
JyJyYu29jhQibxEQAhjkV9AJm9zdIWEExwigMF8smdTel7Wlh7T72/ftXsILN/kZN
+lcizsCo3UnADRWiDmeJz2C3GlbZUmgSbFXKKvTU5hhxGJ6AACutFeyep8AdcHTI
XcXym9s+JizZXptxCjunPulCv2DYJehochqB5fVUUs4qAM/7dgeenbC811TgK03x
ZcTlDna/CmUrQuzm75ciJiE/5TlArmlzXHv2/T8roZofzTGUGWQ5ESLewghKhtK8
20HsBZZo/T8lFsArIJCIEft9zekzeVL6Ft6EEqdevGOO/KGNuJ5fHrYfrJjUo34c
3ElY9Nn12kv7vu2vRFyQKPKi4LFQQmEzZuql8+UA06wcj6GtUNfNnu3QShd5Y1qU
VeGM6oeyK7yArhl0fkNd9HrktWbfnijuffwyRkcJJD/I1kHL7X5uQsb7QkTQvZ+C
ExnTjzBmvInuM33j47F7v0r4nJgsOT79K48dfLasqX7R5EiIoNOLYwVznjGoovWO
aMzLTdoj+ZGH00wAlD8hipL+5s+YL3laItYvJhd+6Jk+QIUyPsaAgXPcljbnP7WH
CQ7tvyz+MXB1/f7g+TIRrNg8FGJ/S/r5QfCmLn1FEPm0WYCC+1S3FA6Y7GVEXKdq
wqHDTkxfBIyBMWRyRtMiPE699PcrH8Zf39wVO+kpudJhM6nTj64VRuKrGLDtkRwf
pn3eClee2ifu9sd5lboNle2nan2+wcRean/xjMxfPqcmUIHYKiy5Kqz5H4LD1c0S
kQBngBptBhtrb/ukyVapeS+hIouNHXTWxaiMfguzXAC6+d42zXacXMYdbuSd5hl9
OTWfywWZ9iqCN9jhQVBPhSRPA2xb0/6S3GLnLAv06+jFHJ2em/L12r4T+jxUCr11
Dmnip5HZnAxhpISwIZ9QbRYKdkK7PdBAKa0ajM+25Mvr1zZqLcQ/+iok3KbqtzS7x
oARX/lnfMuEig4PLBnxvk4TlIkBbalpudJia4YWSMOTyu9R0XmbZKsr746Uzhrv
lpAXF27Xgm1EhabpvJjsNjLFMRd190jcvTtYyc6OKd01HFVdhf93p2uIj6ECXontc
VSWTS7cUBxYdtIVzIAKgi3k/fy9ABfclcnyO7egnABCeNGfA8YB/8Qw5bPA6W1jQ
R11NsYDoic2NsxZ8wjzpbhQ8jaCH7maz0oBE0PxJ2tLtZtehxxoxlj8NZ/fistSs
XhAgJb4Doclp6BKW148Pv8041V7xloPUqGz6U7g0tDAvZkyyFBfMCPn8GSmrK6K8
iV6MhxgTILDSyOWkqXuk8h81et9N6QxS0SukeE2GXTh+Qz2/juPivQv6sF9z8su0Y
AA1n4Gnm6HwB1gt+DSBUw6TBPILPq1QZaRA572qpqbAoHw4srtreRk+D+ZTuDt//2
iGHyzs1edWbJN4iOwpEsuvR9MmckB0Lbbw4iSr8qjiwos4kZY63N7YJUqpcpRYm
0W9TCyGbnb8imRTVkhAv86AdKvgim8ULSFhT0+4qxS8IOgxs9f19Yswo0AalkQjO
5xp9p4GW9lFTVAGuHcvPS11k3P+AM/aJnP0+OThajVQM4ENSksvm9zRJ3FKykX4E
TsXTVvH+fVicEXV6x1f7yRR3rOcLsm/7ZX89+mPZvMpyL3+ejjBW//dKLBjDKNok
PfeX+A4fH/9TmCUSGSSmz/AkPtNwYK/ecMKw+Eqggt+119YjGL7AtFImysk/rvOx
9mcY2Zr30Zk7L+9O0HIV8frPcd6Zy0j9J4EJdEXe+ogcfi0M2rcA4ocw2q3XDeO
kPnYnzcnQUGLE3FO4q8HuPal79Gw1vL9CCefTrMeP9E3Xo+T0ZTckXJA6s1Bp/Nn
rZNEVye4KJBMPERf4vbdL0FuOjPeI3aJPMZIP4XNSpkV2M+iodyoSfXsBZYZim5S
6fmaaTmr581Yx+fWs+6xJ5/fokkHCl/1NUyz7KLbelGlaant177Pex+hvmD5CAZD
qOg+qbPhw+ROS7Ph21IussLi/PybJCkaOQMyr4yfgFGuNSV4a9z0rkMZKTBCwTMW
kFBLUdbj6RPDL4Wrkg5BhZKdQd04p9+AIjRUHu9vz/vy2ipTl09vT9OH/IL/7e00
vgt3Phe317e0PEmzbp3Hw0W+KTDIscxG+HvtC7Yv44s5vePAXj4LwE5vpUSUzu3A
HO5tlMKgnw+VLpixmap1I/K/sAxRWL68DyrdP+Wu0ofhop4B+onz4wBren7KeaEKx
xZo89Kb5JhAbeK7IERURib+i4/CxaNACAmXccsynPyMxNhoYQDxvpEb+HJIwpNg5
IdjMdVlVfsRceJ072y6Yk8IvqObCL4Q/K08UX64BBOfw+zaFOajns7QaEa0U8Ek+
9WHIoMkKeC6Rqm+Z/m6JilVqN9gqgH128cIJKsICZS85MvFrGuge49wL8fHmtAc
ffWS5x3WNKcj1qDYctjkuftf7GR9ASD5j7bIM7xzt0B8P1+F6N/TajtdHWWat09y
Hj19MKe6qAeqSnuTwHpy5QjLnlMiOjrUGmlG5FTTeyv6/VpQW6tj/qudY116ZCju
3TZ/Q+uWbh26pu/ATXTjQhifJFfi3cXRKn76r2JlPudfPguY2mbpamV3nb2IptT6h
1qf7S16vosjm4jP3ElpQF00bzzcw2/TnsAEjgUgZRFExnstJoF8fZLs+NiU2vxak
18NjJQuyaGW+1BCtpB7Y9y7GvHUS6MQ5DSnz4hlFYwvf8B43C1pkYhb9WCYkD8/f
ZgmFjPXTVTiDYXLwreToIBCRlRM4rjDFZY8SaOAZvUkl4QlAb0vC4/q8GviElodv
APrdgAp7ZbEkAPR6s18GfYYkbX0NEubkCoy52wGn5HClatC/f/X7ZZ0Jf9C8EHxg
CzBt7DfjwkZ+Jp7dvlMuTovPq0xSdgqnsTrHanp3ViV3hMMwsue2SgWdMGtBREvd
3b4hFYcXvvr9cwhNBMAZ5j+1cgFSNqnltoLJ3RyhUBCWxx9mv27JW5K7V/0B4Azc
9M+BA2x+wVz0R9Vx3/AzDT2GGGbcqC9SpOonL9h200HP+oh995I/Yybt1lcUluuk
tXfdksEsZDogEu2fm/SSRyzf8yEfClLRRVBu9OLAsnj0+pilC6dI81fjL2QXfMMd
crN9aLsyda5x+pYq7E+SRDSvj9eH4VDj7jVSo1GIkkZsvEHQYz9t3FchuBummlHw
otsoVd/a2j5m3nITLgF18/vN5sF9EB0xJPSzFiKQ7hKx4fXXwTvJP2G0aVtYVgFQ
22WawOj1afiyeIgdNxdFTDjd/CESOGyn0HUEXT+hhysw0nmC3q186GxGg+6KI5J
8/zxYSwe9u0tm6xuo3xBtUoMr/LnV1S4CGtrhk+mdmJq3ta7I6Hb0csHKHnE+D7X
KhzeHwvOZrU8wnTjF4Jx3Jwjs54ihfE3T8vnwUVQSptOp+FRhvlFq84Lnl98agp5B

C3NBZL00EmFTKCl8+paRaSDrIBxMETT3+c99dWJzgMWS6eXxpXhv8aI3kM33nSOD
uH385qNf9IyhIOgoW7Rgq76Z53qU7VpFiSBc0y9z1fJAZ68pjymERWYLcludv+Dp
SvdyILkYRE7NYiu0iB9Uw5YxJqmNYlXyEC1BF/A7252mWRpKyaARQOR/h3ZpPbJ
KvXlMYjmlc+4zQCRQ+FY1tPRG/9q/Yj7IlJg056ynp/iNwbomb1fZkZeKQmSecKU
plVkobZY5mTlblusNRRGLMc89VL7hudGzTU/LrPaDLW23+VfcMT4AR7AgNGMnOjH
CXXKr2LqPkc/njMDVSHGpqcsfBJqCrXLOPxA3DNL6nysVeSk1n9Z0FD3CBCTh7EA
3a1rPlRCCeVAQfM+IY9wJ6E91fOKX8vxCj/kYpayJN2SlnypIJUx/C/SvocaaPJt
d50rvcPhTo4iJkTe0pmlLGABONKSV7aAdlXo2Z+v+TEb3ErSGYHwOX2Fxs/D1DRA
6RSyva8Kv1CsshRow9Jv9FASwgdp+Rngk2a2idUlw9J6vfnQVaYdbxsZ54SKXx3Q
tKNrdh83dzWBTfK7Z4SQiU/SHhudXoUrH89FMvmw28yL0haseyv8WIRsZOmQy86/
D6NXjsr0Wm9Etuc/nZUt14ESEaaE2Ye4HyWHTteM85xJGaeJZMcPneReh0SG8wVP
ht+s+5fmdl/54FW+vzmaPx7XmxxULKHeB4+axLrnwlhHLXGKiHoFYDMG1qCyNjv3
Kr23/ty9Joqng+WPcoV2e/PTjgdJio4g5L2q0H56VOj8IqTxDkneX5wiTh7tQPUG
ZGsIXReF/erNlYK258o+QbyD51HoK8VQC7j1Pfwintt7vTzTF++HWpnc/8RKOiXE
64C+i/z91Vahfu3slm+jyBc/8zuNJY6VEbGniNza/UaewRW2NDLRox7YDLMjkeff
pl+cVvFY9p1LUHT9pVDV6NQ2PaREGZZARA3rjbsiSnjBU2gEe2cIIBljjfifGo/OV
hgZJCMICwfC8K6s3UNXvURE35HQF6MbAJ35IvuXbg8M56K5XMCJxBPePZRDgxWP/
+5WBV99/PPJo1L11Sm6vhD/3iJHSx8udDyh+OU01fLpSil0Q42XPuX5diXanMLVh
3Jd8ue79/7ls7t+uecTwo2kun//amf9mQMjFgDqSngLULrRpTsGswtycWysuVXHv
v991iCvmsJSQ3kuBwyWWFyEii2I4/X3NvG/CELLDPXoku/aKN9eYX7H27j/dkpk4
wjSP/8GunkKv4wNtUq9Xwp7lujkPXWgzvxtAeXtp12MEw/edtsGJKr7U4PPNQB4
qKy992Rij9X4Fcerx1waTUWrrssZv8YTHmXJ/mWNqHQQRJ+/NyAZ9te4iN3xMcZzu
Hy+wCL0gn2CNj7dv7Ioeu8431a4pbKccDNIQ8/if7bcrgHVCNbdGyMy6SqTuYynX
NDQyMzWA72246gq39jZYPAAro7HwCnJKN3ZtIOWt/eaCqAtu21eP9FpJvL5cCjns
uOR7k+X1lsFEehY1kM60ihyoEfpSNiKVEkrVVuVT9vL+R9UZH7FKUmeCtg+5UnOH
6oXzql2gmekubRrCTOUjmoojM3m/6PokvTkiFmtGLX9TzCW/kyYBYa1o1cMbKX71
OR+r0up6PFu/83IYVfHLYN4w0zMVqUxfO/En6WHxFWYq3ut+4D76zVK1J1LSKzon
Drei0haH8PrdVxoHH7Qqg2iYFRkyMxlDrZXJzR0FnCd2mgGa056YvhX030dzhv13
8CVoU/59Mej1lgfesSorWuZ0FH0HXFNrrQmmWt3wf8VklJV2VNY1RCwII/6ZLma3
Dek0n7JylP0YXuZLEr8hb4ZXOupLmDW2Icvf00VyNlF9iJB+JzuBJP1Ecr31WL+m
UbBy5nXoZgF8UxNJxEXK0PJSbn43J3qnRYymHRL91DISga6irUwz4ixmrrx0/k6b/
ue2+IYqvXhQl1pVyZCq2cD6Xgd0Dn+/zJhvApzOBm/Fdczj7BRGg4AFb8gdpNYNE
DDsz5ArQdNXcfCLiHrsUld42tCgbyWPZsenFA8neMFx/H0J01SkeA10sAK6ra1e
vrx4C0Nf6h6aaHAcO/JCZseThkQ4XJh9Hcu4jnosGncKBViYgCT6nACBORQTGuSx
2elGsXwIIL9BGOjxS5p02FhjOQ3IN2jdYEGEPgdbFhicfUUGCfjem08Kn8T++NBe
Rl4vygPyXdyQ/m0dMQ/BWJ3xaSadtiehi92onURYTWraFaTOJFAdKMjiJehaeLL9
9CEVF Eck4WLZIFjRX988jZGi9qPaeOr15X0dkx7SUEaA0DIVbTsRmfjckC0jYuA
Cdzm2Om4dkw9aohfWJF/X5NW4AffNv/EBxjFs4fehb5+eHC3KMrA5VG9H73rHLp9
nfVHLVIHQm7cju5SSGordH4lotQ7QODnwgX00G5CALCmCG8tN0nXEqhORxqzZYhs
1KcsXso58xrvYvOMNYXFx6Q6/VL3TeRAnUKNrZJ6weDI4vFxxSRQS0bd1u5WPUPX
6EEWKFup+pY/TBw3wnifJ1wpYLFJ30D0BCfogaPrhUmmW9uJLii/cTeK4PP0/Qq
hdvq7XjhBcSKUF9MU9tDcH6EfQOy4J9pKS6T+YtWRR0AulaV0KRsraraoE1U0v4H
MueI9pjtYupMbw7fdfGIVV32yK8Gg0m9Fu3jVfUAskeO16hKPUv6qiQ7+47aqN+
HaKj+QR1tkpL8eNlHcsdYzFJjx2ANVnsBq+e/HMj0HiiQhVI4sdPL1S92XpQn5ok
iRchzzculiVf6DGjOogHIu20ldGBkW1LbpgozU7/C9vx4wbqder7KQUKQDTEHC6c
UJiMi4Uhh7pIhxqoZWzVB6yWTLVNA37BRz3uDuNERP97vLYuGXO/F6cSX3Tdg0aD
cDYGxlQZ4riDwks+cJlcrszKRHQ2oEchKiyAOibatamlIL+OTnMluFk3fOFZaoLP
edIUkvmZRgKLFdYTsDIg7WhbsCnjw4H4mTCZvUiTossH95ztznzG8Q/a0xbSqH6bm
4QTWj5yA7actQpw0qO5LttlsY40Ge86c+WpXNGCFC1LrgkfZgzN/6QG3XA9thTn2
Nezzy/BqTyvm+iWh7trZs4mpp6SoDna7e000Zbq7WoqsG5EDtR7qzPXnlkv7JWJX
LakKBUDNNImh0F+R0lKZBZUYZq7ft4qYVRwgC2AzsD1g7mZAYQw95Bv/9c35UFH
jeja6Q+95TRBncLMuTBssYkTUsqXdtfbOmV5uMrt7prPohR0vXgYWONAdgrq7yki
Pjr5xzzjJUZiBj03D4FmTtov6+aVWMWQIRCIz/rJea8g06zvJ3ggwm4VM+u+nVq3g
TzYUp3Sckr/4zi8dNmejoaZiOXt17FPe5t9H8TKmtiPUZkjZozI122AC7oQMuw5
uPw1WhB7tgvwku201i9vj+JhfwJfcymnXPebHqRwK4vhQv4A+HPUEHgStL5npTSA
w+pr4W+WCs7Hl4ajt8TaXeZ4Mc3iJGEFGffVIHv8f4zls2Wy2+PzKzy+4jdtZhID
hnnLtNjsX79ZKrBEkAZMZh9cK7ybvJLFB/+u2tZs9JtqyGzV6o9z5yy2t58h7dlR
WcoF895U+VFJ4DegaOeLeW9k3TUBdDPXJpyFTawp/DV7at7jTaogjEC8Yo4t4/ky
wg+SFJjdxUB2Mc2n+O1DiecPXXuT3iiahGyPFX9ICsknouJzwW+4XJIXhVRH1RPu
aIR8R+Xsk8qNKJZ6a66tX9PgISrmhLSg8cfVCwVfd4NdBYmsEgIaOu6HibiLTQa
5H2BxKgT0Em1U4DyJyfn1j+CH/LCQm0/GJDbGXqpVmwR3z+7xx+haTY5krVf1ssK
Ej1bSBtDUBvRklmWouBe4tDLv6jB9u909mjKoOcTxhQ2NzUDfyYpYgsG5blqtF37
wb/qCVPFhqqvzJYkfmK1HRKpWC1/d/Noisadyi81+DT0+SshRr6q+JUM1A0ntd6J
lqgw9zF1WXcq4UmRrDYjEuv3Vx4XpPcb6spEDxt2Ng+bKi1V13sXC9jzi3EL0g1G
cfR0LFTg8jeGo0lBEyXa0Ov4bG+tjGa66/R0jYID9nu51x1QgU1M1B0xRWkh5mJ
uMtQggy6T6kuPPenFQvHgKDZ1Yw8+nIdZYbc37xGURWey29jsRXLopftB/afXJix
7PPps3SnI2OdDjhFEOe+3L7R38vhlFKnfBka52d/LgzshkiuOLbp+YGIEXRxV5+0
ffKDD1aOk9eoSVzhWQ9J0nIQ7IRgyRwefHbBWS+3MnfIQRXQFDA+I20oCADX0x+
IrK7BLJqd3u3wy+FFRVel86OnDPsRoXpVDSXJJBjQctQQp3foTDbgl8DBoBVDnMf
sKc5r+Ypy8HR1VDRES05AixJlaJY4Sk/pYmAi4hSwAJjUfmVsdSvb4YkjdOFCmp5
zh1uOU7CwyI8cQuSpSQQTR66kwW5oZJGL1dzzyIPs86Tl3gRHx6S0d+yYRbcSREF
SYQsS7NE650MPyz9JYVncCwFsqs9CFI64uJ56A+5fww7DhgzstHtIgYA/1vI8P+E

HYf61Pk011DRA6/DAYwrLUxhfWR5uYjSAHskODyhX7owOhTO1Nr8/vxvTNQh/he2
pWwmj0fb84/4brDZO6/FrsU9W/+XCavvxy4NFmk99u2sxQdQ/DRhNsVUmZb1Dldx
/9S4EANNYddYprv8+QKx5PVNiky+WvX23nEZ5TCCWMeBkKJXckHBQ62tOLstMFAM
rOqv072mqQDow/WfCVwa0MfagGaQwiCyYcKRgNOMWOWu3kLc4p0xRZLLnFaq9tP
L6lm/uScCt2dDVXcdWZbh9chlqj4mHWR23VSIe8Vj0cGz/XvYixnFXjclNaA/aKA
zTUEj9v/2BljKMq03Ehw4XUtT/MbeqxjqLC+Ky5D3ZZGjPB0j1AUwnYd9Be/rshb
ZTac/6SCe/6uGT1DF9RsZzqx6aUNRGvRfs3Fmrqgb41FH9nCdlvqkEEDjtOOEmBE
SfwCsU5B8GnkfgsZcv8BG1+DgYqbe+nFktPplxD7kNs5q0BZ9eFUBPfwrsQZbeR
57R72xCj46qFrR/kFzW6e8q//jpfOrVQwKtvgTcmzq9XMnPtssuA/ge47I2nVKeK
n2zH3zlV0EtV2sY7ZVbw9xjXOlhzchlBZx6h7ddTU9ChcJc664Q2xbIGntkvpcZ0
yQeli0YlDq13B4cYzvugwaK/zQZ5G8vskldAziOh6kMlM3DFml4krq27U08he4sH
l3Lf9bRY1KLg8o351pi5rk9saP4b6ixQiykiDfha2V9sKU5TPRTbOCGGM666PqLP
MhMAETHkheP0OgAfrtsdgljWHvUQ95e4eGAfKduXpJrIphZ3skLXWBSGgb26LZ3X
e4GwoCtn7cJf4M2rL3Mohj7lNhb6Jk9rPfiXi9F13KABfvc2QW3St0mQuK6ufzyIY
BHRcdWogHvO5owMFenB8t5H3FjY9YaMdoqT2W6/BPEdC9ukg8VRs3dYMR02xJ+Ws
AvSeIv4wM+8gAJ9ugkcqTW7cgZul+933qclHIq/Xd8utGZ7LPBYspJP7ZmLMHO
iqpI+Q6yVmFZqzhmlDNnpENwA0LbSOF8hzuRpzRDqPzNuIilB38V7p4FvgFrLIsy
RctNNGiJer5W4FCKq5tSb341IeVIHlvm9A8ulhjmyNW89/XPDBEOt5G2KupArJ+
NWtuR5C1lPbn6bqNNrIQyc8m4G/z93PfwziU8EJPM97N9agMv5m9Zddbh4Gyki2D
Y5waikYGsoa8s0Vsh9X77uJswQ0ujOaQc2T6j7geqx6I2Ous0MP6RdQUTCjEKilP
OzgBlaciurmmvFcjm+c75noPsTayFaZrg8nQLGfDvX8ExXDRlmXOWPnVm7sZbjN3
JXowfcmgHlHvF+3HY2ROlJyc3Ji4tLLDPpyfTEgsfUh5oWtyoyD5nqvxyO+oTlrW
A7Az5jhx0El2cwe1sdAMP/3Ui+baf6DEURVBf/rbszdf9fugGtVEDlhvi6ZA/a2M
S5PNm0Om/gTLvNBZ1gTETVw5Ra64PlOyO1MN9l6YFuuf0EcOA4lpulxxPZPM1xwL
v76Jfj1HsNPC+ppA5oWKRuH5n+kqRg51MtnpKy4UEw7yME+VY8X2BLRSArirrooFW
UTh+A8oZy4PLiDpb2mCbTGI2H8q+QvW1lZowUxaIxj3Pb6VSAnvYNSvcdTiKM0/R
Y9AHxn/PA6giydrWcttyGzSutnpwqH3J4WNSjMURpmn5eHvWdK4Q1i2cAgn+qxn7
3m4bmfcq+5drXB7pCcmD0v5YUnUdI5okJRhmKNI9EJvY6nTor9tiA8DW7nke3Bf
PKc9JNFWVr5ixobcIIYLievzqmKpGxvoi4LBxt0JWwgrMlsWqBnpWgwG0ZlSLzv
Z5VNweqekwoX58/1Qu9+A3Nmycp4w6nA1sg2hfPmE77ep8hcFnfwrDU9t82NdxK9
VJP1VEN7pN3VS4p+v34fVuzXaaHNJ+/p7By+tPps33qW33DEQBRYIOTHD5MJ/ooW
ue5e32UNLD172+Lz3CilOr9Iu5fXCQATAgjitGujsdFvArhfWQZlscuJi6FqTQ+
1PlD+uQodmXdGHBcHyyOzfofyf7OhWp061WYT+UheSoZXkGnXD8txLSpX3ZfrZTlC
Va6yrSM9AKSjCZ4CE0+jciEMV8efqYlQoYnK7cyJ/rqKiP3fxsJ/Euzk7Y0idT7y
agwmqQboH5OgsjPHIk4UxfrQ0W0zPn/qttNt/j/n0ItwzqKXKDZTaseQBEHInoyda
y2IJc+OhJNqAb2QLD4uUWjbf2OLQbrYAzl+JmLziO0g0LK3gj9VCLx+Pd2e7iMa1
vyR7l2KocZ84bXhcr3Y+wBKCvKPYKecwcVn4j9E+H3QSEst4IwrBp8KdHBSae67B
faPJfObSURbgMmRlyJhoAYAHTS596oejrZAMbci/R0VGyGI5cRwKiA365VRzZdNb
VW1qp2klAo/HxftAQYWo52hpe0vWBSBZWCEJmOLAGv8msZgVnkNv8uirPkdGj/zM
19Pqm+Hz7+jdMhi0ilaIuqNcuTnab0jZgJudibQ474Dw8X/BcUxI3GT8Xi78RUM5
0g69tEuvVeg4KdC8X2iGOIpVXtTI5kNLAP6IqljPqjIhzihev9EPdMITvG0BOWjW
6Tk7/ejb3osMgprj/9Ae4PvFpehG+CU9urnmE/p0zNyEUU3D97z+CrFEiR7iK9OW
Y0cO3eHr5Fze0HubU2/HUJV+gExFcvsNb6XHfzKX0NIzOrRBm9aJI0m/I/8jXWbh
kBykJHWErSkSUufKaDRg4cs7Y0RU7OTH5EnQYGCyBnUcPyqgPlLUsk7gKE/Q0h1
RpQfu3gPtBJxfE237es1ZVOKGef9pQ8VPuWfryx37CquKYY/pCJvCzG9Z5Lnfil
ByfFyGtYJGOZCsIj4+6HVWAb6b0q/FDngl6pl5JrHOa7sPnRsZ5wvshzDgDe7e3J
n2kbfLwMiTK3bI+bj0Qu7haYyIckFW5NchrFzpsGCiKcaHb4KtD9lplBRt7VUM0P
x23v3zUrNuINTiOHDKsot042nH6xzW26vhBasbXsPsCgKk5HlBgry8yXfNjqlEgf
5kNEbQP8+uaXXgDU6FFVcradjFhyTis78tooeRroINDAOoXMM8cr6ryMRTZIGho
85EliOpDrV2t18A49SjXRGJxcQoq2G4KDXSgAstKFCwYtfb8ysV0ysQ2ZC6iDuU1
KyUZLz2lIxhN4LeB9kRhhaA6xgY8wPTKrcb8MqXNVkWZ79J3CfHfBVHpeXQvpM
qR8Zc04gLxKzj1oZ/sOFgYmsLbFmfJlNBLBn3Sww5h2N14heGLUQ2Kc+UgOVTVSU
pc/2YbyTAAfx2d556Xzc43fNLp4/2C8qlj41QUvhOvGz2eYU8Mhg3sGAcD9ZSN
GfK7o9HHQXkKhzcgcxxxzOg7+95sd+lGs4utZliLNL1VzgrrzCj1P3kiurRtqOGH3
8YnrsZbcL9TPlt0Hhg7je3gKSoC/D2sf3GoMV4LGuWv4coMzQiwNb87V0y42/Ltr
H0wUaWZqOHANr7vTud/KEp55Utw4hN/+gJ0moTNgFazEVNXRAFF7XifCQ4w1vDQA
qr4/EsK9XqAvvdbJbX7s97zoZpWbYoKU9W+REVZgAiRvqeyzBIAPu5ziBmXfy352
JQfrwIHfUhwObzPjsVvoG+vTk3tgvtEPAPUO/uvOMNDvqlqvHMCQXsJfE3kwsJJl
Y7rW3jG5T73JtCAWOEdpn3nYDQ4asHfky7Qw98BwQ9Y82DwYctGvWMhfsM5HGwg
RAYjGXQHicO+lMEtSEgEq85N/b7wtKz8Q8bulntj/K8H0M/8QV0QpdN4Lhi7jPNe
wuZpfjGUpyz4L+LoTHPZNP018d9//maF40t6zxBedW5fw8X3okADXv4xP57p7/0
BaXhUMVcJrm0PPM/JBx9KU/D+cAlaB53nXUa3QgwWRaQFJ3j/l6C3aIiziXnK5AT
rzBf/sND/yVTf+XQE4nvwGymMXruiTnHBK5bgY+oYDSHN109Cu3Or0IZl0Ta1nJ/
467Mas2WfyYJ2qF0aki7ijH0mjtj2HX0/01AhwsO88ikHpZLPI/RmqD/2pmVTW2s
VwIU8hwiUKNAakV4AvIrpfgBoEKymIvOLzCLi8QGL4TLYMI39OVYtswRFfbbww/r
pGphs0xJ301IoX+mJj1heYXeh4cBt61kCnyNm4+m5WY81j3rlH2FbALC6ED909u
PsQL24fx/hzra3m4BRFwgqVz+vUVDomVDns5eiEhHLLmm436Xq0kUQb+HSjfbzecz
yi9BflCBsczRmNV9WlJPascMrDYUxkzlwRUXQ8FWcbkcGDm+MGfxjKh0CkC6ulk
ldXXb09FtykrI31h8RFAuRkWq/BIO2CYTqodjh9ESgbrZZWPacMvv0aakWwWede
bPTSVQ/RQ3fe3UrtBybvIl7m4mScqPQCXzNOOZCN6/66Uv/32iVIBCOWCVQteQs
8daxlt8/e1//YUftfH+Fiwi/kGoQQi6R0nopWn/ogvfbtqCRU3XelaM55IclGB73
ow3T3RKkTWMD/M3TDuWg9gSNJBEdfGHssM+s0PbkLswTwAPV64XgssTvsKsgGou9d

05dFwGymFkhhvSY7+BVi3yVtLa9B9/C9MdiKpdazLoJVbDD5FcNLmUctZjM5Gvvm
oPgq+i6QRLof/rwRoIn43+61WRs5+t7kY8vOEGwlv3MgXScre5c2jvXjeUUTn2B0
CaG2A/bxwPekJNmyRjI+Qfj5jegu4TmPd+5EAB5HwldSBWZ84Yvda5Maw3z3GbHX
g7BRgaq/smsvKgpAVW++cPkrQO53N2dwqYuEWadL3M5e8ODQey/1RSy7SEH7cr6Y
yyg+lyUI6JwD5YdsOay9ZJLZYVPNTf/igqcjpkWS0mFneKiIcQb5tLptL8pxlfiW
N7AdluC38UEQxHZja06yi50VzFF1k3fR34mmqT2GvMxxpFOaNMS+ymPdZi4kVZRY
H/TAgr2u04Jk0cOgh3Jas65+AAot8kV31fv4Pa3+f/V2QyhUvA9WGGFJEUkFVK9E
Oz4E399osTsy22zsu/qC3PuEN9kNrwwPMiXrKCr5fU2ts2LImF5InsJfjgBSZpwe
tFLAYjp5Kos5CM24NURP/+cYLrWCa6MUXqsQpO/q9Mff4mIeyOTsF2yXh+Xur9ze
xRepI/+HqpMlrKJCLNiQXy4A0JiTWEyhgXQdsWth/RnpZ/udMFOGIWxgidGigOjY
kslWFZe6CpdOS680i/fmSPOruysBlK7a2ksXHHdOm6yk60C/AX/tTKrvZl6Vc3pb
wpKyKzTTlehMaIoC5lq47wzwW7T91957bjluZemC/+sp0HGxqjIvMxLepZTqgaX3
oNXkaIEESIKBIWHoNHqXedTZB4YkGJEqVXX17XvX6tBSBgM4dptvm2NITs3LMeSI
bvfk6XGNPQOrshea52M5Qlmljmd+tToIzonrjegRnYwletm9xLikKnvBGRl7o1Hf
VsProOHZ9Gxe2fVVYrOxZuZCwhv1CKV12LvJrm65k7rAM5HWqHOTDr0iBs6+Fw/i
Sk2rbK86s0N33RJsR+GXHcELsBlCznWzk8sb58moX0PflK4uF7PpXfNuCQGBjg9
HGnFmUjHvXoWk0MtcZlu20vEYAcc7vG+WRMl/ry5ltPRPVognUU3OKqINTzp6rUi
lSVren6odXUL0+9Fl+FoxnjTjb5VWl3G0quz3ipMxnU2rOvE01flqCdJfW4NtnZT
npyY/WYibM9cU53qVxm0Pg1DeWX3GPxs4XH5ScfiikbdYNF0j0wyXYzsskWFzh2G
7ez5pC2JwqwqjER65lcktrvucasz9e1o6BP0sbdRjgBrW7etVQ/tAzVSYnJrLSrl
G02Xa5cZhyGk6rRmTfiTvXudIM52z+N997r1RuGwIbbne2lgnlfjOW50/GarFsdK
FK8OTGLWTPiY4OvW+7Xp6/NmXaTXEhsWx7qfjH3VN8Sg2XaaLZXfHPLK8zRCGu5x
Our7o8Gc2LeMlu7pyzyvHYoj7Kmr2nWhO6C2KsX7Y2pi+/OGf62aQefQmdqlynJ8
pztiQ73u6uslK3Cdi92iLkH16cr/hkwryoZwDKHf6zZmZLB5jCr95aRvKET21uW0
OdXd9+ukpyqlHT6YtCegeSQPo7WKD/1xeT3ADqzxvC7Y3TCa7sdHohdWibged43j
et3oyuJpPqRGWqOiR6vxd4qQ0CNiXusgrqvM03+acNMi5LrglWbGiy3NN6ylmQF
2w4P+nBmiIvLlrTjSBg4/VrcM+ZWBd8ut9NklVzs5aleJTpGefNHhz21PN8WGMi
JbJ2SZ321YYW0GXvQrQZhp1lpvAor06NdPaIlU88GSXNc9TGu/TI/tQzLjTwtj4V
gffV9A0/XEq9cBZ349mFbUblFekkrjW88rOWT7YOK94iQtY6qar76WQ/qG+PHcF4
+ub2Rqe6tIkT+HOja8U4UMeoW69R9tTfdocSbV8nqh90l/VtrAnXPeLlJmcNZptL
a9rGm7WwHKNHhzO3GLOU3VueLqvOvqXlGFL2Fsu8nM/V5LiqXdjDTLkE3sGJDMaT
xxthQWnL86njU9K8nEGe67NgyfflgRnTqhups7MXS62VWpka3WVt7swXTZ2pcLWk
wzRoARKv9tz2YonctBLEtu2Us+6r7bGlDlbqYXBCd5ZN7lrfjrdmMpeq/kx1zt5w
tLeufHI+saYeVw/S9jKOhlYtXyXGItcKy7ujLXO9P1WNc3c2aNfq8wNx7iQ2eD3D
3fhUwX6nVt1pV0kz6mr0RT/g4jVqE0FtowsrlxpoZtkLWnaoTkDy44rWHGnkgTmC
A6ElNwovJkply7sxOb6GZCXEB96pUuXiGketZLLuLDbiszK2cy1Hd1T45zCAhj+v+
UW2ptd4CQtS2sj3sN8J0uaialEq2HKEljdTBp9hxQyeniRlelv7MvDiNsmgcKA/i
qcnSEStmVD06uCUJltAnqsyC6xvt6eJsOu5sj19GwiYWhrMT1R/52z0zBave2ktl
z7HW4My1Egth0POGzmikNQCsqzUS4rd2Eo6bFo/324Ry2SkyJyVrsMTzale1otdr
0G1Pni4fEmcsp2SHYTgW+d6U3HTG6pqrzrdb+1CRjFVie8eAOkTEDeYfTyeEQe+rE
33DJrBRU2YnXN5JockQsy0U9bQb1Tt4g52djr2G38cnK3LFu7u41px0xUU0GnV8
17Qtyh8Z9G5McTFVsU18Ws6GurQdCHrsKP2JxZDTnW03x7WuUWPbG5MKDom42nH7
8ZzajcXJRgxR01Dud0Y6XZnt1WmTK/sagw5Ex37/NKE3Nh2fB4w3b3u7vrExqyZR
pzaHKtzn221H7fcgUmGpJnadW+eeYVarzRp5Kk9zJArHUB0lkX5U5bbbhFXVTega
vRM174e9RffArNZ8Fd80a2y3rqtTVqACGzfm3HggDlWpvnN3ptJVq8+Ynj7dchX9
OF53Vm3vMJR7R+NwahKDuNfgLhdr0FwJh5hd4VxwcGzqUPW04foYldM3XW7HRLvp
4ToTe0cpOvtVm7G0HQUqlmltVlS/wY0jedvVOa8yrEQn31F0jzwfHCLibYyouCY03
rR3jTnxYjuMwqPomIsgEG3WDyUa20d02LXvJuE5lwfZqxmwQjG15s+x1YsafHFFW
JCj7tEHjUr0cmHh8nDHj2lxcuTvOYJuuoPWWdVedj72EjOdGgxguPJ8O2T07wLmk
v7Jxv+bWhLK3XbEOK+1iMiN8Q9dkfjBeh2JVTfQOrSQTana+rCJJnJ4CYi2sh3U+
SEbRwNmCFloaAxGQnyIUvbiBDYl15s02rR3bLrM6rFe+w4tc09yzs32h22cuwQ/x
tLUnBHq6WgYctfA2xqHS9OrlxQvnqfRqHrU/0t4JXwtVd2n5srBx29dJpb+jINAE
N8XxnJ64STy67NQDPQO57Xov7JjGZbAvj0wcaBH4UPvFNei2dlUFTLnurQoe148m
4cHc5ga49bo+Em6nJlMn6JOjN5nRZEKpdrI+L6+h1DR7HXbCA7NezSzatfomNReP
2k7aaKtXa+Kuzd0YbBKzTuSGPFuaTU7sxMpJpQm+Hjd3ZaRlTakmQXnHG9NG2+LW
oX4laxydHC+qHeKjlorUj/NgNiSdJleprsXrCV9EtXpltekvj5OyaLDEkl945/7g
ffZKTSG+MmutLmzt1fTSq9KDTgdvNrRzoqWf3G6pM002o5G672/3x9P8MGyU1emk
sfuW4yVhdhnu6lLYrB0Zf3NKph16FuPX0651ORD1GPxuXltUpuNYtHbchum4rTM3
7z7dZQO1L+qUzITtUa9eXWSOlfmR7Y7mwyFR23bGiyCZkPRst5wYXKOyr9StyWG4
N5TmgJWvptkoe0H1lksKJpPlxNvibu9i+ls+HrXaEr/xuY2wbCN/b7J2Wy3cGLmr
ru30OWsS6Y1FoA9XdL8csEnK8pggVfwzX5gKy6z93hrx4tK7GSYZVq6731lHoTz
XGNkziA5vSYMTjQn79bV66ixaZRzjv2q1zu0O5VB395y6rm52RiXKj4c+ZJoMJVp
v1J1BE9sJgFb6lewlHyg+cy5K+wJ1Zv7w7JBITZdd12nK0cs8L2t01GooNmbXSeL
PTE+94eTmbyc6pfjZdeDAe5paqLifED1++ysw7i9eXl39K41iITtkzm/3RxY9oEC
ki/4mq05iepdukdixig9m7EbbocZdmJiaYRA9WR0LVWUarJY3jJ2qAXRi1L7tbYV
HWx37FvgEqOnlEX7nT2rk5a9mV2JxaYyDlYtUjY3RGeBRI42b5L2ZLgrh4hef3zq
TTaLnb/wl/6MMKvLhFOjTsvjEq4Gv3343ahXp/OgZe8qKr2PWraLfgutiUuU91L1
9kyrshM61ajCBtqqVt3MKtfAqswO1dWlvrQn3a28sHt2bCm8wOm9Vs9orLrOeTPg
exvh6ctVLHW2SkK1f55eg+UpFqEEF4squ+quVYUmTjU8VPou3t7g/Lx/xJdxh1fI
rSFP8GZH0J8Og1JMW+Y3K6MTjMzGVq1t2xNGaAzW9vE8OM5b4a7Cznv7ldG9NGaJ
OWddXhN8tfdlK26FMlxa+UJNvOayAS7uza09ubBmq7PXo+Z4aHLdwZxKNJmBIE22
egrZ8c011R83gu3aHrijoXc1KJYsQ1ByVDx/H0Vhx6Cm6taYR868cRkLw+NwdR6P

KuqmVV1t576Mlxy/Nj4cJfcqCivirLSSdulUDneazObYjpWq1ZiIsUaLvSszqhHJ
+jAbLOlMqLTmnuifOrVQVpdbu6cMlaBnTrwpc5mpF0ktK7pSwyUgz/7putEp/tBY
VXqtWfSsu2gtx7R8nmlpDd+MgOjv8NdG8qbXD6/743JwHFqmlm3454LfI4UZYa7g+
2tfCs0H7w4p3blwm14q3otUwunaDLXQWD9YRj2ryGdC/22xzttrWjMO2y5e3wPJ6
YM8u8103ntSMFekpokaEjDplcULwT3ZPGNmL6STcSfnld45X8UO/MtglduKhXtkF
rU4ZacWqPwqvYVdQ/Cs/GQlmVYk34XET8OPLWwp2iC6/VfF4Xd9b1lDbB+QuDliZ
OfqxJw+DuJxzXGtzeboZrjd+mNTFUD0Xlr68EI0dwXodsVoPutSIPLWOU/OOCsda
36PHtbpco1031C90+2lv6EQ4avHR3dTnzPp6xCuyvRqBiaUSA8exWpOx8atXt8J
bL0prPbspJqW7CjLrvSWcIsr1QEzGB1mM069QPZcqV8mq8k8z07FDr6gBUC3BgZ
/FW90hdjJozJ91x73B11fdd31KNn2fbxWzm3P6Gi973uGy0rhTifZS+fYs3fzPUNX
ufOYM7S1qMULktnPuVanJawG64tpjOaxMoq7SnNYPqIUNvaHsUNx43HvsPVt/dTa
HhmGWB2q4mG9s4ND0ub7C1IKFFJ0z8yUHSQHaml0+XEC0eigrJvr6/xy2AdCc3Ra
jfcTwmDUl1fToVnyuS+3whrGa7k+CNOHk8QJvdTa03a7UrEV4SKjTrNGLynkNFg86
31Vb9BV90saPLt89WjC+NXn2JvJkBoBKV4VwCkaKXjWqfWz09RlwanEUF0tek83
gat4tQr2olWTK+uzhJ/aJ2tC6u7VGrDDcaBcmeZ8e/SWhmDsDtWAuHTY8Valrfm4
lPj59en7UA56ZG6mA3nrzITkzCi4VZ3okdfPLdFdaKAVGF4YQ3DN3f17imJWxQ5
HV5bq5oUtXv1J/+Maptbe3FeXnsjHUqzVRSKA3k1XC/96Mw3cKdJX8zKcSub9AXf
DmfalG15TfzYXTfxQ/2oPX05cacBXv80qvqry3nHX2ojv2UfBgRfbyjSOS8Nce4y
GjmrXLCBEWdcBtUWWWeG9jluq10LUw74dW5+OfYqW9hqVLVw6m64UXXhpjOc0MSB
fxIulZoo+9RIaszxdYleN1qrAVtpE3hgmff2Vd5Pe6rK7Q3RjkbUxQipxaQ/M9sH
uz49zBrGfjZfHbbIsektD2drOG5YzLo+OLLmXic7k/Fmz5QvfdXgd86oD54ZqdPM
/BpPrqSyMqBS3065LFkx7Uag+ORRvW4XrRJ6ZbN6vUTqyEaykYltcDLCKwJpQz
6y9nmuAGo+bAWZCV/ZqTBGvAEZdEJmtoYX+6WQgXVxYH0/FoPhht42Q6rhvx05Z+
tclagXSXYbezGqXNfdkR/1kecEX3W4jZmmRkwUOX3bJaeAoNY/dzrneYmddOmbP
8MmyF7TvrYchfd0fKMLwyo/pw7S18pKgNztTdfos8Lvhqm36ydVbUIY48qj1XoqW
ogmxVLRlkqimGjOyDkSx0cJ1Hke2Leya3IQ6cVPnr7ddWo/1gHZD80REZ1KrTi9b
f8b67IhvNeeu542D8oXnTdx1FvWGOK7j54vmtsa7XX0ukMLkXJtV/Esn51SerFes
BR541918NkuZbrURSd7OYsXFU/pGv3DaZjhdNPFMRNuL1iA5q7K4t9cKrhC60Daa
OK16J2Jr1VvN5Sa72N0uB8S411vV6O20HG+um2Nr21sda+HlyBx6m5gZxPiKJve7
6OiuWGcdul794jHqDHqQToYVWwudS8W3R3KwCDplBqw5t92c88Eq3J2Ytk8szmuZ
4fx+V6EqfnuwXw6jERily3p6MvHdaLeLe9JioOylYe4yGNTKLpWsm2EinejhnrKX
rm+OD1tTKDWdvd2YLJu12bht7TuBc22NN93m3LE25/bpNNJVzxaZFXkorwf08JbQ
6Cn1gYArU4Ua0W1LoITdxDxoTBzuq22PajrG2WgZ9diSXOI4V4/iSh1Nxx21t43L
/lknMS8tf9ZnhPG50yBDoksZ9YNU0UyDqe4b9r7e27Ha4VzZNayTtz9bLrhLFDL
Q3MRTnb9cgp/M9mbbZxz+fG+McYH1LZ5Zq1qawRNO0h6v2EQw2GuXiyVz8iw2dbf1
DS5HvF/dcA19NKxWyjYg1ELanm6Mjuegb3hqNvnLCCa0vzbZhBqSB3zPuNJV3S48
VfQ8qi01NVk1jKz1Gg9Eblne58gZTY+zZP3YHO2W573Z7XOx16xcjiR1mV7iQbg4
C+fLtDUklvu61JMXxrunuXWh5joDvSmVv6vVxKN5Ldg2BlybdDcHnDeArW51SJDn
0T1QVf3cGrLTQyT4Pyo9rbdkUX83JkrDtSVtbhvl2K15bp8tq10Fbd/ML2RNvXR0
nhNI3qxNN67ph8GxNzIjV2Gnk5F5bNGssIbRifTSM1lnkzdkMKlel+eRMomIY0g
cj62BieS0XBmL+/ac6KnHXY7f91qM1Un94v4yFFbN9rx0r5vWnpQ9mnr5id1d1XK
O/YW+01gdrxk1WhfVeHan890OSJ6x+A42igRYxwCjh/0rM6CncRBp3Ltm2uhfC1S
YJ6pk4338N2yNxxvU1+Y5IJuDCVXvyI7f9IN5vd8+OOSolVLSxJLYVnMr010vPkSb
E9Wr1VGDPDFCwZpZ27X1XXk47g+WfJ0Y8OxCSAutiZRBoHr1Z5g1jvKmpufdxY9
OZEKG0b641j2z/Ber6vim9VI1NizvrhuKBxn/ML4wvYaa5ZD2a16rsSEauR5B4Ny
u41BhyZxcaluJrTVK7vuHJckTLzu9B0vXFbaYuW8qymVksirwYis1fAF3ab701kj
afvQd891qYtyZ433TotTgNqVj6gsWgIyWkik5vRkF1oh3bcnFuydVxrkYMXjLRF
14lmXON06Zt+4C/m/ZFyjYmL2+n2tIQk9bKp69rLvJ6UCY6e6KK7XySEy7IR0fKv
KzE6b1fJ9Tg4VKt2V9RlfhqIiYv2EU6HfjQ5VwWu7LrrnUN1SEmzwZaftA0CeDBx
pqsgabRvATzYGIPTpb2h5qzB+OPj20JxqVsnVHhD0fQ6KwZ1CKq7X1TX6PREHk/s
8LgM5sGkVWFHTC2a1JuL5owazqdfuSb6zF7HALEMPTojF33u4xykZiyS8WM1Noi
8EexlyjzwXDOcm5f7V3ppemGK2nrz0Mjaa5ibu5f5no3ik5ey+D40MCXBH0cP93r
PgpN/Hya4Tx/oJoQFG4Ie+NtR21x2R52vT5BnI6H3ZacJik09PxO3K1ZS7Ii2bW
cdCeDcsHGwFD60s3as530oS1ls7J3/gQXviX21Xe1CbEWj1fhdaYNo+k0ak3yI7q
DeVatznDw4Y7a5QDselgEOjsuNpeKbHQqns3eK/RiI8Ou+eFU2vQNGe9pd8/UpcG
ZzQoWb2aZ5Lc8KtWrxl123pZA5LaKNyARRSY+DAYEle5WNqt/KHJ6KNuoJonRqtS
3Stp793WUTvaXbql4oZCzcSti4+e3NAADw8yzVvkLDqD4+KfB4ZwrRznUldfxZNE
FecrrhMPRX1prcNRevj3gyc6muDWHZZ7+1Qi9DdkubQm7nCwoAgxazVrbGZcOKg
G+/6FUJcEhX5UDjwSiigY9rQV6eZqoznTGLjk9WyytirdaV4vuzunCosLk13yjo
IOROhzFBTCxjRzUnjXh52FVHvldjOAFfiK30XBOqJ2qnX8/Rphwiiq4y181Zyzou
e70w6nX1hd7VR9Xk3D1F9jHQW7vEnZ1E3q5X/IRsqFU+8GZ9T97F/UgclX2NM90Z
XPdguThW3XOHVflyIucTZjfvPzKxjsiENPid2RlZg2ldGEwiSzvS6nCqHES+Vt1s
yhuzDFmoZ9vuTD2uTGdyG1+m55VG9AcnY95yBFvUVp7GBMEnSGj5fNPMI28wtXyH
dyyFW+psKyU6L4V8YpvjFqu0WzVTZZPZCO9xTcmbXne20UraW14bXnbHJGnIo3V9
PazW5ld1latXLhHdLy/Kr92pSF/xCx8dm0yjtVDKZbHXIVq0mvyE4nZG/6pz3jBZ
N117r2+CxmH99pYnet1eBrq9K08ox6VGh76wEJe3B9R8XBk3+Cs13B5ntFLR/WO/
F7i9Ha2HJ+Egbm16Y1P6/KpTmsY1PX+Hlw1KrK23ajOenoxda7QEb5tpGopFLFTy
MuLDUDJXyDqDFO2k79Rag1g3dyVbHSy5dqkog+XT17406zO6t0pMV51otoDWH/t4
T4Vo2286HfObdGWXWEodX+pcT+NraioQ+Dyia5ZIKn45dhJNiTj3BHBN+koTVcz
9p2w7Vin7rXhVkcNbe0QB25nXWHnsqSuzBpx2yz2p9FF6kx0iRt8gTb8ry2thk1
0JLKjHwaw0qqN8dJfzvRLcsaORVOFLgVrkIcI7NiZ37SJLtxicdu3KouT1+Xttqt
nN75vDfK0FgmX9kw7k77Y9sbjrrreNBZzG1j28DHdR4sgaketRWLx40qESiXtTjA

92X/jBZYuhULbHy0KirdYKRuRWYzW6I1rkKL54rEuZPmXL/2N4bWUUYnSug2ieow
YXS5UFW6nFrFyXPS4NuLRn29EJaXQ7VW9UBN4XpXlyAaqUNsuImVa2PRAvKdlhwo
xb50Jf36YL2MVztuV3ZDB06y3s/NmcJRjaRrtntTAJZ2fZpoHjdRxxmj06nZp+3S
31Z9HvdK8hXlbWlL8Rfzulzd8vYnbRlu5322xiYn+6xGQle9nuLeZLm/tncn7cIc
NkDxniQtqZagmDW6Oxa6s5npJIRxWnvVcgp/7qw39UHfWdk252/IxoLvVSZii/DX
W9pgmaVaqQ2C1nm4XA6M1q7BLGnd6YW0Jg8XiJetlq2TLc+q1UF9Z1y8aofrypWF
AW5xtPW9SX1mrI+iZnhD2vKsrVodd/3ZWhjbo+bVq8YBTVTjCjqab240RdBXzMWR
vfaZDPc7sx/Mtb67q68tblFnTvth5ert18cNce32JsR8ys0c4Ro41ejUfrru+dQT
FqttrbsfB/toJZZGicuMq+OR0Zka5GRgVzdqdzEeervzdm00+Etyji+zylhdyVrd
fNrnyLYu3mg0PgZEPXviuNqkYw81rtveH6L+dT3QuYEa+c0B3pkvq7XRArTY5u4d6
axis7mG8oJ6+qWUYHt2Z3DivB4bbqg6Xuz4nLdtsfDrO5IAnnPph5LoBbW6smUSQ
4+5JlunAncpjQb9W2kF5TTisn7bkrhMNvJhtD4h4siKD+ah7Ydr9yzlcj/f0aSA5
wwiBq42dflyM6dbkutgk4Z5rS03ZYtux4f+gJyZhyLuNuWx4u27s3NzUx8PRp7b
awjaNXKj6aE6PWswvM1NrZ1ypNa7q0nLjUmv+nRXBF1lGW/AnZc14hhRRNhFUB2F
HXOXPD/vKMcmvx731Rj3prEcdWu25x/GZizi3cp5xOv18orYpr7y955wCJP2eh+3
CL13xuN43AlbU47b9tnG2hQh26DTb0U6u5hK9IXd9PazDrMcD8fjXnmLBYtvom6w
2FMrr9cenlftVYXbHMDxZ6jtiVFFWRJRL1FrrOCd/Eg3tgsZJ+cOPuU05v5yZMrZ
A7ySUELTVfjt1bnm7WO5MvDgyvw67w2Y8XRQPQetuBoPDGPHbbs4wUXqchnr4gGf
6vhKPPRP6vNY6N48NqnEQmp8yGoTU3V4YY1HRR5qkOURnJAbE3t9yp5hp2PI9N
aiFT7Myf9niaKTMgrm0mbUpfeIIbb/iFuZZXzliu8TVuPoym1Y1yKqTjZJrMO9uD
JElfb5V/v33ah44fY7+Vmv1pafuxHf78U2wuXBtbBKF1h19fyBfs5Fjx5qtA/IAT
bdfdm5b1+Gt4Q7xAYVTB+vn9lqI4DPz1z/VO3ahLLWyoGaPeF6zX0qShhg20VldS
MaNWH2I9qaphkm5oA0yvt7QhVpPGGiaDQ4mNOj1JaWrq58+ff8LzBsu94UV30AwE
/kk/oTn8/PBK7qoz+FUz2q2f3yGIFWA/BHvbP10i53RZfw6d/X8Rsb43/+TrdOd
/CdR5lv674/Ywlzuj32YWGvgtdG1hvTX9sRZsJnz7TsJ1/ScsskfI0dz/6CxcEr
jAfmjYUQJjHlGZdd9+gPh5xwVBJ7+fKcVby+/CVjwTLxYFC/xvY5/gi1TQtVWT1A
39DeBo6P/XLampGr5YRylCw8J45tCxeYQXrmzk7f/GBbTvzrxoniIMwWf0+hE9tv
mrpN9dbmy2NN/AW7lbgP/ENkLwPfwgK968SvezPe3Np9GNHHe9WX19eXdlqWCWN4
+fxlRiXs5XN8jrOpfytP/i852f0AjtjY73u0MA8094EFgZjR48QuZDghvclK42E
9O3cfvspWoIox1h82dtfX1Dj+NY8mtntTF3Rb2NeXB7nHsxcRXuJBNGKxzZ/epeOP
Wy0L4dEMsVUC7P+K+fYJm8yG9cms+nlozzFQNPrw8ceyGwLFP9c9E+RLBZ58xUrD
c9IX+Ms7dXrBptm/V2efvni3jJic6oh3TzWi+OLadxsos+i9yhOk6KiQwP7w8iP2
tkDNBo8sRiUoltifn9ooCGHGsbnccfPgbaMjfpQUVHyhyI/3vDyx9AgwZyV6IBBwb
juR23QCJtn2QKN/+csOFn+RCB+v+9Zb07aOcy9fVlH0QgdZJilLudry+f8Qg0ZpE4
LoDa5+Xaefn5Pr2f6p3eyMCMWU/7unEsC7rqSG3taxLzow+CXI+l1kj7+vL7g0ZQ
2G8PUvG9FvZmFJ0ASN9rgflTLUD5MEhArm6jiMyj/ae6Bla+061Q7hZJOOceiTlW
JvboD8B8NG/0IIRhj2XgRgjviRcsDE7oIlUUAoyIgXmgU3d+PiJkCQWwFwDrvi+f
ASZ/+r8f/nwQh/vT+0BNbBPaq3c4+e/pQApe/RWR/Eb3v97J99UFFESwFr2m6vOC
QQ9ro/7668I1/d3PID0dA4ucq/2V/BmpUPQTjh4BVpjvyNoD1V8yGX3J6P4yTEen9
UtA+/+OhK07k9Hvm6tFK5Vb6qQB2Sjz4L9/+8heEpv5rrtIYQnoATmflwGsOaers
tu0fV3JUTQ1Hri5B3j4k+YIE31B4L0EjgB8I8xL60BftGwctiP/bzFmn4HA/21d
0c//ydb1v6H4fy8oph6xmPqvXOKfFuF/4/Ef4jEAIoIE28rwMSXzxoywhQ2icOP7
uyidiH2C5ZrMvoTaa17KVosmPflaA1+/Cm4+4h9eJSC+yuSeGJ7WSY+pj3ZDqBH
CED2ILY//QwDhgF45v5z+PIRMwHhngt8uIPgygmjGHMDwOcfbtU+fnyAnYKYT+Cj
5nPghkAO6w43IIjo/0cpB5SM7Ne89S/gdPpL7Jc9uNbfHrpBP7ndy0u+oiIRhv7F
y5tAgEUAp9iH9BUFLPoFCpkLmMfg22ILN1jusPzdL0/dZ2+/fbul9+0oCKV+v4A2
7y/Q8vcm8ky0EsGAXv9MqF4QuROcMElVwTg4GQEWkFQTofxrGoMHK+BrkDif+roE
SZgOHkP0fcuBgjBpQ2Xilun/vt25481/Gfdgznn/fwUFQkP4+vubfkog/NfudQFC
ZYWzOQA0F58Q4mD/X/pfuaUHDv9xaiUnV32F6Pg3UG2pNdAkDYbBYEG37ywAMlui
9CcsCJEowkOU0EESeTKhffc7nplS7vGfJiOQ5WuUY2Shh0vXAWKHsBdvOoib38vM
LP4wO3PPx2C5K/MWBjax5/780wYcup9/amuGBM6L0XvV+qP6+OvLQNMH2rD2gilg
DbS08fWF+BEbDVpf/2NTxdPu/iG4B3amTLtBfM7N4MYT7OiYmOv4O8D8d0D/LqqF
b17oP7z5e2DmrHLygpY+vHUqSeLjk36BNrymyPQWdtBPDoy3Uu81Knx8pwoc+Gcm
7vWe2nV8YECcFcoB81b2Hf35Z3D3gVol7M1x971iaAjo82tK4fdgNjXB92elGiX5
+K+U1kIOUz41+3Qe3/M4PnxYocjyPTrOSuYyvqPOBF66EzuB/yWNEl4h/jB//P0j
MuUQZtqFMFkQz1hAg8SNnb0Zxq+3woWc3rX5NXdIX1FS7eEXigfSKrdnODDNDHk
EmLLGFuAu207jve6snf5p1Q0Idxdhukvd5X/BR88CI5e0Vje4Alq762w5xK2ChLf
+ncspU15qNjLbXr4bXovSNziJPTTVu+tLYsevJpdhfUFS41dGtmlJVGXAiuoi+b6
skdJMPL17vxfzt8XhXogWb69B5Ikr9PybC471TMSPLG1/g7V079aIgDac1iEEf
rGRpg7MJxPxWquSu/n415JWiGojBU3dz3V8KLv2/2J1V96I3XkHZMjp9AGKA6wpi
iOiZEvJLKnnoOaLoFyXly4In6/gvWBmJ7uLy470PLIrRv+k70LXyomsRLWV9FqKf
c6gYCNhA17uglXiAfoJ9DBN+eeT7YxOpLLlpASvDY/rox2LK3xls1mJWpPQCbm1d
P/Km7vNHD99v8A0ghG+5omi3wrc5FyMvhvTxHZR+rv1G+dEPaEte5tvHJR3Jn74z
vxwYym+fxrjY0XST9N/Xu7/z7OHfu/0ClgKE9+EJ9tuPEIOXzaJZZKDs+DXNEHYI
bNcGLXyo9oJkVZRlroiMkJD+OxriF+ydigiZ36mc/6SR0xMSFSD0IO3Phz9pKt4
8q5UPFPkoThKe2HBYgvD/Ld3SqGfYsQ5rsHE3i2WSXsBfe9wtPi5aXN0sIxeN35j
v6AH334pg+i3N02Vn3x7jxWpXHzJCJnaEjSNNw39kqUjC7cFyvs0Xgp6AUjLLx+y
gPX+CiLoLHwfv70dli+535TZrlstj/KERvFeE/dPCarzPQV8I99IptNQ/sGUYr9E
AejHXZ0zcwOI8F5/bpGqzR6B9/GayUQqT+DiJ8v4D0w9F10icItwD9AzQiH+njJ
gKa8vDkarwvHz/Ma+zBY2A/9wSM0Z9e8QOyJZgT9RCj0RCnLWwPYbQy56OatTdis
SJZrAafBdo8gBEmEc6ofha6a8ch+Cgk+lOqb2D8ndUllYG8rSyhAn+lzi74giYw
8p18bYbBt5Hj+00QB3jR9ENmHWYL5vzW4ts6jyr7nPN418RtsglOMsrY3ptIs2a3

iL3oNcsf3JMGesSaBfC6WZg7yciRB/JAFefmYS2XvabU8UBz10rV9pdvutTRDe5PE
eVmhzfWhrHcIzYOGpvlriI9XAZrHl/cbyMaQF8GiIIyz9YAfPucvsvAh5UdW6k3Y
+UuRlHjMqfyeVfntOTuZP38pyPpSRBwlun0nEn6bX7zHlC0EI0U+Iu0kejdfme
FpHj/z6Cxd0I0ts0lJ+RrH8pNlHe5j+eVbqtoV0V9frlJhc/f0APPxYpot+/Pet6
/nm5+ulG5X9Erv4ggV0I2B8IUppGGf1+c/oVI8Z+opf+IXv6jG4menXWQ+NhAk7ut
lGQG0Cs4cmHWPzIz3SHEB3Zopiby4/tLslnFguZ5YJpqf/Tv2A+hvQhcieuexW7KB
vxR0zLoFYxdB2xgqEdowMAJR/q2Uhnv59r8eGvAsr+FzeEkdhy9v83z1/KGidQxt
8HO2dnjWjFpX/YeWdtnG/uTyYfh308aeP7t2WPz9J6u/XTgsGP+n6wPJf4VK4Jh6
9zY8D+Ts9SZTz60Z2tSQBpoEtrclzJcMB9lJ+rFYHLSvGf6EF+Xfrq49D+4fXGFL
qxerbAWb//4mvZK+CJm+PE/5cVk+dQZ/yMtEaLE8T7yk6vLLt/8HfynlR28l1f8QM
8AVfinB0X9I4FqlsoVIR9qRtn3nuyz37A3Vw400+iXE7DEH/y0mGz/hNiv8PEfy4
uJdSyR9SkUgHnX600cd7wid40KQnNXp3LeW3Qp266di+YAVPf38qZkhyS8mddWo
pbgudwegNk jXkhStlepJqlrvVPMVJAPaMNSff+cOntKeGMhi/zeGpExxVAAFT0T+I
92mvP39nTBqiY/S9Id97st/rKZ/2vc496Emh+/6oTNMU0mWELGny/124ToEHvf0e
YHu2n3y09+5bqby9QUGvtwexirD/UQZAXhAvMWU5VWY0+J8gCV7VeEomOIqWGJaT
JH5We4kNYKQdImLgJ5jRikRGInhSkq8CV2jJFGnOFYmWVVRFXSRBWqqbrEkLqq
yIomaZoqEgLEDeYRLsywLUqoqiQJKqzz99NlvikIKPDwnNZ3XBIVVGIGkNVlIvI7k
KfhHJTRekghJECWeUzVN4kQYmKqpKqUTcnlkeknQGstpoqTwDCsqEnyWKE5UNEhk
KBiToFCcIIq8Cm3RrExB8yohkRytqRrBle/7hq4kCnqmZB0GzZMkRR06JquCIMgC
jFKSWikiFJWF+XOSoJGKKsFTgRI4jpL08oldWhR0kpcYkZdYgmVkgDmracpKCrqg
sQJFCQqRyxTwRkKta4KmeILOkqIm0wKllq+AVBigAaGqGsNJKs0JpExApzAURuJ5
RgKwsrqIe5yqCwJN8SRDA3slUhBgLipBpn0vo84ChQWGBI4qQApFYVS0IQSVSwHr
42mWlxiGEHRG10GKRFLidJilFYaWJZbkn+5IJ3iCoXSV1aGWqGm0rPEyKXASISuc
RtK8QDEYjEg jBFa jKY5neIggYdwCoYusSD59OTJJEHoHwsOJqsJQIGhQlJd1QuJF
gaNlgZcJEBPWIWSSVELZlyiCoHWK4GSFEcXyyFQFsV9VZZIHERCaCmLGk4ooapSG
pBbESQu0Aqgl0rTAKKAwOsPQGgVtg+ivvy9PIESEJ2VFkIFRBMwIugOuwXglniJp
Umm0iWc0Tpc0lpi4aJQUKgiYUv1VBdqu5YygoEITJAEkh+Al1VdFkpJACXhoXgdV
E2SC5hVhKqCqIghAc0rHEYi3RCLJ3UC4WNkXtB0gWUECoklIYnAf0lmFBAWVaYJ
wAGE0yikZDhWUJEoCpWmpWSdLmsZRECB+JOKJwuyppJCsgSoJDAXREtiaVBVmkeT
VmHcUFngRInUWJGB4fEUR5SnqQsKLbCgOzjg14RgqCKnMrQlACCT+qSKtIsTdMs
QAGlSJKgKjS0DRINKgc4Um6M0hVQRgZEGlSYphSZfZWJUHIRFnmWZ4DSPMvJJC2J
SJ5J0DsG1F1hOUQ87mlkIivTGq9xdkgcCeDACAIlqCCBHLAKKDRglgKtBy1SJJGk
GZA9nac0TZBZgST5JzkDpugCTYJUKCSncSyjc7rCg2LBiFRRB+yhWYnWdJ2VWQAP
FtrldCDPIL6iWVuwvgpEX1llyJLoOM0zeYTQeIlWZJkhI6qQoJiyaSkvVCLDCAR
AddMSLICAvJ0+xQQmOJkDbBMJxQWQF4FqKR0EG5AMBWwh2FBLSWN1MBU0BJQNAux
VCWCB214F1pGI3QWVA6UUOJlkdcpXlR1kFaRYXWCAs0AprGsCs9pUCQQWlMRAR0V
gDMFZKXMTVEjRDA3kkBLOmAilFdUhaLAshC6TlKsDuIqE4SsgRKRILJAASAYMAWG
BTx9YgAfc+B1gHeSlhUVyMXB+DiVA/2BAamizCugAbquiRRNGa6C9eMRpyQd4Ep+
+s4HTUbJ50kQT0KGhghYk7LQHqJU6FZnWIZWHZgk64y8ilBggQ8BjvFPjvGyxtS
XJLVaaCpDjYToJvReJ5QNBqUg2ElAG2QXooAs0urBK+AjVaQHvQ4gSvrJgnmj9IB
ZUBDEKEZrDpHRCUwG3avGHVRJSHAGGk4Cf7/nAJQ/DD77vYzy8+2MvA8QY3zT
AazBy9AlcAZASCTwMGQgDyEToszwCgXaTwGHRirKAbIAGr7JGE6C0Rk4CXwCSwe
AilaAqMng5MBTejAVBrGUOAZjgZm8DpIjwbqD0YHzJaoPZEezBlyJB7AFbjHA0an
pKYVgVLAaoIFFxCKKTQYyEWU4TeoLog0qBIFGF/GC4kGiwalKIqCyYIJoqGLWVHX
wKqRNEcQ4FwB5hI0mCRQDoBqcFbatwI9IGihPE2Z5nhREggZHBDRAPNBacByiWaa
p+CSAMAjoADBFwnwY2QSwBBapAQElrqolhvjAaUpQldpBd7C/2BhweJxJCEAFKgA
SIWigmwCT4HhAGMieAdlCFnSFHAULPIxVakgnBVhTCDmyPWSFAekFqE7o+i6DnZM
B3MLPOAoBbsHE+BPFUyYrmng4ujsE2DDkMF34MHfE0UoRfMiQQMCKYA0yNkD66PL
YMXBDpOqrKpIW3kd3FANrMzTl/RAMxypkxzBivcICQgFMgZekw40q6YxMkUA1oBW
0iRoEclxnMIAR8GH0BSFop+cKVoCzRMB9lHvIRRKgWEoig42gwB4gwHsgZyI6PJ
UizMAHCR4iWZZSRdI8VyYyz4qiBdhaiQIIDQAnCpYCoIgBkV/AtkvTtkQfIFCs+Zh
CgpGfLmjwTMDl0Irn4QXwNcERxlqIRIDHygK3FfUIA9uGUg9CYMAW08CpyQBZJcs
cwTCdgERksnfvCaAGIBJFZG7y4JfwaJmg7co6RtGpPfjfgiIwgEcCBVQXCARFYEBa
mQK/XVIBQsvqBA4KzaucPyhaYAYhgQ1B8CX5NTRkMEJadACXejokWAEcCGHaxAR
EAyAqPLFEqIsSwIYbzD8Iri9OrJRARhorELxBFATBsZpABmiJh7AHMC00DwBPhch
gSg+nZlGvqkgEiS4aBzPgxcBmMgI4MQpEAGILEVzsodMIHLAQVvAilEksCES2BQw
X2VFJXwggkxBGUqWwWyzEnjarkKSCZAJK6CygEwsoDx4vCBLYCDAW4GIJispJyHkv
0wy8JbDvDAODEkDeQR80nFmNTAKOhommFROBjBTaRoim3D6wZCAWwY2jNXBGS2j
BgPTAhMpqCylg28D6CrRJMvBKfGKpglGnGQZcG2BneD0aRkWVlXBW9NpsA/PX2oB
U1IoCJoIGAvqkwZAA0YHXDKQLIoF/lSbnFBAPjUIFoFOHLQigikaFAvAlrL5BSTT
VATVjAh+C0ACAAL4oEAesES0SpGaiXBPMARQAESYAUD8E+TYMzIR38KJwBkwJUB
xwQ8ExZmCa4UDZzaIcAl4VhSB5eHBpT8nonbgNLCG7oeT4G8u2M4W6rMl0XSpbkv
751feMwKF01jv3lGm7RQevj+CGUrH8exsNeO/5rvFYpBhEm2qHd7ct+GVxrFt3vv
+TJ0qSxa9rU07tgi0k87JTONvQ9bLj4g2rF3B/Hgv2GfcF+f6ff9xaBnya8Mt3I
fp7K0za80mBuK8W29aU4Z4C2miOm3X2Rj0Dpf3t9xr4yt78WK/+vr8CRD6WDO88U
+G5HDw/f6SF2Ymgsa//75P0nG08pnBZ958d3WfZHVLR6I9J9PcpHLaYvj7sdvut
nDMrFlaQJt02T5ZKPDXY3f3ZpXLvvv0tzzJi6ZHTry/ZQhFa7XEd6+VpA/WtUuB7
QRLZ3SPax46Wez8v1krGbuHXv/0PPf3528uPf69yEr+pC8AK/0Hdn79X+WHdOWOA
EixhzFLom04nbGyHlumbn7D2EBuafoQN7dBZvRSHUR7XoITVBpqeIdCD8CHiA98e
sOi9lz/h0ncbLs6/3FLorUL1/QR5Rr037/5oI80/oQ1IHKJMHd6Xjp+z1Pcpqrpt
gk4Vit9w/ZKx8ONjR09Z+bxkvtKff78GVO7Ha18aOL9vc6l+aF9u28ogDbl3gzZ
WyX9Ozbye0XflzowKCWb+s5o3pXo28u7nf2+2H17F67e3eydPy1Z4Cfuvb/q+c+c

1fn90QPavMt7m8Xf0vB2cODNyvLif+3q63P2wPEt+5wy62324OHdbYm9xJVsn/vT
I7QLvf0vV004/R3+d0/sju+JEwp5R9Frduw/s44FoFlwRbrZWoIXniJApYl1nGN6
wBj+198smeLw9PkRauhNfyVS/P4odvcNALgv1Qmnhwi0DeDdZaXHAs/bL/ahXdpH
UWosX0HP1icnmowN64aGyaN6S9UG+TffA22dyu+2sH0khVF6mAhkxzYjx73kp7o/
pecMswlyZhiidZLZkeHsDFeQHzY62dlXwSLR/Yyl66aZrx7F9h6DrqDd/Ji4iU6G
hMWhhMxtzpyavCKS2/gVBC1tctKcocsjsk7RWKCu6brB6Tze14QPct6goxM18Pry
CdQ43qDnG/OYbvWLMoLOG0Wbr9EmRuixHmOgSGCptgkKLZwdjBBLF/X3YbC0oygI
gQbnbp1PtLeFCdh7ywhVz/egoelncQI6dmtD4TC9C+OBMGVvZjDepYmOA6V9rWDW
0ScslcQop7DrYtAl0AicjbrVtAhppeH4Pk8882VpfbAC0xZ+AnLrg351JrcvNHs
rJ6d7duPpMUEgI4KAiGyIAo9EKW7gk8I2z4Vh8xA4FbQSkHfBg7Byc/4gqql7QJz
kKOJAz6hHzhh4OXdr1B+iQZ2yQcdQffi9QTBNDp9fAs7PqHTKRkH05Hfmj069ukT
okV+AiHOZCYMsnJ5I2iQqOSzHD0egslEJ200F5/iBcw+OwvvpITMr4e5UxQ6z3dw
piWyc5CXdlDsrtn0thkRvX0CaJuPA+wBuB8w5Gx3LGYmcQA8ddAegQuWLR5jyOXP
mIbG1NiSu++s82zzqgmShKafThOAbBd+dqIsl454Y8bpzKK9vXRWl0wEOJ7Wte2j
XUe5R5JpC7p4IRWFE01Wzu4EyEcb3ZtC7MqphDiQqjGOVPGuCiF/cyk/UF1XzvKh
LdSR4y/dJD8It7bzUaKTGLb1EUgl20st7Xdon3WeNmjjVEawzNYivSuOnt5U7fKqg
AQWlsoHmXESTT0ea0ulxg+ld8G58Q2cKkG7dyA3PusM7kqRVXLd4FQWr+AQ+T+/yX
DFKvGSYZ9U4Vvkzoqpqn19DM6MjssMPEogellGSn2IaEuAcWnjMmXdcM9mrKZXHFA
BREFsyO5SDvQ6cu0YfT4Rcma7kDDPSjykpTLok5TuXweXKA5egWoIw+BRHTuD8t
AzPMkio3XC6g5uGqj0yCUUkBrphImcvaFzu6ckfLOLiNNx9SrQ9oxOk0wSgBrV0L
62hjbZDaf6newYY9SdGG2AckIA14JGG0DNAeHMQSSPEfc1RDx9iy6si/2aCTeohT
KQDYZxhN1ENNpPf4b9JSSyQpxetAWRD0LlpYm8iXTLeAWovlNW/LhfbAhFOW5eHtQ
fAQ6qalYmnsHZAMCQJDLG7dzWSwQ5AYpyITBSDjkLMhUqBs6BpyR2boZkey0S86T
DFxuYpIdws1EYBMEEB+kcQxVM01P7vn42WUDqZ4+RnLRLkwN1USNKj0coKukZaN
+jftYX9C13tkZ77RSePoNsKHXfUpBOQy9qmwBhkJb0sTtr:URLxUS3mTcjjakqWh
YWjFNmckfDHL55SWSMXN7LhAsk+EisXY3lAiK+EsCyLkmlTuLwfwTgwulncOFOOG
zqU0APhUaEamNLmpQaPM2Yq8HCBMgdDRbZo3kUfmbTcQfTMeZC3dKXgzWhnJN1Zh
suq9Z8CDBjz9p909FN2mU6aJIUnas4CiVx6vlduTDM/I+UcKrdIXGRJsyMqDw5I
Nt7LHhmoh62q9x1wd08JRn1BG6ZgzJgXRPgt44Q0rYEKZ+efMuYBokd3/EIilnIM
hcwpTzPnKBP71KYV6orGluoeOKiX3O7H4FU7RzsTN9BMP4VJcxEFLihJbmlgi6IC
o42alnnDhamXo/IEaQJCGSj0P01BaPxTAYQqQodzW0MKp2C6A1xeocMZ+YlpPfw
001YBdc9JARf5QlDJHSZ2pf959xdl072HElTyVG42e871u2TbfbuY+fGLx2miSzG
+xVTJwPZVgewOnP605Mu0d3rT5v2wWNeP2YqRCfQSine1uQ2xsxqFDeR3EOH1lBI
YTNzagK/8LnC3MotzChDuPRIT6Y1EAG9ZpUKzkv+prQj3M/Sxw8jysQLiUGUPM1+
FYKj56N70A8D+JqR6A+qI3CO/mUeiQgRtnwkpCd5m2bhY5FoCOoezCIdintV7bt
5khfLzm/hdLsnBHaqR6scu48X8yQ2QHLwkPbC472o0G9BRUZqR4gPgVIFN1jbxQ7
QG7jh8inQoKKXJW0IEoD5eiYGax0T2MpYHkUtRxBTUxudZvMIUioRSrt2C8AC2mt
YXc0ULT07tJ0m2+uRbeYENhHAWQFwiqx8R1r9ymXzIKWt3aRQoF7aqYXjodIZdmi
tLnirBjqKGP1skL159jvAyr8i4fvjhT/QB7ss5m6KwaU4drJDrM6Vna3lQ04b2Yt
B27v0610Ns57Ii+T7lQiUC8IyvyS5H5KYS2Ljh5H2R4NDUzWsN5AUzRVUzF5ht2X
/nraACV7leGSjWL8Dy8/vBRux+2ella90xx+we7s0W73sJRk4S4HHgLeRXrEaOIk
mPbikppYjXxi6JAgHfY5nJnx9HnB7bb0f35HYTyjBxULccld+grCPHpicW3plHF
LDTKS+c5tbsJHI1ukp45qEXvEFK1TnqOKOC4pe2Umo4+onKFvOUwsFTpJ5rMp/XY
wq311BOF+fPZlFpUdUEX3QggYn4/1oOZ3LyxZ36kTiyySmko76exFuAAmvVLQYZ6
XEDxzdtnLSHTrwzCcn/ttbDs0NBLLW3kg4n9gd7l1/c9252i5inzJO9pIycLo7M8
d8RnHz+X00rvNYMsP/aQUswut0FYAGSCYMPcYnK3FA8oluYsH6tm2cvCOQJr5zig
SfV484i200tnckP5kN1CszMa5LpTA43/WzpEWILUIIHwboLtk56c0ggjqtQS83U/5
gjizWjt7dmfPaxw854M+gY1bgFuUDyHLX+ZgmrHj129Fqu7Ra/2QvTQXYDI+FrKZ
os/dqy3hCQwDBCP3yaa7Ypej45gXeoDj1PsMkgimVHjB97jfupuYm7uaufwfP99G
myl+BiPZKhaETd4+vnX32Ld0yt1TSoeEvKy/5DB9n0KqpyXpQqqYUqWor/R6iBx7
03gu6zbnsmzDsFI5f8PnR2R+h805h82iJIXihHTKacN3JEQdj1NwBxIQ0xuXP6Vx
za9dP/szLZw+MU5B9iTr2UwdzJL2ps5B0sg7g6PcfuXwlcHlApA0awWBwvVU4N2N
Ritjqsv2MEZE0TxvijqkHrEbZtPJNwKUp+Ln8fJ707nBKHC5GGOUSVOerFzcMkbp
VIEuD32olPksBUHLmoJ97+fHJ/XHPjwgYAPkgNjclw9/+aGYFejgt+cGn5iXanhU
SNU+CAUN2I+NwyE+W7DN6L96YyfUCK9maAQ6ZscL1J5v6mc+UCN1PosomoR2qc+
aIjhguxGk8wju9WlHosWiUUKGaZVpq+3kvS95M3pSVu8RyN3C5Dnq/P4BHkZ2a1Q
N7nmJHE2mNQGpPh157P9OU83oErPamZsQvuNoqFvnr8rZ04w8ZRm9j+bjnxG0Zyn7
+5L0nyNG/7QMPbaKaFOa6I9vCfmPtPvc9q9SPurHdn+V/m7Lbwp/vwc5H/+P77D7
z/Ugv+3hoRf6V/LXMP1F3kP64F/bPvXcPvWvbZ9+bp/+D7b/eIHJt2ep0pF+1IQ1
7xm9+OeFVUDb+7vNwot/Hkd3YH/QylCaaI4BNooM3WPInOJdtg7wHLyVA6i02RRR
Mr8ozRzdDVtqn1/LSZps0BRv0NUxd8Rz7mBa+AW5PYMR5Ln06LZoce84Km6KfLTE
5Wdm5sJdUhtOSwIPq0PmLWtSXiuShAgykluDlnqAef5mzcJ1lvQf7vFETn7NIEC
6jwR5cE8oGQWfAxpolk+5yGCfEoBFBnu29pS8Y0OQTG/PElfZFKL1PVtyTpb60qz
t3nd10/6nGZ+0Jz+Ft1czU8Pk/HtzCXNwsncrZsI5c5o118WcRq6nyjL5t0yDg8+
em5xs0WNLMfMzQLGtK7y0PKmPLvzvDqQnWIdpudU87xRQZt0LSBNOZdWcm/BCghy
Jm+PmfuXMaqQ2sWHBac80dolaugbbjTJGA1uc2B5oqygy9400fL2PWgFopduRyh1
vpTiUoTy2IvVwaIaSShn66zFoeqHDPs9JmNw1W83IGMvlhO+ZP5QtuxXLLagJj4+
JLmQE439BqV/Ly+gpKnH3Hu93fwAk0RDQylmuzGKHHpUfP1IdjlesZCM9H6BltLu
YeoJNdKlMqhkfLnJs5ZWcPJv6514ttIWhE6RR8x8dt3opVyEKna8/HwL1FAIZAF9
bHdB0U5JbA+gFd5yqykvH2YephcaYT8ErpUiTXom3bdPxR+3gpadrtd/kPhZwPTr
mxKlGz2ybayreP8F5Mv+/8r1VugPP4R++V0v8kpLfU3Yg0idPCT4JpgYe9zB8K
ptwkzElXJ4079xy0mmIu0crBnb4w+yhyUE48NxW1szw+ZnRQk3QVJonsBDb6M8N8

```

Ef3dlEke06bDz5xXIhmeLb8JZRbelmNp7A06ZfR2R/8Pn/HHrxRAoJldg/LxE8oy
3VbB3RO6LytPwq+cc9q0B5XMnZ0CZ4hywSn0FUF+cX9BFoDnsdV7ruNx7QWEL7Q9
lEIf1tGlTbf4st+qK800iLrdDpktbNlpoHjKfxnQEF0QXv9BvDKbgna4ZJlyz/ET
ENRsI0FWDGzVGcaFsmSrO/nyzDsGOY8bAOXTl2Z8v6whXdoEg7jexHlgY8ZRgMhR
BDIpjOd3v6E8A9rp8bSsk16S92v+rRW/lhYhsgWLjwX81TtDQ2q1JHQ/yX31P99A
8ClbQctu0XtMmKXpR2TGwmAfOmgFJpPBVF6BY3Gmnfc8UnqzWYb3Hx4voqggehr3
v+T7ZjJEerh6BmTHjpGKgIRkIlBEdGCEfjBH7LanIw3vbgP9lNmL7BbNbHskXjAl
clEer6u+Lb1pIDSSoeVfe5bhnnU0/WWqDTD6AmZRYFNsIckyaaV9JKmuZEavNKGf
eDtSZ5bt4rltuikSo2jZ6CaxSfSwuF6sbBU1sqTKg/9z3xaUO33LOLst/SVdXHpJ
CQxAWEqr3XfPZFsm8rTZbbyfcz/rzRpaaFoFjKSClnIEZaE+ZZ4kWnjKZDb3fIA5
8Amon8HY3ReMHiz5oiRqxRaFE13v+p2vxt1cl6ex5vCGF99AUN4ElCHbbdh7Cdk+
PW4KuG3PQR6eGT9c0vdIJgCb7sCQOsYXtJ5j5QzK0GAQWjt5TarfPvHnaJ3459e
mZnZ0AJlU6b4QbEZJf+iqmI3ydf03Gxz8NOehRc9u2ENeSKfsqxLjgVPuyyKZQvP
zDeJF5qUjf6RF52uoX152rh2n1Z2WTBk3YAVRLsw0g0OZrboGAdpEjJb58uyXD9k
5T5v9xknFmjdc2Umbvzx85sFy8Jredvww3a9kqtcjONp00bmf393VE5Z4dKAb12
3LYTp019yi7Zzq9lAf6+3KfzUihwecjFti9z6bhOfHnY2OfEZcws1rER3mftg217
dEshSnrYrYpMEgwK6WPi04fELtQOKb3lrFZ2uiCV+ld30loZNmWChBbboMV0NSJd
m71NJqfdzYtDuzawCPX24JznNyyjmmmdA4gqmiLQIVuut7xFZj2zLR43OmeNF8h8
266WL+JvzH2+WlCSqbsCoR0eedAClgCABHsFnQgc0NXsG+0QadFGvjgI0KZ5Owua
YOapjQuyvUIo2EX+B8qUo5ceUlmQfNvOXXcbbUwDWxKXF2+xDyxBnEmCwPhOGS2a
pQvL6yCAsE3gu4yehUb4wq7cBffj29wrg9GTTPMI2Os7WHdLtTitmoJ/AXITb6
YoPnbHuKH3ha+mEheWE/JCvTKTwI8kO+9N7mfWnzTve3CU8nPz1QitLzaP4ptL3d
DfmwO/suxnckua3k3HaTIwc9u6g/F+0oc7NSxX1UmdwBSmNotGf6jU277cTK4Opm
AxC5oiLRmlLgDj+bhz0BjyH83XS9IWXuJrw9GIR+sgrQvPkPxQrpGtlzjWH/839i
8g0Gsy0D2bL9mwwOFH3TQ5aOyXpofbz7EH38ro3FPphopReC+syRL60hfnzTfnr6
6KF9NLIQ+asZZDjQB4R9l3QlvkgFZTHIdD7K+ef3Tg2ixiW0+TPbNpHe2ZurxD3a
eKQGAnAzXwEo1t1veTIU9yBpPgWZgUpb7LJLegtp+4Ll2atUUm6rPoXLXbZJtvrc
TV9mVu6K/HhPlu1W4KdEWW5pXXuFwNi6bQ3J7GE6iSy6TzU4gx6UDUBXA9uA4sv4
Yz6Ge2fFgnixF/Qx3ZdrGEKMNCXT7WhYd4CluWmtZVDAyqEZCSn7F17n7eoP17S
cZv1Y893QMDAjjZmT0nFRzs47T96Y8+LPNINA1KlL/nLeeKg8E9QLiLbYOCiu+JT
M5hFk2kIY4I3esKy77J7D25yNzRtsgRQN+qggWtn00004/sgnl3hbKfrs05xWOMV
Pv4tyrYDRnFoiMX+XJelt0YZkBUbIMIH9q7ETq79Ln4M49qcq8hBbncqcuVHA0e
905ld0o/LY+V/da0YPka1PuxneI4EP9/wMLkn5DL0sBAA==
}

editor %sitebuilder.cgi

```

Here's a little script that I use to create quick header images to get generic sites started. To use in the standard templates in sitebuilder.cgi, convert the image to .jpg, or rename the header.jpg image reference in the templates to header.png:

```

REBOL []

save/png %rebol.png to-image layout/tight [
  origin 0x0 space 0x0
  image logo.gif
  image logo.gif
  image logo.gif
]

save/png %header.png to-image layout/tight [
  origin 0x0 space 0x0 across

  ; Load your own image here:

  image load %rebol.png

  ; Use your own text here:

  box black 400x72 font-color white "Sitebuilder Demo" effect [
    gradient 1x0 tan brown
  ]
  box black 50x72 effect [
    gradient 1x0 brown black
  ]
]

view layout [image %header.png]

```

10.18 Case 18 - A GUI Playing Card Framework (Creating a Freecell Clone)

As far as I know, there's no existing Freecell game implemented in REBOL, and it's my other favorite computer game (Tetris is getting lots of use :). This project will provide some more food for thought about useful GUI techniques. Here's my initial outline:

1. Get the card images compressed and embedded into REBOL code.
2. Write the code to display and move cards around the screen. It will be similar to that found in the Guitar Chord Diagram Maker example presented earlier. I'll need to click and drag images around the screen. I'll also want to make the images "snap" into position onto other cards, rather than floating freely.
3. Create a nice looking GUI layout backdrop for the playing field.
4. Layout the cards in random order, in 8 piles, on the playing field.
5. Allow the selection and movement of cards, based on the rules of Freecell (i.e., cards need to be placed in descending order, red-black-red-black, goal piles must start with aces, and ascend through a single suit, etc.). These rules can be handled by a series of conditional evaluations that are run every time a card is moved. This step will require the most coding thought and will likely need a sub-outline.

To get started with the first step, I remembered seeing a REBOL card game at <http://www.rebolfrance.org/articles/bridge/bridge.html>. The zip package at that location contains all the .bmp card images in a single directory. I downloaded the package and wrote a little variation of the binary resource embedder provided earlier in this tutorial. It loops through all the cards in the directory, reads and compresses the files, and then appends each unit of data to a single block labeled "cards", which is created to hold all the images:

```
REBOL [Title: "Card Image Embedder"]

system/options/binary-base: 64
cards: copy []
foreach file load %./ [
    uncompressed: read/binary file
    compressed: compress to-string uncompressed
    ; There are some other files in the directory that I don't
    ; want to embed. Limiting the file size to 10k weeds them out:
    if ((length? uncompressed) < 10000) [
        append cards compressed
    ]
]
editor cards
```

Because the cards are read in alphabetical order from the directory, I need to change the order of the card data so that they ascend in the following order: Ace, 2, 3, 4, 5, 6, 7, 8, 9, 10, Jack, Queen, King, in each suit. I also added some information after each card's graphical data to identify important characteristics: card name, number value (i.e., ace = 1, jack = 11, etc.), color, and coordinate position at which each card should be placed on screen to begin the game. This provides a nice chunk of data that I can use to build other card games of any type. I saved the code below to a text file named cards.r, so that I can import it later with the "do" function. That'll keep my game code short and readable:

```
REBOL []

cards: [
    64#{
eJzt1z0WwiAMADoc1Wu0OfkOVycvIOncOZOHTwQk2sMBAehL8mzqTqYF1H6Pegj
2J/j+b6FELcqByonKhcqK9iU9kjHbzsurxHLDjFy1Tf6Mo4j1bkFyw6IXOUTn9HH
vu2qi/UwoBZpCKpBcDDBxyTwMZCChyEBquH8iSanK2iGh5NMyp3AfPMccb4x5QIM
ufAxkECfQwB9Dn0MHQ1q3t3WfB3xb75joGvqTUmjaEiEVrUG8rJqGpufqd4jPmGQ
iXg+1FHeUDSmOUzt2SxonHI6FX/zW6bP4luGL/iisf0faJfTb4iymVjlyxnLPGth
M/VBaLapD2aK6S6AvZm44vSmDCcbVFJqNk5rnh/sPYwsJmN5J7K8Wz0AAI/VC/YN
AAA=
} "ace of clubs" 1 "black" 20x20
    64#{
eJzt17FRxTAMhgVHC14hR8UcNFTswBTUGS0FA6miNbKd49nSn0g5KC1Hz/yF1vy
+SL19f37kap8ir6Ivol+iN7RQ7WvMv711HSUtV60rq0rTf5s2yZ9seR6Uc6tK62Y
5OdZT2XkfImyJ7wkl8n0d4ZrDOeMuJxcJnOA8f2pw67PkBkt5c4wNdpXIsPUaDuf
UeyaQbErBu7h6A9kKJWmbXoWoJeyw+xHL92e8RkCexhhxB/uI0OM3HNNIyZ4fjpL
i/J8D48YxbuMjCb/zB+cw8vMvuJkJjOZYUzmCsP0L0x74Z8yDLKsw7D17Tww67WE
```

```

eHsG5M89sf6uxGY1xejcfYnhPp8fMJ1EapKj2macG+4hqq4sk9lnks+wKhqRP6D6
tEzkrIYKZHYZijA2WsOAAIE/ joSYyDdR5NvqB5uyj432DQAA
} "2 of clubs" 2 "black" 100x20
64#{
eJzt1zF2wyAMhpW+r1lX8OuUc3Tj1Dv0FJ19NA89kKasREDei4V+R4obv3QImNiR
P7AEQsDn1/GNavqRspdykPitZUevVT7K+9/3VnQa60Xj2G4ly8M0TXIvklwvyrnd
si4i+fnomzLpZRiy13hILpPp74yok+7BcGKXyeTrIw25DND+N4ySEGRqTaWOZaq1
NzLI9o6BfaJlgXZRKrmX9a0QqZYsc3a9dKnjm/VxBSP68NwyXmH/nsmICfrPTNKs
vN6HS0zHu4y8TQGfD/hzhDl/8ck8hOf+5rixBUq0P0OmnxeI6efXlkwkbtTiT6wP
jTYbMncaU5SezP9i2Iz0KqYF/KsMg9niMNAP+3agH7YF8VIHxha1ni/EFrVWL8SE
CMPz9Xzb2AJ2RYYBuyvLZHaZfDOD9Wfde44pqGm/5SBtLLx9dmoHEo+xlq5i3BRi
ImeiYnNqBBVpT9z2DQAA
} "3 of clubs" 3 "black" 180x20
64#{
eJzt1z1WwzAMgAWPFXYFPCbOwcLEHTgFc46WgQNPYhWSVce/WCp0tB3Xrvwlkiyn
cl7fvx8h1k9uL9zeuHLwu4OHKN95/utJW132eMG+ayeVB8dxcC8SiHCQaSDVRPzx
3N6qK/fbRlBBLZgMwf8ZDA4GPEXwMOCwhwGTYTtKphxHY0UVVEzUffJxomMA8hce
/UG7Pn9loFnDgT0tA0FqwqV2/qJuqFntoTkPCvmFhzamYwaqmHoYliNme0LQ6Xpv
QEDKfpEEk8S9MI+p6pyvYc/0xcOQmG7vQ9dzYTMXjYtZzGIWs5hrGISbMPqHP2Ww
yLUmM8rv3X36c0u2JybEYA7MfqWcN8i5NTP03VcxmsjmDBXyZM/wTGKcbfDU8Nsa
nszorJV1Ad2AweSOFdPGxzamCOTZhzaD812YymoznmfHYbNZXiZnncjzbvUDyCYa
mfYNAAA=
} "4 of clubs" 4 "black" 260x20
64#{
eJzt1zF2wyAMhtW+rg1X8OvUc3Tp1Dv0FJ19NA85kKauVEIGDFKAuM5rhwgTiPwF
fsBG503j+xmCfVF+pfx0+ZPyAzWf/0z3zyfJpc3hgnmWghNVlmWhkjo+XOC9FJzY
RR8vdVPKHqfJ9wn12U8/J4hOe4IhhQfwuAePds6grgqPwJsG3AWA5C/IMgPoNK8
m6k0W3qCLzPyGOEWckxovYvut30nCsB/8rDOK0dJjiuYsiPmPU4J7cLhmro87i8
Yyk8vM6aSp/tOdSMthHGs/SBZ7XSuzNZe7wzf80AcmkGofbUTHySW0x6Iy4z+c26
PVPtGDZT7jw2MzSHWku5IXPQmlp2Z/4XoldxFyMbfpNB/UjdZqz4rtoxzilJTwiI
ZqzM44oxz4i5JWPH7qsYCWrtxm/8UY95JmmfBeJoGnOYzlJWWSsxfC47gPEr09IT
meaa6l2pNGGaiGju2CgzpqfLdG2I6Sqm6VR/05Sd4Acse9Xu9g0AAA==
} "5 of clubs" 5 "black" 340x20
64#{
eJzt1z1WwzAMgAWPFXYFPCbOwcLEHTgFc46WgQNPYjWS5ds/SHo07WOOHDep/MWS
bVnO6/v3IyT5pPpC9Y3qB9U7eEj6ldq/nqS2sqYL1lVuXOhh2za6syamC2KUGxdW
0c9z39Ug98sSLcElmEyE8xnkdpMBhy0CTAZNhmYzDPRM/Ywgqs5WGkPpIMwYgPIH
QV44jOl8nvnTzTMELjvOZRGvSkCdZFaWy0OlzzzkaTIYaGLDw5AesfgTgJ3MQYB
YxlXDOWKD89YU7Gpz+HIjOJhIrvuINXOzz8y2eKNUtIz24NDP5Pc0uln8dwx833R
MvP9dRnGkzc8+cc3h7N8eCnmODX9XW7M/2Lq9TuDkYsVmlhvJYtR4rD0o8ShHihG
btNPPC235BNYzQkeRg6yq+SWfTTaXt571XJC+i47kFH9yYy6pvU7MxFGRCsWIFan
SzPPGHm9jMMfmzFHDYo4XX4AibGWIfYNAAA=
} "6 of clubs" 6 "black" 420x20
64#{
eJzt1zF2wyAMQNW+r1lX8OvUc2Tp1Dv0FJ19NA85kKauVAJiQMigpHamCBOI+AaB
QDyfvn5fIcgp5Q/Kn5S/KT/BS9DP1H5+i7mWOTwWz7HgRJV1WahkjQ8PeB8LTqyi
n3fZVSPPO+RHgpMbMh7+z5A5bhfG45BBN7bHwngQTF1HUBkEKPjUIBia/AchvcAG
HcCo9tQMOE4XnFMzX4wbah22GDlXcn3iIS3TgAmKqxjSI2Z7nIvNIOaFPs/LozaF
p+f6Polj9tewZVqxMJ5NH+9nuQ9vZNKID+bojHoGZT9abKn12n4Wjh4uakY/X8cw
lrhhiT+2NVTj4UHMFt6NrbpPc3dSI5na4zPTelx1hKcOZYTHdab2uM7UK7zBoLRm
X6a2UbenZlsfxoDfETrl7cJuM519mPvpXJZ4IQ5iy+XO68WWdAN3Y4KfIRfZfWIL
rD1treHKdGPCXgy6st2J6d4XWLRpEt7t7jAza6PBmG1Py03MUEYm5ZvI8m31B3Qa
a6P2DQAA
} "7 of clubs" 7 "black" 500x20
64#{
eJzV1z12wyAMx9W+rClX8MuUc3Tp1Dv0FJ19NA85kKasRBikNRhLcmK7r8KECP8e
SPD318fX5Q3EfQieqH5S/ab6Agfp7+n8+T3V0no5o09Tw4X+DMNALfdeOSDG1HDh
Lvo51kNN7LXromXYBZOJ8DyDkoPOUMjBZCLuxTQxIxQnmzHDeMzsVHOH7GflrMY4
4inzQuD8Scn6ZpKfQc04MZtFVjgxmMDLYEoa9MIonOyVDM4dRXsnh9IK+p21OfQ2n
zNQ8TOTQHTqMjuvLzVkmI5iW5mumpbGKaWp1I8YRz7aa34SZ0XydV0Pzk/VZaU/n
7Y8YT8x27p41dOzfztowers/H+8ln16njUvU0zyOJNu+CqD4y22GGV97oy2PumB
agj+9nTVNM+epVUPg7Cb5hFu73DzGsujqlqV97L1GE886p6irp5irl2YIqE244nZ
NBfj+SbyfFtdAaNeJZ72DQAA
} "8 of clubs" 8 "black" 580x20
64#{
eJzV1jtyxCAMhpVM2oQreFLtOdKkyhlyitQ+moscSFVaViDMUyB2vE4msNgr/IOR
4kf47ePnGXz5onah9k7tk9oDPPn+lZ5/v3Ary+p/sK58c5X+bNtGd9dj/Q+s5Zur
rosur/WrmvK4LFYruBiVsXCcQT+HMUMuG5Wx+GcMQvYwGLXPkL8zGFD0HbldGXxR
GKMzdZwlf2zBiLgqGYlhPrNBiAwG0VWVGf5nC+JfdwjjLZP4Eo2RoZJPNiw03PWVN
ecxxDFumLTOMda6roixieIAJi97ESJqvGVFjJSNq9SRmwp9zNX8KE2WOYTUy1p+k
eRZptgGaNQWDO9WLIY2EGDdfy6TA1J3nMFGERvaZbFe7PmPKkp25x1TBIRBjuIef
s7+4FnEZHaOt03Iba4NXpKMNvatTmv+Pe3kuR3XLLINwF4YT/pBBQeVdZhcfyIzi

```

```

wweieFamee2nq3DmFoyWx2YYhOl8eFTzGD+H+hqLmWKoVX9RGFQZjN+LfX/2WQ7X
lmfq199m6rwuMDhW/B33sjKOTYoblytIR+ey9g0AAA==
} "9 of clubs" 9 "black" 20x40
64#{
eJzF101WhDAMgKPrfYKPFeeW40r7+ApXHM0FnOgrNzWtKG/CTSjDFomdFK+F0IS
0vL++fMMsX1Tf6P+Qf2L+gM8xfmZr19euLdtjj+YZx7CQX+WZaExzPj4A+95CEeY
otNrr0q0x2nyo4aTGzIe/s+w7bsMArgH4/B+DEJjrCpArZOFnsEYz1Y4j0l9qNjT
xQIHhJpQGM4npwiZwTXpOiEqGzBR2TVMkFyeKULD0J0dRgugCOHxnIzp+jwI+Z7S
h5AGpzHZNU14NAarqPlguhMMxdD1NnYmV17aYqCNVNJ9FRodlhgEleFLgJgDJRhO
T3DomYVNZp3ZzZCdNUbN+Za5bc7fhClpLgSZ81IY1DHBjH240+7EWGweP7vFh4ZY
nJwbwlw15bzJh5Z30P4u79cES20x1ajimD/Ww0pvX3slpq/hieGCX2nyvmew1S6s
aRi5NklGrnGVPXFBVNfK8lXpdVXW3IYZ5aqFWc04IedpP5X2Q5s5TzsumeZdrsZd
2YHMwB5mdupYZjbb6YMc8HgoNgft15Yvoks3la/90iSufYNAAA=
} "10 of clubs" 10 "black" 100x40
64#{
eJzNVzu02zAQnQRpZoksr7BilXOkSZU75BSpfQS2hAtvvRVbg0W2yIGmCrAJEObn
jLQRUVTWQBZiaMus6afHNx/N0B8+fx9Lnr7geI/jI47POF7RG5s/4Pdv136sx8He
dDj4SV+4uL+/x1lnmr2pNT/ps6fw8a6n2ozXNzftuSE38VlMo7/Hip7+AphGF+j5
R5idMMQ1ZmZjzswp5ZTJpy22Txi9lOQYTjoJPUYsD5iYKFG2eY6eJY8YW75R9nFl
i7tyNef3GJnlAsN5MqjHlFJs/k7hPcb1PGFiClXXWmAo6sswQkIB16Go5ic9kw7D
KDpgXnmWmNmXvhy4FFOigHMFQ8Zjc7uYYHpwGOGrtYwUA2MM0/FgUV1YKrtZhe+
x7iNaSikPPIzFLOrxd6HOAJsn2wxrpUP/QTHUEka/jrxLPLQP08koXImygtwHsaY
oHwKsAOYnCKl+GGNgTH0cFZMQ4odz8yKs68wFX441lMoAleJ8fs5YZh6/Kpug0Od
h9qQh5SouR6zvcdk6KkFtk16wkBPzieiyrMey7EhTy1w5PFMzHHEo3oQ0oQHMetD
NuIxu2p1DlwTnNn7uT8pzxKVDjDO5tY1HBOrqdW3FBTi3lMNZI5WboGpBB4YosD
TM16qw3wiGzXiivqcg4UWPXEuOWJlCECQUcNquV4HvHECClKJp4CkOJyWAO18C4e
TJgdwDPyDx4vKC2kmCYmerAWFkuqS6Ok6w7WEnmoUKuaIet4TgO7EG6E0mlHKcTl
iAc3Tz6kxszdHvBYilINVga0vm4xlugIrfIg3VKug7UsRZEYxdINDXzkQzgxIMGU
B+m28SFVTU44CIkKik/bDoP8xtMC78IDrmeLoRolJUvRB+SYP0ZbHmHWVJeY9njC
xAMvoSaO9cjEoldhxy6U3kmPEol5EGrXk5QIelA+pOMpyGTl0WIIcdn6aej93FAG
1l0almgQ7bnrmEot6LFwM0pTnGvxjLEyDdtLtYZfKkn1X2J+XU88AV0FTY7q4+Zg
xnjbGdZrfdOIIUYi9wzxirP2oK9C0ZGqWc6daYcgxzZvuvEWJGx7Zx3hbVZfuY6w9
W2iC9Xhvt7JVxj1QevSxLemO+0IVj5UnqvbyXZtqJ0Pp9xoP5YY36GsMLqNkdt5
x7PF6ByjzMKd+/5Ig77GwCtj65XIDWQHcezlIUN9i4eaYNS1fGxjKm6kMPZ8isk8
pc9Cs8T9PeQC88fxP2KIXgbz3LgIc8l/okv+W/0GSJQZj/YNAAA=
} "jack of clubs" 11 "black" 180x40
64#{
eJzNVzuS5DYMhV1OUCwvrzDlaM/hZCPfwadwPEdgy1KgKyBVMZnAB0K0VZ2Yfg9S
94hU7fYEGyx71B/2mwfgAQTuF/719XeJ9Q+uz7i+4Pobly/yW+y/4vt/P+3XuF7j
T15f9xc+8Obt7Q2v3OnxJ73vL3xwC09/zFSX9evLS3+2/CU/xT5ARgB4AnGI8In
mNx/Wsw30pDPMBoBe865a006YI63LkDtGJsxHnVAF6QDYwk0+axhDpfybqvT1pKa
YfuUixMGz56r1EaMy7sTZww/3ojJnf70qz9eJAswcAiYTqIHht/wAzBd/EaH8uSP
76L1rtIdjwJjs893YXdMD6fpm9S6YGiKGBgrKcd2njFaSkRPY81GDPxxXlVLRNer
aJ148M8OrEVjT2FMQp8859SrFIK9ZBjj9n+fZg1Ji4bdJDB20XDXWMuyJcC2TWds
2D7xUJuatVwzbSmUKE8YR0CqRWrpTS4bAyoyYeBKVoVsurs2CbzD88xTa/Fike8V
ZwypQcMBA2mYvdSoY2Fnm7GCThhphiy5iZn7UiB5alrrxNNYP6YgIo+nZXHG0Eew
ameZdETB6wUDTUfhatIaEYcklCZbbLhJqoEPC0k3rInHnQoCY5Rvg5hy5RFZb1oX
kDVAESlmHiRiLUYMclqpE0S8xFWrNF2QdEmLETrrDjPeWtLg0WQICq8zt72B3hbQ
2AYFI8oRoloLDoItiUXRaLnobcwXgsIhZ+CksKZrL+uIYVB+A09DmqCfGcwjzzI
jZAHFmmyqftaR58R1Nr55WFLlFtjHeqNTuL7QlQBD/h0rHk0AMQDfQzSUULRY9lR
CdEaj6AllIUheXnEyCH+QumAQfkg8yMm7Unk+SJPsqh9EcsigHlk/AW7nYWUJ54
WEA16iuxwqqKX3iwqpDMWIWJbe/Ck7QiTVHvstF0nv3hQeGJkAgeaJ6kWR+o3BJO
MM4fwkML50YZzpg46nGOKTXj/GlJrFLUGRs2+wHQA+aJ5+RqsbGyr7CIAtbT29y
ofTROSFrzknRr1jNU61SV2Wba3iHRKANTzxzdM2+RLvc2MnzPusGDM6O64aIkraC
Tt737TvGgxREnviJ/afmfSo+MGz3RK4d/+50jXmLDNwxMTY48GrXGJmk2SfMAXpj
J0ulMe5wPB2TasQIS5AYTsL6mHgjdXoAJHEAOryAMTFWs7etQCJi6NWEIfEcGGrb
MfdJPMjQiTCGuxoP/Y47gklDVDoOod3bh65MusEBpokPHrOv3O5R3DIjgTzj9mJ4T
5vC5waGVvbxFMXE7hWGBzg0M77Su/uy3ZRwSwDAF/d3RAZMODBK32xrrZ+f5xj3k
Gfpd9RNiRJ5i+j3E72Gerg9hPvKb6CO/rf4HC5MFI/YNAAA=
} "queen of clubs" 12 "black" 260x40
64#{
eJytlz2S2zAMhZFMGg4niyvspMo50qTKHXKK1D4CW46LvQJbjZotciBUmUkT5j1Q
ki1RXjmbps3/iJ+fQAAE5C/ffn0UH9wfmBxFcd3HO/kg58/Yf7nQzvW4+RPOZ3a
Gx/48Pz8jHeeqf6UWtsbHzyF109bqW68f3ysR8Me9ZCp8v+MiIm+AeMeOGJMjx13
7BFj/6RzIwx6bQ9f4ziOpTlmeEblF18NsxL54DefUNM1U6OEzJHcVGaFXvtQXsin
yQo3UDEm/8oWSxemTba3QCEw5udeZMzmC0/20IVrBSMNwGLUzcAH0Y7hnOhk2Q2G
+qqz8QphO2L89VUMFqK0h+bXjuHSjQFSmw7G6xJ3Mjrta2sLYx67R/8RA98KEF4
MXWT5+TcxCLKRGvasFvMIHWC7CYzZgmYTm647jEy5IzrhZDDFKyegdA5ea6mKBZL
3ssfG84DEZpJERMDp/X2WhWnkfVACmR+Y0jHQcGnSMTYZHIW3TJiMGjEPDZYeeLA
MrdMDTCoRjhzFt9nPZM0wiBs5xKK/HZ7eh2shJ/lXg6SJOzr2DBAHxdjwXhKsXQ6
MHPm1IH/sA9Dgsc1Q+9z8TAnOq6glzpwF7IHvg1Ywchk5p1/YZhusIc6Zeo68PlG
BzuU9lyK3I6OUifjPGMZku9k6+3BvLZCFXKxttdXOq0DTuM8JBbUjU5mtXctgrqa

```

```

B+pYr6MhWUAKLYCQJuvtGREcMEI3Qwf24FfreEWc57VCgpuD20Phrc5T8kuWiLiG
oVQEeRN3zwVJgXXev2ing9PMKhNkItoG9pHu63BrJc/WMMK6XkeZ5cj5GAuS4szF
bxhtOpxn+nDxtWOM9tgohtTiyOhMV2wYxNjlkMy+a0YIdUxFSkEmTlvrDKGemVqT
FxeWmVx2GM9YY5GiK85D3mVAVNY69AgLN5naaiareb7B4CuLLxuBhWv/sExfqrbo
15Trtf95aDriIOLUmoteMd42Vp3EewvFF2ZqeHM3Wnr6ZulqblSvYrytHjC+ZZdu
7a1R9pml6/MmoGf2fGiYzub88TjhjZGXmKV0eEJdlu53IwvG76Wqbpmmmb7nlqt+T
1Uu8qiwrxrbHdtU33dhfGdMkfm+7+Xla/L8xVkdUmhTm+HVv31yFzh44eCU3rOmDc
h2/AHBhzL3PPf6J7/lv9Bas8HtD2DQAA
} "king of clubs" 13 "black" 340x40
64#{
eJzt17EOAIEMhtG4qq9wcfI5XJx8B5/Cmddg4lVu8IGcTDphCy7ShP7x0MR45Xpc
uC9taQmBw+m+dlkurHvWI+uZdeFWedzz/+um6Kv4/DjvSyeNP8Zx5F5GUn5cSqWT
JkP82tWmLCyHIVlyG7YmklwHJvZhKPRhAsUeDBPBZEIwGUZCtJjsrskQG2Fnk5mn
9GAiYDgiu6ZmDhOQw24MEg8yLyg/aWb+hYk2k7c3g5EVbDBLW2ozZVuaZiir2lnN
ZKQy9I6dXjFD+UHyDNULqbuWmfk9hgBGLSrNkFqcmGL/HMMEg8yLyg/lmAMR0zt
iDBGToNtyTOjNy7FYLWQM6DBULRrgTBQvXrV9Gt1R+5EyN3qAeRtVIj2DQAA
} "ace of diamonds" 1 "red" 420x40
64#{
eJzt1zFuwzAMRZUia9orGJlyjiyZeoeorOvoUlX8ZADZQrASaHoFpHIH1BAWqCD
aNMy1GfqlmJA+fh52wWxL/YD+4n9zL4JW+mf+ffL++qtzXKGeV6bcvDNsizclp4s
Z8h5bcpRuviy16GMvUlT9uw6fbhMDq8zFKPLxBiTy2TqYHw9PFKHZsiQCWQZCd8E
Moxk5PFARu8uGakY804cpg4Ec9jDFKRvBTRLmEalZWycZBmlB+ZHM3BtteOVR7w8
Y6adryeMmnd/reJ515Z+5f81mMEMZjCD+edM8hmKPqNqNQGGVK3W1R0wpKs7YOW2
weJrtfubIV2IADPk58/2JD+aq84nerqYsi+rB0uASTUD86znHc2X2VlqRBhvAUl+
bHjLkMvEHsZmxDagI0CPY11MzzdRz7fVHVe+QnD2DQAA
} "2 of diamonds" 2 "red" 500x40
64#{
eJzt1zFuwzAMRdWia9srGJlyjiyZeoeorOvoUlX8dADZQrASaHkRSS/QaKJgaII
bUWJ8kxRfEnbx8/La+ryze3A7cTti9tTeunjM///87Y2KXM/0zyvXTv4y7Is3LeR
2s9U69qlow3xx4dWZeR5mqon5+ndZWq6nck5l3swVMhlavbtYUuUqzkjhsRUmOGF
SHMs07U7TPfIwIC1s5pREfShYuC6GiKstVZ0NcJqYLPRUyyj7OHfPgNjQ07VLvH8
jBm5XxuM2Hdsj5k6kDvlLvn1YP48QwFGZ6BbNzBjU9nNr98yu9WNHW20+Cfk58h+
hfbdyoP5n0zxGTKBZxkVwCjGSCUCilXfWJhXDM4dcyMGOUj6RozydNS9c20h9VCE
7BEXbjH9YXKYrFimCmartowMri0ktcPaArTbuQIXjs3BTPYUaR/ewLgSYiLvRjF3
qyuqXC8m9g0AAA==
} "3 of diamonds" 3 "red" 580x40
64#{
eJzt1zF0xTAMQPMR64crVEycg+VP3IFTMPcannyVDhyICamTv5OGNnb9ayPEgBS3
/qnT913XjuT05fXrnIq8sz6zXlJfWE/pvsyPfP/jYVEpYznTOC5DPvhimiYe8wyV
MxETqZ7yFP88aVc7uRsG8rZeHQZSr9nZgwwEGEwEAgHnbkMhxRy2B7F+uJQDDl
HaSxYwAAr9Vq+cn/IW0cJrtFbQD8lCnhgWVstJn9diQM3w+68ZQ8eQyIetn5ietZ
r9eOMequ47F19tehys9t6UxnOtOZzvxBn1G9KQbzNrbhD9smbVHWj1OMlavViZz
clU8du+W73XINnuqP9yTVGau26GjeCIM+fmpjJfn6mhDjHqt26pNUDLkLKBcL/SZ
GXyGIoy3oJv8HDOOhJjIN1Hk2+oKvccYTPYNAAA=
} "4 of diamonds" 4 "red" 20x60
64#{
eJzt1ztSxDAMQA1DC1whQ8U5tqHiDpyCotdQ5auk2ANTxYwr4Q/xWrJiadhQLLNK
HK+cN7IseW3n8P716LJ8xvIay1ssH7HcuYfcPsf3x6dSqMz5dvNcqnTFH8uyxDq1
YL4dYqnSlZri44Wb6uR+mlCT0/SsMuguZwDA78Eghl2Y8Bt/fPu2KJAeDROAdCIy
ySxXgPoc3TsbWhXGADSGVoX5LDIhmatMsl47I8qZya2rIaLodjxq/uQ4aQwdlXif
XCtX5oyUL85IEufLKKXj2hC/y//rxvWlJhiYdlZvMAFAZQA6Q5wJ7WJwAUMWDJkp
CwYMGYud3Xy2xMcUZ0u+THnv5cZcH+N1JnSTqmfq5CT2fMvUPVLa4zgj7ZWMEfdC
5o+8d9NxDZkyhL8+k5h9rkevEeNRjc/KjOKMPyFfUb4qY8n7pmTGq4xcmBmbPyqj
9WRkLN9Elm+rb8X3AoD2DQAA
} "5 of diamonds" 5 "red" 100x60
64#{
eJzt17FSwzAMQF2uK/ALOSYmPoKFiX/gK5jzG578Kxn6QUzceRKYVV8rxZbEteW4
XpW4jpwXy5Y1N319/74PVT6xPGN5w/KBZRO2tX3G+7sHKLzmeoZ5pqoceLEsc9al
BeoZAKgqR2NcnyfZ1Urupgks+ZoeTQbC6UyOycFEhy3syGSyyaAtk4mCymbHYoSt
Mk0QmmDqNEFogqmmQwicwQePomoaH30f4X4uJQdJTGtMZq2kRcEM+0lgjQcvbIav
Rdc/hbX8LJjuekmmT+7giB8+r5Gks+TXjfm/TDd+BNOLQ8F041kw3bzgZCC/fs1c
et+4xJg9/nH52bNernUfyo25TibZTI420yJXibHcMkCJ1cZoMd8YNXco/8DjHmxx
1brO07Tv/A/2ltzehpTx0BMGU97LLP8Qo+4te0bdWxqj7S18IB0hRkXil1GF0S0d
+VlnwMM4xmMznM+iF8e3lQ9Nm/Jv9g0AAA==
} "6 of diamonds" 6 "red" 180x60
64#{
eJzt1zF2wyAMQGl16ZX8MuUc3TPlDvkFJ19DSau4qEHytT3mKiAEBAIpLhOXofK
JgT5W8hCyM/vx+9XFeQT2gHaB7QTtCf1EvQzXP/axYZlDqea59j5A/4sywK917hw
Kudi5w+vpg99baqR52lynJynN5Zx6veM1VpvhjHmKdWpksYmKxkLL5IMtqgSQzB
wGOWZtJilwxEojB0HZWmj1Y21Ee3M16ZJ00jXfIkjSNdMV07hvfHCnz21pj4VP1D
xrnOMWq9aoZcd+wPLei5emI22V//zN9lyPypGLJuYKZTN5ygbjhbTbiVuXfduIfP
kviI4ixZL9G6kyjN4ClJBrtOMzgeJINDuZ7BS0syOCnW29nMZ018RHHurBdWkutu

```

```

G+Mtk5wc5Ji9vu3RnChXEzPK+cQM905+A/f3oNWNtt2n5mL8EbVF4o+YYWqLTrdm
pKktNt4xrC0XZlhbLDLQSogPk2RCRnOThdXot8IahhURI/kmknxb/QDHNOZR9g0A
AA==
} "7 of diamonds" 7 "red" 260x60
64#{
eJzt1z12wyAMgGlf17RX8OvUc2Tp1Dv0FJ19DSzfxUMP1CnvMakCosYSMLJ+nKly
CAZ/FkII2d5/HHahyBeWNYzvWD6xPISn0j/i9e/nWriM5RfGsvb5wJN5nrHOPVB+
AaBW+chd+PcqvTXYOAXgyc/wYjIQRmds jCYTY5xMBtLdGGLz4lerHmEztpa jTmPy
RS2I1mCKWhAtzuCNC0XU4vboDJ9X7jwNxlre1Bv/FPGWqWcCyx48sRnuZ9U/mbX8
LBhlvSSjrTs4YpXPa0Ud88+KWVkahk9PZ7ibVIA7+3KGL7/K8MC5XM/NbPb4x+Xn
/nolrRKMFOeCUeNZMOq+4MzK/jqbcecn6tXzhgiK83LLFvPy+NC1Fp41dcWGqk51
/nPC1czWOYF3JolkJjXKW4aMVJ9N1Uk02U4cEtOLZ2K6++L0BF7fXyk2ve0enI7K
N30nIXuiaU+9w2Dye5nln8p088aR6eYNuttZdy06uSzGugvT7qiG8dhsiovcfBN5
vq1+ATh8w+n2DQAA
} "8 of diamonds" 8 "red" 340x60
64#{
eJzdlztSxDAMQANDClwhQ8U5aKi4A6egzjVc+SopOBAMV6qEP3ESfWx5w+4yggxLH
K+dFl1XFO315+74fknyE9hzaa2jvod0Md218Cvc/H3KjMqVzmKbcxSP8mOc59HEE
0zkg5i4ecShcnrgpIbfjiJZ8jY8mg8PvGXDOZJxz3mQQ/owBc jdr3Oeg7S34hdmv
PYUCmZyUG5PMItPSZWXCgztDRANx1hkkTBzcJiNaYdKdQyGqmXa87Q90+eyt+ETW
iJNj1HxxRss7dtQqXvDn/FneryOMui7GaPFhjBpnxqj5okw17ycz167ns/i8RgsI
RpkS2bVIUTLsppovNomed8X14wvNpcrQJBy3Y/kDhGnVfJmqVfO0Yww10K556pbO
SO1/1LzUTttbevaorr2uKudkvM0Ar1+FKdFqrAuc3AWQxacrTgXppmv7R+4nndw
YlTWhl+MX6GeoctnZ/ucY2rUMyyTbQivZ5A7DvJ6dnLXR17PLs9V12szYtOWDA2M
zpjSxfr8E/V8W/OA+1G2V/YNAAA=
} "9 of diamonds" 9 "red" 420x60
64#{
eJzVlztSxDAMQANDYecKma04Bw0Vd+AU1LmGK181BQfaih1VRnbirPWJrR1YdnDW
m8h+UWRJdpyXt6+HIZcPqs9UX6m+U70Z7nL7RP2fj0v1Zcq/YZqWUzroYp5n0qeW
mH9DjMspHamJ/g5S1sq34xh75Tg+dZk4/JwBiNBhECB0mYDXY5B3mwyEmsmSZGic
tZosSQagVrRigqEbK0WrJHxoMiIWqfH0MCYVJt+4KeJSV0+IPXvoos8kbcdo/WEuJ
Nfy8kuVRYMRLoUbc+SOFPZbpY1w7DPPPaXTAE0kxPag209ODzB40mc2xsEmSwRKg
whoM76yt0nHnj7QZbjpJlP3PpjlA0osx57tkUOSW5Wdr/VGMSY4pZrf8c8YzdocP
PbFwxPS38ucqOd+Yg5657FkTXGuLZ41yrXWGC0yGO+9MPXUTajWJQegzRbf5bloY
LDda7zjBoIlyBqx3LrennasIqlXnRliVXz6faT+Vt1Ute2jHtW6rmkyE2J7vhUEQ
sY2aaa0/G9NYxzZmt/w5ozJYMygni2Ka3X7G803U/7a6H78BawWaX/YNAAA=
} "10 of diamonds" 10 "red" 500x60
64#{
eJzN1zGulEAMhg2iiUYwV3ii4hw0VnyBU1DvEaYdrVCu4Daa5hVc41VcwrVShFD4
bu+yySS7byWeBJPNy77Jny8e27GzHz//fEs2vmL/gP0T9i/YX9Ebmz/h/Pd3vm/H
yT50Ov1BN3x5fHzEUWcm+9A0+UE3ncKf9y1qN14/PEzPDxmiZ2om+nvNmPsX0Uz5
Dnv+keZKGOJaU2nsjX3WTx6jT2dsK02v1/Su6dN0pBmzgZSep3GeznmtYersQcs2
HCPRH1lofuf8bWW8rySuD3F6wtU/9Epczq4RvqXhi6a/aEYzYwpeQtDwrNGVzBo3
tQ8UsZkmmuYJ8JYT7ZxqSDW2ksae1SbgnnbpDY0UxGvLcf+EKDRrqAxbe9zPF0ra
2dzZrMviJSWic4o9w8PWPxZ3qefAKXhNz4+PFO5h8hiI9aYybDRd9GzscK9hCOO
GRkiewZyMu446tiIaJfLhFI84FAhuNazR6hD5HYcSiVa1ELCCT1ELsdjN1AiwsDF
YLScfBgRSslvppi04wSEkCX5UEyHWzacgmWxDDYcwzI1HKRfIVlhwp6DVOCqqRgk
fssPHKtGMFYC13b2cITmYk0JncSWQzPHMMk81vpHrZbZmjPM6XfxQn65RhcUzsZp
/Zz18SO1ZqBrnDFoiBST4YNwzFEzNODDUBOAHXAmzCZ1b+akobrGOeOcyYjT66p8j
z11BwAzqB/j5kANQUEwSJAff5cAo+i3odG4PeQY1XCbz5HgHzZMh7Aywo1EaDgE
P4cFoxykU8MRY16sgcYyruXoghZMksBxZ4/IxRq1B0kQdvbIGpNQ6vEwtf4ht8af
wPpA7p53w5A/yynQPlfJSkBaakKI6qlD/THMXFvgLI4HdUyLxlyjUNHiUR2z/ua1
DpXoSj0MJXDOqiOf7vYcLbmdwKGPWP/yjtdwULsVj0Cwt/KLpldOPcfoJfIrsLfY
RWntg91Ib5JqsbXyRaPtPyvaZsU52sW8Vc0ab2Pw2cyJqvGWN2u8HbKEeF3jHNaF
Xjs1BW/sodqssXZ9/OZW3qzLfAaNNWRbjrVD15CvHUvc2nPx86TV4oYmVkl9DWv8
A48u/dRNzXpq4+dR/6vRn8Yen1Gv2MQLc1Uj9X2tT97KjzTdmOurn996nRvQXH2H
XGlujuv9Ro45+Cclz4y7NPb+J7vlt9QeRdPNP9g0AAA==
} "jack of diamonds" 11 "red" 580x60
64#{
eJzN1ztuXDKQRWuMSQjCri0IE806nDjyHmYVjrUEpoQw4BYqNZgo8CYceQuMBuJA
oO8tvu5pVttuBQ5MqX/vHV3Wn6237/97Lb4+4PE3Hu/w+AePP+RPv/6I+5/erMe+
Hv1XHH/XC3/w5vn5Ga+8Mv1X51wv/OE1PP0VpW7Wq4eHeW+NB73LTPkFTK3tHnOq
td512vxtmR+kQa+Z/9WGqeqouWPPdDp8XbaBVbP0bjMyp7oYUZ1Lh8xVDHVFvVvJ
mLp0FJevcqHza63/ugyuDE3SnXhC/MZq1/IFKq1YtmZdstgqwkDdJS89qInZ4bG
wbxhqiQ58YgZbnZmHKktSypzcLPD5s8QDzpZqjNKG+C7exLsORhEEQBdxOekWTUZ
VQy52HX8E0yuxbM2U+Femz0rzmQyXJ8JoZbo18oXXc8KewqWmK8Vt7BKLaygqdr
9SiZvX4QZjAiYIMwUpHhOzCICu98VqkamJFNWYR03IfKQGU3Bltkgkwo9FjLQouu
GGSadccKG7IAWJZ2xlikk7Eh4CQd2Bg4Mmkt7/mCTN4ZFANrRF2EZWZ+7YrB36OM
xWz6XgBRtTnoIKg0IfTqLYxIWwp7UdzN7Jy2A0iCUNAZbJthBRBNy1iKegoAy1W
2HxMxgnmxL1gTRfa6TrWCvaKfg2moyt1aPIJBS3Br7msaOw9aVlbKRwyuw53y41g
ZDDUMY1x9qBY1YtO1qAjlLFiT7Us+nTKEnt8Rho59Y/sV+pY1HGZ1nIi0T9CJ8t3
dHI6Db8h9amYy9zEEO7AVvedA8F1oo4V6Kj7zhTzsa8W7notNLNrdkY/2u3B/2B

```



```

+HBmcMDuNY8YN4YWQWSc0a03MaQRQ3xy4y2qBLUWmCQmTdwKKBS0R/ZS2HQK9ur+
rQC1Jmwhz8/GQIglRm9gORjcd/FhAcrqcnaw8VwRiX6hm89NzBHEjrToV9ZLF8tg
Awd3NFnKXon2NBEUh07GdSS7j1UgSU4ajZs97KgvwK/CPXvToe/WNJh+AOFPp0553
ZD40XshwSDIEdd0LvVPrMHuUIsr1W6EGEW527dRymZNRGNJ+9GKLCCwLHDxk/bs8M
P+E+hBINRm+Q8aP8wvD4weJFWB+8MiqZdZSfGf+kHG2IEQd15RxcR96Z8eOQI1zK
GDwnv8MsHex1PEMO5jiCd3smopeYbTBI53GUB7/QMzAIx7+7HnVWfNh7xcus0PXd
HjxVZziH6LuP98icFgOD1E83Mnt8PKJuc+YJ6hU2Q5wv8emdedVj4m758q91fgy6
YwOJ9zvthsmHjuqleCLzo++Q18xP12/IMIZ3mOOL6s+Zu+tFzEv+J3rJ/1bfAGnk
dy/2DQAA
} "queen of diamonds" 12 "red" 20x80
64#{
eJytl0tuFDEQhgvExjJQV4hYcQ42rLgDp2A9R/DWGqG+greRF2TBjBLKFWqFNFKQ
+atsd7e7h3QQ8aRnJu4v9a5y59OXX+/I1jdcH3F9xvUV1yt6Y/sn3P/5v17j0tkP
nU71Q1/4cnd3h0/dKfZDpdQPfekW3j5sRe3W65ubcrTkhg+ZQv/PxHiJ0swsJeJ1
xFymYwbaipnLP8n5Sxp4by++S7aV8MpNOq/9Iv3iJsbPPmFrUuYyLYxjSRCKRMRI
sxXMOoZgMotXotoBW6drTHGV0ML6HeP3amZZ/GIYobcFG1LKPTQ+jAxPxxjDzIXW
zLRm4BvbEiFYrAuMmt4ZVscqU8pjMSRODHkPoz2dQVyaHDN98GtmpNuj7MCILfz2
SJ3ZyEGcK8Pr+KzscUyzKmIpPc5rv5xGrqvSMLZ8reMzM7ahYM37Os4rOaKvoguh
vM5YIkS1UYvDwJRmsu6K/cWOkbmGLYjK08DoPY20T5XyZLrH2kC2cF8yVXHJ5tmo
i3AzM4pdEOWIskdB8sYvTjI3lQshUfQeFurRL7113MhMaUYA++YXj/Q44KHOkAD
Uyc9tz55SMqZrM9WjGC7NoY2LIwmhTa6og+ezaRExgByI+PCrU9JNiQ+KQM/cxoZ
iMmw2rsYVEgi5Mbnv8EZWjngG+QANEj43y4hRbumUj4Fp3fMapCICCGMQQC05b
Xc5HNUiNnpOjy2MMXXRUGSSmr1k7346+646ZUhlLbQ6bGOKPAmGQWYDQk07sek0u
9Rmi7PSabtIMWHqXzqMuJ4JAXpPJqabvmQQxlYEGxNLKddtLM2n0NZ2kjqCPMZv6
QbbVZI/CvMWSSjPRQ5wVgg4mKlgog5gNE3ytG251JgglizBNnhRK6oRcs6pVHRgtc
yxwp4DaBd36xQtYxrhqUM+2YQgHSKYW4nHDyY2QweLSrS3JrtscAED/Wjw4eqbHV
OKGzs86RTX/p+NLCUMiGTNnlvfrSa7IdYm7j141LO7zaoC47pg62Njd7oN4w0uYt
TF+G+YYpQWiLbVlhJmNs+NvkvsJHb/bD2s6C+WxZmHs7XOthJMT9GMNhNTN2k+uh
Jm8XVX7FXOoBXJkWB1Xld3Lmw7ozOq5ptKcd1o8LY2N28KvJEZLOcJmmTXzqQSyW
rVr0AlNwJNVJO4V2tdrjY2Nfp/faL3sM6nGuxBmddpWxfOk4BIHntiHO9ljw8i71
ic26Wfo/MKBad/r65GcnQi+ZysQnniF7vqby9FLmAHmunOliUPPrGLEyvgBzYmXz
mef8T/Sc/63+AJ3HlMT2DQAA
} "king of diamonds" 13 "red" 100x80
64#{
eJzt1zEOwiAUBmA0ruoVGifP4eLkHTyFM9dg4iodPJCTCRM+3utiX8NPkNaY+FrE
4BdoQSg9XZ5bw3GjdKR0pnsltdIbLrf0+30n6T0sn8ZaydJBX/q+pyzVRD5NjJKl
IxXRx2Fc1Yp110UUj24PTTQnjG9jgmtjXPAtDAKHjXPQEHEeGW4uawJVQo19bIZY
yDgP750uG15z6uelTCwYr1QR7h+qBpoQFxuLv5nPeGx46QIm/fOAKsUnb2TJyRqe
CS5vmIwqqjDS1KixLxvVixP3FdC9D8tt1kzF3/yeCQVGTv5tgpq82ujJq0zQk3dG
46GR5zwwMNqZqZlZY4aNGTBowGTCYR/KhjNvZOPawOinUZ3RT75KA6LilLwTlxbx
vQADV0S89g0AAA==
} "ace of hearts" 1 "red" 180x80
64#{
eJzt1ztSxDAMQA2zLewVMlScg4aKO3AK61xDla+SYg9ExYwqIdsDG30YaXaXzkoU
Z5wX2bKvkfLy9vVQunyWPrO+sr6z3pVD71/5+elxqJS1n2VdR9MOvtm2jdvWQ/0s
RKNPr+viy5M2ZeR+WSiSz+UYMlSuZxAgZACghgxhgonwyMl5uwwyG8CSEoaYUcQ
+ghnQ4rBwFwaArK+t+cgGou7YzWlvITp4vgFe78uZvAOBdXbd2GGV51fMMx+BYdV
Z0/1TVgMAoUMld19JlYzMe/GjzFEN/kGJzOZYUxmMv/EYIJRqdfjUKVhj9E51lgt
R1T5HI1Vy+jM7TAIZnqNqaIoMiVAn3PVmRgMI+RG9cZftY0sMK5gWl0WMVUyZhX7
vku/OPNr36Vr0R/G7rRlokDsDIYMZBgbyVYbJxHwoKSbzt5T5t/oGyDsmgPYNAAA=
} "2 of hearts" 2 "red" 260x80
64#{
eJzt1FOxOAMRQNiC3OFihXnYMOkO3AK1r2GV7lKFxyIFZJXxkmESOfHDEjRkjj
NpPKfem6qe2kj88ft6nKq7YHbU/aXrRdpZuqX/X+211ro6z1TOvaunLoxbZt2heN
1DOJtK4cRaU/99aUk+tlkUjel0PISDqeIaJ8CoYzh4xQ7I8aChkm8gyrj0X/9SjE
qJLWLDp3LMONoYihgfFjdwyYQ8ugcVlGgD/SkHw0w+OjKKP3PpjRWdc/OKafwWYV
vNPemz2GSUJGcnc9FasoNpx3eSjW5SQ5EGHOy+SYYYoZml2AYZvJgPPfGuUpZE5U
E2bqz18zbhaDog8Zs15ABsmF+X8MTzAueT3DLnk9Y/PJWU0HNjGOaotlUG0xDKwt
bX3uzKDaUtF53syZawvzbzQNgxk3IDLM3kz8zYhhcW76ZvdrC424G1paZ+JEAafGc
Q4YiQyBwf8uEMsXmfBPNfFt9Aow0CNT2DQAA
} "3 of hearts" 3 "red" 340x80
64#{
eJzt1zGSwyAMRUlm22yu4Em150iTknfYU6T2NVRxFRd7oK0yo0orYACB8aCdOB2y
CfnQK8aYjOTr/Xky3h7cvrjduH1zO5gP75/595/P0Eqb/WnmOXTu4C/LsnDvPORP
QxG6dzgXf1zUCs7ThP17Hc6dxkyrzNoFQxoGktgQDefDtRleEaJcVd2gQvBlwLB
sGCPLUXJYHBDJYr18SMkA2oGYB/Gm7wvKPeVxf8YlNGTgPJZyJFR8HrLdSbMYZKo
noUbm8JESWiwh4lixZAIE4Wf1g77kBT7mZB2+Q8OZjCDGcxg3sSggpE5aYNBgC6T
cmQRzkoGY65t5LgV08iVNDPKuZmxIZU3cneesw2pvFUDRCaP3KHe6NU2GKuzFxxC
RR0Fm7Vfuc7QqiErplmLZoYU+8f2Gc0+JA2DCkYx566pGM07kebd6g9PV+vB9g0A
AA==
} "4 of hearts" 4 "red" 420x80
64#{

```

```

eJzt1ztuwzAMQN2iYz9XMDr1HF069Q49RWZfg5OukqEH61SAE0tJsUWKsqm0BoIC
oS0rpJ8ZWpZM+vX9+2FIcuD2wu2N2we3m+Eu2Sc+/ /mYm5Yp7cM05S5u/ON4PHIf
LZT2gSh3cYsmPjzXrozCjIN58jU+uQwNf2cAIOzBEOEuDJ4dD7ICUCvJsDB8RXKs
FcVgNkOlgIw5mkAy0M/ImFcYjAeHofq+QN5XUc5jUHpfFAjQWcgrZ4XHm9HCYHGz
KmmffKbCzawYBoubWTEMCtez0jNX1TivSQzLY5B2WYNX5qIMdjByxq4wCOAyAMZR
zSCAcVQzahG3GVQvJN8zAI0/uywTPAYzQ1tMzBLojGFTrsz/Y+wKt4xd4YZprHDD
LHNTuQuSWVZ4I8cZppEra6aVcwsTcipv5O4Sc8ipvFUDzEy5cod64/TiWatt8FQM
bTHJq8fEuqyXQcmgYlLdulJDaqZdi6qYtyQzm0iO2ZFepi8el3Gli+n5JvK/re7H
H4xdySf2DQAA
} "5 of hearts" 5 "red" 500x80
64#{
eJzt1zl1OxTAMgAtiBa5QMxEOfibuwCmYew1PuUoHDSSE5Ck4DmntJI2NeOJHem7z
8px+dZrEdtqHp/frieWfYj2VRyrPVC6mK25f6PrrTS5aFj6nzclVoujPuq5Up5bI
5xRjrtKRmuJnrjBvY0U8R0ve5luTidP3GYTgYMDRFxkyGTQZ6stkQDFpBokBtQKq
L7qDDWtFMZiboVlaBiQDfky+8wGj5vmAYZHjAjmuXfkag9L6pkBQayHvLarNN6E7
g7uZTWf7ck2FmaIOdO5mitIwUZgpCj8x+XPjriIGE8Sg2fml5ggL4Qu0/HDhun4
c8304qJmevFVMf041cyJcoIn/ /w0g5LBljnI8/Uc9vYLzQzKzPw/Bh2MjOEDBgFM
ZoskZS5IBot3D3LLxgxyS2FGuSXvz0Zu4X3+D+UW/HwZGjFs1WLSe5mXGeQWZozc
kplxbgEwnCwzQyT3ZQivqc14/D16GMfz2Iznm8jzbFUBqcKs2fyNAAA=
} "6 of hearts" 6 "red" 580x80
64#{
eJzt1ztSxDAMhgNDC1whQ8U5aKi4A6egzjX+yldJwYGomFF1ZHviyLYSmd2dLAVK
vI7sb+WXLCcvb9/3Q5QPTs+cXjm9c7oZ7mL5xPWfDymVMsV7mKaUhYsf5nnmPJT4
eA/epyxcoYh/nmpTjdyOo7fka3w0GT+czwBwF2E8mQwTzn96GG5MMMSdAxqlyHge
FAZRKZKhVIXaCR2SDCSd4xlfjQtyXKvyO4ak9azAFesu/7koPN+MrgytZrIS7ck1
FWYWPWFONbMoDeOFmUXp8VUK3TJ9zNkM+YvswX/mSoyTFU51FD9sGMWfa0bbFzWj
7a+K0fdpyVwoJvTEN6MZkgy1zFacr+ZQPS8KZkdahjoY6SEbDAEmAzSGaokU2ww
xYLRDBWLCdDKIOdzVDBOJURRZQYXzPFCEzKXOYbRdVTjJ5hXZiS2Z2YsvCELZj
SzqfjdgSz/m/FFtwBYawHVviSyn2Y0tkjNhCedZlifPTRIGTGFiNSV89kzGli+n5
Jur5tvoBfRyUSfyNAAA=
} "7 of hearts" 7 "red" 20x100
64#{
eJzN1ztSxDAMhgNDC1whs9Weg4aKO3AK6lxDla+SggNtxYwqI9s4keKHtEMiQ8Tx
SvlW8eOPk7y8ft000T6onKm8Unmncjc8xPhE5z+fUpe2xX2Yp1SFjX7M80x1Pi4
D96nKmwHRIftTN1Vh9+PoNbuMzyrjh98zCKAyAOBUxuNhjGwzUuNCQDqyzeRhCEhH
XAtTGDZOWQBNwM7w9jQY0a8GE433C3i/Vuc6Bnn2xQEn5p3/Mzs03oSuDK5Pfifm
43PK0mSnYHBNk52C8SxNdixatWjeh2ZpDPdp7sHrmbmJVPXvGAami8YTYdHMn+s
eclUNb91aprFMjXNF0xF8wVT03zBtOy/GMdPuCpj6bthDC1zYZhTizZ20uGt3V8h
jNBfEyxri2mN6tiedBoYrqOGgwAqs8ywsOc4g3nUO5pfmI7mM9PTfHo+K5qPz/kb
0jz+vAzlmJhVY8J7mZXpaD4yiuYhvw51NG/ST7zWQqwooj2WTUTY/kmsnxbfQMa
WW519g0AAA==
} "8 of hearts" 8 "red" 100x100
64#{
eJzN1ztSwzAQQA1DC1zBQ8U5aKi4A6eg9hFot9JVXhAgKma2EivJknblW2XIJCiW
nVVeNvo82/HL28/94ssH1Weqr1Tfqd4sd759o8+/HkKVZfPbsm3h4F70zt93OroW
67fF2nBwL9dEu6cyVVu19Vq5Xt9VBm7/J1BAJUBAKMyFq/EIHXODUIGss8UoWuQ
AfCxY2iGivAxZ4AzIfcJFQbL32owdobh/bGh1TSC0xjk2VMARqW7/2YMaL4JzQzm
NCnw+fiasjQxqBjMaWJQMZalicGMqzPO+0XVGLRnOQdPZ9rOS6btvGA6zleM5uEl
mawWt354zQfOY/HDhpzGDVP+2xu6TymbNnc0vnUK3YCFM4jpG7ZFuM0Tww/AQp/
QI76uowJmxiYdp+PsZvR2I+588J351BMf2ctRF/bayp06LghBq152GdmnL80g5zB
mpm5tkxdowblnAxOMIW+LQaZTj0mrBIzZiDcdYb97iKadwrs2bkfLg/K877+/w/
ch5zdwYMTPhmIVQgjeY8xov3wHmIf4cGzvv/raNyaaa8Zjcy/NSdV8SUM/NMNPNS
9QvETVBI9g0AAA==
} "9 of hearts" 9 "red" 180x100
64#{
eJzF1ztSxDAMQANDClxhh4pz0FBxB05BnWuo01W24EBUzKgs/uSj3yYClSVZryPl
xbEs2UqeXj5vhlbeSn0s9bnU11KvhpumH8v197tedRnbbxjH3tsjnByPx9JWDbff
wNybelRV+XuwXblyftjwXvk4308yPPyeAWDYyQgAdxmk/2IIsFqhBcMAQLVCC5qh
rgYteAYkA21GzWHMaF+cYFqRdoG0axW+x5DsfrHKkFH4ot/ZjMFJqKcg/UWLSb2F
uT/p095NY5D7aBxDMA+2ego4YhgFwzgpEm38rMwysLcuLMP11DcknFAVvM+wZ9g8
KmTId+NjfpodsQB8zNMEkvc7wRzznVsXAAdxScfjMBO52L+OOY1w/JOLZiYDwUT
86FgYj4UTMyHwhlywZ8xKC9gyGRsT8xhxhcJn2Zi40xxeMmls6q313KfuNN7QmZv
Se1Rcoal6id7JimDBEMJRM79EDysMCTuO8UsOvs5aWIWa4Mc55ggV1qmOYh0z10Z
7KkcfO5ex4w91YuUcKFY768T02ht8XMxm4ynGdIMuSZ+B3SMOG7qGE2ysUzt+o8
Q3bROWbzcP7JfBNlvq2+AMWyKIX2DQAA
} "10 of hearts" 10 "red" 260x100
64#{
eJzN1z2OHDCQhcuCE6Ih8woLRz6HEKw6g0/heI/AlBAWvAJTg8kGvsRGe4WKBBDW
ovwe2d3TtC5qB7AAiTm9P93fvc4W64fz4dOX99LGXzj+wPERx584fpFf2/17XP/n
t36cx317yv19f+MDHx4fH/HOM9aeYtbf+OApvPw+S3j3d2dvTX0zr/JmPx/psb0
XRiLN9jzg5hXlsEfmU3N1VhrSjFF309HPHYmPthLTJo6UwN/rmemxvj8FKM6q2bJ
IKPZHJh4Yfa58ZDYh7elMXT0gYmN2a3tjB1s3hhFvGQM0+JFXmHUR0y21Hx9eLnY

```

```

89SZZWw0YHBOYGKEQRvz0pAHw72sM9m8993GgfE70+w5Mfa0mbwyfV48+7wzlYyp
wI4DU48+NHO0YeI405nNz+nA4Cdmu804L775+bDu+Ekig+T9F0jJjALPtDscZb7a
qtOCwLYNa+FawIhvNYDIMjMaKFCwCCZrCpErOhqEUlMKIDrCsuz2nHUU0iU7IrnV
oZHhu9c18/JSSnFVJsbDwnHKYxxSqTTqIMLFRRUSmQjWYNRRcwEQfy+uIRYnHbHa
II60jLGqKq1BlNmQPDBeXYPgg9CRpa3H8V6quUHOu44U+ODE0MmlQRKCazf6nGVg
oEMnmwUHw6CSXRlsbjqAIoSQ8oFuhNCKw0WCRsCTnyg06XC1lRFee5xAaNzRvDrM
PQo/FXHvZvDJOI3UQiwrfQFY+X9EpWHuNQRkk+KruBuaKZe09bGT8MtG86xjz+zT3
SYexMfpwltGwnNdi1rHlb2kL39a0IqxnHaQmgvAQG7MOEnMZYGw6/szkHmHHWIWR
Z6aIG2I+iNpgz4q01ImE4MfzvdyG9BQkhKwcGHoX+b6lcmx7mIFBtp9LAjLoj4yp
q0Rwr4IyRnMnHZZUXGAPC6xiqFjBZqaUpbXBUIROlisMixhLHRO9xcklZmFdrIXX
nqAoxld0MFiWW/OphrJ+YdJmT+7NhCWVncFf7sW24VhYpTecptM7zm6w/Tj2xt64
4D3bOtXGtDbm2BvX5iZfZe1409Pa4ZHhzXqT3plle4D82plTB94ZLJ/uzFebGBR5
n9A2V5tVbdsR7DZzuwBG87rTkNUcyp9jlfZ0x15h+rz2jc3ExLgxrl8K+47p4MPN
zwh8hD5ydd15XfycKufEKhXbdq2ms07gzkz74rDnIxNrv3ZYU6POa3vIA/PN8TMY
LXS/A/PWuIm55T/RLf+t/gNy5vcz9g0AAA==
} "jack of hearts" 11 "red" 340x100
64#{
eJzNlZGO5DYQRcuGE6Js8wqDjTbwKZxstHfwKRzPEZgSwkBXyCowmAl8iy3mChUt
0DAG9P9FqbtF9Wxv4GDVrelu6emzWFws4vz5+etv4sffOD/i/ITzL5w/yS9+/RH3
//m9n/vj0d/y+Ng/+MKXl5cXfPJK87e01j/44ix8+TBKHY6fHx7avcMe4l2myf/A
5DzfY04557vM3H5Y5p0wxGtmU7NaF4lmtl7em/mpvcFfWsDgkBsMnPX6Bf5S6jsX
fjle+zDi+8zTqGmtalzlL7Egk52pWCMqaw6rdlgkl8KZbPnyOisYIxxJKPE83Y35
0plXzfAKXmFy5vT0drH5zzGnZpDh82GSln/K88jA485oLpsJZ6b5YHMzzvzw9ht7K
lImYuWwMn3y9xGuVkt4ZXWj03s+eui5jpxHyndn5GSd/QcZqbABDZ+joK+ZEBPFU
WKJSOTpmts8flylSRy08axz93Dys+BVVpFbRWA6MVQ7BkU6FWfo8MfKDTqBD/K5i
rBpLpe2DmYeh010QVJHyBQZmKgF0TaDXvRtqUIG5J7BU7VksFm3GZNTkt0DC7WG
5FnKmlCj0J5hBAQQFAsDq3TSYDNuGEZLDUyEo+SoAluT5SkkGkTL0VLK0c8yZZjN
ZSNAjzPvYdkh0Mlh+1gt0VED7MH0LCwbDpTCVW/YgPXEvOyOhwiZObM8EBAfPg0H+
hEJmlJGc+soLcLdMzCLe6qATcsbig4gnWEYSStCDTuaMcqrQKVNRDJwGPYugKIRc
onlStzlk3esgnqg7qouCgVmVky6H0vce1JTqUVLnjAWTBx0apCoaYERYDaBqJu4
08HDGCUhitUSUIToiaNOpWsxz3rhIGxDOKGI+o2MwWzcpIMz0GHcfR7YBakCu08
01GuFvTSc+8tmcXebuiYJc8wMBPCZ8MaZKJDJ3qmcrcE1I037ZGe8QgbELFKG/2M
UGRIDDyzFquDTuVehCuQaYB4mg7+4U1IVfct8gmjIcWGdUqD6mKIuHkfZH0ZGF8r
M3G0lXseSolUxhqF288+WixeOm3JY41CvdDZq9zyL6ti8+I3MA1FrtsMK3zHNfoQ
f1FJxRPmQ8yUJPCyTSZhnWAlnF2/x3Dck8mu/N1lUFnuGLYNpxBUFnn2Vh6hzkz
3n6c6cspj/1TnVmvi3hh6EbGwv7KpPzhfF2uDL0S1t180S7DBvL1oEvzKkzmlcm
HRhv8/yxrjy2/21HMPq5YQH6NgLz23YwV0zXscVJVLf2ZE4r41lq4Raz+plRxbKz
UJyZr5nNz77VQDwDyuC28zoz82pPM9+shVLP07g07wPQsf3UNe50bd37+whr5lv
Hj8g4xn3bcZjcy+5e3wX8z3/E/lx93+rXx/+A4IDtCr2DQAA
} "queen of hearts" 12 "red" 420x100
64#{
eJytlz9u3DoQxicPaQjihVcwUuUcaV717pBTpPYR2BILQldgK7BxkUuk8hWmCqDC
YL5vKGLF2hs5SKTVaq397cxw/tKf///xr9jxFdcnXP/h+oLrnby35/f4/tuHdvXH
vb3k/r7deOLD4+Mj7nxS7SW1tthtPPsLbx1HUu+Ofu7t6duhdOGWq/DmT0pKmv8DU
hPOMWazZBtrOmew35NwIQzjaw3ctpfh2bsLDcV327iWvZ00P9TlNNSxTx2hQn4sd
YUnp6TssCUcf4t3n6ktJOCIMTROvgREwLiUzlUwypiloZaApt5VA6w3Gg6kBR88s
D89Xm71IESCQhNf3xjz19mhdGeX5bMgD15WOjJZguvDpFspL7Ewz6KmaQqedSQty
dmYhg8e87zZz3YrDVgqSOixeuGlxjzggRdsVAgWZa5E+OwMXp+YerI4FTDEM0XTw
M8IUmjJbQF32dNgYNznYUw3CS6LUF4wkmpVaTg0r5HrGZHYbCGiSarjNwOTY4Qh
BcEI6sA7pMLAZIkzZJQc8BfigsPyQscg7M5H3Ev2XuByjaqXPOjyzuWqyFbJVKUR
67j0jJ8l4hEYqIpUBSelnil4AhNYyzBHNQws3/X2zFEChQlBDj93UVOU3h7PisBy
NEJZDMBclLm3xzsIIiSfy4c2kUtJgy4rrbQ1Ayy0xDIPnpsgaSVjvoDDysDMaRci
DoJ9mUfGN0GVew3KX5FDQTNzei2VV+Q4CmLSILu4JjGbh3hFLBouCRaxahQ+9HIi
BME1Ck95YdtDF8lu0JX5Q0beeeYR4zbG1BdrPy07sITEB3HwT74YRIMjqxYrH+Ne
XGktV0JCCoqbEwsNjPjWlhlSjMrgnheMyVnW/i4s7sE/JsfqzqJq4Z19zzizOegW
lNgE9cylMAhIV0syJQRBQ66iHJiiYslaCbmxdlgxymRPdKKyScioi4WCYsDvWWKo
L0YwJzFFq0B9JJSYAfu9jdKN/2MWi9aHcsmN2zRfHeEW2AchDklKOKqC+Xxf7CFU5
Fqcwjlwe6xTzC+ZUq0INGGXQHIEYss85ile2u8CnzOyRYU9EE2RrhcloYwWsi4NM
Z+dYGZd1phfMwnKwCW39l7P3ykyNYZ1rMFswFDgcrvZwbITapkjrpbXsbcpSDBtF
S66JDJ6oGS7X3mtjLKxTzaytNqTcwr4bh6HaKJ52Zh2eK9MG+Tplrwx8rbcyjm70
cCTPkcGY36d+2wMYg7DvNnO7ELbdgw1UswfBmH6m9IzVT65SbzBWxhz2zNTenm1X
pCQvyEQthznYmG135W2zlyvtwnfGtmVh3aXptmlrQXxlmn9w1pu01FjHZN+sYfc
YjrVXx9kTpC3ypnOBK3rOmHmH3+BOTHmrcxb/id6y/9WPwHf55TR9g0AAA==
} "king of hearts" 13 "red" 500x100
64#{
eJy9lztSxDAMhgVDC7pChopz0FBxB05BnaOl4ECqaIOeTtavWGYwcWLHE3/zs7Zs
bfb1/fsRtHxyfeH6xvWD6x086PuVx7+erOZl1RvW1R5ycWfbNn7Km6A3hGAPueQV
N8+1VFXulyV4hRZ0mQATGJzDEMxhgHAGwws4jMWvy0i40GPMXI8hEYG/M7vFixga
YMCpf/nrHABWwELrc8shveYF9MwbX007j8Yns04OrbN+wxVMr9mzEpskoG0G0+c
1hs69WxGIOlk71bMbogg3GyWDJImceLLuhXDA6JvZqTFw1jC6DAeDdAZo6aow+jE
udj024wqHM0ZY57I45xJ7xN/RIjdwbhQjTU0Gys39lvrLO9pv9tMdEhlbAIVQzEC
5k/iTsYgJPPC1t5QY+JH9L21x0xoX+5EptjPMkY6K4Lmfo5CiIVMfnaiUCGTM4dH

```

```

mUxxBlWglCmYKJTTLlGfZtjsV6jKTI56f+CqPZNFsM+Zz6DKh8qaRW0/yT7lG1TRa
vk+FQsVQmUirbNxxgqjLG5PnxhCFHZui3R8apj1z8+6Wpvf/FNcToV6JjaIosIJAf
L/TjNcJM+eYYjfttle2Pkp9HI6sfYx2h1vYNAAA=
} "ace of spades" 1 "black" 580x100
64#{
eJzt1zF2wyAMQNW+rglX8MuUc3Tp1DvkFJ19NA85kKauqhBNAkkgUmceG5MnPgOS
epb88fXzDtK+uZ+4f3I/c3+BN5GvPH85pf62VW5Y1zTEi39s28Zj1JDcQJSGeEUR
P461KtVel4W8hktwGYL9DIOnfYa3HFyGcIDx9yPT7p5NBpUizZQStGwXj9wXkGW7
eCRjDNsRIFdk+lCiIXQZTCHTs2KI+Qu98BCDA4zhZ55HzBgrxhACUrbnRozlkuTR
/nk1mHqByxBb4MZzI8YeZ67cZCYzmclMZpx50jta3vd9BnWS9RjUC7QeM+tbKt/L
XH1lsMyfRc69as7rC7sGyCqnf9UJBrOnbqmLovqvFGODTGQoPl0tJpV2OWOeV6o3
mlaQFWNYI8nP/fAZKn5l2o3VyVYGoz2iGMMjxn6cNssmfBONfFv9Aj95nK32DQAA
} "2 of spades" 2 "black" 20x120
64#{
eJzt101SwzAMhQXTLfgKGVY9BxtW3IFTsM7RsuBAWnVrFBkYWX6OXJqZdlEnrjvK
F/lPfnZe309PpOlT8lHym+QPyQ90UPssz7+eS67TrDfNcynWS/4syyLlas16U86l
WK/VJD8v3lWTHqcpR4mnFDKZLmekOWkPhhOHTKa4PeIoZFjHvWG4qgoz1YUay5/3
gNERMQzoOxNZR3AMNRqSfaWpi0vIbPriJPkJvXQWwMMtfm1z5kNg/uVOJs2d2LM
WsqIbs9Xh/EvhEyWHgZEcxyrQ8wvd2euwLBfOaFuIIuPZ8T4ddFhzl+n/2T20hav
Y5Dh1k2kq5jZZ76y2y86TJvuzG0x02m06v02gyI4YGCsej8wVqnaP7G2cLl/Ym2x
W3VPE8xKuAvTYXdwQtrID05IW/RcZh1BbbFMTluq2IDz5cYeagvw3tYVIGW+BuI5
cuTH8AImTEPMYDfRyLFVN3+MWqT2DQAA
} "3 of spades" 3 "black" 100x120
64#{
eJzt1ztyxDAIQEkmbcIVPKn2HGLS5Q45RWofzcUeiGpbBSHZQp9Z2PGWwma9yG8k
LBIv35u7yDyx3ph/Wb9ZX2BNxlf+f7lI2ktq5ywrUKSD/6zbRtf40iQE0Jl13JE
If75bKfq5HVZgiW0oMkEOM8QOhjwMOhgwoEPAYbDHmmmwjEvBRUjz1AbHQN6zwmw0
+OMS88ZomDhtZ0Clh7I0tEbNpFzBgFEQZnpesNmyMHouPMwomKyUcedDaTiczbe
8/Px6piBeJgARGYeVs9+htm5yUxmMPOZjJ950jta3vf3GVKV02RGvUTLDGpc8Qds
VRzVyp2hXFxHNXdNRK0egNrhB/sEzTyjb6Hi9LE7evMPZtxrlbWOvkFtszIKczZe
JTf6XrQw4X76SNzRZshIw5BTx2TIwTh8NsXfEl6JPN9W/6HQFrv2DQAA
} "4 of spades" 4 "black" 180x120
64#{
eJzt1zF2wyAMQNW+r1lX8OvUc3Tp1Dv0FJ19NA89kKauqhAQg4QtkjhD34tsTIQ/
IFsKyO+fV88g8s3lJcsHly8uD/Ak7TPf/3lJpZVZTpjNVMDfyzLwnVsITmBKFXx
iE18edVDGXmcJvIEp+AyBNczbe44gmGLD2HwEnsaPCkg1/UGQjNJ14F6zKxAAzOK
z5WiGACwSmszShxoBSWeQtXzNFCjnmVgDjqr+AwOMPF+xYRQMvNrZ0UBV5uzon3a
8ZdM6vjLMB0ZYQhwIJ7rZ7+GKdyd+ccMARI38J/BiQ9kmI4fBFBNxqmWYduyWCz
qFzOUGCqW6Adxr5VO8yt/EVplfQYK3fmGOagNvrW+32mF3mbTC+X0EwvJznZA2lX
702VhcG8ufb23MJI8XIA1M1n5gk1c0DeUm3lJkeq3mHpu5F4hbiB177Va66Uldnz
F+VMcddfhennlosrmbRHGjVUnUMeZMXtcxptpkBn5Jhr5tvoDMLDOXvYNAAA=
} "5 of spades" 5 "black" 260x120
64#{
eJzt10FywjAMRVWm2+IrZLriHN10xR04BescLYseSKtuXVvk2YmtCMiUzDDMocYyc
R+xE8o/ztf/9ALYjLR2VbyoHKm/wzu0znf/Z5tLazDvMc67SRj+WZaE6tUTEicZc
pS010eFTXqQzzTRFz3AKLhPBZjCddxlwGQZcBl2G+nIZGGfKXw0eVAahG9YjQKH3N
4ggGOebCEWMGgN5pnzNyHmj0hcm5EHtnJgZL0vWoz+AAU+dYcNcomOK0905owMuY
iypJrsSLO3Xi1TGKjTAR0M/n5t7vYU7ci3lKrtMNYWj60zL6vGiYK/NLMv+e77cy
a2nUkB7quioYVZ8Fs1K8ovre6Zhr9mLWYVbSaNZ7m8E6LT3GyLEzY+VYtm9be7C8
XE1NSMWbyyibH6sJmBcfpiaUf5iawGs3RxxMKY2rCiTHjVRhLEwCcRMymies+HPOX
0NVztpk4wgyMx2dGvolGvq3+ALZph/D2DQAA
} "6 of spades" 6 "black" 340x120
64#{
eJzt1ztSxDAMhgVDC7pChopz0FBxB05BnaOl2AOpOjXyI4llyY/dBGhQ4s1K/mLH
tvxn8vr+9QjBPrm8cHnj8sH1Dh5CfOb6y1Ms0uZwwjzHiz/4z7IsfPURF05wL178
4UP881w2pex+mlzPaMIu4+AwQ3EMxxl0XcYTpzCEBSNwNBmCvAEwGcjbXB0QTJyL
0pGMX2LtcIZCHihHMDFX0HCuYiglnXb6DA0wvj5jEDMmOSTyhx2k/ZmTE568vV6h
0856KcawEcYBEXb3Vz72I8zK/TO/ypj7vWAs3ZCMnc+CqeyLkrl5n17LnKUTNR0T
TEUPJWPrqmROWi+XXhGUOKGbGYzWpMDaDI8HCIOg4oRU/OTDImkuJlXleKID2M
nlXdjGZINWNoq71eMkol4uuD3reM19kYSZVp5OrGtHI1zkhbWyi9XJva4ktPE6gM
/7G27K/7urbAdm9dW/YHzaa50BZY721oS0qNpras6SOyCG2mZqHbdoqNMtDrbMux
40zXhpiRb6KRB6tvHjBX8/YNAAA=
} "7 of spades" 7 "black" 420x120
64#{
eJzNlzl1WwzAMxwWPFXYFPKaeg4WJO3AK5hwtAwfS1FXyslNsWbFUMpeiRHXl/F4s
W/98vX2cn4HtK/op+nv0z+gP8MT9czz+/ZK9tZl3mOfcpc3+WZYltqmHeAei3KQt
dcWfV3mqzh6niSdKZgMwe0M8hzGTEw5mAzhYUyXc4PnQOaM0JxAHQvqc5ZAMMG1
F4FgAKAP2nyQdSCDdl5ZK0EJrmKwiK4PbAYdTDpeMSFUTAnkvCjgb841cNSLBzXq
1TGKeRgCtHXyZp0WZuWuYRTNS0bTvGQ0zQtG1bXgVM23jK75lvkHmv8Do2le5qxp
XqzhXvXatjxsxnpztuTvW0FOLI7Wx155d147nGnRdyzvVi1z3qE3zmjvdo/l+P2aw
XnaLGazhhRmtYS7fWPNYHq5DzSe3tIqy+76ax/VtaKB5uLxWbWue38sMzRdmqPmV
setFQ82jiZ96reOYZtI648nZNBfj+SbyfFv9AGTB+m/2DQAA

```

```

} "8 of spades" 8 "black" 500x120
64#{
eJzNlZ9WwzAMxgWPFXYFPCbOwCLEHTgFc46WoQf6Jlbjv7EtK5ZpC8Wp60r5JbWl
z8rL6/vXt4X26fQL62+uf7h+Rw/Bv7rZp6fY27aGD61rHPzhfmzb5kbvseFD1sbB
H97lvp75rbp2vyxWaliMyli6nEFYw5hxUzYqY3E7psGjwecMqpBkEFS7lfdMRiCL
H+EaZoTThSGi3mjJjKCDzmiYqBUjGD9ikETXGzqDCcafrxhJkiYZY0uyBmXOyZjI
V/hTJV8d17QZxhJ0HTZrn2UEre7cPsFmtiIjaZUxolYZI2q1ZQ602jD/QKtnMJJW
+ZwlrbiYFnkWo2NyOTGVwZl4uYELanycCRMFids7pknnbzJoAnweQ6kIpFGMTwgt
cm2S4pxTFKuJmK891YhdynurjPOoGsNFORzW3pnazpP7fapuzNSfqTo2Uw8P2zn1
94AJ9X7MoA6pxgzisZoj+OSNMKo/SA/XYR3zXdMhuPu2ekZ51B/qGTnMQz3vN6rC
zPwMrirZPedaq+fLDvVMvtXY3zK8rgsMFMlf4x0kMjPvRDPvVt855Lq+9g0AAA==
} "9 of spades" 9 "black" 580x120
64#{
eJzNlztWxDAMRQ2HFrsFHCrWQUPFHlgFdZaWYhb0KlRjXxJLVmzNwJkZJ05G9p34
o2c5ef/8eXypfYf8FvJHYF8hp7inVD6H+tNLzjzN6XTznG/xCD+WZQn3WOLT6bzP
t3jEonB51Y9q0uM0+VHCREPGu78zue9dBs7RkCHckGE4qQxc/QSnMq5+ZjYkg+Rz
bkgmulgaYg6RdCAN7ousFVKMsxgU0bXGmIHKgDGxvmKI8qqgykApWbvpCbl+N3zq
eeOvMp7ir9Si9Be2ySON2WeG+bBhwCYm/AWgEcPGXjdVC8nCrNw5TJ4zIDGkMkhz
T/DZCSpTmihX0e992L54kS+AvuYFo2ueM3eg+QuYInNpKJpvjUGMahglRjXMYboR
Y+nzeOyGObT44pra+C89m9aOZQ2a1rIlJphiiyVG7YO+MB6yfo+ZJoYXJsX7PgNW
qDRVM8re1DDKHrf3x+VdUdsrVwZlc9X2XDb2o717ZeDvsfPIo+xqHrTo7LHm01uZ
19/ZJNOLURvTiVEbo7yLtsxRujojRa4wkCJvMg61nbF8Elm+rX4BEapi6fYNAAA=
} "10 of spades" 10 "black" 20x140
64#{
eJzNlZ+OEzEUxh+IxvKyvsKKinPQUHEHTkGdi7i1UuwV3EbTbEG/V3kVetIK833P
9mTstNiVFgmcTDKZ+fzn+2d78unLj/di7RuOjzg+4/iK4428s+sH3P9+W4+xHewt
h0P94gsnDw8P+OaVYm8ppX7xxUv4+DBLXbs3d3fluaZ34VmmYOsZ5f2/wBR5gt3/
iLmShrBlupoml5yLMcVYNJRgmd0wyhMXK+NC8fmsSVNN4kSiQObkQ6hVsJjQtaKp
ttAYBvrMmIkkm7WVKVub7SbOPFqWtmBpWLTelVEqmF/lnNPQxia0YB0HZURDC48
rn6dbe6mdkarjm59nxkOE+r1sMs8Kaw2nZlRXRkpLT4Dg3gqDFTfxmoMPLzI11+A
LOZKi3MoU750QQTJL34tPLJhOS+1PVgzldlFsnZu3T/BNPg+i7joZNds1JXlx2m
F0b1WPZ01ELUGYtLkgEiFkFjrytJnJDrInHV4HgcGUZYUoZn6PYOKbmsywlx32M6
8R1hCybIyCyEqHP0x6OnZPDzWIKWUCf103LKJ5qT8zSWXxapOqCOMbME/DiWpxA7
B7oMt3JAVvLELBQizS2zk020rV+4RCGpQsitr0Lhsq9CraGL00nHQdtqq9cIhJJM
9phBuUcZfmUjTtoZ3vJozVehUQfxpUHwvah68WbRFOctDeI9xfxE/NDBc6Xami5m
PzjGssdGfll+bDQ98GmKswnl7jwmFw0amYVCMji2yBxnxt7nllLkZGGXKYZMouSe
UxPKc04zq0FaSkNByYmBDjpnqzArfgv1mAsIobOrlWpFS6FRJ3qaeq54TCXmgynO
nLnSZw50osyl4YSzxfUos/ijlHmeseI7bh7jflfIbRYErnEzw0VCNjpsdhiVDSMV
mRilrYGrHfA7pSGzToEJNYulz1Uz7zK2O+I8co/LFwztC7ou3LaMtx14ZX7d4od3
2X5wv1iWvgGsixy3jcpwVSQjbYdZmbrQVkv6h7Xd6qRoTl10NPK1MsDw03EFuld
xrZV09GrjG3P1Z7HvzSdfC8+Qa4w9YnBQib9caMOnee0x7ky7Q11ZGqcz4VhMmVj
c2daPcdSpnzp6hfmQsQEcXEd4Jwv7q60pz6s4anNglkuGPilfOIdk6rQWGMARj9D
bpg/tv+R6bPytcxz7UXMS/4Tves/1W9aPkPU9g0AAA==
} "jack of spades" 11 "black" 100x140
64#{
eJzNlZlzy3DgQhXtdTlAou6+gcrTn2GQj32FP4VhHQnqlgFdAOoVgFeyBELmKibHv
NTg0CXA1CjYwR9RQMG9e/7JB/fH1+yfx4xv033H+ifMvnL/JR19/xuf/f07n+Xj2
H3l+7m984eL19RXvXGn+I631N764hf9fRqnp+PD01B4d9UkfMk3+B0YAPGCqR/ia
0fbLMv9RBj0ym1qNjcdQa1XpyyNTqVdyCVWVqcPCxPhyKWCaQKkzhxyqpxQXebYU
H246xlqou61kSlbtNfBaodPaT4aqQlvZuB6kM3pktliLgJEgmpzpFjam9oTUGIPB
mZ2hsYFB8GFRfBlMLfns857YbKltTM7n2HcmWHXGLDq+dsG4E7Iq/RmZWsnY4itX
DKKtvCuDJXjC4NW/AmyqF9xBivmV5HH9+NzGeoktkpliJkiG/Gz9E0xKjCI5bjrt
Wt14V8QQ+VBFcQwMmsKC2QYR8k4i+fuXijFbC2bQSLGFB+choEJ0KRLQGCRCrG7
TycmyApE8koIOjAVbyOTVWORqKshrx5atCgnJnZfU250KdLTK4YYmhdWtIc2Md7Q
lrItsiZUi9yWmfGOziiGJYYVb+mCqWYMGdbk9gJ3dGAQF1sDq1UgBKZYHRn2Ukgs
uYQVDEyNouJxUUZXUdgs1kadiCplyrD3ZIXHppNOKbHsa8EMMrNOYd60I+xCB8t2
PGYd7yo9vTyEE8N76fxiYQcGt+DZFjt70tGTzwwiXuvsfyMVZdYJViTULY05IV2z
jrg1xi4SOJG3nht1xE09KGw3bLRuzDqrC+ZzJK6DHv1NuoE91UotiLQejjx2uQP
Pjai3qvezozahm3aMbkaGz9JDIz4SXznoEQrOWt5ybGcysQWmpOj18w1bNA0Wfs
y4KBeI5LY+AY4DCosFZzlGYtDIxk7UMFhbCFiFg9M4Etk6ETfY6nv9fk08eRyR19
XhHbc/eCThv6Odd9WmpzI9ZmBk5gFMCj1frOfWA4pmlrEZ8wGUNRtx14Z3zcUwfl
yslo+0Z7Z/q2wc+5j7aaVtt3mDvTb0qYCT0dMNXu09UVQ9ewZbT9fj4y8Kf1zbau
F0zfVnNutTPononp2305MxxQ7b6Tn/PD1Cy8z4PFqBPDq41B8BiKcTOMx1pIZ9Q3
1FTKZuxYr9qZxgcsDziX+5POyWf1By20Zwuo/H0HbqfY04MnrLpyF5zr1e4MhGSF
LTK1TQyv8cRXoYM7Sif+6Y9318eJefP4BRmvzNtMu4f4FvPweBfzvnv+J3vO/1b/O
39P79g0AAA==
} "queen of spades" 12 "black" 180x140
64#{
eJyTVzuS1DAQbsGslYrtK2wRcQ4SiU7AKYjnCE5dE3AFpVNKNuBAHREi3mtZXkv2
4F1AXtuz9pVxRz9qat59+flefHzD+RHnZ5xfcb6Rd/78gvc/HurZj4v/yeVsbzzw
4enpCXc+Kf4npdQbDz7C5cNItRtvHx/L2bBHPcUU+XeMiIn+B4xH4Axjeo7xwJ5h
7FU8d9KgWz28W15HI9etX36VxAFI4jff8semAsYkDMP7nL3QbQ/FrmDEA+053ZiFR

```

```

VTlQ9aMu9KtfLsGVeynyKkcYhavFMBZGLZWqw9C6EGM1PACYDLYob8CQbbC1lVYL
s7q6E4xfX4+BwoYxu4OBPqualUDmSzs9YuAhxGTNV/nlsPXdqKdUW9ryNcTH3JY6
ka310+XCohDEGMKqHGJUETWpW+LnA8wEoinbJDJptygHGCFR8oBIihIXzRlmb1GI
BKS Ee4pxXz9CY3iXRMKUJtxm2fHMMMZxOc+44Yg3HXmCC5qzRGBACKK046ExYMAD
YRhyvfUYjCZaJPoBwh4Tc6qiWfbgy3Tv2mEiZFBQRE1YoRo4GHKPSZYXDAb8I08c
9CjjQedpKlWeUQ+nMJ8nzkie+UAPJxK+7GHxjLqe0XefdZGw/WTyMGXzwMMo54WH
eQdVkJEHmXJb0HWLEV6J9TmFywwcbBFDHhSUDTxBSL/aiqw37XnCVRAhVbN3jYEn
3NzbZ81rj9rkYhZ23bjEkHgGdbTlUZaaCxRimIaGwkImT0o+e5h3DUxbz6vqea4N
YFBTB3oYuFpjCOCU817PUqGeNmJqG9/qmVjmIYZrzjfOC4Nfw7y4TR6WNF813ji/
FJHvMURHfH5dc/J61DDyqIXJX80+46vokQfOsKoCW8IiesfDlaDlXVub2WHAhOpB
c1WfPTS2x4ApedNE3ap599tjADKSShUqgm1HmLI0XmWHZf5XjMmiWUptz/6lHsN2
31brdTGA1Q3G1wltq4hD3FbZYNafylejZdkpdzD+oerRv8D4snqC8eVZ22rtkkle
yi4+W4xvRHqeumNo+6Y1hj2mlo+smxF/Xg4wy26GpS5tRmwa6mLdCbBD4kapdjkB
MfVbrFXfcm3KQeq2zOuw1L2d79yqlGemTUbDNAGN1GPKD3vIlotGcm8QcwJ5KY+e
ES1+nWA8hv8BcyLmpZiX/CZ6yW+r3/c0VV/2DQAA
} "king of spades" 13 "black" 260x140
64#{
eJztLzEOAieQRdHYkKzDFYiV57Cx8g6ewpoj005tKCw5BAfYbLayxZmhUpMB+xl4
y4b9gc3r5nJ7HQ3XAzkjV+SO7MyB9wN+f0LjswJPE0JbaOBLsglX2qk8TaltouFb
+Dh9H/VTe+9rrzbvuplqX0lchQG3WcggYCgzxyVJcAYmK8DnxLXMApEYE9hZgDMZ
b5WgDGQLAwv/ZUmrQFE/6kf9qB/1o37Uj/prp+pH/fzlZ6QHgehlRnqikd7qDVAb
l+X2DQAA
} "card back side" 0 "none" -200x-200
]

```

Next, I wrote a little GUI app to test that all the cards display appropriately. It builds a GUI block by reading, decompressing, and appending the data in the card block above, using image widgets to display each decompressed card. That GUI block is then viewed with the typical "view layout" code. Note that the card data block above is imported in the beginning of the script, with the "do" function:

```

REBOL []

do %cards.r

; Start creating a GUI layout block by setting the size, background
; color (dark green), etc.:

gui: [size 670x510 backdrop 0.150.0 across ]

; The following foreach loop cycles through the imported cards block,
; and adds only the image data and coordinate info to the GUI block to
; be displayed. Notice that the foreach loop cycles through the card
; block in groups of 5 ITEMS AT A TIME. It reads each card's graphic
; data, text label, number value, color, and coordinate position, each
; time through the loop. The variable words card, label, num, color,
; and pos are assigned to each item:

foreach [card label num color pos] cards [

; Notice that only the cards' graphic data and position information are
; used in the GUI layout. The label, num, and color variables are not
; used, but they are included in the foreach loop above as placeholders
; for each group of 5 data values in the card data block. Notice the
; use of the "compose" function to insert the graphic and coordinate
; data, by reference, directly into the gui block (if you print out the
; created gui block, you'll see a huge mass of data):

append gui compose [
    at (pos) image load to-binary decompress (card)
]

]

view layout gui

```

The code above provides a fundamental way to reuse card images to create all types of games. Adding the "feel movestyle" code presented earlier in this tutorial allows us to click and drag the cards around the GUI. Here I'll make some changes to the code because I want the cards to move using "snap-to" positioning, as if they're placed on a grid and can only jump from one grid position to the next (as opposed to floating freely

across the screen with each click-drag):

```
REBOL []

do %cards.r

; The following function enables the pieces to slide around the
; screen. The coordinates are rounded to multiples of 80 and 20
; pixels to enable snap-to positioning (the horizontal width and
; vertical height distance between each card's origin). The
; additional 20 pixels accounts for the default border around the
; overall GUI:

movestyle: [
  engage: func [face action event] [
    if action = 'down [
      face/data: event/offset
      remove find face/parent-face/pane face
      append face/parent-face/pane face
    ]
    if find [over away] action [
      unrounded-pos: (face/offset + event/offset - face/data)
      snap-to-x: (round/to first unrounded-pos 80) + 20
      snap-to-y: (round/to second unrounded-pos 20) + 20
      face/offset: to-pair rejoin [snap-to-x "x" snap-to-y]
    ]
    show face
  ]
]

; Here's a revised version of the previous GUI block. The only
; difference is that it uses the snap-to positioning definition
; above ("movestyle"):

gui: [size 670x510 backdrop 0.150.0 across ]
foreach [card label num color pos] cards [
  append gui compose [
    at (pos) image load to-binary decompress (card) feel movestyle
  ]
]

view layout gui
```

That code is really starting to look and act like a card game. You can pick up any card, move it around the screen, and it automatically lines up and snaps over any other card on the screen. To create a different layout for other card games, all that would need to change is the initial positions of the cards, and the number of pixels rounded in the snap-to code. So, steps 1 and 2 in the program outline are done. To complete step 3, I simply added the following code to append some graphic lines to the GUI block. It draws the lines on screen using box widgets that are 2 pixels wide, to represent spaces where free cards and ascending stacks of cards should be placed during game play:

```
box-pos: 18x398
loop 4 [
  append gui compose [
    at (box-pos) box green 72x2
    at (box-pos) box green 2x97
    at (box-pos + 320x0) box white 72x2
    at (box-pos + 320x0) box white 2x97
  ]
  box-pos: box-pos + 80x0
]
```

Next, I need to lay out the cards in random order. My thought process to accomplish this is to load the card data block and then select random cards from the pile and swap their coordinate positions. I'll use a foreach loop to run through the deck several times (52 cards, times 3 = 156):

```

random/seed now
loop 156 [
    pos1: pick cards rnd1: (random 52) * 5
    pos2: pick cards rnd2: (random 52) * 5
    poke cards rnd1 pos2
    poke cards rnd2 pos1
]

```

That works to lay out the cards randomly, but there's a bug. The loop in the existing GUI code which places cards on screen runs through the cards in the order in which they appear in our initial card.r data block. Now that their positions are out of order, they are no longer layered correctly on screen into ordered visual columns (their "z-order" overlapping pattern is a mess). To fix that, I created several functions. The first function simply collects and returns a list of the positions of each card on screen:

```

positions: does [
    temp: copy []
    foreach item cards [if ((type? item) = pair!) [append temp item]]
    return sort temp
]

```

The following function uses a foreach loop to run through the block of coordinates returned by the function above. It then uses a nested foreach loop to run through each item on the screen (for each coordinate in the above list). Removing and appending each card image on the main window (append system/view/screen-face/pane/1/pane) changes the order they appear in the GUI, and overlaps them properly in the layout (this same remove-append technique was used earlier in the movestyle code). Notice that I include an if condition to make sure this function only runs on items above points 398 pixels from the top of the screen. That's because I don't want the piles of cards on the bottom of the screen to be disturbed:

```

arrange-cards: does [
    foreach position positions [
        foreach card system/view/screen-face/pane/1/pane [
            if (card/offset = position) and (position/2 < 398) [
                remove find system/view/screen-face/pane/1/pane card
                append system/view/screen-face/pane/1/pane card
            ]
        ]
    ]
    show system/view/screen-face/pane/1/pane
]

```

Because I want all this visual re-arranging to happen before the viewer sees the screen, I'll use "view/new" to create the GUI without immediately displaying it. Then I'll run the arrange-cards function, and finally display the layout with the "do-events" function:

```

view/new center-face layout gui
arrange-cards
do-events

```

As I play with the layout, there's another z-order overlapping issue that comes to my attention. Not so much a bug, but a display option that I want to enforce for the way this game should operate. In the existing movestyle code, when I click on a card, it is removed and appended back to the top of the screen pane, just as in the arrange-cards function. So, whenever I click on a card, it covers up any other card(s) with which it shares pixels (the other cards get hidden behind it). I don't want this to happen - the cards should stay aligned in nice neat columns. To fix this issue, I added the following code to the movestyle event loop, which arranges (overlaps) the cards again properly, every time the mouse button is released:

```

if action = 'up [
    arrange-cards
]

```



```
1
```

Now I can click on any card, pop it out of any column, view it, move it around, and then pop it right back into place, and the other cards will automatically overlap and align properly over/beneath it. Very nice!

As I play more with the code, I realize that there is currently no way to keep track of where cards are located, once they've been moved. That's a simple fix. I just added the following line to the 'down action block in the movestyle code. It stores the starting location of any card, when it is first clicked (before it's moved):

```
start-coord: face/offset
```

Then I added one line to the 'up action block above. This replaces the original coordinate in the card data block, with the new coordinate of the moved card, once the mouse button is released (after the card has been moved):

```
if action = 'up [
    ; Save the new position in the card block:
    replace cards start-coord face/offset
    arrange-cards
]
```

Now I can add code such as the following line, to obtain any desired information about any clicked card, just by searching for coordinates in the card data block. This example prints a card's name every time it's clicked, because every card's label is found 3 items before it's coordinate info, in the card data block:

```
print card-name: pick cards ((index? find cards start-coord) - 3)
```

Here's some code you could use to print out all the current information about every card in the deck:

```
btn "card positions" [
    foreach [card label num color pos] cards [
        print [label pos color num]
    ]
]
```

As I tested the existing code, I realized yet another necessity that will likely occur in any card game. I want to keep users from being able to move cards anywhere they want (outside the playing area, on top of other specified cards, etc.). To implement this feature, I'll just add some conditional evaluations to the above action block to check for certain situations, every time the mouse button is released. The code below checks to see if the offset of the face moved (face = card) is directly on top of (sharing the same coordinate) as any other card, or if it's outside the playing area. If so, the card is moved back to it's original position by setting it's offset to the start-coord variable defined above. It uses another conditional operation to make sure this is only done for cards on the playing field, and not on the stacks on the bottom of the screen (only on pixels 398 and higher):

```
if action = 'up [
    if any [
        (find cards face/offset) ; on top of any other cards
        (face/offset/2 < 20) ; outside the playing area
    ] [
        if (face/offset/2 < 398) [face/offset: start-coord]
    ]
    replace cards start-coord face/offset
    arrange-cards
]
```

At this point we have a generally usable framework for creating just about any card game. In fact, I can actually play a full game of Freecell at this point, if I don't mind the computer allowing me to execute illegal moves. I still need to implement various routines to disallow moves that are considered cheating in the rules of Freecell, but all the display and interaction code needed to move cards around the screen are in place. Here's the full code so far - go ahead and play a few games:

```

Rebol [title: "Playing Card Framework"]

do %cards.r

random/seed now
loop 156 [
    pos1: pick cards rnd1: (random 52) * 5
    pos2: pick cards rnd2: (random 52) * 5
    poke cards rnd1 pos2
    poke cards rnd2 pos1
]

movestyle: [
    engage: func [face action event] [
        if action = 'down [
            start-coord: face/offset
            face/data: event/offset
            remove find face/parent-face/pane face
            append face/parent-face/pane face
        ]
        if find [over away] action [
            unrounded-pos: (face/offset + event/offset - face/data)
            snap-to-x: (round/to first unrounded-pos 80) + 20
            snap-to-y: (round/to second unrounded-pos 20) + 20
            face/offset: (as-pair snap-to-x snap-to-y)
        ]
        if action = 'up [
            if any [
                (find cards face/offset)
                (face/offset/2 < 20)
            ] [
                if (face/offset/2 < 398) [face/offset: start-coord]
            ]
            replace cards start-coord face/offset
            arrange-cards
        ]
        show face
    ]
]

positions: does [
    temp: copy []
    foreach item cards [if ((type? item) = pair!) [append temp item]]
    return sort temp
]

arrange-cards: does [
    foreach position positions [
        foreach card system/view/screen-face/pane/1/pane [
            if (card/offset = position) and (position/2 < 398) [
                remove find system/view/screen-face/pane/1/pane card
                append system/view/screen-face/pane/1/pane card
            ]
        ]
    ]
    show system/view/screen-face/pane/1/pane
]

gui: [size 670x510 backdrop 0.150.0 across ]
foreach [card label num color pos] cards [
    append gui compose [
        at (pos) image load to-binary decompress (card) feel movestyle
    ]
]

```

```

box-pos: 18x398
loop 4 [
  append gui compose [
    at (box-pos) box green 72x2
    at (box-pos) box green 2x97
    at (box-pos + 320x0) box white 72x2
    at (box-pos + 320x0) box white 2x97
  ]
  box-pos: box-pos + 80x0
]

view/new center-face layout gui
arrange-cards
do-events

```

The program as it currently exists is a useful generic foundation for any card game. Now we need to begin working on the game logic for Freecell. Here are the main objectives, along with some pseudo-code ideas to help organize the thought process:

1. If a black card is placed below any red card at the bottom of any of the 8 "physical" piles of cards, or visa-versa (red-black), check to see if the moved card is 1 card lower in value than the card it touches. If not, don't allow the move. For example, a red 8 can be moved below a black 9, but moving a red 8 below a red 9 (not alternate red-black), or a black king beneath a red 3 (not consecutive), isn't allowed. You can make a disallowed card movement happen programmatically by resetting the face/offset of any disallowed card back to the value it held before being moved.
2. Only cards exposed at the bottom of pile, or one of the cards in a descendingly stacked group of alternate red-black cards at the bottom of a pile can be moved. For example, in a group of cards r7, b6, r5, b4, r3 at the bottom of a pile, you can move the red 7 and all the cards underneath it to another pile with an exposed black 8 at the bottom of the pile. You could also grab the black 4 and move it, along with the red 3 together, beneath a pile with a red 5 at the bottom. You could not, however, grab the red 7 from that pile without also moving the rest of the cards (b6, r5, b4, r3) beneath it.
3. The goal of the game is to move all cards from the originally displayed 8 piles to 4 new "goal" piles that are initially empty. Upon completion, each pile must contain only cards of a unique suit (clubs, diamonds, hearts, or spades) and the face values must ascend from ace to king consecutively. Disallow any card movements that don't allow for that arrangement.
4. There are 4 additional spaces, or "free cells" (the name of the game), that can be used to temporarily hold and move cards around between piles. They are useful in moving cards when there are no positions within the initial piles or in the goal piles that allow a card to be moved according to the previous rules. Only single exposed cards (no covered cards or piles) can be moved to a free cell.

Most of the conditional operations in the rest of the program will occur in the 'up action block of the movestyle code, because they need to occur when the user drops a card somewhere. To complete step 1 above we need to check columns for alternating red-black patterns. Then we need to check the ordinal pattern to make sure it goes from high to low in order. That's no so hard to do, because we have all the necessary information attached to each card in our original card data block. I added the following code to the 'up action block of the movestyle code, to determine which cards are in the same column as a moved card:

```

column-coords: copy []

; The loop below checks every coordinate in the card data block. If
; the horizontal position is the same as the card being put down,
; append that coordinate to the "column-coords" block:
foreach item cards [
  if ((type? item) = pair!) [
    if item/1 = face/offset/1 [
      append column-coords item
    ]
  ]
]

column: copy []

; Go through the coordinates collected above, find the name of the
; card at each coordinate, and add each name to the "columns" block:
foreach item (sort copy column-coords) [

```

```

    append column (pick cards ((index? find cards item) - 3))
]

print column

```

Fantastic! Now I can accomplish any computations that have to do with the way columns of cards are arranged :)

You can take the design from here and add as many features as you'd like!

10.19 Case 19 - Downloading Directories - A Server Spidering App

At one point, my notebook computer was disabled by a severe adware breakout. In an attempt to erase the troublesome files, the machine was rendered unable to boot to the operating system. I needed to copy a large number of recent data files that had not yet been backed up. Several options which didn't involve writing code were available to get this kind of job done. I could've removed the hard drive and put it in another machine, and then copied the files directly from one hard drive to another. I didn't have a hardware connector to install the laptop drive, and I didn't feel like taking the machine apart. I could've tried to reinstall the OS, and send the files across the network to be backed up on another computer. Without a system disk immediately available to restore the operating system, that wasn't convenient. I could've also potentially used a stand-alone local file transfer application (the "laplink" type), but without any serial/parallel ports, and without any OS access to provide USB support, I didn't have an application which made that option possible. Instead, I happened to have a Knoppix CD with which I was able to boot the laptop (<http://www.knoppix.org/> provides the complete Linux operating system on a single free CD - it doesn't require any hard drive or any installation to run). I booted the computer to Knoppix, it found my network, and I started the Aprelium web server (<http://aprelum.com/>) on the laptop. Tada! Using another computer on the network, I was able to access all my files through the web server. I had access to the files at that point, but since I had literally thousands of files in hundreds of directories on the laptop, I couldn't download each one manually. Instead, I wrote a little spidering application in REBOL that did the job instantly.

To create the program in natural language, I thought about the process I would go through, and how I would click through the directory structure if I were to manually download each file:

1. Create a new destination folder on the client computer to hold the transferred files.
2. Start in the current subdirectory on the laptop (starting with the folder that held my data), and download all the files in it to the new destination directory on the client computer.
3. Create subdirectories in the destination directory on the client to mirror each folder in the current directory on the laptop.
4. Switch into each of the subdirectories on the laptop and on the client, and repeat steps 2-4 for each subdirectory.

I came up with the outline above by actually sitting down at the computer, and running through the process that I wanted to automate. I just took note of how the thought process was organized. Next, I converted the above ideas to pseudo-code descriptions of how I would accomplish the above things using code constructs:

1. Get an initial remote URL from the user. Use the built-in "request-text" function to do that. Then, create a local folder to mirror it, with a nicely formed name (only allowable Windows file name characters). Use the "replace" function to swap out unusable characters, and the "make-dir" function to create a destination folder with the cleaned up characters.
2. Since the file and directory listings are made available via a web server, I'm going to have to parse a web page for file names to download. That's easy - the web server puts "/" characters at the end of all folder listings, so anything without a "/" at the end is a file. Create a block of file names, and use a "foreach" loop to go through the list of files, using read/binary and write/binary functions to download the actual files to the destination folder.
3. I'll also need to parse the web page for folder names to create. Use another "foreach" loop to work through the block of folder names, and the "make-dir" function to create local directories with those names.
4. Create a function that changes directories on both the local and remote machines. In order to work with the correct folders, I'll need to create some variables to keep track of the directory I started in, the current local folder I'm writing to, and the current remote folder I'm reading. As I switch in and out of each directory, I'll use rejoin and replace functions to concatenate and remove the current folder names to and from the local directory and remote URL variables. Because I need to create a function that repeats both previous steps and THIS CURRENT step in every subdirectory, I'll need to enclose all three of those steps into a function, and call that function from within itself. (You've seen this recursive process of creating a function that calls itself, in the "simple search" case study. It's needed here to do the same thing in every folder, drilling down until there are no more subfolders.

The first step was straightforward. Here's the code I came up with:

```

; Get initial remote URL and create a local folder to mirror
; it, with a nicely formed name (only allowable Windows file
; name characters).

    initial-pageurl: to-url request-text/default trim {
        http://192.168.1.4:8001/4/}
    initial-local-dir: copy initial-pageurl
    replace initial-local-dir "http://" ""
    replace/all initial-local-dir "/" "_"
    replace/all initial-local-dir "\" "_"
    replace/all initial-local-dir ":" "--"
    lrf: to-file rejoin [initial-local-dir "/"]
    if not exists? lrf [make-dir lrf]
    change-dir lrf
    clf: lrf

```

Since steps 2-4 above would all be enclosed in a single function, I decided I should assign some variable words that would refer to the folders I'd be accessing: "lrf" = local-root-folder, "clf" = current-local-folder and "crfu" = current-remote-folder-url.

To begin step 2, I wrote a bit of code to do the parsing of the file and folder names on the current web page directory listing. I combined the parsing requirements from step 2 and 3 above, and decided to use the variable words "files" and "folders" to label the blocks that would contain the parsed results. Here's the code that I came up with to read and parse the contents of the current page into the usable blocks. It looks for any link (anything beginning with href=" and ending with "), and appends it to the folders block if it contains a "/" character. Anything that doesn't contain the "/" character gets appended to the file block:

```

page-data: read crfu
files: copy []
folders: copy []
parse page-data [
    any [
        thru {href="} copy temp to {} (
            last-char: to-string last to-string temp
            either last-char = "/" [
                ; don't go upwards through the folder structure:
                if not temp = "../" [
                    append folders temp
                ]
            ] [
                append files temp
            ]
        )
    ] to end
]

```

To complete step 2, here's the foreach loop that I came up with to download all the files contained in the file block. It contains a replace/rejoin trick to make sure the filename gets concatenated to the current URL correctly (with no extra "/"s):

```

foreach file files [
    print rejoin ["Getting: " file]
    new-page: rejoin [crfu "/" file]
    replace new-page "///" "/"
    write/binary to-file file read/binary to-url new-page
]

```

I ran into some problems with certain links on the web page that weren't actually file or folder listings, or which didn't download properly. I used some conditional "if"s and "error? try" combinations to eliminate those problems. I wrote the errors to a text file, so that I could check them afterwards and download manually if necessary. Here's the revised version of the code above, with the error handling routines:

```

foreach file files [
  if not file = "http://www.aprelium.com" [
    ; The free aprilium server puts that link on all pages
    ; it serves. I didn't want to spider all the contents of
    ; their web page.
    print rejoin ["Getting: " file]
    new-page: rejoin [crfu "/" file]
    replace new-page "///" "/"
    if not exists? to-file file [
      either error? try [read/binary to-url new-page] [
        write/append %/c/errors.txt rejoin [
          "There was an error reading: " new-page
          newline]
      ] [
        if error? try [
          write/binary to-file file read/binary to-url new-page
        ] [
          write/append %/c/errors.txt rejoin [
            "error writing: " crfu newline]
          ]
      ]
    ]
  ]
]

```

I wanted to complete step 3, but realized that that's where the recursion pattern needed to occur - for each folder I copied, I wanted to look inside that folder and create any folders it contained, and then inside those folders, etc. So next, I defined a recursion pattern to change into the current local and remote folders, and to run the function in which all of steps 2-4 were contained. I decided to label the entire enclosing function "copy-current-dir" - it would be passed the parameters "lrf", "clf", and "crfu". That function contains the recurse function, which calls the encompassing copy-current-dir function, which itself contains the recurse function, etc. The effect of this recursion is that every subfolder of every folder is entered. Here's the recurse function:

```

recurse: func [folder-name] [
  change-dir to-file folder-name
  crfu: rejoin [crfu folder-name]
  clf: rejoin [clf folder-name]
  ; NOW HERE'S THE RECURSION - call the function in which
  ; this function is contained:
  copy-current-dir crfu clf lrf
  ; When done, go back up a folder on both the local and
  ; remote machines. The replace actions remove the current
  ; folder text from the end of the current folder strings.
  change-dir %..
  replace clf folder-name ""
  replace crfu folder-name ""
]

```

Finally, I completed steps 3 and 4 by creating local folders to mirror each directory in the current remote folder, and then called the recurse function to spider down through them. I used a foreach loop to work through each directory in the current subdirectory list. Because this loop contains the recurse function, which in turn runs the copy-current-dir, which in turn contains this loop, every subdirectory of every subdirectory is worked through, until the job is complete:

```

foreach folder-name folders [
  make-dir to-file folder-name
  recurse folder-name
]

```

I wrapped the parsing, looping/reading, and recursing sections into the copy-current-dir function so that they could be called recursively. Then I added some error handling routines as I played with the working code. I included a block of URLs to be avoided, and some code in the final foreach loop to check that those URLs weren't already downloaded (in case I had previously run the program on the same directory). Here's the final script:

```

REBOL [title: "Directory Downloader"]

avoid-urls: [
  "/4/Download/en_wikibooks_org/skins-1_5/common/&"
  "Download/groups_yahoo_com/group/Join%20This%20Group!/"
  "Download/pythonide_stani_be/ads/"
  "Nick%20Antonaccio/Desktop/programming/api/ewe/"
]

copy-current-dir: func [
{
  Download the files from the current remote directory
  to the current local directory and create local subfolders
  for each remote subfolder. Then recursively do the same
  thing inside each sub-folder.
}
  crfu ; current-remote-folder-url
  clf  ; current-local-folder
  lrf  ; local-root-folder
] [
  ; Check that the URL about to be parsed is not in the avoid
  ; list above. This provides a way to skip specified folders
  ; if needed:

  foreach avoid-url avoid-urls [
    if find crfu avoid-url [return "avoid"]
  ]

  ; First, parse the remote folder for file and folder names.
  ; Given the URL of a remote page, create 2 list variables.
  ; files: remote files to download (in current directory)
  ; folders: remote sub-directories to recurse through.
  ; There's an error check in case the page can't be read:

  if error? try [page-data: read crfu] [
    write/append %/c/errors.txt rejoin [
      "error reading (target read error): "
      crfu newline]
    return "index.html"
  ]

  ; if the web server finds an index.html file in the folder
  ; it will serve its contents, rather than displaying the
  ; directory structure. Then it'll try to spider the HTML
  ; page. The following will keep that error from occurring.
  ; NOTE: this error was more effectively stopped by
  ; editing the index page names in the Abyss web server:
  if not find page-data {Powered by <b><i>Abyss Web Server} [
    ; </i></b>
    write/append %/c/errors.txt rejoin [
      "error reading (.html read error): "
      crfu newline]
    return "index.html"
  ]

  files: copy []
  folders: copy []
  parse page-data [
    any [
      thru {href=} copy temp to {} (
        last-char: to-string last to-string temp
        either last-char = "/" [
          ; don't go upwards through the folder structure:
          if not temp = "../" [
            append folders temp
          ]
        ][
          append files temp
        ]
      )
    ] to end
  ]
]

```

```

; Next, download the files in the current remote folder
; to the current local folder:

foreach file files [
  if not file = "http://www.aprelium.com" [
    print rejoin ["Getting: " file]
    new-page: rejoin [crfu "/" file]
    replace new-page "///" "/"
    if not exists? to-file file [
      either error? try [read/binary to-url new-page][
        write/append %/c/errors.txt rejoin [
          "There was an error reading: " new-page
          newline]
      ] [
        if error? try [
          write/binary to-file file read/binary to-url new-page
        ][
          write/append %/c/errors.txt rejoin [
            "error writing: "
            crfu newline]
        ]
      ]
    ]
  ]
]

; Check to see if there are no more subfolders. If so,
; exit the copy-current-dir function

if folders = [] [return none]

; Define the recursion pattern. This changes into the
; current local folder, and runs the copy-current-dir
; function (the current function we are in), which itself
; contains the recurse function, which itself will call
; the copy-current-dir, etc. The effect of this recursion
; is that every subfolder of every folder is entered.
; This is what enables the spidering:

recurse: func [folder-name] [
  change-dir to-file folder-name
  crfu: rejoin [crfu
    folder-name]
  clf: rejoin [clf
    folder-name]
  copy-current-dir crfu clf lrf
  ; When done, go back up a folder on both the local
  ; and remote machines. The replace actions remove
  ; the current folder text from the end of the current
  ; folder strings.
  change-dir %..
  replace clf folder-name ""
  replace crfu folder-name ""
]

; Third, create local folders to mirror each directory in
; the current remote folder, and then spider down through
; them using the recurse function to download all the files
; and subdirectories included in each folder:

foreach folder-name folders [
  ; foreach avoid-url avoid-urls [
  ;   if not find folder-name avoid-url [
  ;     make-dir to-file folder-name
  ;     recurse folder-name
  ;   ]
  ; ]
]

; Now, get initial remote URL and create a local folder to
; mirror it, with a nicely formed name (only allowable Windows

```



```

; file name characters).

    initial-pageurl: to-url request-text/default trim {
        http://192.168.1.4:8001/4/}
    initial-local-dir: copy initial-pageurl
    replace initial-local-dir "http://" ""
    replace/all initial-local-dir "/" "_"
    replace/all initial-local-dir "\" "__"
    replace/all initial-local-dir ":" "---"
    lrf: to-file rejoin [initial-local-dir "/" ]
    if not exists? lrf [make-dir lrf]
    change-dir lrf
    clf: lrf

; Start the process by running the copy-current-dir function:

copy-current-dir initial-pageurl clf lrf

print "DONE" halt

```

10.20 Case 20 - Vegetable Gardening

My mother is a retired Microsoft Access developer who loves to garden in her spare time. She's collected a wide scope of knowledge about how certain plants survive better when planted next to each other, and she wanted to create a program to help organize that info. She wanted to create a standalone version that she could use on her home computer and give to friends. She also wanted to publish it to the web as a dynamic database. Additionally, she anticipated creating a version that could be carried into the garden on a pocket pc. I suggested using REBOL, because it could provide a solution for all her needs. She'd been working for several days with her development tools, and I told her I could get the whole thing done that same evening using REBOL. Here's the outline I created:

1. Create a database structure to hold the vegetable compatibility info and other related information.
2. Write a command line version of the script that allows users to display all the info for any selected vegetable (this could be run on any operating system that supports the command line version of REBOL, including pocket pc).
3. Create a CGI version of the above script that works on the web site.
4. Create a pretty GUI version to be used on the home PC.
5. Write a separate GUI to manage the administrative adding of data to the database.
6. Provide a way to update the data files on the web site.

To get things started, I used the listview data grid example from this tutorial to provide a front end for the vegetable data files. This provided a data structure that was suitable for the project, and it formed an instant solution to creating a GUI front end. Steps 1 and 5 were instantly completed (that database example is so useful - many thanks to Henrik Mikael Kristensen for creating the listview module!).

I created a few initial lines of data to work with. Here's the working database.db file that I created:

```

["basil" "" "tomato" "basil protects tomatoes." "" ""]
["beans" "onion" "cabbage carrot radish" "" "" ""]
["cabbage" "celery" "tomato" "" "" ""]
["carrot" "" "tomato"
    "Carrots strengthen the roots of tomatoes."
    "Carrots love tomatoes." ""]
["radish" "cabbage" "beans carrot tomato" "" "" ""]
["tomato" "cabbage" "basil carrot" "" "" ""]

```

Each block holds 6 pieces of information about each possible vegetable:

1. the name of the veggie
2. a list of other veggies that are compatible with the given veggie (those that do well when planted next to the given veggie).
3. a list of other veggies that are incompatible
4. 3 fields for general notes about the given veggie

I decided to add an "upload" button to the listview GUI to satisfy step #6 in my program outline. It made sense to add this functionality here, because the user workflow would generally involve adding/changing

data in the database (using the listview), and then updating the online database to match. Here's the upload code I came up with. It includes some error checking, so that the application doesn't crash if there's a problem with the Internet connection. I added a button to the listview GUI and put the above code in its action block. Here's the complete code I added to the listview:

```
btn "upload to web" [
  url: ftp://user:pass@website.com/public_html/path/
  if error? try [
    ; first, backup former data file:
    write rejoin [url "database_backup.db"] read rejoin [
      url "database.db"]
    write rejoin [url "database.db"] read %database.db
    alert "Update complete."
  ] [alert "Error - check your Internet connection."]
]
```

Next, I realized that adding and removing new vegetables to and from the database would require some special consideration. It ended up being the biggest part of this coding project. I could use the built-in abilities of the listview module to simply add a new vegetable to the database, but there was a problem with that. Every time a new vegetable is added to the database, it creates a list of compatibilities. Aside from simply adding a new block to the database with fields listing the compatibilities and incompatibilities, that new veggie needs to be added to the compatibility list of every other vegetable with which it's compatible. It also needs to be added to the incompatibility list of every vegetable with which it's not compatible. Editing those blocks manually would take a lot of work and introduce a greater likelihood for user errors, especially as the database grows larger. Instead, I decided to create a little script to do it automatically. Here's the pseudo code thought process for that script:

1. Create a list of existing vegetables. This can be done by reading the existing database, looping through each block, and picking out the first item in each block (the vegetable name).
2. Create a small new GUI to enter the new veggie info. It should include an input field for the new veggie name, 2 text-lists showing the possible compatible and incompatible veggies (read from the existing list of veggies in the database), and 3 note fields.
3. Use a foreach loop to run through the lists of compatible and incompatible veggies. Have the loop automatically add the new vegetable to the other veggies' respective compatibility lists.

I created the GUI code and put the foreach loop inside the action block of a button used to add the new veggie. Here's the code, which I saved as "add_veggie.r":

```
REBOL [title: "Add Veggie"]

; read the current database:
veggies: copy load %database.db
; get the list of veggies (the 1st item in each block):
veggie-list: copy []
foreach veggie veggies [append veggie-list veggie/1]

; create a GUI with the appropriate fields and text-lists:
view/new center-face add-gui: layout [
  across
  text "new vegetable:" 88x24 right new-veg: field
  return
  text "compatible:" 88x24 right
  new-compat: text-list data veggie-list
  return
  text "incompatible:" 88x24 right
  new-incompat: text-list data veggie-list
  return
  text "note 1:" 88x24 right new-note1: field
  return
  text "note 2:" 88x24 right new-note2: field
  return
  text "note 3:" 88x24 right new-note3: field
  return

  ; now add a button to run the foreach loops:

  tabs 273 tab btn "Done" [
    ; First, append the new veggie data block to
```

```

; the existing database block. Create the new
; block from the text typed into each field,
; and from the items picked in each of the
; lists above ("reduce" evaluates the listed
; items, rather than including the actual text.
; i.e., you want to add the text typed into the
; new-veg field, not the actual text
; "new-veg/text"). "append/only" appends the
; new block to the database as a block, rather
; than as a collection of single items:
append/only veggies new-block: reduce [
  new-veg/text
  ; "reform" creates a quoted string from the
  ; block of picked items in the text-lists:
  reform new-compatible/picked
  reform new-incompatible/picked
  new-note1/text
  new-note2/text new-note3/text
]
; Now loop through the compatibility list of the
; new veggie, and add the new veggie to the
; compatibility lists of all those other
; compatible veggies. I put a space in if there
; were already other veggies in the list:
foreach onecompat new-compatible/picked [
  foreach veggie veggies [
    if find veggie/1 onecompat [
      either veggie/2 = "" [spacer: ""] [
        spacer: " "]
      append veggie/2 rejoin [spacer
        new-veg/text]
    ]
  ]
]
; Now do the same thing for the incompatibility
; list:
foreach oneincompat new-incompatible/picked [
  foreach veggie veggies [
    if find veggie/1 oneincompat [
      either veggie/3 = "" [spacer: ""] [
        spacer: " "]
      append veggie/3 rejoin [spacer
        new-veg/text]
    ]
  ]
]
save %database.db veggies
; start the veggie data editor again when done:
launch %veggie_data_editor.r
unview add-gui
]
focus new-veg
do-events

```

Because the add_veggie.r script will always be run from the veggie_data_editor.r program, I added the following code to the action block for the "add veggie" button in the data editor. It launches the above add_veggie program, and closes the listview:

```
btn "add veggie" [launch %add_veggie.r quit]
```

When the user closes the add_veggie program, the "launch %veggie_data_editor.r" code at the end of the program relaunched the data editor. This handles flipping back and forth between the two screens. When the data editor is relaunched, all the new data is automatically updated and displayed, so I don't need to manually update any displayed info. After playing with the system, I realized before closing the data editor I'd better save the changes made to the database. So I adjusted the above code as follows:

```

btn "add veggie" [
  launch %add_veggie.r
  backup-file: to-file rejoin ["backup_" now/date]
  write backup-file read %database.db
  save %database.db theview/data
  quit
]

```

Next, I used the above code to create a similar "remove_veggie.r" program. Instead of building a GUI for it, I just added some code to the "remove veggie" button in the veggie data editor to save the name of the currently selected vegetable to a file (veggie2remove.r). I also copied the backup routine from the code above to make sure any changes in the listview are saved before going on:

```

btn "remove veggie" [
  if (to-string request-list "Are you sure?"
    [yes no]) = "yes" [
    ; get the veggie name from the currently selected
    ; row in the listview:
    first-veg: copy first theview/get-row
    theview/remove-row
    write %veggie2remove.r first-veg
    launch %remove_veggie.r
    backup-file: to-file rejoin ["backup_" now/date]
    write backup-file read %database.db
    save %database.db theview/data
    quit
  ]
]

```

The remove_veggie.r script just reads the vegetable name from the veggie2remove.r file created above, and runs through some foreach loops to delete that vegetable from the compatibility lists of the other veggies:

```

REBOL [title: "Remove Veggie"]

veggies: copy load %database.db
remove-veggie: read %veggie2remove.r

; remove the selected veggie from compatible lists (the second
; field in each block). This is done by replacing any
; occurrence of the remove-veggie with an empty string ("").
; That effectively erases every occurrence of the veggie:

foreach veggie veggies [
  replace veggie/2 remove-veggie ""
]

; do the same thing to the incompatible lists of all other
; veggies (field 3 in each block):

foreach veggie veggies [
  replace veggie/3 remove-veggie ""
]

save %database.db veggies
; start the veggie data editor again when done:
launch %veggie_data_editor.r

```

Now the listview data editor and all its helper scripts are complete. Because the listview is generally run from the GUI version of the main program ("veggie_gui.r" - not yet written), I added the following code to the existing listview close routine:

```
launch "veggie_gui.r"
```

When I design the main veggie_gui program, I'll add a button to launch the listview. When I close the listview, the above code will relaunch the GUI program to handle flipping back and forth between those two screens. Here's the final listview data grid code with all the described changes and additions:

```
REBOL [title: "Veggie Data Editor"]

evt-close: func [face event] [
  either event/type = 'close [
    inform layout [
      across
      btn "Save Changes" [
        ; when the save btn is clicked, a backup data
        ; file is automatically created:
        backup-file: to-file rejoin ["backup_" now/date]
        write backup-file read %database.db
        save %database.db theview/data
        launch "veggie_gui.r"
        quit
      ]
      btn "Lose Changes" [
        launch "veggie_gui.r"
        quit
      ]
      btn "CANCEL" [hide-popup]
    ] none ] [
    event
  ]
]
insert-event-func :evt-close

if not exists? %list-view.r [write %list-view.r read
  http://www.hmkdesign.dk/rebol/list-view/list-view.r
]
do %list-view.r

if not exists? %database.db [write %database.db {[][]}]
database: load %database.db

view center-face gui: layout [
  h3 {To enter data, double-click any row, and type directly
    into the listview. Click column headers to sort:}
  theview: list-view 775x200 with [
    data-columns: [Vegetable Yes No Note1 Note2
      Note3]
    data: copy database
    tri-state-sort: false
    editable?: true
  ]
  across
  btn "add veggie" [
    launch %add_veggie.r
    backup-file: to-file rejoin ["backup_" now/date]
    write backup-file read %database.db
    save %database.db theview/data
    quit
  ]
  btn "remove veggie" [
    if (to-string request-list "Are you sure?"
      [yes no]) = "yes" [
      first-veg: copy first theview/get-row
      theview/remove-row
      write %veggie2remove.r first-veg
      launch %remove_veggie.r
      backup-file: to-file rejoin ["backup_" now/date]
      write backup-file read %database.db
      save %database.db theview/data
    ]
  ]
]
```

```

        quit
    ]
]
btn "filter veggies" [
    filter-text: request-text/title trim {
        Filter Text (leave blank to refresh all data):}
    theview/filter-string: filter-text
    theview/update
]
btn "upload to web" [
    uurl: ftp://user:pass@website.com/public_html/path/
    if error? try [
        ; first, backup former data file:
        write rejoin [
            uurl "database_backup.db"] read rejoin [
            uurl "database.db"]
        write rejoin [uurl "database.db"] read %database.db
        alert "Update complete."
    ] [alert "Error - check your Internet connection."]
]
]
]

```

Next, I created a command line version of the program. The "Looping Through Data" example provided earlier in this tutorial served as a perfect model. I just changed some of the variable labels and loaded the data from the existing database.db file. Here's the code:

```

REBOL [title: "Veggies"]

veggies: load %database.db

a-line: copy [] loop 65 [append a-line "-"]
a-line: trim to-string a-line

print-all: does [
    foreach veggie veggies [
        print a-line
        print rejoin ["Veggie:   " veggie/1]
        print a-line
        print rejoin ["Matches:  " veggie/3]
        print rejoin ["No-nos:   " veggie/2]
        print rejoin ["Note 1:   " veggie/4]
        print rejoin ["Note 2:   " veggie/5]
        print rejoin ["Note 3:   " veggie/6]
        print newline
    ]
]

forever [
    prin "^(1B)[J"
    print "Here are the current foods in the database:^/"
    print a-line
    foreach veggie veggies [prin rejoin [veggie/1 "  "]]
    print "" print a-line
    print "Type a vegetable name below.^/"
    print "Type 'all' for a complete database listing."
    print "Press [Enter] to quit.^/"
    answer: ask {What food would you like info about? }
    print newline
    switch/default answer [
        "all"      [print-all]
        ""         [ask "^^/Goodbye!  Press [Enter] to end." quit]
    ][
        found: false
        foreach veggie veggies [
            if find veggie/1 answer [
                print a-line
                print rejoin ["Veggie:   " veggie/1]
                print a-line
                print rejoin ["Matches:  " veggie/3]
                print rejoin ["No-nos:   " veggie/2]
            ]
        ]
    ]
]

```

```

        print rejoin ["Note 1:  " veggie/4]
        print rejoin ["Note 2:  " veggie/5]
        print rejoin ["Note 3:  " veggie/6]
        print newline
        found: true
    ]
]
if found <> true [
    print "That vegetable is not in the database!^/"
]
]
ask "Press [ENTER] to continue"
]
halt

```

That was easy! Just compare it to the original example - it's virtually identical. Again, that generalized example was presented in this tutorial to provide a model for use in many varied situations. Using it, I didn't even need to write any pseudo code.

Now I extended the above command line example to create a CGI application. To get started, I used the final CGI example provided earlier in this tutorial as a model. To it, I added the code that I'd created for the command line example above. The only real changes I needed to make were some additional HTML formatting tags, required make the page display properly in a browser (mostly newline "< B R >"s). Again, just an amalgam of several existing examples. No pseudo code required - I just had to think about how to arrange the existing command line code to fit into the general CGI outline. Here's the code:

```

#! /home/path/public_html/rebol/rebol -cs
REBOL [title: "Veggies"]
print "content-type: text/html^/"
print [<HTML><HEAD><TITLE>"Veggies"</TITLE></HEAD><BODY>]

veggies: load %database.db

a-line: copy [] loop 65 [append a-line "-"]
a-line: trim to-string a-line

print-all: does [
    foreach veggie veggies [
        print a-line
        print [<BR>]
        print rejoin ["Veggie:  " veggie/1]
        print [<BR>]
        print a-line
        print [<BR>]
        print rejoin ["Matches:  " veggie/3]
        print [<BR>]
        print rejoin ["No-nos:  " veggie/2]
        print [<BR>]
        print rejoin ["Note 1:  " veggie/4]
        print [<BR>]
        print rejoin ["Note 2:  " veggie/5]
        print [<BR>]
        print rejoin ["Note 3:  " veggie/6]
        print [<BR>]
    ]
]

print "Here are the current foods in the database:^/"
print [<BR>]
print a-line
print [<BR><strong>]
foreach veggie veggies [prin rejoin [veggie/1 "  "]]
print ""
print [</strong><BR>]
print a-line
print [<BR>]

submitted: decode-cgi system/options/cgi/query-string
if submitted/2 <> none [

```

```

switch/default submitted/2 [
  "all"      [print-all]
][
  found: false
  foreach veggie veggies [
    if find veggie/1 submitted/2 [
      print a-line
      print [<BR>]
      print rejoin ["Veggie:   " veggie/1]
      print [<BR>]
      print a-line
      print [<BR>]
      print rejoin ["Matches:  " veggie/3]
      print [<BR>]
      print rejoin ["No-nos:   " veggie/2]
      print [<BR>]
      print rejoin ["Note 1:   " veggie/4]
      print [<BR>]
      print rejoin ["Note 2:   " veggie/5]
      print [<BR>]
      print rejoin ["Note 3:   " veggie/6]
      found: true
    ]
  ]
  if found <> true [
    print [<BR>]
    print "That vegetable is not in the database!"
    print [<BR>]
  ]
]

print [<FORM ACTION="http://website.com/rebol/veggie.cgi">]
print [<BR><HR><BR>"Enter a veggie you'd like info about:"<BR>]
print ["Veggie: "<INPUT TYPE="TEXT" NAME="username" SIZE="25">]
print [<INPUT TYPE="SUBMIT" NAME="Submit" VALUE="Submit">]
print [</FORM>]
print [</BODY></HTML>]

```

I didn't like the way the CGI required the user to type in the name of a listed vegetable. Instead, I got rid of the list printout, and added the list to a selectable dropdown box. Here's the final cgi example with the HTML dropdown box:

```

#! /home/path/public_html/rebol/rebol -cs
REBOL [title: "Veggies"]
print "content-type: text/html^/"
print [<HTML><HEAD><TITLE>"Veggies"</TITLE></HEAD><BODY>]

veggies: load %database.db

a-line: copy [] loop 65 [append a-line "-"]
a-line: trim to-string a-line

print-all: does [
  foreach veggie veggies [
    print a-line
    print [<BR>]
    print rejoin ["Veggie:   " veggie/1]
    print [<BR>]
    print a-line
    print [<BR>]
    print rejoin ["Matches:  " veggie/3]
    print [<BR>]
    print rejoin ["No-nos:   " veggie/2]
    print [<BR>]
    print rejoin ["Note 1:   " veggie/4]
    print [<BR>]
    print rejoin ["Note 2:   " veggie/5]
    print [<BR>]
    print rejoin ["Note 3:   " veggie/6]
  ]
]

```



```

        print [<BR>]
    ]
]

submitted: decode-cgi system/options/cgi/query-string
if submitted/2 <> none [
    switch/default submitted/2 [
        "all"      [print-all]
    ][
        found: false
        foreach veggie veggies [
            if find veggie/1 submitted/2 [
                print a-line
                print [<BR>]
                print rejoin ["Veggie:   " veggie/1]
                print [<BR>]
                print a-line
                print [<BR>]
                print rejoin ["Matches:  " veggie/3]
                print [<BR>]
                print rejoin ["No-nos:   " veggie/2]
                print [<BR>]
                print rejoin ["Note 1:   " veggie/4]
                print [<BR>]
                print rejoin ["Note 2:   " veggie/5]
                print [<BR>]
                print rejoin ["Note 3:   " veggie/6]
                found: true
            ]
        ]
        if found <> true [
            print [<BR>]
            print "That vegetable is not in the database!"
            print [<BR>]
        ]
    ]

    print [<FORM ACTION="http://website.com/rebol/veggie.cgi">]
    print [<BR>"Please select a veggie you'd like info about:"<BR>]
    print ["Veggie: "<select NAME="username"><option>"all"
    foreach veggie veggies [prin rejoin ["<option>" veggie/1]]
    print [</option>]
    print [<INPUT TYPE="SUBMIT" NAME="Submit" VALUE="Submit">]
    print [</FORM>]
    print [</BODY></HTML>]

```

The final part of the outline that I needed to address was the GUI display version of the program. I needed to create this from scratch, so I came up with an outline and some pseudo code to organize my thoughts:

1. Display the complete list of vegetables in the database (build the list using a foreach loop similar to the ones used in the command line program, and display that block in a text list widget).
2. Display the info for any vegetable selected from the text list widget (when an item is selected, collect all the info for the selected vegetable and display it, nicely formatted, in a separate text area widget).
3. Add a button to run the listview editor created earlier.

First I borrowed some code from the add_veggies.r example to create a list of all the veggies in the database. It uses a foreach loop to cycle through each block in the database, and creates a list of the first item in each block (the name of each vegetable). Then it sorts the list alphabetically. This should be run before the GUI is displayed:

```

load-data: does [
    veggies: copy load %database.db
    veggie-list: copy []
    foreach veggie veggies [append veggie-list veggie/1]
    veggie-list: sort veggie-list
]

```

I decided to use a text-list widget to display the block of vegetable names. To display the info for each vegetable, I used a simple text area display. Here's the REBOL layout code to do that:

```
list-veggies: text-list 200x400 data veggie-list
display: area "" 300x400
```

To that text-list widget's action block I added some code to display the info about the selected vegetable (it gets evaluated whenever the user selects an item from the list):

```
; First, build a block of text with all the info about the
; selected vegetable, nicely formatted with newlines and
; capitalized section headings:

current-info: []
foreach veggie veggies [
  if find veggie/1 value [
    current-info: rejoin [
      "COMPATIBLE:      " veggie/3 newline newline
      "INCOMPATIBLE:    " veggie/2 newline newline
      "NOTE 1:          " veggie/4 newline newline
      "NOTE 2:          " veggie/5 newline newline
      "NOTE 3:          " veggie/6
    ]
  ]
]

; Now display and update that text in the text area widget:

display/text: current-info
show display show list-veggies
```

Finally, add a button to run the listview data editor:

```
btn "Edit Tables" [do %veggie_data_editor.r]
```

That's basically it. Here's the final version:

```
REBOL [title: "Veggie Matches"]

load-data: does [
  veggies: copy load %database.db
  veggie-list: copy []
  foreach veggie veggies [append veggie-list veggie/1]
  veggie-list: sort veggie-list
]

load-data

view display-gui: layout [
  h2 "Click a veggie name to display matches and other info:"
  across
  list-veggies: text-list 200x400 data veggie-list [
    current-info: []
    foreach veggie veggies [
      if find veggie/1 value [
        current-info: rejoin [
          "COMPATIBLE:      " veggie/3 newline newline
          "INCOMPATIBLE:    " veggie/2 newline newline
          "NOTE 1:          " veggie/4 newline newline
          "NOTE 2:          " veggie/5 newline newline
          "NOTE 3:          " veggie/6
        ]
      ]
    ]
  ]
]
```

```

        ]
    ]
    display/text: current-info
    show display show list-veggies
]
display: area "" 300x400 wrap
return
btn "Edit Tables" [
    do %veggie_data_editor.r
    ; launch "veggie_data_editor.r"
    ; load-data
    ; show list-veggies
    ; show display
]
]
]

```

There are 5 complete local script files that make up the completed veggie program: veggie_data_editor.r, add_veggie.r, remove_veggie.r, veggie_command_line.r, veggie_gui.r. In general, the main desktop applications are started by running the veggie_gui.r script. The veggie_data_editor.r can also be run by itself (remember that it runs the veggie_gui.r program when it closes). In order for the veggie_data_editor to work, the listview.r file needs to be included in the same directory. The created database.db should also be kept in the same directory. I packed all those files into an executable using XpackerX, and sent it to my Mom. The 6th script file, veggie.cgi, got uploaded to the web site. The database.db file was also uploaded manually, but my Mom prefers using the upload button in the veggie_data_editor to update the database on the web site. The veggie2remove.r and database backup files are created automatically when the program is used - they're found in the same folder as the script files.

10.21 Case 21 - An Additional Teacher Automation Project

Now that the group scheduling system is complete, I want to automate our daily checkout routine. Every day, our teachers are paid directly by their students. In turn, they pay us a rental/referral fee for room and resource use. That's our primary source of income. At the end of the day, teachers add up all the students they've seen, and pay a given fee for each completed half hour session. Some students prepay their teachers, and the teachers in turn prepay us so that they don't have to manage rental fees for prepaid appointments in the future.

It takes a lot of time to manually figure daily fees, and the process is error prone when calculated by hand. I want to automate the payment calculations based on the existing online schedule information, and I want to create an integrated record keeping system to more easily track prepayments. Teachers need to keep track of missed/rescheduled appointment payments, so that students are given proper credit for rolled over appointment times. Also, in addition to daily local lessons, some of our instructors teach online lessons, for which we're paid directly by students. For those lessons, we deduct room rent from the total paid to us by the teachers. We need a solution to easily manage and track all those daily calculations for all the teachers. The objective is to keep a running total of how much money is due by each teacher every night, and how much money is owed to the teachers by students. To create a software outline, I thought about what I do manually every day to calculate the checkout fees for a single person. This thought process will serve as an outline to design the automated record keeping system:

1. Each day at checkout time, the total number of lessons for a teacher is added up.
2. The teacher owes us a given amount for lessons that occurred in the local studio that day.
3. We owe the teacher a given deduction for each lesson they performed online that day.
4. Any lessons which had previously been prepaid by the teacher are deducted from the total owed us.
5. The teacher prepays us for any future lessons which were prepaid by students that day, and records are updated to track the current prepaid amounts.
6. Occasionally, other deductions are made from the amount owed us (sometimes the teacher provides a complimentary lesson for various reasons, or we provide complimentary time to the teacher/student, etc.). Those amounts are deducted from the total owed us.

Based on the guidelines above, here's how I organized my thoughts about what the automated multiuser system should do:

1. The multiuser requirements of the application are similar to those of the scheduling app from the previous section. I can use the code from the scheduling app to provide a current teacher list, simple password protection, loading/saving/backup of required data files for the selected teacher, etc.
2. In order to perform daily calculations for a single instructor, I want to provide a dynamically created list of daily students and I want to retrieve current prepay records for the given teacher. That data will be stored on the web site, any changes will be backed up locally and on the web site. I'll need to come up with a data structure to store the prepay records. All other information (random deductions, complimentary lessons, etc.) will be provided by the user on a daily basis. The regular daily student

- list and prepay records can be downloaded and displayed in text lists. The other random deductions and additions can be entered manually in text input fields, and displayed in text lists.
3. By default, each teacher owes a given amount for each of the students selected from the daily list (number_of_students X half_hour_rate). Add to that any fees for additional students not in the daily list (rescheduled lessons, occasional additional appointments, etc.)
 4. For each online lesson, subtract 1 student from the total number of students taught that day, and deduct the appropriate amount from the grand total due.
 5. Subtract any previous prepayments from the grand total due. Whenever that happens, make an adjustment to the teacher's record of prepayments.

To satisfy step 1, I'll use the scheduling app from the previous section of this case study. As it stands, that code is capable of selecting a specified teacher directory on the website and downloading any required data files (current daily students, prepay records, individual teacher fee rates, etc.).

The main work of creating the application is in step 2. The required calculations are in steps 3-5. Here's a more structured outline, with pseudo code, to guide the writing of the program code:

1. Read a current list of daily students from the selected teacher's schedule.txt file on the web server. Store that info in a block and display it in a GUI text-list widget. Store a list of local students selected from the above widget in a separate block.
2. Display today's students again in a second text-list widget, so that the user can select those who took lessons online. Store that selected data in another block.
3. Provide a text input field to allow the addition of any students not in the daily list. Display a text-list widget to contain students entered into the text field. Update the text-list display any time a student is added. In order to remove incorrect entries from this list, the action block of the text-list should contain code to delete any students selected by the user.
4. Provide another text field and text-list for the entry of deductions, with the same layout and remove code.
5. Provide a button to manage prepayment entries and calculations. To handle that whole process, create a separate script - to be outlined below.
6. Provide a "Calculate Total Fees" button. The action block of this button should add and subtract the total number of items in all of the text-lists, according to the rules defined in steps 3-5 of the overall program outlined above. Provide an HTML summary, which the teacher can print out and submit every day.

Here's the code I came up with to do all that:

```
; The "url" variable below comes from the multiuser framework
; borrowed from the scheduler app:
students: read/lines rejoin [url "/schedule.txt"]
; Initialize some other variables:
other-additions: [] other-deductions: [] prepay: []
pay-for: copy [] online: copy []

view center-face layout [
  h2 "Local Students:"
  ; "face/picked" refers to the currently selected items in
  ; the text-list (use [Ctrl] + mouse click to select multiple
  ; items, and assign that to the variable "pay-for":
  text-list data copy students [pay-for: copy face/picked]
  h2 "Other Additions:"
  field [
    ; add the entered info to the text-list, and update
    ; the display:
    append other-additions copy face/text
    show other-additions-list
  ]
  other-additions-list: text-list 200x100 data other-additions [
    ; remove any entry when selected by the user, and update
    ; the display
    remove-each item other-additions [item = value]
    show other-additions-list
  ]
  at 250x20
  h2 "Online Students:"
  text-list data copy students [online: face/picked]
  h2 "Other Deductions:"
  field [
    append other-deductions copy face/text
    show other-deductions-list
  ]
]
```

```

]
other-deductions-list: text-list 200x100 data other-deductions [
    remove-each item other-deductions [item = value]
    show other-deductions-list
]
at 480x20
h2 "Prepaid Lessons:"
prepay-list: text-list data prepay [
    remove-each item prepay [item = value]
    show prepay-list
]
; I still need to create the prepay.r program:
btn 200x30 "Calculate Prepaid Lessons" [
    save %prepay.txt load rejoin [url "/prepay.txt"]
    do %prepay.r
]
at 480x320
btn 200x100 font-size 17 "Calculate Total Fees" [
    total-students: (
        (length? pay-for) - (length? online) +
        (length? other-additions) - (length? other-deductions) -
        (length? prepay)
    )
    ; I want to create an HTML output for this section:
    alert rejoin ["Total: " to-string total-students]
]
]

```

Now all that's left to create is a separate program to manage prepayment info. Here's an outline describing my intentions:

1. Create and upload a "prepay.txt" data file to store prepayment information for each teacher. It should contain a separate block for each student who prepays, with fields for the student name, a nested block for the amounts and dates of each prepayment, and a nested block for dates of each lesson attended and the amount deducted from the prepayment for each lesson.
2. Create a GUI with a text-list displaying each student who has prepaid. Loop through the prepay.txt data to get the student names (the first item in each block). Whenever a name is selected by the user, display the student name, prepay dates and amounts, and lesson dates in separate text lists. Display the total prepay balance for the selected student in a text field.
3. There should be an "Add" button and some text fields for entering new prepayments. There should be fields for student name, amount, and date of prepay. If an existing student is selected from the list, those fields should be populated automatically with today's date, and with the name of the existing student. The action block of the add button should append the information to appropriate blocks in the prepay.txt file.
4. There should be an "Apply Today" button to select prepayment(s) to be applied to today's balance. Store the names of the selected students in a block, save that block to be read and used in the main application, and add the date information to the appropriate blocks in the prepay.txt file.
5. There should be a "Done" button on the list-view GUI to allow the information to be changed and saved. Whenever a student is selected from the list, their prepayment records should be displayed in an editable list-view (import the listview module and use the database example from earlier in this tutorial as a model). There should be fields for prepay amounts and dates, and lesson dates and amounts.
6. When the main prepay application is closed, the prepay.txt file should be backed up and saved to the web site.

For step 1, here's an example of the block structure I came up with to store data in the prepay.txt file:

```

[
    ; name:
    "John Smith"

    ; prepayment amounts and dates:
    [ [$100 4-April-2006] [$100 5-May-06] ]

    ; dates of lessons:
    [
        [$20 4-April-06] [$20 11-April-06] [$20 18-April-06]
        [$20 25-April-06] [$20 5-May-06]
    ]
]

```

```

]

[
  "Paul Brown"

  [ [$100 4-April-2006] ]

  [
    [$20 4-April-06] [$20 25-April-06]
  ]
]

[
  "Bill Thompson"

  [ [$200 22-March-2006] ]

  [
    [$20 22-March-06] [$20 29-March-06] [$20 5-April-06]
    [$20 12-April-06] [$20 19-April-06] [$20 26-April-06]
    [$20 3-May-06]
  ]
]

[
  ; name:
  "John Smith"

  ; prepayment amounts and dates:
  [ "$100 4-April-2006" "$100 5-May-06" ]

  ; dates of lessons:
  [
    "$20 4-April-06" "$20 11-April-06" "$20 18-April-06"
    "$20 25-April-06" "$20 5-May-06"
  ]
]

[
  "Paul Brown"

  [ "$100 4-April-2006" ]

  [
    "$20 4-April-06" "$20 25-April-06"
  ]
]

[
  "Bill Thompson"

  [ "$200 22-March-2006" ]

  [
    "$20 22-March-06" "$20 29-March-06" "$20 5-April-06"
    "$20 12-April-06" "$20 19-April-06" "$20 26-April-06"
    "$20 3-May-06"
  ]
]

```

Here's the code I created to fulfill my outline requirements:

```

REBOL [title: "Prepayment Calculator"]

prepays: load rejoin [url "/prepay.txt"]
names: copy []
prepay-history: []
lesson-history: []

```

```

display-todays-bal: does [
    ; calculate and display the current balance for the
    ; selected student:
    todays-balance: $0
    foreach payment prepay-history [
        todays-balance: todays-balance + (
            first (to-block payment)
        )
    ]
    foreach lesson-event lesson-history [
        todays-balance: todays-balance - (
            first (to-block lesson-event)
        )
    ]
    ; update the display of today's balance for the
    ; selected student :
    today-bal/text: to-string todays-balance
    show today-bal
]
foreach block prepay [append names first block]
view center-face gui: layout [
    across
    text bold "New Prepayment:"
    text right "Name:" new-name: field
    text right "Date:" new-date: field 125 to-string now/date
    text right "Amount:" new-amount: field 75 "$"
    btn "Add" [
        create-new-block: true
        foreach block prepay [
            if (first block) = new-name/text [
                create-new-block: false
                append (second block) to-string rejoin [
                    new-amount/text " " new-date/text
                ]
            ]
        ]
        if create-new-block = true [
            new-prepay: copy []
            append new-prepay to-string new-name/text
            append new-prepay to-string rejoin [
                new-amount/text " " new-date/text
            ]
            append prepay new-prepay
            names: copy []
            foreach block prepay [append names first block]
        ]
        display-todays-bal
        show existing show pre-his show les-his show today-bal
    ]
    return
    text bold underline "Edit Data Manually" [
        view/new center-face layout [
            new-prepay: area 500x300 mold prepay
            btn "Save Changes" [
                prepay: copy new-prepay/text
                unview
            ]
        ]
        names: copy []
        foreach block prepay [append names first block]
        show gui
        show existing show pre-his show les-his show today-bal
    ]
    return
    text "Existing Prepayments:" pad 75
    text "Prepayment History:" pad 85
    text "Lesson History:" pad 100
    text "Balance:"
    return
    existing: text-list data names [
        ; When a name is selected from this text list, update
        ; the other fields on the screen:

```

```

        new-name/text: value
        show new-name
        foreach block prepay [
            if (first block) = value [
                ; update the other text lists to show the
                ; selected student's prepay and lesson history:
                prepay-history: pre-his/data: second block
                show pre-his
                lesson-history: les-his/data: third block
                show les-his
            ]
        ]
        display-todays-bal
        ; get the list of selected students
        prepaid-today: copy face/picked
    ]
    pre-his: text-list data prepay-history
    les-his: text-list data lesson-history
    today-bal: field 85
    return
    btn "Apply Selected Prepayments Today" [
        save %prepaid.txt prepaid-today

        unview
    ]
]

```

In the original scheduling outline, I replace all references in the code to "schedule.txt" with "prepay.txt":

```

REBOL [title: "Payment Calculator"]

error-message: does [
    ans: request {Internet connection is not available.
        Would you like to see one of the recent local backups?}
    either ans = true [
        editor to-file request-file quit
    ] [
        quit
    ]
]

if error? try [
    teacherlist: load ftp://user:pass@website.com/teacherlist.txt
] [
    error-message
]
teachers: copy []
foreach teacher teacherlist [append teachers first teacher]
view center-face layout [
    text-list data teachers [folder: value unview]
]

pass: request-pass/only
correct: false
foreach teacher teacherlist [
    if ((first teacher) = folder) and (pass = (second teacher)) [
        correct: true
    ]
]
if correct = false [alert "Incorrect password." quit]

url: rejoin [http://website.com/teacher/ folder]
ftp-url: rejoin [
    ftp://user:pass@website.com/public_html/teacher/ folder
]

if error? try [
    write %prepay.txt read rejoin [url "/prepay.txt"]
] [

```



```

        error-message
    ]

    ; backup (before changes are made):
    cur-time: to-string replace/all to-string now/time ":" "-"
    ; local:
    write to-file rejoin [
        folder "-prepay_" now/date "_" cur-time ".txt"
    ] read %prepay.txt
    ; online:
    if error? try [
        write rejoin [
            ftp-url "/" now/date "_" cur-time
        ] read %prepay.txt
    ][
        error-message
    ]

    editor %prepay.txt

    ; backup again (after changes are made):
    cur-time: to-string replace/all to-string now/time ":" "-"
    write to-file rejoin [
        folder "-prepay_" now/date "_" cur-time ".txt"
    ] read %prepay.txt
    if error? try [
        write rejoin [
            ftp-url "/" now/date "_" cur-time
        ] read %prepay.txt
    ][
        alert "Internet connection not available while backing up."
    ]

    ; save to web site:
    if error? try [
        write rejoin [ftp-url "/prepay.txt"] read %prepay.txt
    ][
        alert {Internet connection not available while updating web
            site. Your schedule has NOT been saved online.}
        quit
    ]
    browse url

```

I also need to replace the line "editor %prepay.txt" with new code that does the work of calculating daily fees and tracking prepayments.

Now that the program is complete, please notice how the outline developed. It took several steps. First, I thought through my daily manual calculations. Then I thought about how that could be encapsulated into a program, and I created a basic outline about what I wanted the program to do. When it came to writing pseudo code outlines to create the actual program, the whole process was made easier by having organized outlines of everything I needed to accomplish. To write the program, I first defined some required data (provided by the multiuser scheduler app), then conceived a user interface, and then performed calculations based on existing data and user input. Following that type of outline structure (define required data, define a UI, perform calculations) tends to be an organized and successful approach in many cases.

It should be noted that I'm not concerned about data security in this app. It is important that the teachers are able to access this info conveniently from any location. It's also important that local backups are made. The automatic backing up of files provides a historical audit trail of transactions and changes to the records, which is an important concern since this program manages income. It's not a problem for these records to become publicly accessible, so I'm using ftp and a public web site to store and retrieve the data. Writing secure applications, however, is an important requirement in most situations involving financial transactions. You should be aware that data security is a primary concern if you intend to do any programming related to typical business transactions, but that topic is beyond the scope of this tutorial. This case study was provided as an additional example of how coding thought can be organized to take you from conceptual phases to a final product. This particular code should not be emulated, however, for projects requiring secure data transactions.

11. Other Scripts

This section of the tutorial contains various random scripts that you might find useful.

The first script provides a quick visual reference of all REBOL's built in colors:

```
REBOL [Title: "Quick Color Guide"]

echo %colors.txt ? tuple! echo off
lines: read/lines %colors.txt
colors: copy []
gui: copy [across space 1x1]
count: 0
foreach line at lines 2 [
    if error? try [append colors to-word first parse line none][]
]
foreach color colors [
    append gui [style box box [alert to-string face/color]]
    append gui reduce ['box 110x25 color to-string color]
    count: count + 1
    if count = 5 [append gui 'return count: 0]
]
view center-face layout gui
```

This next quick script demonstrates how to convert REBOL color tuples to HTML colors, and visa-versa:

```
to-binary request-color
to-tuple #{00CD00}
view layout [box to-tuple #{5C743D}] ; view an HTML color on screen!
```

This is a quick way to review the console history of your current REBOL session:

```
foreach line reverse copy system/console/history [print line]
```

Here's how to remove the last 2 items from a block:

```
x: ["asdf" "qwer" "zxcv" "uiop" "hjkl" "vbnm"]
y: head clear skip tail x -2
probe y
```

The script below demonstrates how to use email ports to read one message at a time from a pop server. Be sure to set your email user account settings before running this one (that's explained earlier in this tutorial):

```
for i 1 length? pp: open pop://user@site.com 1 compose [
    ask find pp/(i) "Subject:"
]
```

Here are a few examples of how the "request" function can be used:

```
; Two different formats include passing either a string or a block.
; If you pass a string, the default buttons will be "yes", "no", and
; "cancel". If you pass a block, you can specify the text on the
; buttons:

request "Could this be useful?"
request ["Just some information."]
request ["Here are 2 buttons with altered text:" "Probably" "Not Really"]
request ["3 buttons with altered text:" "Probably" "Not Really" "Dunno"]
```

```

; "Request" only returns 'true 'false or 'none. For an example like the
; one below, the user response can be converted to strings using a switch
; structure:

answer: form request ["Complex example:" "choice 1" "choice 2" "choice 3"]
switch/default answer [
    "true" [the-answer: "choice 1"]
    "false" [the-answer: "choice 2"]
    "none" [the-answer: "choice 3"]
] []
print the-answer

; The "/type" modifier changes the icon displayed:

request/type ["Here's a better icon for information display."] 'info
request/type ["Altered title and button text go in a block:" "Good"] 'info
request/ok/type "This example is the EXACT same thing as 'alert'." 'alert
request/ok/type "Here's alert with a different icon." 'info
request/ok/type "Here's another icon!" 'stop
halt

```

Here is a home made resizable requestor that I use when I don't want the "REBOL - " title bar to appear. It has a default timeout (set to 6 seconds in the example below), and can also be closed with a button click. This is particularly suitable for full screen commercial kiosk types of applications):

```

sz: 5
view layout [
    btn "Click here to see a requestor with a 6 second timeout" [
        view/new/options center-face information: layout [
            text font-size (8 * sz) "Here's a message!" rate :00:06 feel [
                engage: func [f a e] [
                    if a = 'time [unview/only information]
                ]
            ]
            box 1x1 ; spacer
            btn as-pair (12 * sz) (8 * sz) font-size (5 * sz) "Ok" [
                unview/only information
            ]
        ][no-title]
    ]
]

```

To edit the source of any mezzanine function, use the following format:

```

editor mold :request
editor mold :inform

```

I actually use the following script to check the source files of this tutorial, to make sure that none of the lines of code are wider than 79 characters:

```

REBOL [title: "Find Long Lines"]

doc: read/lines to-file request-file
the-text: {}
foreach line doc [
    if ((find/part line " " 4)) [
        if ((length? line) > 78) [
            print line
            the-text: rejoin [the-text newline line]
        ]
    ]
]

```

```
editor the-text
```

Here's a duo of scripts that I use to sync my computer's clock to the time and date on my web server. The Windows API time setting function is based on Ladislav Mecir's [Nist Clock Sync Script](#):

```
REBOL []

dif: 7:00 ; difference between web server and your local time zone
date: (to-date trim read http://site.com/time.cgi) + dif

lib: load/library %kernel32.dll

set-clock: make routine! [
    systemtime [struct! []]
    return: [integer!]
] lib "SetSystemTime"

current: make struct! [
    wYear [short]
    wMonth [short]
    wDayOfWeek [short]
    wDay [short]
    wHour [short]
    wMinute [short]
    wSecond [short]
    wMilliseconds [short]
] reduce [
    date/year
    date/month
    date/weekday
    date/day
    date/time/hour
    date/time/minute
    to-integer date/time/second
    0
]

either ((set-clock current) = 1) [
    ask rejoin ["Time has been set to: " now "^/^/[Enter]... "]
] [
    ask "Error setting time. Please check your Internet connection."
]

free lib
```

Here's the CGI script that the above code needs (to obtain the date and time from the web server). Put it at the URL which is read when the 'date' word above is set:

```
#!/home/path/public_html/rebol/rebol -cs
REBOL [title: "time"]
print "content-type: text/html^/"
print now
```

Here's Ladislav's (better) version of the above Windows function. The script at <http://www.fm.tul.cz/~ladislav/rebol/nistclock.r> can set both Linux *and* Windows system clocks (the "set-system-time-lin" does the same thing in Linux):

```
the-date: to-date trim read http://site.com/time.cgi

set-system-time-win: func [
    {set system time in Windows; return True in case of success}
    [catch]
    date
    /local set-system-time
```

```

] [
  unless value? 'kernel32 [kernel32: load/library %kernel32.dll]
  set-system-time: make routine! [
    systemtime [struct! []]
    return: [int]
  ] kernel32 "SetSystemTime"
  date: date - date/zone
  date/zone: 0:0
  0 <> set-system-time make struct! [
    wYear [short]
    wMonth [short]
    wDayOfWeek [short]
    wDay [short]
    wHour [short]
    wMinute [short]
    wSecond [short]
    wMilliseconds [short]
  ] reduce [
    date/year
    date/month
    date/weekday
    date/day
    date/time/hour
    date/time/minute
    to integer! date/time/second
    0
  ]
]

set-system-time-win the-date

```

I use the following script to upload screen shots of my desktop directly to my web site (in the version I use, I put the text of the included script directly into my code):

```

REBOL []

do http://www.rebol.org/download-a-script.r?script-name=capture-screen.r

the-image: ftp://user:pass@site.com/path/current.png

; You can also save to your local hard drive if you want:
; the-image: %current.png

view center-face gui: layout [
  button 150 "Upload Screen Shot" [
    unview gui
    wait .2
    save/png the-image capture-screen
    view center-face gui
  ]
]

```

The following script demonstrates how to add and remove widgets from a GUI layout:

```

view gui: layout [
  button1: button
  button2: button "remove" [
    remove find gui/pane button1
    show gui
  ]
  button3: button "add" [
    append gui/pane button1
    show gui
  ]
]

```

Here's a way to get a unique string identifier from the current time (useful for MCI buffer names and other situations when you need to generate absolutely unique identifier strings without any odd characters):

```
replace/all replace/all replace/all form now "/" "" ":" "x" "-" "q" "." ""
; precise version (w/ milliseconds):

replace/all replace/all replace/all replace/all form now/precise trim {
/} "" ":" "x" "-" "q" "." ""
```

This script creates an image, saves it to the hard drive, and then opens it in mspaint.exe:

```
save/bmp %test.bmp to-image layout [box]
call/show join "mspaint.exe " to-local-file join what-dir %test.bmp
```

This script demonstrates how to use the AutoIT DLL to control the madplay.exe mp3 player:

```
REBOL []

if not exists? %AutoItDLL.dll [
  write/binary %AutoItDLL.dll
  read/binary http://musiclessonz.com/rebol_tutorial/AutoItDLL.dll
  write/binary %madplay.exe
  read/binary http://musiclessonz.com/rebol_tutorial/madplay.exe
]

lib: load/library %AutoItDLL.dll

move-mouse: make routine! [
  return: [integer!] x [integer!] y [integer!] z [integer!]
] lib "AUTOIT_MouseMove"

send-keys: make routine! [
  return: [integer!] keys [string!]
] lib "AUTOIT_Send"

winactivate: make routine! [
  return: [integer!] wintitle [string!] wintext [string!]
] lib "AUTOIT_WinActivate"

set-option: make routine! [
  return: [integer!] option [string!] param [integer!]
] lib "AUTOIT_SetTitleMatchMode"

set-option "WinTitleMatchMode" 2
call/show {madplay.exe -v *.mp3}

view layout [
  across
  btn "forward" [
    winactivate "\reb" ""
    send-keys "f"
  ]
  btn "back"[
    winactivate "\reb" ""
    send-keys "b"
  ]
  btn "volume up" [
    winactivate "\reb" ""
    send-keys "+"
  ]
  btn "volume-down"[
    winactivate "\reb" ""
    send-keys "-"
  ]
]
```

```

    btn "pause" [
        winactivate "\reb" ""
        send-keys "p"
    ]
    btn "quit" [
        winactivate "\reb" ""
        send-keys "q"
        quit
    ]
]

```

Here's a quick and dirty way to print out help for all built in functions. Also includes a complete list of VID styles ("view layout" GUI widgets), VID layout words, and VID facets (standard properties available for all the VID styles). Give it a minute to run...

```

REBOL [title: "Quick Manual"]

print "This will take a minute..." wait 2
echo %words.txt what echo off ; "echo" saves console activity to a file
echo %help.txt
foreach line read/lines %words.txt [
    word: first to-block line
    print "
    print rejoin ["word: " uppercase to-string word] print "
    do compose [help (to-word word)]
]
echo off
x: read %help.txt
write %help.txt "VID STYLES (GUI WIDGETS):^/^/"
foreach i extract svv/vid-styles 2 [write/append %help.txt join i newline]
write/append %help.txt "^/^/LAYOUT WORDS:^/^/"
foreach i svv/vid-words [write/append %help.txt join i newline]
b: copy []
foreach i svv/facet-words [
    if (not function? :i) [append b join to-string i "^/"]
]
write/append %help.txt rejoin [
    "^/^/STYLE FACETS (ATTRIBUTES):^/^/" b "^/^/SPECIAL STYLE FACETS:^/^/"
]
y: copy ""
foreach i (extract svv/vid-styles 2) [
    z: select svv/vid-styles i
    ; additional facets are held in a "words" block:
    if z/words [
        append y join i ": "
        foreach q z/words [if not (function? :q) [append y join q " "]]
        append y newline
    ]
]
write/append %help.txt rejoin [
    y "^/^/CORE FUNCTIONS:^/^/" at x 4
]
editor %help.txt

```

Here's an email program that demonstrates how to set all your email account settings:

```

m: system/schemes/default q: system/schemes/pop
view layout [ style f field
    u: f "username" p: f "password" s: f "smtp.address" o: f "pop.address"
    btn bold "Save Server Settings" [
        m/user: u/text m/pass: p/text m/host: s/text q/host: o/text
    ] tab
    e: f "user@website.com" j: f "Subject" t: area
    btn bold "SEND" [
        send/subject to-email e/text t/text j/text alert "Sent"
    ] tab
]

```

```

y: f "your.email@somesite.com"
btn bold "READ" [foreach i read to-url join "pop://" y/text [ask i]]
]

```

This example keeps a real time word count of text in an area widget. Changing the rate will reduce system resource usage, but also slow the response time (a rate of 3-4 updates per second should be suitable for most cases):

```

view layout [
  i: info rate 0 feel [
    engage: func [f a e] [
      if a = 'time [
        l: length? parse m/text none
        i/text: join "Wordcount: " l
        show i
      ]
    ]
  ]
  m: area
]

```

Here are two versions of the VOIP program given earlier in the section about ports. These are likely the most compact VOIP programs you'll find anywhere. The first features port error handling, automatic localhost testing (just press [ENTER] to use localhost as the IP address), hands-free operation, and automatic minimum volume testing (squench - data not sent unless a given volume is detected, to save bandwidth). It can be pasted directly into the REBOL console, or saved to a file and run. The second is barebones (user sees errors when the connection is broken, must be saved to a file and run, etc.) but it does work. The file sizes of these scripts are 693 bytes and 554 bytes!!:

```

REBOL[do[write %w{REBOL[if error? try[p: first wait open/binary/no-wait
tcp://:8][quit]wait 0 s: open sound:// forever[if error? try[m: find v:
copy wait p #"]][quit]i: to-integer to-string copy/part v m while[i >
length? remove/part v next m][append v p]insert s load to-binary
decompress v]}launch %w lib: load/library %winmm.dll x: make routine![c[
string!]return:[logic!]]lib"mciExecute"if(i: ask"Connect to IP: ")=""[i:
"localhost"]if error? try[p: open/binary/no-wait rejoin[tcp:// i":8"]][
quit]x"open new type waveaudio alias b"forever[x"record b"wait 2 x
"save b r"x"delete b from 0"insert v: compress to-string read/binary
%r join l: length? v #""if l > 4000[insert p v]]]

REBOL[write %w{REBOL[if error? try[p: first wait open/binary/no-wait
tcp://:8][quit]wait 0 s: open sound:// forever[m: find v: copy wait p #""
i: to-integer to-string copy/part v m while[i > length? remove/part v next
m][append v p]insert s load v]}launch %w lib: load/library %winmm.dll x:
make routine![c[string!]return:[logic!]]lib"mciExecute"i: ask"IP: "p:
open/binary/no-wait rejoin[tcp:// i":8"]x"open new type waveaudio alias b"
forever[x"record b"wait 2 x"save b r"x"delete b from 0"insert v:
read/binary %r join length? v #""insert p v]

```

Here's an instant message example that allows users to upload their connection info (username, WAN IP, LAN IP, and network port), to a text file on an FTP server. Then others can simply click on their user name in a drop down box (choice button), to connect:

```

REBOL [title: "Instant Messenger"]

servers: ftp://username:password@yoursite.com/public_html/im.txt ; EDIT
flash "Retrieving server list..."
if error? try [server-info: reverse read/lines servers] [
  alert "Internet connection not available."
  server-info: copy []
]
unview
name-list: copy []
foreach server server-info [append name-list first to-block server]

```



```

insert head name-list "Connect to a Server:"

view center-face layout [
  across
  choice 280 data name-list [
    mode: request [ {
      SELECT MODE: By default, this program is able to connect to
      a server running on any other computer in your Local Area
      Network. Choosing "LAN" mode connects you to a server's local
      IP address. If you select "Internet" Mode, you will connect
      to the server's WAN IP address (typically the address of
      the user's _router_). In order for Internet mode to work
      correctly, the selected port number chosen by the server user
      must be exposed on the Internet, or be forwarded from their
      router to the IP address of the computer running the server
      program.
    } "LAN" "Internet"]
    foreach server server-info [
      server-block: parse server " "
      if ((form first server-block) = form value) [
        b/text: server-block/1 show b
        either mode = false [
          remote-ip: server-block/2
        ] [
          remote-ip: server-block/3
        ]
        j/text: server-block/4
        show j
        p: open/lines rejoin [tcp:// remote-ip j/text]
        z: 1
        focus g
        break
      ]
    ]
  ]
  text "OR run as server:"
  b: field 106 "Username"
  text "Port: "
  j: field 55 ":8080"
  q: button 84 "Start Server" [
    parse read http://guitarz.org/ip.cgi [
      thru <title> copy p to </title>
    ]
    parse p [thru "Your IP Address is: " copy wan-ip to end]
    write/append servers rejoin [
      b/text " " ; username
      wan-ip " " ; wan ip
      read join dns:// read dns:// " " ; local ip
      j/text "^/" ; port
    ]
    alert {
      Server is running. Connections from clients running on
      your Local Area Network should work without any problems.
      If you want to accept connections from the Internet, and
      you are connected by a router, then the port number you've
      selected must be forwarded from your router to the IP
      address of this computer (see portforward.com for more
      information about forwarding ports).
    }
    focus g
    p: first wait open/lines (join tcp:// j/text)
    z: 1
  ]
  return
  r: area 700x400 rate 4 feel [
    engage: func [f a e][
      if a = 'time and value? 'z [
        if error? try [x: first wait p] [quit]
        r/text: rejoin ["--> " x "^/" r/text]
        show r
      ]
    ]
  ]
]

```

```

]
return
g: field 400 "Type message here, then press [ENTER]" [
  r/text: rejoin ["<-- " value "^/" r/text]
  show r
  insert p value
  focus face
]
tabs 618
tab
button "Save Chat Text" [editor r/text]
return
]

```

The following function converts number values to their spoken English equivalent (i.e., 23482194 = "Twenty Three million, Four Hundred Eighty Two thousand, One Hundred Ninety Four"). This code was created for a check writing application, but is perhaps useful elsewhere. The algorithm was partially derived from the article at <http://www.blackwasp.co.uk/NumberToWords.aspx> (C# code):

```

REBOL [title: "Number Verbalize"]

verbalize: func [a-number] [
  if error? try [a-number: to-decimal a-number] [
    return "*** Error ** Input must be a decimal value"
  ]
  if a-number = 0 [return "Zero"]
  the-original-number: round/down a-number
  pennies: a-number - the-original-number
  the-number: the-original-number
  if a-number < 1 [
    return join to-integer ((round/to pennies .01) * 100) "/"100"
  ]
  small-numbers: [
    "One" "Two" "Three" "Four" "Five" "Six" "Seven" "Eight"
    "Nine" "Ten" "Eleven" "Twelve" "Thirteen" "Fourteen" "Fifteen"
    "Sixteen" "Seventeen" "Eighteen" "Nineteen"
  ]
  tens-block: [
    { } "Twenty" "Thirty" "Forty" "Fifty" "Sixty" "Seventy" "Eighty"
    "Ninety"
  ]
  big-numbers-block: ["Thousand" "Million" "Billion"]
  digit-groups: copy []
  for i 0 4 1 [
    append digit-groups (round/floor (mod the-number 1000))
    the-number: the-number / 1000
  ]
  spoken: copy ""
  for i 5 1 -1 [
    flag: false
    hundreds: (pick digit-groups i) / 100
    tens-units: mod (pick digit-groups i) 100
    if hundreds <> 0 [
      if none <> hundreds-portion: (pick small-numbers hundreds) [
        append spoken join hundreds-portion " Hundred "
      ]
      flag: true
    ]
    tens: tens-units / 10
    units: mod tens-units 10
    if tens >= 2 [
      append spoken (pick tens-block tens)
      if units <> 0 [
        if none <> last-portion: (pick small-numbers units) [
          append spoken rejoin [" " last-portion " "]
        ]
        flag: true
      ]
    ]
  ]
]

```

```

    if tens-units <> 0 [
        if none <> tens-portion: (pick small-numbers tens-units) [
            append spoken join tens-portion " "
        ]
        flag: true
    ]
    if flag = true [
        commas: copy {}
        case [
            ((i = 4) and (the-original-number > 999999999)) [
                commas: {billion, }
            ]
            ((i = 3) and (the-original-number > 999999)) [
                commas: {million, }
            ]
            ((i = 2) and (the-original-number > 999)) [
                commas: {thousand, }
            ]
        ]
        append spoken commas
    ]
    append spoken rejoin [
        "and " to-integer ((round/to pennies .01) * 100) "/100"
    ]
    return spoken
]

; HERE'S AN EXAMPLE OF HOW TO USE IT:

print verbalize ask "Enter a number to verbalize: "
halt

```

Here's a fun program that lets you record your voice or other sounds to be played as alarms for any number of multiple events. Save and Load event lists. All alarm sounds repeat until stopped. Record yourself saying 'wake up you lazy bum' or 'hey dude, get up and walk the dog', then set alarms to play those voice messages on any given day/time. If you set the alarm as a date/time, the alarm will go off only once, on that date. If you set the alarm as a time, the alarm will go off every day at that time. The .wav recording code is MS Windows only, but the program can play any wave file that is usable in REBOL:

```

REBOL [title: "Voice Alarms"]

lib: load/library %winmm.dll
mci: make routine! [c [string!] return: [logic!]] lib "mciExecute"

write %play-alarm.r {
    REBOL []
    wait 0
    the-sound: load %tmp.wav
    evnt: load %event.tmp
    if (evnt = []) [evnt: "Test"]
    forever [
        if error? try [
            insert s: open sound:// the-sound wait s close s
        ] [
            alert "Error playing sound!"
        ]
        delay: :00:07
        s: request/timeout [
            join uppercase evnt " alarm - repeats until you click 'stop':"
            "Continue"
            "STOP"
        ] delay
        if s = false [break]
    ]
}

current: rejoin [form now/date newline form now/time]

```

```

view center-face layout [
  c: box black 400x200 font-size 50 current rate :00:01 feel [
    engage: func [f a e] [
      if a = 'time [
        c/text: rejoin [form now/date newline form now/time]
        show c
        if error? try [
          foreach evnt (to-block events/text) [
            if any [
              evnt/1 = form rejoin [
                now/date {/} now/time
              ]
              evnt/1 = form now/time
            ] [
              if error? try [
                save %event.tmp form evnt/3
                write/binary %tmp.wav
                read/binary to-file evnt/2
                launch %play-alarm.r
              ] [
                alert "Error playing sound!"
              ]
              ; request/timeout [(form evnt/3) "Ok"] :00:05
            ]
          ]
        ]
        ] [] ; do nothing if user is manually editing events
      ]
    ]
  ]
  h3 "Alarm Events (these CAN be edited manually):"
  events: area ; {[8:00:00am %alarm1.wav "Test Alarm - DELETE ME"]}
  across
  btn "Record Alarm Sound" [
    mci "open new type waveaudio alias wav"
    mci "record wav"
    request ["*** NOW RECORDING *** Click 'stop' to end:" "STOP"]
    mci "stop wav"
    if error? try [x: first request-file/file/save %alarm1.wav] [
      mci "close wav"
      return
    ]
    mci rejoin ["save wav " to-local-file x]
    mci "close wav"
    request [rejoin ["Here's how " form x " sounds..."] "Listen"]
    if error? try [
      save %event.tmp "test"
      write/binary %tmp.wav
      read/binary to-file x
      launch %play-alarm.r
    ] [
      alert "Error playing sound!"
    ]
  ]
  btn "Add Event" [
    event-name: request-text/title/default "Event Title:" "Event 1"
    the-time: request-text/title/default "Enter a date/time:" rejoin [
      now/date {/} now/time
    ]
    if error? try [set-time: to-date the-time] [
      if error? try [set-time: to-time the-time] [
        alert "Not a valid time!"
        break
      ]
    ]
    my-sound: request-file/title/file ".WAV file:" "" %alarm1.wav
    if my-sound = none [break]
    event-block: copy []
    append event-block form the-time
    append event-block my-sound
    append event-block event-name
    either events/text = "" [spacer: ""][spacer: newline]
    events/text: rejoin [events/text spacer (mold event-block)]
  ]
]

```

```

        show events
    ]
    btn "Save Events" [
        write to-file request-file/file/save %alarm_events.txt events/text
    ]
    btn "Load Events" [
        if error? try [
            events/text: read to-file request-file/file %alarm_events.txt
        ] [return]
        show events
    ]
]

```

Here is a nice generic CGI example which demonstrates how to enter and decode both Get and Post data, slightly revised from the earlier examples in this text:

```

#!./rebol276 -cs
REBOL[]
print "content-type: text/html^/"
either system/options/cgi/request-method = "POST" [
    data: copy "" buffer: copy ""
    while [positive? read-io system/ports/input buffer 16380][
        append data buffer
        clear buffer
    ]
] [
    data: system/options/cgi/query-string
]
cgi: construct decode-cgi data
if (length? first cgi) < 2 [
    print {
        <FORM METHOD="post" ACTION="./test.cgi">
        <CENTER>
        <INPUT TYPE=hidden NAME=hiddenvalue VALUE="foo">
        <INPUT TYPE=text size=50 name=text><BR><BR>
        <TEXTAREA cols=75 name=message rows=5></textarea><br><br>
        <INPUT TYPE="SUBMIT" NAME="Submit" VALUE="Submit">
        </CENTER>
        <FORM>
    }
    quit
]
print rejoin [
    cgi/hiddenvalue "<br><br>"
    cgi/text "<br><br>"
    "<pre>" cgi/message "</pre>"
]

```

Here is another version of Andreas Bolka's decode-multipart-form-data function (covered in the section of this tutorial about CGI programming):

```

decode-multipart-form-data: func [
    p-content-type
    p-post-data
    /local list ct pd bd delim-beg delim-end mime-part ] [
    list: copy []
    if not found? find p-content-type "multipart/form-data" [ return list ]
    ct: copy p-content-type
    pd: copy p-post-data
    bd: join "--" copy find/tail ct "boundary="
    delim-beg: join crlf crlf
    delim-end: rejoin [ crlf bd ]
    mime-part: [
        ( ct-dispo: content: none ct-type: "text/plain" )
        thru bd
        thru "content-disposition: " copy ct-dispo to crlf
    ]
]

```

```

    opt [ thru "content-type: " copy ct-type to crlf ]
    thru delim-beg copy content to delim-end
    ( handle-mime-part ct-dispo ct-type content )
]
handle-mime-part: func [
    p-ct-dispo p-ct-type p-content /local fieldname
] [
    p-ct-dispo: parse p-ct-dispo [describe ;=" here]
    fieldname: select p-ct-dispo "name"
    append list to-set-word fieldname
    either found? find p-ct-type "text/plain" [append list content][
        append list make object! [
            filename: select p-ct-dispo "filename"
            type: copy p-ct-type
            content: either none? p-content [ none ] [ copy p-content ]
        ]
    ]
]
]
]
use [ ct-dispo ct-type content ] [
    parse/all pd [ some mime-part ]
]
return list
]
]
```

This is a set of scripts by Andrew Grossman and Luis Rodriguez Jurado which also work with form-multipart data (just an example - NOT necessary for production use if you have Andreas's function):

```

#!c:/rebol.exe -cs

REBOL [
    TITLE: "form-upload"
    FILE: %form-upload.r
    DATE: 29-April-2000
]
print "Content-Type: text/html^/^/"
print {
<form METHOD=POST ACTION="post.r"
  enctype="multipart/form-data">
  Enter a description of the file:: <input TYPE=text
  SIZE=50 NAME=text><br>
  Select the file: <input TYPE=file SIZE=15
  NAME=myUpload><br><br>
  <input TYPE=submit VALUE="post.r">
</FORM></INPUT>
}

#!c:/rebol.exe -cs
REBOL [
    Title:      "multipart POST"
    Date:       15-Sep-1999
    Version:    1.2
    File:       %POST.r
    Author:     {Andrew Grossman (modified by: Luis Rodriguez J -
.29-April-2000)}
    Email:      [grossdog--dartmouth--edu]
    Owner:      "REBOL Technologies"
    Purpose:    {
        To decode multipart encoded POST requests, including file uploads.
    }
    Usage:      {
        Call this file in your CGI script and do decode-multi with a
        file argument of the directory where uploaded files will go and
        a logic argument to set whether files will be given the field they
        were uploaded as a name. Files are saved and variables are
        decoded and set.
    }
    Notes:      {
        Fixed problem recognizing EOF.
    }
]
```

```

        Functionality is now rock solid.  Function
        calls won't change, so this is certainly useable.
        See the comment in the decode-multi function if you need mime
        types.  Tested with MSIE and Netscape for Mac.
    }
category: ['web 'cgi 'utility]
]
decode-multi: func [
    file-dir      [file!] {Directory in which to put uploaded files}
    save-as-field [logic!] {save files as field name or uploaded filename}
    /local str boundary done name file done2 content
][
    if equal? system/options/cgi/request-method "POST" [
        either not parse system/options/cgi/content-type
            ["multipart/form-data" skip thru {boundary=} skip some {-}
            copy boundary to end]
        [
            str: make string! input do decode-cgi str[]
            str: make string! input
            done: false
            while [not done] [
                name: make string! ""
                str: make string! input
                either equal? "" str [done: true] [
                    either parse/all str [skip thru {name=} copy name to {"}
                    skip thru {filename=} copy file to {"} skip to end] [
                        str: make string! input
                        if not equal? str "" [str: make string! input]
                        comment {if you need mime put "parse/all str [
                            "Content-Type:" skip copy mime to end
                        ]" into the preceding if block.}
                        done2: false
                        content: make string! ""
                        while [not done2] [
                            content-length: to-integer system/options/cgi/content-length
                            str: make string! content-length
                            read-io system/ports/input str content-length
                                either d: find/reverse tail str boundary [
                                    e: find/reverse tail copy/part str (index? d)
                                    {^/}
                                    content: copy/part str (index? e) - 2
                                    done2: true]
                                [
                                    append content str
                                ]
                            ]
                        if not none? file
                    either save-as-field [name: dehex name write/binary
                    file-dir/:name content] [
                        file: dehex file write/binary file-dir/:file
                        content
                    ]
                ]
            ]
            parse str [skip thru {name=} copy name to {"}]
            str: make string! input str: dehex make string! input
            set to-word name str str: make string! input
        ]
    ]
    decode-multi %. true

```

This is a slightly edited version of the 3D Maze program (raycasting engine) by Olivier Auverlot:

```

REBOL [title: "3D Maze - Ray Casting Example"]

px: 9 * 1024 py: 11 * 1024 stride: 2 heading: 0 turn: 5

```

```

laby: [
  [ 8 7 8 7 8 7 8 7 8 7 8 7 ]
  [ 7 0 0 0 0 0 0 0 13 0 0 8 ]
  [ 8 0 0 0 12 0 0 0 14 0 9 7 ]
  [ 7 0 0 0 12 0 4 0 13 0 0 8 ]
  [ 8 0 4 11 11 0 3 0 0 0 0 7 ]
  [ 7 0 3 0 12 3 4 3 4 3 0 8 ]
  [ 8 0 4 0 0 0 3 0 3 0 0 7 ]
  [ 7 0 3 0 0 0 4 0 4 0 9 8 ]
  [ 8 0 4 0 0 0 0 0 0 0 0 7 ]
  [ 7 0 5 6 5 6 0 0 0 0 0 8 ]
  [ 8 0 0 0 0 0 0 0 0 0 0 7 ]
  [ 8 7 8 7 8 7 8 7 8 7 8 7 ]
]
ctable: []
for a 0 (718 + 180) 1 [
  append ctable to-integer (((cosine a ) * 1024) / 20)
]
palette: [
  0.0.128 0.128.0 0.128.128
  0.0.128 128.0.128 128.128.0 192.192.192
  128.128.128 0.0.255 0.255.0 255.255.0
  0.0.255 255.0.255 0.255.255 255.255.255
]
get-angle: func [ v ] [ pick ctable (v + 1) ]
retrace: does [
  clear display/effect/draw
  xy1: xy2: 0x0
  angle: remainder (heading - 66) 720
  if angle < 0 [ angle: angle + 720 ]
  for a angle (angle + 89) 1 [
    xx: px
    yy: py
    stepx: get-angle a + 90
    stepy: get-angle a
    l: 0
    until [
      xx: xx - stepx
      yy: yy - stepy
      l: l + 1
      column: make integer! (xx / 1024)
      line: make integer! (yy / 1024)
      laby/:line/:column <> 0
    ]
    h: make integer! (1800 / 1)
    xy1/y: 200 - h
    xy2/y: 200 + h
    xy2/x: xy1/x + 6
    color: pick palette laby/:line/:column
    append display/effect/draw reduce [
      'pen color
      'fill-pen color
      'box xy1 xy2
    ]
    xy1/x: xy2/x + 2 ; set to 1 for smooth walls
  ]
]
player-move: function [ /backwards ] [ mul ] [
  either backwards [ mul: -1 ] [ mul: 1 ]
  newpx: px - ((get-angle (heading + 90)) * stride * mul)
  newpy: py - ((get-angle heading) * stride * mul)
  c: make integer! (newpx / 1024)
  l: make integer! (newpy / 1024)
  if laby/:l/:c = 0 [
    px: newpx
    py: newpy
    refresh-display
  ]
]
]
evt-key: function [ f event ] [] [
  if (event/type = 'key) [
    switch event/key [

```



```

        up [ player-move ]
        down [ player-move/backwards ]
        left [
            heading: remainder (heading + (720 - turn)) 720
            refresh-display
        ]
        right [
            heading: remainder (heading + turn) 720
            refresh-display
        ]
    ]
]
event
]
insert-event-func :evt-key
refresh-display: does [
    retrace
    show display
]
screen: layout [
    display: box 720x400 effect [
        gradient 0x1 0.0.0 128.128.128
        draw []
    ]
    edge [
        size: 1x1
        color: 255.255.255
    ]
]
refresh-display
view screen

```

Here are a couple tiny utility scripts that I found useful:

```

; to replace a specific string inside special characters:

code: "text1 <% replace this %> text3"
replace code "<% replace this %>" "<% text2 %>"
print code

; to replace everything between special characters:

code: "text1 <% replace this %> <% replace this %> text3"
parse/all code [
    any [thru "<%" copy new to "%>" (replace code new " text2 ")] to end
]
print code

```

This script demonstrates how to insert a string into a file at a found position:

```

REBOL []

file: %mp3.html
a-string: {<BODY bgcolor="#C8C8C8">}

; first way:

write file read http://re-bol.com/examples/mp3.html
content: read file
insert (skip find content a-string length? a-string) trim {
    <center><h1>MP3 Example!</h1></center>}
write file content
editor file

; second way:

```

```

write file read http://re-bol.com/examples/mp3.html
content: read file
begin: (index? find content a-string) + (length? a-string)
altered: rejoin [
    (copy/part content begin)
    {<center><h1>MP3 Example!</h1></center>}
    (at content begin)
]
write file altered
editor file

```

This code determines the operating system you're running:

```

switch system/version/4 [
    2 [print "OSX"]
    3 [print "Windows"]
    4 [print "Linux"]
    7 [print "FreeBSD"]
    8 [print "NetBSD"]
    9 [print "OpenBSD"]
    10 [print "Solaris"]
] [alert "Can't be dertermined"]

```

Here's a CGI program I keep on my web server to delete masses of email which contain any given "spam" text:

```

#! /home/path/public_html/rebol/rebol -cs
REBOL []
print "content-type: text/html^/"
print [<HTML><HEAD><TITLE>"Remove Emails"</TITLE></HEAD><BODY>]

spam: [
    {Failure} {Undeliverable} {failed} {Returned Mail} {not be delivered}
    {mail status notification} {Mail Delivery Subsystem} {(Delay)}
]

print "logging in..."
mail: open pop://user:pass@site.com
print "logged in"

while [not tail? mail] [
    either any [
        (find first mail spam/1) (find first mail spam/2)
        (find first mail spam/3) (find first mail spam/4)
        (find first mail spam/5) (find first mail spam/6)
        (find first mail spam/7) (find first mail spam/8)
    ] [
        remove mail
        print "removed"
    ] [
        mail: next mail
    ]
    print length? mail
]
close mail
print [</BODY></HTML>]
halt

```

The following utility script takes an input string and returns an HTML string with all the web URLs appropriately wrapped as links:

```

bb: "some text http://guitarz.org http://yahoo.com"
bb_temp: copy bb
append bb_temp " " ; in case the URL doesn't have a trailing space

```

```

append bb " "
parse bb [any [thru "http://" copy link to " " (
  replace bb_temp (rejoin [{http://} link]) (rejoin [
    {<a href=} {http://} link {" target=_blank>http://}
    link {</a>}]])) to end
]
bb: copy bb_temp
print bb

```

I use the following utility CGI script to copy entire directories of files from one web server to another:

```

#!/home/path/public_html/rebol/rebol -cs
REBOL []
print "content-type: text/html^/"
print [<HTML><HEAD><TITLE>"wgetter"</TITLE></HEAD><BODY>]
foreach file (read ftp://user:pass@site.com/public_html/path/) [
  print file
  print <BR>
  write/binary (to-file file)
    (read/binary (to-url (rejoin [http://site.com/path/ file])))
]
print [</BODY></HTML>]

```

I use this next script to make sure that there are no files chmod 777 on my web servers. Built in is a routine that writes the name of every folder and every file on my server, to a text file. I run this one in the CGI console, with a "do chmod777to555.r":

```

REBOL [title: "chmod777to555"]

start-dir: what-dir
all-files: to-file join start-dir %find777all.txt

write all-files ""

recurse: func [current-folder] [
  out-data: copy ""
  write/append all-files rejoin["CURRENT_DIRECTORY: " what-dir newline]
  call/output {ls -al} out-data
  write/append all-files join out-data newline
  foreach item (read current-folder) [
    if dir? item [
      change-dir item
      recurse %.\
      change-dir %..\
    ]
  ]
]
recurse %.\

file-list: to-file join start-dir %found777.txt
write file-list ""
current-directory: ""
foreach line (read/lines all-files) [
  if find line "CURRENT_DIRECTORY: " [
    current-directory: line
  ]
  if find line "rwxrwxrwx" [
    write/append file-list rejoin [
      (find/match current-directory "CURRENT_DIRECTORY: ")
      (last parse/all line " ")
    ]
    write/append file-list newline
  ]
]

foreach file (read/lines file-list) [

```

```

    call rejoin [{chmod 755 } (to-local-file file)]
]

```

I've used variations of the following script to rename all the files with a given extension in a folder, to a different extension. The script copies all the files to the same name, without any extension at all:

```

foreach file read % [
    if (suffix? file) = %.src [
        write (to-file first parse file ".")(read to-file file)
    ]
]

```

I use the following script to keep my collection of Haxe language libraries up to date:

```

REBOL []

write %haxelibs.txt read http://lib.haxe.org/files/

the-list: read/lines %haxelibs.txt
clean: copy []

foreach line the-list [
    x: (parse/all form (find line ".zip") ">")
    if (length? x) > 2 [
        y: parse form second x "<"
        append clean first y
    ]
]

errors: copy []
make-dir %haxelibs
change-dir %haxelibs
save %list.txt clean ; comment this if you need to edit list.txt

downloaded: read %.

foreach file clean [
    if not (find downloaded (to-file file)) [
        either error? try [
            size? (join http://lib.haxe.org/files/ file)
        ] [
            print join "ERROR: " file
            append errors file
        ] [
            print rejoin [
                {Downloading: } file { (}
                size? (join http://lib.haxe.org/files/ file) { kb)}
            ]
            if error? try [
                write/binary
                    (to-file file)
                    (read/binary (join http://lib.haxe.org/files/ file))
            ] [
                print join "ERROR: " file
                append errors file
            ]
        ]
    ]
]

save %haxe_lib_download_errors.txt errors
print "Done."
halt

```

I use the following line to view/edit the code of script which has been run directly from a zip file (compressed

folder) in Windows:

```
editor to-file request-file system/script/path
```

Here's how to refer to widgets in the main window pane of a GUI window:

```
foreach item system/view/screen-face/pane/1/pane [
  remove find system/view/screen-face/pane/1/pane item
  ; this removes all widgets
]
```

Here is a Windows API function to use MCI functions:

```
lib: load/library %winmm.dll
mciSendString: make routine! [
  command [string!]
  rStr [string!]
  cchReturn [integer!]
  hwndCallback [integer!]
  return: [integer!]
] lib "mciSendStringA"
```

The following scripts demonstrate several different ways to run the code from the action block of another widget (i.e., to simulate mouse clicks or other actions on any given face). To understand more, run "source do-face" and "source do-face-alt" in the REBOL console to see how the "do-face" and "do-alt-face" functions work:

```
view layout [
  button1: btn "Button 1" [alert "Button 1 action block has been run."]
  btn "Button 2" [do-face button1 1]
]

view layout [
  b1: btn "B1" [alert "B1 left click"] [alert "B1 right click"]
  btn "B2" [do-face b1 1] [do-face-alt b1 1]
]

view layout [
  button1: btn "Button 1" [alert "Button 1 action block has been run."]
  btn "Button 2" [button1/action button1 none]
  ; "button1 none" in the line above releases the down state of the btn
]
```

The following script from <http://www.pat665.free.fr/gtk/rebol-view.html> demonstrates another way to do the same thing:

```
view layout [
  b: button "Test" [print "Test pressed"]
  button "In" [b/state: true show b]
  button "Out" [b/state: false show b]
  a: button "Action" [
    b/feel/engage :b 'down none
    b/feel/engage :b 'up none
    a/state: false show a ; Not sure why this line is needed...
  ]
]
```

Here's a 92 character version of the classic "FizzBuzz" program:

```
repeat i 100[j:""if i // 3 = 0[j:"fizz"]if i // 5 = 0
  [j: join j"buzz"]if j = ""[j: i]print j]
```

Here is a version of the Windows webcam program from earlier in this tutorial. This version was written for REBOL/face, and includes all the common avicap32.dll constants. It also contains the "do" files required in REBOL/face (they should be deleted if using REBOL/view). It also contains a function that can be used to hide and unhide windows:

```
REBOL []

do %gfx-colors.r
do %gfx-funcs.r
do %view-funcs.r
do %view-vid.r
do %view-edit.r
do %view-feel.r
do %view-images.r
do %view-styles.r
do %view-request.r
do %view.r

;WM_CAP_START: 0x400
;WM_START: to-integer #{00000400}
WM_CAP_START: 1024
WM_CAP_UNICODE_START: WM_CAP_START + 100
WM_CAP_PAL_SAVEA: WM_CAP_START + 81
WM_CAP_PAL_SAVEW: WM_CAP_UNICODE_START + 81
WM_CAP_UNICODE_END: WM_CAP_PAL_SAVEW
WM_CAP_ABORT: WM_CAP_START + 69
WM_CAP_DLG_VIDEOCOMPRESSION: WM_CAP_START + 46
WM_CAP_DLG_VIDEODISPLAY: WM_CAP_START + 43
WM_CAP_DLG_VIDEOFORMAT: WM_CAP_START + 41
WM_CAP_DLG_VIDEOSOURCE: WM_CAP_START + 42
WM_CAP_DRIVER_CONNECT: WM_CAP_START + 10
WM_CAP_DRIVER_DISCONNECT: WM_CAP_START + 11
WM_CAP_DRIVER_GET_CAPS: WM_CAP_START + 14
WM_CAP_DRIVER_GET_NAMEA: WM_CAP_START + 12
WM_CAP_DRIVER_GET_NAMEW: WM_CAP_UNICODE_START + 12
WM_CAP_DRIVER_GET_VERSIONA: WM_CAP_START + 13
WM_CAP_DRIVER_GET_VERSIONW: WM_CAP_UNICODE_START + 13
WM_CAP_EDIT_COPY: WM_CAP_START + 30
WM_CAP_END: WM_CAP_UNICODE_END
WM_CAP_FILE_ALLOCATE: WM_CAP_START + 22
WM_CAP_FILE_GET_CAPTURE_FILEA: WM_CAP_START + 21
WM_CAP_FILE_GET_CAPTURE_FILEW: WM_CAP_UNICODE_START + 21
WM_CAP_FILE_SAVEASA: WM_CAP_START + 23
WM_CAP_FILE_SAVEASW: WM_CAP_UNICODE_START + 23
WM_CAP_FILE_SAVEDIBA: WM_CAP_START + 25
WM_CAP_FILE_SAVEDIBW: WM_CAP_UNICODE_START + 25
WM_CAP_FILE_SET_CAPTURE_FILEA: WM_CAP_START + 20
WM_CAP_FILE_SET_CAPTURE_FILEW: WM_CAP_UNICODE_START + 20
WM_CAP_FILE_SET_INFOCHUNK: WM_CAP_START + 24
WM_CAP_GET_AUDIOFORMAT: WM_CAP_START + 36
WM_CAP_GET_CAPSTREAMPTR: WM_CAP_START + 1
WM_CAP_GET_MCI_DEVICEA: WM_CAP_START + 67
WM_CAP_GET_MCI_DEVICEW: WM_CAP_UNICODE_START + 67
WM_CAP_GET_SEQUENCE_SETUP: WM_CAP_START + 65
WM_CAP_GET_STATUS: WM_CAP_START + 54
WM_CAP_GET_USER_DATA: WM_CAP_START + 8
WM_CAP_GET_VIDEOFORMAT: WM_CAP_START + 44
WM_CAP_GRAB_FRAME: WM_CAP_START + 60
WM_CAP_GRAB_FRAME_NOSTOP: WM_CAP_START + 61
WM_CAP_PAL_AUTOCREATE: WM_CAP_START + 83
WM_CAP_PAL_MANUALCREATE: WM_CAP_START + 84
WM_CAP_PAL_OPENA: WM_CAP_START + 80
WM_CAP_PAL_OPENW: WM_CAP_UNICODE_START + 80
WM_CAP_PAL_PASTE: WM_CAP_START + 82
WM_CAP_SEQUENCE: WM_CAP_START + 62
```

```

WM_CAP_SEQUENCE_NOFILE: WM_CAP_START + 63
WM_CAP_SET_AUDIOFORMAT: WM_CAP_START + 35
WM_CAP_SET_CALLBACK_CAPCONTROL: WM_CAP_START + 85
WM_CAP_SET_CALLBACK_ERRORA: WM_CAP_START + 2
WM_CAP_SET_CALLBACK_ERRORW: WM_CAP_UNICODE_START + 2
WM_CAP_SET_CALLBACK_FRAME: WM_CAP_START + 5
WM_CAP_SET_CALLBACK_STATUSA: WM_CAP_START + 3
WM_CAP_SET_CALLBACK_STATUSW: WM_CAP_UNICODE_START + 3
WM_CAP_SET_CALLBACK_VIDESTREAM: WM_CAP_START + 6
WM_CAP_SET_CALLBACK_WAVESTREAM: WM_CAP_START + 7
WM_CAP_SET_CALLBACK_YIELD: WM_CAP_START + 4
WM_CAP_SET_MCI_DEVICEA: WM_CAP_START + 66
WM_CAP_SET_MCI_DEVICEW: WM_CAP_UNICODE_START + 66
WM_CAP_SET_OVERLAY: WM_CAP_START + 51
WM_CAP_SET_PREVIEW: WM_CAP_START + 50
WM_CAP_SET_PREVIEWRATE: WM_CAP_START + 52
WM_CAP_SET_SCALE: WM_CAP_START + 53
WM_CAP_SET_SCROLL: WM_CAP_START + 55
WM_CAP_SET_SEQUENCE_SETUP: WM_CAP_START + 64
WM_CAP_SET_USER_DATA: WM_CAP_START + 9
WM_CAP_SET_VIDEOFORMAT: WM_CAP_START + 45
WM_CAP_SINGLE_FRAME: WM_CAP_START + 72
WM_CAP_SINGLE_FRAME_CLOSE: WM_CAP_START + 71
WM_CAP_SINGLE_FRAME_OPEN: WM_CAP_START + 70
WM_CAP_STOP: WM_CAP_START + 68

avicap32.dll: load/library %avicap32.dll
user32.dll: load/library %user32.dll

; Hide rebface console:

get-focus: make routine! [return: [int]] user32.dll "GetFocus"
hwnd-hide-console: get-focus
hide-window: make routine! [
    hwnd [int]
    a [int]
    return: [int]
] user32.dll "ShowWindow"
hide-window hwnd-hide-console 0

view/new center-face layout/tight [
    image 320x240
    across
    btn "Take Snapshot" [
        sendmessage cap-result WM_CAP_GRAB_FRAME_NOSTOP 0 0
        sendmessage-file cap-result WM_CAP_FILE_SAVEDIBA 0 "scrshot.bmp"
    ]
    btn "Exit" [
        sendmessage cap-result WM_CAP_END 0 0
        sendmessage cap-result WM_CAP_DRIVER_DISCONNECT 0 0
        free user32.dll
        quit
    ]
]

; Set window title:

set-caption: make routine! [
    hwnd [int]
    a [string!]
    return: [int]
] user32.dll "SetWindowTextA"
hwnd-set-title: get-focus
set-caption hwnd-set-title "Web Camera"

find-window-by-class: make routine! [
    ClassName [string!]
    WindowName [integer!]
    return: [integer!]
] user32.dll "FindWindowA"
hwnd: find-window-by-class "REBOLWind" 0

```

```

cap: make routine! [
  cap [string!]
  child-val1 [integer!]
  val2 [integer!]
  val3 [integer!]
  width [integer!]
  height [integer!]
  handle [integer!]
  val4 [integer!]
  return: [integer!]
] avicap32.dll "capCreateCaptureWindowA"
sendmessage: make routine! [
  hWnd [integer!]
  val1 [integer!]
  val2 [integer!]
  val3 [integer!]
  return: [integer!]
] user32.dll "SendMessageA"

sendmessage-file: make routine! [
  hWnd [integer!]
  val1 [integer!]
  val2 [integer!]
  val3 [string!]
  return: [integer!]
] user32.dll "SendMessageA"

cap-result: cap "cap" 1342177280 0 0 320 240 hWnd 0
; 1342177280 in the line above is the value I got from
; BitOR(WS_CHILD,WS_VISIBLE) in two seperate development environments,
; but not sure if it will always hold true.
sendmessage cap-result WM_CAP_DRIVER_CONNECT 0 0
sendmessage cap-result WM_CAP_SET_SCALE 1 0
sendmessage cap-result WM_CAP_SET_OVERLAY 1 0
sendmessage cap-result WM_CAP_SET_PREVIEW 1 0
sendmessage cap-result WM_CAP_SET_PREVIEWRATE 1 0

do-events

```

Here's one final version of the web cam program, with a nicer save feature. In order for the save routine to work properly, this code should be saved to a .r script and run from there:

```

REBOL []

avicap32.dll: load/library %avicap32.dll
user32.dll: load/library %user32.dll
get-focus: make routine! [return: [int]] user32.dll "GetFocus"
set-caption: make routine! [
  hWnd [int] a [string!] return: [int]
] user32.dll "SetWindowTextA"
find-window-by-class: make routine! [
  ClassName [string!] WindowName [integer!] return: [integer!]
] user32.dll "FindWindowA"
sendmessage: make routine! [
  hWnd [integer!] val1 [integer!] val2 [integer!] val3 [integer!]
  return: [integer!]
] user32.dll "SendMessageA"
sendmessage-file: make routine! [
  hWnd [integer!] val1 [integer!] val2 [integer!] val3 [string!]
  return: [integer!]
] user32.dll "SendMessageA"
cap: make routine! [
  cap [string!] child-val1 [integer!] val2 [integer!] val3 [integer!]
  width [integer!] height [integer!] handle [integer!]
  val4 [integer!] return: [integer!]
] avicap32.dll "capCreateCaptureWindowA"

view/new center-face layout/tight [
  image 320x240

```



```

across
btn "Take Snapshot" [
  sendmessage cap-result 1085 0 0
  sendmessage-file cap-result 1049 0 "scrshot.bmp"
  save-path: first split-path system/options/script
  view/new center-face layout [
    image load join save-path %scrshot.bmp
    btn "save" [
      (write/binary
        to-file pp: request-file/save/file %photo1.bmp
        read/binary join save-path %scrshot.bmp
      )
      alert join "Saved " pp
      unview
    ]
  ]
]
btn "Exit" [
  sendmessage cap-result 1205 0 0
  sendmessage cap-result 1035 0 0
  free user32.dll
  quit
]
]
hwnd-set-title: get-focus
set-caption hwnd-set-title "Web Camera" ; title bar
hwnd: find-window-by-class "REBOLWind" 0
cap-result: cap "cap" 1342177280 0 0 320 240 hwnd 0
sendmessage cap-result 1034 0 0
sendmessage cap-result 1077 1 0
sendmessage cap-result 1075 1 0
sendmessage cap-result 1074 1 0
sendmessage cap-result 1076 1 0
do-events

```

This is a sound synthesizing example derived from the [quick hack](#) demo by Cyphre:

```

REBOL []

wait 0
octave: ["c" "cs" "d" "ds" "e" "f" "fs" "g" "gs" "a" "as" "b" "c"]
notes: copy []
oct: -1
repeat n 12 * 6 [
  if (n - 1 // 12 + 1) = 1 [oct: oct + 1]
  insert tail notes reduce [
    to-word join pick octave n - 1 // 12 + 1 oct 440 / (
      2 ** ((46 - n) / 12)
    )
  ]
]
]
make-sound: func [type freq ln /local tone freq2 result] [
  switch type [
    square [
      freq: to-integer 22050 / freq
      tone: head insert/dup copy #{} to-char 0 freq
      result: copy #{}
      freq2: to-integer freq / 2
      repeat n freq2 [
        poke tone n to-char 0
        poke tone n + freq2 to-char 255
      ]
      insert/dup result tone ln / freq
      return result
    ]
  ]
]
make-pattern: func [
  tracks

```

```

    /local out snd-tracks t tempo mix
] [
    out: make sound [
        rate: 22050
        channels: 1
        bits: 8
        volume: 0.5
        data: #{}
    ]
    snd-tracks: copy []
    loop (length? tracks) / 2 [
        insert tail snd-tracks copy #{}
    ]
    t: 0
    tempo: (60 / 120) ; SET THE TEMPO HERE
    foreach [inst track] tracks [
        t: t + 1
        repeat n length? track [
            either track/:n = 'xx [
                insert/dup tail
                    snd-tracks/:t to-char 128 to-integer 22050 * tempo / 4
            ] [
                insert tail snd-tracks/:t
                    make-sound inst select notes
                    track/:n to-integer 22050 * tempo / 4
            ]
        ]
    ]
    out/data: head insert/dup copy #{} to-char 0 length? snd-tracks/1
    mix: array/initial length? snd-tracks/1 0
    foreach track snd-tracks [
        repeat n length? snd-tracks/1 [
            poke mix n mix/:n + track/:n
        ]
    ]
    repeat n length? snd-tracks/1 [
        poke out/data n to-char to-integer mix/:n / ((length? tracks) / 2)
    ]
    return out
]

soundtrack: make sound [
    rate: 22050
    channels: 1
    bits: 8
    volume: 0.5 ; SET THE VOLUME HERE
    data: #{}
]

; Here are the notes to be played. All tracks should have the same
; number of notes. The note names for the musical alphabet are:
; c2 cs2 d2 ds2 e2 f2 fs2 g2 gs2 a2 as2 b2. Use "xx" for rests.

; -----

tracks-1: [
    square [
        c1 cs1 d1 ds1 e1 f1 fs1 g1 gs1 a1 as1 b1
        c1 xx cs1 xx d1 xx ds1 xx e1 xx f1 xx fs1 xx
        g1 xx gs1 xx a1 xx as1 xx b1
    ]
    square [
        e2 f2 fs2 g2 gs2 a2 as2 b2 c3 cs3 d3 ds3
        e2 xx f2 xx fs2 xx g2 xx gs2 xx a2 xx as2 xx
        b2 xx c3 xx cs3 xx d3 xx ds3
    ]
]

; -----

; This initiates the playing:

pl: make-pattern tracks-1

```

```

insert/dup tail soundtrack/data p1/data 2
; p2: make-pattern tracks-2
; insert/dup tail soundtrack/data p2/data 1
; the last # is the number of times to repeat the soundtrack
sp: open sound://
insert sp soundtrack

; Here are some start-stop controls:

ask "press enter to quit"
; wait sp
close sp

```

This script by Volker Nitsch demonstrates how to use the "set-it" func of the GUI list style:

```

stuff: copy []
view layout [
  lst: list [across info info] 400x400 supply [
    either count > length? stuff [face/text: "" face/image: none] [
      lst/set-it face stuff index count
    ]
  ]
  with [probe words source set-it] ; get some hints
  button "add now" [
    append/only stuff reduce [mold 1 + length? stuff mold now/time]
    show lst
  ]
]

```

The following code demonstrates how to check for async keystrokes (including arrow keys) in the REBOL shell:

```

print ""
p: open/binary/no-wait console://
q: open/binary/no-wait [scheme: 'console]

forever [
  if not none? wait/all [q :00:00.30] [
    wait q
    qq: to string! copy q
    probe qq
  ]
]

```

Don't forget to look at all the scripts at rebol.org - not just in the scripts section, but also in the email and AltME archives. It's a treasure trove of working code examples and answers to virtually any coding problem!

12. Learning More About REBOL - IMPORTANT DOCUMENTATION LINKS

A very old edition of this text with several hundred screen shot images is available at http://musiclessonz.com/rebol_tutorial-images.html). If you're completely new to programming, that text may offer some helpful simple perspective.

The tutorial at <http://www.rebol.com/docs/rebol-tutorial-3109.pdf> provides a nice summary of fundamental concepts. It's a great document to read next. To learn REBOL in earnest, read the REBOL core users manual: <http://rebol.com/docs/core23/rebolcore.html>. It covers all of the data types, built-in word functions and ways of dealing with data that make up the REBOL/Core language (but not the graphic extensions in View). It also includes many basic examples of code that you can use in your programs to complete common programmatic tasks. Also, be sure to keep the REBOL function dictionary handy whenever you write any REBOL code: <http://rebol.com/docs/dictionary.html>. It defines all the words in the REBOL language and their specific syntax use. The dictionary is also helpful in cross-referencing function words that do related actions in the language (great when you can't remember a function name you're looking for). Along the way, read the REBOL View and VID documents at: <http://rebol.com/docs/easy-vid.html>, <http://rebol.com/docs/view-guide.html>, <http://rebol.com/docs/view-system.html>, <http://www.rebol.com/how->

[to/feel.html](#) , <http://www.pat665.free.fr/gtk/rebol-view.html> , and run the script at <http://www.rebol.org/download-a-script.r?script-name=vid-usage.r>. Those documents explain how to write Graphical User Interfaces in REBOL. Once you've got an understanding of the grammar and vocabulary of the language, dive into the REBOL cookbook: <http://www.rebol.net/cookbook/>. It contains many simple and useful examples of code needed to create real-world applications. When you've read all that, finish the rest of the documents at <http://rebol.com/docs.html>.

Beyond the basic documentation, there is a library of hundreds of commented REBOL scripts at <http://rebol.org/>. There's also a searchable archive of the mailing list and AltME (community forum) containing several hundred thousand posts at rebol.org. That archive contains answers to many thousands of questions encountered by REBOL programmers. [Rebol.org](http://rebol.org) is an essential resource! There are numerous other web sites such as <http://www.codeconscious.com/rebol>, <http://www.rebolforces.com/> (duplicated at <http://www.rebolplanet.com/>), <http://www.reboltech.com/library/library.html>, <http://www.fm.vslib.cz/~ladislav/rebol/>, <http://www.compkarori.com/vanilla/display/index>, <http://www.rebol.net/>, <http://reboltutorial.com/>, <http://blog.revoluent.net/search/label/REBOL>, <http://www.reboltalk.com/forum/>, <http://anton.wildit.net.au/rebol>, <http://rebolweek.blogspot.com/>, <http://groups-beta.google.com/group/Rebol>, and [rebolfrance \(translated by Google\)](#) that provide more help in understanding and using the language. Don't miss Carl Sassenrath's [personal blog](#), [discussions about REBOL3](#), [alpha downloads](#) of REBOL3, and [REBOL3 documentation](#). For a complete list of all web pages and articles related to REBOL, see <http://dmoz.org/Computers/Programming/Languages/REBOL/>.

Don't forget to click the rebsite icons in the "REBOL" and "Public" folders, right in the desktop of the REBOL interpreter. Right-click any of the hundreds of individual program icons and select "edit" to see the code for any example. That's a great way to see how to do things in REBOL.

13. Beyond REBOL

Modern computers are complex systems built upon multiple layers of technology. The physical hardware (CPU, RAM memory, hard drive, keyboard, mouse, monitor, etc.) form the foundation. The operating system (Windows, Mac, Linux, etc.) manages that hardware, enables software drivers, provides a common user interface, and provides many basic facilities to make the whole system useful (file management, connection to network protocols, etc.). Software built upon the fundamental components in the operating system make more specific applications possible (word processors, games, etc.). In our modern world, many of the applications we use are built upon *multiple* software layers, on top of the already complex foundation. The Internet is made up of many types of hardware systems, running many different operating systems, connected by compatible network protocols, running many different web and email server programs, storing information via database programs of all types, etc. All those layers work together to serve data via generally compatible formats (HTML files containing page layouts, standard image types such as .jpg and .gif, standard sound formats such as .mp3 and .wav, and standard video formats such as Flash). That's all accessed by a variety of different web browser programs, email clients, cell phone apps, etc., which connect to those standard protocols through the OS, and read/save info in those formats. On top of that complex structure, languages like Javascript run within web browser software to control data which appears on web pages. Languages like PHP and others run on web server software to control how they output data.

REBOL is a language that operates at many of those levels. It can run as a browser plug-in to control data display in web pages. It can run on a web server to build and serve web sites. It neatly "wraps" up most common functions that various operating systems enable, to provide file handling, network control, and other system level facilities. It provides a single, simple format that lets you talk to all different computers in the same ways, at all those levels. It's got it's own way of speaking that is [different](#) from many other languages. That grammar and vocabulary is called the "API". If you continue to pursue programming in various environments, you'll encounter many different language APIs which, in the end, do most of the same things as REBOL, but which use very different approaches to grammar and syntax. Eventually, you'll learn to deal with the raw API of the operating system (using native language compilers, DLLs, and other native interfaces). The operating system API is the base language that most other languages are actually *translating* to. Because the operating system needs to access the computer hardware quickly, it is written in a "lower level" language - one that is formatted to think more like the computer's raw calculations, and less like human speech.

With REBOL, you can do most typical things that programmers want to do, but there are many functions in the various operating system APIs that aren't included (i.e., web cam access, sound input, low level hardware control, etc.). To do that, be prepared to explore the raw operating system API, and the language (s) in which it was written. On Windows, Unix, Macintosh, and other platforms, that typically means learning the syntax and structure of the "C" and "C++" languages. Also, learning common methods for accessing shared code files such as .dll's is very important. Once you've learned the full REBOL API, that's a good direction to take in your studies.

Other favorite programming languages of this author, which pack a lot of computing punch, like Rebol, include:

1. [Haxe/Neko](#) - compiles your code to several different languages/platforms. It runs on Windows, Mac, and Linux, using the exact same code. It contains the entire Flash Actionscript3 API, and can compile directly to standard .swf files, which makes it extraordinarily powerful for creating multimedia applications, for use in both online and desktop applications. Haxe can compile to the Neko virtual machine, for use in server and desktop applications. Neko applications can be converted directly to native Windows, Mac and Linux executables. Haxe can also compile directly to Javascript, PHP, and C++ code, all using the exact same core language. It uses a traditional syntax familiar to those who know Java and C++. It's a very small download, runs extremely fast, is free/open source, and is very stable. Haxe is a great tool to compliment REBOL, because it's strengths cover some of REBOL's weaknesses (Flash multimedia development and integration with other popular high level and low level development tools). [Mtasc](#) is another free Flash compiler, created by the same person as Haxe. It's older, but may be useful if you want to compile code written in the Actionscript2 API. [Openlaszlo](#) is one more free, cross-platform tool for those interested in developing rich multimedia web applications. It has its own language implementation (different from the Flash Actionscript API), but can compile the exact same code to either Flash or DHTML, so applications written in Openlaszlo can run in virtually any web environment.
2. [JAVA](#) - The most popular programming language around. If you want a job programming, JAVA should be in your short list of languages to learn. Programs written in JAVA can run on Windows, Mac, Linux, cell phones, web browsers, and most other modern operating platforms, using the same code. JAVA has tens of millions of users, so support for it is enormous, and integration with other tools is ubiquitous. The overwhelming majority of desktop computers already have the JAVA virtual machine installed, and you can accomplish just about any programming goal with JAVA tools. One down side of JAVA is that it's much larger and more complex (both in language structure and download size) than REBOL and other tools. You'll need to learn more about traditional object oriented design patterns to work with JAVA.
3. [Python](#) - Another very popular free/open source programming tool that runs on most operating systems. It's smaller and easier to learn than JAVA, but is still powerful and has strong support around the world. It's great for creating web site scripts as well as desktop apps of all sorts. Python covers much of the same problem domain, and has some size/simplicity features similar to REBOL (although REBOL is much smaller and simpler to use :).
4. [Purebasic](#) - A nice compiler that creates very small and fast native applications for Windows, Mac, and Linux. It's not free, but it is inexpensive, and upgrades are free for life. Purebasic offers many of the benefits of programming with lower level languages such as assembler and C/C++ (execution speed, and access to low level optimization). It comes with a very nice integrated development environment and makes use of a friendly and very productive cross platform language implementation.
5. [AutoIt](#) - The unique characteristic of AutoIt is that it includes many built-in functions to **control other Windows programs**. You can programatically push buttons, type text, select menu items, choose items from lists, etc. in any program window, as if those actions had been performed by a user clicking and typing on screen. This allows you to automate and speed up repetitive routines, and to customize the use of existing applications. AutoIt is extremely simple to learn, it's free and quick to download/install, has a large user base, easily compiles scripts to standard .exe programs, and is a powerful general purpose scripting language that can be used to create all types of applications for Windows.
6. If your goal is to work as a commercial programmer, you should become fluent with the most popular tools. To work with development teams, you need to know the language(s) they use. The list at <http://www.tiobe.com/index.php/content/paperinfo/tpci/index.html> will point you in the right direction (C/C++, C#, Visual Basic, PHP, PERL, etc.). You'll also need to know HTML and Javascript if you want to do any work as a web developer.

Exploring those tools should give focus to your further studies. Good luck and have fun!

For feedback, bugs reports, suggestions, etc., please email Nick at:

```
reverse {moc tod znosselcismus ta lober}
```

To hire the author for tutoring, to develop software or web site applications, or for general consultation/computing support, see <http://com-pute.com/> or call 267-352-3625.

14. Appendix 1: A REBOL Song

You can find an MP3 of the following REBOL song at http://re-bol.com/examples/rebol_song.mp3:

```
I've got some operators and a little block code
And with VID I'm gonna build a new window.
I'm gonna hack it out, simple and fast
And make a killer REBOL app that lasts.
```

They tell me I should give Python a try
But they don't know how that'd make me cry.
It takes ten times as long to install that mess
And still gives an error at some memory address.

REBOL REBOL - Get it done fast
R-E-B-O-L - and have a blast
REBOL REBOL - It's in my path
Thanks Mr. Sassenrath

Gonna take some strings and put 'em in a series
And loop through so fast, it'll bring you to your knees.
'Bind, 'set, 'use, 'context, and 'get
Once you get how they work, they're no sweat.

I never felt this way about anything else
Not C++, JAVA, or Haskell.
It's 2am, and I'm almost done
but I'm codin' on, cause it's so much fun.

REBOL REBOL - Get it done fast
R-E-B-O-L - and have a blast
REBOL REBOL - It's in my path
Thanks Mr. Sassenrath

Regular expressions in PERL are alright
But let me loose with parse - I can do that all night.
PHP's ok, for data on the net
but nothing's slicker than an IOS Reblet.

"Foreach" 100 lines they have to code
I just use a dialect to lighten my load.
And just when I'm stuck on the toughest part
Some guru writes code that looks like REBOL art.

REBOL REBOL - Get it done fast
R-E-B-O-L - and have a blast
REBOL REBOL - It's in my path
Thanks Mr. Sassenrath

Delphi, C, Ruby, LUA - no more.
When REBOL came along, they went out the door.
You can't get a thing done with those old dogs
And I don't want to run another resource hog.

PC, MAC, Linux - they all work for me
Heck, I can even do OpenBSD.
We even have a plug-in for your browser
Ooh look, those BASIC guys just peed their trousers :)

REBOL REBOL - Get it done fast
R-E-B-O-L - and have a blast
REBOL REBOL - It's in my path
Thanks Mr. Sassenrath

When you need function help, who wants to grab a book,
It's built right into REBOL - you know where to look.
One half a meg - that's all it takes
To get rid of all your coding headaches.

It may be tough to convince your boss
To try out REBOL, even though it's not FOSS.
But the best things in life are still free.
It's just the REBOL source, that we'll never see

REBOL REBOL - Get it done fast
R-E-B-O-L - and have a blast
REBOL REBOL - It's in my path
Thanks Mr. Sassenrath

I don't need a single library

```
for all the protocols and datatypes I ever need.  
Build a GUI in a line or 2  
Who needs modules, I just type "do".
```

```
Productivity they can't comprehend,  
with REBOL I do the work of 10 men.  
I don't wanna code any other way  
Just write .r scripts every day.
```

```
REBOL REBOL - Get it done fast  
R-E-B-O-L   - and have a blast  
REBOL REBOL - It's in my path  
Thanks Mr. Sassenrath
```

```
Now I spend all my time on AltME  
While I pour another cup of black coffee  
Another job done, I'm crankin' 'em out  
Just wish that REBOL could make a darn printout.
```

```
I never said it's perfect, but I don't care  
REBOL keeps me from pulling out my hair.  
Without it I'd really have to give up  
And install some 100 megabyte setup.
```

```
REBOL REBOL - Get it done fast  
R-E-B-O-L   - and have a blast  
REBOL REBOL - It's in my path  
Thanks Mr. Sassenrath
```

Keywords:

software development, learn to program a computer, how to write software, learn computer programming, easy coding, how to create programs, learn to write code, computer programming tutorial, programming course, learn about programming, coding, easiest way to program, simple programming, best programming language, best computer language, easiest programming language, easiest way to program, learn programming, get started programming

Copyright © Nick Antonaccio 2005-2010, All Rights Reserved

[MakeDoc2 by REBOL](#) - 28-Mar-2010