NEWHAVEN DISPLAY INTERNATIONAL

Product Specification

NHD-C12832A1Z-FSR-FBW-3V3

COG (Chip-On-Glass) Liquid Crystal Display Module

NHD-	Newhaven Display
C12832-	128 x 32 Pixels
A1Z-	Model
F-	Transflective
SR-	Red LED Edge Backlight
F-	FSTN (+)
B-	6:00 Optimal View
W-	Wide Temperature
3V3-	3Vdd, 3V Backlight

Newhaven Display International, Inc.
2661 Galvin Court, Elgin, IL 60124 USA

Ph: 847.844.8795 | Fx: 847.844.8796
www.newhavendisplay.com

REACH Compliant

RoHS Compliant

NEWHAVEN DISPLAY INTERNATIONAL

Table of Contents

Document Revision History 2
Mechanical Drawing 3
Recommended PCB Footprint 4
Pin Description 5
Wiring Diagram 5
Electrical Characteristics 6
Optical Characteristics 6
Controller Information 6
Timing Characteristics 7
Table of Commands 8
Example Initialization Program 9
Quality Information 10

Additional Resources

- **Support Forum:** https://support.newhavendisplay.com/hc/en-us/community/topics
- **GitHub:** https://github.com/newhavendisplay
- **Example Code:** https://support.newhavendisplay.com/hc/en-us/categories/4409527834135-Example-Code/
- **Knowledge Center:** https://www.newhavendisplay.com/knowledge_center.html
- **Quality Center:** https://www.newhavendisplay.com/quality_center.html
- **Precautions for using LCDs/LCMs:** https://www.newhavendisplay.com/specs/precautions.pdf
- **Warranty / Terms & Conditions:** https://www.newhavendisplay.com/terms.html

Document Revision History

Revision	Date	Description	Changed By
0	11/12/2008	Initial Release	-
1	09/27/2010	User Guide Reformat	BE
2	05/06/2013	Electrical and Optical characteristics updated. Pin Description, Wiring Diagram, Mechanical Drawing Page and Example Initialization Program Updated.	JN
3	01/24/2017	Mechanical Drawing, Electrical & Optical Char. Updated	SB
4	07/05/2019	Added PCB Footprint Drawing	AS
5	01/30/2020	Glass Panel Updated	SB
6	06/17/2020	Updated 2D Mechanical Drawing & Quality Information	AS
7	04/14/2024	PCB Footprint Drawing Updated	KL
8	06/11/2024	Date Code Format Updated on Mechanical Drawing	KL

Mechanical Drawing





SECTION A–A









DOTS Detail
Scale 20:1



LED backlight circuit

COM & SEG Layout

Pin Assignment	
NO.	Symbol
1	V0
2	V1
3	V2
4	V3
5	V4
6	C2-
7	C2+
8	C1+
9	C1-
10	VOUT
11	VSS
12	VDD
13	SI
14	SCL
15	A0
16	/RES
17	CS1B

Product Description: 128x32 Graphic COG LCD

1. Driver IC: ST7565R
2. Driving Mode: 1/33 Duty, 1/6 Bias
3. Interface: 4-Wire SPI
4. Power Requirement: 3.0V LCD
5. Optical Features: FSTN (+), Transflective, 6:00 View, Red Backlight

Standard Tolerance:
(Unless otherwise specified)
Linear: ±0.3mm

NEWHAVEN DISPLAY INTERNATIONAL

Drawing/Part Number: NHD-C12832A1Z-FSR-FBW-3V3
Revision: 1A

Unless otherwise specified:
• Dimensions are in Millimeters
• Third Angle Projection

Drawn By: K. Lewis
Approved By: K. Lewis
Drawn Date: 06/11/2024
Approved Date: 06/11/2024

This drawing is solely the property of Newhaven Display International, Inc. The information it contains is not to be disclosed, reproduced or copied in whole or part without written approval from Newhaven Display.

Mechanical Drawing

Recommended PCB Footprint



Applicable Displays:

1) NHD-C12832A1Z-FSW-FBW-3V3
2) NHD-C12832A1Z-NSW-BBW-3V3
3) NHD-C12832A1Z-FSR-FBW-3V3
4) NHD-C12832A1Z-FSB-FBW-3V3

Standard Tolerance:
(Unless otherwise specified)
Linear: ±0.3mm

NEWHAVEN DISPLAY INTERNATIONAL

Drawing/Part Number: NHD-C12832A1Z-Monochrome-Footprint		Revision: -
Unless otherwise specified: • Dimensions are in Millimeters • Third Angle Projection	Drawn By: K. Lewis	Approved By: K. Lewis
	Drawn Date: 04/09/2024	Approved Date: 04/09/2024

This drawing is solely the property of Newhaven Display International, Inc. The information it contains is not to be disclosed, reproduced or copied in whole or part without written approval from Newhaven Display.

Pin Description

Pin No.	Symbol	External Connection	Function Description
1	V_0	Power Supply	0.1µF – 1µF Capacitor to V_{SS}
2	V_1	Power Supply	0.1µF – 1µF Capacitor to V_{SS}
3	V_2	Power Supply	0.1µF – 1µF Capacitor to V_{SS}
4	V_3	Power Supply	0.1µF – 1µF Capacitor to V_{SS}
5	V_4	Power Supply	0.1µF – 1µF Capacitor to V_{SS}
6	C2-	Power Supply	Connect 1µF – 2.2µF Capacitor to C2+ (pin 7)
7	C2+	Power Supply	Connect 1µF – 2.2µF Capacitor to C2- (pin 6)
8	C1+	Power Supply	Connect 1µF – 2.2µF Capacitor to C1- (pin 9)
9	C1-	Power Supply	Connect 1µF – 2.2µF Capacitor to C1+ (pin 8)
10	V_{OUT}	Power Supply	Connect 1µF – 2.2µF Capacitor to VSS (pin 11)
11	V_{SS}	Power Supply	Ground
12	V_{DD}	Power Supply	Supply Voltage for LCD and Logic (+3V)
13	SI	MPU	Serial Data
14	SCL	MPU	Serial Clock
15	A0	MPU	Register Select. A0=0: Instruction; A0=1: Data
16	/RST	MPU	Active LOW Reset signal
17	/CS1	MPU	Active LOW Chip Select signal
A	LED+	Power Supply	Backlight Anode (+3V)
K	LED-	Power Supply	Backlight Cathode (Ground)

Recommended LCD connector: 1.5mm pitch pins, solder directly into PCB
Backlight connector: 1.2mm Wide pins, solder directly into PCB **Mates with**: ---
Recommended Breakout Board: NHD-PCB12832A1Z

Wiring Diagram



Electrical Characteristics

Item	Symbol	Condition	Min.	Typ.	Max.	Unit
Operating Temperature Range	T_{OP}	Absolute Max	-20	-	+70	°C
Storage Temperature Range	T_{ST}	Absolute Max	-30	-	+80	°C
Supply Voltage		-	2.7	3.0	3.3	V
Supply Current	I_{DD}	V_{DD} =3.0V	0.1	0.4	1.0	mA
Supply for LCD (contrast)	V_{LCD}	T_{OP} = 25°C	5.8	6.0	6.2	V
"H" Level input	V_{IH}	-	0.8 *V_{DD}	-	V_{DD}	V
"L" Level input	V_{IL}	-	V_{SS}	-	0.2 * V_{DD}	V
"H" Level output	V_{OH}	-	0.8 * V_{DD}	-	V_{DD}	V
"L" Level output	V_{OL}	-	V_{SS}	-	0.2 * V_{DD}	V
Backlight supply voltage	V_{LED}	-	2.9	3.0	3.1	V
Backlight supply current	I_{LED}	V_{LED}=3.0V	10	20	26	mA

Optical Characteristics

Item		Symbol	Condition	Min.	Typ.	Max.	Unit
Optimal Viewing Angles	Top	φY+	CR ≥ 2	-	20	-	º
	Bottom	φY-		-	40	-	º
	Left	θX-		-	40	-	º
	Right	θX+		-	40	-	º
Contrast Ratio		CR	-	2	8	-	-
Response Time	Rise	T_R	T_{OP} = 25°C	-	200	250	ms
	Fall	T_F		-	250	320	ms

Controller Information

Built-in ST7565R Controller: https://support.newhavendisplay.com/hc/en-us/articles/4414899357591-ST7565R

Timing Characteristics

The 4-line SPI Interface



Item	Signal	Symbol	Condition	Rating		Units
				Min.	Max.	
4-line SPI Clock Period	SCL	Tscyc		50	—	ns
SCL "H" pulse width		Tshw		25	—	
SCL "L" pulse width		TSLW		25	—	
Address setup time	A0	TSAS		20	—	
Address hold time		Tsah		10	—	
Data setup time	SI	Tsds		20	—	
Data hold time		TSDH		10	—	
CS-SCL time	CS	Tcss		20	—	
CS-SCL time		Tcsh		40	—	

*1 The input signal rise and fall time (tr, tf) are specified at 15 ns or less.
*2 All timing is specified using 20% and 80% of VDD as the standard.

Reset Timing



Table of Commands

Command	Command Code											Function
	A0	/RD	/WR	D7	D6	D5	D4	D3	D2	D1	D0	
(1) Display ON/OFF	0	1	0	1	0	1	0	1	1	1	0 1	LCD display ON/OFF 0: OFF, 1: ON
(2) Display start line set	0	1	0	0	1	Display start address						Sets the display RAM display start line address
(3) Page address set	0	1	0	1	0	1	1	Page address				Sets the display RAM page address
(4) Column address set upper bit Column address set lower bit	0	1	0	0	0	0	1	Most significant column address				Sets the most significant 4 bits of the display RAM column address. Sets the least significant 4 bits of the display RAM column address.
				0	0	0	0	Least significant column address				
(5) Status read	0	0	1	Status				0	0	0	0	Reads the status data
(6) Display data write	1	1	0	Write data								Writes to the display RAM
(7) Display data read	1	0	1	Read data								Reads from the display RAM
(8) ADC select	0	1	0	1	0	1	0	0	0	0	0 1	Sets the display RAM address SEG output correspondence 0: normal, 1: reverse
(9) Display normal/ reverse	0	1	0	1	0	1	0	0	1	1	0 1	Sets the LCD display normal/ reverse 0: normal, 1: reverse
(10) Display all points ON/OFF	0	1	0	1	0	1	0	0	1	0	0 1	Display all points 0: normal display 1: all points ON
(11) LCD bias set	0	1	0	1	0	1	0	0	0	1	0 1	Sets the LCD drive voltage bias ratio 0: 1/9 bias, 1: 1/7 bias (ST7565R)
(12) Read-modify-write	0	1	0	1	1	1	0	0	0	0	0	Column address increment At write: +1 At read: 0
(13) End	0	1	0	1	1	1	0	1	1	1	0	Clear read/modify/write
(14) Reset	0	1	0	1	1	1	0	0	0	1	0	Internal reset
(15) Common output mode select	0	1	0	1	1	0	0	0 1	*	*	*	Select COM output scan direction 0: normal direction 1: reverse direction
(16) Power control set	0	1	0	0	0	1	0	1	Operating mode			Select internal power supply operating mode
(17) V_0 voltage regulator internal resistor ratio set	0	1	0	0	0	1	0	0	Resistor ratio			Select internal resistor ratio(Rb/Ra) mode
(18) Electronic volume mode set Electronic volume register set	0	1	0	1	0	0	0	0	0	0	1	Set the V_0 output voltage electronic volume register
				0	0	Electronic volume value						
(19) Sleep mode set	0	1	0	1	0	1	0	1	1	0	0 1	0: Sleep mode, 1: Normal mode
				*	*	*	*	*	*	0	0	
(20) Booster ratio set	0	1	0	1	1	1	1	1	0	0	0	select booster ratio 00: 2x,3x,4x 01: 5x 11: 6x
				0	0	0	0	0	0	step-up value		
(21) NOP	0	1	0	1	1	1	0	0	0	1	1	Command for non-operation
(22) Test	0	1	0	1	1	1	1	*	*	*	*	Command for IC test. Do not use this command

Example Initialization Program

```
 void data_out(unsigned char i) //Data Output Serial Interface
{
            unsigned int n;
            CS = 0;
            A0 = 1;
            for(n=0; n<8; n++){
   i <<=1;
            SCL = 0;
            P1  = i;
            delay(2);
            SCL = 1;
            }
            CS = 1;
}
void comm_out(unsigned char j) //Command Output Serial Interface
{
            unsigned int n;
            CS = 0;
            A0  = 0;
            for(n=0; n<8; n++){
   j <<=1;
            SCL = 0;
            P1  = j;
            delay(2);
            SCL = 1;
            }
            CS = 1;
}

/*****************************************************
*         Initialization For controller          *
*****************************************************/
void init_LCD()
{
comm_out(0xA0);
comm_out(0xAE);
comm_out(0xC0);
comm_out(0xA2);
comm_out(0x2F);
comm_out(0x21);
comm_out(0x81);
comm_out(0x3F);
}
/*****************************************************/
```

Quality Information

Test Item	Content of Test	Test Condition	Note
High Temperature storage	Endurance test applying the high storage temperature for a long time.	+80°C, 96hrs	2
Low Temperature storage	Endurance test applying the low storage temperature for a long time.	-30°C, 96hrs	1,2
High Temperature Operation	Endurance test applying the electric stress (voltage & current) and the high thermal stress for a long time.	+70°C, 96hrs	2
Low Temperature Operation	Endurance test applying the electric stress (voltage & current) and the low thermal stress for a long time.	-20°C, 96hrs	1,2
High Temperature / Humidity Operation	Endurance test applying the electric stress (voltage & current) and the high thermal with high humidity stress for a long time.	+40°C, 90% RH, 96hrs	1,2
Thermal Shock resistance	Endurance test applying the electric stress (voltage & current) during a cycle of low and high thermal stress.	-20°C, 30min -> 70°C, 60min = 1 cycle For 20 cycles	
Vibration test	Endurance test applying vibration to simulate transportation and use.	10-50Hz, 5G amplitude. 30min in each of 3 directions X, Y, Z	3
Static electricity test	Endurance test applying electric static discharge.	Air: ±8kV 150pF/330Ω, 5 Times Contact: ±4kV 150pF/330Ω, 5 Times	

Note 1: No condensation to be observed.
Note 2: Conducted after 4 hours of storage at 25°C, 0%RH.
Note 3: Test performed on product itself, not inside a container.