





Sheet: /PCB1/
File: PCB1.kicad_sch

Title:

Size: USLetter Date:
KiCad E.D.A. 9.0.6

Rev:
Id: 13/12




Sheet: /PCB1/PCB1-Speakers and Connectors/
File: speakers.kicad_sch

Title:

Size: USLetter | Date:
KiCad E.D.A. 9.0.6

Rev:
Id: 2/12



Sheet: /PCB1/PCB1-Charging and Power Port + USB switch/
File: powerport.kicad_sch


Title:

Size: USLetter Date:

KiCad E.D.A. 9.0.6

Rev:

Id: 11/12





Sheet: /PCB1/PCB1-Charging and Power/
File: charging_power.kicad_sch


Title:

Size: USLetter Date:
KiCad E.D.A. 9.0.6


Rev:
Id: 16/12







auto-retry functionality and the ability to enable or disable with an external logic signal.
Figure 28 shows how an external logic signal can drive EN through RFAULT and maintain auto-retry functionality.
The resistor-capacitor time constant determines the auto-retry time-out period.



Sheet: /PCB2/PCB2-USB 2.0 Bridge/PCB2-USB Current Limiter Switches/
File: USBCurrentLimiter.kicad_sch

Title:


Size: USLetter

Date:

Rev:

KiCad E.D.A. 9.0.6

Id: 11/12



Sheet: /PCB2/PCB2-PWM and Motors/
File: pwm_motors.kicad_sch

Title:

Size: USLetter Date:
KiCad E.D.A. 9.0.6

Rev:
Id: 11/12