




Object Recognition and Haptic Guidance Headband for Blind Users


Ferhaan Hawas (40224777)
Ardalan Jamshidi (27079265)
Gabriel Lemieux (40031680)
Arthur Mosnier (40122836)
Anass Taoussi (40229052)
Frankies Vat (40218933)


Sheet: /
File: 490_0.kicad_sch

Title:

Size: USLetter Date:
KiCad E.D.A. 9.0.6

Rev:
Id: 1/12






Sheet: /PCB1/PCB1-Speakers and Connectors/
File: speakers.kicad_sch

Title:

Size: USLetter Date:
KiCad E.D.A. 9.0.6

Rev:
Id: 2/12



Sheet: /PCB1/PCB1-Charging and Power Port + USB switch/
File: powerport.kicad_sch

Title:


Size: USLetter Date:

KiCad E.D.A. 9.0.6

Rev:

Id: 11/12

J12
2000-1-1-20-00-BK




LAYOUT NOTE: > ROUTE MIPI DIFFERENTIAL PAIRS STRICTLY THROUGH SP3003 PADS.
DO NOT USE STUBS. MAINTAIN 100-OHM IMPEDANCE.

Sheet: /PCB1/PCB1-ToF HDMI Connector/
File: TOF_HDMI_CONNECTOR_PCB1.kicad_sch

Title:

Size: USLetter Date:
KiCad E.D.A. 9.0.6

Rev:
Id: 12/12



Sheet: /PCB1/PCB1-Charging and Power/
File: charging_power.kicad_sch


Title:


Size: USLetter Date:

KiCad E.D.A. 9.0.6

Rev:

Id: 16/12






Sheet: /PCB1/PCB1-HDMI/
File: hdmi.kicad_sch


Title:

Size: USLetter Date:
KiCad E.D.A. 9.0.6

Rev:
Id: 19/12



auto-retry functionality and the ability to enable or disable with an external logic signal.
 Figure 28 shows how an external logic signal can drive EN through RFAULT and maintain auto-retry functionality.
 The resistor-capacitor time constant determines the auto-retry time-out period.



Sheet: /PCB2/PCB2-USB 2.0 Bridge/PCB2-USB Current Limiter Switches/
 File: USBCurrentLimiter.kicad_sch


Title:

Size: USLetter
 KiCad E.D.A. 9.0.6

Date:

Rev:

Id: 11/12



Sheet: /PCB2/PCB2-PWM and Motors/
 File: pwm_motors.kicad_sch

Title:

Size: USLetter Date:
 KiCad E.D.A. 9.0.6

Rev:
 Id: 11/12