Well	KN-104	Rig	Rig KD-3	Report no	10	Date	2011-03-11
Hole size	12¼ in	Depth 00:00	1,966.5 m MD	Depth 24:00	2,159.8 m MD	TVD 24:00	2,159.8 m
Spud date	2011-03-02	Days from spud	10	RT elevation	123 m	Field	Kathal Nala

24 H SUMMARY

Drilled 12¼ in hole from 1,967 m to 2,160 m, 193 m, circulated. NPT 15.2 h: partial losses in tipam sand.

24 H FORECAST

Pulled out of hole from 2,160 m for a bit change.

OPERATIONS

From	To	Hrs	Code	Depth m	Operation
00:00	05:53	5.88	DRL	2,109.0	Drilled 12¼ in hole from 1,967 m to 2,109 m, avg ROP 24.2 m/h. WOB 17 t, 110 rpm, 920 gpm. Connections and MWD surveys each stand.
05:53	06:55	1.03	DRL	2,129.1	Drilled 12¼ in hole from 2,109 m to 2,129 m, avg ROP 19.5 m/h. WOB 17 t, 110 rpm, 920 gpm. Connections and MWD surveys each stand.
06:55	12:25	5.50	NPT	2,129.1	Partial losses of 32 bbl/h at 9.8 ppg.
12:25	22:07	9.70	NPT	2,129.1	Pumped a 44 bbl LCM pill and reduced flow. Losses cured.
22:07	23:30	1.39	DRL	2,159.8	Drilled 12¼ in hole from 2,129 m to 2,160 m, avg ROP 22.1 m/h. WOB 17 t, 110 rpm, 920 gpm. Connections and MWD surveys each stand.
23:30	24:00	0.50	CIRC	2,159.8	Circulated bottoms up at 2,160 m before tripping.

INCIDENTS AND NPT

INCIDENT KN-104-B02 | LOSSES
Title: Partial losses in Tipam sand
Start: 06:55 **Depth:** 2,129.1 m MD **MW:** 9.8 ppg **NPT:** 15.2 h
Description: Partial losses of 32 bbl/h at 9.8 ppg.
Action: Pumped a 44 bbl LCM pill and reduced flow. Losses cured.
Remarks: Pre-treat with 15 ppb LCM and hold ECD under 10.2 ppg.

MUD PROPERTIES

Type	Mud weight	Funnel vis	PV	YP	Fluid loss
WBM, KCl-polymer	9.8 ppg	48 s	22 cP	23 lb/100 ft²	5.4 ml

BIT RECORD

Bit no	Size	Type	Depth in	Metres	Hours
4	12¼ in	PDC, 6 blade	1,459.8 m	700.0	23.7

SURVEYS

MD m	Inc deg	Azi deg	TVD m
1,980.0	0.47	263.0	1,980.0
2,010.0	0.56	265.4	2,010.0
2,040.0	0.61	267.8	2,040.0
2,070.0	0.59	262.8	2,070.0
2,100.0	0.55	262.8	2,100.0
2,130.0	0.66	258.4	2,130.0