Well	KN-104	**Rig**	Rig KD-3	**Report no**	13	**Date**	2011-03-14
Hole size	12¼ in	**Depth 00:00**	2,850.0 m MD	**Depth 24:00**	2,859.8 m MD	**TVD 24:00**	2,859.7 m
Spud date	2011-03-02	**Days from spud**	13	**RT elevation**	123 m	**Field**	Kathal Nala

24 H SUMMARY

Drilled 12¼ in hole from 2,850 m to 2,860 m, 10 m, circulated, tripped. NPT 12.4 h: partial losses in tipam sand.

24 H FORECAST

Drill ahead 12¼ in hole.

OPERATIONS

From	To	Hrs	Code	Depth m	Operation
00:00	00:14	0.23	DRL	2,853.7	Drilled 12¼ in hole from 2,850 m to 2,854 m, avg ROP 16.4 m/h. WOB 17 t, 110 rpm, 920 gpm. Connections and MWD surveys each stand.
00:14	04:44	4.50	NPT	2,853.7	Partial losses of 22 bbl/h at 9.8 ppg.
04:44	12:38	7.90	NPT	2,853.7	Pumped a 33 bbl LCM pill and reduced flow. Losses cured.
12:38	12:50	0.20	DRL	2,859.8	Drilled 12¼ in hole from 2,854 m to 2,860 m, avg ROP 29.9 m/h. WOB 17 t, 110 rpm, 920 gpm. Connections and MWD surveys each stand.
12:50	13:50	1.00	CIRC	2,859.8	Circulated bottoms up at 2,860 m before tripping.
13:50	22:30	8.67	TRIP	2,859.8	Pulled out of hole from 2,860 m for a bit change.
22:30	24:00	1.50	TRIP	2,859.8	Ran in hole with bit #6 to 2,860 m.

INCIDENTS AND NPT

INCIDENT KN-104-B03 | LOSSES
Title: Partial losses in Tipam sand
Start: 00:14 **Depth:** 2,853.7 m MD **MW:** 9.8 ppg **NPT:** 12.4 h
Description: Partial losses of 22 bbl/h at 9.8 ppg.
Action: Pumped a 33 bbl LCM pill and reduced flow. Losses cured.
Remarks: Pre-treat with 15 ppb LCM and hold ECD under 10.2 ppg.

MUD PROPERTIES

Type	Mud weight	Funnel vis	PV	YP	Fluid loss
WBM, KCl-polymer	9.8 ppg	47 s	15 cP	23 lb/100 ft²	5.5 ml

BIT RECORD

Bit no	Size	Type	Depth in	Metres	Hours
6	12¼ in	PDC, 6 blade	2,859.8 m	0.0	3.3