

```
In [24]: from ucimlrepo import fetch_ucirepo
import matplotlib.pyplot as plt
import pandas as pd
import numpy as np
import math
import random
from sklearn import datasets
from sklearn.model_selection import train_test_split
from sklearn.svm import SVC
from sklearn.metrics import accuracy_score, precision_score, recall_score, f1_score
from sklearn.naive_bayes import GaussianNB
from sklearn.metrics import roc_curve, auc
```


roll die 4 times

```
In [27]: faces = 4
num_simulations = 1000
k = 4

sums = []
weights=[]
faces=[]
for i in range(1,k+1):
    if k == 1:
        faces.append(i)
        weights.append(1/2**(k-1))
    else:
        faces.append(i)
        weights.append(1/2**(k-1))

for i in range(num_simulations):
    c_face = random.choices(range(1,k+1),weights=weights,k=4)
    sums.append(sum(c_face))
#print(sums)
expected_sum_theoretical = sum([i / (2 ** (i - 1)) for i in range(2, k + 1)])
expected_sum_theoretical =expected_sum_theoretical + 1/(2 ** (k - 1))
```

```
In [30]: five_num_summary = np.percentile(sums, [0, 25, 50, 75, 100])
plt.hist(sums, bins=np.arange(min(sums), max(sums) + 1.5) - 0.5, alpha=0.5, density)
plt.xlabel("Sum of Upward Face Values")
plt.ylabel("Probability")
plt.title(f"Frequency Distribution (k = {k}, 4 rolls)")
plt.show()
print("Theoretical Expected Sum:", expected_sum_theoretical*4)
print("Actual Expected Sum (Simulation):", np.mean(sums))
print("Five-Number Summary:", five_num_summary)
```



Theoretical Expected Sum: 9.5

Actual Expected Sum (Simulation): 10.035

Five-Number Summary: [4. 8. 10. 12. 16.]


roll die 8 times

```
In [31]: faces = 4
num_simulations = 1000
k = 4

sums = []
weights=[]
faces=[]
for i in range(1,k+1):
    if k == 1:
        faces.append(i)
        weights.append(1/2**(k-1))
    else:
        faces.append(i)
        weights.append(1/2**(k-1))

for i in range(num_simulations):
    c_face = random.choices(range(1,k+1),weights=weights,k=6)
    sums.append(sum(c_face))
#print(sums)
expected_sum_theoretical = sum([i / (2 ** (i - 1)) for i in range(2, k + 1)])
expected_sum_theoretical = expected_sum_theoretical + 1/(2 ** (k - 1))
```

```
In [32]: five_num_summary = np.percentile(sums, [0, 25, 50, 75, 100])
plt.hist(sums, bins=np.arange(min(sums), max(sums) + 1.5) - 0.5, alpha=0.5, density)
plt.xlabel("Sum of Upward Face Values")
plt.ylabel("Probability")
plt.title(f"Frequency Distribution (k = {k}, 6 rolls)")
plt.show()
print("Theoretical Expected Sum:", expected_sum_theoretical*6)
print("Actual Expected Sum (Simulation):", np.mean(sums))
print("Five-Number Summary:", five_num_summary)
```



Theoretical Expected Sum: 14.25

Actual Expected Sum (Simulation): 14.889

Five-Number Summary: [7. 13. 15. 17. 23.]


die with 16 roll

```
In [34]: faces = 4
num_simulations = 1000
k = 4

sums = []
weights=[]
faces=[]
for i in range(1,k+1):
    if k == 1:
        faces.append(i)
        weights.append(1/2**(k-1))
    else:
        faces.append(i)
        weights.append(1/2**(k-1))

for i in range(num_simulations):
    c_face = random.choices(range(1,k+1),weights=weights,k=16)
    sums.append(sum(c_face))
#print(sums)
expected_sum_theoretical = sum([i / (2 ** (i - 1)) for i in range(2, k + 1)])
expected_sum_theoretical =expected_sum_theoretical + 1/(2 ** (k - 1))
```

```
In [35]: five_num_summary = np.percentile(sums, [0, 25, 50, 75, 100])
plt.hist(sums, bins=np.arange(min(sums), max(sums) + 1.5) - 0.5, alpha=0.5, density
plt.xlabel("Sum of Upward Face Values")
plt.ylabel("Probability")
plt.title(f"Frequency Distribution (k = {k}, 6 rolls)")
plt.show()
print("Theoretical Expected Sum:", expected_sum_theoretical*16)
print("Actual Expected Sum (Simulation):", np.mean(sums))
print("Five-Number Summary:", five_num_summary)
```



Theoretical Expected Sum: 38.0

Actual Expected Sum (Simulation): 40.024

Five-Number Summary: [27. 37. 40. 43. 54.]

PART-B

```
In [57]: # fetch dataset
spambase = fetch_ucirepo(id=94)
```

```
In [58]: # data (as pandas dataframes)
X = spambase.data.features
y = spambase.data.targets
```

```
In [59]: # data (as pandas dataframes)
X = spambase.data.features.to_numpy()
y = spambase.data.targets.to_numpy()
```

```
In [60]: X_train, X_temp, y_train, y_temp = train_test_split(X, y, test_size=0.3, random_state=42)
X_val, X_test, y_val, y_test = train_test_split(X_temp, y_temp, test_size=0.5, random_state=42)
y_train = y_train.ravel()
y_test = y_test.ravel()
y_val = y_val.ravel()
```

Naive bayes on normal data

```
In [89]: classes = np.unique(y_train)
n_row, n_col = X_train.shape
n_classes = len(classes)
mean_np = np.zeros((2, n_col), dtype=np.float64)
variance_np = np.zeros((2, n_col), dtype=np.float64)
```

```
In [90]: class_prior = np.zeros(n_classes, dtype=np.float64)
class_prior[0] = sum(y_train==0)/n_row
class_prior[1] = sum(y_train==1)/n_row
```

```
In [91]: for n_class in range(0,2):
        sample = X_train[y_train == n_class]
        for cur_col in range(n_col):
            mean_np[n_class,cur_col]=np.mean(sample[:,cur_col])
            variance_np[n_class,cur_col]=np.var(sample[:,cur_col])
```

```
In [92]: def normal_distribution(target,mean,var):
        epsilon = 1e-10 # A small constant to prevent division by zero
        if var < epsilon:
            var = epsilon
        numerator = np.exp((-1)*(target-mean)**2 / (2 * var))
        denominator = np.sqrt(2 * np.pi * var) + epsilon
        return numerator/denominator
```

```
In [93]: def predict(X_test):
        n_r,n_c = X_test.shape
        y_pred=[]
        for i in range(n_r):
            #c_0=np.log(class_prior[0])
            #c_1=np.log(class_prior[1])
            c_0=0
            c_1=0
            for col in range(n_c):
                c_0+= np.log(normal_distribution(X_test[i][col],mean_np[0][col],variance_np[0][col]))
                c_1+= np.log(normal_distribution(X_test[i][col],mean_np[1][col],variance_np[1][col]))
            if(c_0>c_1):
                y_pred.append(0)
            else:
                y_pred.append(1)
        return np.array(y_pred)
```

```
In [94]: y_pred=predict(X_test)
```

```
<ipython-input-93-674281384692>:11: RuntimeWarning: divide by zero encountered in log
      c_1+= np.log(normal_distribution(X_test[i][col],mean_np[1][col],variance_np[1][col]))
<ipython-input-93-674281384692>:10: RuntimeWarning: divide by zero encountered in log
      c_0+= np.log(normal_distribution(X_test[i][col],mean_np[0][col],variance_np[0][col]))
```

```
In [95]: accuracy = accuracy_score(y_test, y_pred)

# Calculate precision
precision = precision_score(y_test, y_pred)

# Calculate recall
recall = recall_score(y_test, y_pred)

# Calculate F1-score
f1 = f1_score(y_test, y_pred)

# Print the metrics
print(f"Accuracy: {accuracy}")
print(f"Precision: {precision}")
print(f"Recall: {recall}")
print(f"F1-Score: {f1}")
```

```
Accuracy: 0.8567293777134588
Precision: 0.7444444444444445
Recall: 0.9745454545454545
F1-Score: 0.8440944881889764
```

Naive Bayes after Log transformation

```
In [96]: X = np.log1p(X)
X = np.where(np.isinf(X) | np.isnan(X), 0, X)
X_train, X_temp, y_train, y_temp = train_test_split(X, y, test_size=0.3, random_state=42)
X_val, X_test, y_val, y_test = train_test_split(X_temp, y_temp, test_size=0.5, random_state=42)
y_train = y_train.ravel()
y_test = y_test.ravel()
y_val = y_val.ravel()
```

```
In [97]: y_pred=predict(X_test)
```

```
<ipython-input-93-674281384692>:11: RuntimeWarning: divide by zero encountered in log
    c_1+= np.log(normal_distribution(X_test[i][col],mean_np[1][col],variance_np[1][col]))
<ipython-input-93-674281384692>:10: RuntimeWarning: divide by zero encountered in log
    c_0+= np.log(normal_distribution(X_test[i][col],mean_np[0][col],variance_np[0][col]))
```

```
In [98]: accuracy = accuracy_score(y_test, y_pred)

# Calculate precision
precision = precision_score(y_test, y_pred)

# Calculate recall
recall = recall_score(y_test, y_pred)

# Calculate F1-score
f1 = f1_score(y_test, y_pred)

# Print the metrics
print(f"Accuracy: {accuracy}")
print(f"Precision: {precision}")
print(f"Recall: {recall}")
print(f"F1-Score: {f1}")
```

```
Accuracy: 0.8393632416787264
Precision: 0.7192513368983957
Recall: 0.9781818181818182
F1-Score: 0.8289676425269646
```

using sckit learn library

```
In [99]: X_train, X_temp, y_train, y_temp = train_test_split(X, y, test_size=0.3, random_state=42)
X_val, X_test, y_val, y_test = train_test_split(X_temp, y_temp, test_size=0.5, random_state=42)
y_train = y_train.ravel()
y_test = y_test.ravel()
y_val = y_val.ravel()
original_model = GaussianNB()
original_model.fit(X_train, y_train)
```

```
Out[99]: GaussianNB()
```

```
In [100]: X_log = np.log1p(X)
X_log = np.where(np.isinf(X_log) | np.isnan(X_log), 0, X_log)
X_train_log, X_temp_log, y_train_log, y_temp_log = train_test_split(X_log, y, test_size=0.3, random_state=42)
X_val_log, X_test_log, y_val_log, y_test_log = train_test_split(X_temp_log, y_temp_log, test_size=0.5, random_state=42)
y_train_log = y_train_log.ravel()
y_test_log = y_test_log.ravel()
y_val_log = y_val_log.ravel()
log_transformed_model = GaussianNB()
log_transformed_model.fit(X_log, y)
```

```
C:\Users\HP\AppData\Local\Programs\Python\Python39\lib\site-packages\sklearn\utils\validation.py:63: DataConversionWarning: A column-vector y was passed when a 1d array was expected. Please change the shape of y to (n_samples, ), for example using y.ravel().
```

```
    return f(*args, **kwargs)
```

```
Out[100]: GaussianNB()
```

```
In [101]: y_pred_o = original_model.predict(X_test)
y_pred_log = log_transformed_model.predict(X_test_log)
```


```
In [102... #Calculate ROC curve and AUC for model1
fpr1, tpr1, _ = roc_curve(y_test, y_pred_o)
roc_auc1 = auc(fpr1, tpr1)

# Calculate ROC curve and AUC for model2
fpr2, tpr2, _ = roc_curve(y_test, y_pred_log)
roc_auc2 = auc(fpr2, tpr2)
```

```
In [103... # Plot the ROC curves for both models
plt.figure(figsize=(8, 6))
plt.plot(fpr1, tpr1, color='b', lw=2, label=f'Model 1 (AUC = {roc_auc1:.2f})')
plt.plot(fpr2, tpr2, color='r', lw=2, label=f'Model 2 (AUC = {roc_auc2:.2f})')

plt.plot([0, 1], [0, 1], color='gray', lw=1, linestyle='--')
plt.xlim([0.0, 1.0])
plt.ylim([0.0, 1.05])
plt.xlabel('False Positive Rate')
plt.ylabel('True Positive Rate')
plt.title('Receiver Operating Characteristic')
plt.legend(loc='lower right')

plt.show()
```



```
In [104... accuracy_original = accuracy_score(y_test, y_pred_o)
print(f"Accuracy for the original model: {accuracy_original}")

# Calculate accuracy for the log-transformed model
accuracy_log_transformed = accuracy_score(y_test, y_pred_log)
print(f"Accuracy for the log-transformed model: {accuracy_log_transformed}")
```

Accuracy for the original model: 0.8581765557163531
Accuracy for the log-transformed model: 0.8625180897250362

In []: