




Machine Learning

Recommender Systems

Problem formulation

Example: Predicting movie ratings

→ User rates movies using ~~one~~ to five stars
 zero



Movie	Alice (1)	Bob (2)	Carol (3)	Dave (4)
Love at last	5	5	0	0
Romance forever	5	?	?	0
Cute puppies of love	?	5	0	?
Nonstop car chases	0	0	5	4
Swords vs. karate	0	0	5	?

$$n_u = 4$$

$$n_m = 5$$

→ n_u = no. users

→ n_m = no. movies

→ $r(i, j) = 1$ if user j has rated movie i

→ $y^{(i, j)}$ = rating given by user j to movie i (defined only if $r(i, j) = 1$)

0, ..., 5



Machine Learning

Recommender Systems

Content-based
recommendations

Content-based recommender systems

$n_u = 4, n_m = 5$

$x_0 = 1$

Movie	Alice (1) $\theta^{(1)}$	Bob (2) $\theta^{(2)}$	Carol (3) $\theta^{(3)}$	Dave (4) $\theta^{(4)}$
Love at last 1	5	5	0	0
Romance forever 2	5	?	?	0
Cute puppies of love 3	?	4	0	?
Nonstop car chases 4	0	0	5	4
Swords vs. karate 5	0	0	5	?

$x^{(1)} \rightarrow$ Love at last 1
 $x^{(2)} \rightarrow$ Romance forever 2
 $x^{(3)} \rightarrow$ Cute puppies of love 3
 $x^{(4)} \rightarrow$ Nonstop car chases 4
 $x^{(5)} \rightarrow$ Swords vs. karate 5

$x^{(i)} = \begin{bmatrix} 1 \\ 0.9 \\ 0 \end{bmatrix}$

$n = 2$

treat each as a separate linear regression problem

→ For each user j , learn a parameter $\theta^{(j)} \in \mathbb{R}^3$. Predict user j as rating movie i with $x^{(i)}$ stars. $\theta^{(j)} \in \mathbb{R}^{n+1}$

$$x^{(3)} = \begin{bmatrix} 1 \\ 0.99 \\ 0 \end{bmatrix} \leftrightarrow \theta^{(1)} = \begin{bmatrix} 0 \\ 5 \\ 0 \end{bmatrix}$$

$$(\theta^{(1)})^T x^{(3)} = 5 \times 0.99 = 4.95$$

Problem formulation

- $r(i, j) = 1$ if user j has rated movie i (0 otherwise)
- $y^{(i,j)}$ = rating by user j on movie i (if defined)

→ $\theta^{(j)}$ = parameter vector for user j

→ $x^{(i)}$ = feature vector for movie i

→ For user j , movie i , predicted rating: $\underline{\underline{(\theta^{(j)})^T (x^{(i)})}}$

$$\theta^{(j)} \in \mathbb{R}^{n+1}$$

→ $\underline{m^{(j)}}$ = no. of movies rated by user j

To learn $\underline{\theta^{(j)}}$:

n is the number of features

$$\min_{\theta^{(j)}} \frac{1}{2} \sum_{i: r(i,j)=1} \left((\theta^{(j)})^T x^{(i)} - y^{(i,j)} \right)^2 + \frac{\lambda}{2} \sum_{k=1}^n (\theta_k^{(j)})^2$$

sum of all the movies that user j has rated

Optimization objective:

To learn $\theta^{(j)}$ (parameter for user j):

$$\rightarrow \min_{\theta^{(j)}} \underbrace{\frac{1}{2} \sum_{i:r(i,j)=1} \left((\theta^{(j)})^T x^{(i)} - y^{(i,j)} \right)^2}_{\text{user } j \text{ loss}} + \underbrace{\frac{\lambda}{2} \sum_{k=1}^n (\theta_k^{(j)})^2}_{\text{regularization}}$$

To learn $\theta^{(1)}$, $\theta^{(2)}$, ..., $\theta^{(n_u)}$:

$$\min_{\theta^{(1)}, \dots, \theta^{(n_u)}} \frac{1}{2} \sum_{j=1}^{n_u} \sum_{i:r(i,j)=1} \left((\theta^{(j)})^T x^{(i)} - y^{(i,j)} \right)^2 + \frac{\lambda}{2} \sum_{j=1}^{n_u} \sum_{k=1}^n (\theta_k^{(j)})^2$$

$\theta^{(1)}, \dots, \theta^{(n_u)}$

Optimization algorithm:

$$\min_{\theta^{(1)}, \dots, \theta^{(n_u)}} \underbrace{\frac{1}{2} \sum_{j=1}^{n_u} \sum_{i:r(i,j)=1} \left((\theta^{(j)})^T x^{(i)} - y^{(i,j)} \right)^2 + \frac{\lambda}{2} \sum_{j=1}^{n_u} \sum_{k=1}^n (\theta_k^{(j)})^2}_{J(\theta^{(1)}, \dots, \theta^{(n_u)})}$$

Gradient descent update:

$$\theta_k^{(j)} := \theta_k^{(j)} - \alpha \sum_{i:r(i,j)=1} \left((\theta^{(j)})^T x^{(i)} - y^{(i,j)} \right) x_k^{(i)} \quad \text{(for } k = 0 \text{)}$$

$$\theta_k^{(j)} := \theta_k^{(j)} - \alpha \left(\sum_{i:r(i,j)=1} \left((\theta^{(j)})^T x^{(i)} - y^{(i,j)} \right) x_k^{(i)} + \lambda \theta_k^{(j)} \right) \quad \text{(for } k \neq 0 \text{)}$$

$\frac{1}{m^{(j)}}$

$\frac{\partial}{\partial \theta_k^{(j)}} J(\theta^{(1)}, \dots, \theta^{(n_u)})$





Machine Learning

Recommender Systems

Collaborative filtering

Problem motivation

Movie	Alice (1)	Bob (2)	Carol (3)	Dave (4)	 x_1	 x_2
					(romance)	(action)
Love at last	5	5	0	0	0.9	0
Romance forever	5	?	?	0	1.0	0.01
Cute puppies of love	?	4	0	?	0.99	0
Nonstop car chases	0	0	5	4	0.1	1.0
Swords vs. karate	0	0	5	?	0	0.9

Problem motivation

Movie	Alice (1) $\theta^{(1)}$	Bob (2) $\theta^{(2)}$	Carol (3) $\theta^{(3)}$	Dave (4) $\theta^{(4)}$	x_1 (romance)	x_2 (action)
$x^{(1)}$ Love at last	→ 5	→ 5	→ 0	→ 0	→ 1.0	→ 0.0
Romance forever	5	?	?	0	[?]	[?]
Cute puppies of love	?	4	0	?	[?]	[?]
Nonstop car chases	0	0	5	4	[?]	[?]
Swords vs. karate	0	0	5	?	[?]	[?]

$x^{(1)} = \begin{bmatrix} 1.0 \\ 0.0 \end{bmatrix}$
 $\theta^{(1)} = \begin{bmatrix} 0 \\ 5 \\ 0 \end{bmatrix}$, $\theta^{(2)} = \begin{bmatrix} 0 \\ 5 \\ 0 \end{bmatrix}$, $\theta^{(3)} = \begin{bmatrix} 0 \\ 0 \\ 5 \end{bmatrix}$, $\theta^{(4)} = \begin{bmatrix} 0 \\ 0 \\ 5 \end{bmatrix}$
 $\theta^{(j)}$

$(\theta^{(1)})^T x^{(1)} \approx 5$
 $(\theta^{(2)})^T x^{(1)} \approx 5$
 $(\theta^{(3)})^T x^{(1)} \approx 0$
 $(\theta^{(4)})^T x^{(1)} \approx 0$

Optimization algorithm

Given $\theta^{(1)}, \dots, \theta^{(n_u)}$, to learn $x^{(i)}$:

$$\min_{x^{(i)}} \frac{1}{2} \sum_{j:r(i,j)=1} ((\theta^{(j)})^T x^{(i)} - y^{(i,j)})^2 + \frac{\lambda}{2} \sum_{k=1}^n (x_k^{(i)})^2$$

Given $\theta^{(1)}, \dots, \theta^{(n_u)}$, to learn $x^{(1)}, \dots, x^{(n_m)}$:

$$\min_{x^{(1)}, \dots, x^{(n_m)}} \frac{1}{2} \sum_{i=1}^{n_m} \sum_{j:r(i,j)=1} ((\theta^{(j)})^T x^{(i)} - y^{(i,j)})^2 + \frac{\lambda}{2} \sum_{i=1}^{n_m} \sum_{k=1}^n (x_k^{(i)})^2$$

Collaborative filtering

Given $x^{(1)}, \dots, x^{(n_m)}$ (and movie ratings),
can estimate $\theta^{(1)}, \dots, \theta^{(n_u)}$ ↗

$\sigma^{(i,j)}$
 $y^{(i,j)}$

Given $\theta^{(1)}, \dots, \theta^{(n_u)}$,
can estimate $x^{(1)}, \dots, x^{(n_m)}$

Guess $\Theta \rightarrow x \rightarrow \Theta \rightarrow x \rightarrow \Theta \rightarrow x \rightarrow \dots$



Machine Learning

Recommender Systems

Collaborative
filtering algorithm

Collaborative filtering optimization objective

→ Given $x^{(1)}, \dots, x^{(n_m)}$, estimate $\theta^{(1)}, \dots, \theta^{(n_u)}$:

$$\min_{\theta^{(1)}, \dots, \theta^{(n_u)}} \left[\frac{1}{2} \sum_{j=1}^{n_u} \sum_{i:r(i,j)=1} ((\theta^{(j)})^T x^{(i)} - y^{(i,j)})^2 + \frac{\lambda}{2} \sum_{j=1}^{n_u} \sum_{k=1}^n (\theta_k^{(j)})^2 \right]$$

对每一个user 求和

$(i,j) : r(i,j)=1$
 $x \in \mathbb{R}^n$
 $\theta \in \mathbb{R}^n$
 $x_i = 1$

→ Given $\theta^{(1)}, \dots, \theta^{(n_u)}$, estimate $x^{(1)}, \dots, x^{(n_m)}$:

$$\min_{x^{(1)}, \dots, x^{(n_m)}} \left[\frac{1}{2} \sum_{i=1}^{n_m} \sum_{j:r(i,j)=1} ((\theta^{(j)})^T x^{(i)} - y^{(i,j)})^2 + \frac{\lambda}{2} \sum_{i=1}^{n_m} \sum_{k=1}^n (x_k^{(i)})^2 \right]$$

对每一个movie 求和

Minimizing $x^{(1)}, \dots, x^{(n_m)}$ and $\theta^{(1)}, \dots, \theta^{(n_u)}$ simultaneously:

$$J(x^{(1)}, \dots, x^{(n_m)}, \theta^{(1)}, \dots, \theta^{(n_u)}) = \frac{1}{2} \sum_{(i,j):r(i,j)=1} ((\theta^{(j)})^T x^{(i)} - y^{(i,j)})^2 + \frac{\lambda}{2} \sum_{i=1}^{n_m} \sum_{k=1}^n (x_k^{(i)})^2 + \frac{\lambda}{2} \sum_{j=1}^{n_u} \sum_{k=1}^n (\theta_k^{(j)})^2$$

$$\min_{\substack{x^{(1)}, \dots, x^{(n_m)} \\ \theta^{(1)}, \dots, \theta^{(n_u)}}} J(x^{(1)}, \dots, x^{(n_m)}, \theta^{(1)}, \dots, \theta^{(n_u)})$$

$\theta \rightarrow x \rightarrow \theta \rightarrow x \rightarrow \dots$

Collaborative filtering algorithm

- 1. Initialize $x^{(1)}, \dots, x^{(n_m)}, \theta^{(1)}, \dots, \theta^{(n_u)}$ to small random values.
- 2. Minimize $J(x^{(1)}, \dots, x^{(n_m)}, \theta^{(1)}, \dots, \theta^{(n_u)})$ using gradient descent (or an advanced optimization algorithm). E.g. for every $j = 1, \dots, n_u, i = 1, \dots, n_m$:

$$x_k^{(i)} := x_k^{(i)} - \alpha \left(\sum_{j:r(i,j)=1} ((\theta^{(j)})^T x^{(i)} - y^{(i,j)}) \theta_k^{(j)} + \lambda x_k^{(i)} \right)$$

$$\theta_k^{(j)} := \theta_k^{(j)} - \alpha \left(\sum_{i:r(i,j)=1} ((\theta^{(j)})^T x^{(i)} - y^{(i,j)}) x_k^{(i)} + \lambda \theta_k^{(j)} \right)$$

Handwritten notes: $\frac{\partial}{\partial x_k^{(i)}} J(\dots)$ and $\frac{\partial}{\partial \theta_k^{(j)}} J(\dots)$ with arrows pointing to the respective terms in the equations.

- 3. For a user with parameters θ and a movie with (learned) features x , predict a star rating of $\theta^T x$.

$$(\theta^{(j)})^T (x^{(i)})$$



Machine Learning

Recommender Systems

Vectorization:
Low rank matrix
factorization

Collaborative filtering

Movie	Alice (1)	Bob (2)	Carol (3)	Dave (4)
Love at last	5	5	0	0
Romance forever	5	?	?	0
Cute puppies of love	?	4	0	?
Nonstop car chases	0	0	5	4
Swords vs. karate	0	0	5	?

↑ ↑ ↑ ↑

$$n_m = 5$$
$$n_u = 4$$

$$Y = \begin{bmatrix} 5 & 5 & 0 & 0 \\ 5 & ? & ? & 0 \\ ? & 4 & 0 & ? \\ 0 & 0 & 5 & 4 \\ 0 & 0 & 5 & 0 \end{bmatrix}$$

$y^{(i,j)}$

Collaborative filtering

$$Y = \begin{bmatrix} 5 & 5 & 0 & 0 \\ 5 & ? & ? & 0 \\ ? & 4 & 0 & ? \\ 0 & 0 & 5 & 4 \\ 0 & 0 & 5 & 0 \end{bmatrix}$$

Predicted ratings:

$$\begin{bmatrix} (\theta^{(1)})^T(x^{(1)}) & (\theta^{(2)})^T(x^{(1)}) & \dots & (\theta^{(n_u)})^T(x^{(1)}) \\ (\theta^{(1)})^T(x^{(2)}) & (\theta^{(2)})^T(x^{(2)}) & \dots & (\theta^{(n_u)})^T(x^{(2)}) \\ \vdots & \vdots & \vdots & \vdots \\ (\theta^{(1)})^T(x^{(n_m)}) & (\theta^{(2)})^T(x^{(n_m)}) & \dots & (\theta^{(n_u)})^T(x^{(n_m)}) \end{bmatrix}$$

$$X = \begin{bmatrix} -(x^{(1)})^T \\ -(x^{(2)})^T \\ \vdots \\ -(x^{(n_m)})^T \end{bmatrix}$$

$$\Theta = \begin{bmatrix} -(\theta^{(1)})^T \\ -(\theta^{(2)})^T \\ \vdots \\ -(\theta^{(n_u)})^T \end{bmatrix}$$

→ Low rank matrix factorization

Finding related movies

For each product i , we learn a feature vector $\underline{x^{(i)}} \in \mathbb{R}^n$.

→ $x_1 = \text{romance}$, $x_2 = \text{action}$, $x_3 = \text{comedy}$, $x_4 = \dots$

How to find movies j related to movie i ?

Small $\|x^{(i)} - x^{(j)}\| \rightarrow$ movie j and i are "similar"

5 most similar movies to movie i :

Find the 5 movies j with the smallest $\|x^{(i)} - x^{(j)}\|$.



Machine Learning

Recommender Systems

Implementational
detail: Mean
normalization

Users who have not rated any movies

Movie	Alice (1)	Bob (2)	Carol (3)	Dave (4)	Eve (5)
→ Love at last	<u>5</u>	<u>5</u>	0	0	<u>?</u>
Romance forever	5	?	?	0	<u>?</u>
Cute puppies of love	?	4	0	?	<u>?</u>
Nonstop car chases	0	0	5	4	<u>?</u>
→ Swords vs. karate	0	0	<u>5</u>	?	<u>?</u>

$Y = \begin{bmatrix} 5 & 5 & 0 & 0 & ? \\ 5 & ? & ? & 0 & ? \\ ? & 4 & 0 & ? & ? \\ 0 & 0 & 5 & 4 & ? \\ 0 & 0 & 5 & 0 & ? \end{bmatrix}$

$$\min_{\substack{x^{(1)}, \dots, x^{(n_m)} \\ \theta^{(1)}, \dots, \theta^{(n_u)}}} \frac{1}{2} \sum_{(i,j): r(i,j)=1} ((\theta^{(j)})^T x^{(i)} - y^{(i,j)})^2 + \frac{\lambda}{2} \sum_{i=1}^{n_m} \sum_{k=1}^n (x_k^{(i)})^2 + \frac{\lambda}{2} \sum_{j=1}^{n_u} \sum_{k=1}^n (\theta_k^{(j)})^2$$

$n=2$ $\underline{\theta}^{(5)} \in \mathbb{R}^2$ $\underline{\theta}^{(5)} = \begin{bmatrix} 0 \\ 0 \end{bmatrix}$ $\frac{\lambda}{2} [(\theta_1^{(5)})^2 + (\theta_2^{(5)})^2] \leftarrow$

$(\underline{\theta}^{(5)})^T \underline{x}^{(i)} = 0$

Mean Normalization:

$$Y = \begin{bmatrix} 5 & 5 & 0 & 0 & ? \\ 5 & ? & ? & 0 & ? \\ ? & 4 & 0 & ? & ? \\ 0 & 0 & 5 & 4 & ? \\ 0 & 0 & 5 & 0 & ? \end{bmatrix}$$

Handwritten annotations: Blue circles around the first row's first four elements (5, 5, 0, 0) and the last element (?). Blue arrows point to the first three rows and the last row. A red minus sign is between the two matrices.

$$\mu = \begin{bmatrix} 2.5 \\ 2.5 \\ 2 \\ 2.25 \\ 1.25 \end{bmatrix}$$

Handwritten annotations: Blue circles around the first and last elements (2.5 and 1.25). Blue arrows point to the first three rows and the last row.

$$\rightarrow \underline{Y} = \begin{bmatrix} 2.5 & 2.5 & -2.5 & -2.5 & ? \\ 2.5 & ? & ? & -2.5 & ? \\ ? & 2 & -2 & ? & ? \\ -2.25 & -2.25 & 2.75 & 1.75 & ? \\ -1.25 & -1.25 & 3.75 & -1.25 & ? \end{bmatrix}$$

Handwritten annotations: Blue circles around the first row's first four elements (2.5, 2.5, -2.5, -2.5) and the last element (?). Blue arrows point to the first three rows and the last row.

For user j , on movie i predict:

$$\rightarrow (\theta^{(j)})^T (x^{(i)}) + \mu_i$$

learn $\underline{\theta^{(j)}}$, $\underline{x^{(i)}}$

User 5 (Eve):

$$\underline{\theta^{(5)}} = \begin{bmatrix} 0 \\ 0 \end{bmatrix}$$

$$\underbrace{(\theta^{(5)})^T (x^{(i)})}_{= 0} + \boxed{\mu_i}$$